

Google Map | ExpressionEngine Plugin

version 0.6

This plugin outputs a full width Google Map based on tag coordinates or location. The plugin uses version 3 of Google Maps script, with no need for an API key.

Usage

```
{exp:googlemap zoom="17" container="map1" width="60%" height="400px" location="New York, USA" streetview="false"}
```

or

```
{exp:googlemap zoom="17" container="map1" width="60%" height="400px" lat="53.3218692" lon="-6.2645621" streetview="true"}
```

The **container** should have a different name for each embedded map. **Width** and **height** allow for both percentage and pixel dimensions (note that 'em' is also available). The **streetview** parameter is mandatory. A map tag should have either a **location** parameter or a **lat/lon** combination, not both.

Features

- Responsive (smartphone, tablet compatible)
- HTML5 compatible/valid

Installation

1. Upload the **googlemap** folder to your /third-party/ (do not rename it, the correct folder name should be **googlemap**)
2. Add the tag to your template (see below, or check the plugin's documentation inside ExpressionEngine)

Core is a free, feature-limited edition of ExpressionEngine. [Upgrade Now](#) to get all the features.

[Home](#) [Content](#) [Design](#) [Add-Ons](#) [Members](#) [Admin](#) [Tools](#) [Help](#) [+ Add](#)

ExpressionEngine Development Server

ExpressionEngine Development Server

CP Home

Design

Template Manager

Edit Template (about/index)

Ciprian

Log-out

[show sidebar](#)

[View Rendered Template](#)

Edit Template: about/index

From Database

```
<div class="feature_end"></div>

<div id="content_pri" class="about"> <!-- This is where all primary content, left column gets entered -->

    <!-- Standard Channel Entries tag, but instead of relying on the URL for what to display, we request a specific e
    http://ellislab.com/expressionengine/user-guide/modules/channel/parameters.html#par_url_title

    and we force the channel entries tag to ignore the URL and always deliver the same content by using dynamic="no":
    http://ellislab.com/expressionengine/user-guide/modules/channel/parameters.html#par_dynamic
    -->

        {exp:channel:entries channel="about" dynamic="no" url_title="about_the_label" limit="1" disable="pagination|membe
        {about_extended}
    {/exp:channel:entries}

</div>

<div id="content_sec" class="staff_profiles right green40">
    <h3 class="staff">Google Map</h3>
    {exp:googlemap zoom="17" container="map1" width="100%" height="400px" location="New York, USA" streetview="false"}
</div> <!-- ending #content_sec -->

{global_footer}
{wrapper_close}
{js}
{html_close}
```

Preferences