

# Java MongoDB : Query document

By mkyong (<http://www.mkyong.com/author/mkyong/>) | May 10, 2011 | Updated : April 2, 2013 | Viewed : 117,351 times


In this tutorial, we show you few common ways to get or query document from collection.

## Test Data

Insert 5 dummy documents for testing.

```
{ "_id" : { "$oid" : "id" } , "number" : 1 , "name" : "mkyong-1"}
{ "_id" : { "$oid" : "id" } , "number" : 2 , "name" : "mkyong-2"}
{ "_id" : { "$oid" : "id" } , "number" : 3 , "name" : "mkyong-3"}
{ "_id" : { "$oid" : "id" } , "number" : 4 , "name" : "mkyong-4"}
{ "_id" : { "$oid" : "id" } , "number" : 5 , "name" : "mkyong-5"}
```

Java



## 1. Find() examples

1.1 Get first matched document only.

```
DBObject doc = collection.findOne();
System.out.println(dbObject);
```

Java

Output

```
{ "_id" : { "$oid" : "id" } , "number" : 1 , "name" : "mkyong-1"}
```

Bash

1.2 Get all matched documents.

```
DBCursor cursor = collection.find();
while(cursor.hasNext()) {
    System.out.println(cursor.next());
}
```

Java

Output

```
{ "_id" : { "$oid" : "id" } , "number" : 1 , "name" : "mkyong-1"}
{ "_id" : { "$oid" : "id" } , "number" : 2 , "name" : "mkyong-2"}
{ "_id" : { "$oid" : "id" } , "number" : 3 , "name" : "mkyong-3"}
{ "_id" : { "$oid" : "id" } , "number" : 4 , "name" : "mkyong-4"}
{ "_id" : { "$oid" : "id" } , "number" : 5 , "name" : "mkyong-5"}
```

Bash

1.3 Get single field from matched document.

```
BasicDBObject allQuery = new BasicDBObject();
BasicDBObject fields = new BasicDBObject();
fields.put("name", 1);


DBCursor cursor = collection.find(allQuery, fields);
while (cursor.hasNext()) {
    System.out.println(cursor.next());
}
```

Java

Output

```
{ "_id" : { "$oid" : "id" } , "name" : "mkyong-1"}
{ "_id" : { "$oid" : "id" } , "name" : "mkyong-2"}
{ "_id" : { "$oid" : "id" } , "name" : "mkyong-3"}
{ "_id" : { "$oid" : "id" } , "name" : "mkyong-4"}
{ "_id" : { "$oid" : "id" } , "name" : "mkyong-5"}
```

Bash



2. Find() and Comparison

2.1 Get all documents where number = 5 .

```
BasicDBObject whereQuery = new BasicDBObject();
whereQuery.put("number", 5);
DBCursor cursor = collection.find(whereQuery);
while(cursor.hasNext()) {
    System.out.println(cursor.next());
}
```

Java

Output

```
{ "_id" : { "$oid" : "id" } , "number" : 5 , "name" : "mkyong-5"}
```

Bash

2.2 \$in example – Get documents where number in 2, 4 and 5 .

Java

```

BasicDBObject inQuery = new BasicDBObject();
List<Integer> list = new ArrayList<Integer>();
list.add(2);
list.add(4);
list.add(5);
inQuery.put("number", new BasicDBObject("$in", list));
DBCursor cursor = collection.find(inQuery);
while(cursor.hasNext()) {
    System.out.println(cursor.next());
}

```

## Output

```

{ "_id" : { "$oid" : "id" } , "number" : 2 , "name" : "mkyong-2"}
{ "_id" : { "$oid" : "id" } , "number" : 4 , "name" : "mkyong-4"}
{ "_id" : { "$oid" : "id" } , "number" : 5 , "name" : "mkyong-5"}

```

Bash

## 2.3 \$gt \$lt example – Get documents where 5 > number > 2 .

```

BasicDBObject gtQuery = new BasicDBObject();
gtQuery.put("number", new BasicDBObject("$gt", 2).append("$lt", 5));
DBCursor cursor = collection.find(gtQuery);
while(cursor.hasNext()) {
    System.out.println(cursor.next());
}

```

Java

## Output

```

{ "_id" : { "$oid" : "id" } , "number" : 3 , "name" : "mkyong-3"}
{ "_id" : { "$oid" : "id" } , "number" : 4 , "name" : "mkyong-4"}

```

Bash

## 2.4 \$ne example – Get documents where number != 4 .

```

BasicDBObject neQuery = new BasicDBObject();
neQuery.put("number", new BasicDBObject("$ne", 4));
DBCursor cursor = collection.find(neQuery);
while(cursor.hasNext()) {
    System.out.println(cursor.next());
}

```

Java

## Output

```

{ "_id" : { "$oid" : "id" } , "number" : 1 , "name" : "mkyong-1"}
{ "_id" : { "$oid" : "id" } , "number" : 2 , "name" : "mkyong-2"}
{ "_id" : { "$oid" : "id" } , "number" : 3 , "name" : "mkyong-3"}
{ "_id" : { "$oid" : "id" } , "number" : 5 , "name" : "mkyong-5"}

```

Bash

# 3. find() and Logical

3.1 \$and example – get documents where number = 2 and name = 'mkyong-2' .

Java

```
BasicDBObject andQuery = new BasicDBObject();
List<BasicDBObject> obj = new ArrayList<BasicDBObject>();
obj.add(new BasicDBObject("number", 2));
obj.add(new BasicDBObject("name", "mkyong-2"));
andQuery.put("$and", obj);

System.out.println(andQuery.toString());

DBCursor cursor = collection.find(andQuery);
while (cursor.hasNext()) {
    System.out.println(cursor.next());
}
```

Output

Bash

```
{ "$and" : [ { "number" : 2 } , { "name" : "mkyong-2" } ] }

{ "_id" : { "$oid" : "id" } , "number" : 2 , "name" : "mkyong-2" }
```

4. find() and Regex

Find document with regular expression pattern.

4.1 \$regex example – get documents where name like pattern 'Mky.\*-[1-3]', case insensitive .

Java

```
BasicDBObject regexQuery = new BasicDBObject();
regexQuery.put("name",
    new BasicDBObject("$regex", "Mky.*-[1-3]")
    .append("$options", "i"));

System.out.println(regexQuery.toString());

DBCursor cursor = collection.find(regexQuery);
while (cursor.hasNext()) {
    System.out.println(cursor.next());
}
```

Output

Bash

```
{ "name" : { "$regex" : "Mky.*-[1-3]" , "$options" : "i" } }

{ "_id" : { "$oid" : "515ad59e3004c89329c7b259" } , "number" : 1 , "name" : "mkyong-1" }
{ "_id" : { "$oid" : "515ad59e3004c89329c7b25a" } , "number" : 2 , "name" : "mkyong-2" }
{ "_id" : { "$oid" : "515ad59e3004c89329c7b25b" } , "number" : 3 , "name" : "mkyong-3" }
```

There are more...

Read this MongoDB operator documentation (<http://docs.mongodb.org/manual/reference/operators/>) for complete set of query operators supported in MongoDB.

## 5. Full Example

Java

```
package com.mkyong.core;

import java.net.UnknownHostException;
import java.util.ArrayList;
import java.util.Calendar;
import java.util.List;

import com.mongodb.BasicDBObject;
import com.mongodb.DB;
import com.mongodb.DBCollection;
import com.mongodb.DBCursor;
import com.mongodb.DBObject;
import com.mongodb.Mongo;
import com.mongodb.MongoException;

/**
 * Java MongoDB : Query document
 *
 * @author mkyong
 *
 */
public class QueryApp {

    public static void insertDummyDocuments(DBCollection collection) {

        List<DBObject> list = new ArrayList<DBObject>();

        Calendar cal = Calendar.getInstance();

        for (int i = 1; i <= 5; i++) {

            BasicDBObject data = new BasicDBObject();
            data.append("number", i);
            data.append("name", "mkyong-" + i);
            // data.append("date", cal.getTime());

            // +1 day
            cal.add(Calendar.DATE, 1);

            list.add(data);

        }

        collection.insert(list);

    }

    public static void main(String[] args) {

        try {

            Mongo mongo = new Mongo("localhost", 27017);
            DB db = mongo.getDB("yourdb");
```

```

// get a single collection
DBCollection collection = db.getCollection("dummyColl");

insertDummyDocuments(collection);

System.out.println("1. Find first matched document");
DBObject dbObject = collection.findOne();
System.out.println(dbObject);

System.out.println("\n1. Find all matched documents");
DBCursor cursor = collection.find();
while (cursor.hasNext()) {
    System.out.println(cursor.next());
}

System.out.println("\n1. Get 'name' field only");
BasicDBObject allQuery = new BasicDBObject();
BasicDBObject fields = new BasicDBObject();
fields.put("name", 1);

DBCursor cursor2 = collection.find(allQuery, fields);
while (cursor2.hasNext()) {
    System.out.println(cursor2.next());
}

System.out.println("\n2. Find where number = 5");
BasicDBObject whereQuery = new BasicDBObject();
whereQuery.put("number", 5);
DBCursor cursor3 = collection.find(whereQuery);
while (cursor3.hasNext()) {
    System.out.println(cursor3.next());
}

System.out.println("\n2. Find where number in 2,4 and 5");
BasicDBObject inQuery = new BasicDBObject();
List<Integer> list = new ArrayList<Integer>();
list.add(2);
list.add(4);
list.add(5);
inQuery.put("number", new BasicDBObject("$in", list));
DBCursor cursor4 = collection.find(inQuery);
while (cursor4.hasNext()) {
    System.out.println(cursor4.next());
}

System.out.println("\n2. Find where 5 > number > 2");
BasicDBObject gtQuery = new BasicDBObject();
gtQuery.put("number", new BasicDBObject("$gt", 2).append("$lt", 5));
DBCursor cursor5 = collection.find(gtQuery);
while (cursor5.hasNext()) {
    System.out.println(cursor5.next());
}

System.out.println("\n2. Find where number != 4");
BasicDBObject neQuery = new BasicDBObject();
neQuery.put("number", new BasicDBObject("$ne", 4));
DBCursor cursor6 = collection.find(neQuery);

```

```

while (cursor6.hasNext()) {
    System.out.println(cursor6.next());
}

System.out.println("\n3. Find when number = 2 and name = 'mkyong-2' example");
BasicDBObject andQuery = new BasicDBObject();

List<BasicDBObject> obj = new ArrayList<BasicDBObject>();
obj.add(new BasicDBObject("number", 2));
obj.add(new BasicDBObject("name", "mkyong-2"));
andQuery.put("$and", obj);

System.out.println(andQuery.toString());

DBCursor cursor7 = collection.find(andQuery);
while (cursor7.hasNext()) {
    System.out.println(cursor7.next());
}

System.out.println("\n4. Find where name = 'Mky.*-[1-3]', case sensitive example");
BasicDBObject regexQuery = new BasicDBObject();
regexQuery.put("name",
    new BasicDBObject("$regex", "Mky.*-[1-3]")
        .append("$options", "i"));

System.out.println(regexQuery.toString());

DBCursor cursor8 = collection.find(regexQuery);
while (cursor8.hasNext()) {
    System.out.println(cursor8.next());
}

collection.drop();

System.out.println("Done");

} catch (UnknownHostException e) {
    e.printStackTrace();
} catch (MongoException e) {
    e.printStackTrace();
}
}
}

```

Done.

## References


1. Query, Update, and Projection Operators Quick Reference  
(<http://docs.mongodb.org/manual/reference/operators/>)

Tags : [mongodb \(http://www.mkyong.com/tag/mongodb/\)](http://www.mkyong.com/tag/mongodb/) | [query \(http://www.mkyong.com/tag/query/\)](http://www.mkyong.com/tag/query/)



# Share this article on

Twitter ([https://twitter.com/intent/tweet?text=Java MongoDB : Query document&url=http://www.mkyong.com/mongodb/java-mongodb-query-document/&via=mkyong](https://twitter.com/intent/tweet?text=Java+MongoDB+%3A+Query+document&url=http://www.mkyong.com/mongodb/java-mongodb-query-document/&via=mkyong))    Facebook (<https://www.facebook.com/sharer/sharer.php?u=http://www.mkyong.com/mongodb/java-mongodb-query-document/>)    Google+ (<https://plus.google.com/share?url=http://www.mkyong.com/mongodb/java-mongodb-query-document/>)




Powered by Google




Top 20 Java Websites



Spring Data MongoDB – Select fields to return




Find out your Java heap memory size



Spring 3 MVC and example

NEXT >

## Reader also read :




MongoDB : Sort exceeded memory



Spring Data MongoDB – Aggregation




Spring Data MongoDB – Select fields to



MongoDB – Allow remote access



limit of 104857600 bytes ( <a href="http://www.mkyong.com/mongodb/mongodb-sort-exceeded-memory-limit-of-104857600-bytes/">http://www.mkyong.com/mongodb/mongodb-sort-exceeded-memory-limit-of-104857600-bytes/</a> )	Grouping Example ( <a href="http://www.mkyong.com/mongodb/mongodb-aggregation-grouping-example/">http://www.mkyong.com/mongodb/mongodb-aggregation-grouping-example/</a> )	return ( <a href="http://www.mkyong.com/mongodb/mongodb-select-fields-to-return/">http://www.mkyong.com/mongodb/mongodb-select-fields-to-return/</a> )	( <a href="http://www.mkyong.com/mongodb/mongodb-how-to-remove-a-field-from-document/">http://www.mkyong.com/mongodb/mongodb-how-to-remove-a-field-from-document/</a> )
---	---	---	---



MongoDB – How to remove a field from document  
(<http://www.mkyong.com/mongodb/mongodb-how-to-remove-a-field-from-document/>)

## About the Author



mkyong

Founder of Mkyong.com (<http://mkyong.com>) and HostingCompass.com (<http://hostingcompass.com>), love Java and open source stuff. Follow him on Twitter (<https://twitter.com/mkyong>), or befriend him on Facebook (<http://www.facebook.com/java.tutorial>) or Google Plus (<https://plus.google.com/110948163568945735692?rel=author>). If you like my tutorials, consider make a donation to these charities (<http://www.mkyong.com/blog/donate-to-charity/>).

## Comments

Office 365 Business

Einfach mehr erledigen: mit brandneuen 2016-Apps

Microsoft

Hier klicken

APIs will change  
your industry.



Find out how





Mkyong  
48,353 likes

 Like Page

 Sign Up

Be the first of your friends to like this





---

Android Getting Started (<http://developer.android.com/training/index.html>)  
Google App Engine – Java (<https://cloud.google.com/appengine/docs/java/>)  
Spring 2.5.x Documentation (<http://docs.spring.io/spring/docs/2.5.x/reference/index.html>)  
Spring 3.2.x Documentation (<http://docs.spring.io/spring/docs/3.2.x/spring-framework-reference/html/>)  
Spring 4.1.x Documentation (<http://docs.spring.io/spring/docs/4.1.x/spring-framework-reference/html/>)  
Java EE 5 Tutorial (<http://docs.oracle.com/javaee/5/tutorial/doc/docinfo.html>)  
Java EE 6 Tutorial (<http://docs.oracle.com/javaee/6/tutorial/doc/docinfo.html>)  
Java EE 7 Tutorial (<https://docs.oracle.com/javaee/7/tutorial/index.html>)  
Java 6 API (<http://docs.oracle.com/javase/6/docs/api/overview-summary.html>)  
Java 7 API (<http://docs.oracle.com/javase/7/docs/api/overview-summary.html>)  
Java 8 API (<http://docs.oracle.com/javase/8/docs/api/overview-summary.html>)  
JSF Home Page (<https://javaserverfaces.java.net/>)  
JSP Home Page (<https://jsp.java.net/>)

Maven Central Repository (<http://search.maven.org/>)  
Hibernate ORM (<http://hibernate.org/orm/>)  
JAX-WS Home Page (<https://jax-ws.java.net/>)  
JAX-RS Home Page (Jersey) (<https://jax-ws.java.net/>)

---

Java Code Geeks (<http://www.javacodegeeks.com/>)  
TestNG Founder (<http://beust.com/weblog/>)  
DZone (<https://dzone.com>)

---

Mkyong.com is for Java and J2EE developers, all examples are simple and easy to understand, and well tested in my development environment.

Mkyong.com is created, written by, and maintained by Yong Mook Kim, aka Mkyong. It is built on WordPress (<https://wordpress.org/>), hosted by Liquid Web (<http://mkyong.com/go/liquidweb/>), and the caches are served by CloudFlare CDN.