

# EE511 Assignment1

Zechen Ha

January 2020

# 1 Question1

## Statement:

Simulate tossing a fair coin (a Bernoulli trial) 50 times. Count the number of heads. Record the longest run of heads.

## Experiment:

To simulate the process of tossing a fair coin and repeat 50 times independently, I create a random number with `random.random()` in Python, and set the range  $[0,0.5]$  as Tail, and set the range  $(0.5,1]$  as Head. Repeat the process for 50 times and count the number of heads and the longest run of heads.

## Answer:

Number of Heads: 26

The longest run of Heads: 6

## Question-a Statement:

Repeat the above experiment 20, 100, 200, and 1000 times. Generate a histogram for each showing the number of heads in 50 flips. Comment on the limit of the histogram.

## Answer:




Figure 1: Repeat experiment 20 times




Figure 2: Repeat experiment 100 times




Figure 3: Repeat experiment 200 times




Figure 4: Repeat experiment 1000 times

#### Comment on the limit of histogram

Each experiment is a Bernoulli trial, which leads to two results with equal probability. Repeat independently and identically in a group of experiments results in binomial trials. In probability theory, the pmf (probability mass function) of binomial hints that probability gets small when  $n$  goes far from the mean, and the peak of the distribution is the mean. According to CLT (central limit theorem), the distribution is similar to normal distribution.

We can analyse the limit of the histogram with the help of pmf and CLT. The mean of the binomial distribution is equal to  $n \cdot p$ , in which  $n=50$  and  $p=0.5$ . So the mean is equal to 25. When the number of heads is far from the mean, there are less times and the times reach peak when number of heads is around 25.

#### Question1 Code

```
1 import numpy as np
2 import matplotlib.pyplot as plt
3 import random
4
5 #Initial conditions
6 fair_coin_boundary = 0.5
7 count_number_Head = 0
8 experiment_times = 50
```

```

9 repeat_times = 1000
10 run_Head = 0
11 longest_run_Head = 0
12 count_number_Head_list = []
13
14 #Simulation
15 for r in range(repeat_times):
16     run_Head = 0
17     count_number_Head = 0
18     for experiment in range(experiment_times):
19         if(random.random()>fair_coin_boundary):#Head
20             count_number_Head+=1
21             run_Head+=1
22             if(longest_run_Head < run_Head):
23                 longest_run_Head = run_Head
24         else:#Tail
25             run_Head = 0
26     count_number_Head_list.append(count_number_Head)
27
28 #Output
29 print(longest_run_Head)
30 # print(count_number_Head_list)
31
32 #Graph
33 n,bins,patches = plt.hist(count_number_Head_list,bins=15,rwidth
    =0.9,edgecolor='black',alpha=0.8)
34 plt.xlim(min(count_number_Head_list),max(count_number_Head_list))
35 plt.grid(axis='y',alpha=0.8)
36 plt.ylabel('Times',fontsize=12)
37 plt.xlabel('Number of heads',fontsize=12)
38 plt.title('Number of Heads Histogram',fontsize=15)
39 plt.show()

```

## 2 Question2

### Statement:

Simulate tossing a biased coin 200 times where  $P[\text{HEAD}]=0.80$ . Count the number of heads. Record the longest run of heads. Generate a histogram for the Bernoulli outcomes.

### Experiment:

The experiment is similar to the first one. Simulate the Bernoulli trial with Python function `random.random()`, and set the range of  $(0.2,1]$  as heads and set the range of  $[0,0.2]$  as tails. Repeat the experiment 200 times. Count the number of heads and the longest run of heads during the process.

### Answer:

The number of heads: 165

The longest run of heads: 13




Figure 5: Histogram for Bernoulli outcomes

In probability theory, the mathematical expectation of Bernoulli distribution is  $n \cdot p$ , which is equal to  $200 \cdot 0.8 = 160$ . The result of the simulation is approximately the same as the expectation.

### Question2 Code

```

1 import numpy as np
2 import matplotlib.pyplot as plt
3 import random
4
5 #Initial conditions
6 fair_coin_boundary = 0.2
7 experiment_times = 200
8 repeat_times = 1
9 run_Head = 0
10 longest_run_Head = 0
11 count_number_Head_list = []
12 count_number_Head = 0
13
14 #Simulation
15 for r in range(repeat_times):
16     run_Head = 0
17     for experiment in range(experiment_times):
18         if(random.random() > fair_coin_boundary): #Head
19             count_number_Head_list.append(1)
20             count_number_Head += 1

```

```

21         run_Head+=1
22         if(longest_run_Head < run_Head):
23             longest_run_Head = run_Head
24     else:#Tail
25         run_Head = 0
26         count_number_Head_list.append(0)
27
28 #Output
29 print(longest_run_Head)
30 print(count_number_Head)
31
32 #Graph
33 n,bins,patches = plt.hist(count_number_Head_list,bins=2,rwidth=1,
34                             edgecolor='black',alpha=0.8,range=(-0.5,1.5))
35 # plt.xlim(min(count_number_Head_list),max(count_number_Head_list))
36 plt.grid(axis='y',alpha=0.8)
37 plt.ylabel('Counts',fontsize=12)
38 plt.xlabel('Heads=1; Tails=0',fontsize=12)
39 plt.title('Histogram for Bernoulli outcomes',fontsize=15)
40 plt.show()

```

### 3 Question3

#### Statement:

Simulate tossing a fair coin 100 times. Generate a histogram showing the heads run lengths.

#### Experiment:

The experiment is similar and I just count the length of the heads run during the group of experiments.

#### Answer:




Figure 6: Run heads length histogram

### Question3 Code

```
1 import numpy as np
2 import matplotlib.pyplot as plt
3 import random
4
5 #Initial conditions
6 fair_coin_boundary = 0.5
7 experiment_times = 100
8 repeat_times = 1
9 run_Head = 0
10 run_length_list = []
11
12 #Simulation
13 for r in range(repeat_times):
14     run_Head = 0
15     for experiment in range(experiment_times):
16         if(random.random()>fair_coin_boundary):#Head
17             run_Head+=1
18         else:#Tail
19             if(run_Head!=0):
20                 run_length_list.append(run_Head)
21             run_Head = 0
22
23 #Output
24 print(run_length_list)
25
26 #Graph
27 n,bins,patches = plt.hist(run_length_list,bins=6,rwidth=0.9,
28                             edgecolor='black',alpha=0.8)
29 plt.xlim(min(run_length_list),max(run_length_list))
30 plt.grid(axis='y',alpha=0.8)
31 plt.ylabel('Counts',fontsize=12)
32 plt.xlabel('Heads run length',fontsize=12)
33 plt.title('Heads run length Histogram',fontsize=15)
34 plt.show()
```

## 4 Question4

### Statement:

Simulate tossing a fair coin and count the number of tosses until reaching a user-specified positive number of heads.

### Experiment:

Use the input function to get the user-specified positive number of heads. Then check whether it is a valid number. Simulate the Bernoulli trial in a similar way to count the heads number until it reaches the set goal.

### Answer:



Number of Heads	Number of Experiment	Heads/Experiment
100	205	0.489
500	985	0.508
1000	2018	0.496
5000	10110	0.495

The number of the needed number of experiment is approximately twice as many as the user-specified number of heads. It meets the expectation of the Bernoulli trial.

#### Question4 Code

```

1 import random
2
3 #initial conditions
4 fair_coin_boundry = 0.5
5 experiment_number = 0
6 head_number = 0
7
8 #Input validation test
9 try:
10     #input number of heads
11     goal = int(input("Please input the positive number of heads:"))
12     #Simulation
13     while(head_number<goal):
14         if(random.random()>fair_coin_boundry):#Head
15             head_number+=1
16             experiment_number+=1
17
18     #Output
19     print(experiment_number)
20     print(head_number)
21 except:
22     print("Invalid input, please check")

```