

A Dynamic **Card** in React Bootstrap - Part 1

Phillip G. Bradford*

March 27, 2025

Abstract

The Card component in React bootstrap can be made dynamic. Card components play an important role for our block explorer. This dynamic card uses the *useState* function from *React hooks*. A stacks block is featured here.

1 Stacks block dynamic card component

To create a basic Card component for a *Stacks block*, do the next steps.

1. `npx create-react-app card-example-dynamic`
2. `cd card-example-dynamic`

In Listing 1, we update the *App.js* file in the `src` directory. We have truncated the hash values to fit on the page.

```
1 import './App.css';
2
3 import DynamicCard from './components/DynamicCard';
4
5 const container =
6 {
7   "canonical": true,
8   "height": 733786,
9   "hash": "0x456ff10c1f3d870697fe8ea80ce27f01756ba4875515c47d...",
10  "block_time": 1741441821,
11  "block_time_iso": "2025-03-08T13:50:21.000Z",
12  "tenure_height": 187940,
13  "index_block_hash": "0xa9900a4323c92ae587f8e55622b8d46cb991...",
```

*phillip.bradford@uconn.edu, phillip.g.bradford@gmail.com, UNIVERSITY OF CONNECTICUT, DEPARTMENT OF COMPUTING, STAMFORD, CT USA

```

14   "parent_block_hash": "0xfeb3d1dd27e2555ea372669c9547b7887d3...",
15   "burn_block_time": 1741441223,
16   "burn_block_time_iso": "2025-03-08T13:40:23.000Z",
17   "burn_block_hash": "0x00000000000000000000079a14b7bcddfc0c1...",
18   "burn_block_height": 886865,
19   "miner_txid": "0x0813472654ee73ed1686c1a72a3e7d28c655ded29d...",
20   "execution_cost_read_count": 0,
21   "execution_cost_read_length": 0,
22   "execution_cost_runtime": 0,
23   "execution_cost_write_count": 0,
24   "execution_cost_write_length": 0,
25   "txs": [
26     "0xc2f9bb6a6a73e08ce38da86757cd866e54381c2bde43141e70ab52...",
27     "0xd0c97bf834e9e87e6e0811a1e7fb4ccc9dbf1fc3ebccee83ab2ebc..."
28   ],
29   "parent_microblock_hash": "",
30   "parent_microblock_sequence": -1,
31   "microblocks_accepted": [],
32   "microblocks_streamed": [],
33   "microblock_tx_count": {}
34 };
35
36 export default function App() {
37   return (
38     <div className="App">
39       <header className="App-header">
40         <DynamicCardFull props={container} />
41       </header>
42     </div>
43   );
44 }

```

Listing 1: Update app.js in the *src* folder for a Stacks block

3. `npm install react bootstrap react-bootstrap`

4. Replace the code in App.js in the *src* directory with the code in Listing 1.

Next we generate the component `<DynamicCardFull />`.

1. Create a subdirectory `components` of the *src* directory.

2. Create a file `BlockCard.js` in the *src/components* directory.

- Put the content of Listing 2 in `DynamicCardFull.js`.

This code will host a *DynamicCardFull* in *App.js* on line 7. Specifically, Add `<DynamicCardFull />` between `<header className="App-header">` and `</header>`

This card is dynamic. It is dynamic by storing *state* based on `const [open, setOpen] = useState(false);`
This is from *React hooks*.

Update `<DynamicCardFull />` with the following properties in the *container* object.

[illegible]

In Listing 1, the basic updated version is,

<DynamicCardFull props={container} />

```

1  import React, { useState } from "react";
2  import { Card, Button } from "react-bootstrap";
3  import "bootstrap/dist/css/bootstrap.min.css";
4
5  export default function DynamicCardFull ({ props }) {
6    const [open, setOpen] = useState(false);
7
8    return (
9      <div className="card custom-card border-primary mb-3">
10        <Card style={{ maxWidth: "700px", margin: "auto" }}
11          className="container ms-0" >
12          <Card.Body>
13            <Card.Title><h3>Burn Block</h3></Card.Title>
14            <ul className="list-group list-group-flus no-bullets">
15              <li class="list-group-item text-primary">
16                <Button
17                  onClick={() => setOpen(!open)}
18                  aria-controls="collapse-text"
19                  aria-expanded={open}
20                  className="mb-2"
21                >
22              </Button>
23              <h6>{open ? "Hash tail: " + props['hash'].slice(-20)
24                : "Hash: " + props['hash']}</h6>
25            </li>
26            <ul className="list-group list-group-flus no-bullets">
27              {Object.entries(props).map(([key, value]) => (
28                <li key={key}>
29                  <h6>{key}: {JSON.stringify(value)}</h6>
30                </li>
31              ))}
32            </ul>
33          </ul>
34        </Card.Body>
35      </Card>
36    </div>
37  );
38  };

```

Listing 2: Basic Dynamic Card for a Stacks block

Listing 2 shows a basic *dynamic* card from React-bootstrap. This card holds a Stacks

block. This is in the file `DyanmicCardFull.js` in the `src/components` directory.

References

- [1] Ryan J. Blake: *Mastering Bootstrap 5*, Beginners Handbook, 2024.
- [2] React Bootstrap: *React Bootstrap Cards*,
<https://react-bootstrap.netlify.app/docs/components/cards/> , Accessed: 2025-03-15.