

ROCIP6 Excavation & Trenching Check List

Miss Utility Permit # :

Date:

Section 1 – Preparation (Contractor's Qualified Person or Safety Manager Completes Section 1)

Job Name/Contract Number:	
Name of Contractor:	
Location of The Excavation Work:	
Description of Excavation Work :	
Third Party Utility Locating Company Name:	Locater Employee Name:
Private Utilities Verification Signatures:	

Following Items Listed Below Must Be Done Prior To Opening an Excavation

Pre-Planning Meeting with DC Water	Yes	No
Plans Reviewed For Existing Utilities	Yes	No
Utility Grid Sweep Conducted of the "Entire" Excavation Area and 5 feet beyond marked excavation perimeter.	Yes	No
Are pre-excavation photos taken showing the utility markings prior to excavating?	Yes	No
Utilities Marked and Utilities Physically/Visually Located (hand dig, pot hole, hydroexcavate)	Yes	No

Section 2 – Excavation (Contractor's Competent Person Completes Section 2)

Competent Person Name:	
Soil Type:	Slope Ratio: Protective System Used (Tabulated Data Submitted to DC Water):
Excavation/Trench Depth:	Excavation/Trench Width:
Note: Soils that have been previously disturbed (e.g. existing utilities, sewer,) are classified as "C" type soils	

Section 3 – Hazard Assessment and Control (Contractor's Competent Person Completes Section 3)

Controls to be Implemented (Contractor shall perform excavation work in accordance of CFR1926 sub part P).		Completed	N/A
Personnel & Property Safety Issues	Competent Person has inspected excavation, adjacent areas, and protective systems prior to employees performing work in the excavation/trench.		
	Professional Engineer was obtained to approve excavation of >20' depth.		
	Trench area has restricted access via physical barrier for vehicle traffic and guardrails, fencing 6 feet back for pedestrian protection.		
	Employees protected from loose rock/soil that could pose a hazard by falling or rolling into the excavation/trench.		
	Trench is shored and/or sloped per CFR 1926 Subpart P requirements.		
	Trench is free from standing water and other contaminants.		
	Excavated material, equipment and other items will be placed at least 2' from edge of trench.		
	Employees are prohibited working under suspended loads.		
	Walkways and bridges over excavations/trenches 6 feet or more in depth shall have standard guardrails and toe boards.		
	Trench box system meets all regulatory requirements. Tabulated datasheets shall be available on site.		
	Underground utilities protected, supported or removed when excavation is open (P.E. may be required for supporting utilities).		
	Wood used for shoring or bracing is in good condition and free from defects.		
	Ladder provided in trench >4' depth with ladder extending at least 3' above top of trench.		
	Ladder, ramp, or stair is provided within 25' of all personnel working in trench.		
Air testing was performed at 4' depth or more (Oxygen, LEL, Toxics). Results:			
Soils Classified as "B" type soil shall have first bench 6 feet.			

Section 4 – Approvals – I have reviewed this Permit and all conditions and agree that work can proceed safely.

Contractor Project Manager Name & Signature:	Date:
Competent Person Name, Title & Signature:	Date: