

In[]:=

```
SetDirectory[NotebookDirectory[]];  
<< AdditiveDecomposition.m
```

AdditiveDecomposition.m is written by Hao Du and Elaine Wong, Austrian Academy of Sciences, RICAM, Version 0.1 (May 14, 2020)
→ Type ?AdditiveDecomposition for help

In[]:=

? AdditiveDecomposition

Welcome to AdditiveDecomposition.m. This package accompanies the paper **An Additive Decomposition in Logarithmic Towers and Beyond** by Hao Du, Jing Guo, Ziming Li and Elaine Wong.

The main objective of this package is an implementation of the algorithm for decomposing a function in an S-primitive tower into its integrable part and a remainder that is minimal in some sense, both of which are in the same field. If the tower is also logarithmic, then we are able to determine an extension field such that the function can be decomposed further. A function in an S-primitive tower is integrable in the tower if and only if the remainder is equal to zero.

The following commands serve the above objectives: AddDecompInField and WellGenLogTower.

Common subtasks in the above algorithm are Hermite reduction and computing the matryoshka decomposition. These are also provided in this implementation via HermiteReduceGeneral and ProperDecomposition, respectively. Please refer to the example notebook for usage examples.

Some other functions that might be useful:

ExtendedEuclidean, HeadTerm, MonomialIndicator, AddDecompLogTower.

Part 1: Examples from the Paper

Example 3.1

In[]:= $f = (t_2 + x) (t_3^2 - t_1 t_3 + x t_2) / (x t_2 t_3)$
genlist = {t1, t2, t3};
ProperDecomposition[f, genlist] // Together

Out[]:=
$$\frac{(t_2 + x) (-t_1 t_3 + t_3^2 + t_2 x)}{t_2 t_3 x}$$

Out[]:=
$$\left\{ \frac{-t_1 + t_3}{x}, 0, \frac{-t_1 + t_3}{t_2}, \frac{t_2 + x}{t_3} \right\}$$

Example 4.9

```

In[ ]:= f = 
$$\frac{1}{\text{Log}[x] \text{LogIntegral}[x]} + \frac{-2 x \text{Log}[x] + \text{LogIntegral}[x]}{\text{Log}[x]^2} + \text{Log}[\text{Log}[x]];$$

Print["f = ", f];
Print["Generators and derivatives:"];
genlog = {Log[x], LogIntegral[x], Log[Log[x]]}
derlog = D[#, x] & /@ genlog // Together
Print["Renaming generators and substituting into f:"];
genlist = Table[Symbol["t" <> ToString[i]], {i, Length[genlog]}]
subs = Thread[genlog -> genlist];
derlist = derlog //. subs
fnew = f //. subs;
Print["f = ", fnew];
Print["Additive decomposition {integrable part, remainder}:"];
adif = AddDecompInField[fnew, x, genlist, derlist]
Print["Remainder in the base field:"];
subt = GenSubstitute[x, genlist, derlist];
r = (adif[[2]]) //. subt

f = 
$$\text{Log}[\text{Log}[x]] + \frac{1}{\text{Log}[x] \text{LogIntegral}[x]} + \frac{-2 x \text{Log}[x] + \text{LogIntegral}[x]}{\text{Log}[x]^2}$$

Generators and derivatives:
Out[ ]:= {Log[x], LogIntegral[x], Log[Log[x]]}

Out[ ]:= 
$$\left\{ \frac{1}{x}, \frac{1}{\text{Log}[x]}, \frac{1}{x \text{Log}[x]} \right\}$$

Renaming generators and substituting into f:
Out[ ]:= {t1, t2, t3}
Out[ ]:= 
$$\left\{ \frac{1}{x}, \frac{1}{t1}, \frac{1}{t1 x} \right\}$$

f = 
$$\frac{1}{t1 t2} + t3 + \frac{t2 - 2 t1 x}{t1^2}$$

Additive decomposition {integrable part, remainder}:
Out[ ]:= 
$$\left\{ -t2 + \frac{t2^2}{2} - \frac{t2 x}{t1} + t3 x - \frac{x^2}{t1}, \frac{1}{t1 t2} \right\}$$

Remainder in the base field:
Out[ ]:= 
$$\frac{1}{\text{Log}[x] \text{LogIntegral}[x]}$$


```

Example 5.1

```

In[ ]:= f = 
$$\frac{\text{Log}[(1+x) \text{Log}[x]]}{x \text{Log}[x]}$$
;
Print["f = ", f];
f = 
$$\frac{\text{Log}[(1+x) \text{Log}[x]]}{x \text{Log}[x]}$$


In[ ]:= Print["Generators and derivatives for Tower (i):"];
genlog = {Log[x], Log[(x+1) Log[x]]}
derlog = D[#, x] & /@ genlog // Together
Print["Renaming generators and substituting into f:"];
genlist = Table[Symbol["t" <> ToString[i]], {i, Length[genlog]}]
subs = Thread[genlog -> genlist];
derlist = derlog //. subs
fnew = f //. subs;
Print["f = ", fnew];
Print["Additive decomposition {integrable part, remainder}:"];
adif = AddDecompInField[fnew, x, genlist, derlist]
Print["Remainder in the base field:"];
subt = GenSubstitute[x, genlist, derlist];
r = (adif[[2]]) //. subt

Generators and derivatives for Tower (i):

Out[ ]:= {Log[x], Log[(1+x) Log[x]]}

Out[ ]:= 
$$\left\{ \frac{1}{x}, \frac{1+x+x \text{Log}[x]}{x(1+x) \text{Log}[x]} \right\}$$


Renaming generators and substituting into f:

Out[ ]:= {t1, t2}

Out[ ]:= 
$$\left\{ \frac{1}{x}, \frac{1+x+t1 x}{t1 x(1+x)} \right\}$$



$$f = \frac{t2}{t1 x}$$


Additive decomposition {integrable part, remainder}:

Out[ ]:= 
$$\left\{ 0, \frac{t2}{t1 x} \right\}$$


Remainder in the base field:

Out[ ]:= 
$$\frac{\text{Log}[1+x] + \text{Log}[\text{Log}[x]]}{x \text{Log}[x]}$$


```

```

In[ ]:= f = 
$$\frac{\text{Log}[1 + x] + \text{Log}[\text{Log}[x]]}{x \text{Log}[x]}$$
;
Print["f = ", f];
f = 
$$\frac{\text{Log}[1 + x] + \text{Log}[\text{Log}[x]]}{x \text{Log}[x]}$$


In[ ]:= Print["Generators and derivatives for Tower (ii):"];
genlog = {Log[x], Log[x + 1], Log[Log[x]]}
derlog = D[#, x] & /@ genlog // Together
Print["Renaming generators and substituting into f:"];
genlist = Table[Symbol["u" <> ToString[i]], {i, Length[genlog]}]
subs = Thread[genlog → genlist];
derlist = derlog //. subs
fnew = f //. subs;
Print["f = ", fnew];
Print["Additive decomposition {integrable part, remainder}:"];
adif = AddDecompInField[fnew, x, genlist, derlist]
Print["Remainder in the base field:"];
subt = GenSubstitute[x, genlist, derlist];
r = (adif[[2]]) //. subt

Generators and derivatives for Tower (ii):

Out[ ]:= {Log[x], Log[1 + x], Log[Log[x]]}

Out[ ]:=  $\left\{ \frac{1}{x}, \frac{1}{1 + x}, \frac{1}{x \text{Log}[x]} \right\}$ 

Renaming generators and substituting into f:

Out[ ]:= {u1, u2, u3}

Out[ ]:=  $\left\{ \frac{1}{x}, \frac{1}{1 + x}, \frac{1}{u1 x} \right\}$ 

f = 
$$\frac{u2 + u3}{u1 x}$$


Additive decomposition {integrable part, remainder}:

Out[ ]:=  $\left\{ \frac{u3^2}{2}, \frac{u2}{u1 x} \right\}$ 

Remainder in the base field:

Out[ ]:= 
$$\frac{\text{Log}[1 + x]}{x \text{Log}[x]}$$


```

Example 5.7

```
In[ ]:= Print["Generators and derivatives:"];
genlog = {Log[x], Log[x Log[x]], Log[(x + 1) (Log[x] + 1) Log[x Log[x]]]};
derlog = D[#, x] & /@ genlog // Together
Print["Renaming generators:"];
genlist = Table[Symbol["t" <> ToString[i]], {i, Length[genlog]}]
subs = Thread[genlog → genlist];
derlist = derlog /. subs
Print["Associated matrix with respect to the matryoshka decomposition:"];
AssMat[genlist, derlist]
Print["We embed the previous tower into a well-generated one:"];
wgl = WellGenLogTower[x, genlist, derlist];
newgenlist = wgl[[1]];
newderlist = wgl[[3]];
subsu = Thread[genlist → newgenlist.wgl[[2]]]
wgl[[4]] // MatrixForm
```

Generators and derivatives:

$$\text{Out[]} = \left\{ \frac{1}{x}, \frac{1 + \text{Log}[x]}{x \text{Log}[x]}, \left(1 + x + 2 \text{Log}[x] + 2 x \text{Log}[x] + \text{Log}[x]^2 + x \text{Log}[x]^2 + \right. \right. \\ \left. \left. \text{Log}[x] \text{Log}[x \text{Log}[x]] + 2 x \text{Log}[x] \text{Log}[x \text{Log}[x]] + x \text{Log}[x]^2 \text{Log}[x \text{Log}[x]] \right) / \right. \\ \left. \left(x (1 + x) \text{Log}[x] (1 + \text{Log}[x]) \text{Log}[x \text{Log}[x]] \right) \right\}$$

Renaming generators:

Out[] = {t1, t2, t3}

$$\text{Out[]} = \left\{ \frac{1}{x}, \frac{1 + t1}{t1 x}, \right. \\ \left. \left(1 + 2 t1 + t1^2 + t1 t2 + x + 2 t1 x + t1^2 x + 2 t1 t2 x + t1^2 t2 x \right) / \left(t1 (1 + t1) t2 x (1 + x) \right) \right\}$$

Associated matrix with respect to the matryoshka decomposition:

$$\text{Out[]} // \text{MatrixForm} = \begin{pmatrix} \frac{1}{x} & \frac{1}{x} & \frac{1}{1+x} \\ 0 & \frac{1}{t1 x} & \frac{1}{(1+t1) x} \\ 0 & 0 & \frac{1+t1}{t1 t2 x} \end{pmatrix}$$

We embed the previous tower into a well-generated one:

Out[] = {t1 → u1, t2 → u1 + u3, t3 → u2 + u4 + u5}

Out[]:=MatrixForm=

$$\begin{pmatrix} \frac{1}{x} & \frac{1}{1+x} & 0 & 0 & 0 \\ 0 & 0 & \frac{1}{u1 x} & \frac{1}{(1+u1) x} & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & \frac{1+u1}{u1 (u1+u3) x} \\ 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

$$\text{In[]:= } f1 = \frac{(1+t1)^2 + t1 t2}{t1 (1+t1) t2 x}; \quad f2 = \frac{t3}{x};$$

Print["f1 = ", f1, " and f2 = ", f2];

phif1 = f1 /. subsu; phif2 = f2 /. subsu;

Print[" $\phi(f1)$ = ", phif1, " and $\phi(f2)$ = ", phif2];

Print["Additive decompositions for all f1, $\phi(f1)$, f2, $\phi(f2)$, respectively:"];

adif1 = AddDecompInField[f1, x, genlist, derlist]

adwg1 = AddDecompInField[phif1, x, newgenlist, newderlist]

adif2 = AddDecompInField[f2, x, genlist, derlist]

adwg2 = AddDecompInField[phif2, x, newgenlist, newderlist]

Print["Projections of the remainders of f2 and $\phi(f2)$, respectively:"];

ProperDecomposition[adif2[[2]], genlist]

ProperDecomposition[adwg2[[2]], newgenlist]

$$f1 = \frac{(1+t1)^2 + t1 t2}{t1 (1+t1) t2 x} \quad \text{and} \quad f2 = \frac{t3}{x}$$

$$\phi(f1) = \frac{(1+u1)^2 + u1 (u1+u3)}{u1 (1+u1) (u1+u3) x} \quad \text{and} \quad \phi(f2) = \frac{u2+u4+u5}{x}$$

Additive decompositions for all f1, $\phi(f1)$, f2, $\phi(f2)$, respectively:

$$\text{Out[]:= } \left\{ 0, \frac{1+2 t1+t1^2+t1 t2}{t1 (1+t1) t2 x} \right\}$$

$$\text{Out[]:= } \{u4+u5, 0\}$$

$$\text{Out[]:= } \left\{ -t1+t1 t3, \frac{(-1-2 t1-t1^2+t2-x-2 t1 x-t1^2 x+t2 x-t1 t2 x-t1^2 t2 x)}{(1+t1) t2 x (1+x)} \right\}$$

$$\text{Out[]:= } \left\{ -u1+u1 u2+u4+u1 u4+u1 u5, \frac{-1-u1-x-u1 x-u1^2 x-u1 u3 x}{(u1+u3) x (1+x)} \right\}$$

Projections of the remainders of f2 and $\phi(f2)$, respectively:

$$\text{Out[]:= } \left\{ \frac{t1}{-1-x}, \frac{1}{(1+t1) x}, \frac{-1-t1}{t2 x}, 0 \right\}$$

$$\text{Out[]:= } \left\{ \frac{u1}{-1-x}, 0, 0, \frac{-1-u1}{(u1+u3) x}, 0, 0 \right\}$$

Part 2: Illustration of the Main Functions

AddDecompInField

In[]:= ? AddDecompInField

AddDecompInField[f, var, gen, der] takes a function in an S-primitive tower and outputs the pair {integrable part of f, minimal remainder (0, if f is integrable)} from the same tower.

In[]:= AddDecompInField[t4, x, {t1, t2, t3, t4}, {1/x, 1/t1, 1/t2, 1/t3}]

Out[]:= $\left\{ t4 x, -\frac{x}{t3} \right\}$

In[]:= AddDecompInField[t4, x, {t1, t2, t3, t4},
 $\left\{ \frac{1}{x}, \frac{1}{1+x}, \frac{1}{t1}, (-t1 t2 - 2 t1 t3 + 2 x + t1 x - t1 t2 x - 2 t1 t3 x + 2 x^2 + 2 t3 x^2 + 2 t3 x^3) / (t1 x (1+x) (t2 + 2 t3 + t3^2 x)) \right\}$]

Out[]:= $\left\{ t4 x, (t1 t2 + 2 t1 t3 - 2 x - t1 x + t1 t2 x + 2 t1 t3 x - 2 x^2 - 2 t3 x^2 - 2 t3 x^3) / (t1 (1+x) (t2 + 2 t3 + t3^2 x)) \right\}$

In[]:= AddDecompInField[t2 + t2 t3 + $\frac{t2 - 2 t1 x}{t1^2}$, x, {t1, t2, t3}, { $\frac{1}{x}, \frac{1}{t1 x}, \frac{1}{1+x}$ }]

Out[]:= $\left\{ -\frac{x}{t1} - \frac{t2 x}{t1} + t2 t3 x, \frac{1 + t2 + t1 t2 - t3 - x + t2 x - t3 x - 2 x^2}{t1 (1+x)} \right\}$

WellGenLogTower

In[]:= ? WellGenLogTower

WellGenLogTower[var, gen, der] takes input from a primitive tower and outputs {new generators, the transfer matrix between old and new generators, new derivatives, associated matrix} of a well-generated tower.

In[]:= (* This is an example of an S-primitive tower satisfying (CLI) and (MI) to be used for input. *)

WellGenLogTower[x, {t1, t2, t3, t4}, { $\frac{1}{x}, \frac{1}{1+x}, \frac{1}{t1} + \frac{1}{x}, \frac{1}{t1} + \frac{1}{t2} + \frac{1}{x}$ }]

Out[]:= $\left\{ \{u1, u2, u3, u4\}, \{ \{1, 0, 1, 1\}, \{0, 1, 0, 0\}, \{0, 0, 1, 1\}, \{0, 0, 0, 1\} \}, \left\{ \frac{1}{x}, \frac{1}{1+x}, \frac{1}{u1}, \frac{1}{u2} \right\}, \left\{ \left\{ \frac{1}{x}, \frac{1}{1+x}, 0, 0 \right\}, \left\{ 0, 0, \frac{1}{u1}, 0 \right\}, \left\{ 0, 0, 0, \frac{1}{u2} \right\}, \{0, 0, 0, 0\} \right\} \right\}$

```

In[ ]:= (* This is an example of an S-
primitive tower not satisfying (CLI) and (MI) to be used for input. *)
(* Note that u4' is u3-simple. *)
WellGenLogTower[x, {t1, t2, t3, t4},
{
 $\frac{1}{x}, \frac{1}{1+x}, \frac{1}{t1}, \frac{2+t1+t1 t3^2+2 x+2 t3 x+t1 t3^2 x+2 t3 x^2}{t1 (1+x) (t2+2 t3+t3^2 x)}$ 
}]]

Out[ ]:= {
{u1, u2, u3, u4}, {{1, 0, 0, 1}, {0, 1, 0, 0}, {0, 0, 1, 0}, {0, 0, 0, 1}},
{
 $\frac{1}{x}, \frac{1}{1+x}, \frac{1}{u1}, (-u1 u2 - 2 u1 u3 + 2 x + u1 x - u1 u2 x - 2 u1 u3 x + 2 x^2 + 2 u3 x^2 + 2 u3 x^3) /$ 
 $(u1 x (1+x) (u2 + 2 u3 + u3^2 x))$ 
}, {{
 $\frac{1}{x}, \frac{1}{1+x}, 0, 0$ 
}, {
 $0, 0, \frac{1}{u1}, 0$ 
}, {
 $0, 0, 0, 0$ 
}},
{
 $0, 0, 0, (-u1 u2 - 2 u1 u3 + 2 x + u1 x - u1 u2 x - 2 u1 u3 x + 2 x^2 + 2 u3 x^2 + 2 u3 x^3) /$ 
 $(u1 x (1+x) (u2 + 2 u3 + u3^2 x))$ 
}]]}

In[ ]:= (* This is an example of a S-
primitive tower not satisfying (CLI) and (MI) to be used for input. *)
(* Note that u4' is NOT u3-simple. *)
WellGenLogTower[x, {t1, t2, t3, t4},
{
 $\frac{1}{x}, \frac{1}{t1}, \frac{2}{t1} + \frac{1}{1+x}, \frac{2+t1+t1 t2^2+2 x+2 t2 x+t1 t2^2 x+2 t2 x^2}{t1 (1+x) (t3+t2^2 x)}$ 
}]]

Out[ ]:= {
{u1, u2, u3, u4}, {{1, 0, 0, 1}, {0, 0, 1, 0}, {0, 1, 2, 0}, {0, 0, 0, 1}},
{
 $\frac{1}{x}, \frac{1}{1+x}, \frac{1}{u1}, (-u1 u2 - 2 u1 u3 + 2 x + u1 x - u1 u2 x - 2 u1 u3 x + 2 x^2 + 2 u3 x^2 + 2 u3 x^3) /$ 
 $(u1 x (1+x) (u2 + 2 u3 + u3^2 x))$ 
}, {{
 $\frac{1}{x}, \frac{1}{1+x}, 0, 0$ 
}, {
 $0, 0, \frac{1}{u1}, 0$ 
}, {
 $0, 0, 0, 0$ 
}},
{
 $0, 0, 0, (-u1 u2 - 2 u1 u3 + 2 x + u1 x - u1 u2 x - 2 u1 u3 x + 2 x^2 + 2 u3 x^2 + 2 u3 x^3) /$ 
 $(u1 x (1+x) (u2 + 2 u3 + u3^2 x))$ 
}]]}

```

Part 3: Useful Functions

ExtendedEuclidean

In[]:= ? ExtendedEuclidean

ExtendedEuclidean[a, b, c, var] computes {r,s} such that
 $r a + s b = c$ and the degree of r with respect to var is lower than that of b.


```
In[ ]:= Catch[ExtendedEuclidean[ $\frac{x(1+x)(1+y)}{-1+y}$ ,  $\frac{(-1+x)(1+y)}{-2+y}$ ,  $1+x^2$ ,  $x$ ]]
(* Check: r a + s b = c *)
Simplify[%[[1]] *  $\frac{x(1+x)(1+y)}{-1+y}$  + %[[2]] *  $\frac{(-1+x)(1+y)}{-2+y}$  -  $(1+x^2)$ ]
Out[ ]:=  $\left\{ \frac{-1+y}{1+y}, \frac{2-y}{1+y} \right\}$ 
Out[ ]:= 0
```

HermiteReduceGeneral

```
In[ ]:= ? HermiteReduceGeneral
```

HermiteReduceGeneral[f, var, gen, der] outputs {g, h, p}, such that $f = g' + h + p$, where h is simple and p is a polynomial with respect to the last generator in gen.

(* A hand made example *)

```
HermiteReduceGeneral[ $\frac{t2+x}{(-t1+t2)^2}$ , x, {t1, t2}, {1/x, 1/t1}]
Out[ ]:=  $\left\{ \frac{-t1^2 x - t1 x^2}{(t1 - t2)(t1 - x)}, \frac{t1^3 + 2 t1^2 x - 2 x^2 - t1 x^2}{(t1 - t2)(t1 - x)^2}, 0 \right\}$ 
```

(* Example from Bronstein's book Example 2.2.1 *)

```
HermiteReduceGeneral[
   $(x^7 - 24 x^4 - 4 x^2 + 8 x - 8) / (x^8 + 6 x^6 + 12 x^4 + 8 x^2)$ , x, {}, {}]
Out[ ]:=  $\left\{ \frac{3}{2+x^2} + \frac{4(1+2x^2)}{x(2+x^2)^2}, \frac{1}{x}, 0 \right\}$ 
```

ProperDecomposition

```
In[ ]:= ? ProperDecomposition
```

ProperDecomposition[f, {t₁, ..., t_n}] outputs a list of functions {f₀, f₁, ..., f_n} such that $f = f_0 + f_1 + \dots + f_n$, f_i in $K(t_1, \dots, t_i)[t_{i+1}, \dots, t_n]$ with t_i -proper coefficients for all i with $i > 0$ and f_0 in $K[t_1, \dots, t_n]$.

```
In[ ]:= ProperDecomposition[ $\frac{t1^2 t2 + t2^2 + x + t1 x}{(t1 - x)(-t1 + t2 + x)}$ , {t1, t2}]
Out[ ]:=  $\left\{ 1 + t1 + x, \frac{t2}{t1 - x} + \frac{x^2}{t1 - x}, \frac{-t1^2 - t1^3 - x + t1 x + t1^2 x - x^2}{(t1 - x)(t1 - t2 - x)} \right\}$ 
```

In[*]:= ProperDecomposition[$\frac{1+t1}{x}$, {t1}]

Out[*]:= $\left\{\frac{1}{x} + \frac{t1}{x}, 0\right\}$

In[*]:= ProperDecomposition[
 $(t^2 + t1 t^2 + t3 + t1 t3 + 2 t2 t3 + 2 t1 t2 t3 + 2 t2^2 t3 + t1 t2^2 t3 + t3^2 + t1 t3^2 + 4 t2 t3^2 +$
 $2 t1 t2 t3^2 + 2 t3^3 + t1 t3^3 + t2^2 x + t1 t2^2 x + t3 x + t1 t3 x + 2 t2 t3 x + 2 t1 t2 t3 x +$
 $t2^2 t3 x + t3^2 x + t1 t3^2 x + 2 t2 t3^2 x + t3^3 x) / ((1+t1) t3 (t2+t3)^2 (1+x))$
 ,
 {t1,
 t2,
 t3}]

Out[*]:= $\left\{\frac{1}{1+x}, \frac{1}{1+t1}, 0, \frac{t2^2 + t3 + 2 t2 t3 + t3^2}{t3 (t2+t3)^2}\right\}$

Head Term

In[*]:= ? HeadTerm

HeadTerm[f, gen] outputs the highest term among all of the leading terms of each projection of f with respect to the proper decomposition in the form of {coefficient, monomial}.

In[*]:= HeadTerm[$\frac{t2}{t3} + \frac{t2^2 t3}{t1} + t2 t3^2$, {t1, t2, t3}]

HeadTerm[$\frac{1}{(-1+t1)(1+t2)t3}$
 $(-t2 + t1 t2 - t2^2 + t1 t2^2 - t1^5 t3^2 + t1^6 t3^2 - 2 t2 t3^2 + 2 t1 t2 t3^2 - t3^4 + t1 t3^4 + t1 t3^5 + t1$
 $t2 t3^5 - t3 x - t2 t3 x - t1 t2 t3 x + t1^2 t2 t3 x - t1 t2^2 t3 x + t1^2 t2^2 t3 x), \{t1, t2, t3\}]$

Out[*]:= {1, t2 t3²}

Out[*]:= $\left\{1 + \frac{1}{-1+t1}, t3^4\right\}$

MonomialIndicator

? MonomialIndicator

MonomialIndicator[monomial, gen] outputs the index of the lowest generator (with respect to the generator list, gen) appearing in the monomial. It outputs the length of gen if the monomial is 1.

```
In[ ]:= MonomialIndicator[x, {t1, t2, t3}]
MonomialIndicator[t2^3 t3^8, {t1, t2, t3}]
MonomialIndicator[t2^3 t3^8, {t3, t2, t1}]
MonomialIndicator[1, {t3, t2, t1}]
```

```
Out[ ]:= 3
```

```
Out[ ]:= 2
```

```
Out[ ]:= 1
```

```
Out[ ]:= 3
```

AddDecompLogTower

? AddDecompLogTower

? CheckAddDecompLogTower

AddDecompLogTower[f, var, gen, der] takes a function in a well-generated S-primitive tower and outputs the pair {integrable part of f, its minimal remainder (0 if f is integrable)} and all of the information needed to transform the old generators to the new ones in the form of a triple {new generator names, transfer matrix from old to new generators, new derivatives},

CheckAddDecompLogTower[f, var, gen, results] takes the results from AddDecompLogTower[f, var, gen, der] and outputs True if the decomposition is correct.

```
AddDecompLogTower[t4, x, {t1, t2, t3, t4}, {1/x, 1/t1, 2/t1 + 1/(1+x), 1/t2 + 1/(1+x)}]
```

```
CheckAddDecompLogTower @@ Append[{t4, x, {t1, t2, t3, t4}}, %]
```

```
Out[ ]:= {{u2 - x + u2 x + u4 x, -x/u3}, {{u1, u2, u3, u4},
      {{1, 0, 0, 0}, {0, 0, 1, 1}, {0, 1, 2, 0}, {0, 0, 0, 1}}, {1/x, 1/(1+x), 1/u1, 1/u3}}}}
```

```
Out[ ]:= True
```

```
AddDecompLogTower[t4, x, {t1, t2, t3, t4},
  { $\frac{1}{x}$ ,  $\frac{1}{t1}$ ,  $\frac{2}{t1} + \frac{1}{1+x}$ ,  $\frac{2+t1+t1 t2^2+2 x+2 t2 x+t1 t2^2 x+2 t2 x^2}{t1 (1+x) (t3+t2^2 x)}$ }]
CheckAddDecompLogTower @@ Append[{t4, x, {t1, t2, t3, t4}}, %]
```

```
Out[8]= { { -x + u1 x + u4 x, (u1 u2 + 2 u1 u3 - 2 x - u1 x + u1 u2 x + 2 u1 u3 x - 2 x^2 - 2 u3 x^2 - 2 u3 x^3) /
  (u1 (1 + x) (u2 + 2 u3 + u3^2 x)) },
  { {u1, u2, u3, u4}, {{1, 0, 0, 1}, {0, 0, 1, 0}, {0, 1, 2, 0}, {0, 0, 0, 1}},
  {  $\frac{1}{x}$ ,  $\frac{1}{1+x}$ ,  $\frac{1}{u1}$ ,  $(-u1 u2 - 2 u1 u3 + 2 x + u1 x - u1 u2 x - 2 u1 u3 x + 2 x^2 + 2 u3 x^2 + 2 u3 x^3) /$ 
  (u1 x (1 + x) (u2 + 2 u3 + u3^2 x)) } } }
```

```
Out[9]= True
```

```
In[10]:= (* The following shows that Mathematica is unable
  to integrate the integrable part (but we can!). *)
inttemp = Log[x + 1] - x + Log[x + 1] x + x Integrate[1/LogIntegral[x], x]
ftemp = Log[x + 1] + Integrate[1/LogIntegral[x], x]
remtemp = -x/LogIntegral[x]
Simplify[D[inttemp, x] + remtemp - ftemp]
Integrate[Together[ftemp - remtemp], x]
```

```
Out[10]= -x + x  $\int \frac{1}{\text{LogIntegral}[x]} dx$  + Log[1 + x] + x Log[1 + x]
```

```
Out[10]=  $\int \frac{1}{\text{LogIntegral}[x]} dx$  + Log[1 + x]
```

```
Out[10]= -  $\frac{x}{\text{LogIntegral}[x]}$ 
```

```
Out[10]= 0
```

```
Out[10]=  $\int \left( \left( x + \left( \int \frac{1}{\text{LogIntegral}[x]} dx \right) \text{LogIntegral}[x] + \text{Log}[1 + x] \text{LogIntegral}[x] \right) / \right. \\ \left. \text{LogIntegral}[x] \right) dx$ 
```

Part 4: Testsuite

```
In[11]:= (* This collection of examples were used for
  timings. Examples provided by Christoph Koutschan. *)
christoph1 = Import["decomp_examples_collection1.m"];
```

... Import: File not found during Import.

```
(* Testing Christoph's examples that take longer than a second to compute. *)
```

```
list = {22, 52, 53, 54, 57, 58, 76, 81, 92, 93, 94, 95, 96, 98};
```

```
Do[
```

```
  Print[{list[[i]], Timing[adwgtemp = AddDecompLogTower @@ christoph1[[list[[i]]]]];},
```

```
    CheckAddDecompLogTower @@
```

```
      Append[christoph1[[list[[i]]]][[1 ;; 3]], adwgtemp]]], {i, 1, Length[list]}
```

```
{22, {0.868701, Null}, True}
```

```
{52, {6.58974, Null}, True}
```

```
{53, {1.86005, Null}, True}
```

```
{54, {9.83859, Null}, True}
```

```
{57, {11.7119, Null}, True}
```

```
{58, {16.3598, Null}, True}
```

```
{76, {1.79769, Null}, True}
```

```
{81, {17.6016, Null}, True}
```

```
{92, {1.41359, Null}, True}
```

```
{93, {1.90118, Null}, True}
```

```
{94, {1.41863, Null}, True}
```

```
{95, {1.90065, Null}, True}
```

```
{96, {1.53078, Null}, True}
```

```
{98, {1.04365, Null}, True}
```

```
(* 82 and 90 takes a long time, but at least it finishes! *)
```

```
Do[Print[{i, Timing[adwgtemp = AddDecompLogTower @@ christoph1[[i]]];},
```

```
  CheckAddDecompLogTower @@
```

```
    Append[christoph1[[i]][[1 ;; 3]], adwgtemp]]], {i, 82, 82}]
```

```
{82, {7104.54, Null}, True}
```

```
Do[Print[{i, Timing[adwgtemp = AddDecompLogTower @@ christoph1[[i]]];},
```

```
  CheckAddDecompLogTower @@
```

```
    Append[christoph1[[i]][[1 ;; 3]], adwgtemp]]], {i, 90, 90}]
```

```
{90, {3575.02, Null}, True}
```