

Code Along 9

Wong Wei Qi

2023-10-18

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.2      v readr      2.1.4
## v forcats    1.0.0      v stringr   1.5.0
## v ggplot2    3.4.3      v tibble    3.2.1
## v lubridate  1.9.2      v tidyr     1.3.0
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
tidydata <- tribble(
  ~country, ~year, ~cases, ~population,
  "Afghanistan", 1999, 745, 19987071,
  "Afghanistan", 2000, 2666, 20595360,
  "Brazil", 1999, 37737, 172006362,
  "Brazil", 2000, 80488, 174504898,
  "China", 1999, 212258, 1272915272,
  "China", 2000, 213766, 1280428583)
tidydata
```

```
## # A tibble: 6 x 4
##   country      year  cases population
##   <chr>      <dbl> <dbl>      <dbl>
## 1 Afghanistan 1999     745   19987071
## 2 Afghanistan 2000    2666   20595360
## 3 Brazil      1999   37737   172006362
## 4 Brazil      2000   80488   174504898
## 5 China       1999 212258 1272915272
## 6 China       2000 213766 1280428583
```

```
nontidydata <- tribble(
  ~country, ~year, ~rate,
  "Afghanistan", 1999, "745/19987071",
  "Afghanistan", 2000, "2666/20595360",
  "Brazil", 1999, "37737/172006362",
  "Brazil", 2000, "80488/174504898",
  "China", 1999, "212258/1272915272",
```

```
"China", 2000, "213766/1280428583")
nontidydata
```

```
## # A tibble: 6 x 3
##   country      year rate
##   <chr>        <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil       1999 37737/172006362
## 4 Brazil       2000 80488/174504898
## 5 China        1999 212258/1272915272
## 6 China        2000 213766/1280428583
```

```
nontidydata
```

```
## # A tibble: 6 x 3
##   country      year rate
##   <chr>        <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil       1999 37737/172006362
## 4 Brazil       2000 80488/174504898
## 5 China        1999 212258/1272915272
## 6 China        2000 213766/1280428583
```

```
tidieddata <- nontidydata %>%
  separate(rate, into = c("cases",
    "population"),
  sep = "/")
tidieddata
```

```
## # A tibble: 6 x 4
##   country      year cases population
##   <chr>        <dbl> <chr>    <chr>
## 1 Afghanistan 1999 745    19987071
## 2 Afghanistan 2000 2666    20595360
## 3 Brazil       1999 37737    172006362
## 4 Brazil       2000 80488    174504898
## 5 China        1999 212258    1272915272
## 6 China        2000 213766    1280428583
```

```
newtidieddata <- tidieddata %>%
  pivot_longer(
    cols = cases:population,
    names_to = "measurement",
    values_to = "value"
  )
newtidieddata
```

```
## # A tibble: 12 x 4
##   country      year measurement value
##   <chr>        <dbl> <chr>      <dbl>
```

```
##      <chr>      <dbl> <chr>      <chr>
##  1 Afghanistan  1999 cases      745
##  2 Afghanistan  1999 population 19987071
##  3 Afghanistan  2000 cases      2666
##  4 Afghanistan  2000 population 20595360
##  5 Brazil       1999 cases      37737
##  6 Brazil       1999 population 172006362
##  7 Brazil       2000 cases      80488
##  8 Brazil       2000 population 174504898
##  9 China        1999 cases      212258
## 10 China        1999 population 1272915272
## 11 China        2000 cases      213766
## 12 China        2000 population 1280428583
```

```
df <- tribble(
  ~id, ~bp1, ~bp2,
  "A", 100, 120,
  "B", 140, 115,
  "C", 120, 125
)
df
```

```
## # A tibble: 3 x 3
##   id      bp1  bp2
##   <chr> <dbl> <dbl>
## 1 A      100  120
## 2 B      140  115
## 3 C      120  125
```

```
df %>%
  pivot_longer(
    cols = bp1:bp2,
    names_to = "measurement",
    values_to = "value"
  )
```

```
## # A tibble: 6 x 3
##   id      measurement value
##   <chr> <chr>      <dbl>
## 1 A      bp1          100
## 2 A      bp2          120
## 3 B      bp1          140
## 4 B      bp2          115
## 5 C      bp1          120
## 6 C      bp2          125
```

```
newtidieddata %>%
  pivot_wider(names_from="measurement",
    values_from="value")
```

```
## # A tibble: 6 x 4
##   country      year cases population
```

```
##   <chr>          <dbl> <chr> <chr>
## 1 Afghanistan  1999 745    19987071
## 2 Afghanistan  2000 2666   20595360
## 3 Brazil       1999 37737  172006362
## 4 Brazil       2000 80488   174504898
## 5 China        1999 212258 1272915272
## 6 China        2000 213766 1280428583
```

```
newtidieddata
```

```
## # A tibble: 12 x 4
##   country      year measurement value
##   <chr>        <dbl> <chr>      <chr>
## 1 Afghanistan  1999 cases      745
## 2 Afghanistan  1999 population 19987071
## 3 Afghanistan  2000 cases      2666
## 4 Afghanistan  2000 population 20595360
## 5 Brazil       1999 cases      37737
## 6 Brazil       1999 population 172006362
## 7 Brazil       2000 cases      80488
## 8 Brazil       2000 population 174504898
## 9 China        1999 cases      212258
## 10 China       1999 population 1272915272
## 11 China       2000 cases      213766
## 12 China       2000 population 1280428583
```

```
df <- tribble(
  ~id, ~measurement, ~value,
  "A", "bp1", 100,
  "B", "bp1", 140,
  "B", "bp2", 115,
  "A", "bp2", 120,
  "A", "bp3", 105
)
df
```

```
## # A tibble: 5 x 3
##   id      measurement value
##   <chr> <chr>          <dbl>
## 1 A     bp1            100
## 2 B     bp1            140
## 3 B     bp2            115
## 4 A     bp2            120
## 5 A     bp3            105
```

```
df %>%
  pivot_wider(
    names_from = measurement,
    values_from = value
  )
```

```
## # A tibble: 2 x 4
```


```
##   id      bp1   bp2   bp3
##   <chr> <dbl> <dbl> <dbl>
## 1 A      100   120   105
## 2 B      140   115    NA
```

```
library(tidyverse)
```

```
songs <- billboard %>%
  pivot_longer(
    cols = starts_with("wk"),
    names_to = "Weeks",
    values_to = "Ranking",
    values_drop_na = TRUE,
  ) %>%
  mutate(week = parse_number(Weeks))
songs
```

```
## # A tibble: 5,307 x 6
##   artist track date.entered Weeks Ranking week
##   <chr> <chr> <date> <chr> <dbl> <dbl>
## 1 2 Pac Baby Don't Cry (Keep... 2000-02-26 wk1 87 1
## 2 2 Pac Baby Don't Cry (Keep... 2000-02-26 wk2 82 2
## 3 2 Pac Baby Don't Cry (Keep... 2000-02-26 wk3 72 3
## 4 2 Pac Baby Don't Cry (Keep... 2000-02-26 wk4 77 4
## 5 2 Pac Baby Don't Cry (Keep... 2000-02-26 wk5 87 5
## 6 2 Pac Baby Don't Cry (Keep... 2000-02-26 wk6 94 6
## 7 2 Pac Baby Don't Cry (Keep... 2000-02-26 wk7 99 7
## 8 2Ge+her The Hardest Part Of ... 2000-09-02 wk1 91 1
## 9 2Ge+her The Hardest Part Of ... 2000-09-02 wk2 87 2
## 10 2Ge+her The Hardest Part Of ... 2000-09-02 wk3 92 3
## # i 5,297 more rows
```

```
ggplot(songs) +
  aes(x=week ,y= Ranking, colour=Ranking) +
  geom_line() +
  theme_bw()
```



```
patients <- cms_patient_experience %>%
  pivot_wider(
    names_from = "measure_cd",
    values_from = "prf_rate",
    id_cols = starts_with("org")
  )
patients
```

```
## # A tibble: 95 x 8
##   org_pac_id org_nm CAHPS_GRP_1 CAHPS_GRP_2 CAHPS_GRP_3 CAHPS_GRP_5 CAHPS_GRP_8
##   <chr>      <chr>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>
## 1 0446157747 USC C~         63         87         86         57         85
## 2 0446162697 ASSOC~         59         85         83         63         88
## 3 0547164295 BEAVE~         49         NA         75         44         73
## 4 0749333730 CAPE ~         67         84         85         65         82
## 5 0840104360 ALLIA~         66         87         87         64         87
## 6 0840109864 REX H~         73         87         84         67         91
## 7 0840513552 SCL H~         58         83         76         58         78
## 8 0941545784 GRITM~         46         86         81         54         NA
## 9 1052612785 COMMU~         65         84         80         58         87
## 10 1254237779 OUR L~         61         NA         NA         65         NA
## # i 85 more rows
## # i 1 more variable: CAHPS_GRP_12 <dbl>
```