

Week 9 Code Along & Challenge

Wong Zi Xin

2023-10-16

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.2      v readr      2.1.4
## v forcats    1.0.0      v stringr   1.5.0
## v ggplot2     3.4.3      v tibble    3.2.1
## v lubridate  1.9.2      v tidyr     1.3.0
## v purrr       1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
tidydata <- tribble(
  ~country, ~year, ~cases, ~population,
  "Afghanistan", 1999, 745, 19987071,
  "Afghanistan", 2000, 2666, 20595360,
  "Brazil", 1999, 37737, 172006362,
  "Brazil", 2000, 80488, 174504898,
  "China", 1999, 212258, 1272915272,
  "China", 2000, 213766, 1280428583)
```

```
tidydata
```

```
## # A tibble: 6 x 4
##   country      year cases population
##   <chr>      <dbl> <dbl>      <dbl>
## 1 Afghanistan 1999     745  19987071
## 2 Afghanistan 2000    2666  20595360
## 3 Brazil      1999   37737  172006362
## 4 Brazil      2000   80488  174504898
## 5 China       1999 212258 1272915272
## 6 China       2000 213766 1280428583
```

```
nontidydata <- tribble(
  ~country, ~year, ~rate,
  "Afghanistan", 1999, "745/19987071",
  "Afghanistan", 2000, "2666/20595360",
  "Brazil", 1999, "37737/172006362",
  "Brazil", 2000, "80488/174504898",
```

```
"China", 1999, "212258/1272915272",
"China", 2000, "213766/1280428583")
```

nontidydata

```
## # A tibble: 6 x 3
##   country      year rate
##   <chr>      <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil      1999 37737/172006362
## 4 Brazil      2000 80488/174504898
## 5 China       1999 212258/1272915272
## 6 China       2000 213766/1280428583
```

nontidydata

```
## # A tibble: 6 x 3
##   country      year rate
##   <chr>      <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil      1999 37737/172006362
## 4 Brazil      2000 80488/174504898
## 5 China       1999 212258/1272915272
## 6 China       2000 213766/1280428583
```

```
tidieddata <- nontidydata %>%
  separate(rate, into = c("cases",
                          "population"),
            sep = "/")
```

tidieddata

```
## # A tibble: 6 x 4
##   country      year cases population
##   <chr>      <dbl> <chr>    <chr>
## 1 Afghanistan 1999 745      19987071
## 2 Afghanistan 2000 2666     20595360
## 3 Brazil      1999 37737    172006362
## 4 Brazil      2000 80488    174504898
## 5 China       1999 212258   1272915272
## 6 China       2000 213766   1280428583
```

```
newtidieddata <- tidieddata %>%
  pivot_longer(
    cols = cases:population,
    names_to = "measurement",
    values_to = "value"
  )
```

newtidieddata

```
## # A tibble: 12 x 4
##   country      year measurement value
##   <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 cases       745
## 2 Afghanistan 1999 population 19987071
## 3 Afghanistan 2000 cases       2666
## 4 Afghanistan 2000 population 20595360
## 5 Brazil      1999 cases       37737
## 6 Brazil      1999 population 172006362
## 7 Brazil      2000 cases       80488
## 8 Brazil      2000 population 174504898
## 9 China       1999 cases       212258
## 10 China      1999 population 1272915272
## 11 China      2000 cases       213766
## 12 China      2000 population 1280428583
```

```
df <- tribble(
  ~id, ~bp1, ~bp2,
  "A", 100, 120,
  "B", 140, 115,
  "C", 120, 125
)
df
```

```
## # A tibble: 3 x 3
##   id      bp1    bp2
##   <chr> <dbl> <dbl>
## 1 A      100    120
## 2 B      140    115
## 3 C      120    125
```

```
df %>%
  pivot_longer(
    cols = bp1:bp2,
    names_to = "measurement",
    values_to = "value"
  )
```

```
## # A tibble: 6 x 3
##   id      measurement value
##   <chr> <chr>      <dbl>
## 1 A      bp1          100
## 2 A      bp2          120
## 3 B      bp1          140
## 4 B      bp2          115
## 5 C      bp1          120
## 6 C      bp2          125
```

```
newtidieddata
```

```
## # A tibble: 12 x 4
##   country      year measurement value
```

```
##      <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 cases      745
## 2 Afghanistan 1999 population 19987071
## 3 Afghanistan 2000 cases      2666
## 4 Afghanistan 2000 population 20595360
## 5 Brazil      1999 cases      37737
## 6 Brazil      1999 population 172006362
## 7 Brazil      2000 cases      80488
## 8 Brazil      2000 population 174504898
## 9 China       1999 cases      212258
## 10 China      1999 population 1272915272
## 11 China      2000 cases      213766
## 12 China      2000 population 1280428583
```

```
newtidieddata %>%
  pivot_wider(names_from = "measurement",
              values_from = "value")
```

```
## # A tibble: 6 x 4
##   country      year cases population
##   <chr>      <dbl> <chr> <chr>
## 1 Afghanistan 1999 745    19987071
## 2 Afghanistan 2000 2666   20595360
## 3 Brazil      1999 37737  172006362
## 4 Brazil      2000 80488  174504898
## 5 China       1999 212258 1272915272
## 6 China       2000 213766 1280428583
```

```
df <- tribble(
  ~id, ~measurement, ~value,
  "A", "bp1", 100,
  "B", "bp1", 140,
  "B", "bp2", 115,
  "A", "bp2", 120,
  "A", "bp3", 105
)
df
```


```
## # A tibble: 5 x 3
##   id      measurement value
##   <chr> <chr>      <dbl>
## 1 A      bp1          100
## 2 B      bp1          140
## 3 B      bp2          115
## 4 A      bp2          120
## 5 A      bp3          105
```

```
df %>%
  pivot_wider(
    names_from = measurement,
    values_from = value
  )
```

```
## # A tibble: 2 x 4
##   id      bp1    bp2    bp3
##   <chr> <dbl> <dbl> <dbl>
## 1 A      100    120    105
## 2 B      140    115     NA
```

```
billboard_dataset <- billboard %>%
  pivot_longer(cols = starts_with("wk"),
               names_to = "week",
               values_to = "rank",
               values_drop_na = TRUE) %>%
  mutate(week = parse_number(week))

ggplot(billboard_dataset, aes(x = week, y = rank)) +
  geom_line() +
  labs(x = "Week", y = "Rank") +
  theme_minimal()
```



```
patient_exp <- cms_patient_experience %>%
  pivot_wider(
    id_cols = starts_with("org"),
    names_from = measure_cd,
    values_from = prf_rate
  )

patient_exp
```

```
## # A tibble: 95 x 8
##   org_pac_id org_nm CAHPS_GRP_1 CAHPS_GRP_2 CAHPS_GRP_3 CAHPS_GRP_5 CAHPS_GRP_8
##   <chr>      <chr>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>
## 1 0446157747 USC C~          63          87          86          57          85
## 2 0446162697 ASSOC~          59          85          83          63          88
## 3 0547164295 BEAVE~          49          NA          75          44          73
## 4 0749333730 CAPE ~          67          84          85          65          82
## 5 0840104360 ALLIA~          66          87          87          64          87
## 6 0840109864 REX H~          73          87          84          67          91
## 7 0840513552 SCL H~          58          83          76          58          78
## 8 0941545784 GRITM~          46          86          81          54          NA
## 9 1052612785 COMMU~          65          84          80          58          87
## 10 1254237779 OUR L~          61          NA          NA          65          NA
## # i 85 more rows
## # i 1 more variable: CAHPS_GRP_12 <dbl>
```