


DRAWING NUMBER: MD-216-3100-EG-CV-DED-2024 | REV: D01




SECTION 1-1
(SCALE-1:50)




SECTION 2-2
(SCALE-1:50)




SECTION 3-3
(SCALE-1:50)




SECTION 4-4
(SCALE-1:50)




SECTION 5-5
(SCALE-1:50)




R.C. DETAIL OF PEDESTAL MKD. PD3
(1 NO. REQUIRED)
(SCALE- 1:50)




R.C. DETAIL OF PEDESTAL MKD. PD4
(1 NO. REQUIRED)
(SCALE- 1:50)




R.C. DETAIL OF PEDESTAL MKD. PF1
(1 NO. REQUIRED)
(SCALE- 1:50)




R.C. DETAIL OF FOUNDATION MKD. F1
(1 NO. REQUIRED)
(SCALE- 1:50)




R.C. DETAIL OF FOUNDATION MKD. CF1
(1 NO. REQUIRED)
(SCALE- 1:50)




R.C. DETAIL OF
PEDESTAL MKD. PD1
(2 NOS. REQUIRED)
(SCALE- 1:20)




R.C. DETAIL OF
PEDESTAL MKD. PD2
(1 NO. REQUIRED)
(SCALE- 1:20)



TYP. DET. OF 150 THK. GRADE SLAB
(SCALE - 1:10)



TYP. CROSS SECTION OF
GRADE BEAM
(GRADE SLAB REIN. NOT SHOWN FOR CLARITY)
(SCALE- 1:25)



R.C. DETAIL OF SECTION 7-7
(REFER DRG. NO. MD-216-3100-EG-CV-GAD-2025)
(SCALE-1:20)

LEGENDS :-

R.L. - REDUCED LEVEL
FDN. - FOUNDATION.
T.O.C. - TOP OF CONCRETE.
F.G.L. - FINISHED GROUND LEVEL.
F.F.L. - FINISHED FLOOR LEVEL.
B.O.F. - BOTTOM OF FOUNDATION
TYP. - TYPICAL.
R.C. - REINFORCED CONCRETE
P.C.C - PLAIN CEMENT CONCRETE
MKD. - MARKED.
THK. - THICK
B/W - BOTH WAYS
Ld - DEVELOPMENT LENGTH
BOTTOM REINFORCEMENT (B) - ———
TOP REINFORCEMENT (T) - – – – – – –
ALTH - ALLTHROUGH
B/F - BOTHFACE
REIN. - REINFORCEMENT
PD - PEDESTAL FOR DUCT SUPPORT
PF - PEDESTAL FOR FAN

NOTES :-

1. ALL DIMENSIONS ARE IN MILLIMETRES AND LEVELS AND CO-ORDINATES ARE IN METRES. UNLESS OTHERWISE STATED.
2. GRADE OF CONCRETE SHALL BE C35 FOR FOUNDATION.
3. GRADE OF REINFORCEMENT SHALL BE DEFORMED BAR ASTM A615 - GRADE 60 (fy = 420 MPa).
4. NET SAFE BEARING CAPACITY OF SOIL AT BOTTOM OF FOUNDATION CONSIDERED 500KN/ SQ. M.
5. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE AS
   a) FOUNDATION = 75 mm (BOTTOM & SIDE) 50 mm. (TOP)
   b) COLUMN & PEDESTAL = 50mm
   c) BEAM = 50mm
   d) SLAB = 40mm
6. FOR MINIMUM LAP LENGTH OF REINFORCEMENT AND OTHER GENERAL NOTES FOR CIVIL WORKS REFER STANDARD DRG : MD-216-1000-EG-CV-DED-1001
7. READ THIS DRAWING IN CONJUNCTION WITH DRG: MD-216-3100-EG-CV-GAD-2023, 2024 & 2025
8. FOR OTHER STANDARD REINFORCEMENT DETAILS REFER DRG : MD-216-1000-EG-CV-DED-1005

DOCUMENT NUMBER	REFERENCE DOCUMENTS	REV	DATE	REVISION DESCRIPTION	DRN	CHK	ENG	APP	EMP
		D01	10/03/2023	AS-BUILT	JKM	SBY	APL	PRI	
		C01	11/01/2021	ISSUED FOR CONSTRUCTION	JKM	SBY	APL	PRI	
		A02	26/11/2020	REVISED AS PER EMPLOYER COMMENTS DATED 21/10/2020 AND ISSUED FOR REVIEW & REVISED AS MARKED A02	JKM	SBY	APL	PRI	
MD-216-3100-EG-CV-GAD-2025	LAYOUT OF FAN AND DUCT SUPPORT FOUNDATION	A01	24/09/2020	ISSUED FOR REFERENCE	JKM	SBY	APL	PRI	

RESERVED FOR VENDOR LOGO AND DRAWING NUMBER

LARSEN & TOUBRO

This drawing is the property of LARSEN & TOUBRO and must not be passed on to any person or body not authorized by us to receive it nor be copied or otherwise made use either in full or in part by such person or body without our prior permission in writing.

Outotec

The content of these documents are the sole property of Outotec Oyj. Any rights not expressly granted herein are reserved. Reproduction, transfer or distribution of part or all of the contents in any form without prior written permission of Outotec is prohibited.

MA'ADEN معادن
Saudi Arabian Mining Company شركة معادن العربية السعودية

This document and the information contained herein is Ma'aden proprietary know-how. This document or any part thereof should not be reproduced, stored in a retrieval system or transmitted by any means, electronic or otherwise, or divulged without prior written permission of Ma'aden.

LARSEN & TOUBRO DRAWING NUMBER: 019045_080_C_D_24367_005 | REVISION: 3
OUTOTEC DRAWING NUMBER: 900707__GAU01__ZC01__CTB17__31016 | DOCUMENT ID: OU100692097 | REVISION: 3

DRAWN	JKM	22/09/2020
CHECKED	SBY	23/09/2020
ENGINEER	APL	21/09/2020
APPROVED	PRI	24/09/2020
EMPLOYER		
SCALE	1:50,20	A1

MANSOURAH - MASSARAH GOLD PROJECT
DETAIL DRAWING
CRUSHING
RC DETAIL OF FAN AND DUCT SUPPORT FOUNDATION

DRAWING NUMBER: MD-216-3100-EG-CV-DED-2024 | REV: D01