

Unit 118 - Field Data Review

Mohawk Valley West Slope demonstration. Method **Tractor**, 70.2 ac, BAF 20 variable-radius cruise on a 300 ft grid, 34 plots, 374 trees tallied. Simulated data with planted recording errors; see docs/methods.md.

Table 1. Stand summary from the BAF 20 cruise, per acre

STAND DENSITY		STAND INFO	
Basal area	220 sq ft/ac (1 SE of mean, BA 3.2 %)	Type	Sierran mixed conifer
Trees per acre	76	CWHR size / density	4 / D (cover 91 %)
QMD	23.1 in	SDI	278 (47 % of max 595)
SAWTIMBER (>= 10 in)		BIOMASS (< 10 in)	
BA QMD	219 sq ft/ac 23.4 in	BA QMD	1 sq ft/ac 8.7 in
TPA	73	TPA	3
Volume	36.0 MBF/ac (7180 cu ft)	Volume	0.6 green tons/ac (26 cu ft)
TREATMENT TARGET		CRUISE DESIGN	
Leave	35 % of max SDI = ~165 sq ft/ac BA	Sampling error (volume)	7.1 % at 95 % (CV 20 %, t = 2.03, n = 34)
Species (BA)	WF 76, PP 59, DF 38, IC 35, SP 13	Stratum standard	40 % of volume - MEETS; plots for standard: 2
		Sampling error (basal area)	6.4 % at 95 % (CV 18 %); secondary, not the standard
		Plot count	34 vs 20-plot local practice, not a handbook standard: ok

Cubic volume = total-stem CVTS by species (PNW-FIA California equations, MacLean and Berger 1976, CARB 2011 compendium) net of defect; Scribner board feet at 5.02 bf/cu ft (Keegan et al. 2010, table 2, California 2000-2006); green tons at PP 45, WF 47, DF 38, SP 49, IC 45 lb/cu ft of wood (Miles and Smith 2009, NRS-38 table 1A). SDI in the summation form; maximum is the basal-area-weighted FVS Western Sierra species maximum (table 3.5.1, rev. 2025-09-23). The Keegan ratio is Scribner log scale per cubic foot of delivered sawlog fiber, so applied to total-stem CVTS it overstates sawlog volume; merchantable cubic volume would be the consistent pairing. Sampling error at 95 % confidence with Student's t on plot net cubic volume per acre, the quantity the handbook standards apply to (FSH 2409.12 ch. 40, 41.1(5)(a) and (b)); stratum standard 40 % of volume for tree-measurement sales; the basal-area error is secondary. Stand-summary BA counts every tallied tree (plot count x BAF); the stand and stock tables exclude records flagged by QA, such as an out-of-range DBH, so the two can differ by a few tenths. Sources and URLs: cruise_data.xlsx, Standards and assumptions.

Table 2. Stand table by 4-inch DBH class, per acre

DBH class, in	Trees	TPA	BA	cu ft	MBF
8-11.9	7	6.9	4.1	98	0.5
12-15.9	29	14.9	17.1	419	2.1
16-19.9	42	13.8	24.7	694	3.5
20-23.9	73	16.5	42.9	1233	6.2
24-27.9	67	10.7	39.4	1283	6.4
28-31.9	43	5.2	25.3	869	4.4
32-35.9	35	3.4	20.6	710	3.6
36-39.9	28	2.1	16.5	618	3.1
40-43.9	11	0.7	6.5	272	1.4
44-47.9	19	1.0	11.2	478	2.4
48-51.9	6	0.3	3.5	144	0.7
52-55.9	3	0.1	1.8	80	0.4
56-59.9	4	0.1	2.4	111	0.6
60-63.9	7	0.2	4.1	199	1.0
All	374	75.9	220.0	7206	36.2

Table 3. Stock table by species, per acre

Species	Trees	TPA	BA	QMD	cu ft	MBF
WF	129	29.5	75.9	21.7	2445	12.3
PP	100	21.6	58.8	22.4	2131	10.7
DF	64	11.7	37.6	24.3	1210	6.1
IC	59	9.4	34.7	26.0	978	4.9
SP	22	3.7	12.9	25.5	442	2.2
All	374	75.9	220.0	23.1	7206	36.2

Trees = trees tallied in the cruise; TPA, BA (sq ft/ac), cubic feet and Scribner MBF per acre by BAF expansion. Species: PP ponderosa pine, WF white fir, DF Douglas-fir, SP sugar pine, IC incense-cedar.

Unit 118: plots on the 300 ft grid (orange = QA flag)




Figure 1. Plot locations with QA status.

QA findings: no issues found; unit accepted

Table 4. Plot list

Plot	Trees in	BA sq ft/ac	Slope %	Status
118-01	12	240	17	ok
118-02	10	200	15	ok
118-03	12	240	12	ok
118-04	9	180	3	ok
118-05	15	300	16	ok
118-06	12	240	15	ok
118-07	11	220	13	ok
118-08	11	220	27	ok
118-09	10	200	17	ok
118-10	5	100	27	ok
118-11	10	200	22	ok
118-12	13	260	22	ok
118-13	12	240	18	ok
118-14	12	240	14	ok
118-15	11	220	15	ok
118-16	8	160	15	ok
118-17	12	240	17	ok
118-18	11	220	15	ok
118-19	11	220	8	ok
118-20	7	140	8	ok
118-21	13	260	15	ok
118-22	8	160	17	ok
118-23	11	220	15	ok
118-24	13	260	14	ok
118-25	10	200	9	ok
118-26	11	220	9	ok
118-27	10	200	5	ok
118-28	15	300	10	ok
118-29	13	260	9	ok
118-30	11	220	12	ok
118-31	12	240	9	ok
118-32	10	200	12	ok
118-33	12	240	18	ok
118-34	11	220	9	ok