

Unit 115 Field Data Review

Mohawk Valley West Slope demonstration. **Tractor** unit, 84.0 ac. 39 plots, BAF 20, variable-radius cruise on a 300 ft grid, 444 trees tallied. Simulated data with planted recording errors; see docs/methods.md.

TABLE 1. STAND SUMMARY, BAF 20 CRUISE, PER ACRE

STAND DENSITY		STAND INFO	
Basal area	228 sq ft/ac (1 SE of mean, BA 2.0 %)	Type	Sierran mixed conifer
Trees per acre	87	CWHR size / density	4 / D (cover 92 %)
QMD	21.9 in	SDI	292 (51 % of max 578)
SAWTIMBER (>= 10 in)		BIOMASS (< 10 in)	
BA QMD	227 sq ft/ac 22.2 in	BA QMD	1 sq ft/ac 8.2 in
TPA	85	TPA	3
Volume	35.7 MBF/ac (7114 cu ft)	Volume	0.4 green tons/ac (18 cu ft)
TREATMENT TARGET		CRUISE DESIGN	
Leave	35 % of max SDI, about 158 sq ft/ac	BA Sampling error (volume)	8.1 % at 95 % (CV 25 %, t = 2.02, n = 39)
Species (BA)	WF 68, PP 67, IC 34, DF 33, SP 26	Stratum standard	40 % of volume, MEETS; plots for standard 2
		Sampling error (basal area)	4.0 % at 95 % (CV 12 %); reference, not the standard
		Plot count	39; 20-plot local practice, not a handbook standard: ok

Cubic volume is total-stem CVTS by species (PNW-FIA California equations, MacLean and Berger 1976, CARB 2011 compendium), net of defect. Scribner board feet at 5.02 bf/cu ft (Keegan et al. 2010, table 2, California 2000-2006). Green tons at PP 45, WF 47, DF 38, SP 49, IC 45 lb/cu ft of wood (Miles and Smith 2009, NRS-38 table 1A). SDI in the summation form; maximum is the basal-area-weighted FVS Western Sierra species maximum (table 3.5.1, rev. 2025-09-23). The Keegan ratio is Scribner log scale per cubic foot of delivered sawlog fiber; applied to total-stem CVTS it overstates sawlog volume. Merchantable cubic volume is the consistent pairing. Sampling error at 95 % confidence, Student's t, on plot net cubic volume per acre, the quantity the handbook standards test (FSH 2409.12 ch. 40, 41.1(5)(a) and (b)); stratum standard 40 % of volume for tree-measurement sales. The basal-area error is reference only. Stand-summary BA counts every tallied tree (plot count x BAF); the stand and stock tables drop records flagged by QA, such as an out-of-range DBH, so the two can differ by a few tenths. Sources and URLs: [cruise_data.xlsx](#), Standards and assumptions.

TABLE 2. STAND TABLE BY 4-INCH DBH CLASS, PER ACRE

DBH class, in	Trees	TPA	BA	cu ft	MBF
4-7.9	1	1.8	0.5	9	0.0
8-11.9	11	8.8	5.6	114	0.6
12-15.9	43	20.2	22.1	513	2.6
16-19.9	64	18.7	32.8	794	4.0
20-23.9	73	14.2	37.4	1068	5.4
24-27.9	68	9.8	34.9	1110	5.6
28-31.9	51	5.4	26.2	883	4.4
32-35.9	48	3.9	24.6	889	4.5
36-39.9	31	2.1	15.9	593	3.0
40-43.9	22	1.2	11.3	437	2.2
44-47.9	15	0.7	7.7	312	1.6
48-51.9	9	0.3	4.6	211	1.1
52-55.9	5	0.2	2.6	112	0.6
60-63.9	3	0.1	1.5	88	0.4
All	444	87.3	227.7	7132	35.8

TABLE 3. STOCK TABLE BY SPECIES, PER ACRE

Species	Trees	TPA	BA	QMD	cu ft	MBF
WF	132	24.4	67.7	22.6	2139	10.7
PP	130	24.9	66.7	22.2	2313	11.6
IC	66	14.5	33.8	20.7	839	4.2
DF	65	12.4	33.3	22.2	1045	5.2
SP	51	11.2	26.2	20.7	795	4.0
All	444	87.3	227.7	21.9	7132	35.8

Trees: tally trees. TPA, BA (sq ft/ac), cubic feet and Scribner MBF per acre by BAF expansion. Species codes: PP ponderosa pine, WF white fir, DF Douglas-fir, SP sugar pine, IC incense-cedar.

Unit 115 plots, 300 ft grid (orange: QA flag)




Figure 1. Plot locations with QA status.

QA findings: none; unit accepted

TABLE 4. PLOT LIST

Plot	Trees in	BA sq ft/ac	Slope %	Status
115-01	13	260	21	ok
115-02	10	200	12	ok
115-03	8	160	10	ok
115-04	12	240	20	ok
115-05	12	240	26	ok
115-06	12	240	17	ok
115-07	11	220	24	ok
115-08	11	220	13	ok
115-09	11	220	16	ok
115-10	9	180	30	ok
115-11	12	240	4	ok
115-12	12	240	12	ok
115-13	10	200	15	ok
115-14	10	200	10	ok
115-15	12	240	19	ok
115-16	9	180	24	ok
115-17	11	220	27	ok
115-18	11	220	9	ok
115-19	8	160	10	ok
115-20	11	220	7	ok
115-21	11	220	17	ok
115-22	14	280	16	ok
115-23	12	240	18	ok
115-24	12	240	15	ok
115-25	12	240	15	ok
115-26	10	200	6	ok
115-27	12	240	8	ok
115-28	12	240	13	ok
115-29	12	240	8	ok
115-30	11	220	17	ok
115-31	12	240	14	ok
115-32	12	240	5	ok
115-33	12	240	7	ok
115-34	12	240	5	ok
115-35	13	260	6	ok
115-36	15	300	3	ok
115-37	11	220	4	ok
115-38	12	240	15	ok
115-39	12	240	4	ok