Extend functionality with bundles

Service/parameter overriding

- Define service/parameter with the same name
- Only the latest definition is used

https://github.com/oroinc/platform/blob/3.1/src/Oro/Bundle/EntityBundle/Resources/config/services.yml#L2-L7

Demonstration code, e.g. in customization >>>

Service decoration

- Decorates original service
- Can inject original service into decorator
- Most of the time, the decorator should be declared private

https://github.com/oroinc/orocommerce/blob/3.1/src/Oro/Bundle/WebsiteSearchBundle/Resources/config/services.yml#L108-L114

Compiler passes

- Dynamic manipulations with services and parameters
- Allows to add custom logic during the compilation of DIC
- Examples
 - Add method call
 - Change class

Bundle inheritance

- Allows to override parts where bundle based paths are used (e.g. @OroUserBundle)
 - Routing
 - Controllers
 - Templates
- Each bundle may have only one parent bundle

[Documentation]

Overriding at the application level

- Allows to override parts where bundle based paths are used (e.g. @OroUserBundle)
 - Routing
 - Controllers
 - Templates
- All custom files have to be at the src/Resources/<bundle> directory

[Documentation]

Routes overriding

- Define routes with the same name
- The latest route wins
- Might be used to override controllers

Template inheritance

- Uses {% extends %} tag
- Allows to redefine or extend blocks
- parent()

{% extends 'OroUIBundle:actions:update.html.twig' %}

https://github.com/oroinc/platform/blob/3.1/src/Oro/Bundle/UserBundle/Resources/views/User/view.html.twig

Template placeholders

- New twig token parser
 - extends \Twig_TokenParser
- Uses {% placeholder %} tag
- Allows to inject required blocks at the defined positions (similar to events)

https://github.com/oroinc/platform/blob/3.1/src/Oro/Bundle/U IBundle/Resources/views/actions/view.html.twig#L47-L54

https://github.com/oroinc/platform/blob/3.1/src/Oro/Bundle/DataAuditBundle/Resources/config/oro/placeholders.yml

Twig extensions

- Filters
 - o 'label'|trans
- Functions
 - oro_currency_name(currency)
- Tests
 - o value is defined
- Operators
 - o value == value
- Globals

https://github.com/oroinc/platform/blob/3.1/src/Oro/Bundle/EntityBundle/Twig/EntityExtension.php

Form extensions

- Add features on top of existing types
 - Add specific feature to a single type
 - Add generic feature to several types
- Cases
 - Add new fields to forms
 - Process submitted data
 - Modify existing form behaviour

[Symfony documentation]

Configuration files

- config/config.yml
- <bundle>/Resources/config/oro/app.yml
- php bin/console debug:config --help

https://github.com/oroinc/orocommerce-application/blob/3.1/config/config.yml#L37-L43

https://github.com/oroinc/orocommerce/blob/3.1/src/Oro/Bundle/CMSBundle/Resources/config/oro/app.yml

Events

- Presented in all components
- Allow to change data or behaviour
- ORO Events, eg. Datagrid, Import, UI
 - o <bundle>/Event
- Doctrine Events, eg. Lifecycle
- Symfony Events, eg. Form

https://github.com/oroinc/platform/blob/3.1/src/Oro/Bundle/DataGridBundle/Datagrid/Builder.php#L112-L113