충전소 예약 API (v1.0)

Download OpenAPI specification: Download

전기차 충전소 예약 관리 시스템

문의 API

1:1 문의 작성 / 조회 / 수정 / 삭제 API

본인 문의 목록 조회

memberId 로 본인이 작성한 문의 목록을 조회합니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

memberId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

```
Array [
```

inquiryId	integer <int64>
memberId	integer <int64>
statId	string
chargerId	string

category	string
title	string
content	string
status	string
answerContent	string
answerAt	string <date-time>
insertTime	string <date-time>

]

GET /api/inquiries

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
        "inquiryId": 0,
        "memberId": 0,
        "statId": "string",
        "chargerId": "string",
        "category": "string",
        "title": "string",
        "content": "string",
        "status": "string",
        "answerContent": "string",
        "answerAt": "2019-08-24T14:15:22Z",
        "insertTime": "2019-08-24T14:15:22Z"
    }
]
```

문의 작성

새로운 1:1 문의를 작성합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

inquiryId	integer <int64>
memberId	integer <int64>
statId	string
chargerId	string
category	string
title	string
content	string
status	string
answerContent	string

answerAt	string <date-time>
insertTime	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

inquiryId	integer <int64>
memberId	integer <int64>
statId	string
chargerId	string
category	string
title	string
content	string
status	string
answerContent	string
answerAt	string <date-time>
insertTime	string <date-time>

POST /api/inquiries

Request samples

Payload

Content type
application/json

Copy

```
{
    "inquiryId": 0,
    "memberId": 0,
    "statId": "string",
    "chargerId": "string",
    "category": "string",
    "title": "string",
    "content": "string",
    "status": "string",
    "answerContent": "string",
    "answerAt": "2019-08-24T14:15:22Z",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "inquiryId": 0,
    "memberId": 0,
    "statId": "string",
    "chargerId": "string",
    "category": "string",
    "title": "string",
    "content": "string",
    "status": "string",
    "answerContent": "string",
    "answerAt": "2019-08-24T14:15:22Z",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

본인 문의 상세 조회

inquiryId 와 memberId 로 본인 문의 상세 내용을 조회합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

inquiryId required	integer <int64>

QUERY PARAMETERS

memberId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

inquiryId	integer <int64>
memberId	integer <int64>
statId	string
chargerId	string
category	string
title	string
content	string
status	string
answerContent	string
answerAt	string <date-time>
insertTime	string <date-time>

GET /api/inquiries/{inquiryId}

Response samples

200

Content type
application/json

Copy


```
{
    "inquiryId": 0,
    "memberId": 0,
    "statId": "string",
    "chargerId": "string",
    "category": "string",
    "title": "string",
    "content": "string",
    "status": "string",
    "answerContent": "string",
    "answerAt": "2019-08-24T14:15:22Z",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

문의 삭제

PENDING 상태인 문의만 삭제 가능합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

inquiryId required	integer <int64>

QUERY PARAMETERS

memberId required	integer <int64>

Responses

— **200** OK

DELETE /api/inquiries/{inquiryId}

문의 수정

PENDING 상태인 문의만 수정 가능합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

inquiryId required	integer <int64>

QUERY PARAMETERS

memberId required	integer <int64>

REQUEST BODY SCHEMA: application/json
required

inquiryId	integer <int64>
memberId	integer <int64>
statId	string
chargerId	string
category	string
title	string
content	string

status	string
answerContent	string
answerAt	string <date-time>
insertTime	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

inquiryId	integer <int64>
memberId	integer <int64>
statId	string
chargerId	string
category	string
title	string
content	string
status	string
answerContent	string
answerAt	string <date-time>
insertTime	string <date-time>

PATCH /api/inquiries/{inquiryId}

Request samples

Payload

Content type
application/json

Copy

```
{
    "inquiryId": 0,
    "memberId": 0,
    "statId": "string",
    "chargerId": "string",
    "category": "string",
    "title": "string",
    "content": "string",
    "status": "string",
    "answerContent": "string",
    "answerAt": "2019-08-24T14:15:22Z",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "inquiryId": 0,
    "memberId": 0,
    "statId": "string",
    "chargerId": "string",
    "category": "string",
    "title": "string",
    "content": "string",
    "status": "string",
    "answerContent": "string",
    "answerAt": "2019-08-24T14:15:22Z",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

충전소 API

충전소 조회 / 검색 / 마커 / 통계 API

충전소 상세 조회

statId 로 특정 충전소의 상세 정보 / 실시간 현황 / 요금 정보를 반환합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

statId required	string

QUERY PARAMETERS

userLat	number <double>
userLng	number <double>

Responses

200 OK

RESPONSE SCHEMA: application/json

statId	string
statNm	string
addr	string
bnm	string
location	string
useTime	string

lat	number <double>
lng	number <double>
distance	number <double>
availableCount	integer <int32>
totalCount	integer <int32>
brokenCount	integer <int32>
occupancy	string
lastUpdated	string
statSummary	string
markerColor	string
warningLevel	string
fastChargerStatus	string
slowChargerStatus	string
limitYn	string
parkingFree	string
limitDetail	string
parkingInfo	string
openStatus	string
currentPrice	number <double>
lastYearPrice	number <double>
priceDiff	number <double>
slowPrice	number <double>
slowLastYearPrice	number <double>
slowPriceDiff	number <double>

season	string
chargers >	Array of objects (ChargerDto)
priceDetail >	object (ChargerPriceDto)
priceDisplayText	string

GET /api/stations/{statId}

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
{
  "statId": "string",
  "statNm": "string",
  "addr": "string",
  "bnm": "string",
  "location": "string",
  "useTime": "string",
  "lat": 0.1,
  "lng": 0.1,
  "distance": 0.1,
  "availableCount": 0,
  "totalCount": 0,
  "brokenCount": 0,
  "occupancy": "string",
  "lastUpdated": "string",
  "statSummary": "string",
  "markerColor": "string",
  "warningLevel": "string",
  "fastChargerStatus": "string",
  "slowChargerStatus": "string",
  "limitYn": "string",
  "parkingFree": "string",
  "limitDetail": "string",
```

```
    "parkingInfo": "string",
    "openStatus": "string",
    "currentPrice": 0.1,
    "lastYearPrice": 0.1,
    "priceDiff": 0.1,
    "slowPrice": 0.1,
    "slowLastYearPrice": 0.1,
    "slowPriceDiff": 0.1,
    "season": "string",
  - "chargers": [
      + { … }
    ],
  - "priceDetail": {
        "priceId": 0,
        "bnm": "string",
        "speedType": "string",
        "applyYear": 0,
        "season": "string",
        "unitPrice": 0.1,
        "remark": "string",
        "lastYearPrice": 0.1,
        "diff": 0.1,
        "trendMessage": "string",
        "updateDt": "2019-08-24T14:15:22Z"
    },
    "priceDisplayText": "string"
}
```

메인페이지 통계 조회

총 충전소 수 / 총 충전기 수 / 가용 충전기 수를 반환합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

totalStations	integer <int64>
totalChargers	integer <int64>
availableChargers	integer <int64>
chargingCount	integer <int64>
reservedCount	integer <int64>

GET /api/stations/stats

Response samples

200

Content type
application/json

Copy

```
{
    "totalStations": 0,
    "totalChargers": 0,
    "availableChargers": 0,
    "chargingCount": 0,
    "reservedCount": 0
}
```

충전소 검색

키워드와 현재 위치로 주변 충전소를 검색합니다 (작년 요금 비교 포함)

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

lat required	number <double>

lng required	number <double>
keyword	string

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

statId	string
statNm	string
addr	string
bnm	string
location	string
useTime	string
lat	number <double>
lng	number <double>
distance	number <double>
availableCount	integer <int32>
totalCount	integer <int32>
brokenCount	integer <int32>
occupancy	string
lastUpdated	string
statSummary	string
markerColor	string

warningLevel	string
fastChargerStatus	string
slowChargerStatus	string
limitYn	string
parkingFree	string
limitDetail	string
parkingInfo	string
openStatus	string
currentPrice	number <double>
lastYearPrice	number <double>
priceDiff	number <double>
slowPrice	number <double>
slowLastYearPrice	number <double>
slowPriceDiff	number <double>
season	string
chargers >	Array of objects (ChargerDto)
priceDetail >	object (ChargerPriceDto)
priceDisplayText	string

]

GET /api/stations/search

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "statId": "string",
      "statNm": "string",
      "addr": "string",
      "bnm": "string",
      "location": "string",
      "useTime": "string",
      "lat": 0.1,
      "lng": 0.1,
      "distance": 0.1,
      "availableCount": 0,
      "totalCount": 0,
      "brokenCount": 0,
      "occupancy": "string",
      "lastUpdated": "string",
      "statSummary": "string",
      "markerColor": "string",
      "warningLevel": "string",
      "fastChargerStatus": "string",
      "slowChargerStatus": "string",
      "limitYn": "string",
      "parkingFree": "string",
      "limitDetail": "string",
      "parkingInfo": "string",
      "openStatus": "string",
      "currentPrice": 0.1,
      "lastYearPrice": 0.1,
      "priceDiff": 0.1,
      "slowPrice": 0.1,
      "slowLastYearPrice": 0.1,
      "slowPriceDiff": 0.1,
      "season": "string",
    + "chargers": [ … ],
    + "priceDetail": { … },
      "priceDisplayText": "string"
    }
]
```

지도 마커 조회

위도/경도 기준 반경 1.5km 이내 충전소 마커 정보를 반환합니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

lat required	number <double>
lng required	number <double>

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

statId	string
statNm	string
lat	number <double>
lng	number <double>
occupancy	string
markerColor	string
warningLevel	string
availabilityRate	number <double>

]

GET /api/stations/markers

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
        "statId": "string",
        "statNm": "string",
        "lat": 0.1,
        "lng": 0.1,
        "occupancy": "string",
        "markerColor": "string",
        "warningLevel": "string",
        "availabilityRate": 0.1
    }
]
```

주변 충전소 목록 조회

위도/경도 기준 반경 1.5km 이내 충전소 100개를 반환합니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

lat required	number <double>
lng required	number <double>
page	integer <int32> Default: 0
type	string

Default: `"급속"`

Responses

200 OK

RESPONSE SCHEMA: application/json

```
Array [
```

statId	string
statNm	string
addr	string
bnm	string
location	string
useTime	string
lat	number <double>
lng	number <double>
distance	number <double>
availableCount	integer <int32>
totalCount	integer <int32>
brokenCount	integer <int32>
occupancy	string
lastUpdated	string
statSummary	string
markerColor	string
warningLevel	string
fastChargerStatus	string

slowChargerStatus	string
limitYn	string
parkingFree	string
limitDetail	string
parkingInfo	string
openStatus	string
currentPrice	number <double>
lastYearPrice	number <double>
priceDiff	number <double>
slowPrice	number <double>
slowLastYearPrice	number <double>
slowPriceDiff	number <double>
season	string
chargers >	Array of objects (ChargerDto)
priceDetail >	object (ChargerPriceDto)
priceDisplayText	string

]

GET /api/stations/around

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
      "statId": "string",
      "statNm": "string",
      "addr": "string",
      "bnm": "string",
      "location": "string",
      "useTime": "string",
      "lat": 0.1,
      "lng": 0.1,
      "distance": 0.1,
      "availableCount": 0,
      "totalCount": 0,
      "brokenCount": 0,
      "occupancy": "string",
      "lastUpdated": "string",
      "statSummary": "string",
      "markerColor": "string",
      "warningLevel": "string",
      "fastChargerStatus": "string",
      "slowChargerStatus": "string",
      "limitYn": "string",
      "parkingFree": "string",
      "limitDetail": "string",
      "parkingInfo": "string",
      "openStatus": "string",
      "currentPrice": 0.1,
      "lastYearPrice": 0.1,
      "priceDiff": 0.1,
      "slowPrice": 0.1,
      "slowLastYearPrice": 0.1,
      "slowPriceDiff": 0.1,
      "season": "string",
    + "chargers": [ … ],
    + "priceDetail": { … },
      "priceDisplayText": "string"
    }
]
```

충전기 API

충전기 조회 API

충전소별 충전기 목록 조회

충전소 ID(statId)로 해당 충전소의 충전기 목록을 조회합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

statId required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

statNm	string
createdAt	string
updatedAt	string
chargerTypeNm	string
chargerName	string
address	string
status	string
fast	boolean

statId	string
chgerId	string
chgerType	string
stat	string
statUpdDt	string
output	integer <int32>
method	string
lastTsdt	string
lastTedt	string
nowTsdt	string

]

GET /api/chargers/station/{statId}

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
        "statNm": "string",
        "createdAt": "string",
        "updatedAt": "string",
        "chargerTypeNm": "string",
        "chargerName": "string",
        "address": "string",
        "status": "string",
        "fast": true,
        "statId": "string",
        "chgerId": "string",
        "chgerType": "string",
        "stat": "string",
        "statUpdDt": "string",
        "output": 0,
        "method": "string",
        "lastTsdt": "string",
        "lastTedt": "string",
        "nowTsdt": "string"
    }
]
```

이메일 API

회원가입 이메일 인증 API

인증번호 확인

발송된 인증번호가 일치하는지 검증합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

email	string non-empty

authCode string non-empty \d{6}

Responses

200 OK

RESPONSE SCHEMA: application/json

string

POST /api/email/verify

Request samples

Payload

Content type
application/json

Copy

```
{
    "email": "string",
    "authCode": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
"string"
```

인증번호 발송

입력한 이메일로 6자리 인증번호를 발송합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

email	string	non-empty

Responses

200 OK

RESPONSE SCHEMA: application/json

string

POST /api/email/send

Request samples

Payload

Content type
application/json

Copy

```
{
    "email": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
"string"
```

회원 API

회원가입 / 로그인 / 로그아웃 / 회원정보 조회 및 수정 API

내 정보 조회

현재 로그인한 회원의 정보를 조회합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

memberId	integer <int64>
loginId	string
loginPw	string
email	string
name	string
phone	string
status	string

memberGrade	string
provider	string
providerId	string
penaltyCount	integer <int32>
suspendedUntil	string <date-time>

GET /api/member/me

Response samples

200

Content type
application/json

Copy

```
{
    "memberId": 0,
    "loginId": "string",
    "loginPw": "string",
    "email": "string",
    "name": "string",
    "phone": "string",
    "status": "string",
    "memberGrade": "string",
    "provider": "string",
    "providerId": "string",
    "penaltyCount": 0,
    "suspendedUntil": "2019-08-24T14:15:22Z"
}
```

회원 정보 수정

이름, 전화번호, 비밀번호를 수정합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

memberId	integer <int64>
loginId	string
loginPw	string
email	string
name	string
phone	string
status	string
memberGrade	string
provider	string
providerId	string
penaltyCount	integer <int32>
suspendedUntil	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

string

PUT /api/member/me

Request samples

Payload

Content type
application/json

Copy

```
{
    "memberId": 0,
    "loginId": "string",
    "loginPw": "string",
    "email": "string",
    "name": "string",
    "phone": "string",
    "status": "string",
    "memberGrade": "string",
    "provider": "string",
    "providerId": "string",
    "penaltyCount": 0,
    "suspendedUntil": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
"string"
```

회원 탈퇴

현재 로그인한 회원을 탈퇴 처리합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

string

DELETE /api/member/me

Response samples

200

Content type
application/json

Copy

```
"string"
```

토큰 재발급

AccessToken 만료 시 RefreshToken 쿠키로 새 AccessToken 을 발급합니다

AUTHORIZATIONS: > *bearerAuth*

COOKIE PARAMETERS

refreshToken	string

Responses

200 OK

RESPONSE SCHEMA: application/json

object

POST /api/member/refresh

Response samples

200

Content type
application/json

Copy

```
{ }
```

로그아웃

DB 에서 RefreshToken 을 삭제하고 로그아웃합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

string

POST /api/member/logout

Response samples

200

Content type
application/json

Copy

```
"string"
```

로그인

아이디와 비밀번호로 로그인합니다. AccessToken 은 응답 body, RefreshToken 은 HttpOnly 쿠키로 발급됩니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

memberId	integer <int64>
loginId	string
loginPw	string
email	string
name	string
phone	string
status	string
memberGrade	string
provider	string
providerId	string
penaltyCount	integer <int32>
suspendedUntil	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

object

POST /api/member/login

Request samples

Payload

Content type
application/json

Copy

```
{
    "memberId": 0,
    "loginId": "string",
    "loginPw": "string",
    "email": "string",
    "name": "string",
    "phone": "string",
    "status": "string",
    "memberGrade": "string",
    "provider": "string",
    "providerId": "string",
    "penaltyCount": 0,
    "suspendedUntil": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{ }
```

회원가입

아이디, 비밀번호, 이름, 이메일, 전화번호로 회원가입합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

memberId	integer <int64>
loginId	string
loginPw	string
email	string
name	string
phone	string
status	string
memberGrade	string
provider	string
providerId	string
penaltyCount	integer <int32>
suspendedUntil	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

string

POST /api/member/join

Request samples

Payload

Content type
application/json

Copy

```
{
    "memberId": 0,
    "loginId": "string",
    "loginPw": "string",
    "email": "string",
    "name": "string",
    "phone": "string",
    "status": "string",
    "memberGrade": "string",
    "provider": "string",
    "providerId": "string",
    "penaltyCount": 0,
    "suspendedUntil": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
"string"
```

비밀번호 재설정 (임시 비밀번호 발송)

정보 일치 시 임시 비밀번호를 메일로 발송합니다.

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

property name*
additional property string

Responses

200 OK

RESPONSE SCHEMA: application/json

object

POST /api/member/find-pw

Request samples

Payload

Content type
application/json

Copy

```
{
    "property1": "string",
    "property2": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
{ }
```

아이디 찾기

정보 일치 시 회원의 아이디 일부를 마스킹하여 반환합니다.

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

memberId	integer <int64>
loginId	string
loginPw	string
email	string
name	string
phone	string
status	string
memberGrade	string
provider	string
providerId	string
penaltyCount	integer <int32>
suspendedUntil	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

object

POST /api/member/find-id

Request samples

Payload

Content type
application/json

Copy

```
{
    "memberId": 0,
    "loginId": "string",
    "loginPw": "string",
    "email": "string",
    "name": "string",
    "phone": "string",
    "status": "string",
    "memberGrade": "string",
    "provider": "string",
    "providerId": "string",
    "penaltyCount": 0,
    "suspendedUntil": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{ }
```

아이디 중복 확인

사용 가능한 아이디면 true, 중복이면 false 를 반환합니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

loginId required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

boolean

GET /api/member/check-id

Response samples

200

Content type
application/json

Copy

```
true
```

키오스크 API

충전소 키오스크 인증 / 충전 시작 / 종료 / 상태 조회 API

충전 조기 종료

충전을 예약 시간 전에 조기 종료합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

chargerId	string non-empty
pin	string non-empty
statId	string

Responses

200 OK

RESPONSE SCHEMA: application/json

string

POST /api/kiosk/stop

Request samples

Payload

Content type
application/json

Copy

```
{
    "chargerId": "string",
    "pin": "string",
    "statId": "string"
```

```
}
```

Response samples

200

Content type
application/json

Copy

```
"string"
```

충전 정상 종료

충전을 정상적으로 종료합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

`chargerId`	string	non-empty
`statId`	string	

Responses

200 OK

RESPONSE SCHEMA: application/json

string

POST `/api/kiosk/end`

Request samples

Payload

Content type
application/json

Copy

```
{
    "chargerId": "string",
    "statId": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
"string"
```

키오스크 인증 및 충전 시작

예약 PIN 번호로 인증 후 충전을 시작합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

chargerId	string	non-empty
pin	string	non-empty
statId	string	

Responses

200 OK

RESPONSE SCHEMA: application/json

string

POST /api/kiosk/auth

Request samples

Payload

Content type
application/json

Copy

```
{
    "chargerId": "string",
    "pin": "string",
    "statId": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
"string"
```

충전기 상태 조회

chargerId 로 특정 충전기의 현재 상태를 조회합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

chargerId required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

chargerId	string
status	string
statId	string
startTime	string <date-time>
endTime	string <date-time>

GET /api/kiosk/status/{chargerId}

Response samples

200

Content type
application/json

Copy

```
{
    "chargerId": "string",
    "status": "string",
    "statId": "string",
    "startTime": "2019-08-24T14:15:22Z",
    "endTime": "2019-08-24T14:15:22Z"
}
```

알림 API

사용자 알림 조회 및 읽음 처리 API

알림 읽음 처리

notiId 로 특정 알림을 읽음 처리합니다 (isRead N → Y)

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

notiId required	integer <int64>

Responses

— **200** OK

PATCH /api/notifications/{notiId}/read

내 알림 목록 조회

현재 로그인한 사용자의 알림 목록을 반환합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

```
Array [
    notiId          integer <int64>
    title           string
    message         string
    notiType        string
    targetUrl       string
    isRead          string
    createdAt       string
]
```

GET /api/notifications

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "notiId": 0,
        "title": "string",
        "message": "string",
        "notiType": "string",
        "targetUrl": "string",
        "isRead": "string",
        "createdAt": "string"
    }
]
```

예약 API

충전소 예약 생성 / 조회 / 취소 API

예약 생성

회원 ID 와 충전기 정보로 새 예약을 생성합니다. 성공 시 예약 PIN 번호가 발급됩니다

AUTHORIZATIONS: > *bearerAuth*

HEADER PARAMETERS

X-MemberId required	integer <int64>

REQUEST BODY SCHEMA: application/json
required

startTime required	string <date-time>
chargerId	string non-empty
chargerType	string non-empty
carNumber	string non-empty
statId	string

Responses

200 OK

RESPONSE SCHEMA: application/json

id	integer <int64>
memberName	string
chargerId	string
carNumber	string
statId	string
reservationPin	string
startTime	string <date-time>
endTime	string <date-time>
status	string
actualEndTime	string <date-time>
chargerType	string
isAlertSent	string

POST /api/reservations

Request samples

Payload

Content type
application/json

Copy

```
{
    "chargerId": "string",
    "chargerType": "string",
    "carNumber": "string",
    "statId": "string",
    "startTime": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "id": 0,
    "memberName": "string",
    "chargerId": "string",
    "carNumber": "string",
    "statId": "string",
    "reservationPin": "string",
    "startTime": "2019-08-24T14:15:22Z",
    "endTime": "2019-08-24T14:15:22Z",
    "status": "string",
    "actualEndTime": "2019-08-24T14:15:22Z",
    "chargerType": "string",
    "isAlertSent": "string"
}
```

예약 취소

예약 ID 와 회원 ID 로 본인 예약을 취소합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

id required	integer <int64>

HEADER PARAMETERS

X-MemberId required	integer <int64>

Responses

— **200** OK

PATCH /api/reservations/{id}/cancel

예약 단건 조회

예약 ID 와 회원 ID 로 본인 예약 상세 정보를 조회합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

id required	integer <int64>

HEADER PARAMETERS

X-MemberId required	integer <int64>

Responses

✓ **200** OK

RESPONSE SCHEMA: application/json

id	integer <int64>

memberName	string
chargerId	string
carNumber	string
statId	string
reservationPin	string
startTime	string <date-time>
endTime	string <date-time>
status	string
actualEndTime	string <date-time>
chargerType	string
isAlertSent	string

GET /api/reservations/{id}

Response samples

200

Content type
application/json

Copy

```
{
  "id": 0,
  "memberName": "string",
  "chargerId": "string",
  "carNumber": "string",
  "statId": "string",
  "reservationPin": "string",
  "startTime": "2019-08-24T14:15:22Z",
  "endTime": "2019-08-24T14:15:22Z",
  "status": "string",
```

```
    "actualEndTime": "2019-08-24T14:15:22Z",
    "chargerType": "string",
    "isAlertSent": "string"
}
```

내 예약 목록 조회

현재 로그인한 회원의 예약 목록을 전체 조회합니다

AUTHORIZATIONS: > *bearerAuth*

HEADER PARAMETERS

X-MemberId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

id	integer <int64>
memberName	string
chargerId	string
carNumber	string
statId	string
reservationPin	string
startTime	string <date-time>
endTime	string <date-time>
status	string

actualEndTime	string <date-time>
chargerType	string
isAlertSent	string

]

GET /api/reservations/me

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
  - {
      "id": 0,
      "memberName": "string",
      "chargerId": "string",
      "carNumber": "string",
      "statId": "string",
      "reservationPin": "string",
      "startTime": "2019-08-24T14:15:22Z",
      "endTime": "2019-08-24T14:15:22Z",
      "status": "string",
      "actualEndTime": "2019-08-24T14:15:22Z",
      "chargerType": "string",
      "isAlertSent": "string"
    }
]
```


충전기 가용 여부 조회

statId + chargerId 로 해당 충전기의 현재 예약 가능 여부를 조회합니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

`chargerId` required	string
`statId` required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

boolean

GET `/api/reservations/available`

Response samples

200

Content type
application/json

Copy

```
true
```

관리자 API

관리자 페이지 전용 API (JWT 인증 필요 / MEMBER_GRADE = Y)

관리자 등록

SUPER 권한만 가능. 회원을 관리자로 등록합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

adminId	integer <int64>
memberId	integer <int64>
adminRole	string
adminPart	string
name	string

Responses

200 OK

RESPONSE SCHEMA: application/json

adminId	integer <int64>
memberId	integer <int64>
adminRole	string
adminPart	string
name	string

POST /api/admin

Request samples

Payload

Content type
application/json

Copy

```
{
    "adminId": 0,
    "memberId": 0,
    "adminRole": "string",
    "adminPart": "string",
    "name": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "adminId": 0,
    "memberId": 0,
    "adminRole": "string",
    "adminPart": "string",
    "name": "string"
}
```

공지사항 목록 조회

관리자면 누구나 조회 가능합니다. 삭제된 공지는 제외됩니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

page	integer <int32> Default: 0

Responses

200 OK

RESPONSE SCHEMA: application/json

totalPages	integer <int32>
totalElements	integer <int64>
size	integer <int32>
content >	Array of objects (AdminNoticeDto)
number	integer <int32>
sort >	object (SortObject)
first	boolean
last	boolean
numberOfElements	integer <int32>
pageable >	object (PageableObject)
empty	boolean

GET /api/admin/notices

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
  "totalPages": 0,
```

```
    "totalElements": 0,
    "size": 0,
  - "content": [
     + { … }
    ],
    "number": 0,
  - "sort": {
        "empty": true,
        "sorted": true,
        "unsorted": true
    },
    "first": true,
    "last": true,
    "numberOfElements": 0,
  - "pageable": {
        "offset": 0,
     + "sort": { … },
        "paged": true,
        "pageSize": 0,
        "pageNumber": 0,
        "unpaged": true
    },
    "empty": true
}
```

공지사항 등록

SUPER / INQUIRY 파트만 가능. 새 공지사항을 등록합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

noticeId	integer <int64>
title	string
content	string
writerId	string

fixYn	string
deleteYn	string
insertTime	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

noticeId	integer <int64>
title	string
content	string
writerId	string
fixYn	string
deleteYn	string
insertTime	string <date-time>

POST /api/admin/notices

Request samples

Payload

Content type
application/json

Copy

```
{
    "noticeId": 0,
    "title": "string",
```

```
    "content": "string",
    "writerId": "string",
    "fixYn": "string",
    "deleteYn": "string",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "noticeId": 0,
    "title": "string",
    "content": "string",
    "writerId": "string",
    "fixYn": "string",
    "deleteYn": "string",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

문의 답변 등록

SUPER / INQUIRY 파트만 가능. 문의에 답변을 등록합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

inquiryId required	integer <int64>

REQUEST BODY SCHEMA: application/json
required

inquiryId	integer <int64>
memberId	integer <int64>

statId	string
chargerId	string
category	string
title	string
content	string
status	string
answerContent	string
answerAt	string <date-time>
insertTime	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

inquiryId	integer <int64>
memberId	integer <int64>
statId	string
chargerId	string
category	string
title	string
content	string
status	string
answerContent	string
answerAt	string <date-time>

insertTime	string <date-time>

POST /api/admin/inquiries/{inquiryId}/answer

Request samples

Payload

Content type
application/json

Copy

```
{
    "inquiryId": 0,
    "memberId": 0,
    "statId": "string",
    "chargerId": "string",
    "category": "string",
    "title": "string",
    "content": "string",
    "status": "string",
    "answerContent": "string",
    "answerAt": "2019-08-24T14:15:22Z",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "inquiryId": 0,
    "memberId": 0,
    "statId": "string",
    "chargerId": "string",
    "category": "string",
    "title": "string",
```

```
    "content": "string",
    "status": "string",
    "answerContent": "string",
    "answerAt": "2019-08-24T14:15:22Z",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

관리자 역할 변경

SUPER 권한만 가능. 관리자의 역할을 변경합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

targetId required	integer <int64>

QUERY PARAMETERS

newRole required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

adminId	integer <int64>
memberId	integer <int64>
adminRole	string
adminPart	string
name	string

PATCH /api/admin/{targetId}/role

Response samples

200

Content type
application/json

Copy

```
{
    "adminId": 0,
    "memberId": 0,
    "adminRole": "string",
    "adminPart": "string",
    "name": "string"
}
```

관리자 파트 변경

SUPER 권한만 가능. 관리자의 담당 파트를 변경합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

targetId required	integer <int64>

QUERY PARAMETERS

newPart required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

adminId	integer <int64>
memberId	integer <int64>
adminRole	string
adminPart	string
name	string

PATCH /api/admin/{targetId}/part

Response samples

200

Content type
application/json

Copy

```
{
    "adminId": 0,
    "memberId": 0,
    "adminRole": "string",
    "adminPart": "string",
    "name": "string"
}
```

예약 삭제

SUPER / RESERVATION 파트만 가능. 예약을 삭제합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

reservationId required	integer <int64>

Responses

— **200** OK

DELETE /api/admin/reservations/{reservationId}

예약 강제 취소

SUPER / RESERVATION 파트만 가능. 예약을 강제 취소합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

reservationId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

reservationId	integer <int64>
memberId	integer <int64>
chargerId	string
carNumber	string

startTime	string <date-time>
endTime	string <date-time>
actualEndTime	string <date-time>
status	string

PATCH /api/admin/reservations/{reservationId}

Response samples

200

Content type
application/json

Copy

```
{
    "reservationId": 0,
    "memberId": 0,
    "chargerId": "string",
    "carNumber": "string",
    "startTime": "2019-08-24T14:15:22Z",
    "endTime": "2019-08-24T14:15:22Z",
    "actualEndTime": "2019-08-24T14:15:22Z",
    "status": "string"
}
```

패널티 삭제

SUPER / PENALTY 파트만 가능. 패널티를 삭제합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

penaltyId required	integer <int64>

Responses

— **200** OK

DELETE /api/admin/penalties/{penaltyId}

패널티 취소

SUPER / PENALTY 파트만 가능. 패널티를 취소 처리합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

penaltyId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

penaltyId	integer <int64>
memberId	string
reservationId	integer <int64>
carNumber	string

reason	string
nudgeCount	integer <int32>
status	string Enum: "ACTIVE" "CLEARED" "CANCELED"
notiSentYn	string
insertTime	string <date-time>

PATCH /api/admin/penalties/{penaltyId}

Response samples

200

Content type
application/json

Copy

```
{
    "penaltyId": 0,
    "memberId": "string",
    "reservationId": 0,
    "carNumber": "string",
    "reason": "string",
    "nudgeCount": 0,
    "status": "ACTIVE",
    "notiSentYn": "string",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

공지사항 삭제

SUPER / INQUIRY 파트만 가능. 공지사항을 소프트 삭제합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

noticeId required	integer <int64>

Responses

— **200** OK

DELETE /api/admin/notices/{noticeId}

공지사항 수정

SUPER / INQUIRY 파트만 가능. 공지사항을 수정합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

noticeId required	integer <int64>

REQUEST BODY SCHEMA: application/json
required

noticeId	integer <int64>
title	string
content	string
writerId	string
fixYn	string
deleteYn	string

insertTime	string <date-time>

Responses

200 OK

RESPONSE SCHEMA: application/json

noticeId	integer <int64>
title	string
content	string
writerId	string
fixYn	string
deleteYn	string
insertTime	string <date-time>

PATCH /api/admin/notices/{noticeId}

Request samples

Payload

Content type
application/json

Copy

```
{
  "noticeId": 0,
  "title": "string",
  "content": "string",
  "writerId": "string",
  "fixYn": "string",
  "deleteYn": "string",
```

```
    "insertTime": "2019-08-24T14:15:22Z"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "noticeId": 0,
    "title": "string",
    "content": "string",
    "writerId": "string",
    "fixYn": "string",
    "deleteYn": "string",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

회원 상태 변경

SUPER / MEMBER 파트만 가능. 회원 상태를 ACTIVE / SUSPENDED / WITHDRAWN 으로 변경합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

`memberId` required	integer <int64>

QUERY PARAMETERS

`newStatus` required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

memberId	integer <int64>
loginId	string
name	string
email	string
phone	string
status	string
penaltyCount	integer <int32>
suspendedUntil	string <date-time>
memberGrade	string

PATCH /api/admin/members/{memberId}

Response samples

200

Content type
application/json

Copy

```
{
    "memberId": 0,
    "loginId": "string",
    "name": "string",
    "email": "string",
    "phone": "string",
    "status": "string",
    "penaltyCount": 0,
    "suspendedUntil": "2019-08-24T14:15:22Z",
    "memberGrade": "string"
}
```

충전기 상태 변경

SUPER / CHARGER 파트만 가능. 충전기 상태를 변경합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

statId required	string
chargerId required	string

QUERY PARAMETERS

newStat required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

statId	string
chargerId	string

chargerType	string
stat	string
output	integer <int32>
method	string
statUpdDt	string
statLabel	string

PATCH /api/admin/chargers/{statId}/{chargerId}

Response samples

200

Content type
application/json

Copy

```
{
    "statId": "string",
    "chargerId": "string",
    "chargerType": "string",
    "stat": "string",
    "output": 0,
    "method": "string",
    "statUpdDt": "string",
    "statLabel": "string"
}
```

관리자 단건 조회

adminId 로 특정 관리자 정보를 조회합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

adminId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

adminId	integer <int64>
memberId	integer <int64>
adminRole	string
adminPart	string
name	string

GET /api/admin/{adminId}

Response samples

200

Content type
application/json

Copy

```
{
    "adminId": 0,
    "memberId": 0,
    "adminRole": "string",
    "adminPart": "string",
    "name": "string"
}
```

충전소 목록 조회

관리자면 누구나 조회 가능합니다. keyword 파라미터로 검색 가능합니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

keyword	string

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

statId	string
statNm	string
addr	string
location	string
useTime	string
bnm	string
parkingFree	string

limitYn	string
limitDetail	string

]

GET /api/admin/stations

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
  - {
        "statId": "string",
        "statNm": "string",
        "addr": "string",
        "location": "string",
        "useTime": "string",
        "bnm": "string",
        "parkingFree": "string",
        "limitYn": "string",
        "limitDetail": "string"
    }
]
```

예약 전체 목록 조회

관리자면 누구나 조회 가능합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

```
Array [
```

reservationId	integer <int64>
memberId	integer <int64>
chargerId	string
carNumber	string
startTime	string <date-time>
endTime	string <date-time>
actualEndTime	string <date-time>
status	string

```
]
```

GET /api/admin/reservations

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
        "reservationId": 0,
        "memberId": 0,
        "chargerId": "string",
        "carNumber": "string",
        "startTime": "2019-08-24T14:15:22Z",
        "endTime": "2019-08-24T14:15:22Z",
        "actualEndTime": "2019-08-24T14:15:22Z",
        "status": "string"
    }
]
```

패널티 전체 목록 조회

관리자면 누구나 조회 가능합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

penaltyId	integer <int64>
memberId	string
reservationId	integer <int64>
carNumber	string
reason	string
nudgeCount	integer <int32>

status	string Enum: "ACTIVE" "CLEARED" "CANCELED"
notiSentYn	string
insertTime	string <date-time>

]

GET /api/admin/penalties

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
  - {
      "penaltyId": 0,
      "memberId": "string",
      "reservationId": 0,
      "carNumber": "string",
      "reason": "string",
      "nudgeCount": 0,
      "status": "ACTIVE",
      "notiSentYn": "string",
      "insertTime": "2019-08-24T14:15:22Z"
    }
]
```

회원 전체 목록 조회

SUPER / MEMBER 파트만 가능. 전체 회원 목록을 반환합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

```
Array [
    memberId          integer <int64>
    loginId           string
    name              string
    email             string
    phone             string
    status            string
    penaltyCount      integer <int32>
    suspendedUntil    string <date-time>
    memberGrade       string
]
```

GET /api/admin/members

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "memberId": 0,
        "loginId": "string",
        "name": "string",
        "email": "string",
        "phone": "string",
        "status": "string",
        "penaltyCount": 0,
        "suspendedUntil": "2019-08-24T14:15:22Z",
        "memberGrade": "string"
    }
]
```

관리자 전체 목록 조회

등록된 모든 관리자 목록을 반환합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

adminId	integer <int64>
memberId	integer <int64>
adminRole	string
adminPart	string
name	string

]

GET /api/admin/list

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
  - {
      "adminId": 0,
      "memberId": 0,
      "adminRole": "string",
      "adminPart": "string",
      "name": "string"
    }
]
```

문의 전체 목록 조회

관리자면 누구나 조회 가능합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

inquiryId	integer <int64>
memberId	integer <int64>

statId	string
chargerId	string
category	string
title	string
content	string
status	string
answerContent	string
answerAt	string <date-time>
insertTime	string <date-time>

]

GET /api/admin/inquiries

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "inquiryId": 0,
        "memberId": 0,
        "statId": "string",
        "chargerId": "string",
        "category": "string",
        "title": "string",
        "content": "string",
        "status": "string",
        "answerContent": "string",
        "answerAt": "2019-08-24T14:15:22Z",
        "insertTime": "2019-08-24T14:15:22Z"
    }
]
```

대시보드 통계 조회

총 회원 수, 오늘 예약 수, 충전소 수, 고장 충전기 수, 미답변 문의 수를 반환합니다

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

totalMembers	integer <int64>
todayReservations	integer <int64>
totalStations	integer <int64>
brokenChargers	integer <int64>
pendingInquiries	integer <int64>

GET /api/admin/dashboard

Response samples

200

Content type
application/json

Copy

```
{
    "totalMembers": 0,
    "todayReservations": 0,
    "totalStations": 0,
    "brokenChargers": 0,
    "pendingInquiries": 0
}
```

충전기 목록 조회

관리자면 누구나 조회 가능합니다. statId 파라미터로 특정 충전소 충전기만 조회 가능합니다

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

statId	string

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

statId	string

chargerId	string
chargerType	string
stat	string
output	integer <int32>
method	string
statUpdDt	string
statLabel	string

]

GET /api/admin/chargers

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
      "statId": "string",
      "chargerId": "string",
      "chargerType": "string",
      "stat": "string",
      "output": 0,
      "method": "string",
      "statUpdDt": "string",
      "statLabel": "string"
    }
]
```

관리자 해제

SUPER 권한만 가능. 관리자를 해제하고 MEMBER_GRADE 를 N 으로 변경합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

`targetId` required	integer <int64>

Responses

— **200** OK

DELETE `/api/admin/{targetId}`

SMS API

패널티 문자 발송 API

패널티 문자 발송

예약 ID 와 사유를 받아 패널티를 처리하고 문자를 발송합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

`property name*` additional property	object

Responses

200 OK

RESPONSE SCHEMA: application/json

object

POST /api/sms/send-penalty

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "property1": { },
    "property2": { }
}
```

Response samples

200

Content type
application/json

Copy

```
{ }
```

공지사항 API

공지사항 조회 / 등록 / 수정 / 삭제 / 복구 API

공지사항 수정

noticeId 로 공지사항을 수정합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

noticeId required	integer <int64>

REQUEST BODY SCHEMA: application/json
required

title	string non-empty
content	string non-empty
fixYn	string
noticeId	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

success	boolean
message	string
result >	object (NoticeResponseDto)

page	integer <int32>
totalNumber	integer <int64>

PUT /api/notices/admin/{noticeId}

Request samples

Payload

Content type
application/json

Copy

```
{
    "title": "string",
    "content": "string",
    "fixYn": "string",
    "noticeId": 0
}
```

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "success": true,
    "message": "string",
```

```
  - "result": {
        "noticeId": 0,
        "title": "string",
        "content": "string",
        "writerId": "string",
        "fixYn": "string",
        "insertTime": "2019-08-24T14:15:22Z",
        "updateTime": "2019-08-24T14:15:22Z",
        "formattedDate": "string",
        "new": true
    },
    "page": 0,
    "totalNumber": 0
}
```

공지사항 삭제

공지사항을 소프트 삭제합니다 (deleteYn N → Y)

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

noticeId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

success	boolean
message	string
result	object
page	integer <int32>

totalNumber integer <int64>

DELETE /api/notices/admin/{noticeId}

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "success": true,
    "message": "string",
    "result": { },
    "page": 0,
    "totalNumber": 0
}
```

관리자용 공지사항 전체 목록 조회

삭제된 공지사항 포함 전체 목록을 반환합니다 (deleteYn = N + Y)

AUTHORIZATIONS: > *bearerAuth*

Responses

200 OK

RESPONSE SCHEMA: application/json

success boolean

message	string
result >	Array of objects (NoticeResponseDto)
page	integer <int32>
totalNumber	integer <int64>

GET /api/notices/admin

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "success": true,
    "message": "string",
  - "result": [
      + { … }
    ],
    "page": 0,
    "totalNumber": 0
}
```

공지사항 등록

새 공지사항을 등록합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

title	string non-empty

content	string non-empty
fixYn	string
noticeId	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

success	boolean
message	string
result >	object (NoticeResponseDto)
page	integer <int32>
totalNumber	integer <int64>

POST /api/notices/admin

Request samples

Payload

Content type
application/json

Copy

```
{
    "title": "string",
    "content": "string",
    "fixYn": "string",
    "noticeId": 0
}
```

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
{
    "success": true,
    "message": "string",
  - "result": {
        "noticeId": 0,
        "title": "string",
        "content": "string",
        "writerId": "string",
        "fixYn": "string",
        "insertTime": "2019-08-24T14:15:22Z",
        "updateTime": "2019-08-24T14:15:22Z",
        "formattedDate": "string",
        "new": true
    },
    "page": 0,
    "totalNumber": 0
}
```

공지사항 복구

삭제된 공지사항을 복구합니다 (deleteYn Y → N)

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

noticeId required	integer <int64>

Responses

200 OK

RESPONSE SCHEMA: application/json

success	boolean
message	string
result	object
page	integer <int32>
totalNumber	integer <int64>

PATCH /api/notices/admin/restore/{noticeId}

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "success": true,
    "message": "string",
    "result": { },
    "page": 0,
    "totalNumber": 0
}
```

고객용 공지사항 목록 조회

삭제되지 않은 공지사항 목록을 반환합니다 (deleteYn = N)

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

page	integer <int32> Default: 1

Responses

200 OK

RESPONSE SCHEMA: application/json

success	boolean
message	string
result >	Array of objects (NoticeResponseDto)
page	integer <int32>
totalNumber	integer <int64>

GET /api/notices

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "success": true,
    "message": "string",
  - "result": [
      + { ... }
    ],
    "page": 0,
    "totalNumber": 0
}
```

패널티 API

패널티 등록 및 회원별 패널티 내역 조회 API

패널티 등록

노쇼 발생 시 패널티를 등록하고 문자를 발송합니다

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

memberId	string
reservationId	integer <int64>
carNumber	string
reason	string

Responses

200 OK

RESPONSE SCHEMA: application/json

penaltyId	integer <int64>
memberId	string
carNumber	string
reason	string
nudgeCount	integer <int32>
status	string Enum: "ACTIVE" "CLEARED" "CANCELED"
notiSentYn	string
insertTime	string <date-time>

POST /api/penalties

Request samples

Payload

Content type
application/json

Copy

```
{
    "memberId": "string",
    "reservationId": 0,
    "carNumber": "string",
    "reason": "string"
}
```

Response samples

200

Content type
application/json

Copy


```
{
    "penaltyId": 0,
    "memberId": "string",
    "carNumber": "string",
    "reason": "string",
    "nudgeCount": 0,
    "status": "ACTIVE",
    "notiSentYn": "string",
    "insertTime": "2019-08-24T14:15:22Z"
}
```

회원별 패널티 내역 조회

memberId 로 해당 회원의 패널티 내역 목록을 조회합니다

AUTHORIZATIONS: > *bearerAuth*

PATH PARAMETERS

memberId required	string

Responses

200 OK

RESPONSE SCHEMA: application/json

Array [

penaltyId	integer <int64>
memberId	string
carNumber	string
reason	string
nudgeCount	integer <int32>

status	string Enum: "ACTIVE" "CLEARED" "CANCELED"
notiSentYn	string
insertTime	string <date-time>

]

GET /api/penalties/{memberId}

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
      "penaltyId": 0,
      "memberId": "string",
      "carNumber": "string",
      "reason": "string",
      "nudgeCount": 0,
      "status": "ACTIVE",
      "notiSentYn": "string",
      "insertTime": "2019-08-24T14:15:22Z"
   }
]
```

sse-controller

subscribe

AUTHORIZATIONS: > *bearerAuth*

QUERY PARAMETERS

`loginId` required	string

Responses

200 OK

RESPONSE SCHEMA: text/event-stream

`timeout`	integer <int64>

GET `/api/notifications/subscribe`