

WITH A AS (  
 SELECT /\*+ INDEX(WITH\_TEST WITH\_TEST\_PK) \*/ \*  
 FROM WITH\_TEST  
 )  
 SELECT \*  
 FROM A  
 WHERE CUST\_NO >= 2000;

↑ 'WITH' 서브쿼리 안에서 Hint 작성

스크립트 출력 x | 질의 결과 x | 계획 설명 x

SQL | 0.041초

OPERATION	OBJECT_NAME	OPTIONS	CARDINALITY	COST
SELECT STATEMENT				103
TABLE ACCESS	WITH_TEST	BY INDEX ROWID BATCHED	103	10
INDEX	WITH_TEST_PK	RANGE SCAN	103	2
Access Predicates				
WITH_TEST.CUST_NO>=2000				

WITH A AS (  
 SELECT \*  
 FROM WITH\_TEST  
 )  
 SELECT /\*+ INDEX(WITH\_TEST WITH\_TEST\_PK) \*/ \*  
 FROM A  
 WHERE CUST\_NO >= 2000;

↖ 메인 쿼리에서 Hint 작성

스크립트 출력 x | 질의 결과 x | 계획 설명 x

SQL | 0.017초

OPERATION	OBJECT_NAME	OPTIONS	CARDINALITY	COST
SELECT STATEMENT				103
TABLE ACCESS	WITH_TEST	FULL	103	2
Filter Predicates				
WITH_TEST.CUST_NO>=2000				