

WITH A AS (
 SELECT /*+ INDEX(WITH_TEST WITH_TEST_PK) */ *
 FROM WITH_TEST
)
 SELECT *
 FROM A
 WHERE CUST_NO >= 2000;

↑ 'WITH' 서브쿼리 안에서 Hint 작성

스크립트 출력 x | 질의 결과 x | 계획 설명 x

SQL | 0.041초

OPERATION	OBJECT_NAME	OPTIONS	CARDINALITY	COST
SELECT STATEMENT				103 10
TABLE ACCESS	WITH_TEST	BY INDEX ROWID BATCHED		103 10
INDEX	WITH_TEST_PK	RANGE SCAN		103 2
Access Predicates				
WITH_TEST.CUST_NO>=2000				

WITH A AS (
 SELECT *
 FROM WITH_TEST
)
 SELECT /*+ INDEX(WITH_TEST WITH_TEST_PK) */ *
 FROM A
 WHERE CUST_NO >= 2000;

↘ 메인 쿼리에서 Hint 작성

스크립트 출력 x | 질의 결과 x | 계획 설명 x

SQL | 0.017초

OPERATION	OBJECT_NAME	OPTIONS	CARDINALITY	COST
SELECT STATEMENT				103 2
TABLE ACCESS	WITH_TEST	FULL		103 2
Filter Predicates				
WITH_TEST.CUST_NO>=2000				