

Filter [T×F]	DNSMOS (P.808)↑	DNSMOS(P.835) SIG↑ BAK↑ OVL↑	SI-SDR↑	PESQ↑	STOI↑	ESTOI↑	CSIG↑	CBAK↑	COVL↑	LSD↓	MCD↓
3×3	3.45	3.38 3.98 3.07	16.70	3.29	0.948	0.868	4.40	3.59	3.88	0.73	2.28
1×3	3.45	3.38 3.96 3.06	16.09	3.28	0.947	0.868	4.39	3.57	3.87	0.72	2.31
1×5	3.46	3.39 3.94 3.06	15.24	3.28	0.946	0.866	4.42	3.53	3.89	0.76	2.40
1×7	3.46	3.38 3.95 3.05	16.18	3.26	0.947	0.867	4.40	3.56	3.86	0.74	2.32
3×1	3.44	3.37 3.94 3.04	15.57	3.20	0.945	0.861	4.38	3.49	3.82	0.80	2.49
5×1	3.44	3.38 3.88 3.01	13.83	3.20	0.946	0.865	4.35	3.42	3.80	0.78	2.53

Table 1: Filter tap ablation on the VoiceBank+DEMAND 48 kHz test set. The default row uses a 3 x 3 time-frequency filtering neighborhood. The F-only rows use frequency-only neighborhoods, and the T-only rows use time-only neighborhoods.