

- [Home](#)
- [Disclaimer](#)
- [Contact](#)


Restore Your USB Key to its original state

After having tooled around with a USB Linux version using your image overwritten or multi partitioned flash pen drive, you might find it necessary to revert it back to a single fat partition (restore the flash pen drive to its original state) that can again be read by all computers. Windows users can follow the Windows instructions below to Restore a Flash Drive using the *HP USB Format Tool*. For those working from Linux this task can easily be accomplished via the Linux Flash Drive Restoration tutorial that follows.

Restoring your USB key to its original state using Windows/Mac OS:

– Manual Method via Diskpart – Windows:

1. Open a command Prompt as administrator (`cmd.exe`)
2. Type **Diskpart** and press Enter
3. Type **List Disk** and press Enter
4. Type **Select Disk X** (where **X** is the disk number of your USB drive) and press Enter
5. Type **Clean** and press Enter
6. Type **Create Partition Primary** and press Enter
7. Type **Active** and press Enter
8. Type **Format fs=Fat32 Quick** and press Enter
9. Type **Exit** and press Enter



```
Administrator: Command Prompt ...
DISKPART> List Disk

Disk ###  Status        Size      Free      Dyn  Gpt
-----  -
Disk 0    Online       238 GB    0 B
Disk 1    Online       29 GB     0 B

DISKPART> Select Disk 1

Disk 1 is now the selected disk.

DISKPART> clean

DiskPart succeeded in cleaning the disk.

DISKPART> Create Partition Primary

DiskPart succeeded in creating the specified partition.

DISKPART> Active

DiskPart marked the current partition as active.


DISKPART> Format fs=Fat32 Quick

100 percent completed
DiskPart successfully formatted the volume.

DISKPART> _
```


– Multiple GUI Methods – Windows:

Windows and or Mac OS users could use the [SD Formatter Tool](#) to reformat and restore a USB Drive.




Or alternately, Windows users could use [BOOTICE](#)


1. [Download](#), extract, and run Pauly's B00TICE Tool
2. (1) Select your USB Flash Drive from the list, (2) Click Parts Manage



3. (1) Click Repartitioning



4. (1) Under Disk Mode, Choose **USB-FDD**, **USB-HDD**, or **USB-ZIP** mode I use **USB-HDD** as it works with every BIOS I use. (2) Click OK



Restoring your USB key to its original state using Linux:

A. First we need to delete the old partitions that remain on the USB key.

1. Open a terminal and type **sudo su**
2. Type **fdisk -l** and note your USB drive letter.
3. Type **fdisk /dev/sd~~x~~** (replacing ~~x~~ with your drive letter)
4. Type **d** to proceed to delete a partition
5. Type **1** to select the 1st partition and press **enter**
6. Type **d** to proceed to delete another partition (fdisk should automatically select the second partition)

B. Next we need to create the new partition.

1. Type **n** to make a new partition
2. Type **p** to make this partition primary and press **enter**
3. Type **1** to make this the first partition and then press **enter**
4. Press **enter** to accept the default first cylinder
5. Press **enter** again to accept the default last cylinder
6. Type **w** to write the new partition information to the USB key
7. Type **umount /dev/sd~~x~~1** (replacing ~~x~~ with your drive letter)

C. The last step is to create the fat filesystem.

1. Type `mkfs.vfat -F 32 /dev/sdx1` (replacing ~~x~~ with your USB key drive letter)

That's it, you should now have a restored USB key with a single fat 32 partition that can be read from any computer.

Similar Portable Linux Posts:

- [Recommended USB Linux flash drives](#)
- [Install Puppy Linux to a Flash Drive using the CD](#)
- [LiveUSB Install – Live USB Creator](#)

Restore Your USB Key to its original state published under [USB flash pen drive tools](#), [Using and Configuring Linux](#)

[flash pen](#), [format tool](#), [linux version](#), [mkfs](#), [partition fdisk](#), [partition type](#), [pen drive](#), [usb key](#), [usb linux](#), [windows users](#)

The information provided on this site is being offered in hopes that it will be useful. We are providing absolutely no warranty for this information. Please see our [Disclaimer](#) for more details.

Unless specifically stated otherwise, Pendrivelinux.com is not a part of, affiliated with or endorsed by any mentioned Linux distribution or non-pendrivelinux created software tool.

• Portable Linux Categories

- [Flash drive installs using Live CD](#)
- [Flash drive installs using Windows](#)
- [USB Virtual Machine Emulation](#)
- [Using and Configuring Linux](#)

• Pendrive Linux Posts

- [Make a USB Boot CD for Ubuntu 11.10](#)
- [Boot DOS from USB – RUFUS](#)
- [LiveUSB Install – Live USB Creator](#)
- [XB00T – Multiboot ISO USB Creator \(Windows\)](#)
- [YUMI – Multiboot USB Creator](#)
- [SARDU – Multiboot USB Creator \(Windows\)](#)
- [Boot Multiple ISO from USB via Grub2 using Linux](#)
- [Creating a Kubuntu Live USB from CD](#)
- [Creating an Xubuntu Live USB from CD](#)
- [Creating an Ubuntu Live USB from CD](#)
- [Using UNetbootin to create a Linux USB from Linux](#)
- [MultiSystem – Create a MultiBoot USB from Linux](#)
- [Put Mandriva 2010 on a USB Flash Drive \(Windows\)](#)
- [Put Bitdefender Rescue CD on a USB Flash Drive](#)
- [Put Lucid Puppy on USB Flash Drive from Windows](#)

©2006–2017 Pendrivelinux.com – Run Linux From USB. [Credits, Resources and Sources](#) – [Cookies & Privacy Policy](#)

Linux® is a registered trademark of Linus Torvalds. Windows is a

registered trademark of Microsoft. Other names and logos may also be trademarked by their respective owners.