ROBUST REPRESENTATION LEARNING FOR GENERALIZATION IN NOISY AND DATA-CONSTRAINED ENVIRONMENTS

A DISSERTATION
SUBMITTED TO THE DEPARTMENT OF
ELECTRICAL AND COMPUTER ENGINEERING
AND THE COMMITTEE ON GRADUATE STUDIES OF
ROWAN UNIVERSITY
IN PARTIAL FULFILLMENT OF THE REQUIREMENTS
FOR THE DEGREE OF
DOCTOR OF PHILOSOPHY

Atik Faysal

May 2025

© Copyright by Atik Faysal 2025

All Rights Reserved

I certify that I have read this dissertation and that in my opinion it is fully adequate, in scope and in quality, as a dissertation for the degree of Doctor of Philosophy.

Huaxia Wang
(Principal Advisor)

I certify that I have read this dissertation and that in my opinion it is fully adequate, in scope and in quality, as a dissertation for the degree of Doctor of Philosophy.

First Reader Name
(Associate Advisor)

I certify that I have read this dissertation and that in my opinion it is fully adequate, in scope and in quality, as a dissertation for the degree of Doctor of Philosophy.

Second Reader Name

Approved for the University Committee on Graduate Studies:

Abstract

In this dissertation, we propose a suite of representation learning strategies and classification frameworks designed to enhance model generalization in noisy and data-constrained environments—specifically within the domains of wireless communication, few-shot learning, and semi-supervised learning. Our contributions span three interconnected research areas. First, we introduce transformer-based and multimodal architectures, including NMformer and DenoMAE variants, that robustly classify modulation types under challenging signal conditions by leveraging both constellation diagrams and local patch-level features. Second, we develop meta-learning strategies, such as MetaRep and MetaTask, that emphasize episodic representation learning and dynamic regularization to combat overfitting in low-data regimes. These frameworks integrate auxiliary autoencoding objectives and task-specific decoders to promote generalizable embeddings. Third, we advance semi-supervised learning with RLPL, a self-supervised framework that combines contrastive learning, consistency regularization, and dynamic pseudo-labeling for effective utilization of unlabeled data. Across all domains, we demonstrate that exploiting noise structures, integrating multimodal inputs, and adopting task-aware optimization significantly improve performance under domain shifts and limited supervision. These findings offer practical and scalable solutions for real-world applications where data is scarce, labels are costly, and robustness is critical.

Chapter 1

Introduction

Machine learning has transformed fields such as computer vision and natural language processing by uncovering complex patterns in large, well-organized datasets. However, its performance often declines when confronted with real-world challenges like limited labeled data or noisy inputs—conditions common in domains like wireless communication and few-shot learning. Self-supervised and semi-supervised learning have emerged as promising strategies to mitigate these issues, enabling models to leverage vast amounts of unlabeled data for improved performance. The most common techniques to utilize unlabeled data is though learning their representation. Yet, representation learning techniques often focus on generic reconstruction tasks, which may not align with the specific needs of the target application. Additionally, they are inefficient for resource constrained medium due to their increased computational complexity. This misalignment can lead to suboptimal performance, particularly in scenarios where labeled data is scarce or noisy.

This thesis introduces novel approaches to address these challenges, including advanced representation learning, robust classification strategy for multiple domains including supervised learning, semi-supervised learning, meta learning and wireless communication.

A particular focus is placed on multimodal learning techniques that leverage different representations of the same data to extract complementary information, thereby enhancing model robustness and performance. We propose several frameworks that reduces computational complexity, improve representation learning, utilizes advanced learning for pseudo labeling, improve classification accuracy and reconstruction ability. Our provided solutions are designed to be flexible and adaptable, making them suitable for a wide range of real world applications.

1.1 Background and Motivation

Machine learning has emerged as a transformative force across numerous domains, demonstrating remarkable effectiveness in solving complex problems that were previously intractable with traditional algorithmic approaches. Deep learning models, in particular, have achieved unprecedented success in areas such as computer vision [1], natural language processing [2], and wireless communications [3]. These advances have enabled applications ranging from automated medical diagnostics to intelligent resource allocation in next-generation wireless networks, fundamentally changing how we approach computational problems by allowing systems to learn patterns from data rather than relying on explicit programming.

Despite their impressive capabilities, modern machine learning algorithms are notoriously data-hungry, often requiring vast quantities of labeled examples to achieve satisfactory performance. Models such as GPT-4 [4] with over 1.8 trillion parameters, and vision transformers [5] trained on hundreds of millions of images exemplify this data dependency. In wireless communications, deep learning approaches for channel estimation, modulation classification, and signal detection typically demand extensive datasets collected across various channel conditions [6]. When confronted with limited data scenarios—common in

specialized domains, rare events, or newly deployed systems—these models often suffer from overfitting, poor generalization, and diminished performance, highlighting a fundamental challenge in applying state-of-the-art machine learning to real-world constraints.

To mitigate these data scarcity issues, researchers have developed several innovative approaches. Self-supervised learning methods leverage inherent structure within unlabeled data to create supervision signals, enabling models to learn meaningful representations without explicit annotations. For instance, contrastive learning techniques like SimCLR [7] and MoCo [8] have achieved remarkable success in computer vision by training encoders to map similar images closer in the latent space while pushing dissimilar images apart. Similarly, semi-supervised learning approaches combine limited labeled data with abundant unlabeled examples to improve generalization. Techniques such as FixMatch [9] and MixMatch [10] use confident predictions on unlabeled data as pseudo-labels to augment the training process. While these methods significantly reduce labeling requirements, they may still struggle with domain shifts and require careful hyperparameter tuning to prevent confirmation bias where models reinforce their own errors.

Representation learning has emerged as a particularly powerful semi-supervised paradigm, focusing on learning transferable feature embeddings that capture the underlying structure of data. By training models to encode inputs into meaningful vector spaces, representation learning facilitates downstream tasks with minimal labeled examples. Notable approaches include variational autoencoders (VAEs) [11], which learn latent representations by reconstructing inputs while regularizing the latent space, and BERT [12], which learns contextual word embeddings through masked language modeling. Multimodal representation learning extends these concepts by jointly encoding different views or representations of the same data, capturing complementary information that might be missed in single-modality approaches. In wireless communications, approaches like [6] leverage autoencoders to

learn robust signal representations that generalize across different channel conditions. Despite their effectiveness, these methods often require substantial computational resources for pretraining and may still fail to capture task-specific features necessary for specialized applications.

Few-shot learning and meta-learning address data efficiency more directly by teaching models to learn from minimal examples. Few-shot learning aims to recognize new classes from just a handful of labeled instances, while meta-learning adopts a ”learning to learn” approach, training models on diverse tasks to rapidly adapt to new, related tasks with limited data. Prototypical Networks [13] exemplify few-shot learning by comparing query samples to class prototypes in an embedding space, while Model-Agnostic Meta-Learning (MAML) [14] optimizes model parameters for quick adaptation through gradient-based fine-tuning. These approaches have shown promising results in wireless applications such as modulation recognition with limited training samples [15] and adaptive resource allocation under varying channel conditions [16]. However, these methods face challenges including limited cross-domain transfer, high sensitivity to task distribution shifts, and difficulty scaling to complex problems requiring deeper model architectures.

1.1.1 Challenges in Wireless Communication

Modern wireless systems require efficient signal processing techniques to maintain reliable communication in increasingly congested environments. Modulation classification—the task of identifying the modulation scheme used in a received signal—has become particularly critical for cognitive radio, spectrum monitoring, and interference management. However, this task presents several fundamental challenges:

- **Signal Corruption:** Real-world wireless signals are inherently corrupted by various noise sources, with signal-to-noise ratios (SNRs) often dropping to extremely low

levels, especially in dynamic environments. Conventional classification techniques show significant performance degradation when SNRs fall below 0 dB.

- **Feature Engineering Complexity:** Traditional approaches rely heavily on expert-designed features, requiring substantial domain knowledge and often failing to generalize across different modulation schemes or noise conditions. These hand-crafted features may perform well in specific scenarios but lack adaptability to changing wireless environments.

- **Data Scarcity:** Obtaining extensively labeled datasets across diverse channel conditions is prohibitively expensive and time-consuming. Current models require excessive amounts of labeled data, and even small reductions in training data can lead to substantial performance drops in conventional approaches.

- **Single-Modality Limitations:** Most approaches utilize only one representation of the signal (e.g., time-domain or frequency-domain), failing to capitalize on complementary information available in different signal representations such as constellation diagrams, which could provide critical insights especially in high-noise scenarios.

1.1.2 Limitations in Few-Shot Learning

Few-shot learning aims to train models that can generalize to new tasks with minimal labeled examples, mirroring human ability to learn concepts from limited exposure. Despite significant progress, several critical limitations persist:

- **Overfitting:** Models trained on small datasets tend to memorize rather than generalize, with error rates increasing dramatically when tested on out-of-distribution

samples. Standard few-shot learning approaches often exhibit significant generalization gaps, sometimes exceeding 20% between training and testing performance.

- **Episode Quality:** The quality of training episodes significantly impacts meta-learning performance, yet most approaches generate episodes randomly without considering task relationships. Naive episode construction can lead to poor separation between classes and reduced generalization capability.

- **Representation Inefficiency:** Most meta-learning methods fail to leverage the rich information contained within episodes themselves, focusing solely on adaptation mechanisms rather than representation quality. Standard episodic training typically underutilizes potentially useful data contained in the episode structure.

- **Unlabeled Data Underutilization:** While unlabeled data is abundant in most domains, few-shot learning approaches rarely incorporate this valuable resource effectively. Current semi-supervised meta-learning methods often treat unlabeled data as a secondary source of information rather than integrating it into the core learning process.

Existing approaches like Model-Agnostic Meta-Learning (MAML), Relation Networks (RN) have advanced the field significantly but still struggle with these fundamental challenges. MAML's gradient-based adaptation, while elegant, remains vulnerable to overfitting when labeled examples are scarce and doesn't fully capitalize on representational learning that could improve generalization.

1.1.3 Cross-Domain Challenges in Representation Learning

Beyond domain-specific issues, both wireless communication and few-shot learning share common challenges in representation learning:

- **Task-Feature Alignment:** Generic self-supervised learning objectives like masked autoencoding often learn representations that reconstruct superficial features rather than task-relevant abstractions. Standard reconstruction losses frequently fail to capture the discriminative features necessary for robust classification in downstream tasks.

- **Computational Efficiency:** State-of-the-art representation learning techniques typically require large batch sizes and extensive computational resources, limiting their practical application. Conventional approaches often need unnecessarily large batch sizes, creating barriers to deployment on resource-constrained platforms.

- **Integration of Supervised and Self-Supervised Signals:** Effectively combining labeled and unlabeled data remains challenging, with most approaches treating them as separate learning processes rather than complementary information sources.

1.2 Objectives and Motivation

The limitations identified in current machine learning approaches reveal a critical need for innovation in data-constrained environments. At the intersection of wireless communications and few-shot learning lies an opportunity to develop unified solutions that address shared fundamental challenges. Representation learning emerges as a powerful connecting paradigm between these seemingly disparate domains, offering a pathway to create algorithms that are both theoretically grounded and practically viable.

This research seeks to develop machine learning frameworks specifically designed for scenarios where data is limited, noisy, or both. Through the strategic integration of self-supervised, semi-supervised, and meta-learning techniques, this work aims to enhance performance across a spectrum of supervised learning tasks. Our objectives include developing

frameworks that:

- Efficiently leverage unlabeled data to compensate for limited labeled examples
- Process noisy inputs without relying on extensive preprocessing steps
- Align representation learning with downstream task requirements rather than generic reconstruction goals
- Enable effective knowledge transfer across tasks while maintaining robustness to overfitting
- Function within reasonable computational constraints for practical deployment
- Harness complementary information from multiple data modalities to enhance model resilience and performance

By pursuing these objectives through an integrated approach, this thesis contributes to advancing machine learning capabilities in challenging real-world environments. The resulting methodologies offer solutions that transcend specific application domains and provide broadly applicable techniques for scenarios where traditional deep learning approaches fail due to data limitations.

1.3 Scope

This thesis centers on three key application domains: wireless communication, few-shot learning, and semi-supervised representation learning. In wireless communication, it addresses the classification and denoising of modulation signals under varying noise conditions, leveraging multimodal representations such as time-domain signals and constellation diagrams along with noise as a modality. In few-shot learning, it focuses on enhancing

generalization to new tasks with minimal labeled examples. In semi-supervised learning, it explores improved representation learning and pseudo-labeling techniques that maximize unlabeled data utility while reducing computational resource requirements. These domains are interconnected through shared challenges of limited labeled data, with the approaches developed for semi-supervised learning serving as bridges that enhance both wireless communication and few-shot learning performance. Although these are the primary areas of exploration, the techniques developed here hold potential for broader applications in other fields facing similar data limitations.

1.4 Contributions

This thesis presents seven key papers, organized into two main categories—wireless communication and few-shot learning—with an additional contribution in semi-supervised learning that connects both domains. These works collectively provide flexible, data-efficient solutions to pressing machine learning challenges.

1.4.1 In Wireless Communication

- **NMformer: A Transformer for Noisy Modulation Classification in Wireless Communication:** Introduces a Vision Transformer-based model that classifies modulation signals using constellation diagrams, achieving high accuracy across diverse signal-to-noise ratios with minimal fine-tuning.

- **DenoMAE: A Multimodal Autoencoder for Denoising Modulation Signals:** Proposes a self-supervised multimodal autoencoder to denoise modulation signals, utilizing multiple representations of the same signal data to extract additional information. This approach reduces reliance on labeled data and boosts classification

performance by exploiting the strengths of each modality.

1.4.2 In Few-Shot and Meta-Learning

- **BEpiC: Binary Episodes for Meta-Learning Towards Better Generalization:** Presents a method to optimize episode generation in meta-learning, enhancing generalization in one-shot and few-shot classification tasks.

- **MetaRep: Improving Meta-Learning Accuracy by Learning Episodic Representation:** Develops a framework that learns unsupervised representations within episodes, improving meta-learning performance with minimal labeled data.

- **Meta-Task: A Method-Agnostic Framework for Learning to Regularize in Few-Shot Learning:** Introduces a regularization approach using auxiliary tasks to prevent overfitting in few-shot learning, adaptable to various meta-learning architectures.

1.4.3 In Semi-Supervised Learning

- **Maximizing Unlabeled Data Utility with Improved Representation Learning and Pseudo Labeling:** Proposes a technique to enhance representation learning using unlabeled data and pseudo labeling, achieving strong accuracy with smaller batch sizes and serving as a versatile method applicable to both wireless communication and few-shot learning.

These contributions collectively push the boundaries of machine learning by offering innovative, practical solutions to data-constrained scenarios.

1.5 Structure

This thesis is organized into five chapters, designed to guide the reader from specific challenges to broadly applicable solutions:

- **Chapter 1: Introduction:** Presents the challenges of machine learning in data-constrained environments, with focus on wireless communication and few-shot learning. Provides essential background on representation learning approaches, articulates research motivation and objectives, and outlines the thesis contributions and organization.

- **Chapter 2: Robust Classification Methods for Wireless Communication:** Explores the contributions of NMformer and DenoMAE focusing on modulation classification and denoising. Each section begins with relevant background and related work specific to wireless communication challenges, followed by methodology details and comprehensive experimental results demonstrating performance improvements in wireless signals processing.

- **Chapter 3: Enhancing Generalization in Few-Shot Learning:** Details BEpiC, MetaRep, and Meta-Task, highlighting advances in generalization and regularization. The chapter incorporates essential background and prior approaches in meta-learning and few-shot learning contexts, along with experimental evaluations validating the effectiveness of each proposed technique across standard few-shot benchmarks.

- **Chapter 4: Unlabeled Data Utilization through Semi-Supervised Learning:** Examines the semi-supervised approach and its cross-domain applicability, prefaced by background on semi-supervised learning methods and their current limitations. This chapter presents experimental evidence showing how the proposed methods maximize unlabeled data utility while reducing computational requirements.

- **Chapter 5: Conclusion and Future Directions:** Summarizes the research, underscores its impact, and outlines potential future research paths.

This structure ensures a clear progression from domain-specific issues to generalizable innovations, with each technical chapter containing its own background, related work, methodology, and experimental validation sections to provide comprehensive context for the contributions presented.

Chapter 2

Robust Classification Methods for Wireless Communication

2.1 Introduction

Modern wireless communication systems operate in increasingly congested spectral environments, creating significant challenges for reliable signal processing and classification. These systems must adapt to variable noise conditions, limited spectrum availability, and diverse transmission schemes while maintaining high performance. Modulation classification—the task of identifying the modulation scheme of a received signal—represents a fundamental challenge in this domain, with applications ranging from cognitive radio to security monitoring and interference management. However, conventional approaches often struggle with low signal-to-noise ratios (SNRs), limited training data, and feature representation issues that hamper performance in real-world deployments.

This chapter presents novel approaches to address these challenges through advanced

representation learning and robust classification techniques. We explore three complementary contributions: (1) NMformer, a transformer-based architecture that leverages constellation diagrams for resilient modulation classification across diverse noise conditions; (2) DenoMAE, a multimodal autoencoder that jointly processes time-domain signals and constellation representations to improve denoising and classification; and (3) DenoMAE2.0, which enhances representation learning through local patch classification strategies. Each method approaches the core challenges from a different perspective, collectively addressing the limitations of conventional techniques while maintaining computational efficiency.

Our work demonstrates that by reimagining how wireless signals are represented and processed, significant performance improvements can be achieved even with limited labeled data and in high-noise environments. Through careful experimental validation on standard wireless communication benchmarks, we establish the effectiveness of these approaches and their potential impact on real-world wireless systems. The methods presented in this chapter not only advance the state of the art in modulation classification but also contribute transferable insights to the broader field of representation learning for signal processing.

2.2 Automatic Modulation Classification in Wireless Communication

In today's increasingly connected world, wireless communication has become the foundation of modern life. From smartphones and Wi-Fi to satellite systems and military radios, the seamless exchange of data over the airwaves is a remarkable technological achievement. A crucial but often overlooked part of this process is understanding how information is encoded onto signals — a task that becomes particularly important when the modulation

scheme of a signal is unknown or rapidly changing. This is where Automatic Modulation Classification (AMC) comes into play [17].

At its core, AMC is the process by which a wireless receiver determines the modulation type of a received signal without prior knowledge. Modulation is the technique used to encode data onto a carrier wave — altering its amplitude, frequency, or phase to represent digital or analog information. The ability to automatically identify this modulation is essential in many non-cooperative or dynamic communication scenarios, where the receiver has limited information about the signal's origin or format [18].

In traditional communication systems, the transmitter and receiver are designed to operate with a shared set of parameters, including the modulation scheme. However, this assumption does not hold in many real-world applications. For instance, in military or surveillance contexts, a system might intercept signals from unknown sources. Similarly, cognitive radios — smart devices that dynamically access available spectrum — must identify and adapt to the modulation schemes of nearby transmissions to avoid interference [19]. In these cases, AMC enables the receiver to make sense of unfamiliar signals quickly and reliably.

AMC also plays a vital role in spectrum monitoring and management. As more devices compete for limited wireless bandwidth, understanding how that spectrum is being used becomes increasingly important. Regulators and service providers use AMC to analyze traffic patterns, detect anomalies, and ensure fair usage across frequency bands. Moreover, as networks grow more heterogeneous, incorporating different types of devices and standards, AMC helps maintain interoperability by allowing systems to adapt to each other's communication styles.

Despite its benefits, implementing AMC is not without challenges. Wireless environments are notoriously unpredictable — signals often encounter noise, fading, reflections,

and other distortions as they travel. This makes it harder for a receiver to accurately identify the modulation, especially under low signal-to-noise conditions [20]. Additionally, real-time classification requires systems that are both fast and resource-efficient, which can be a constraint for mobile or embedded devices.

Nonetheless, advances in signal processing and artificial intelligence have significantly improved the performance and reliability of AMC systems. With the rise of machine learning, particularly deep learning, modern AMC frameworks are becoming more robust to environmental variations and capable of handling a wider range of signal types [21, 22]. These developments are pushing the boundaries of what's possible in adaptive and intelligent communication systems.

2.3 Related Work

The field of automatic modulation classification has evolved significantly over the past decades, transitioning from traditional statistical methods to sophisticated machine learning approaches. This section examines the historical progression and current state of modulation classification techniques, with emphasis on their application to wireless communication systems operating in challenging environments. We review both conventional approaches that rely on expert-designed features and contemporary deep learning methods that automatically extract relevant representations. Special attention is given to recent advances that address the persistent challenges of noise robustness, limited training data, and efficient feature extraction in wireless communication systems.

2.3.1 Traditional Modulation Classification Approaches

Early research in AMC predominantly focused on two main paradigms: likelihood-based (LB) methods, which aim for statistical optimality, and feature-based (FB) methods, which prioritize computational simplicity and practicality by extracting discriminative signal characteristics.

Likelihood-Based (LB) Approaches. Early automatic modulation classification (AMC) systems formulated the modulation recognition problem as multiple-hypothesis testing, selecting the modulation scheme that maximizes the likelihood of observed baseband samples [23, 24]. The maximum-likelihood classifier (MLC) achieves Bayes-optimal performance when complete signal and channel parameters are known [23]. To address practical scenarios with unknown parameters, researchers developed variants including average (ALRT), generalized (GLRT), and hybrid likelihood-ratio tests that estimate unknown parameters through marginalization or plug-in estimates [24].

Despite their theoretical elegance, likelihood-based methods face significant implementation challenges in real-time radio systems. These limitations include: (1) combinatorial complexity when searching across unknown phase, timing, noise variance, and symbol sequences; (2) dependency on accurate channel statistics; and (3) substantial performance degradation under model mismatch or non-Gaussian interference conditions.

Feature-based (FB) approaches. Feature-based (FB) approaches aim to reduce the complexity of likelihood-based (LB) methods by extracting low-dimensional, discriminative statistics, which are then classified using techniques such as thresholding, decision trees, or support vector machines (SVMs). Among these, higher-order cumulants are widely utilized; notably, the hierarchical fourth-order cumulant classifier developed by Swami

and Sadler remains a benchmark, offering robust performance in low signal-to-noise ratio (SNR) environments due to the property that all higher-order cumulants of Gaussian noise vanish [18]. Cyclostationary statistics exploit periodic correlations introduced by the symbol rate or carrier frequency and are resilient to unknown timing and phase offsets [25].

Other handcrafted descriptors, such as instantaneous amplitude/phase, wavelet-domain features, and constellation density metrics, have been proposed [26, 27]. However, FB methods are considered sub-optimal because the manual feature extraction process can discard useful information, is sensitive to channel variations, and often requires re-engineering for each new air-interface.

2.3.2 Deep Learning for Modulation Classification

The shortcomings of LB and FB methods, including their heavy computational overhead and fragile hand-crafted feature pipelines, motivated the adoption of deep learning (DL) approaches for AMC. By directly learning hierarchical representations from minimally processed baseband signals (e.g., IQ samples), DL methods aim to overcome the bottlenecks inherent in LB and FB paradigms.

Early DL research was dominated by convolutional neural networks (CNNs). O'Shea and Corgan showed that a shallow CNN fed with raw IQ vectors or constellation-image tensors can outperform classical FB techniques, especially at low SNR [28]. Follow-up work deepened these architectures—adding residual connections or squeeze-excitation blocks—to create more expressive yet still convolutional models [29]. To capture temporal dynamics that CNNs may miss, *recurrent* models such as LSTM- or GRU-based classifiers were explored, either standalone or in hybrid CNN-RNN stacks; sequential processing improved recognition of long-range dependencies and yielded further accuracy gains [30].

Despite the performance gains delivered by deep architectures, DL-based AMC still

encounters three recurring obstacles: vanishing or unstable gradients that hamper the optimisation of very deep networks on long IQ sequences, prompting the use of residual and sequence-gated remedies [31]; chronic data scarcity, since assembling large, labelled waveform corpora across diverse channels is costly, leading researchers to rely on aggressive augmentation, synthetic data generation, and transfer-learning pipelines to exploit unlabeled signals [32, 33]; and stringent edge-deployment constraints, because state-of-the-art models often exceed the latency, memory, and power budgets of IoT or UAV radios, motivating lightweight architectures that prune parameters, quantise weights, or embed efficient attention blocks while preserving accuracy [34].

2.3.3 Recent Advances in Wireless Communication

Driven by the growing complexity of wireless environments, recent work has adapted more expressive neural architectures—originally devised for natural–language and vision tasks—to automatic modulation classification (AMC). Transformers were first ported to raw IQ sequences after their success in natural-language processing; the self-attention mechanism captures long-range dependencies that elude local convolutions, yielding sizeable gains at low SNR [2, 35]. Vision Transformers (ViT) extend this idea to two-dimensional signal representations: constellation diagrams and spectrograms are treated as patch sequences so that global spatial structure can be modelled via attention, improving robustness to noise-induced distortion [36, 37]. In parallel, Graph Neural Networks (GNNs) have been explored for AMC by casting samples or spectral components as graph nodes and learning over their relational topology, an approach shown to enhance classification under multi-path interference and cross-modality fusion settings [38, 39].

Recognising the complementary inductive biases of different backbones, researchers

have proposed hybrid designs that combine CNNs for local feature extraction with Transformers or RNNs for global or temporal reasoning, and even GNN layers for relational aggregation [35, 40]. Such composites aim to exploit spatial, sequential and structural cues simultaneously, delivering state-of-the-art accuracy across diverse channel conditions.

Alongside the push for accuracy, a parallel line of inquiry targets lightweight AMC suitable for edge deployment. Techniques range from depth-wise separable convolutions and efficient attention blocks to parameter pruning, weight quantisation and knowledge distillation; custom networks such as MobileRaT, MobileAmcT and other mobile-ViT variants demonstrate that meaningful reductions in FLOPs and model size can be achieved with minimal loss in accuracy [41, 42, 43]. Balancing these resource constraints with classification performance remains a central challenge for real-time, on-device AMC.

2.4 Semi-Supervised Learning Approaches

As purely supervised approaches face persistent challenges due to the scarcity and cost of labeled wireless-signal datasets, semi-supervised learning strategies have gained prominence in automatic modulation classification (AMC). These methods combine limited labeled data with abundant unlabeled samples to learn robust, discriminative representations suitable for downstream classification tasks.

Contrastive learning has recently emerged as promising solutions to the pervasive scarcity of labeled data in automatic modulation classification (AMC). Inspired by advances such as SimCLR [44] and MoCo [45] from computer vision, contrastive methods create supervisory signals by pulling representations of augmented views from the same input closer while pushing apart representations of different instances [32]. When adapting this strategy to AMC, augmentations typically involve signal perturbations like noise addition, frequency shifts, phase offsets, or time-segment shuffling, thus encouraging learned

representations to remain invariant to common wireless-channel variations [33]. While these methods effectively leverage unlabeled data, their success strongly depends on carefully designed augmentation policies and informative negative-sample selection, posing particular challenges in highly noisy wireless environments [32, 33].

Representation learning approaches, particularly autoencoders (AEs) and variational autoencoders (VAEs), provide another semi-supervised pathway by focusing on learning robust latent representations of signal data. AEs achieve this through reconstruction objectives, compressing input signals into bottleneck latent codes, whereas VAEs introduce probabilistic constraints on the latent space to encourage structured and noise-resistant representations [46]. Applied within AMC, these models typically serve dual purposes: extracting compressed signal representations useful for downstream classification, and performing implicit signal denoising by reconstructing clean waveforms from noisy inputs [47, 48]. Nevertheless, standard AE and VAE objectives prioritize reconstruction rather than class separability, potentially limiting their discriminative power for modulation classification tasks [47]. This limitation spurred the shift towards Self-Supervised Learning (SSL), which uses pretext tasks on unlabeled data to learn more discriminative representations. SSL methods, often employed in a pre-training and fine-tuning paradigm, leverage vast amounts of unlabeled signal data to learn robust features, subsequently improving classification performance with fewer labeled examples.

A more recent approach in representation learning is learning two variants of the same representation, through augmentation or distortion to the inputs. This strategy eliminates the need for negative samples and make the learning process faster and more effective. The two representations are then compared using a consistency loss function, which encourages the model to learn meaningful features that are invariant to the augmentations applied. This approach has shown promise in various domains, including image classification and

natural language processing, and is now being explored in the context of AMC [49]. Non-contrastive methods like BYOL [50] and SimSiam [51] avoid the need for explicit negative pairs, using architectural or operational asymmetries (e.g., momentum encoders, stop-gradients) to prevent representational collapse. Barlow Twins [52] offers another approach, focusing on reducing redundancy within the learned feature vectors. A critical challenge across all SSL methods when applied to AMC is the design of effective, signal-specific data augmentations – transformations that alter the signal without destroying its core modulation identity [53]. Unlike image data where standard augmentations are well-established, finding equivalent transformations for complex-valued time-series signals requires domain expertise and is an active area of research [54]. Despite this challenge, SSL holds significant promise for enhancing AMC by learning robust, discriminative features from abundant unlabeled wireless data [55].

Masking strategies have increasingly become integral within semi-supervised AMC frameworks, driven by the notable success of masked autoencoder (MAE)-based self-supervised techniques originally developed for computer vision and natural-language processing tasks [56, 2]. Masking methods deliberately obscure portions of input signals, tasking neural encoders and lightweight decoders with reconstructing missing segments, thereby implicitly learning robust contextual dependencies within the data [56]. For AMC specifically, these strategies have been adapted across diverse signal domains including time-domain IQ samples, frequency-domain spectral components. Niizumi et al. [57] applied spectrogram masking techniques that obscure frequency-time regions, forcing the model to learn spectral relationships that persist even when portions of the signal are corrupted. Medhat et al. [58] extend these ideas to frequency-domain features, demonstrating that masking strategies can be effective across different signal representations. These approaches share conceptual similarities with BERT in natural language processing and MAE

in computer vision, adapting self-supervised pretraining paradigms to wireless communication challenges. Extensions incorporating auxiliary classification tasks during masking-based pre-training further refine learned representations, enhancing discriminability and effectively balancing global reconstruction objectives with local modulation-specific features [56].

2.4.1 Multimodal Learning Based Methods

Multimodal representation learning seeks to build models that integrate information from diverse sources, such as vision, language, audio, and sensor data like radio frequency (RF) signals [59], aiming for a more comprehensive understanding than unimodal approaches. The core motivation lies in leveraging complementary information across modalities to enhance model accuracy, robustness, particularly in noisy or data-scarce scenarios [60], and transferability. Key objectives involve bridging the 'heterogeneity gap' by learning joint or coordinated representations [61], enabling cross-modal translation, and facilitating effective fusion for downstream tasks. Common strategies range from simple feature concatenation or element-wise operations to sophisticated attention mechanisms, notably cross-modal attention within transformer architectures, which implicitly learn alignments and interactions [62]. A dominant paradigm involves learning joint embedding spaces, often via contrastive objectives applied to large-scale paired datasets. Works like CLIP [63] and ALIGN [64] demonstrated that training image and text encoders contrastively on web-scale data yields powerful, transferable representations capable of impressive zero-shot generalization, highlighting the efficacy of natural language supervision.

These principles find application in specialized domains such as signal processing, particularly for Automatic Modulation Classification (AMC), which aims to identify the modulation scheme of received signals [65]. Multimodal AMC leverages diverse signal

representations—including raw I/Q sequences, constellation diagrams, time-frequency distributions, or spectral correlation functions [66]—to improve classification accuracy, especially in low signal-to-noise ratio (SNR) conditions where traditional methods falter [67]. Specific frameworks adapt general techniques: DeepSIG employs hybrid architectures for heterogeneous signal inputs [65], MCLRL combines multi-domain contrastive learning with reinforcement learning for few-shot AMC [66] uses a multimodal autoencoder for improving data efficiency. While offering benefits like improved performance and robustness, multimodal learning faces challenges including increased model complexity, effective alignment and fusion across heterogeneous data types, handling missing modalities [68], and mitigating modality dominance or imbalance [69]. Efficient adaptation of large pretrained models using techniques like MMLoRA [70, 71] and generative approaches like MVAE [72] or SMVAE [73, 74] for modeling joint distributions and handling missing data represent ongoing research directions addressing these practical hurdles.

2.4.2 Constellation Diagram Analysis

Constellation diagrams, which plot the complex baseband symbols in the I/Q plane, provide a visually intuitive representation of modulation schemes. The distinct geometric patterns formed by symbol points offer discriminative features for classification [75]. Early feature-based methods attempted to capture these patterns using statistical moments, density metrics, or geometric shape descriptors [76]. However, these handcrafted features often proved sensitive to noise and channel impairments like phase and frequency offsets.

The advent of deep learning enabled treating constellation diagrams as images, allowing CNNs to automatically learn robust spatial hierarchies directly from the plotted points [77, 21]. This image-based approach demonstrated significant improvements over traditional feature engineering, particularly in low-SNR regimes where constellation points

become dispersed [78]. More recently, ViT architectures have been adapted for constellation analysis, leveraging self-attention mechanisms to capture global dependencies between symbol points, further enhancing noise robustness and classification accuracy compared to purely convolutional approaches [34]. Despite these advances, generating clean and informative constellation diagrams often requires accurate synchronization and channel estimation, and their performance can still degrade significantly under severe channel distortion or very low SNR conditions, motivating research into multimodal approaches that combine constellation views with other signal representations like time-domain IQ sequences [79, 80].

2.5 Proposed Methods

Addressing the identified gaps in modulation classification, particularly concerning noise robustness and data efficiency, this thesis introduces three novel methods. Each method leverges recent advances in deep learning, specifically transformers and autoencoders, but applies them in distinct ways to tackle the challenges inherent in wireless signal processing. The following subsections detail these contributions: NMformer and DenoMAE.

2.5.1 NMformer: A Transformer for Noisy Modulation Classification

Modulation classification in noisy environments is challenging, often requiring complex denoising steps. NMformer addresses this by proposing a Vision Transformer (ViT) based model designed to classify modulation schemes directly from constellation diagrams, even with significant noise. Recognizing the effectiveness of ViTs on image data, we represent modulated signals as 2D constellation diagrams. NMformer is trained on a large dataset (106,800 images) to establish a base classifier, which is then fine-tuned using a

much smaller dataset (3,000 images) for specific SNR tasks.

This approach demonstrates strong performance in both in-distribution and out-of-distribution scenarios. When fine-tuned and tested on high-SNR in-distribution classes, NMformer surpasses the base classifier accuracy by 4.67%. Notably, the fine-tuned model also achieves higher accuracy than the base classifier on low-SNR tasks and shows effectiveness on unseen data from out-of-distribution classes. Extensive experiments confirm NMformer's robustness across a wide range of SNRs without needing explicit denoising, offering a computationally efficient solution for noisy modulation classification.

2.5.2 DenoMAE: A Multimodal Autoencoder for Denoising Modulation Signals

DenoMAE introduces a novel multimodal autoencoder framework focused on denoising modulation signals during pretraining. It extends the masked autoencoder (MAE) concept by incorporating multiple input modalities—specifically, raw modulation signals and their constellation diagrams—and treating noise as an explicit input modality. This multimodal approach enhances cross-modal learning and improves denoising capabilities.

The network is pre-trained on unlabeled noisy signals and diagrams, learning to reconstruct their clean equivalents. This self-supervised pretraining allows DenoMAE to achieve state-of-the-art classification accuracy with significantly less data: requiring 10 times less unlabeled pretraining data and 3 times less labeled fine-tuning data compared to existing methods. Furthermore, DenoMAE demonstrates robust performance across various SNRs and can extrapolate effectively to unseen lower SNRs. This makes DenoMAE an efficient, flexible, and data-parsimonious solution for joint denoising and classification in noise-intensive wireless environments.

2.6 Dataset Description

The evaluation of the proposed modulation classification methods relies heavily on well-defined and representative datasets. This section details the generation process for the synthetic datasets used throughout this thesis, including the creation of constellation diagrams and the specific parameters employed. We also utilize standard benchmark datasets where applicable to ensure comparability with existing research.

2.6.1 Constellation Diagram Generation

Constellation diagrams provide a spatial representation of modulated signals by projecting complex samples $\mathbf{x} \in \mathbb{C}^n$ onto a two-dimensional complex plane $\Omega \subset \mathbb{C}$. Formally, given a modulated signal $\mathbf{x} = [x_1, x_2, ..., x_n]$, where each $x_i = a_i + jb_i$ represents an in-phase/quadrature (I/Q) sample, the constellation mapping function $\mathcal{C} : \mathbb{C}^n \to \mathbb{R}^{h \times w}$ transforms these samples into a structured representation that preserves discriminative modulation characteristics.

For computational tractability, we constrain the projection domain to a finite 7×7 complex region, discretized as:

$$\Omega = \{(u, v) \in \mathbb{C} : -3.5 \leq \text{Re}(u) \leq 3.5, -3.5 \leq \text{Im}(v) \leq 3.5\} \tag{2.1}$$

This bounded representation is optimized to capture the statistical distribution of signal points across the SNR range $\gamma \in [-10, 10]$ dB, where the spread of constellation points under additive white Gaussian noise (AWGN) can be characterized as:

$$p(x_i|s_i, \gamma) = \frac{1}{\pi\sigma^2(\gamma)} \exp\left(-\frac{|x_i - s_i|^2}{\sigma^2(\gamma)}\right) \tag{2.2}$$

Here, s_i represents the noiseless symbol and $\sigma^2(\gamma) = \frac{1}{2\gamma}$ is the noise variance as a

function of SNR. The finite support of Ω is designed to contain approximately 99.9% of the probability mass of this distribution across the operational SNR range, balancing between resolution fidelity and computational efficiency while minimizing information loss from outlier samples.

2.6.2 Data Enhancement and Representation

To maximize the discriminative power of constellation diagrams for modulation classification tasks, we formulate multiple representation techniques that transform raw constellation points into structured formats optimized for deep learning models. Let $\mathcal{X} = \{x_i\}_{i=1}^{n} \subset \mathbb{C}$ represent the set of complex signal samples. We define progressively sophisticated mapping functions that increase the information density captured from these samples.

Gray Image Generation: The basic mapping $\mathcal{G}_1 : \mathcal{X} \to \mathbb{R}^{h \times w}$ discretizes the complex plane into an $h \times w$ grid and computes pixel intensities based on sample density:

$$\mathcal{G}_1(\mathcal{X})_{j,k} = \sum_{i=1}^{n} \mathbb{I}(x_i \in \mathcal{C}_{j,k}) \tag{2.3}$$

where $\mathcal{C}_{j,k}$ represents the cell in the complex grid corresponding to pixel (j, k) and $\mathbb{I}(\cdot)$ is the indicator function. This representation, however, neglects precise sample positions within pixels and disregards sample influences on neighboring pixels.

Enhanced Gray Image Generation: We introduce an enhanced mapping $\mathcal{G}_2 : \mathcal{X} \to \mathbb{R}^{h \times w}$ incorporating spatial influence through an exponential decay model:

$$\mathcal{G}_2(\mathcal{X})_{j,k} = \sum_{i=1}^{n} P_i \cdot e^{-\alpha \|z_{j,k} - x_i\|_2} \tag{2.4}$$

where $z_{j,k} \in \mathbb{C}$ denotes the complex coordinate corresponding to pixel (j, k), P_i represents the power of sample point x_i, $\|\cdot\|_2$ is the Euclidean distance in the complex plane, and

$\alpha > 0$ is a decay parameter controlling the spatial influence. This formulation ensures that pixels capture a continuous gradient of influence from nearby samples, preserving more detailed spatial information.

Three-Channel RGB Image Generation: For transformer architectures requiring RGB inputs, we define a vector-valued mapping $\mathcal{G}_3 : \mathcal{X} \to \mathbb{R}^{h \times w \times 3}$ that generates three channels with different decay parameters:

$$\mathcal{G}_3(\mathcal{X})_{j,k,c} = \sum_{i=1}^{n} P_i \cdot e^{-\alpha_c \|z_{j,k} - x_i\|_2}, \quad c \in \{1, 2, 3\} \tag{2.5}$$

where $\alpha_1 < \alpha_2 < \alpha_3$ represents an increasing sequence of decay parameters. This creates a multi-resolution representation where each channel c captures spatial relationships at different scales, with smaller α_c values producing more diffuse distributions and larger values yielding sharper localization.

By constructing these multi-scale, spatially-aware representations, we enable transformer architectures to leverage both local and global features through their self-attention mechanisms. Empirically, we observe that these enhanced representations significantly improve classification accuracy across varying SNR regimes, particularly in challenging low-SNR environments where traditional constellation representations become highly degraded.

2.6.3 Parameters in Sample Generation

The datasets for this research encompass a set of modulation schemes $\mathcal{M} = \{M_1, M_2, \ldots, M_{10}\}$ commonly encountered in wireless communication systems. These modulation schemes are outlined in Table 2.1.

Each modulation class $M_i \in \mathcal{M}$ initially generates signals $\mathbf{x}^{(i)} \in \mathbb{C}^{L_0}$ of fixed length $L_0 = 1024$. To ensure compatibility with transformer architectures that typically require

Table 2.1: List of all modulation classes

Class Number	Modulation Technique	Abbreviation
1	4-Amplitude Shift Keying	4ASK
2	4-Pulse Amplitude Modulation	4PAM
3	8-Amplitude Shift Keying	8ASK
4	16-Pulse Amplitude Modulation	16PAM
5	Continuous-Phase Frequency Shift Keying	CPFSK
6	Differential Quadrature Phase Shift Keying	DQPSK
7	Gaussian Frequency Shift Keying	GFSK
8	Gaussian Minimum Shift Keying	GMSK
9	On-Off Keying	OOK
10	Offset Quadrature Phase Shift Keying	OQPSK

specific input dimensions, we define a transformation pipeline $\Phi : \mathbb{C}^{L_0} \to \mathbb{R}^{d \times d \times c}$ consisting of:

1. A reshaping function $\phi_1 : \mathbb{C}^{L_0} \to \mathbb{R}^{d_1 \times d_1}$ that maps the complex vector to a two-dimensional matrix $S_1 = \phi_1(\mathbf{x}^{(i)}) \in \mathbb{R}^{32 \times 32}$

2. An interpolation function $\phi_2 : \mathbb{R}^{d_1 \times d_1} \to \mathbb{R}^{d_2 \times d_2}$ that upscales the representation to $S_2 = \phi_2(S_1) \in \mathbb{R}^{224 \times 224}$

For modulation formats with inherently longer sequence lengths, e.g., GMSK with $\mathbf{x}_{orig} \in \mathbb{C}^L$ where $L > L_0$, a downsampling operator $\mathcal{D} : \mathbb{C}^L \to \mathbb{C}^{L_0}$ is applied such that:

$$\mathbf{x} = \mathcal{D}(\mathbf{x}_{orig}) = \{\mathbf{x}_{orig}[i \cdot r]\}_{i=0}^{L_0-1} \tag{2.6}$$

where $r = \lfloor L/L_0 \rfloor$ is the downsampling ratio.

All signals are sampled uniformly at sampling frequency $f_s = 200$ kHz, yielding a Nyquist bandwidth of $f_{Nyq} = f_s/2 = 100$ kHz. The complex baseband signals are subsequently corrupted with additive white Gaussian noise (AWGN) to simulate realistic channel conditions:

$$\mathbf{y} = \mathbf{x} + \mathbf{n}, \quad \mathbf{n} \sim \mathcal{CN}(0, \sigma^2 \mathbf{I}) \tag{2.7}$$

where the noise variance σ^2 is determined by the target signal-to-noise ratio $\gamma \in \Gamma = \{-10, -8, \ldots, 8, 10\}$ dB:

$$\sigma^2 = \frac{\mathbb{E}[|\mathbf{x}|^2]}{10^{\gamma/10}} \tag{2.8}$$

This controlled noise injection creates a comprehensive test corpus spanning a 20 dB dynamic range, enabling systematic evaluation of classification robustness across varying channel conditions.

2.7 Methodology Preliminaries

Before discussing our specific approaches, we outline the core architectural components shared across our three proposed methods. Each contribution—NMformer, DenoMAE, and DenoMAE2.0—builds upon Vision Transformer (ViT) architectures with specific adaptations for wireless signal processing tasks.

2.7.1 Vision Transformers for Signal Processing

The Vision Transformer (ViT) [36] represents a paradigm shift in computer vision by extending the self-attention mechanism from natural language processing to image analysis. Unlike convolutional neural networks (CNNs) that process images through local receptive fields, ViT decomposes images into fixed-size patches and processes them as a sequence, enabling global context modeling. This architecture is particularly well-suited for constellation diagram analysis in wireless communications for several reasons:

1. **Global context awareness**: The self-attention mechanism allows ViT to capture long-range dependencies between distant parts of constellation diagrams, facilitating the recognition of global modulation patterns even under severe noise conditions.

2. **Position-aware representation**: Since modulation schemes often manifest as distinctive spatial arrangements in the constellation space, the positional encoding in transformers helps preserve this critical spatial information.

3. **Adaptability to noise**: The non-local processing of transformers allows them to better distinguish between noise-induced artifacts and actual modulation features.

2.7.2 Core ViT Architecture

The Vision Transformer (ViT) architecture consists of several interconnected components that collectively enable effective processing of image data. This section details each component and its role in the overall architecture.

2.7.2.1 Patch Embedding

Given a constellation image $\mathbf{X} \in \mathbb{R}^{H \times W \times C}$ with height H, width W, and C channels, the ViT first reshapes it into a sequence of N flattened 2D patches $\mathbf{x}_p \in \mathbb{R}^{N \times (P^2 \cdot C)}$, where (P, P) is the patch resolution and $N = HW/P^2$ is the resulting sequence length. This patchification process can be expressed as:

$$\mathbf{x}_p^i = \text{Reshape}(\mathbf{X}_{[iP:(i+1)P, jP:(j+1)P, :]}), \quad i \in \{0, 1, ..., H/P - 1\}, j \in \{0, 1, ..., W/P - 1\} \tag{2.9}$$

where each patch $\mathbf{x}_p^i \in \mathbb{R}^{P^2 \cdot C}$ represents a flattened $P \times P \times C$ region of the original image.

Each patch is then linearly projected to a D-dimensional embedding space using a learnable projection matrix $\mathbf{E} \in \mathbb{R}^{(P^2 \cdot C) \times D}$:

$$\mathbf{e}_i = \mathbf{x}_p^i \mathbf{E} + \mathbf{b}_E \tag{2.10}$$

where $\mathbf{b}_E \in \mathbb{R}^D$ is a learnable bias vector. This linear projection serves as a trainable feature extraction mechanism that maps raw pixel values to a latent representation suitable for transformer processing.

2.7.2.2 Positional Embedding

Unlike convolutional neural networks, transformers process inputs as sequences without inherent spatial awareness. To incorporate spatial information, ViT adds learnable position embeddings $\mathbf{E}_{pos} \in \mathbb{R}^{(N+1) \times D}$ to the patch embeddings:

$$\mathbf{z}_0 = [\mathbf{x}_{class}; \mathbf{e}_1; \mathbf{e}_2; \cdots; \mathbf{e}_N] + \mathbf{E}_{pos} \tag{2.11}$$

where $\mathbf{x}_{class} \in \mathbb{R}^D$ is a learnable class token that aggregates global information.

The position embeddings are fully learnable parameters that encode the 2D positional information of patches. Alternative approaches include fixed sinusoidal encodings or relative positional embeddings:

$$\mathbf{E}_{pos,\text{fixed}}^{(i,j)} = \begin{bmatrix} \sin(\omega_k \cdot i/H) \\ \cos(\omega_k \cdot i/H) \\ \sin(\omega_k \cdot j/W) \\ \cos(\omega_k \cdot j/W) \end{bmatrix}_{k=1}^{D/4} \tag{2.12}$$

where i, j are the spatial coordinates and ω_k are logarithmically spaced frequencies.

2.7.2.3 Transformer Encoder Backbone

The core of ViT consists of L identical transformer encoder layers. Each encoder layer processes the sequence of embedded patches through self-attention mechanisms and feed-forward networks:

$$\mathbf{z}'_\ell = \text{MSA}(\text{LN}(\mathbf{z}_{\ell-1})) + \mathbf{z}_{\ell-1}, \quad \ell = 1 \dots L \tag{2.13}$$

$$\mathbf{z}_\ell = \text{MLP}(\text{LN}(\mathbf{z}'_\ell)) + \mathbf{z}'_\ell, \quad \ell = 1 \dots L \tag{2.14}$$

where LN denotes Layer Normalization, MSA is Multi-head Self-Attention, and MLP is a Multi-Layer Perceptron consisting of two linear transformations with a GELU non-linearity:

$$\text{MLP}(\mathbf{x}) = \text{GELU}(\mathbf{x}\mathbf{W}_1 + \mathbf{b}_1)\mathbf{W}_2 + \mathbf{b}_2 \tag{2.15}$$

with $\mathbf{W}_1 \in \mathbb{R}^{D \times 4D}$, $\mathbf{W}_2 \in \mathbb{R}^{4D \times D}$, and bias vectors $\mathbf{b}_1$, $\mathbf{b}_2$.

The multi-head self-attention operation with h heads is defined as:

$$\text{MSA}(\mathbf{Z}) = [\text{head}_1; \dots; \text{head}_h]\mathbf{W}^O \tag{2.16}$$

where $\mathbf{W}^O \in \mathbb{R}^{hD_h \times D}$ is a projection matrix and each attention head computes:

$$\text{head}_i = \text{Attention}(\mathbf{Z}\mathbf{W}_i^Q, \mathbf{Z}\mathbf{W}_i^K, \mathbf{Z}\mathbf{W}_i^V) \tag{2.17}$$

with projection matrices $\mathbf{W}_i^Q, \mathbf{W}_i^K, \mathbf{W}_i^V \in \mathbb{R}^{D \times D_h}$ where $D_h = D/h$ is the dimension per head.

The scaled dot-product attention is:

$$\text{Attention}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^T}{\sqrt{D_h}}\right)\mathbf{V} \tag{2.18}$$

This attention mechanism enables each position in the sequence to attend to all other positions, capturing global dependencies within the constellation diagram. The multi-head design allows the model to jointly attend to information from different representation subspaces at different positions.

2.7.2.4 Transformer Decoder Backbone

For generative or reconstruction tasks such as masked autoencoding, a transformer decoder processes encoded representations to reconstruct the original input. Similar to the encoder, the decoder consists of L_d layers, each containing self-attention, cross-attention, and feed-forward networks:

$$\mathbf{y}'_\ell = \text{MSA}(\text{LN}(\mathbf{y}_{\ell-1})) + \mathbf{y}_{\ell-1}, \quad \ell = 1 \dots L_d \tag{2.19}$$

$$\mathbf{y}''_\ell = \text{MCA}(\text{LN}(\mathbf{y}'_\ell), \mathbf{z}_L) + \mathbf{y}'_\ell, \quad \ell = 1 \dots L_d \tag{2.20}$$

$$\mathbf{y}_\ell = \text{MLP}(\text{LN}(\mathbf{y}''_\ell)) + \mathbf{y}''_\ell, \quad \ell = 1 \dots L_d \tag{2.21}$$

where MCA is Multi-head Cross-Attention defined as:

$$\text{MCA}(\mathbf{Q}, \mathbf{K}) = [\text{cross-head}_1; \dots; \text{cross-head}_h]\mathbf{W}^O_{cross} \tag{2.22}$$

with:

$$\text{cross-head}_i = \text{Attention}(\mathbf{Q}\mathbf{W}^Q_i, \mathbf{K}\mathbf{W}^K_i, \mathbf{K}\mathbf{W}^V_i) \tag{2.23}$$

The decoder architecture enables effective information flow from the encoder representations to the reconstruction targets, which is particularly important for denoising and masked autoencoding tasks in wireless signal processing.

2.7.2.5 Masking Strategy

For masked autoencoding tasks, a crucial component is the masking strategy that determines which parts of the input are concealed during training. Given the patch sequence $\{\mathbf{x}_p^i\}_{i=1}^N$, a binary mask $\mathbf{M} \in \{0,1\}^N$ is generated where:

$$\mathbf{M}_i = \begin{cases} 1 & \text{if patch } i \text{ is masked} \\ 0 & \text{otherwise} \end{cases} \tag{2.24}$$

The masking ratio r_m determines the proportion of patches to be masked. Various masking strategies exist:

- **Random masking**: Patches are selected uniformly at random.
- **Block masking**: Contiguous rectangular regions are masked.
- **Attention-guided masking**: Masks are generated based on attention scores from a pre-trained model.
- **Noise-level dependent masking**: Masking rates vary with estimated SNR.

For constellation diagrams, specialized masking strategies can be developed that respect the structure of modulation schemes, such as masking along decision boundaries or preserving key constellation points while masking intermediate regions.

2.7.2.6 Fine-tuning Classification Head

After pre-training with masked autoencoding or other self-supervised objectives, the model can be fine-tuned for downstream classification tasks. The classification head typically operates on the class token representation from the final transformer encoder layer:

$$\mathbf{y} = \text{softmax}(\mathbf{z}_0^L \mathbf{W}_{cls} + \mathbf{b}_{cls}) \tag{2.25}$$

where $\mathbf{W}_{cls} \in \mathbb{R}^{D \times C_{out}}$ projects the D-dimensional representation to C_{out} classes, and $\mathbf{b}_{cls} \in \mathbb{R}^{C_{out}}$ is a bias vector.

Alternatively, more sophisticated classification strategies include:

- **Mean pooling**: Averaging all patch representations before classification.
- **Attention pooling**: Using an additional learnable attention mechanism to weight patch contributions.
- **Multi-layer feature fusion**: Combining representations from multiple transformer layers.

The classification head is typically trained with cross-entropy loss:

$$\mathcal{L}_{CE} = -\sum_{c=1}^{C_{out}} y_c \log(\hat{y}_c) \tag{2.26}$$

where y_c is the one-hot encoded ground truth and $\hat{y}_c$ is the predicted probability for class c.

For modulation classification, specialized loss functions may incorporate prior knowledge about modulation hierarchies or SNR-dependent weighting to improve performance across diverse noise conditions.

2.8 Task 1: NMformer: A Transformer for Noisy Modulation Classification

2.8.1 Introduction

AMC is a critical technology within wireless communication, playing a pivotal role in cognitive radio, spectrum sensing, and interference identification. Accurately recognizing modulation schemes in a communication system facilitates more efficient spectrum utilization and enhances the adaptability and efficacy of wireless networks. Achieving successful modulation classification has posed a longstanding challenge for the research community, primarily due to various factors influencing the channels, such as ambient noise. The earlier approaches to modulation classification use traditional machine learning and deep learning networks such as convolution neural networks (CNNs) [81, 29, 82]. In the domain of modulation classification, Peng et al. [81] transformed raw modulated signals into constellation diagrams, employing these diagrams as inputs for AlexNet, a CNN-based architecture. Conversely, an alternative investigation [29] introduced MCNet, a CNN model distinguished by its utilization of multiple convolutional blocks. Notably, incorporating skip connections between these blocks effectively mitigates the issue of vanishing gradients, a common challenge in deep learning architectures. Moreover, each convolutional block is augmented with asymmetric kernels strategically crafted to capture the spatio-temporal correlations inherent within the signals under analysis.

Similarly, in a separate study detailed in [82], a CNN framework was devised for the AMC task. Here, the authors leveraged various signal representations, including constellation diagrams, ambiguity function (AF), and eye diagrams. Among these representations, empirical evaluations during testing revealed that constellation diagrams outperformed AF and eye diagrams regarding classification accuracy. Furthermore, a notable observation

emerged from the study: combining multiple signal representations, such as constellation and eye diagrams, yielded improved classification accuracy compared to individual representations.

Attention-based models such as transformers have been popular for AMC in recent years [83, 84, 85]. Vaswani et al. pioneered transformers [2], a deep learning model that excels at processing sequential data like text, speech, and DNA sequences. Transformers' main innovation is using an "attention" mechanism, which enables the model to dynamically focus on the most relevant parts of the input while producing the output. Transformer-based architectures have garnered considerable interest in AMC due to their ability to discern robust modulation features from input data [85, 86, 87]. Cai et al. [85] introduced transformers to the domain of AMC. They presented a transformer network (TRN)-based approach that surpasses conventional methods like CNNs in capturing extensive dependencies in sequential data, which is pivotal in modulation classification tasks. This makes them especially well-suited to modulation classification, where these dependencies are critical for distinguishing between different modulation schemes. The proposed method accepts preprocessed signal sequences as input and routes them to a TRN encoder. The encoder's self-attention mechanism enables it to learn long-term dependencies effectively. A multilayer perceptron (MLP) head classifies the encoded signal representation. This method has potential advantages over traditional methods, particularly in low SNR scenarios.

Kong et al. [86] improved transformer-based AMC by incorporating convolutional embedding, attention bias, and attention pooling into deep neural networks. Their approach entails first training transformer encoders on unlabeled data using contrastive learning and data augmentation, followed by fine-tuning on a small labeled dataset. Their model outperforms conventional methods by incorporating convolutional elements tailored for radio signal data, especially useful in real-world scenarios with limited labeled data. To address the challenges of applying transformers to AMC tasks with limited labeled data,

they use a deep neural network with convolutional embedding, attention bias, and attention pooling. In a complementary effort, Qu et al. [87] addressed the challenge of capturing long-range dependencies within signals by proposing a hybrid architecture combining transformers and long short-term memory (LSTM) networks. Transformers capture global correlations, whereas LSTMs are adept at handling temporal dependencies. To improve robustness against irrelevant signal characteristics, they introduce segment substitution (SS) as a new data augmentation technique. SS selectively manipulates signal segments to emphasize modulation-specific features while mitigating the influence of irrelevant factors, such as channel effects, thus augmenting the model's discriminative capacity.

2.8.2 Contributtions

Most available methods [88, 89] deal with classifying signals generated in deal conditions, meaning no noise is present. This approach is not feasible for practical use as signals often get mixed with noise through the medium. Moreover, few existing approaches [90, 91] have a solution for fine-tuning downstream tasks with a smaller dataset. To address these issues, in this study, we developed a ViT model for AMC tasks. The main contributions of this paper are as follows:

- We generated RGB constellation diagrams from modulation signals with a wide range of SNRs.

- We applied a ViT, named NMformer, to classify the modulation data. The proposed method uses the powerful self-attention mechanism to make decisions conditioned on global image characteristics in contrast to local image characteristics used in traditional CNN-based approaches. Our approach achieves high accuracy even for low SNR samples.

- We trained a base classifier and fine-tuned it for downstream tasks. The proposed model obtains higher F1 scores for all the downstream tasks.

2.8.3 Related Work

Achieving successful modulation classification has posed a longstanding challenge for the research community, primarily due to various factors influencing the channels, such as ambient noise. The earlier approaches to modulation classification use traditional machine learning and deep learning networks such as Convolution Neural Networks (CNNs) [81, 29, 82].

In the domain of modulation classification, Peng et al. [81] transformed raw modulated signals into constellation diagrams, employing these diagrams as inputs for AlexNet, a Convolutional Neural Network (CNN)-based architecture. Conversely, an alternative investigation [29] introduced MCNet, a CNN model distinguished by its utilization of multiple convolutional blocks. Notably, incorporating skip connections between these blocks effectively mitigates the issue of vanishing gradients, a common challenge in deep learning architectures. Moreover, each convolutional block is augmented with asymmetric kernels strategically crafted to capture the spatio-temporal correlations inherent within the signals under analysis.

Similarly, in a separate study detailed in [82], a CNN framework was devised for the Automatic Modulation Classification (AMC) task. Here, the authors leveraged various signal representations, including constellation diagrams, Ambiguity Function (AF), and eye diagrams. Among these representations, empirical evaluations during testing revealed that constellation diagrams outperformed AF and eye diagrams regarding classification accuracy. Furthermore, a notable observation emerged from the study: combining multiple

signal representations, such as constellation and eye diagrams, yielded improved classification accuracy compared to individual representations.

Attention-based models such as transformers have been popular for AMC in recent years [83, 84, 85]. Vaswani et al. pioneered transformers [2], a deep learning model that excels at processing sequential data like text, speech, and DNA sequences. Transformers' main innovation is using an "attention" mechanism, which enables the model to dynamically focus on the most relevant parts of the input while producing the output. Transformer-based architectures have garnered considerable interest in AMC due to their ability to discern robust modulation features from input data [85, 86, 87]. Cai et al. [85] introduced Transformers to the domain of AMC. They presented a Transformer Network (TRN)-based approach that surpasses conventional methods like Convolutional Neural Networks (CNNs) in capturing extensive dependencies in sequential data, which is pivotal in modulation classification tasks. This makes them especially well-suited to modulation classification, where these dependencies are critical for distinguishing between different modulation schemes. The proposed method accepts preprocessed IQ signal sequences as input and routes them to a TRN encoder. The encoder's self-attention mechanism enables it to learn long-term dependencies effectively. A multi-layer perceptron (MLP) head classifies the encoded signal representation. This method has potential advantages over traditional methods, particularly in low signal-to-noise ratio (SNR) scenarios.

Kong et al. [86] improved transformer-based AMC by incorporating convolutional embedding, attention bias, and attention pooling into deep neural networks. Their approach entails first training Transformer encoders on unlabeled data using contrastive learning and data augmentation, followed by fine-tuning on a small labeled dataset. Their model outperforms conventional methods by incorporating convolutional elements tailored for radio signal data, especially useful in real-world scenarios with limited labeled data. To address the challenges of applying transformers to AMC tasks with limited labeled data, they use a

deep neural network with convolutional embedding, attention bias, and attention pooling. In a complementary effort, Qu et al. [87] addressed the challenge of capturing long-range dependencies within signals by proposing a hybrid architecture combining Transformers and Long Short-Term Memory (LSTM) networks. Transformers capture global correlations, whereas LSTMs are adept at handling temporal dependencies. To improve robustness against irrelevant signal characteristics, they introduce Segment Substitution (SS) as a new data augmentation technique. SS selectively manipulates signal segments to emphasize modulation-specific features while mitigating the influence of irrelevant factors, such as channel effects, thus augmenting the model's discriminative capacity.

2.8.4 NMformer for Classification

We employed NMformer for modulation classification with a ViT backbone, capitalizing on its demonstrated effectiveness in image classification tasks. The architecture of NMformer is shown in Figure 2.1 Our implementation can be found at
https://github.com/atik666/NMformer.

2.8.4.1 Parameters Selection in Data Generation

In all our experiments, we explore ten modulation formats. The samples are generated with dimensions of 32 pixels for both height and width, equating to a sampling frequency of 200 kHz. The constellation's scale for depiction is fixed at 2.5. Furthermore, we incorporate reduced path delays of 0, 0.0004, and 0.0008 seconds. The number of filter taps employed is 8.



Figure 2.1: NMformer system sequential pipeline: starting with generating constellation diagrams from raw signals and culminating in modulation classification using a ViT architecture.

2.8.4.2 Parameters Selection for Classifier

For the NMformer, we adhere to most of the hyperparameters outlined in [5] for the network architecture. The input image size is configured to 224×224, representing RGB images. Each input image is partitioned into 16 equal square patches, which, in ViT, are regarded as tokens and processed by the transformer encoder. Each patch undergoes linear projection to the embedding dimension of 768. The ViT model comprises 12 transformer layers. The multi-head self-attention mechanism employs 12 attention heads, facilitating simultaneous focus on different input segments. The dimensionality of the hidden layers within the feedforward networks in the transformer blocks is fixed at $3,072$.

The number of output classes is set to 10 for the classification task, aligning with the ten modulation formats. We employ cross-entropy loss and an Adam optimizer with a learning

rate 0.00005. A consistent batch size of 128 is utilized across all classifiers. The base classifier undergoes training for 50 epochs, whereas the fine-tuned classifier is trained for 100 epochs. We implement model saving based on the criterion of achieving the lowest validation loss or the highest validation accuracy, satisfying either condition.

2.8.4.3 Base Classifier

For the base classifier, we consider 11 variations of SNRs ranging from 0 dB to 10 dB. Within each SNR, every training class comprises at least $1,000$ images and up to $1,100$ images. Hence, the total number of training samples amounts to $106,800$. We ensure that the validation set is generated with the same distribution as the training set, which contains samples from SNRs observed during training. Specifically, we generate samples with 4 different SNRs for validation: 0 dB, 4 dB, and 8 dB, with a total of $3,000$ samples.

During testing, we evaluate the classifier on two distinct datasets: one follows the in-sample distribution, where the data originates from the same SNRs seen during training, while the other is out-of-sample distribution data, comprising novel SNRs not encountered during training.

2.8.4.4 Fine-tuned Classifier

To refine the performance of the base classifier model for specific tasks with limited samples, we engage in fine-tuning the learned parameters. In this process, we freeze all layers of the NMformer except for the last linear layer. During fine-tuning, each SNR is associated with 100 training samples for each class, contrasting with the base classifier, which has a minimum of $1,000$ samples per class. Post-fine-tuning, we evaluate the model's performance not only on novel classes but also on novel SNRs for both the base and fine-tuned classifiers.

2.8.5 Results and Discussion

This section presents the test results derived from the base classifier trained over 100 epochs. However, it is noteworthy that the model attains its optimal performance around the 40^{th} epoch. Therefore, we save the model at this stage and evaluate its performance using the saved parameters. In our experiments, the out-of-distribution data typically presents a more challenging scenario for the classifier than the in-sample distribution. The outcomes are summarized in Table 2.2.

Table 2.2: Performance of the classifier on different settings.

Model		Base		Fine-tuned	
Sample		106,800		3,000	
		Accuracy (%)		Accuracy (%)	
Distribution Type	SNRs	In	Out	In	Out
	0 dB, 4 dB, 10 dB	71.10	-	-	-
	0.5, 1.5, 4.5 dB	-	67.48	71.60	70.51
	5.5, 7.5, 9.5 dB	-	72.12	75.77	71.87

In the first test, we evaluated the performance of the base classifier using data from the same distribution. Specifically, the test classes included SNRs of 0 dB, 4 dB, and 10 dB. The resulting test accuracy achieved in this scenario was 71.10%.

Subsequently, we conducted tests on two out-of-distribution datasets. The first dataset comprises SNRs of 0.5 dB, 1.5 dB, and 4.5 dB, where the lower SNRs pose greater challenges for classification. In this case, the obtained test accuracy is 67.48%. Conversely, the second dataset contains SNRs of 5.5 dB, 7.5 dB, and 9.5 dB, presenting less challenging classification tasks due to higher SNRs. Here, we achieved a test accuracy of 72.12%.

The challenges posed by different SNR distributions are reflected in the accuracy results, where the less challenging distribution yields higher accuracy than the base classifier

tested on all the in-distribution samples.

In the subsequent task, we fine-tune the base classifier using only a limited number of samples for specific SNRs. For the in-distribution SNRs of 0.5 dB, 1.5 dB, and 4.5 dB, we achieve an accuracy of 71.60%. Surprisingly, this surpasses the accuracy of the base classifier by 0.50%, despite the samples having lower SNRs. This result demonstrates that our model can achieve higher accuracy when fine-tuned with a few yet challenging samples.

Conversely, when tested with higher SNR samples of 5.5 dB, 7.5 dB, and 9.5 dB, the same fine-tuned classifier achieves an accuracy of 71.87%. This accuracy is higher than that of the in-distribution samples, as higher SNR samples are less challenging to classify.

Furthermore, our test on the in-distribution samples of 5.5 dB, 7.5 dB, and 9.5 dB yields the highest accuracy of all, 75.77%. On the other hand, the out-of-distribution samples with SNRs of 0.5 dB, 1.5 dB, and 4.5 dB achieve the lowest accuracy, which is 70.51%. This lower accuracy is expected since the classifier is trained on fewer noisy samples, performing better on similar samples but experiencing a drop in accuracy for noisier ones. Nevertheless, this accuracy is 3.03% higher than that of our base classifier for the same distribution, demonstrating the superiority of our fine-tuned classifier.

We present the model convergence plots illustrating the smooth convergence of our fine-tuned model. These plots showcase the convergence behavior across different SNRs, specifically at 0.5 dB, 1.5 dB, and 4.5 dB for the more challenging tasks and at 5.5 dB, 7.5 dB, and 9.5 dB for the less challenging tasks.

Although the training and validation losses closely align in the first plot, they are noticeably higher compared to the latter plot. Consequently, the model achieves relatively lower accuracy at lower SNRs. However, across both plots, the model consistently converges towards the global minima as the training progresses.



(a) Loss for 0.5 dB, 1.5 dB, and 4.5 dB SNRs.



(b) Loss for 5.5 dB, 7.5 dB, and 9.5 dB SNRs.

Figure 2.2: Loss convergence plots across different SNR settings.

In Figure 2.3, we present the confusion matrices for our base classifier and two fine-tuned classifiers. Notably, all samples were misclassified for classes OOK and 16PAM in the base classifier. However, in Figure 2.3(b), corresponding to the fine-tuned classifier, we observe a notable increase in correctly classified samples for these classes. Subsequently, in Figure 2.3(c), there is a significant further increase in the number of correctly classified samples, indicating the clear superiority of our fine-tuned classifier.

To dive deeper into class performance analysis, we compute the classifier's precision, recall, and F1 score, as shown in Table 2.3. The base classifier exhibits the lowest precision, recall, and F1 score among all classifiers. The precision, recall and F1 score values show improvement for both the fine-tuned classifiers. Notably, the fine-tuned classifier with a higher SNR achieves the highest F1 score, indicating superior performance across all evaluated metrics.

Table 2.3: Analysis of classifier performance.

Classifier	Precision	Recall	F1 Score
Base (0 dB – 10 dB)	0.6170	0.6933	0.6291
Fine-tuned (0.5 dB, 1.5 dB, 4.5 dB)	0.7188	0.7163	0.7118
Fine-tuned (5.5 dB, 7.5 dB, 9.5 dB)	0.7598	0.7577	0.7572



(a) Base classifier.



(b) Fine-tuned (0.5 dB, 1.5 dB, 4.5 dB).



(c) Fine-tuned (5.5 dB, 7.5 dB and 9.5 dB).

Figure 2.3: Confusion matrix for different classifiers.

2.8.6 Conclusion

In this study, we presented an effective model named NMformer for modulation classification in wireless communication systems leveraging a ViT model. Our proposed AMC

method achieves remarkable accuracy across diverse SNRs by training on constellation diagrams of modulation signals. We demonstrate substantial improvement in classification performance by carefully fine-tuning the base classifier with limited samples tailored to specific SNRs. Our method surpasses the baseline classifier's accuracy and exhibits superior resilience to out-of-distribution data, particularly in challenging low SNR scenarios. The efficacy of our approach is further underscored by the precision, recall, and F1 score analyses, which consistently show significant improvements in classification metrics, particularly for classes traditionally prone to misclassification. Overall, our findings underscore the potentiality of NMformer for classifying noisy modulation signals.

2.9 Task 2: DenoMAE: A Denoising Masked Autoencoder for Modulation Classification

2.9.1 Introduction

Recent deep learning approaches have shifted toward addressing the high costs and scarcity of labeled data. Self-supervised learning has emerged as an efficient solution that leverages abundant raw data during pretraining, drastically reducing labeled data requirements while maintaining strong downstream performance [92]. These methods have shown remarkable success in natural language processing [93], computer vision [94] and other domains, opening new applications in fields with limited labeled data, including communications.

Wireless communication systems face critical challenges in maintaining reliable signal classification and interpretation, particularly in dynamic and noise-laden environments. Current approaches to modulation signal classification are predominantly supervised, requiring substantial amounts of labeled data across various Signal-to-Noise Ratios (SNRs) to achieve acceptable performance [95]. These models often exhibit significant degradation

when faced with previously unseen modulation types or noise conditions that deviate from their training distribution [96]. This performance gap is striking in low SNR scenarios, where noise dominates the signal characteristics, leading to misclassifications and system failures [97]. Despite advances in deep learning architectures for communications, the fundamental challenge remains: developing models that simultaneously maintain robustness to noise variation and generalize effectively with minimal labeled data requirements.

Existing solutions have explored several directions to address these challenges. Traditional denoising techniques treat noise as an unwanted component to be filtered out, often leading to information loss in the original signal [98]. Single-modality masking approaches have shown promise in learning representations but fail to capture the complex interplay between signal characteristics and noise patterns. More recent multimodal learning approaches [99, 100] integrate data from multiple sources but typically treat noise as a distortion rather than an informative signal component. This fundamental limitation prevents these models from fully understanding the structural relationship between noise and signal modalities, restricting their ability to generalize across varying noise conditions. Additionally, most current methods require extensive labeled datasets across multiple SNR levels, making them impractical for rapidly evolving communication environments.

Our motivation stems from a key insight: noise in communication signals contains valuable structural information that enhances representation learning. By treating noise as an additional modality rather than a nuisance, we develop models that learn intrinsic relationships between clean signals and their noisy counterparts, enabling better generalization with less data. Building on this, we present DenoMAE, a multimodal autoencoder designed for communication systems that treats noise as an additional modality. This approach allows the model to generate all modalities from a single input, helping it comprehensively

understand noise across modalities while enhancing denoising capabilities and learning robust signal representations. We employ random masking to challenge the model in reconstructing missing patches, reducing computational complexity while introducing beneficial uncertainty for effective learning.



Figure 2.4: **DenoMAE Pretraining Strategy**: We apply a random 75% masking [101] (not to scale in the illustration) across all input modalities. The remaining 25% of visible patches are processed by a shared encoder, while each modality utilizes a dedicated decoder to reconstruct its masked patches. Only the encoder is reused for fine-tuning the downstream tasks.

2.9.2 Contributtions

Our contributions to DenoMAE are threefold:

- We propose a novel multimodal paradigm that incorporates noise as an additional

modality, enabling more effective pretraining on modulation signals and enhancing model resilience to noise.

- We demonstrate that our pre-trained model achieves significant improvements in classification accuracy under low SNR conditions, with accuracy gains of up to 22.1% over non-pre-trained models.

- DenoMAE outperforms traditional methods, achieving superior results while requiring only one-tenth of the unlabeled data for pretraining and one-third of the labeled data for fine-tuning, underscoring its efficiency and scalability for real-world applications.

2.9.3 Related Work

Modulation Classification: Recent advancements in deep learning have transformed AMC by enabling advanced analysis of constellation and other image diagrams. Much of the research emphasizes CNN-based architectures designed to classify modulation types while handling varying channel conditions [102]. Innovative approaches include time-frequency adaptive decomposition with hybrid neural networks that reduce model parameters while maintaining accuracy and interpretability [103]. Attention-based models like LSTMs and GRUs have evolved for processing modulation signals as time-series data [104, 105], with transformer-based architectures gaining prominence for their ability to incorporate global sequence information [86]. Transformer-deep recurrent hybrids have shown particular promises [106], while contrastive learning approaches have emerged to address generalization error and improve transferability under low SNR conditions [107]. Recent semi-supervised frameworks combine transformers with contrastive learning to overcome labeled data limitations [108]. Despite these advancements, many architectures still lack robustness across diverse noise scenarios, limiting their generalization beyond specific tasks.

Multisensory Masked Modeling: Masking large portions of the input and training the model to reconstruct or predict missing elements has become a popular self-supervised approach, especially within autoencoder-based methods. For example, BERT [109] introduced masked language modeling by masking words in sentences and training the model to predict them, a concept adapted for vision with Masked Autoencoders (MAE) [101], where image patches are masked to encourage the model to learn robust visual representations. In multimodal contexts, masked modeling extends to tasks combining text, vision, and audio, promoting cross-modal understanding. For instance, Vision-Language Pretraining (VLP) models [110] utilize masked language and vision modeling to jointly learn from masked image regions and text tokens. Additionally, image modality-centered models like MultiMAE [99] and 4M [111] have demonstrated strong performance by pretraining on multiple image modalities and enhancing inference capabilities across diverse inputs. These multimodal masking methods have demonstrated significant gains in self-supervised learning, advancing model performance in tasks that benefit from multimodal reasoning.

2.9.4 DenoMAE Architecture

DenoMAE consists of four primary components: input embedding, encoder, shared latent space, and decoder. Figure 2.4 illustrates the overall architecture. Our codes are public at `https://github.com/atik666/denoMae/tree/master`.

2.9.4.1 Input Embedding

For each modality $m \in 1, ..., n$, we represent the input as a C-channel image $X_m \in \mathbb{R}^{C \times H \times W}$. We divide each image into non-overlapping patches of size $p \times p$, resulting in $N = (H/p)^2$ patches per modality. Each patch is flattened and linearly projected to a D-dimensional embedding space:

$$E_m = [e_1^m, ..., e_N^m] + E_{pos}, \quad e_i^m \in \mathbb{R}^D \tag{2.27}$$

where E_{pos} represents learnable positional embeddings. Here, e_i^m denotes the i-th patch embedding for modality m, and N is the total number of patches per modality.

2.9.4.2 Encoder

The encoder f_{enc} is a series of L transformer blocks. We randomly mask a high proportion (e.g., 75%) of the input patches for each modality. The encoder processes the visible patches:

$$H_m = f_{\text{enc}}([e_{i_1}^m, ..., e_{i_k}^m]), \quad i_j \in \text{visible patches} \tag{2.28}$$

2.9.4.3 Shared Latent Space

To enable cross-modal learning, we project the encoded representations from all modalities into a shared latent space. We use a linear projection followed by layer normalization, LN:

$$Z_m = LN(W_m H_m + b_m) \tag{2.29}$$

where W_m is the projection matrix for modality m, H_m is the encoded representation, and b_m is the corresponding bias term.

The shared latent representation Z_m is the concatenation of all modality-specific projections: $Z_m = [Z_1; ...; Z_n]$.

2.9.4.4 Decoder

The decoder f_{dec} reconstructs the masked patches for all modalities simultaneously. It takes the shared latent representation Z_m as input and processes it through a series of transformer blocks. The output is then split into modality-specific representations and projected back to the original patch space:

$$\hat{X}_m = f_{\text{proj}_m}(f_{\text{dec}}(Z_m)) \tag{2.30}$$

where f_{proj_m} is a modality-specific projection layer.

2.9.4.5 Loss Function

We employ a multi-modal reconstruction loss that combines individual losses for each modality:

$$\mathcal{L} = \sum_{m=1}^{n} w_m \mathcal{L}_m \tag{2.31}$$

where w_m is the weight for modality m, and $\mathcal{L}_m$ is the reconstruction loss for that modality. We use the Mean Squared Error (MSE) as the reconstruction loss.

2.9.5 Fine-Tuning on Downstream Tasks

After pretraining, we adapt the encoder for downstream tasks by removing the decoder and attaching a classification head. For modulation classification, we use a two-layer multi-layer perceptron network (MLP) with ReLU activation and dropout regularization. The process begins by embedding input patches and adding positional embeddings to form x'. The encoder processes these embeddings, and we apply global average pooling (GAP) to obtain representation z. This representation passes through the classifier to produce

predictions $\hat{y}$:

$$\hat{y} = W_2(ReLU(W_1 \cdot GAP(f_{enc}(x')) + b_1)) + b_2 \tag{2.32}$$

During fine-tuning, we optimize the entire network using cross-entropy loss, with the pretrained encoder parameters updated at a reduced learning rate.

2.9.6 Experimental Setup

To evaluate the effectiveness of DenoMAE in modulation classification tasks, we conducted a series of experiments under varying signal-to-noise ratio (SNR) conditions. Our experimental methodology encompasses data preparation, model architecture configuration, pretraining strategy, and fine-tuning protocols.

2.9.6.1 Constellation Diagram Generation

Constellation diagrams provide more informative visualization for modulation classification than raw signals [112]. The generation process involves mapping signals onto a complex plane across SNR ranges of -10 dB to 10 dB. Our enhancement process involves two steps: creating a gray image that handles varying pixel densities, then developing enhanced grayscale images using an exponential decay model that accounts for sample positions and neighborhood influence. This model incorporates sample power, point-pixel distance, and decay rate parameters. For compatibility with DenoMAE's RGB input requirements, we generate three-channel images by creating distinct enhanced grayscale images from the same data samples, each with different exponential decay rates.

2.9.6.2 Parameters in Sample Generation

The dataset comprises signals from ten modulation formats, each originally of length $L_0 = 1024$. To conform to the transformer's input dimensions, signals undergo a two-step preprocessing: (1) reshaping to $\mathbf{S}_1 \in \mathbb{R}^{32\times32}$, and (2) interpolation to $\mathbf{S}_2 \in \mathbb{R}^{224\times224}$. For formats with $L_0 > 1024$ (e.g., $L_{\text{GMSK}} = 8196$), signals are initially downsampled to L_0. To match the three-channel structure of constellation images $\mathbf{I} \in \mathbb{R}^{3\times224\times224}$, $\mathbf{S}_2$ is replicated across three channels, yielding $\mathbf{S}_3 \in \mathbb{R}^{3\times224\times224}$. All signals are sampled at $f_s = 200$ kHz, ensuring consistency across modulation formats.

2.9.6.3 Parameters for DenoMAE

The DenoMAE architecture processes $n = 5$ modalities of input images $\mathbf{X} \in \mathbb{R}^{3\times224\times224}$, segmented into 16×16 patches. The model employs a transformer-based encoder-decoder structure with $d_{\text{model}} = 768$ embedding dimensions. The encoder consists of $L_e = 12$ layers, while the decoder uses $L_d = 4$ layers, both utilizing $h = 12$ attention heads. During training, a random masking strategy with $p_{\text{mask}} = 0.75$ is applied. The model is optimized using AdamW with learning rate $\eta = 10^{-4}$ over 100 epochs, using batches of size $B = 64$. This flexible architecture allows for easy adaptation to various multi-modal denoising tasks.

2.9.6.4 Finetuning Parameters

The fine-tuning task adapts the pre-trained DenoMAE model for classification across $C = 10$ classes. The encoder f_{enc} from DenoMAE, with a depth, $d_{\text{model}} = 768$, is used as a backbone, followed by a classifier head $H(\cdot)$ consisting of a two-layer MLP with hidden dimension 512 and dropout $p = 0.5$, for an input $X \in \mathbb{R}^{3\times224\times224}$. The model is trained for $N_{\text{epoch}} = 150$ epochs using Adam optimizer with learning rate $\eta = 10^{-4}$ and batch size $B = 32$. Training data undergoes normalization but no augmentation.

2.9.7 Results and Discussion

This section presents a comprehensive analysis of DenoMAE's performance across various signal-to-noise ratios and modulation schemes. We examine the model's reconstruction capabilities during pretraining, classification accuracy during fine-tuning, and comparative performance against baseline approaches. Our analysis particularly focuses on the performance improvements in low SNR environments, which represent the most challenging scenarios for modulation classification in real-world applications. Additionally, we investigate the data efficiency of our approach compared to traditional supervised methods.

2.9.7.1 Pretraining Performance

The pretraining effectiveness of DenoMAE was evaluated using $10,000$ unlabeled signal samples across five modalities. We used 100 constellation samples equally distributed across classes as validation data during pretraining. Visual inspection of the denoised constellation diagram outputs (Figure 2.5) demonstrates strong reconstruction capabilities, particularly for samples in the first two rows where the model successfully removes noise while preserving signal characteristics. While reconstruction quality slightly diminishes for samples in the last row, the overall shape and pattern retention remain sufficient for downstream tasks.

2.9.7.2 Impact of SNRs

In fine-tuning, we utilized a labeled dataset comprising of constellation images evenly distributed across classes. The dataset was partitioned into $1,000$ training images, 100 validation images, and 100 testing images, with 10 classes: 4ASK, 8ASK (Amplitude Shift



Figure 2.5: Denoised outputs on constellation diagrams at different SNRs.

Keying), 4PAM, 16PAM (Pulse Amplitude Modulation), CPFSK (Continuous Phase Frequency Shift Keying), DQPSK (Differential Quadrature Phase Shift Keying), GFSK (Gaussian Frequency Shift Keying), GMSK (Gaussian Minimum Shift Keying), OOK (On-Off Keying), OQPSK (Offset Quadrature Phase Shift Keying). The impact of SNR on classification performance reveals DenoMAE's robust noise resilience. As shown in Figure 2.6, the pre-trained model achieves 77.50% accuracy even at -10 dB SNR, with performance steadily improving to 84.30% at 10 dB. The pretraining advantage is most pronounced

in challenging low-SNR conditions, demonstrating a 22.1% improvement over the non-pre-trained baseline at -10 dB. This performance gap gradually narrows at higher SNRs, suggesting that pretraining is particularly valuable for learning noise-robust features.



Figure 2.6: Classification accuracy for constellation diagrams at different SNRs.

2.9.7.3 Effect of Masking Ratio

We investigated the impact of masking ratio during pretraining on downstream classification. As shown in Figure 2.7, masking ratio significantly influences performance, with accuracy rising from 79.6% at 10% masking to peak at 83.5% with 75% masking, before declining to 81.4% at 80% and 79.0% at 90% masking. This pattern indicates moderate to high masking ratios (60-75%) compel the model to learn more robust features by reconstructing substantial missing information. Extremely high ratios (>80%) provide insufficient context for effective reconstruction, while low ratios (<40%) fail to sufficiently

challenge the model. The optimal approach thus involves masking a significant but not overwhelming portion of input data.



Figure 2.7: Effect of masking ratio on fine-tuning accuracy.

2.9.7.4 Extrapolation on Out-of-bound SNRs

DenoMAE demonstrates impressive extrapolation capabilities when evaluated on SNR conditions significantly outside its training range. Although trained only on SNR levels above -10 dB, the model continues to deliver meaningful reconstruction performance at challenging SNR levels between -11 dB and -20 dB. As shown in Figure 2.8, DenoMAE effectively denoises highly noisy input constellation diagrams, making the first two samples visually recognizable. The final sample, while impacted by extreme noise, still approximates the outer shape of the ground truth.



Figure 2.8: Extrapolation-ability of DenoMAE on out-of-bound lower SNRs.

2.9.7.5 Ablation Study on Modality Impact

Our shared encoded space enables complementary information from different modalities to enhance each other through cross-modal knowledge transfer. When one modality (e.g., constellation diagrams) is severely corrupted by noise, the model can leverage information from the other modalities (e.g., signals) through this integrated representation. By aligning different views of the same signal in a common space, the model learns to distinguish between noise artifacts and true signal characteristics, significantly improving denoising performance.

Table 2.4: Performance Comparison Across Different Modalities

Constellation		Signal		Noise	Test Accuracy (%)
Clean	Noisy	Clean	Noisy		
✓					81.30
✓	✓				81.90
✓	✓	✓			83.20
✓	✓	✓	✓		83.30
✓	✓	✓	✓	✓	83.50

Our ablation study on modality impact, detailed in Table 2.4, reveals the effectiveness of the multimodal approach. The full model with five modalities (noisy image, noisy signal, noiseless image, noiseless signal, and noise) achieves 83.50% accuracy. Performance degrades gracefully as modalities are removed, with even the single-modality version maintaining 81.30% accuracy. This suggests that while additional modalities contribute to performance gains, the model maintains robust performance even with reduced modality input, indicating efficient cross-modal learning capabilities.

2.9.7.6 Comparative Analysis

Table 2.5 presents a comparison between DenoMAE and existing modulation classification approaches. Our model achieves 83.5% accuracy at 0.5 dB SNR, outperforming AlexNet (82.8% at 2 dB), NMformer (71.6% at 0.5-4.5 dB), CNN-AMC (50.40% at -6 dB), and DL-GRF (59% at 0 dB). DenoMAE demonstrates remarkable data efficiency, requiring only 10,000 pretraining and 1,000 fine-tuning samples—an $80\times$ reduction compared to AlexNet's 800,000 samples and a $10.7\times$ reduction versus NMformer. Notably, DenoMAE maintains 77.50% accuracy even at -10 dB SNR, highlighting its robust performance in challenging noise conditions.

From a computational perspective, DenoMAE has comparable model complexity to NMformer (both 85.8M parameters) with identical inference time (14.5 ms), yet delivers

11.9% higher accuracy. While CNN-AMC offers faster inference (0.13 ms) with fewer parameters (1.6M), it achieves lower accuracy and classifies only 4 modulation types versus DenoMAE's 10 classes. Similarly, DL-GRF (23.5M parameters, 10 ms inference) handles only 4 classes. These results demonstrate DenoMAE's exceptional balance between performance, data efficiency, and complexity for real-world wireless communications.

Table 2.5: Comparison of DenoMAE with other modulation classification methods

Methods	**Number of samples**		**SNR dB**	**Number of classes**	**Finetuning parameters**	**Inference time (ms)**	**Test accuracy (%)**
	Pretraining	**Fine-tuning**					
AlexNet[88]	800,000 (train)	8,000 (test)	2	8	22.5M	2.0	82.8
NMformer [113]	106,800	3,000	0.5 - 4.5	10	85.8M	14.5	71.6
CNN-AMC [78]	79,200	228,060	-6	4	1.6M	0.13	50.40
DL-GRF [75]	2,000 (train)	200 (test)	0	4	23.5M	10	59
DenoMAE (**Ours**)	10,000	1,000	0.5	10	85.8M	14.5	83.5
DenoMAE (**Ours**)	10,000	1,000	-10	10	85.8M	14.5	77.50

2.9.8 Conclusion

We presented DenoMAE, a multimodal autoencoder framework that achieves state-of-the-art performance in modulation signal denoising while requiring significantly less training data than existing approaches. Our experiments demonstrate that by incorporating multiple modalities and treating noise as an explicit modality, DenoMAE delivers superior classification accuracy and robust performance across varying SNR conditions, including extrapolation to out-of-bound low SNRs. Future work could explore its extension to diverse signal types and optimization for computational efficiency.

2.10 Overall Summary and Findings

Together, these methods offer a comprehensive toolkit for addressing AMC challenges in real-world wireless communication systems, providing solutions that are simultaneously more accurate, more data-efficient, and more robust to noise than conventional approaches.Across all three approaches, several common findings emerged. First, transformer-based architectures consistently demonstrated superior ability to capture global signal patterns crucial for modulation classification. Second, self-supervised and semi-supervised learning strategies significantly reduced the need for labeled data while maintaining or improving performance. Third, explicitly modeling and learning from noise—rather than simply trying to eliminate it—proved highly effective for building robust classifiers. Finally, the integration of multiple complementary learning objectives enhanced representation quality and downstream task performance. DenoMAE introduced a novel multimodal paradigm that treats noise as an additional modality rather than merely as a distortion. This innovative approach allowed the model to learn intrinsic relationships between clean and noisy signal representations through masked autoencoding. The pretraining-finetuning strategy proved remarkably data-efficient, requiring only 10,000 unlabeled samples for pretraining and 1,000 labeled samples for fine-tuning—a significant reduction compared to prior methods. DenoMAE achieved 83.5% accuracy at 0.5 dB SNR and maintained robust performance even at extremely challenging -10 dB SNR conditions (77.50%). The model also demonstrated impressive extrapolation capabilities, effectively denoising signals at SNR levels (-11 to -20 dB) well beyond its training range. NMformer demonstrated the effectiveness of vision transformers in directly classifying noisy constellation diagrams without explicit denoising stages. By leveraging the powerful global attention mechanisms inherent in transformer architectures, NMformer achieved robust classification performance

across diverse SNR conditions. Importantly, the fine-tuning experiments revealed that NM-former can be effectively adapted to specific SNR ranges with limited training samples, achieving up to 75.77% accuracy on high-SNR tasks and maintaining strong performance (70.51%) even on out-of-distribution low-SNR scenarios. This adaptability makes NM-former particularly valuable in real-world deployments where signal conditions may vary significantly. This chapter has presented three novel approaches to address the persistent challenges in modulation classification for wireless communication systems. Each method contributes unique solutions to the fundamental issues of noise resilience, data efficiency, and feature extraction, collectively advancing the state-of-the-art in AMC.

Chapter 3

Enhancing Generalization in Few-Shot Learning

3.1 Introduction

Few-shot learning aims to recognize novel classes when only a handful of labeled examples are available, mirroring human ability to learn from limited exposure. This paradigm typically employs meta-learning, where models ”learn to learn” by training on a distribution of tasks rather than individual examples. This chapter provides a comprehensive overview of the theoretical foundations and methodological approaches that underpin the advancements presented in our research. The unifying theme across our body of work has been the enhancement of model generalization capabilities in few-shot learning contexts, particularly when facing distribution shifts between source and target domains.

Our research trajectory begins with fundamental explorations of representation learning for few-shot tasks, progresses through the development of adaptive feature extraction mechanisms, and culminates in robust cross-domain transfer methodologies. This arc reflects the

natural evolution of addressing increasingly complex challenges in few-shot generalization: from basic representation issues to sophisticated transfer learning techniques.

The techniques and frameworks discussed in this chapter form the theoretical backbone for our three main contributions: (1) developing alignment-based methods that effectively bridge the gap between source and target domains to address cross-domain generalization challenges, (2) introducing task-conditioned feature modulation to improve model adaptability to diverse tasks, and (3) enhancing domain adaptation through novel classification and regularization techniques for few-shot learning.

By establishing this foundation, we aim to contextualize our specific contributions within the broader landscape of few-shot learning research and highlight the incremental advances that each subsequent study builds upon. The principles and methods outlined here provide the necessary background to appreciate the technical innovations detailed in subsequent chapters.

3.2 What is Few-Shot Learning or Meta-Learning?

In many real-world situations, we often learn new tasks with minimal instruction. A child can recognize a new animal after seeing just one picture. A doctor can diagnose a rare condition based on a handful of previous cases. This ability to generalize from limited information is a hallmark of human intelligence. In contrast, traditional machine learning models struggle in such situations, typically requiring thousands or even millions of labeled examples to perform well. Bridging this gap is the goal of few-shot learning and meta-learning — two rapidly growing areas in artificial intelligence [114].

Few-shot learning is a learning paradigm designed to help models generalize from only a few labeled examples. Instead of needing extensive datasets, few-shot models aim to

identify new patterns after being exposed to just one or a handful of examples. This approach is especially useful in fields where collecting large labeled datasets is difficult, such as medical imaging, scientific research, or low-resource languages [115]. By drastically reducing data requirements, few-shot learning enables AI systems to be more practical, accessible, and adaptable in the real world.

Meta-learning, often described as "learning to learn," provides the foundation for most few-shot learning approaches. It focuses on building models that can quickly adapt to new tasks by drawing on prior experience. Rather than solving a single problem, a meta-learning model is trained across many small tasks so that it can develop a kind of general-purpose adaptability [14]. This is similar to how a person becomes better at picking up new skills the more they learn — not just through direct knowledge, but by improving their ability to learn itself.

The synergy between few-shot learning and meta-learning lies in their shared goal: making AI more flexible and sample-efficient. In fast-changing environments or in domains where data is rare or expensive, such as robotics or personalized healthcare, this adaptability becomes a major advantage. A robot, for example, could be shown how to manipulate a new object with just a few demonstrations. A voice assistant could learn to recognize a user's unique speech patterns with minimal input. The possibilities are vast, and they mirror the kind of intuitive, transferable learning that defines human cognition [13].

Despite their promise, few-shot and meta-learning still face several challenges. Performance often hinges on how similar new tasks are to those the model has encountered before. If the training and testing situations are too different, generalization can suffer. Additionally, designing training tasks that prepare models for the wide variety of real-world conditions they might encounter remains an open problem. Yet, with continued research and improvements in data efficiency, interpretability, and robustness, these learning approaches are poised to play a central role in the next generation of artificial intelligence.

3.3 Related Work

This section provides a comprehensive review of the literature related to few-shot learning and meta-learning, with particular focus on generalization challenges, representation learning approaches, episode generation techniques, data augmentation strategies, regularization methods, and prominent architectural frameworks. By examining these interconnected themes, we establish the theoretical context for our research contributions and position our work within the broader academic discourse.

3.3.1 The Challenge of Generalization in Few-Shot Learning

Few-shot meta-learners frequently overfit to the idiosyncrasies of their meta-training tasks, leading to poor transfer even within the same domain [116, 117]. Traditional regularizers such as weight decay or dropout offer limited mitigation, since the model may still learn task-specific shortcuts rather than broad inductive biases. To address this, meta-regularization techniques have been proposed: perturbing the inner-loop gradients to enforce flat minima—analogous to Sharpness-Aware Minimization—improves robustness against task shifts [118]. Similarly, adversarial meta-learning frameworks generate challenging support-query pairs during training, effectively stress-testing the learner's adaptation mechanism and reducing meta-overfitting [119]. Despite these advances, achieving reliable performance under distributional drift—when meta-test tasks differ significantly from those seen in meta-training—remains an open problem, motivating ongoing work on domain-aware and uncertainty-guided meta-training strategies [120, 121].

3.3.2 Representation Learning for Meta-Learning

Effective few-shot adaptation hinges on learning feature embeddings that capture task-agnostic structure. Early meta-learners relied on supervised pretraining, but recent work integrates self-supervised pretext tasks directly into the meta-learning loop. For instance, clustering-based unsupervised meta-learning constructs episodes from pseudo-labels, yielding representations that transfer to downstream classes without human annotation [122]. Set-level contrastive objectives—extending SimCLR to operate over entire support–query sets—encourage the emergence of features that are both discriminative and adaptable [44]. Moreover, meta-learned representation update rules aim to jointly optimize embeddings for rapid fine-tuning, balancing reconstruction, clustering, and classification losses in a unified framework [123]. These approaches have shown significant gains on benchmarks such as Meta-Dataset, underscoring the value of end-to-end representation learning in meta-learning contexts [124, 125].

3.3.3 Strategies for Effective Episode Generation

Standard fixed-way, fixed-shot episodic sampling fails to capture the diversity of real-world tasks. The Meta-Dataset benchmark introduced by Triantafillou *et al.* samples episodes from multiple datasets with varying numbers of classes and shots, revealing that flexibility in episode construction is key to robust meta-learner performance [124]. Building on this, stochastic any-way sampling draws class counts and shot numbers from learned distributions, enabling the model to accommodate varied task complexities at test time [126]. Curriculum-based and active sampling methods further tailor episodes to the learner's current weaknesses by selecting support examples that maximize predictive uncertainty or

anticipated generalization gain [127]. In graph meta-learning, episodes generated via unsupervised node-sampling based on structural similarity empower few-shot node classification without labels [128].

3.3.4 Leveraging Data Augmentation in Meta-Learning

Data augmentation diversifies the training distribution but must be applied judiciously in meta-learning. Augmenting query samples consistently enhances evaluation robustness, whereas naive augmentation of support sets can mislead the learner about the true task structure [129]. Meta-specific approaches such as Meta-MaxUp generate multiple augmented variants of each support example and train on those yielding the highest loss, effectively hardening the meta-learner against worst-case perturbations [130]. More automated techniques—AutoAugment and RandAugment—have been adapted for meta-learning by optimizing augmentation policies jointly with meta-parameters, achieving state-of-the-art results on mini-ImageNet and tiered-ImageNet benchmarks [131, 129]. Task-level augmentation methods like MetaMix, which interpolates entire support–query tasks, further broaden the meta-training distribution and improve generalization under domain shifts [132].

3.3.5 Regularization Techniques to Combat Overfitting

Beyond augmentation, specialized regularizers tailored to few-shot regimes improve both stability and adaptability. MAML++ [133] introduces inner-loop learning-rate annealing, per-step batch-norm statistics, and gradient clipping, substantially reducing meta-training instability. Sharp-MAML [118] constrains updates to lie within flat regions of the loss landscape via sharpness-aware minimization, mitigating sensitivity to support-set noise.

In transductive settings, Laplacian Regularization [134] enforces smooth label assignments across query points, while Attentive Feature Regularization [135] selectively penalizes or promotes feature channels based on task relevance, sharpening class separation. Graph-based few-shot learners employ K-hop Neighbourhood Regularization [136] to stabilize embedding propagation in low-resource regimes, highlighting the interplay between structural priors and meta-learner robustness.

3.3.6 Prominent Meta-Learning Architectures

Meta-learning encompasses a diverse array of architectures, each with unique strengths and weaknesses. Below, we summarize some of the most influential frameworks that have shaped the field:

- **MAML** [116] learns a universal parameter initialization that can be fine-tuned in just a few gradient steps on a new task, making it highly effective for few-shot learning. MAML is model-agnostic and can be applied to any learning algorithm trained with gradient descent, enabling rapid adaptation to new tasks with minimal data. Its bilevel optimization structure has inspired numerous extensions and improvements.

- **Prototypical Networks** [13] compute class prototypes in the embedding space and classify based on nearest neighbor distances, achieving strong performance on few-shot classification tasks. By representing each class as the mean of its support embeddings, Prototypical Networks provide a simple yet powerful inductive bias for metric-based learning, and are computationally efficient during both training and inference.

- **Relation Networks** [137] learn a similarity function between support and query examples, allowing for flexible adaptation to new classes without explicit prototypes. This

approach leverages a deep neural network to model complex relationships between samples, enabling the system to learn a task-specific metric for each episode and handle more nuanced class boundaries.

- **SNAIL** [138] combines MAML with temporal convolutions to capture long-term dependencies in sequential data, enhancing performance on time-series tasks. SNAIL's architecture integrates temporal convolutions and attention mechanisms, allowing it to aggregate information across the entire support set and adaptively focus on relevant examples for each query.

- **Reptile** [139] approximates MAML's inner loop by performing multiple gradient updates on each task before averaging the parameters, reducing computational overhead. Unlike MAML, Reptile does not require second-order derivatives, making it more scalable to large models and datasets while still promoting fast adaptation.

- **Implicit MAML (iMAML)** [140] formulates inner-loop adaptation as a regularized optimization solved via implicit differentiation, allowing many adaptation steps with bounded memory use. iMAML enables deeper adaptation without the memory bottleneck of backpropagating through long unrolled computation graphs, and is particularly useful for tasks requiring extensive fine-tuning.

- **MetaOptNet** [141] replaces the classification head with a differentiable convex solver (e.g., SVM), yielding sharper decision boundaries and strong performance on mini-ImageNet. By integrating optimization-based solvers into the meta-learning pipeline, MetaOptNet can leverage powerful inductive biases from classical machine learning within a deep learning framework.

- **LEO** (*Latent Embedding Optimization*) [142] projects parameters into a low-dimensional latent space before adaptation, reducing overfitting in high-capacity models. LEO learns

to generate task-specific model parameters in a compressed latent space, improving generalization and sample efficiency, especially in high-dimensional settings.

- **ANIL** (*Almost No Inner Loop*) [143] shows that adapting only the final classification layer suffices, freezing the shared feature encoder to simplify and accelerate training. This finding highlights the importance of robust feature representations and reduces computational cost by limiting adaptation to the last layer.

- **Meta-Curvature** [144] learns full-matrix preconditioning transforms, optimizing both the direction and magnitude of gradient updates to better capture task-specific curvature. By meta-learning the curvature of the loss landscape, Meta-Curvature enables more efficient and effective adaptation, particularly in complex or highly non-convex tasks.

- **Sharp-MAML** [118] integrates sharpness-aware minimization into MAML's bilevel objective, guiding the meta-learner toward flat minima that generalize more robustly under domain shift. This approach explicitly penalizes sharp loss landscapes during meta-training, improving stability and robustness to distributional changes between meta-training and meta-testing tasks.

3.4 Preliminaries

Meta-learning frameworks require precise mathematical formulation to understand their underlying mechanisms. This section introduces the key notation and concepts that form the foundation of our work.

3.4.1 Problem Formulation

Let $\mathcal{X}$ be the input space and $\mathcal{Y}$ be the label space. In standard supervised learning, we aim to learn a function $f : \mathcal{X} \to \mathcal{Y}$ using training data $\{(x_i, y_i)\}_{i=1}^{N}$ drawn from a distribution $P(X, Y)$. In contrast, meta-learning operates on a distribution of tasks $p(\mathcal{T})$, where each task $\mathcal{T}_i$ is a learning problem with its own data distribution $P_i(X, Y)$.

3.4.2 Task Structure

Each task $\mathcal{T}$ consists of:

- A **support set** $\mathcal{S} = \{(x_j, y_j)\}_{j=1}^{|\mathcal{S}|}$ for adaptation
- A **query set** $\mathcal{Q} = \{(x_k, y_k)\}_{k=1}^{|\mathcal{Q}|}$ for evaluation

In N-way K-shot classification, the support set contains K labeled examples from each of N classes, totaling $|\mathcal{S}| = N \times K$ examples.

3.4.3 Meta-Learning Objective

The core objective of meta-learning is to find parameters θ that enable fast adaptation across the task distribution:

$$\theta^* = \arg\min_{\theta} \mathbb{E}_{\mathcal{T} \sim p(\mathcal{T})}[\mathcal{L}_{\mathcal{T}}(f_{\theta'_{\mathcal{T}}})] \tag{3.1}$$

where $\theta'_{\mathcal{T}}$ represents the adapted parameters for task $\mathcal{T}$, typically obtained through:

$$\theta'_{\mathcal{T}} = \mathcal{A}(\theta, \mathcal{S}_{\mathcal{T}}) \tag{3.2}$$

with $\mathcal{A}$ being an adaptation algorithm (e.g., gradient descent) and $\mathcal{L}_{\mathcal{T}}$ the loss evaluated on the query set $\mathcal{Q}_{\mathcal{T}}$.

3.4.4 Meta-Training and Meta-Testing

The meta-learning process consists of two phases:

Meta-training: The model learns from a collection of tasks $\{\mathcal{T}_i\}_{i=1}^{M}$ sampled from $p(\mathcal{T})$. Each task contributes to updating the global parameters θ that facilitate rapid adaptation across the task distribution.

Meta-testing: The model encounters previously unseen tasks $\mathcal{T}_{\text{test}}$ with novel classes. Using only the support set $\mathcal{S}_{\mathcal{T}_{\text{test}}}$, the model must adapt its parameters and make accurate predictions on the corresponding query set $\mathcal{Q}_{\mathcal{T}_{\text{test}}}$.

3.4.5 Episodic Training

Most meta-learning approaches employ episodic training, where each training iteration simulates the few-shot scenario the model will face during testing (see Algorithm 1):

Algorithm 1 Episodic Meta-Training

1: **for** iteration $= 1, \ldots$ **do**
2: Sample task $\mathcal{T}_i \sim p(\mathcal{T})$
3: Extract support set $\mathcal{S}_i$ and query set $\mathcal{Q}_i$
4: Adapt model: $\theta_i' = \mathcal{A}(\theta, \mathcal{S}_i)$
5: Compute loss: $\mathcal{L}_i = \mathcal{L}(\theta_i', \mathcal{Q}_i)$
6: Update meta-parameters: $\theta \leftarrow \theta - \alpha \nabla_\theta \mathcal{L}_i$
7: **end for**

This episodic structure encourages the model to develop generalizable learning strategies rather than memorizing specific class features, which is crucial for effective few-shot learning.

3.5 Proposed Methodology

In this section, we introduce the core methodologies developed to address the challenges of generalization in few-shot learning. Each proposed approach is motivated by the limitations identified in prior work and is designed to enhance adaptability, robustness, and performance in low-data regimes. We provide an overview of the underlying principles, algorithmic innovations, and practical considerations that inform our contributions. The following subsections detail the specific methods and their empirical validation.

3.5.1 BEpiC: Binary Episodes for Meta-Learning Towards Better Generalization

In practical machine learning applications, image classification often involves discerning the category to which an object belongs. In this paper, we present a novel approach called Binary Episode Classifier (BEpiC) within the context of meta-learning. BEpiC aims to optimize episode generation by strategically selecting training samples. The methodology involves training the initial class with a comprehensive set of similar images while the contrasting class is exposed to a diverse array of dissimilar images. We create highly dissimilar image sets by randomly forming multiple image clusters. Identifying the cluster centers and selecting the representative image closest to each center facilitates the determination of the among clusters. The distance of these images from the other class is then calculated. The cluster whose representative image exhibits the greatest distance is chosen as the definitive class. Our proposed method showcases significant efficacy for binary meta-learning classification across diverse classes. While our experimentation primarily focused on Model-Agnostic Meta-Learning (MAML), the adaptability of the episode generation strategy extends to a spectrum of meta-learning classifiers. Empirical findings substantiate that the proposed method attains remarkable accuracy in one-shot classification scenarios

and moderately higher accuracy in few-shot classification tasks.

3.5.2 MetaRep: Improving Meta-Learning Accuracy by Learning Episodic Representation

Meta-learning algorithms face a fundamental challenge: while they train on episodes from one distribution and test on episodes from different distributions, current approaches do not capture unlabeled representations in episodes. We present MetaRep, a novel meta-representation learning framework that learns unsupervised latent representations within episodes to address this gap. Our approach employs weakly augmented samples for the support set and strongly augmented variants for the query set, utilizing a temperature-scaled cross-entropy loss to prevent overfitting during representation learning. The learned parameters are then fine-tuned through supervised meta-learning, making MetaRep model-agnostic and capable of improving any metalearning architecture. Through extensive experiments on standard few-shot learning benchmarks, we demonstrate that MetaRep significantly improves accuracy across multiple architectures including MAML (+3.8%) and Relation Networks (+4%). Our method shows particular strength in low-data regimes, achieving state-of-the-art performance with up to 75% fewer labeled samples. Additionally, we empirically validate MetaRep's effectiveness through ablation studies and transfer learning experiments.

3.5.3 Meta-Task: A Method-Agnostic Framework for Learning to Regularize in Few-Shot Learning

Overfitting is a significant challenge in Few-Shot Learning (FSL), where models trained on small, variable datasets tend to memorize rather than generalize to unseen tasks. Regularization is crucial in FSL to prevent overfitting and enhance generalization performance. To address this issue, we introduce Meta-Task, a novel, method-agnostic framework that leverages both labeled and unlabeled data to enhance generalization through auxiliary tasks for regularization. Specifically, Meta-Task introduces a Task-Decoder, which is a simple example of the broader framework, that refines hidden representations by reconstructing input images from embeddings, effectively mitigating overfitting. Our framework's method-agnostic design ensures its broad applicability across various FSL settings. We validate Meta-Task's effectiveness on standard benchmarks, including Mini-ImageNet, Tiered-ImageNet, and FC100, where it consistently improves existing state-of-the-art meta-learning techniques, demonstrating superior performance, faster convergence, reduced generalization error, and lower variance—all without extensive hyperparameter tuning. These results underline Meta-Task's practical applicability and efficiency in real-world, resource-constrained scenarios.

3.6 Task 1: BEpiC: Binary Episodes for Meta-Learning Towards Better Generalization

3.6.1 Introduction

A fundamental task in image classification problems is to determine with high confidence whether an object belongs to a specific class. These binary classifiers have applications

in several safety-critical systems, such as self-driving cars for obstacle detection and automated visual inspection of aircraft engines for defects. For instance, autonomous vehicles must make split-second navigational decisions upon detecting an obstacle irrespective of the type of obstacle, such as a pedestrian, bike, or any other object.

On the other hand, training a binary classifier, using datasets with limited categories poses a significant hurdle. This challenge becomes apparent during testing when confronted with unfamiliar images. On the other hand, real-world scenarios often present an infinite array of new classes. Similarly, traditional supervised learning methods for multi-class classification fall short in classifying new classes without additional retraining [145].

Meta-learning and few-shot learning [146] offer promising solutions to address the challenges posed by new or unseen classes in classification problems by learning from a few samples. Most meta-learnings rely on episodic-based learning where an episode is defined as each training run involving different classes. In episodes, the training data is divided into support and query sets. The support sets train the meta-trainer classifier with a few samples for each task. The query sets, which consist of new unseen examples, evaluate the classifier's performance post-training for optimizing the meta-trainer parameters. This dynamic adjustment enhances the adaptability and generalization capabilities of the model [147], enabling it to handle new classes with limited examples effectively.

MAML is a meta-learning approach that aims to discover optimal initial parameters across task embeddings for rapid adaptation [14]. Several variants of MAML, such as Reptile [148], Meta-SGD [149], and LEO [142] are also developed recently with the common goal of achieving efficient adaptation. On the other hand, metric-based meta-learning approaches, such as prototypical [13] and relation networks [150], learn a metric space where classification is executed through distance computations and similarity, respectively, to prototype representations of each class. While meta-learning has effectively tackled the challenge of classifying new classes with minimal data, to the best of our knowledge, no

studies have specifically addressed binary classification scenarios where one class encompasses multiple categories. The Regular meta-learning episodes only contain samples of the same distribution in that particular class. Therefore, special attention needs to be paid to making it more adaptable for our specific application.

Motivated by this critical, unique, and unexplored dimension in meta-learning, in this paper, we introduce a Binary Episode Classifier (BEpiC) in the meta-learning framework. The methodology involves training the initial class with a comprehensive set of similar images while the contrasting class is exposed to a diverse array of dissimilar images. Unlike the conventional episode generation methods, referred to "Regular" episodes, BEpiC enriches variability in each training episode by selecting images with maximum class distance. Thus, BEpiC assists the meta-trainer through abundant training samples for improved selection. For binary classification, in the first class, we curate samples from the same category, while the second class is populated with samples from diverse sources distinctly dissimilar to those in the first class.

To formulate the BEpiC episodes, we randomly generated multiple data clusters containing samples from numerous distributions. We reduced sample dimensionality using Principal Component Analysis (PCA) [151] to identify each cluster's centroid. The sample nearest to the centroid was designated as the representative of its respective class. To quantify class dissimilarity, we employed the Oriented FAST and Rotated BRIEF (ORB) [152] to identify the most dissimilar representative image from the representative image of the other class, which contains only similar samples.

In addition, we integrate the "Regular" and "BEpiC" techniques, referred to as "Regular+BEpiC," to leverage the complete range of accessible data. We performed experimental studies for both episode generation techniques using Caltec256 and miniImageNet datasets. The results illustrate that the BEpiC and Regular+BEpiC techniques notably boost classifier accuracy and robustness, affirming their effectiveness in meta-learning accuracy.

3.6.2 Contributions

The main contributions of BEpiC are:

1. A novel episode generation technique for the binary meta-learning approach to assist the meta-trainer for improved classification.
2. The generation of multiple class clusters randomly.
3. The reduction in sample dimensionality to identify each cluster's centroid.
4. Quantification of class dissimilarity by using the Oriented FAST and Rotated BRIEF (ORB) approach.

3.6.3 Background and Problem Statement

This section offers a theoretical background. We initiate our discussion with an overview of the MAML classifier, followed by a comprehensive problem description.

Meta-learning aims to refine a model's initial parameters, facilitating optimal performance on a new task. This is achieved through parameter adjustments via gradient steps computed with a limited dataset. In the case of MAML, this strategy is adopted to obtain a generalized performance. MAML exhibits effectiveness across regression, classification, and reinforcement tasks. Given its superior performance, we have chosen MAML as the primary and only classifier for our work.

MAML is a meta-learning approach that is optimization-based and tries to find the initialization parameters, Θ, for fast adaptation. For a particular task $\tau_i = (D^{train}, D^{val})$, where D^{train} and D^{val} demote the train and validation support and query sets [153], MAML computes the updated parameters $\Theta_i^{'}$ by applying gradient descent, given by:

$$\Theta_i^{'} = \Theta - \alpha \nabla_{\Theta} \mathcal{L}_{\tau_i}^{train}(f_{\Theta}) \tag{3.3}$$

where α is the learning rate of the inner loop and $\mathcal{L}_{\tau_i}^{train}$ is the training loss in the inner loop. ∇_Θ is the gradient operator with respect to the model parameters Θ.

The initial parameters are used to do forward propagation on the validation set and update the meta-learning parameters via a second-order gradient descent, given by

$$\Theta \leftarrow \Theta - \eta \nabla_\Theta \sum_{\tau_i \sim p(\tau)} \mathcal{L}_{\tau_i}^{val}(f_{\Theta_i'}) \tag{3.4}$$

where η is the learning rate and $\mathcal{L}_{\tau_i}^{val}$ is the validation loss in the outer loop.

In meta-learning, conventional episode generation involves randomly selecting classes from the dataset, followed by sampling instances from those chosen classes. The inter-class or intra-class distance is never considered when generating the episodes. However, it is crucial in binary meta-classification, where a variety of samples may need to be classified against one class. On the other hand, formulating such episodes with dissimilarity is challenging since there are so many possible combinations, and calculating the distance between each sample is computationally expensive.

Therefore, the problem at hand is to generate episodes that can use the intra- or inter-class dissimilar to classify a variety of classes against one class. A solution to this problem is presented in the next section by introducing BEpiC classifier. It is important to note that our proposed approach of selecting class representatives cut down the computational expenses to a great extent.

3.6.4 Proposed Methodology

In this section, we propose a solution to the problem of episode generation along with the development of the BEpiC algorithm. The solution involves formulating the classes with the best samples selected using PCA and ORB. A visual representation of our episode

generation process is illustrated in Figure 3.1. Our implementation can be found at https://github.com/atik666/BEpiC.



Figure 3.1: Episode generation of Regular and BEpiC from the data pool. In BEpiC, we select the most dissimilar samples.

3.6.4.1 Samples Selection

Since the goal of the episode generation is to diversify the samples, sample selection identifies samples that maximize the inter-class distance, which is one of the contributions of our paper. However, computing the distance between every sample across different classes poses a substantial computational challenge, especially for large datasets. To address this,

we employ a strategy of randomly designing multiple episodes. For instance, considering a class (referred to as the "cat" class for clarity), we determine which mixture of other classes would yield the most dissimilar set.

The sample selection process involves calculating the centroid of each episode cluster. It is achieved through PCA for dimensionality reduction and mean calculation to determine the centroid. The Euclidean distance metric is then applied to identify the sample closest to the centroid, which is subsequently designated as the class representative. To streamline computations, we later only compare the most centroid images with the ones from the "cat" class. This strategic reduction in the number of comparisons contributes to managing the computational complexity of analyzing large datasets.

We employ the ORB feature-matching algorithm to assess the dissimilarity between samples from the two classes. We select the one with the highest dissimilarity score from a pool of numerous samples. In cases where multiple outputs exhibit the same lowest dissimilarity, we prioritize the first one on the list. This approach ensures we pinpoint the most dissimilar pair of samples, effectively identifying representative class instances. In the following subsection, we provide a brief description of PCA and ORB.

PCA: Given a dataset $X \in \mathbb{R}^{n \times p}$ with n observations and p variables, PCA seeks to find a set of orthogonal vectors, that capture the most variance in the data. The first step in PCA is to subtract the mean of each variable from the dataset X, resulting in,

$$X_{\text{centered}} = X - \bar{X} \tag{3.5}$$

Next, we compute the covariance matrix using the center,

$$C = \frac{1}{n-1} X_{\text{centered}}^T X_{\text{centered}} \tag{3.6}$$

We solve $CV = V\Lambda$ to get eigenvectors V and eigenvalues Λ and project the data onto

the new coordinate system $Y = X_{\text{centered}}V$. We select the top k eigenvectors to reduce the dataset dimensionality: $Y_k = X_{\text{centered}}V_k$.

The variance explained by the i-th principal component is $\frac{\lambda_i}{\sum_{j=1}^{p}\lambda_j}$, where λ_i is the i-th eigenvalue.

ORB: ORB calculates the angle intensity based on its center offset, making it suitable for determining orientation., given by

$$\mathrm{m}_{pq} = \sum_{x,y} x^p y^q I(x,y) \tag{3.7}$$

where m is referred to as the moment patch, p and q are the sequences of moments comparable to mechanical moments, and (x, y) is the pixel coordinate keypoint of image, I. The centroid can then be determined using the moment in (3.7) as

$$C = \left(\frac{m_{10}}{m_{00}}, \frac{m_{01}}{m_{00}}\right) \tag{3.8}$$

The centroid will be located using the image's pixel matrix, designated as $\{m_{00}, m_{01}, \cdots\}$. The vector is created by connecting the centroid C with the angle's center. In other words, the patch's orientation can be computed as:

$$\Theta_{orient} = arctan(m_{01}, m_{10}) \tag{3.9}$$

where Θ_{orient} is the orientation angle based on the gradients. These selected samples craft the BEpiC episodes using any dataset that contains numerous classes.

3.6.5 Dataset

We conduct experiments on two popular datasets in meta-learning, Caltech 256 [154] and miniImageNet [155]. The statistics for the two datasets can be found in Table 3.1.

Table 3.1: Statistics from the two image datasets.

Dataset	**#Classes**	**#Training**	**#Validation**	**#Test**	**#Total samples**	**#Samples/Class**
Caltech 256	256	150	56	50	30,607	at least 80
miniImageNet	100	64	16	20	60,000	600

3.6.5.1 Caltech 256

The Caltech 256 dataset is considered an enhancement over its predecessor, the Caltech 101 dataset, due to features such as larger category sizes and the inclusion of new and more extensive clutter categories [156]. This dataset is ideal for developing visual recognition and classification models, comprising 30,607 real-world images across 257 classes of varying sizes (256 object classes plus an additional clutter class). Each class includes 100 training images and 20 test images.

3.6.5.2 miniImageNet

miniImagenet, a subset derived from the extensive ImageNet dataset, is specifically tailored for few-shot learning tasks. The unique challenge posed by miniImagenet lies in its demand for machine learning models to generalize effectively with only a limited number of training examples. This dataset consists of 100 classes, each accompanied by 600 images. We allocate 64 classes for training, 16 classes for validation, and 20 classes for testing. This division ensures a balanced distribution of classes across different sets, enabling a comprehensive assessment of model performance.

The experimental evaluation and results are presented in the next sections, which employ the sampling process and dataset.

3.6.6 Experimental Evaluation

We conducted a comprehensive evaluation of our model, focusing on its test accuracy to ensure a thorough examination of its performance. We extended our analysis to encompass the accuracy of various model configurations. The evaluation employed terminologies commonly used in meta-learning research, specifically the n-way k-shot learning framework, where n-way denotes the number of classes and k-shot indicates the number of samples the classifier encounters in each training episode.

For binary classification, the number of ways is fixed as 2-way. However, we vary the k-shot classification to explore different configurations with $1, 5, 20$ values. Across all experiments, the total number of epochs is set at 10, each comprising $10,000$ training episodes and 100 test episodes.

For every input, the image size is standardized to $(84, 84, 3)$, ensuring uniformity in the dataset preprocessing. This consistent approach to experimental design allows for a thorough investigation of the model's performance under distinct k-shot scenarios, shedding light on its adaptability and effectiveness in binary classification tasks.

We experimented with two configurations: 1. exclusively utilizing the BEpiC setup and, 2. incorporating both BEpiC and Regular setups for episode generation. Our findings indicate that the BEpiC configuration exhibits superior generalization compared to the sole use of regular task generation. Moreover, a significant performance enhancement is observed when combining BEpiC with the Regular setup, particularly with increased episodes and shots in each task.

Table 3.2 provides insights into the classifier's performance on the BEpiC test set, where

the test class comprises samples from the most dissimilar classes. On the other hand, Table 3.3 outlines the classifier's performance on the BEpiC test set in conjunction with the Regular test data. Lastly, Table 3.4 provides the classifier's performance on random test sets, where both the training and test sets were designed randomly without adhering to our proposed method, implying that the largest inter-class distance was not a focal consideration. These comparative tables underscore the effectiveness and advantages of our proposed approach.

Table 3.2: Performance of the classifier on the BEpiC test dataset.

Train methods	**Test accuracy (%)**					
	Caltech 256			**miniImageNet**		
	1-shot	**5-shot**	**20-shot**	**1-shot**	**5-shot**	**20-shot**
Regular	60.50	70.90	81.05	63.50	70.80	75.25
BEpiC	**61.00**	**71.90**	**81.50**	**64.00**	**71.00**	**76.66**
Regular+BEpiC	**63.50**	**72.80**	**81.80**	**65.00**	**71.40**	**76.66**

Table 3.3: Performance of the classifier on the Regular+BEpiC test dataset.

Train methods	**Test accuracy (%)**					
	Caltech 256			**miniImageNet**		
	1-shot	**5-shot**	**20-shot**	**1-shot**	**5-shot**	**20-shot**
Regular	61.00	70.00	**81.50**	65.50	69.60	76.46
BEpiC	**62.00**	**70.40**	80.96	65.00	**70.50**	**76.70**
Regular+BEpiC	**63.00**	**71.97**	81.25	**67.00**	**71.00**	**76.83**

3.6.7 Results and Discussion

The findings from Table 3.2 provide compelling evidence supporting the superiority of BEpiC over Regular episodes in 1-shot classification scenarios. In this context, where test

Table 3.4: Performance of the classifier on the random test dataset.

Train methods	**Test accuracy (%)**					
	Caltech 256			**miniImageNet**		
	1-shot	**5-shot**	**20-shot**	**1-shot**	**5-shot**	**20-shot**
Regular	57.50	70.70	80.70	62.40	**70.20**	74.83
BEpiC (random)	**58.00**	**71.00**	**81.25**	**63.70**	70.10	**75.33**
Regular+BEpiC (random)	**61.00**	**71.30**	**81.50**	**64.90**	**71.16**	**76.23**

samples encompass any two different categories from the real world, our proposed MAML training method consistently outperforms the conventional approach for both datasets. The subsequent amalgamation of Regular and BEpiC setups results in a noteworthy 2% and 1.5% improvement in accuracy for 1-shot classifications on both datasets. This enhancement can be attributed, in part, to the doubled sample size, indicating that the classifier operates more effectively on the intended test samples in this combined arrangement. Expanding the evaluation to 5-shot and 20-shot classifications reveals a consistent trend, with Regular+BEpiC achieving the highest accuracy in all cases for both Caltech 256 and miniImageNet datasets.

The insights from Table 3.3 introduce intriguing nuances to our analysis. In the context of Caltech 256, including Regular test samples alongside BEpiC samples led to a 0.5% improvement in accuracy for the Regular classifier in 1-shot classification. This improvement is intuitively understandable, as adding Regular test samples facilitated the Regular setup's classification task. Surprisingly, the MAML classifier tested on BEpiC and Regular test samples achieved 1% higher accuracy than the previous BEpiC-only output. This seemingly counterintuitive result is clarified by recognizing the reduced challenge in classifying Regular test samples due to minimal intra-class distance. Consequently, the classifier excelled in handling Regular samples alongside BEpiC samples, resulting in higher accuracy. Notably, the 20-shot Regular Caltech 256 classification achieved the highest accuracy in

this setup, suggesting that Regular test samples favored the Regular approach in achieving higher accuracy in 20-shot scenarios. However, for 5-shot learning, a drop in accuracy across all classifiers indicates the proposed method's increased suitability when there is greater variety in test samples. For miniImageNet, Regular+BEpiC consistently achieved the highest accuracy, except in 1-shot scenarios where BEpiC achieved slightly lower accuracy, with Regular achieving a 0.5% advantage.

Table 3.4 serves as a cautionary demonstration of the repercussions of disregarding the proposed method. The outputs reveal the necessity of our proposed approach by employing random samples for training episodes, irrespective of their inter-class distance, and testing with a BEpiC setup using random samples. Lower accuracy in 1-shot learning across all outputs compared to Table 3.2 reinforces the importance of strategically selecting samples with higher inter-class distance. This trend persists in 20-shot and 5-shot Caltech 256 scenarios. However, in 5-shot miniImageNet, Regular training outperforms BEpiC (random), affirming the suitability of our proposed method, mainly when training on BEpiC samples with significant intra-class distance.

In summary, the evidence presented consistently advocates for the effectiveness of the proposed BEpiC methodology. Regular+BEpiC emerges as a robust approach, showcasing superior performance across various few-shot learning scenarios compared to conventional and random training methods.

3.6.8 Ablation Study

In our investigation of classifier performance, we systematically varied the number of clusters for the negative class to discern its impact. The choice of cluster count plays a pivotal role in influencing the selection of the most distant samples while considering computational costs. Striking the right balance is crucial for optimizing our research outcomes.

Table 3.5 showcases the classifier's performance with the negative classes drawn from 5 clusters. The results, compared against those from BEpiC in Table 3.2, are evaluated based on the change in test accuracy (%). Positive change indicates improved accuracy, while negative values signify a decline. For 5 clusters, there is a consistent drop in test accuracy across all shot learning scenarios, ranging from 0.1% to 0.66%. This implies a discernible reduction in classifier performance across various settings when employing 5 clusters.

In Table 3.6, we extend our analysis to 20 negative class clusters, observing a mixed performance outcome. While some scenarios show improvement, others exhibit marginal decreases. Factors such as multiple clusters being equidistant may contribute to the performance fluctuations. The change in accuracy spans from -0.66% to 0.27%. However, the absence of consistent accuracy improvement, coupled with a doubling of computational time, leads us to choose 10 clusters as the optimal value.

Our exploration underscores the delicate trade-off between the number of clusters, computational efficiency, and classifier performance. The choice of 10 clusters emerges as a judicious compromise, balancing enhancing accuracy and managing computational costs in our research endeavors.

Table 3.5: Performance of the classifier on the random test dataset.

5 Clusters	**Test accuracy (%)**					
	Caltech 256			**miniImageNet**		
	1-shot	**5-shot**	**20-shot**	**1-shot**	**5-shot**	**20-shot**
BEpiC	60.72	71.32	81.30	63.67	70.90	76.00
(%) change	-0.28	-0.58	-0.20	-0.33	-0.10	-0.66

Table 3.6: Performance of the classifier on the random test dataset.

20 Clusters	**Test accuracy (%)**					
	Caltech 256			**miniImageNet**		
	1-shot	**5-shot**	**20-shot**	**1-shot**	**5-shot**	**20-shot**
BEpiC	61.16	71.83	81.67	64.11	71.27	76.00
(%) change	0.16	-0.07	0.17	0.11	0.27	-0.66

3.6.9 Conclusion and Future Work

This study introduces a novel episode generation strategy for binary classification tasks that distinguish between positive and negative classes and comprise various samples. The proposed approach leverages statistical analysis to curate training episodes, emphasizing samples with the highest inter-class distance. The results underscore the proposed method's robustness in effectively identifying test samples using BEpiC episodes. Across all scenarios, the proposed method consistently outperforms classifiers trained through conventional methods, showcasing superior accuracy.

An additional enhancement to the proposed methodology involves the integration of BEpiC with Regular training samples. This hybrid approach adds robustness to the classifiers and improves accuracy. The findings emphasize the potential of combining different training setups to achieve superior performance in binary classification tasks.

This study aims to extend the classifier's capabilities to handle multi-class classification scenarios as part of future work. Additionally, efforts will be directed toward contributing to the evolution of the classifier's architecture to mitigate any overfitting issues. These advancements are expected to broaden the applicability and effectiveness of the proposed meta-learning strategy, fostering its utility in diverse classification tasks.

3.7 Task 2: MetaRep: Improving Meta-Learning Accuracy by Learning Episodic Representation

3.7.1 Introduction

Traditional machine learning (ML) algorithms require massive datasets to reach their peak performance. In addition, these algorithms also suffer if the test domain slightly deviates from the training domain. Above all, if a new class is introduced, it requires retraining from scratch. On the other hand, human learning is far more advanced as people can learn from only a few samples and distinguish a new class without seeing many examples. This is because humans use their previous experience to learn a new task. Meta-learning, a relatively new branch of ML, mimics this process to bridge the gap between ML and human learning with fewer data from different domains [157].

Most meta-learning algorithms [158, 149, 148, 159] are centered around the concept of "learning-to-learn," which involves generating tasks or episodes to discern patterns from a limited number of samples. This process entails the training and testing phases, where the samples are partitioned into support and query sets [160]. The support set aids in comprehending class representations, while the query set is utilized for inference. To train a meta-learner, batches of data (episodes in meta-learning) are generated by sampling the training data. Therefore, during training, meta-learning algorithms are exposed to a variety of classes that may not be present in the test classes. This allows ample opportunity to incorporate more classes into the training process. However, existing meta-learning approaches fail to fully exploit the potential of abundant training samples to learn episodic representations without label information [161]. This limitation stems from their reliance on labeled support sets for task adaptation. Moreover, these approaches are primarily designed around supervised learning principles, where labeled samples are necessary for learning

[162]. Consequently, the rich diversity in unlabeled data remains unused. To overcome this limitation, a more flexible representation-learning strategy is required that effectively integrates unlabeled data into the episodic learning process to improve model adaptability and performance [163].

Representation learning is a widely established way [164, 165] of boosting classification accuracy in a low-data regime. Typically, representation learning unfolds in two stages [7, 50]: unsupervised representation learning followed by supervised learning applied to the acquired parameters. However, in the context of meta-learning, where episodes are pivotal, the conventional representation learning approaches designed for batch learning may not be directly implemented in meta-learning.

To address this challenge, we introduce MetaRep, a representation-learning approach tailored specifically for meta-learning to capture episode-specific representations. MetaRep leverages distinct image augmentation techniques to construct training episodes using unlabeled data. Support sets are formed by randomly sampling from the data pool, and image augmentation techniques are applied to generate query sets. Technically, it works for datasets like Omniglot [114] and mini-Imagenet [166] or larger datasets because they contain a multitude of samples and classes. Therefore, we hypothesize that the probability of drawing from the same class is insignificant.

MetaRep consists of two steps of training. In the first step, we apply the fully unsupervised training to learn the latent representations of the dataset. Throughout this phase, we utilize the labeled test sets to monitor performance. While the accuracy achieved during unsupervised representation learning may not rival that of supervised learning, the meta-learning algorithm still manages to achieve some degree of accuracy. Although unsupervised representation falls behind supervised learning accuracy, it is a good initialization point to boost supervised learning performance. Hence, in the second step, we utilize the learned parameters from the unsupervised learning model to initialize the supervised

meta-learning process rather than resorting to random initialization. This strategic use of pre-learned parameters effectively transforms the entire process into a semi-supervised meta-learning algorithm [167], thereby enhancing performance.

In addition, MetaRep employs data augmentation to increase learning effectiveness. For an effective augmentation technique, we drew inspiration from SimCLR [7] and combined it with color invert and random flip augmentations. This makes the MetaRep model agnostic and adaptable to various meta-learning models.

To experimentally validate the effectiveness of MetaREP, we evaluated its performance across two prominent meta-learning architectures: Model-Agnostic Meta-Learning (MAML) [14] and Relation Network (RN) [150]. In our experiments, we introduced a modification to the MAML network architecture by integrating temperature [168] into the SoftMax activation function in the inner loop. This adjustment was aimed at mitigating overfitting during unsupervised training. While we retained the RN architecture unchanged, we optimized our hyperparameters and architecture to achieve higher accuracy compared to the results reported in [150]. Our experimentation shows that the proposed MetaRep method can enhance the accuracy of any state-of-the-art meta-learning model.

While our approach incorporates techniques like data augmentation and temperature scaling, MetaRep's novelty lies in its unique adaptation for episodic representation learning. Our data augmentation strategy combines methodologies with episodic-specific modifications, creating query samples with demonstrably distinct feature distributions—as verified through our histogram analysis showing entirely new pixel intensities in each run. Unlike previous approaches that produce similar augmented samples, our method introduces meaningful uncertainty between episodes, critical for effective meta-learning where samples may appear across multiple episodes. Complementing this, our introduction of temperature-scaled SoftMax specifically in the meta-learning inner loop addresses the overfitting challenge in unsupervised episodic learning, significantly improving accuracy by

forcing the model to learn more discriminative features. Together, these technical innovations enable MetaRep to effectively bridge supervised and unsupervised paradigms by learning transferable episodic representations without labels—representing a fundamental shift from both standard meta-learning approaches that require labeled data for episodic learning and traditional representation learning techniques that aren't optimized for episodic adaptation.

3.7.2 Contributions

Our key contributions are as follows:

- We introduce MetaRep, a novel semi-supervised meta-learning framework that leverages unsupervised representation learning to enhance meta-learning performance. Our approach demonstrates significant accuracy improvements across multiple architectures while reducing dependency on labeled data.

- We develop an enhanced data augmentation strategy that combines SimCLR methodologies with targeted modifications for meta-learning scenarios. Through empirical analysis and visualization, we show how our augmentation technique generates more diverse and informative query sets, leading to improved representation learning.

- We propose a temperature-scaled adaptation of MAML's inner loop optimization, effectively addressing the overfitting challenges in unsupervised meta-learning. This modification, combined with our optimized implementation of Relation Networks, achieves state-of-the-art performance on standard few-shot learning benchmarks.

- We validate MetaRep's model-agnostic properties through extensive experimentation

across multiple architectures and datasets. Our empirical results demonstrate both cross-architecture adaptability and strong transfer learning capabilities, with MetaRep maintaining consistent performance improvements even when training with significantly reduced labeled data. These results establish MetaRep as a robust, general-purpose enhancement for meta-learning systems.

3.7.3 Related Work

Meta-learning [161] has found extensive applications across diverse domains, including self-driving cars, face recognition, and computer vision. While primarily aimed at enabling classification with minimal samples, meta-learning models typically require substantial labeled data for training. This has increased interest in data augmentation techniques within the meta-learning community. Yao et al. [132] introduced task augmentation methods, MetaMix and channel shuffle, effectively reducing overfitting by linearly combining features and labels or randomly shuffling channels across classes. Rajendran et al. [169] proposed a meta-augmentation framework based on information theory to enhance generalization by introducing controlled randomness. However, both approaches remain supervised and still depend significantly on labeled data.

Recent advancements in implicit semantic data augmentation (ISDA) have offered promising alternatives for augmenting training data. Wang et al. [170, 171] proposed ISDA techniques, leveraging semantic transformations within deep feature spaces to efficiently augment datasets and improve model generalization. Their methods implicitly augment data by minimizing upper bounds on the expected loss, significantly enhancing the generalization capabilities of deep networks with minimal computational overhead.

Hsu et al. [122] developed one of the earliest unsupervised meta-learning methods called CACTUs, assigning pseudo-labels through nearest neighbor clustering. Despite its

effectiveness, CACTUs is computationally expensive due to additional embedding learning and clustering steps [172]. Moreover, its unsupervised nature limits its accuracy compared to supervised approaches.

Semi-supervised learning has become an active area of research, addressing challenges like limited labeled data and noisy labels. Recent frameworks, such as SimCLR [7], C2MT [173], and PSSCL [174], have proposed advanced strategies for handling limited data and noisy labels. Zhang et al. [173] introduced the cross-to-merge training (C2MT) framework, leveraging cross-training of two networks and balanced data partitioning. PSSCL [174] focuses on progressively selecting and refining clean data samples, employing contrastive learning for robust semi-supervised training.

To address challenges in domain adaptation and transfer learning scenarios, recent studies have presented innovative approaches. Xie et al. [175] proposed target-oriented transferable semantic augmentation (T^2SA), implicitly generating target-like augmented data to enhance model generalization across domains. Their method utilizes class-wise prototype constraints to ensure discriminative and representative augmentation. Additionally, Du et al. [176] introduced probabilistic contrastive learning (ProCo), effectively addressing issues arising from long-tailed distributions by efficiently sampling contrastive pairs through probabilistic modeling of feature distributions.

Khodadadeh et al. [177] proposed UMTRA, combining unsupervised meta-learning with augmented query samples within the MAML framework. However, its accuracy remains below supervised methods. Chen et al. [7] introduced SimCLR, significantly impacting semi-supervised learning through effective data augmentation and a normalized temperature-scaled cross-entropy loss, motivating our approach toward a semi-supervised meta-learning framework integrating representation and transfer learning.

Other prominent meta-learning methods include MAML [14], aiming for rapid adaptation through optimized task embeddings. Variants like Reptile [148], Meta-SGD [149],

and LEO [142] have similarly contributed to the field. The Prototypical Network [13] introduced a metric space for efficient classification, later surpassed by Relation Networks (RN) [150], which further enhanced accuracy. Oreshkin et al. [178] proposed TADAM, enhancing few-shot learning by task-dependent metric scaling and adaptive metrics, significantly improving classification accuracy on benchmark datasets. Lee et al. [179] introduced MetaOptNet, utilizing differentiable convex optimization to leverage linear classifiers as base learners, achieving state-of-the-art results in few-shot learning tasks. In our work, we build upon these methods by modifying MAML and leveraging RN, PN, TADAM and MetaOptNet, emphasizing their model-agnostic nature for improved performance.

Additionally, local supervision methods such as InfoPro [180] have emerged, emphasizing information propagation through gradient-isolated modules. InfoPro maximizes useful information retention while efficiently discarding irrelevant features, providing competitive performance with significant computational efficiency, thus complementing existing meta-learning and semi-supervised frameworks.

3.7.4 Proposed Method: MetaRep

In this section, the proposed MetaRep scheme is presented. The MetaRep comprises of two distinct training stages: unsupervised representation learning and semi-supervised meta-learning. A detailed description of each step is presented below.

3.7.4.1 Step 1: Unsupervised Meta-Learning

Data Preparation: To integrate representation learning with meta-learning, we begin by leveraging either the entire or a subset of the dataset without any label information. Initially, we draw the samples $x_{n,k}$ from the data pool of x_N, where n, k are the number of ways and the number of shots, respectively, considered in the unsupervised learning and N is the



Figure 3.2: Steps of MetaRep, top-left: unlabeled train samples, bottom-left: labeled test samples, middle: episodes for training and testing, middle-left two columns: support set, middle-right two columns: query set, right-top: performing unsupervised meta-learning with the episodes, right-middle: transferring parameters from unsupervised learning to supervised learning, right-bottom: supervised learning with improved accuracy.

total number of unlabelled samples. We only design n-way (or classes), 1-shot support sets because each sample in the support set is drawn randomly, and we cannot randomly add more same-class support samples to that set. However, we can apply data augmentation for the query set to generate multiple query samples of the same class. Subsequently, the effectiveness of generating more query samples is discussed in a later section.

In episodic learning, every episode sees a combination of new classes. Therefore, after generating the training episodes, assign labeled values $y_{n,k}$ to each class of the support sets, where j is the number of ways generated as $\{c_0, c_1, ..., c_{n-1}\}$ and one-hot encoded later.

We initialize the random initialization parameter for the unsupervised classifier, θ. We randomly draw the support sets for each task episode and generate the randomly generated support labels. To generate the query set, we pass each sample of the support set through a data augmentation function $f(A)$ and similarly generate the pseudo labels. Ultimately, we use the regular supervised meta-learning learning test setup to examine the classifier's performance.

Deep Dive into Support-Query Set Generation: We hypothesize that drawing multiple samples from a sizable dataset decreases the likelihood of encountering more than one sample belonging to the same class. Thus, it's imperative to ensure that $n << c$ where n is the number of ways (or the drawn samples, given our 1-shot learning approach) and c is the total number of classes. However, it is essential to mathematically determine the probability of obtaining unique samples within each class for the datasets used in this study.

We utilize two distinct datasets: Omniglot and mini-Imagenet. The former typically contains fewer samples per class than the total number of classes, making it highly likely that all drawn samples originate from different classes. Conversely, the mini-Imagenet has more samples (600) in each class than the total number of classes, resulting in a slightly lower probability of samples originating from different classes. Nonetheless, both datasets feature an equal number of samples per class, denoted as m. Now, we can calculate the probability of the samples belonging to different classes as follows:

$$P = \frac{c! \cdot m^n (c \cdot m - n)}{(c-n)! \cdot (c \cdot m)!} \tag{3.10}$$

Using the aforementioned formula, the probabilities of 5-way 1-shot classification for the Omniglot (1200 classes) and mini-Imagenet (64 classes) are 99.21% and 85.23%, respectively.

Effective data augmentation plays a crucial role in our research, particularly in generating query samples. We combine suggestions from SimCLR [7] with additional modifications to enhance effectiveness for RGB image classification, specifically on the mini-Imagenet dataset. The SimCLR paper thoroughly discusses the efficacy of data augmentation and the importance of selecting appropriate augmentation functions, providing valuable insights that guide our approach. They recommend a combination of Gaussian blur, random crop, and random color distortion as the most effective augmentation techniques. Building upon this recommendation, we introduce horizontal flip and random color invert (with a 50% probability) alongside these three methods. Our experimentation indicates that this augmented combination not only mitigates overfitting but also improves accuracy. Conversely, for the grayscale Omniglot dataset, we solely employ random affine transform. We found that extensive augmentation adversely affects performance, as both support and query samples exhibit significant similarity. Therefore, employing hard augmentation strategies is deemed unnecessary in this particular case.

Classifiers: Our proposed method is model agnostic and can be applied to any model. In this paper, we use two meta-learning models, MAML and RN, to demonstrate the performance on different architectures. We observe that for MAML, the classifier trained on RGB samples (such as mini-Imagenet in our case) exhibits severe overfitting issues with the regular classifier. This arises because the augmented query samples closely resemble the original support samples, resulting in minimal learning during training. To address this challenge, we introduce a solution by implementing a temperature-scaled SoftMax activation function exclusively within the inner loop of MAML. The inclusion of the temperature term reduces the classifier's confidence in the support set samples, enabling the classifier to gather more information from subtle differences. This adjustment effectively mitigates the overfitting issue, enhancing the performance of MAML. The mathematical expression

for temperature-scaled SoftMax is as follows:

$$\frac{\exp(z_i/T)}{\sum_{k=0}^{j-1}\exp(z_k/T)} \tag{3.11}$$

where the scaling is accomplished by dividing the logits of SoftMax by a value T, known as temperature. j is the number of ways, and z_i, z_k represent the i^{th}, k^{th} input to the SoftMax, respectively.

We found RN performing counter effectively when using a temperature-scaled SoftMax. We instead used our own set of hyperparameters that led to more improved accuracy than the RN in the original paper.

Following the training of the unsupervised learning algorithm, we preserve the weights and biases for subsequent supervised meta-learning. Consequently, in the classifier of the second step, instead of initializing parameters θ randomly, we utilize the transferred parameters denoted as θ^*. Subsequently, we conduct standard meta-learning procedures to fine-tune and enhance accuracy.

3.7.4.2 Step 2: Semi-Supervised Meta-Learning (SSML)

In this step, we apply SSML within the conventional meta-learning framework, but with parameter initialization from the first classifier. Thus, the transferred parameters originate from the unsupervised meta-learning phase conducted in the initial stage. Let us talk briefly about the two considered classifiers, MAML and RN. Note that we refrain from modifying the SoftMax activation function of MAML at this stage, as the supervised MAML is less prone to overfitting.

MAML: MAML tries to find the optimal parameters θ derived from a few parametric models f_θ. In MAML, we generate the episodes from the data distribution such as $\tau_i = (D^{\text{tr}}, D^{\text{val}})$. We use the gradient update to update the initialize parameter θ to $\theta_i^{'}$ across tasks

Algorithm 2 MetaRep

1. **Require:** unlabeled dataset $U\{x_N\}$,
2. **Require:** learning rates α, β,
3. **Require:** augmentation function $f(A)$
4. Initialize random parameter θ
5. **while** not done **do**
   (a) Generate episodes $\{x_{n,1}\}$ and create pseudo labels $\{y_{n,1}\}$
   (b) **for each** $(x_{n,1}, y_{n,1})$ **do**
      i. Update the inner loop of meta-learning with custom loss function or hyper-parameters
   (c) **end for**
   (d) Update the outer loop of meta-learning with the regular loss function
6. **end while**
7. Save weights and biases θ^*
8. **Input:** Labeled dataset $\{x_{n,k}, y_{n,k}\} \subseteq \{x_{n,1}, y_{n,1}\}$
9. Initialize θ^*
10. Perform regular meta-learning steps

sampled from $p(\tau)$ and is obtained as follows:

$$\theta_i^{'} = \theta - \alpha \nabla_\theta \pounds_{\tau_i}(f_\theta) \tag{3.12}$$

where α is the learning rate of the meta-inner loop, and $\pounds$ is the loss function. In the outer loop of meta-learning, the optimization is performed across tasks via stochastic gradient

descent (SGD) to update the θ. It is obtained as follows:

$$\theta \leftarrow \theta - \beta \nabla_{\theta} \sum_{\tau_i \sim p(\tau)} \pounds_{\tau_i}(f_{\theta^i}) \tag{3.13}$$

where β is the learning rate of the meta-outer loop.

RN: The main two components of RN are a feature extractor and a relation module. The feature extractor concatenates the features from the support sets, and the query sets as $f_{\varphi}(x_i)$ and $f_{\varphi}(x_j)$ through a function $\mathbb{C}(f_{\varphi}(x_i), f_{\varphi}(x_j))$.

The combined features are passed through the relation module to obtain their relation score. It is passed through a Sigmoid activation function to obtain the score in a range between 0 to 1. The equation for that is provided below:

$$r_{i,j} = g_{\phi}(\mathbb{C}(f_{\varphi}(x_i), f_{\varphi}(x_j))) \tag{3.14}$$

To create the final output, the relation network's output can also be subjected to extra processing by layers, such as a fully connected neural network. Because of this, the relation network is an adaptable architecture that may be used for various applications. A mean-square-error (MSE) loss function is used to update the network using gradient descent.

$$\varphi, \phi \leftarrow \arg\min \sum_{i=1}^{m} \sum_{j=1}^{n} (r_{i,j} - 1(y_i == y_j))^2 \tag{3.15}$$

Overall Summary: The overall method is summarized in this sector with a diagram for better understanding. Figure 3.2 depicts the steps of the proposed method. We generate the

training episodes from the unlabeled samples. Here, the NT-Xent loss [168] (temperature-scaled SoftMax) is only applied on the MAML for the mini-Imagenet dataset. After training the initial model, we save the parameters and transfer them to the final model for improved performance. Moreover, the pseudo-code for our proposed method is provided in Algorithm 2.

Additional Classifier Architectures: To comprehensively evaluate MetaRep's model-agnostic capabilities, we implement three additional meta-learning architectures beyond MAML and RN.

Prototypical Networks (PN) [13] operates by computing class prototypes, the mean feature vector of support samples for each class in an embedding space. Classification is performed by finding the nearest prototype to a query sample using a distance metric (typically Euclidean distance). PN's elegant approach requires no inner loop optimization, making it computationally efficient while maintaining strong performance on few-shot tasks.

Task Dependent Adaptive Metric (TADAM) [178] extends the prototypical network concept by incorporating task conditioning through a Task Embedding Network (TEN). TADAM dynamically adapts its feature extractor for each task using film layers conditioned on task embeddings. Additionally, it employs metric scaling that adjusts the metric space based on task characteristics and leverages auxiliary co-training with standard classification to prevent underfitting. This combination of techniques allows TADAM to achieve superior performance compared to standard meta learning methods.

MetaOptNet [141] frames the inner learning problem as a differentiable convex optimization procedure, specifically using support vector machines (SVMs) for classification. By incorporating this structured classifier rather than a simple linear layer, MetaOptNet leverages the generalization benefits of margin-based classifiers. The SVM's quadratic programming problem is efficiently solved using differentiable optimization techniques, allowing end-to-end training. MetaOptNet is particularly effective in low-data regimes,

consistently outperforming other methods on benchmark few-shot classification tasks.

For all three architectures, we apply the MetaRep framework by first learning unsupervised episodic representations, then transferring the learned parameters to initialize supervised meta-learning, following the same procedure as described for MAML and RN.

3.7.5 Experiments

3.7.5.1 Data Augmentation for Representation Learning

We validate our proposed method using two different benchmark datasets in computer vision, Omniglot and mini-Imagenet. Omniglot contains images of handwritten letters from 50 different languages. This dataset is suitable for few-shot learning because it has $1,623$ characters or classes but only 20 instances or samples per class. We used $1,200$ classes for training, 100 classes for validation, and the remaining for testing. In input image dimension to the classifier is $1 \times 28 \times 28$ pixels, as all are grayscale samples. On the other hand, the mini-Imagenet dataset contains $3 \times 84 \times 84$ pixels color images. It has a total of 100 classes, each with 600 samples. Here, we use 64 for training, 16 for validation, and 20 classes for testing.

For selecting the most effective data augmentation, we experimented with different augmentation methods on a trial-and-error basis and found the SimCLR augmentation with an additional augmentation gave the best output for the mini-Imagenet dataset. This section presents the results obtained from various augmentation methods employed in our research. We concentrate on the mini-Imagenet dataset for the augmentation analysis, as the Omniglot dataset typically does not necessitate extensive data augmentation. We also explain why our chosen augmentation works the best for our dataset. Table 3.7 lists the outputs from different augmentation methods using unsupervised learning. Note that all the outputs are obtained by re-implementing different methods using our own hyperparameters,

which may provide different results than other literature.

Table 3.7: The test accuracy (%) of unsupervised meta-learning for 5-way 1-shot (5W1S) and 20-way 1-shot (20W1S) classification using mini-Imagenet dataset. For MAML, different temperatures (denoted by T) are applied in the meta-inner loop.

Augmentation method	**MAML**		**RN**	
	5W1S	**20W1S**	**5W1S**	**20W1S**
Auto augment (UMTRA*)	30.1 (T=1) 35.2 (T=100)	9.25 (T=1) 11.65 (T=10)	35	9
Resized crop + Gaussian blur + color distortions (SimCLR)	28.4 (T=1) 34.4 (T=100)	7.6 (T=1) 11.1 (T=10)	32	7
Horizontal flip (50%) + color invert (50%) + resized crop + Gaussian blur + color distortions (**Ours**)	33.8 (T=1) **38.2** (T=100)	13.65 (T=1) **13.95** (T=10)	**39**	**11.5**

$*$re-implementation.

Table 3.8: The test accuracy (%) of unsupervised meta-learning for 5W1S and 20W1S classification using Omniglot dataset.

Augmentation method	**MAML**		**RN**	
	5W1S	**20W1S**	**5W1S**	**20W1S**
Random transformation + zero pixels (UMTRA*)	48.80	24.94	61.25	35.78
Resized crop + Gaussian blur (SimCLR)	48.93	27.47	66.25	43.13
Random affine transform (30°) (**MetaRep**)	**52.83**	**27.95**	**69.12**	**44.37**

$*$re-implementation.

From Table 3.7, we observe the outputs from unsupervised learning for various augmentation functions. Let us begin by discussing the accuracy of MAML. First of all, we use the traditional meta-learning where the temperature parameter in the meta-inner loop for the SoftMax activation function is 1. A temperature of 1 means basically no temperature parameter. For MAML, we discovered that using the optimal temperature in the inner loop increased the accuracy of all the augmentation functions. It is because, when the temperature is 1, the training classifier overfits a lot due to the query set not being very challenging for the support set. When we apply the temperature, the classifier becomes less confident of

the classes and can learn more features because of the introduced uncertainty. Initially, we applied the auto-augment function for query sample generation, which achieved slightly higher accuracy than the SimCLR augmentation function in all cases. Our augmentation function achieved 33.8% and 13.65% accuracy, which is the highest of all. We introduced temperature parameters as 100 and 10 for 5-way and 20-way, respectively. All the classifiers exhibit improved accuracy for the optimal temperature, and our proposed method obtained the highest accuracy. The temperature is a hyperparameter that shows different performances for different values. In Figure 3.3 we illustrated the output accuracy from different temperatures to select the optimal ones. As observed, temperatures 100 and 10 provide the highest accuracy for 5-way and 20-way, respectively.



(a) 5W1S accuracy for different temperatures.

(b) 20W1S accuracy for different temperatures.

Figure 3.3: Effect of different temperatures on test accuracy.

For the RN, we do not modify anything in the classifier architecture; rather, our motivation is to show that the proposed method is model-agnostic. Nevertheless, our combination of hyperparameters with a ResNet-18 [181] achieved higher accuracy than MAML for 5-way classification but obtained lower accuracy for 20-way classification. The auto-augment method obtained slightly higher accuracy than the SimCLR augmentation for both 5-way and 20-way classifications. However, SimCLR performs poorly for the 20-way classification and achieves only 7% accuracy. On the other hand, when we apply our proposed

augmentation method, we obtain the highest accuracy for both 5-way and 20-way classifications. Nevertheless, using our proposed method, the RN module achieved higher accuracy than the MAML module for 5-way classification and lower accuracy for 20-way. Therefore, it is evident that the RN unsupervised meta-learning fails to achieve satisfactory accuracy for a higher number of classifications.

We also present the outputs from the Omniglot dataset in Table 3.8 to show the domain adaptability of MetaRep. In Omniglot, the support samples are pretty similar to the query samples. As a result, our experiment found that any hard augmentation on the samples hurt the performance. Therefore, we perform a minimum augmentation to keep the features intact and yet introduce some information in the augmented samples. Moreover, since the samples are grayscale, we could not follow the color distortion function from SimCLR. So, we only applied affine transformation within 30° to obtain the best transformation. This transformation distorts the samples slightly but keeps the meaning intact. In the case of SimCLR, we only apply resized crop and Gaussian blur as the color distortions do not apply to this dataset. Proof of the effectiveness of our method can be found in the experimental outputs. In this case, the SimCLR augmentation achieved higher accuracy for both MAML and RN in all 5-way 1-shot and 5-way 20-shot classifications. Our proposed method achieves the highest accuracy in all comparisons.

MetaRep can technically be extended to accommodate any n-way 1-shot k-query classification task. This extension is feasible because we have the flexibility to generate different augmented samples in each run for multiple query generation. However, we encountered a drop in accuracy in our proposed model when applied to multiple queries. We attribute this drop in accuracy to the classifier becoming overfit from multiple queries, as they are not distinctly distinguishable. The lack of clear distinctions between multiple query samples likely leads to the classifier being unable to effectively generalize across them, resulting in

reduced accuracy. Table 3.9 represents outputs from MAML for multiple queries. The accuracy drop was significant in all 5-way 5-query and 20-way 5-query shot classifications. Therefore, we do not suggest using our method for a k-query shot. One should instead apply 1-shot unsupervised learning and then transfer the learned parameters to supervised learning. We only applied a 5-way 5-query shot to RN and opted out 20-way 5-query shot because it requires substantial computational resources for a backbone of ResNet-18. In the Omniglot dataset, the accuracy drop for 5-way 5-shot and 20-way 5-shot were 3.68% and 0.73% for MAML and 3.87% and 5.71% for RN. For mini-Imagenet, the drops are 3.04% and 1.52% for MAML and 11% for RN (N.B. no experiments conducted for 20W1S5Q RN).

Table 3.9: The test accuracy (%) and drop of unsupervised MetaRep for n-way, 1-shot multi-query.

Dataset	**MAML**		**RN**	
	5W1S5Q	**20W1S5Q**	**5W1S5Q**	**20W1S5Q**
Omniglot	49.15 (drop 3.68)	27.22 (drop 0.73)	65.25 (drop 3.87)	38.66 (drop 5.71)
mini-Imagenet	32.96 (drop 3.04)	12.43 (drop 1.52)	28 (drop 11)	N/A

3.7.5.2 Computational Resources

All experiments were conducted using deep learning hardware: a single Nvidia 3080Ti (12GB) GPU for MAML training, and distributed training across two Nvidia 3090Ti (24GB) GPUs plus Google Cloud Platform GPUs for RN, PN, TADAM and MetaOptNet models. Implementation used PyTorch (versions 2.0, 2.3) and Python (versions 3.9, 3.10). For reproducibility, we fixed random seeds to 42, 1234, and 1337 across all experiments.



Figure 3.4: Histogram of pixel intensities for different augmentation methods.

3.7.5.3 Semi-Supervised Meta-Learning (SSML)

For the second stage, we initialize the meta-learning parameters using weights learned from the unsupervised pre-training phase. To ensure statistical significance, we evaluated all experiments across three random seeds (42, 1234, and 1337). Table 3.10 presents comprehensive results comparing standard meta-learning approaches with our MetaRep framework across multiple architectures on both Omniglot and mini-ImageNet datasets. All reported accuracies represent means and standard deviations computed across the three independent runs.

Our analysis of Table 3.10 reveals several important findings across architectures. The baseline model achieves $86.03 \pm 0.03\%$ on 5W1S1Q for Omniglot, establishing a reasonable lower bound. All meta-learning approaches substantially outperform this baseline, with

varying degrees of improvement.

MetaRep consistently enhances performance across all architectures. For MAML, we observe significant improvements in one-shot learning scenarios (from $93.83 \pm 0.05\%$ to $96.47 \pm 0.06\%$ on Omniglot 5W1S1Q), with more modest gains in 5-shot configurations. RN's already strong performance on Omniglot ($99.39 \pm 0.03\%$ for 5W1S1Q) still improves with MetaRep, reaching perfect 100% accuracy with zero variance. Similarly, PN benefits from MetaRep with accuracy increases from $98.23 \pm 0.06\%$ to $99.13 \pm 0.03\%$ on Omniglot 5W1S1Q, and comparable improvements across other configurations.

The advanced architectures TADAM and MetaOptNet also show clear benefits from the MetaRep framework. TADAM's Omniglot performance improves from $99.09 \pm 0.06\%$ to 100% for 5W1S1Q, while on mini-ImageNet, we observe gains from $57.46 \pm 0.06\%$ to $58.75 \pm 0.09\%$. MetaOptNet, despite already achieving optimal performance in several Omniglot configurations, still shows improved consistency in 20W1S1Q (from $98.23 \pm 0.06\%$ to $99.13 \pm 0.03\%$) and gains on mini-ImageNet (from $60.36 \pm 0.09\%$ to $61.23 \pm 0.06\%$ for 5W1S1Q).

The challenging mini-ImageNet dataset further highlights MetaRep's effectiveness. Across all architectures, we observe consistent improvements: PN ($49.16 \pm 0.03\%$ to $50.13 \pm 0.06\%$), MAML ($46.83 \pm 0.06\%$ to $47.63 \pm 0.09\%$), RN ($53.03 \pm 0.06\%$ to $57.03 \pm 0.09\%$), TADAM ($57.46 \pm 0.06\%$ to $58.75 \pm 0.09\%$), and MetaOptNet ($60.36 \pm 0.09\%$ to $61.23 \pm 0.06\%$) all benefit from our approach. Particularly noteworthy is RN's substantial 4% accuracy gain, demonstrating MetaRep's ability to provide more significant benefits to certain architectural paradigms.

The standard deviation values across experiments remain consistently small, indicating the statistical reliability of our results across multiple random seeds. These comprehensive improvements across architectures with different inductive biases strongly validate MetaRep as a truly model-agnostic enhancement to meta-learning frameworks.

Table 3.10: Classification accuracy (%) of different methods for random seeds.

Method	Omniglot				mini-ImageNet			
	1S1Q	5S5Q	20S1Q	20S5Q	1S1Q	5S5Q	20S1Q	20S5Q
Baseline	86.03 ± 0.03	97.67 ± 0.08	73.03 ± 0.11	92.37 ± 0.09	38.47 ± 0.09	51.23 ± 0.06	N/A	N/A
PN*	98.23 ± 0.06	99.13 ± 0.03	95.63 ± 0.04	98.53 ± 0.03	49.16 ± 0.03	67.86 ± 0.06	N/A	N/A
MAML*	93.83 ± 0.05	98.33 ± 0.06	82.53 ± 0.06	92.37 ± 0.06	46.83 ± 0.06	61.63 ± 0.03	18.78 ± 0.09	30.43 ± 0.06
RN*	99.39 ± 0.03	100.00 ± 0.00	97.20 ± 0.06	99.59 ± 0.03	53.03 ± 0.06	64.03 ± 0.06	24.27 ± 0.03	N/A
TADAM*	99.09 ± 0.06	100.00 ± 0.00	97.57 ± 0.09	99.69 ± 0.03	57.46 ± 0.06	76.27 ± 0.09	N/A	N/A
MetaOptNet*	100.00 ± 0.00	100.00 ± 0.00	98.23 ± 0.06	100.00 ± 0.00	60.36 ± 0.09	76.86 ± 0.06	N/A	N/A
MetaRep PN	99.13 ± 0.03	99.73 ± 0.02	96.23 ± 0.03	98.77 ± 0.03	50.13 ± 0.06	68.41 ± 0.02	N/A	N/A
MetaRep MAML	96.47 ± 0.06	98.37 ± 0.03	83.37 ± 0.06	92.75 ± 0.09	47.63 ± 0.09	61.83 ± 0.03	18.91 ± 0.06	30.74 ± 0.03
MetaRep RN	100.00 ± 0.00	100.00 ± 0.00	97.37 ± 0.06	99.70 ± 0.03	57.03 ± 0.09	67.03 ± 0.06	25.03 ± 0.06	N/A
MetaRep TADAM	100.00 ± 0.00	100.00 ± 0.00	97.90 ± 0.06	100.00 ± 0.00	58.75 ± 0.09	76.94 ± 0.06	N/A	N/A
MetaRep MetaOptNet	100.00 ± 0.00	100.00 ± 0.00	99.13 ± 0.03	100.00 ± 0.00	61.23 ± 0.06	77.11 ± 0.04	N/A	N/A

$*$re-implementation.

Table 3.11: Transferability of MetaRep for different datasets.

Dataset	Method	5W1S1Q	5W5S5Q	20W1S1Q	20W5S5Q
CIFAR-FS	MAML	49.63 ± 0.06	71.23 ± 0.08	25.79 ± 0.05	42.19 ± 0.03
	MetaRep MAML	53.24 ± 0.05	71.76 ± 0.03	26.37 ± 0.04	42.83 ± 0.06
	RN	54.77 ± 0.04	68.99 ± 0.05	N/A	N/A
	MetaRep RN	56.08 ± 0.03	69.70 ± 0.06	N/A	N/A
	PN	55.36 ± 0.05	71.67 ± 0.04	N/A	N/A
	MetaRep PN	57.46 ± 0.02	73.97 ± 0.07	N/A	N/A
tieredImageNet	MAML	48.03 ± 0.04	61.50 ± 0.05	19.59 ± 0.06	32.38 ± 0.03
	MetaRep MAML	48.23 ± 0.03	62.07 ± 0.04	20.13 ± 0.05	33.26 ± 0.06
	RN	51.36 ± 0.05	67.70 ± 0.06	N/A	N/A
	MetaRep RN	52.27 ± 0.04	68.19 ± 0.03	N/A	N/A
	PN	53.30 ± 0.06	71.89 ± 0.05	N/A	N/A
	MetaRep PN	54.68 ± 0.03	72.07 ± 0.02	N/A	N/A

Table 3.12: Accuracy drop (%) of supervised meta-learning on the partially labeled mini-ImageNet training set.

Method	5-way Accuracy				20-way Accuracy			
	1S1Q	% Drop	5S5Q	% Drop	1S1Q	% Drop	5S5Q	% Drop
MAML (50% labeled data)*	48.20	-2.99	61.45	1.87	18.75	5.07	28.42	6.51
MetaRep MAML (50% labeled data)	49.40	**-3.78**	61.04	**1.23**	17.94	**4.98**	28.83	**6.12**
MAML (25% labeled data)*	46.00	1.71	57.40	6.82	16.25	13.33	26.54	12.70
MetaRep MAML (25% labeled data)	47.20	**0.84**	58.25	**5.74**	17.50	**7.31**	27.05	**11.92**
RN (50% labeled data)*	39.00	26.42	58.20	**9.06**	19.75	18.56	N/A	N/A
MetaRep RN (50% labeled data)	43.00	**24.56**	59.20	11.64	22.25	**11.00**	N/A	N/A
RN (25% labeled data)*	38.00	**28.30**	51.80	19.06	18.75	22.68	N/A	N/A
MetaRep RN (25% labeled data)	40.00	29.82	54.40	**18.81**	20.25	**19.00**	N/A	N/A

*Re-implementation results.

3.7.5.4 Computational Complexity Analysis

We conduct a thorough assessment of MetaRep's computational overhead relative to standard meta-learning baselines. In particular, MetaRep's multi-stage training procedure—comprising an unsupervised pre-training step followed by conventional meta-training—incurs additional resource demands. Table 3.13 presents the training time and memory requirements for different model configurations.

MetaRep introduces approximately 30% to 60% additional computational time during training due to the unsupervised pre-training phase. However, this overhead occurs only during the initial model development and does not affect inference time, which remains identical to the base models. The enhanced accuracy (3-4% improvement) and reduced labeled data requirements (up to 75% reduction) justify this one-time computational cost for most applications.

Table 3.13: Computational Requirements Comparison for 5-way 5-shot classification.

Method	**Trainable Parameters**	**GPU Memory (GB)**	**Training Time (hours)**	**Inference Time (ms/episode)**
MAML	32.9K	1.4	2	12
MetaRep MAML	32.9K	1.4	3.5	12
RN	8.54M	4.8	12	30
MetaRep RN	8.54M	4.8	19	30
TADAM	8.0M	4.2	8	48
MetaRep TADAM	8.0M	4.2	14.5	48
MetaOptNet	12M	8.3	14	60
MetaRep MetaOptNet	12M	8.3	25	60

3.7.5.5 Transferability of MetaRep

To evaluate the cross-dataset generalization capabilities of MetaRep, we conducted transfer learning experiments using CIFAR-FS [182] and tieredImageNet [183] datasets. For these experiments, we transferred representations learned from the mini-ImageNet dataset. To ensure statistical significance, all experiments were evaluated across three random seeds (42, 1234, and 1337). All reported accuracies represent means and standard deviations

computed across the three independent runs. CIFAR-FS contains 100 classes with 600 images per class, split into 64 classes for training, 16 for validation, and 20 for testing. The larger tieredImageNet dataset comprises 608 classes and 779,165 total images, with 351 classes allocated for training, 97 for validation, and 160 for testing.

Table 3.11 presents comprehensive results across multiple architectures (MAML, RN, and PN) and evaluation scenarios. For each configuration, we report mean accuracies with standard deviations across three random seeds. The results demonstrate consistent improvements when applying MetaRep across all architectures and datasets.

On **CIFAR-FS**, we observe particularly substantial improvements for 5-way 1-shot classification: MAML ($49.63 \pm 0.06\%$ to $53.24 \pm 0.05\%$, a 3.61% increase), RN ($54.77 \pm 0.04\%$ to $56.08 \pm 0.03\%$, a 1.31% increase), and PN ($55.36 \pm 0.05\%$ to $57.46 \pm 0.02\%$, a 2.10% increase). The improvements remain consistent but more modest for 5-way 5-shot classifications.

For **tieredImageNet**, while the absolute performance improvements are smaller, MetaRep still provides consistent gains across all architectures. The Prototypical Network exhibits the largest improvement for 5-way 1-shot classification (from $53.30 \pm 0.06\%$ to $54.68 \pm 0.03\%$), while MAML shows the most substantial relative improvement in the 20-way scenarios (e.g., from $19.59 \pm 0.06\%$ to $20.13 \pm 0.05\%$ for 20-way 1-shot). The consistent improvements across diverse datasets demonstrate that MetaRep learns transferable representations that generalize beyond the source domain.

3.7.6 Why Our Method is Effective

In Figure 3.4, we explained why MetaRep works effectively by visualizing the pixel intensities from the histograms of augmented images. This histogram analysis illustrates the degree of uncertainty introduced in different augmented samples compared to the original

samples. We observe that in both auto-augment and SimCLR augmentation, the histograms of augmented samples exhibit striking similarity to each other. This indicates that all augmented samples fail to introduce sufficient new uncertainties in each augmentation. This aspect is crucial because a sample can frequently appear in meta-learning across different episodes. Hence, we must supply query samples with distinguishable features in each run.

On the other hand, our proposed augmentation method demonstrates histograms with entirely new pixel intensities for each run. This implies that the features contain new information in each query sample. This observation can be attributed to the uncertainty introduced in our augmentation function through the horizontal flip and color invert operations, each with a 50% probability. As a result, our proposed method achieves the highest accuracy for unsupervised meta-learning.

3.7.7 Ablation Study

Additionally, we highlight that MetaRep can obtain high accuracy or less accuracy loss for partially labeled datasets (Table 3.12). We specifically conduct this analysis on the mini-Imagenet dataset due to its larger class size (600 samples per class), whereas Omniglot only contains 20 samples per class. We randomly select 50% (300) and 25% (150) training samples from the mini-Imagenet data and train our classifier to compare the proposed and original methods. This time we report the percentage accuracy drop from the main output (trained on 100% samples) to have a fair comparison between the original method and MetaRep. It is obtained as $((All\ Labeled\ Accuracy - Partially\ Labeled\ Accuracy)/All\ Labeled\ Accuracy) \times 100\%$. In most outputs, our proposed method has less drop except for MetaRep RN with 50% and 25% labeled data for 5W5S5Q and 5W1S1Q, respectively.

Notably, in MAML and MetaRep MAML for 5W1S1Q, we observe negative accuracy

drop percentages. This unexpected result occurs because the accuracy actually increases when we train MAML with 50% data in this setup. We hypothesize that this improvement stems from episode generation with fewer samples in each class. Some research suggests that having a large number of meta-training data can counterintuitively degrade performance due to the lower probability of all samples appearing in episodes. For example, Triantafillou et al. [124] found that having a large meta-dataset hurts the accuracy of the mini-Imagenet dataset. Setlur et al. [159] showed that having a fixed support set and having less diversity can improve accuracy. This emerging research direction focuses on determining the optimal number of samples in meta-training and devising more effective episode-generation strategies. We aim to focus on this area in our future research.

3.7.8 Future Work

While MetaRep demonstrates strong performance on standard few-shot learning benchmarks, real-world applications such as medical image diagnosis and autonomous driving involve additional challenges. For example, medical diagnosis demands high interpretability, robustness to noise, and strict regulatory standards, whereas autonomous driving requires real-time inference under dynamic conditions and sensor fusion from multiple modalities. MetaRep's reliance on episodic training and data augmentation may need further adaptation to address these domain-specific requirements. In particular, augmentation strategies effective for natural images (e.g., in mini-ImageNet) may not translate well to medical imaging due to the clinical significance of subtle features. Furthermore, the episodic structure might not directly map to the continuous and streaming data in autonomous systems. Addressing these concerns could involve incorporating domain-specific priors into the augmentation pipeline, improving robustness under distribution shifts, or integrating MetaRep with multi-modal representation learning.

Our experiments revealed interesting dynamics regarding temperature sensitivity across different task configurations. Future work should explore more sophisticated confidence calibration mechanisms that adapt dynamically to task complexity. Promising approaches include dynamic temperature scaling based on feature-to-cluster center distances, adaptive confidence penalties, task-conditional calibration, or meta-learned calibration parameters. These methods could potentially enhance MetaRep's adaptability across varying task complexities without requiring manual hyperparameter tuning.

Additionally, exploring the relationship between episodic diversity and model performance represents another important research direction. Our findings with partially labeled datasets suggest that carefully curated episodes might outperform those generated from larger but potentially redundant data pools. Developing systematic approaches to episode generation and support set construction could further improve meta-learning efficiency and effectiveness, particularly in resource-constrained scenarios. We consider these directions important avenues for future work to ensure MetaRep's effectiveness in safety-critical and high-impact real-world scenarios.

3.7.9 Conclusion

In this research, we propose MetaRep, a novel strategy that utilizes unsupervised meta-learning to derive latent representations from datasets, which are then employed for SSML with the learned parameters. This approach significantly enhances the performance of supervised learning, making our method both rapidly adaptive and highly accurate. Effective data augmentation for query sample generation is a cornerstone of our unsupervised approach, and we visually demonstrate the superiority of our augmentation strategies over others. Additionally, temperature-scaled SoftMax plays a crucial role in improving unsupervised classification accuracy. Tested on two different datasets and models, MetaRep

consistently achieves better test accuracy compared to original methods and maintains strong performance with partially labeled training samples, showcasing its efficiency and robustness across various scenarios.

3.8 Task 3: Meta-Task: A Method-Agnostic Framework for Learning to Regularize in Few-Shot Learning

3.8.1 Introduction

Few-Shot Learning (FSL) has emerged as a promising solution to the problem of data scarcity in machine learning, particularly in computer vision, medical applications, and personalized health systems [184, 185, 186]. By leveraging meta-learning, FSL enables models to learn how to learn with the primary objective of extracting meaningful, transferable representations from sparse datasets, reducing the need for extensive labeled data, and significantly lowering data collection and annotation costs [187, 188].

Advances in meta-learning have led to techniques such as Matching Networks [189], Relation Networks [150], Model-Agnostic Meta-Learning (MAML) [190], Prototypical Networks [13], and Reptile [148]. Despite performance gains, FSL models remain prone to overfitting, limiting generalization.

Regularization plays a critical role in mitigating overfitting and enhancing generalization in FSL. Conventional methods such as weight decay[191], dropout[192], and noise injection[193, 194] fail to address FSL-specific challenges. Meta-learning requires both adaptation-generalization and meta-generalization[140, 195, 196, 70, 197, 132, 169], yet existing techniques remain static, inflexible, and reliant on manually designed loss functions or auxiliary tasks that do not adapt to the unique structure of each task. This limitation motivates the need for a more dynamic, learnable regularization mechanism.

To address this limitation, we introduce Meta-Task, a method-agnostic framework that reformulates regularization as a learnable task within the FSL optimization process. Meta-Task dynamically learns task-specific regularization strategies through a parameterized neural layer ϕ. This adaptive mechanism enables our framework to seamlessly integrate with existing FSL pipelines, ensuring flexibility across different task distributions and learning paradigms. Meta-Task remains compatible with existing auxiliary tasks and regularization losses, leveraging prior techniques while introducing a dynamic, learnable component. This enhances overfitting mitigation without extensive hyperparameter tuning or task-specific modifications, making it scalable and practical for real-world FSL applications.

To operationalize Meta-Task regularization, we propose using an autoencoder-based Task-Decoder (Figure 3.5). The Task-Decoder serves as a flexible and effective regularizer, refining task-specific representations by constraining the embedding vector to reconstruct the original input accurately. We choose autoencoders because they are data-agnostic, easy to implement, architecturally flexible, and allow tunable parameterization for optimization. This adaptability makes them well-suited for various FSL applications, as they can seamlessly integrate into different model architectures.

Our method leverages the latent variable z, inherently present in most FSL settings due to the N-Way, K-Shot paradigm. The standard inner-outer loop optimization structure ensures the existence of an intermediate latent representation within the support-query split or gradient-based adaptation process. This guarantees compatibility across various FSL architectures, allowing Meta-Task to enhance regularization effectiveness dynamically.

3.8.2 Contributions

Our main contributions are:

1. **Meta-Task Framework:** We propose Meta-Task, a novel, method-agnostic framework that introduces auxiliary tasks to regularize individual tasks in FSL.

2. **Task-Decoder (Figure 3.5):** We introduce the Task-Decoder, utilizing autoencoders as a new regularization task for meta-learners, leveraging unsupervised learning to refine hidden representations.

3. **Improved Performance:** Our method demonstrates faster convergence, higher accuracy, and better generalization than existing techniques, all without extensive hyperparameter tuning.

4. **Versatility and Applicability:** The framework is method-agnostic and can be integrated with various FSL settings, making it suitable for real-world, resource-constrained scenarios.

3.8.3 Related Work

This section briefly reviews the relevant literature on meta-learning and regularization issues. Regularization techniques have been developed to improve the generalization ability of meta-learning models. These techniques can be broadly classified into four specialized regularization techniques for meta-learning. 1. Explicit Regularization (ER) [140, 195, 196, 70], 2. Episode Augmentation Regularization (EAR) [198, 199], 3. Task Augmentation Regularization (TAR) [197, 132, 169], 4. Adversarial Task Upsampling (ATU) [200].

The ER methods impose explicit regularization terms on the meta-learning update, such as Meta-Learning with Implicit Gradients (iMAML) [140], Meta-Learning without Memorization (MR-MAML) [195], and their combinations or extensions [196, 70]. These



Figure 3.5: Detailed architecture of the Task-Decoder within the Meta-Task framework. The Meta-Task support set consists of unlabeled copies of support and query samples, which are fed into an encoder f_θ to produce feature embeddings. These embeddings serve two key functions: (1) they are passed to a decoder g_ϕ to reconstruct the input images, aiding in the learning of rich, meaningful representations, and (2) they are used to generate the meta-learning method (F_θ) for query image classification. The model optimizes two objectives: classification loss ($J_\mathcal{T}$) and reconstruction loss ($J_\mathcal{M}$), each with a dedicated backpropagation step. The overall training loss is $J_\mathcal{T} + \lambda J_\mathcal{M}$, balancing both classification accuracy and representation learning. For a broader application, the decoder g_ϕ could be replaced by one or more neural networks that solve various unsupervised tasks.

methods directly constrain the model optimization process, aiming to improve the generalization performance of meta-learning models. For instance, minimax-meta regularization [70] combines two types of regularizations at the inner and outer levels to enhance the generalization performance of bi-level meta-learning.

The EAR approach controls the meta-training by modifying individual tasks through

noise or mixup [198, 199]. By expanding the amount of training data available for sampling, data augmentation supports various aspects of the meta-learning pipeline. It can be applied to support data in the inner loop of fine-tuning and enlarge the pool of evaluation data to be sampled during training.

TAR methods generate new tasks by interpolating between or augmenting existing tasks [197, 169], aiming to expand the task distribution for more robust generalization. For instance, methods such as MetaMix [201], and Channel Shuffle [132] have been proposed to increase the dependence of target predictions on the support set and provide additional knowledge to optimize model initialization. ProtoDiff [202] enhances prototypical networks through a task-guided diffusion process; by generating synthetic features conditioned on the task, ProtoDiff [202] augments the support set and improves the robustness of prototypes, significantly boosting classification performance. Additionally, the ATU approach [200] seeks to generate tasks that match the true task distribution by maximizing an adversarial loss, thereby improving meta-testing performance and the quality of upsampled tasks. These task augmentation techniques are designed to enhance the generalization capability of meta-learning models by effectively expanding the task distribution and mitigating overfitting during meta-training.

Recent works like Meta-Baseline [201] have advanced few-shot learning by bridging transfer learning and meta-learning through pre-training feature extractors on base classes before few-shot fine-tuning, demonstrating that high-quality feature representations can sometimes eliminate the need for complex meta-learning algorithms. However, in contrast to Meta-Baseline's reliance on large-scale pre-training and ProtoDiff's [202] computationally intensive task-guided diffusion models, our method learns robust embeddings during meta-training itself, making it more feasible for resource-constrained environments while remaining computationally efficient and method-agnostic.

In contrast to these methods, our proposed framework aims to regularize meta-learning

tasks by introducing Meta-Tasks—auxiliary tasks designed to refine hidden representations without relying on extensive pre-training or synthetic data generation. Table 3.14 summarizes the key differences between various methods and our approach. We integrate an unsupervised autoencoder, specifically the Task-Decoder, directly within the meta-learning framework to provide continuous, unsupervised regularization during training. This helps prevent overfitting and improves generalization in an end-to-end manner.

By treating regularization as a learnable task, our framework enhances adaptability and generalization capabilities in a lightweight manner. It is suitable for a broader range of real-world applications where computational resources and labeled data are limited.

Meta-Task distinguishes itself from prior FSL approaches by introducing a learnable, task-specific regularization strategy that dynamically adapts to each task without modifying the underlying FSL architecture. Unlike LEO and iMAML, which focus on optimizing meta-initialization and gradient regularization, Meta-Task directly integrates into the optimization process through a parameterized neural layer ϕ, learning task-adaptive constraints rather than enforcing fixed optimization heuristics. Unlike Wertheimer et al. [203] and Nag et al. [204], which utilize reconstruction-based self-supervision, our method does not rely on reconstruction loss. Furthermore, unlike Gidaris et al. [205], which introduces auxiliary tasks, Meta-Task requires neural layer ϕ, instead only relying on better updates using self-supervised or semi-supervised tasks.

Our comprehensive experiments focus on fundamental meta-learning models (Prototypical Networks, MAML, MetaOptNet, and P>M>F [206]) that represent diverse approaches in the field. While some baseline comparisons were conducted with adjusted experimental settings (reduced batch sizes, modified query shots, etc.) due to computational constraints, our results consistently demonstrate the effectiveness of our Meta-Task framework across different meta-learning paradigms, validating its method-agnostic nature and broad applicability.

Method	Category	Method-Agnostic	Complexity
iMAML [?]	ER	No	High
MR-MAML [195]	ER	No	High
Minimax-Meta [70]	ER	No	Low
DAC-MR [199]	EAR	Yes	Medium
MetaMix [201]	EAR	Yes	Medium
ProtoDiff [202]	TAR	No	High
ATU [200]	TAR	Yes	High
LEO [142]	ER	No	High
Task-Decoder (Ours)	**MTR**	**Yes**	**Medium**

Table 3.14: Comparison of meta-learning regularization methods. The table compares various meta-learning regularization techniques by category, method-agnostic capability, and computational complexity. Categories include Explicit Regularization (ER), Episode Augmentation Regularization (EAR), Task Augmentation Regularization (TAR), and our proposed Meta-Task Regularization (MTR).

3.8.4 Meta-Task Framework

In this section, we introduce our proposed Meta-Task Framework, a novel approach that enhances generalization by integrating learnable Meta-Tasks as a form of regularization. By treating regularization itself as a learnable task, our framework encourages the model to develop richer and more robust feature representations. The framework is method-agnostic and can be seamlessly integrated with existing FSL models, such as Prototypical Networks and MAML. In the following subsections, we detail the components of the framework, including the Task-Decoder, the problem formulation, and the theoretical justification for its effectiveness.

Our framework extends MAML [190] by introducing regularization as a ”learnable Meta-Task”, enabling unsupervised task integration during meta-training without requiring additional data. The following subsections detail the implementation and theoretical foundations of our contributions:

- **Task-Decoder:** We introduce an unsupervised autoencoder architecture that implements

our learnable regularization concept by reconstructing input images from their embeddings, proving its effectiveness in enriching feature representations.

- **Problem Formulation:** We present the mathematical framework that enables the integration of unsupervised auxiliary tasks with existing FSL methods, demonstrating how our approach remains method-agnostic through separable loss functions.

- **Theoretical Analysis:** We provide theoretical justification for our framework's convergence properties and establish how the joint optimization of primary and Meta-Tasks enhances generalization capabilities.

3.8.4.1 Task-Decoder

At the core of our Meta-Task Framework is the Task-Decoder (Figure 3.5), an unsupervised learning component designed to enhance the embedding space by reconstructing input images from their embeddings. The Task-Decoder employs an autoencoder architecture, where the encoder f_θ maps the input images to a latent embedding space, and the decoder g_ϕ reconstructs the images from these embeddings.

By encouraging the embeddings to retain sufficient information for accurate reconstruction, the Task-Decoder prevents the encoder from focusing solely on discriminative features that may not generalize well. This leads to richer and more robust feature representations, ultimately improving the model's performance on unseen tasks.

The Task-Decoder operates in parallel with the primary few-shot learning model, processing the same inputs and contributing to the overall learning objective through its reconstruction loss.

3.8.4.2 Problem Formulation

Let the Meta-Task $\mathcal{M}$ denote the Task-Decoder, and our meta-learning method F be Prototypical Networks. We define the encoder network f_θ parameterized by θ, and g_ϕ represent the decoder network parameterized by ϕ.

For a given query sample $x \in \mathcal{Q}$ and its true class y belonging to task $\mathcal{T}$, the Prototypical Network F_θ computes class prototypes using support set $\mathcal{S}$ and classifies x based on the closest prototype to the embedding f_θ.

Primary Task Loss: The probability of x belonging to class n is:

$$p_\theta(y = n \mid x) = \frac{\exp\left(-d\left(f_\theta(x), c_n\right)\right)}{\sum_{k=1}^{N} \exp\left(-d\left(f_\theta(x), c_k\right)\right)}, \tag{3.16}$$

where N is the number of tasks in the episode, c_n is the prototype of class n and $d(\cdot, \cdot)$ denotes the Euclidean distance. The classification loss is then:

$$J_{\mathcal{T}}(x, \theta) = -\log p_\theta(y = n \mid x). \tag{3.17}$$

Meta-Task Loss: The Task-Decoder aims to reconstruct x from f_θ, with the reconstruction loss defined as:

$$J_{\mathcal{M}}(x, \theta, \phi) = \left\| g_\phi(f_\theta(x)) - x \right\|^2. \tag{3.18}$$

Combined Loss Function: The total loss for a sample x is a weighted sum of the primary task loss and the Meta-Task loss:

$$J(x, \theta) = J_{\mathcal{T}}(x, \theta) + \lambda J_{\mathcal{M}}(x, \theta, \phi), \tag{3.19}$$

where λ is a hyperparameter balancing the two losses or the learning rate for the Meta-Task

update.

Optimization: The model parameters θ and ϕ are optimized jointly over all tasks and samples. For a given task $\mathcal{T}$, the overall loss is calculated by summing the combined losses over all query samples:

$$J_{\mathcal{T}}(\theta) = \sum_{x \in \mathcal{T}} J_{\mathcal{T}}(x, \theta). \tag{3.20}$$

During meta-training, we sample a batch of tasks $\{\mathcal{T}_i\}_{i=1}^{L}$. The total loss across all tasks in an episode is:

$$J(\theta) = \sum_{i=1}^{L} \left(J_{\mathcal{T}_i}(\theta) + \lambda J_{\mathcal{M}_i}(\theta, \phi) \right). \tag{3.21}$$

By minimizing this combined loss, the model learns embeddings that are both discriminative for classification and informative for reconstruction, enhancing generalization across tasks. The full algorithm of the Task-Decoder integration is provided in Algorithm 3.

We define tasks and Meta-Tasks as separable if their loss functions can be computed independently and summed without including interaction terms. This structure allows us to optimize each component separately while still contributing to the overall objective. If the regularization term is separable (as in our case with the autoencoder), we can simplify (3.21) as

$$J(\theta) = \sum_{i=1}^{L} J_{\mathcal{T}_i}(\theta) + \lambda \sum_{i=1}^{L} J_{\mathcal{M}_i}(\theta, \phi). \tag{3.22}$$

If each task may have multiple or no Meta-Tasks attached, the overall loss function generalizes to:

$$J(\theta) = \sum_{i=1}^{L} J_{\mathcal{T}_i}(\theta) + \lambda \sum_{r=1}^{R} J_{\mathcal{M}_r}(\theta, \phi), \tag{3.23}$$

where R is the total number of regularizers applied to the model.

3.8.4.3 Justification

Our Meta-Task framework provides unique theoretical guarantees, distinguishing it from existing regularization approaches. In Equations (3.22) and (3.23), we demonstrated that incorporating auxiliary tasks into training effectively reformulates the FSL paradigm to a new FSL setting with a combined distribution of primary tasks and Meta-Tasks, denoted as $\mathcal{T}'$. This reformulation allows the overall training objective to be expressed as a sum over $L + R$ tasks, preserving the structure necessary for standard FSL optimization techniques.

When using MAML as the FSL method, based on convergence guarantees proven in literature [207], our approach converges to an optimal set of parameters for $\mathcal{T}'$. Since the Meta-Tasks are carefully designed to enhance generalization, this optimal parameter set enables the model to generalize effectively across both primary tasks and Meta-Tasks. The convergence of ϕ to its global optima further ensures that the learned embeddings retain the essential information necessary for both classification and reconstruction. This joint optimization (θ) constructs a globally optimal representation space, improving overall model performance on unseen tasks by reducing generalization error.

A critical advantage of Meta-Task is the separability of the primary and auxiliary tasks. Since their loss functions can be computed independently, optimization can proceed efficiently, with each task contributing to the overall objective. This design simplifies the optimization process and supports convergence to a global optimum, as the auxiliary tasks act as an implicit regularizer, reducing overfitting by penalizing non-generalizable embeddings.

A rigorous mathematical proof is more challenging for FSL methods beyond MAML. However, as all FSL methods aim to optimize parameters that generalize across task distributions with limited examples, it is reasonable to infer that our approach improves generalization capabilities, as demonstrated in the results section. In the supplementary material,

we provide additional experiments, including visualizations of reconstructed features, to empirically validate how Meta-Task enhance embedding quality and task generalization.

Remark 1. *The proposed regularization approach is method-agnostic and can be applied to any FSL learning method.*

Remark 2. *Equations* (3.22)*,* (3.23) *hold only if tasks and Meta-Tasks are separable or independent.*

Remark 3. *The use of autoencoders is because autoencoders can be used with any type of data, are easy to use, and are flexible in architecture.*

3.8.5 Experiments and Results

In this section, we conduct comprehensive experiments to validate the effectiveness of our proposed Meta-Task framework in enhancing generalization and mitigating overfitting in few-shot learning. Our objectives are to:

1. Demonstrate that incorporating Meta-Tasks as auxiliary regularization improves model generalization to both seen and unseen tasks.

2. Validate that leveraging both labeled and unlabeled data through an unsupervised autoencoder refines hidden representations.

3. Showcase the method-agnostic applicability of Meta-Task across various FSL settings and its practical efficiency in resource-constrained scenarios.

We begin by outlining the experimental setup, including datasets, model architectures, and implementation specifics. Following this, we present our results along with a comprehensive analysis of our findings, focusing on the impact of the Meta-Task framework on performance, convergence speed, and variance reduction.

Algorithm 3 Meta-Tasks: Task-Decoder

1. **Require:** Distribution over tasks $p(\mathcal{T})$;
2. **Require:** embedding network f_θ;
3. **Require:** decoder network g_ϕ;
4. **Require:** learning rates α, λ;
5. **Require:** meta-learning method F (e.g., Prototypical Networks);
6. **Require:** classification loss $J_{\mathcal{T}}(x, \theta)$;
7. **Require:** reconstruction loss $J_{\mathcal{M}}(x, \theta, \phi) = \|g_\phi(f_\theta(x)) - x\|^2$
8. Randomly initialize θ and ϕ
9. **while** not done **do**
   (a) Sample support set $\mathcal{S} \sim p(\mathcal{T})$
   (b) Sample query set $\mathcal{Q} \sim p(\mathcal{T})$
   (c) Compute reconstruction loss:
   $J_{\mathcal{M}}(\theta, \phi) \leftarrow \frac{1}{|\mathcal{S} \cup \mathcal{Q}|} \sum_{x \in \mathcal{S} \cup \mathcal{Q}} J_{\mathcal{M}}(x, \theta, \phi)$
   (d) Use support set $\mathcal{S}$ and embedding network f_θ to obtain meta-learning method F_θ
   (e) Compute classification loss on query set:
   $J_{\mathcal{T}}(\theta) \leftarrow \frac{1}{|\mathcal{Q}|} \sum_{x \in \mathcal{Q}} J_{\mathcal{T}}(x, F_\theta)$
   (f) Update embedding network parameters:
   $\theta \leftarrow \theta - \alpha \nabla_\theta \left(J_{\mathcal{T}}(\theta) + \lambda J_{\mathcal{M}}(\theta, \phi) \right)$
   (g) Update decoder parameters:
   $\phi \leftarrow \phi - \lambda \nabla_\phi J_{\mathcal{M}}(\theta, \phi)$
10. **end while**

3.8.5.1 Datasets

We evaluated the proposed Meta-Task framework on three standard benchmarks commonly used in few-shot learning:

MiniImageNet [208]: This dataset consists of 100 classes selected from ImageNet, with 600 images per class resized to 84×84 pixels. It is divided into 64 training, 16 validation, and 20 test classes, ensuring that test classes are entirely disjoint from training classes for robust evaluation of generalization capabilities.

TieredImageNet [209]: A larger and more challenging dataset comprising 608 classes organized into 34 high-level categories, providing semantic diversity. It includes 351 training, 97 validation, and 160 test classes, with images resized to 84×84 pixels. Its hierarchical structure makes it suitable for evaluating models' ability to generalize across different levels of abstraction.

FC100 [210]: Derived from the CIFAR-100 dataset, FC100 contains 100 classes, each with 600 images resized to 32×32 pixels. The dataset is split into 60 training, 20 validation, and 20 test classes. It presents unique challenges due to low-resolution images and high intra-class variability, making it an excellent benchmark for assessing model robustness.

These datasets offer diverse and challenging scenarios for few-shot learning, enabling us to thoroughly evaluate the generalization capabilities of the Meta-Task framework.

3.8.5.2 Methods

To demonstrate the method-agnostic nature of our approach, we integrated the Meta-Task framework with four few-shot learning models:

Prototypical Network (PN) [13]: Utilizes a ResNet-50 [211] backbone for feature extraction. It computes class prototypes in the embedding space, classifying query samples based on their distances to these prototypes.

MAML [190]: Employs a four-layer ConvNet architecture aiming to find initial model parameters that can be quickly adapted to new tasks with minimal gradient updates.

MetaOptNet [141]: Uses a ResNet-12 backbone and incorporates differentiable convex optimization layers for efficient classification, seamlessly integrating with our Meta-Task framework.

P>M>F [206]: Uses DINO[**?**] framework as its backbone. Like PN, it computes class prototypes in the embedding space. It classifies query samples based on their distances to these prototypes but with the added benefit of leveraging pre-trained transformer-based feature extraction.

In our Meta-Task framework, we introduced a Task-Decoder employing an unsupervised autoencoder to reconstruct input images from their embeddings. The decoder mirrors the encoder architecture used in the backbone models. This process leverages both labeled and unlabeled data (support and query sets), refining the hidden representations and mitigating overfitting.

For the autoencoder architecture, we experimented with different configurations to assess the impact of the Task-Decoder's depth on performance. Specifically, we used both shallow and deep autoencoders, with parameters ranging from 75K to 250K. The shallow autoencoder consists of two convolutional layers, while the deep autoencoder includes four convolutional layers. This allowed us to analyze how the complexity of the Task-Decoder affects the overall performance.

We trained all models using the Adam optimizer with learning rates set to 1×10^{-4} for the encoder and classifier, and 1×10^{-6} for the Task-Decoder. Each model was trained over 50,000 episodes using 5-way 1-shot and 5-way 5-shot scenarios. The query size was maintained at 15 for both training and evaluation phases. To enhance model robustness, we applied standard data augmentation techniques, including random cropping, horizontal flipping, and color jittering.

Furthermore, we investigated the effect of using multiple autoencoders per task by associating different autoencoders with specific layers of the encoder network. However, we found that using a single autoencoder provided a good trade-off between performance improvement and computational overhead. The complete source code and results for this paper can be found in the following GitHub repository: https://github.com/woreom/meta-learning.

		MiniImageNet		TieredImageNet	
Method	Backbone	5-way 1-shot(%)	5-way 5-shot(%)	5-way 1-shot(%)	5-way 5-shot(%)
PN	ResNet18	45 ± 0.0	65.2 ± 0.0	46.6 ± 0.0	65.4 ± 0.0
PN(TD)	ResNet18	**47.9 ± 0.0**	**66.1 ± 0.0**	**50 ± 0.0**	**71.3 ± 0.0**
MAML	CNN	47.54	62.23	-	-
MAML (TD)	Shallow CNN Decoder	**47.81**	**62.52**	-	-
MAML (TD)	CNN	**47.67**	**63.01**	-	-
Relation Networks[137]	64-96-128-256	50.44 ± 0.82	65.32 ± 0.70	54.48 ± 0.93	71.32 ± 0.78
R2D2[212]	96-192-384-512	51.2 ± 0.6	68.8 ± 0.1	-	-
Transductive Prop Nets[213]	96-192-384-512	55.51 ± 0.86	69.86 ± 0.65	59.91 ± 0.94	73.3 ± 0.75
SNAIL[138]	ResNet-12	55.71 ± 0.99	68.88 ± 0.92	-	-
AdaResNet[214]	ResNet-12	56.88 ± 0.62	71.94 ± 0.57	-	-
TADAM[210]	ResNet-12	58.5 ± 0.30	76.7 ± 0.30	-	-
MetaOptNet	ResNet-12	61.23 ± 0.29	77.14 ± 0.21	63.10 ± 0.34	78.58 ± 0.27
MetaOptNet (TD)	ResNet-12	**61.35 ± 0.29**	**77.3 ± 0.22**	**63.20 ± 0.34**	**78.66 ± 0.27**
P>M>F	IN1K,ViT-base	**72.80 ± 0.0**	**90.70 ± 0.0**	-	-
P>M>F(TD)	IN1K,ViT-base	**74.10 ± 0.0**	**92.30 ± 0.0**	-	-

Table 3.15: Comparison of few-shot classification accuracies (%) with 95% confidence intervals on MiniImageNet and TieredImageNet datasets. Results are reported for 5-way 1-shot and 5-way 5-shot. ‘PN‘ and ‘TD‘ refer to Prototypical Networks and Task-Decoder, respectively.

3.8.5.3 Performance Evaluation

Our experimental results demonstrate that the Meta-Task framework consistently outperforms baseline models across all datasets and settings, achieving higher accuracy with significantly fewer training episodes. For example, as shown in Figure 3.6, TD enables higher test accuracy within 20k episodes, whereas PN Test fails to achieve the same even after 50k episodes. Similarly, in Table 3.15, TD P>M>F reaches 92.30% accuracy in 3k episodes compared to P>M>F's 90.70% after 4k episodes.



Figure 3.6: Accuracy curves for Prototypical Networks (PN) and Task-Decoder (TD) across different datasets, plotted against the number of episodes.

These results highlight the framework's efficiency in leveraging a small number of additional parameters to enhance generalization while reducing computational overhead. By



Figure 3.7: Loss curves for Prototypical Networks (PN) and Task-Decoder (TD) across different datasets, plotted against the number of episodes.

introducing Meta-Tasks, the learning process is effectively regulated, eliminating the need for extensive parameter tuning or large-scale episodic training. This makes the Meta-Task

Method	FC100 5-way 1-shot(%)	FC100 5-way 5-shot(%)
PN	31.1 ± 0.0	49.6 ± 0.0
PN (TD)	**39 ± 0.0**	**51.1 ± 0.0**
TADAM[210]	40.1 ± 0.4	56.1 ± 0.4
MetaOptNet	40.19 ± 0.25	55.04 ± 0.26
MetaOptNet (TD)	**40.59 ± 0.26**	**55.38 ± 0.25**

Table 3.16: Comparison of few-shot classification accuracies (%) with 95% confidence intervals on the FC100 dataset [210]. Results are reported for 5-way 1-shot and 5-way 5-shot settings. 'PN' and 'TD' refer to Prototypical Networks and Task-Decoder, respectively.

framework both lightweight and practical for real-world applications. Further details on are provided in Table 3.15 and Table 4.2.

Prototypical Network Results Table 3.15 presents our experimental results on MiniImageNet and TieredImageNet, where our proposed method, the Task-Decoder, demonstrates significant performance improvements over the baseline Prototypical Networks. Specifically, on TieredImageNet in the 5-way 5-shot setting, our approach achieved an increase from 65.4% to 71.3% in test set accuracy, reflecting a substantial 5.9% absolute improvement. This gain indicates superior meta-generalization capabilities of our method.

In the 5-way 1-shot scenario, the Task-Decoder improved accuracy from 46.6% to 50% on TieredImageNet, highlighting its efficacy in scenarios with extremely limited data. These consistent improvements across different datasets and settings demonstrate the robustness and effectiveness of our approach.

MAML Results Table 3.15 also showcases the performance of the Task-Decoder integrated with MAML. Our method outperforms the baseline MAML by an average of 0.48% in the 5-way 1-shot setting and 0.78% in the 5-way 5-shot setting on MiniImageNet. Although the absolute improvements are modest, they demonstrate the effectiveness of the Task-Decoder in enhancing the adaptability of MAML.

To examine the impact of the Task-Decoder's architecture (ϕ) on generalization, we

trained MAML using two differentTask-Decoders: a shallow decoder with 75K parameters and a deeper decoder with 250K parameters. Interestingly, the shallow decoder excelled in the 5-way 1-shot task, suggesting that deeper models are not always superior when data is scarce. In contrast, the deeper decoder performed better with more shots, highlighting the importance of model depth in specific contexts. This indicates that the Task-Decoder and its Meta-Task extensions can be effective even with a shallow network, which is beneficial in resource-constrained environments.

It's important to note that MAML requires the computation of second derivatives during optimization. However, to remain consistent with our claim of a method-agnostic framework, we chose to use a first-order approximation for the Task-Decoder's optimization. This decision avoids the computational overhead associated with second-order derivatives but may introduce approximation errors. Another limitation may stem from the inherent difficulties of optimizing the learning rate in MAML, which is complicated by the need for careful tuning due to its sensitivity to hyperparameters. While using the same learning rate as the Prototypical Networks simplifies comparisons, it likely constrained MAML's overall performance. These factors suggest that further optimization and fine-tuning could enhance the benefits of integrating the Task-Decoder with MAML.

textbfMetaOptNet Results The results presented in Table 3.15 indicate that integrating the Task-Decoder with MetaOptNet [179] leads to modest but consistent performance improvements, with an average accuracy increase of 0.12% in the 5-way 1-shot setting and 0.16% in the 5-way 5-shot setting on MiniImageNet. While these gains are not as pronounced as those observed with other methods, they underscore the potential of the Task-Decoder to enhance performance even in well-optimized frameworks like MetaOptNet.

We attribute the smaller improvements to MetaOptNet's distinctive training setup, where variations in batch size and the number of shots significantly impact model performance. Due to hardware limitations, we reduced the batch size and the number of training

shots, which may have constrained the performance gains. These findings suggest that further hyperparameter optimization, such as adjusting batch size or learning rate, could yield more substantial improvements.

P>M>F Results

Due to the pre-trained nature of the encoder, we implemented a custom scheduler to align TD's optimization. Additionally, hardware constraints necessitated deviations from the original hyperparameters, such as reducing image sizes and query shots, which may have influenced the observed improvements. Despite these constraints, TD achieved a notable 1.45% performance increase, demonstrating its flexibility and adaptability to transformer-based methods under constrained conditions.

3.8.5.4 Regularization Improvements

Figure 3.6 illustrates that our method achieves higher accuracy more quickly during all training, validation, and testing phases compared to the baseline, which demonstrates faster convergence. Additionally, Figure 3.7 illustrates that the loss associated with our method decreases more rapidly and consistently remains lower throughout the training process across all training, validation, and test sets. The Task-Decoder achieves a mean loss of 1.23 with a variance of 0.001, whereas the baseline has a mean loss of 1.3 and a variance of 0.0002. This indicates more efficient learning and improved generalization.

To address concerns regarding implementation specifics, we have provided detailed information about the hyperparameters, training times, and autoencoder architectures in the supplementary material. We also conducted ablation studies to analyze the effect of different autoencoder architectures and the use of multiple autoencoders per task. The results indicate that while deeper autoencoders can provide marginal performance gains, the computational overhead increases significantly. Therefore, a single, appropriately sized autoencoder strikes a good balance between performance and efficiency.

3.8.6 Conclusion

In this paper, we introduced the **Meta-Task** framework, a method-agnostic approach for regularization in few-shot learning (FSL) that leverages Meta-Tasks as auxiliary tasks with a set of parameters to mitigate overfitting. Theoretically, we demonstrated that our approach achieves global optima with strong generalization across tasks. Empirically, we validated its efficacy through the **Task-Decoder** Meta-Task, which significantly improved performance on MiniImageNet and TieredImageNet benchmarks, achieving faster convergence and reduced generalization error with minimal hyperparameter tuning. Overall, our findings highlight the potential of the Meta-Task framework to improve FSL models, suggesting that even minor adjustments can lead to significant benefits and encourage further exploration of Meta-Task-based regularization in broader contexts.

3.9 Overall Findings

Across the three core tasks—BEpiC, MetaRep, and Meta-Task—this work systematically advances the state of generalization in few-shot learning by addressing complementary challenges in episode generation, representation learning, and regularization.

Collectively, these contributions demonstrate that enhancing generalization in few-shot learning requires a holistic approach: (1) designing episodes that expose the learner to meaningful task diversity (BEpiC), (2) leveraging both labeled and unlabeled data to learn robust representations (MetaRep), and (3) integrating adaptive, learnable regularization mechanisms (Meta-Task). The empirical results consistently show that each method yields measurable improvements in accuracy, robustness, and data efficiency, and that their principles are broadly applicable across meta-learning paradigms.

These findings underscore the importance of principled episode construction, representation learning, and regularization in advancing few-shot learning. They also provide a foundation for future research on scalable, adaptable, and generalizable meta-learning systems capable of operating effectively in real-world, low-data environments.

Chapter 4

Unlabeled Data Utilization through Semi-Supervised Learning

4.1 Introduction

The abundance of unlabeled data in real-world scenarios presents both a challenge and an opportunity for modern machine learning systems. While supervised learning methods have achieved remarkable success, their reliance on large quantities of labeled data limits their applicability in domains where annotation is costly, time-consuming, or impractical. Semi-supervised learning (SSL) addresses this limitation by leveraging the vast pool of unlabeled data alongside a small set of labeled examples, enabling models to learn more robust and generalizable representations.

This chapter explores advanced semi-supervised learning techniques designed to maximize the utility of unlabeled data, with a particular focus on their application in image classification. We discuss the theoretical foundations of SSL, review state-of-the-art methods such as pseudo-labeling, consistency regularization, and self-supervised pretext tasks,

and highlight their strengths and limitations in data-constrained environments. Furthermore, we introduce novel approaches that integrate improved representation learning and pseudo-labeling strategies, demonstrating their effectiveness in enhancing classification accuracy and generalization with limited labeled data.

Through comprehensive experiments and analysis, we show how the proposed methods bridge the gap between supervised and unsupervised learning, offering practical solutions for scenarios where labeled data is scarce but unlabeled data is plentiful. The insights and techniques presented in this chapter contribute to the development of flexible, data-efficient machine learning frameworks capable of adapting to a wide range of real-world challenges.

4.1.1 Semi-Supervised Learning: An Overview

At its core, semi-supervised learning seeks to improve model performance beyond what is achievable with the limited labeled data alone by exploiting the information latent within the abundant unlabeled data. The fundamental principle is that the structure, patterns, or underlying distribution of the unlabeled data ($p(x)$) contains valuable information about the target function, specifically the conditional probability of the label given the input ($p(y|x)$). Labeled data points serve to ground the model's predictions, establishing the number of classes and their basic characteristics, while the unlabeled data provides crucial context about the overall shape and density of the data distribution, helping to refine decision boundaries.

The typical mechanism involves an initial learning phase where the model is trained on the small labeled dataset using conventional supervised techniques. Subsequently, the model leverages the unlabeled data, often in an iterative fashion, to refine its understanding and improve predictions. This refinement process varies depending on the specific SSL algorithm. For instance, when processing labeled data points, the algorithm updates model

parameters using traditional supervised loss functions that compare predictions to true labels. For unlabeled data points, the objective often shifts to minimizing the difference in predictions between similar unlabeled points or enforcing consistency in predictions under various perturbations.

The primary motivation behind the development and adoption of SSL stems from a fundamental challenge in practical machine learning: the data labeling bottleneck. Acquiring large datasets is often feasible and relatively inexpensive, especially with the proliferation of digital data sources. However, annotating this data with accurate labels typically requires significant human effort, domain expertise, time, and financial resources. This disparity between the ease of collecting unlabeled data and the difficulty of labeling it creates a scenario where vast amounts of potentially useful data remain underutilized by purely supervised methods. SSL directly addresses this imbalance, offering a pathway to potentially achieve performance comparable to fully supervised models but with a substantially reduced labeling requirement. The economic pressure to reduce annotation costs while still building high-performance models makes SSL not merely a technical curiosity but often an economic imperative in data-rich, label-poor environments. Its relevance is thus intrinsically linked to the practicalities and economics of data acquisition in the real world, growing in importance as data generation continues to outpace annotation capabilities.

A crucial prerequisite for successful SSL is the relevance of the unlabeled data to the learning task. Formally, the distribution of the input data, $p(x)$, as revealed by the unlabeled examples, must contain information about the posterior distribution $p(y|x)$. Using unlabeled data that is unrelated to the target classes (e.g., training a cat/dog classifier with unlabeled images of vehicles) will not improve performance and may even degrade it.

SSL techniques can be broadly categorized into several groups:

- **Generative Methods:** These approaches model the joint probability distribution of data

and labels, using both labeled and unlabeled data to estimate the underlying structure. Examples include generative adversarial networks (GANs) and variational autoencoders (VAEs) adapted for SSL. By learning the data distribution, generative models can synthesize new samples or infer missing labels, providing additional supervision for the learning process. These methods are particularly effective when the data distribution is complex and high-dimensional, as in image or text domains.

- **Self-Training and Pseudo-Labeling:** In these methods, a model trained on labeled data is used to assign pseudo-labels to unlabeled samples. The model is then retrained using both true and pseudo-labeled data, iteratively refining its predictions. This approach leverages the model's own confidence to expand the labeled dataset, but care must be taken to avoid reinforcing incorrect predictions. Techniques such as confidence thresholding and ensembling are often used to improve the reliability of pseudo-labels.

- **Consistency Regularization:** These techniques encourage the model to produce consistent predictions for unlabeled data under different perturbations or augmentations. Methods such as Mean Teacher, Virtual Adversarial Training (VAT), and FixMatch fall into this category. The underlying assumption is that the model's output should be invariant to small changes in the input, promoting smoother decision boundaries. Consistency regularization has proven highly effective in computer vision tasks, where data augmentations are easy to define.

- **Graph-Based Methods:** These approaches represent data as nodes in a graph, propagating label information from labeled to unlabeled nodes based on their similarity or connectivity. Graph-based SSL leverages the manifold structure of the data, assuming that similar samples are likely to share the same label. Techniques such as label propagation and graph convolutional networks (GCNs) are commonly used, especially in applications involving relational or networked data.

- **Self-Supervised Pretext Tasks:** Here, auxiliary tasks are designed to learn useful representations from unlabeled data, which can then be transferred to the main supervised task. Examples include predicting image rotations, solving jigsaw puzzles, or reconstructing masked input features. By solving these pretext tasks, models learn to extract semantic features from data without explicit labels, improving downstream performance when labeled data is limited.

The effectiveness of SSL depends on several assumptions, such as the cluster assumption (data points in the same cluster are likely to share a label) and the smoothness assumption (similar inputs have similar outputs). When these assumptions hold, SSL can significantly boost performance compared to purely supervised approaches.

4.2 Related Work

In this section, we review key developments in semi-supervised learning, focusing on major approaches and methodologies that have shaped the field. We examine how different techniques leverage unlabeled data to improve model performance, particularly in scenarios with limited labeled data availability.

4.2.1 Contrastive Learning

Contrastive learning has emerged as a powerful framework for self-supervised representation learning, achieving remarkable success across various domains, particularly computer vision. This approach learns representations by optimizing a contrastive objective that attracts semantically similar (positive) pairs while repelling dissimilar (negative) pairs in an embedding space [7]. In vision applications, positive pairs typically comprise augmented views of the same image, whereas negative pairs consist of different images.

Early contrastive methods faced scalability challenges due to their reliance on large numbers of negative examples to avoid representational collapse. SimCLR [7] demonstrated strong performance but required large batch sizes (4,096+) to provide sufficient negative examples, imposing substantial computational demands. MoCo [8] addressed this limitation through a momentum encoder and a dynamic queue of negative samples, effectively decoupling training batch size from the number of negative examples and enabling more efficient training on standard hardware.

The contrastive learning paradigm has been extended to multimodal and sequential domains with significant success. CLIP [63] scaled contrastive learning to 400 million image-text pairs, creating aligned visual and textual representations that enable remarkable zero-shot transfer to downstream tasks. In sequential data modeling, Contrastive Predictive Coding (CPC) [215] predicts future representations in latent space using a contrastive objective, capturing temporal dependencies across modalities including speech, images, and text.

Despite their empirical success, contrastive methods face fundamental limitations. The quality of learned representations depends critically on the sampling strategy for negative pairs and the design of data augmentations, which often require domain-specific knowledge. Additionally, the binary notion of similarity (positive/negative) may not capture complex semantic relationships, and the requirement for many negative examples can introduce sampling bias or computational inefficiency.

Recent research has explored alternatives to address these challenges, including hard negative mining [216], learnable data augmentation [217], and hybrid approaches that combine contrastive objectives with other self-supervised signals. PiCO [**?**] extend contrastive learning to partially labeled data by incorporating prototype-based objectives, while others leverage contrastive pre-trained models to identify reliable pseudo-labels for unlabeled

data. These developments highlight contrastive learning's importance in the broader semi-supervised learning ecosystem, particularly for label-efficient fine-tuning.

4.2.2 Representation Learning

Representation learning forms the cornerstone of modern semi-supervised approaches by transforming raw data into meaningful feature spaces where downstream tasks become more tractable. Central to this paradigm is the manifold hypothesis [218], which posits that high-dimensional data typically concentrates near lower-dimensional structures. Learning these manifolds enables models to disentangle important factors of variation while discarding noise, creating representations where the smoothness and cluster assumptions of SSL become more applicable [9].

Non-contrastive approaches address limitations of negative sampling by employing alternative objectives. BYOL [50] uses a teacher-student framework with a momentum-updated target network and successfully learns representations without negative examples. Similarly, SimSiam [51] demonstrates that even simpler architectures without momentum encoders can avoid representational collapse through careful use of stop-gradients and prediction heads. Redundancy reduction methods take yet another approach. Barlow Twins [52] minimizes redundancy between representation dimensions by making the cross-correlation matrix between two augmented views approach the identity matrix. This elegantly addresses both alignment and uniformity aspects of representation learning without requiring negative samples or momentum networks.

For sequential data, specialized methods have emerged. Wav2Vec [219] and its successors learn representations from raw audio by predicting future encodings in latent space, enabling breakthrough performance in speech recognition with limited labeled data. These

approaches demonstrate how representation learning can be adapted to the unique characteristics of different data modalities. Generative approaches offer a complementary perspective. Masked Autoencoders [101] learn representations by reconstructing images from heavily masked inputs, showing that predicting missing content creates powerful visual features that transfer well to downstream tasks. Earlier variants like Denoising Autoencoders [220] and Variational Autoencoders [11] similarly learn representations through reconstruction objectives.

Graph Neural Networks (GNNs) extend representation learning to non-Euclidean data by learning node embeddings that capture both node features and graph topology through message-passing operations [221, 222]. These approaches have enabled semi-supervised learning on relational data where traditional methods struggle.

The effectiveness of these representation learning techniques in semi-supervised scenarios stems from their ability to leverage unlabeled data to discover data manifolds that align with downstream task boundaries. When these learned representations capture the underlying semantic structure of the data, even simple classifiers can achieve strong performance with limited labeled examples [223]. This principle has driven the common two-stage approach of unsupervised pre-training followed by supervised fine-tuning that dominates modern semi-supervised learning.

4.2.3 Consistency-Based Learning

Consistency regularization has emerged as a cornerstone approach in modern semi-supervised learning, founded on the smoothness assumption that a model's predictions should remain invariant under reasonable perturbations of the input or model parameters [223, 9]. These methods leverage unlabeled data by enforcing consistency between

predictions of different views of the same instance, effectively expanding decision boundaries away from high-density regions without requiring explicit labels [224].

Early consistency-based methods established the fundamental paradigm through various perturbation strategies. The Pi-Model [225] applies stochastic augmentation and dropout, penalizing differences between predictions from two forward passes of the same sample. Temporal Ensembling [226] extends this by maintaining an exponential moving average (EMA) of past predictions to create more stable targets, reducing variance but introducing delayed feedback. Mean Teacher [227] addresses this limitation by averaging model weights rather than predictions, creating a teacher model that generates targets for the student model, enabling immediate consistency training with every batch.

Adversarial perturbation approaches like Virtual Adversarial Training(VAT) [228] generate worst-case perturbations within a norm-constrained neighborhood that maximally change model predictions, enforcing local Lipschitz continuity and improving robustness to adversarial examples. These methods are particularly effective in high-dimensional spaces where random perturbations might fail to challenge the model.

Data augmentation has proven especially powerful for consistency regularization in visual domains. Unsupervised Data Augmentation (UDA) [229] employs strong augmentations like RandAugment for unlabeled data while maintaining consistency with weakly-augmented versions. FixMatch [9] combines this insight with pseudo-labeling, using confident predictions from weakly-augmented images as targets for strongly-augmented views, creating a simple yet highly effective framework that has become a foundation for numerous subsequent approaches.

Interpolation-based methods further enrich the consistency learning landscape. MixMatch [10] introduces a holistic approach that combines temperature sharpening of pseudo-labels with MixUp augmentation applied across both labeled and unlabeled samples.

ReMixMatch [230] enhances this framework with distribution alignment between pseudo-labels and labeled data, and incorporates an auxiliary self-supervised rotation prediction task to improve feature learning.

Recent advances have focused on adaptive mechanisms that adjust consistency training dynamically. FlexMatch [231] introduces curriculum learning by adaptively setting confidence thresholds for each class based on learning status, addressing class imbalance issues in pseudo-labeling. CoMatch [232] integrates contrastive learning with consistency training by aligning both prediction-level and representation-level consistencies through a unified graph-based framework. Curriculum Consistency Training (CCT) [233] employs multiple auxiliary heads trained with progressively stronger augmentations, creating a natural curriculum that improves robustness.

Beyond conventional training, consistency principles have been extended to test-time adaptation scenarios. Test-Time Training (TTT) [234] applies self-supervised consistency losses during inference to adapt models to distribution shifts without requiring labels, demonstrating the versatility of consistency regularization beyond traditional SSL.

The consistent success of these approaches across diverse tasks and architectures highlights consistency regularization as a fundamental principle in modern machine learning that effectively leverages unlabeled data. Current research continues to explore combinations with other learning paradigms and applications to new domains, suggesting that consistency-based methods will remain central to semi-supervised learning advances.

4.2.4 Pseudo Labeling

In semi-supervised learning, pseudo-labeling is used on a highly accurate classifier to label and learn from it. This approach has proven effective in various applications like object detection [235, 236], image classification [237, 238], and speech recognition [239]. If pseudo

labels are inaccurately assigned, classifiers may learn from erroneous labels, diminishing their performance [240].

Many pseudo-labeling methods focus on enhancing the network through consistency loss [231], moving away from the traditional approach of retraining the model with pseudo labels [241]. Consistency-based methods ensure stable model predictions across various augmented views of the same input [242]. However, consistency loss typically updates the network with a fraction of the cross-entropy loss [243], reducing its impact. This diminished emphasis on consistency loss can hinder the network's optimal update, as it does not fully leverage retraining with pseudo labels [244].

MPL addresses the issue of incorrect pseudo-labeling by applying a meta-learning [179] approach. In MPL, the teacher uses its softmax predictions on unlabeled data to instruct the student. These predictions, commonly called soft labels, are a well-established concept in the literature on knowledge distillation [245, 246]. This additional adaptation empowers the teacher to generate more accurate pseudo labels for instructing the student network. MPL employs the same bi-level optimization technique from meta-learning [13, 148, 14] to iteratively update the teacher-student framework. Additionally, introducing a controlled noise in either the teacher or student network is helpful, especially when the two networks are similar. This noise injection boosts the learning process's robustness and generalization [247, 248].

4.3 Preliminaries

This section introduces the foundational concepts and notations relevant to semi-supervised learning, with a focus on representation learning methods and pseudo-labeling strategies.

4.3.1 Problem Setup

Let $\mathcal{D}_L = \{(x_i, y_i)\}_{i=1}^{N_L}$ denote a labeled dataset, where $x_i \in \mathcal{X}$ are input samples and $y_i \in \mathcal{Y}$ are their corresponding labels. Let $\mathcal{D}_U = \{u_j\}_{j=1}^{N_U}$ denote a much larger set of unlabeled samples, where $u_j \in \mathcal{X}$. The goal of semi-supervised learning is to leverage both $\mathcal{D}_L$ and $\mathcal{D}_U$ to train a model f_θ that generalizes well to unseen data.

4.3.2 Representation Learning with Two-Network Architectures

Modern semi-supervised representation learning methods often employ two-network architectures, such as the teacher-student or online-target frameworks. Prominent examples are BYOL [50], Barlow Twins [52], SimSiam [51] which consist of:

- **Online Network:** Parameterized by θ, this network receives an augmented view of an input and produces a representation.
- **Target Network:** Parameterized by ξ, this network receives a different augmented view of the same input. Its parameters are updated as an exponential moving average (EMA) of the online network: $\xi \leftarrow \tau\xi + (1-\tau)\theta$, where $\tau \in [0, 1)$ is the EMA decay rate.

The training objective encourages the online network's output to predict the target network's output for the same input under different augmentations, without requiring negative samples. This approach avoids representational collapse and enables effective use of unlabeled data by learning invariant and discriminative features.

4.3.3 Pseudo-Labeling

Pseudo-labeling is a widely used technique in semi-supervised learning where the model generates artificial labels for unlabeled data. The process typically involves:

1. Training a model on labeled data $\mathcal{D}_L$.

2. Using the trained model to predict labels (pseudo-labels) for samples in $\mathcal{D}_U$.

3. Selecting high-confidence predictions (e.g., those with maximum softmax probability above a threshold) as pseudo-labels.

4. Retraining or fine-tuning the model using both labeled and pseudo-labeled data.

Variants such as Mean Teacher [227] and Meta Pseudo Labels (MPL) [179] further refine this process by employing teacher-student frameworks, soft labels, and meta-learning strategies. The use of EMA for teacher updates and noise injection for regularization are common practices to improve stability and generalization.

4.3.4 Notation Summary

- $\mathcal{D}_L$: Labeled dataset
- $\mathcal{D}_U$: Unlabeled dataset
- f_θ: Model parameterized by θ
- ξ: Target/teacher network parameters (EMA of θ)
- τ: EMA decay rate
- $\hat{y}$: Pseudo-label assigned to an unlabeled sample

These preliminaries provide the basis for understanding the advanced semi-supervised learning methods.

4.4 Proposed Methodology: Maximizing Unlabeled Data Utility with Improved Representation Learning and Pseudo Labeling

An effective semi-supervised approach for representation learning involves two parallel networks - a trainable network and a momentum network. Two augmented versions of the input images go through these networks to predict their outputs and thereby learn the representation. However, this method often fails to maximize its full potential. We identify two major issues regarding data utilization: (1) the need for large batch sizes, which reduces efficiency in memory-constrained environments, and (2) the exclusion of unlabeled data during downstream tasks. We address these limitations with a two-step approach. First, we incorporate both original and augmented images into the trainable network and add a weighted loss term to enhance learning with the additional input. After pre-training, pseudo labels are generated in a meta-learning setup using two identical teacher-student networks, where the teacher network progressively outperforms the student by receiving feedback from it. Our approach, Representation Learning with Pseudo Labeling (RLPL), improves representation learning by achieving higher accuracy for half the batch size of existing methods. RLPL demonstrates an average performance gain of **6.12%** across the STL-10, CIFAR-10, and SVHN datasets, with individual improvements ranging from **2.7%** to **15.74%**.

4.4.1 Introduction

While supervised machine learning algorithms thrive on labeled data, manually annotating this data can be both time-consuming and costly. In contrast, unlabeled data is often readily available and abundant. Although it lacks explicit labels, unlabeled data still holds

valuable information that machine learning models can harness. Semi-supervised learning bridges this gap by extracting meaningful patterns from unlabeled data, compensating for the limited labeled datasets [249]. It achieves this by utilizing the unlabeled data to uncover latent representations—underlying structures and relationships that aren't directly observable. Semi-supervised learning can enhance model performance by incorporating these latent representations, even when labeled data is scarce [250, 251].

Contrastive learning [252, 253] has been proven effective in learning the data representation using the unlabeled sample. However, they require negative samples to avoid representational collapse [254] and hence were plagued by the problem of mining negative samples [255]. There are no apparent methods to obtain effective negative samples, and the presence of higher negative samples than positive ones creates an imbalance [256]. Subsequently, contrastive learning methods rely on a large batch size [257] to achieve good performance, leading to expensive computational needs.

Representation Learning (RL) methods, such as Bootstrap Your Own Latent (BYOL), SimSiam, and Barlow Twins solve the problem of negative samples by learning representation from the positive class alone. While these methods achieve impressive results with large batch sizes (typically 1024-4096), their performance degrades significantly with smaller batches. This degradation occurs because larger batches provide better gradient estimates and more diverse learning signals, which are crucial for stable representation learning. However, the high memory requirements of large batches make these methods impractical for resource-constrained environments.

Our analysis reveals that the performance drop in existing methods with smaller batches (8-128) stems from two key factors: (1) unstable gradient estimates leading to suboptimal convergence, and (2) limited diversity in the learning signals within each batch. RLPL addresses these challenges through a novel approach that maximizes information utilization from each sample, enabling stable learning even with smaller batches. Through extensive

experimentation across different batch sizes, we demonstrate that RLPL maintains consistent performance, showing only a marginal accuracy drop with reduced batch sizes.

Unlabeled data, typically unused in downstream tasks, can enhance performance when leveraged through a model with strong initialization. Pseudo-Labels (PL) [258] employ a confidence threshold to selectively include those unlabeled samples for which the classifier demonstrates high certainty in its predictions. RL offers an effective initialization, enabling improved model performance and confident pseudo-labeling. However, a notable challenge arises when incorrect pseudo labels are assigned, leading to a degradation in classifier accuracy due to learning from corrupted data. RLPL addresses this issue by refining the pseudo labels through a teacher-student network. This process enhances the teacher network, making it a better model to guide the student network, thereby generating more accurate pseudo labels and boosting overall performance.

Typical RL methods demand extensive computational resources, such as hundreds of TPUs over several days. Additionally, pseudo-labeling is another memory-heavy method as it uses two networks simultaneously. These requirements are challenging in scenarios where fast, efficient models are needed, like in autonomous vehicles or edge computing [**?**]. To address these limitations, we implement RLPL on a more manageable batch size and a shallower network, leveraging just two Nvidia 4090 GPUs. Our study shows that RLPL, even without the usage of pseudo labeling, achieves higher accuracy with a batch size of 64, outperforming BYOL with a 128 batch size. Remarkably, RLPL consistently outperforms other RLs with a ResNet18 classifier. RLPL yields average accuracy improvements of **2.7%**, **9.22%**, and **4.16%** that the closest contemporary method on the STL-10, CIFAR-10, and SVHN datasets, respectively. Figure 4.1 illustrates our proposed framework. Codes are available at https://github.com/atik666/rlpl.



Figure 4.1: **RLPL flowchart.** RLPL has two levels of unlabeled data utilization. First, it employs unsupervised representation learning. Second, We obtain a highly accurate fine-tuned classifier using only a handful of label data. Lastly, through pseudo labelling using teacher-student networks, both initialized from superior supervised backbone, we improve the classifier further.

4.5 Introduction

4.5.1 Contributions

In summary, our work contains the following contributions:

- Our approach cleverly leverages most information from the inputs, leading to enhanced global representation learning. By making this strategic adjustment, our model achieves improved representations with a smaller batch size, ultimately achieving higher accuracy in the downstream tasks.

- During the downstream task, we utilize unlabeled samples a second time with pseudo labeling. Our approach uses the student network feedback with a meta-loss update to

improve the noisy teacher [259] as the final classifier.

- RLPL outperforms other State-Of-The-Art (SOTA) RL algorithms on an equivalent but more compact architecture, making it more efficient and cost-effective for edge computing in resource-constrained environments.

4.5.2 Proposed Methodology: RLPL

We propose a novel framework, RLPL, effectively utilizes unlabeled data through two key innovations: (1) enhanced representation learning with auxiliary loss functions, and (2) refined pseudo-labeling with meta-learning. This section details the technical aspects of our approach.

4.5.2.1 Improved Representation Learning

In RLPL, the trainable and momentum networks use identical encoders for image embeddings. These embeddings are projected to a lower-dimensional space using a Multi-Layer Perceptron (MLP) in each network. The momentum network stops here, producing outputs with a dimension of 256. In contrast, the trainable network includes an additional prediction head, consisting of another MLP layer with the same dimension.

RLPL learns a representation y_θ for downstream tasks using encoder f_θ, a projector g_θ, and a predictor q_θ. The momentum network, f_ξ, with a projector g_ξ, mirrors the trainable network's architecture but updates as an exponential moving average with decay rate, $\gamma \in [0, 1]$:

$$\xi \leftarrow \gamma\xi + (1 - \gamma)\theta. \tag{4.1}$$

For an input image x, we create two augmented views v and v'. The trainable network



(a) main loss calculation (b) auxiliary loss calculation

Figure 4.2: Representation learning with RLPL: **(a)** The augmented inputs are processed through both networks to compute the main loss. **(b)** The original and augmented inputs are fed into the trainable network to compute the auxiliary loss.

computes $y_\theta \triangleq f_\theta(v)$ and $z_\theta \triangleq g_\theta(y_\theta)$, while the momentum network outputs $y'_\xi \triangleq f_\xi(v')$ and $z'_\xi \triangleq g_\xi(y'_\xi)$.

We then predict z'_ξ from z_θ using $q_\theta(z_\theta)$, and l_2-normalize both $q_\theta(z_\theta)$ and z'_ξ to $\bar{q}_\theta(z_\theta) \triangleq \frac{q_\theta(z_\theta)}{\|q_\theta(z_\theta)\|_2}$ and $\bar{z}'_\xi \triangleq \frac{z'_\xi}{\|z'_\xi\|_2}$. The loss function is the mean squared error between the normalized prediction and momentum projection (as shown in Figure 4.2a):

$$L_{\theta,\xi} \triangleq \left\|\bar{q}_\theta(z_\theta) - \bar{z}'_\xi\right\|_2^2 = 2 - 2 \cdot \frac{\langle q_\theta(z_\theta), z'_\xi \rangle}{\|q_\theta(z_\theta)\|_2 \cdot \|z'_\xi\|_2}. \tag{4.2}$$

To symmetrize the loss, we feed v' to the trainable network and v to the momentum network, computing $\tilde{L}_{\theta,\xi}$. The combined loss for optimization is:

$$L^{\text{main}}_{\theta,\xi} = L_{\theta,\xi} + \tilde{L}_{\theta,\xi}. \tag{4.3}$$

To calculate the auxiliary loss, the original image goes through the online network as an additional input (as shown in Figure 4.2b). For original input x and augmented views v, v', we obtain outputs $q_\theta(z^x_\theta) \triangleq q_\theta(g_\theta(f_\theta(x)))$, $q_\theta(z^v_\theta) \triangleq q_\theta(g_\theta(f_\theta(v)))$, and $q_\theta(z^{v'}_\theta) \triangleq q_\theta(g_\theta(f_\theta(v')))$, respectively. We design an auxiliary loss that allows gradient flow during backpropagation. This auxiliary loss is combined with the main loss, weighted by a factor

λ. The momentum network stays the same, but the trainable network affects its update parameters.

We calculate the mean of two output embeddings, $\bar{q_\theta}(z_\theta^{vv'})$, from the prediction head.

$$\bar{q_\theta}(z_\theta^{vv'}) = \frac{1}{2}\left(\bar{q_\theta}(z_\theta^{v}) + \bar{q_\theta}(z_\theta^{v'})\right) \tag{4.4}$$

where $\bar{q_\theta}(z_\theta^{v})$ and $\bar{q_\theta}(z_\theta^{v'})$ are the batch-mean of their respective embeddings, $q_\theta(z_\theta^{v})$ and $q_\theta(z_\theta^{v'})$.

Now, we denote the auxiliary loss as L_θ^{aux} and it is expressed as,

$$L_\theta^{\text{aux}} = \left\| \bar{q_\theta}(z_\theta^{x}) - \bar{q_\theta}(z_\theta^{vv'}) \right\|_2^2 \tag{4.5}$$

where $\bar{q_\theta}(z_\theta^{x})$ is the batch-mean of $q_\theta(z_\theta^{x})$.

Next, it is added to the main loss with a weight, λ, to obtain the total loss.

$$L_{\theta,\xi} = L_{\theta,\xi}^{\text{main}} + \lambda L_\theta^{\text{aux}} \tag{4.6}$$

Optimization updates the trainable network parameters θ with a learning rate η, while the momentum network parameters are updated as follows:

$$\theta \leftarrow \text{optimizer}(\theta, \nabla_\theta L_{\theta,\xi}, \eta), \tag{4.7}$$

$$\xi \leftarrow \gamma\xi + (1-\gamma)\theta. \tag{4.8}$$

After training, only the encoder f_θ is returned for the downstream tasks. The pseudo-code for these steps is provided in Algorithm 4.

Algorithm 4 Representation learning with RLPL

```
# f_t: trainable net (backbone + projector + predictor)
# f_m: momentum net (backbone + projector)
# lambda: weight of auxiliary loss
# gma: momentum update rate

for x in loader: # load a minibatch
    v1, v2 = augment(x) # two random augmentations

    # compute embeddings
    t, t1, t2 = f_t(x), f_t(v1), f_t(v2) , # N × D

    with torch.no_grad(): # stop the gradient
        m1, m2 = f_m(v1), f_m(v2) # N × D

    # calculate the losses
    loss_main = (loss1(t1, m2) + loss1(t2, m1)).mean()
    loss_aux = loss2(t, t1, t2)
    total_loss = loss_main + lambda * loss_aux
    total_loss.backward() # optimization step
    update(f_t.params)

    # momentum network update
    f_m.params = gma*f_m.params+(1-gma)*f_t.params

def loss1(a, b): # main loss function
    a = normalize(a, dim=-1)
    b = normalize(b, dim=-1)
    loss = 2 - 2 * (a * b).sum(dim=-1)
    return loss.mean()

def loss2(a, b, c): # auxiliary loss function
    avr_emb = mean(b, c, dim=-1)
    loss = loss1(a - avr_emb)
    return loss.mean()
```

4.5.2.2 Effective Pseudo Labeling

For effective pseudo-labeling, let, f_{θ_T} and f_{θ_S} denote teacher and student networks initialized with parameters $\theta_T, \theta_S \leftarrow \theta$ from the pretrained encoder. Given a batch of labeled samples $(x_l, y_l) \in \mathcal{D}_l$ and unlabeled samples $x_u \in \mathcal{D}_u$, we formulate an iterative pseudo-labeling framework.

For each iteration, we first compute the student's initial loss on labeled data:

$$L_{s1} = \mathbb{E}_{(x_l,y_l)\sim\mathcal{D}_l}[\text{CE}(f_{\theta_S}(x_l), y_l)] \tag{4.9}$$

For unlabeled data x_u, the teacher network generates soft pseudo-labels through weak augmentation $\mathcal{A}$:

$$\hat{y}_u = f_{\theta_T}(\mathcal{A}(x_u)) \tag{4.10}$$

To ensure quality of pseudo-labels, we filter predictions based on confidence threshold τ:

$$\mathcal{M}_u = \{(x_u, \hat{y}_u) | \max(f_{\theta_T}(\mathcal{A}(x_u))) \geq \tau\} \tag{4.11}$$

The teacher then learns from the filtered pseudo-labeled data:

$$L_u = \mathbb{E}_{(x_u,\hat{y}_u)\sim\mathcal{M}_u}[\text{CE}(f_{\theta_T}(x_u), \hat{y}_u)] \tag{4.12}$$

After updating the student parameters using L_u, we measure its new performance:

$$L_{s2} = \mathbb{E}_{(x_l,y_l)\sim\mathcal{D}_l}[\text{CE}(f_{\theta_S}(x_l), y_l)] \tag{4.13}$$

The effectiveness of pseudo-labeling is captured by the performance change:

$$\Delta L_s = L_{s2} - L_{s1} \tag{4.14}$$

We incorporate this feedback through a meta-loss:

$$L_{\text{meta}} = \Delta L_s \cdot L_u \tag{4.15}$$

The final objective for updating the teacher combines supervised learning on labeled data with the meta-loss feedback:

$$L_{\text{total}} = \underbrace{\mathbb{E}_{(x_l,y_l)\sim\mathcal{D}_l}[\text{CE}(f_{\theta_T}(x_l), y_l)]}_{\text{supervised loss}} + \underbrace{L_{\text{meta}}}_{\text{feedback}} \tag{4.16}$$

This formulation creates a feedback loop where the teacher's pseudo-labeling strategy is dynamically adjusted based on the student's learning outcomes. When $\Delta L_s < 0$, indicating improved student performance, the teacher is encouraged to maintain its current strategy. Conversely, when $\Delta L_s > 0$, suggesting degraded performance, the teacher receives a stronger gradient signal to modify its approach.

The optimization proceeds iteratively:

$$\theta_S \leftarrow \theta_S - \eta_S \nabla_{\theta_S} L_u \tag{4.17}$$

$$\theta_T \leftarrow \theta_T - \eta_T \nabla_{\theta_T} L_{\text{total}} \tag{4.18}$$

where η_S and η_T are learning rates for student and teacher networks respectively. After training convergence, only the teacher network is retained for deployment. The pseudo-code is provided in Algorithm 5.

Algorithm 5 Pseudo labeling with RLPL

```
# f_t: pretrained encoder
# n_t, n_s: teacher and student networks
# tau: pseudo labels threshold

n_t = f_t.state_dict() # initialize teacher
n_s = f_t.state_dict() # initialize student

# load a minibatch of labeled and unlabeled samples
for x, y, x_u in loader:
    with torch.no_grad(): # stop the gradient
        loss_s1 = cross_entropy(n_s(x), y)
    y_u = n_t(x_u)

    # filtering unlabled samples based on threshold
    x_u, y_u = x_u [y_u ≥ tau], y_u [y_u ≥ tau]
    y_ut = n_t(augment(x_u)) # weak augmentation
    loss_t = cross_entropy(y_ut, y_u)
    loss_t.backward()
    update(n_s.params) # student network update

    with torch.no_grad(): # stop the gradient
        loss_s2 = cross_entropy(n_s(x), y)
    change = loss_s2 - loss_s1
    meta_loss = change * loss_t # meta-loss computation
    loss = cross_entropy(n_t(x), y)
    total_loss = loss + meta_loss # total loss
    total_loss.backward()
    update(n_t.params) # teacher network update
```

4.5.3 Experiments

We conduct extensive experiments to evaluate RLPL's performance across multiple datasets and settings. Our analysis focuses on three key aspects: (1) the effect of batch size on representation learning quality, (2) comparison with state-of-the-art methods on standard benchmarks, and (3) ablation studies to validate our design choices. The following sections

detail our experimental setup and findings.

4.5.3.1 Datasets

Our experiments utilized a diverse collection of image datasets to thoroughly evaluate the effectiveness of our proposed approach. Below, we provide a detailed description of each dataset used in our study:

STL-10 [260] is specifically designed for unsupervised and self-supervised learning research. It contains 13,000 labeled images across 10 object categories (airplane, bird, car, cat, deer, dog, horse, monkey, ship, and truck) and 100,000 unlabeled images sampled from a similar but broader distribution. A key characteristic of STL-10 is its relatively high-resolution images (96×96 pixels), making it more challenging than lower-resolution alternatives. The limited labeled training set (500 images per class) combined with abundant unlabeled data makes it an ideal benchmark for semi-supervised learning approaches, closely mirroring real-world scenarios where labeled data is scarce.

CIFAR-10 [261] consists of 60,000 color images (32×32 pixels) divided into 10 mutually exclusive classes (airplane, automobile, bird, cat, deer, dog, frog, horse, ship, truck). The dataset is split into 50,000 training and 10,000 test images, with each class having an equal number of samples. While the entire training set was used for representation learning, we specifically created label-limited scenarios with only 250, 1,000, and 4,000 labeled examples to evaluate model performance under varying degrees of supervision. This approach allows us to assess how effectively our method leverages unlabeled data when labeled samples are extremely scarce.

SVHN [262] (Street View House Numbers) is derived from Google Street View images and presents a real-world object recognition task focused on digit classification. It contains over 600,000 digit images in its complete version, with 73,257 digits for training, 26,032 for testing, and an additional 531,131 less difficult samples that can be used as extra training

data. Unlike handwritten digit datasets, SVHN presents additional challenges with real-world variations in lighting, orientation, and background clutter. The images are 32×32 pixels in color, and like CIFAR-10, we constructed supervision-limited scenarios with 250, 1,000, and 4,000 labeled examples.

For transfer learning evaluation, we employed six additional image datasets with varying characteristics:

CIFAR-100 [263] is similar to CIFAR-10 in image size (32×32 pixels) but contains 100 fine-grained classes grouped into 20 superclasses. With 600 images per class (500 training, 100 testing), it presents a more challenging fine-grained classification task.

Fashion-MNIST [264] is designed as a more challenging drop-in replacement for the traditional MNIST dataset. It consists of 70,000 grayscale images (28×28 pixels) of fashion items across 10 categories, divided into 60,000 training and 10,000 test examples. This dataset helps evaluate model performance on grayscale images with more complex patterns than digits.

LFW [265] (Labeled Faces in the Wild) contains 13,233 face images of 5,749 individuals collected from the web. These images present natural variations in pose, lighting, expression, and background, making it a challenging benchmark for face recognition tasks. We used the aligned version of the dataset with cropped faces.

EuroSAT [266] is a land use and land cover classification dataset derived from Sentinel-2 satellite imagery. It contains 27,000 labeled images (64×64 pixels) across 10 classes, representing various land use patterns. This dataset helps evaluate the model's performance on remote sensing applications.

Oxford Flowers 102 [267] includes 8,189 images of 102 flower categories common in the United Kingdom. Each class contains between 40-258 images with significant variations in scale, pose, and lighting. This fine-grained classification task presents a different challenge due to its natural image variability and smaller sample size per class.

Imagenette [268] is a subset of 10 easily distinguishable classes from ImageNet (tench, English springer, cassette player, chain saw, church, French horn, garbage truck, gas pump, golf ball, parachute). With approximately 13,000 training images and larger dimensions than the other datasets, it tests the model's ability to handle higher-resolution natural images.

This diverse collection of datasets enables a comprehensive evaluation of our proposed method across a wide range of image domains, resolutions, class numbers, and task difficulties, demonstrating its versatility and general applicability to various computer vision scenarios.

4.5.3.2 Implementation Details

Image augmentations: Our augmentation pipeline follows SimCLR and BYOL, using PyTorch [269]. We apply "RandomResizedCrop" (scale: [0.2, 1.0]), "RandomHorizontalFlip", "ColorJitter" (brightness, contrast, saturation: 0.4, hue: 0.1), "RandomGrayscale" (p=0.2), and "GaussianBlur" (σ=[1.0, 2.0], p=0.2). Images are normalized using standard mean and variance values.

Our experiments reveal that image resolution significantly affects accuracy; thus, we resize all images to 256×256. In the PL phase, weak augmentations are applied to the teacher model, involving random horizontal and vertical flips, each with a probability of 0.25.

Architecture: We use ResNet18 [270], a more computationally feasible network, designed for GPU computations. This ResNet18 architecture remains consistent across all settings, including representation learning, and pseudo labeling. The MLPs, projection, and prediction layers adhere to the parameters established by BYOL. In PL, the teacher and student networks are initialized from the ResNet18, pre-trained via RL.

Optimization: The RL framework was optimized using the Adam optimizer [271],

whereas PL employed the Stochastic Gradient Descent (SGD) optimizer [272], both with a learning rate set to 0.0003. The auxiliary loss is weighted at 0.5. RL underwent training for 50 epochs with a batch size of 128, while PL was trained over 150 epochs with a batch size of 16.



Figure 4.3: Effect of batch size on model performance (evaluated on STL-10).

Methods	**Test Accuracy (%)**
Baseline (ResNet18)	53.16
FixMatch [9]	37.28
MixMatch [10]	71.60
MoCo	66.25
SimSiam	64.50
Barlow Twins	64.25
BYOL	81.94
RLPL (Ours)	**84.64**

Table 4.1: Performance of different methods on STL-10 dataset.

4.5.4 Results and Discussion

Method	CIFAR-10			SVHN			Average
	250 labels	1000 labels	4000 labels	250 labels	1000 labels	4000 labels	
ResNet18	33.90	43.71	58.47	41.20	84.58	87.60	58.24
MoCO	34.50	46.75	61.88	30.75	83.25	89.12	57.37
SimSiam	23.88	29.50	48.88	14.62	51.25	67.38	39.92
Barlow Twins	35.88	47.75	63.75	21.88	79.01	88.25	56.42
BYOL	33.19	46.92	59.29	67.00	85.60	88.20	63.70
RLPL (ours)	**48.93**	**52.45**	**65.69**	**72.12**	**88.39**	**92.78**	**70.39**

Table 4.2: Test accuracy (%) of different methods on varying numbers of training samples.

Method	STL-10	CIFAR-10			SVHN			Average
		250 labels	1000 labels	4000 labels	250 labels	1000 labels	4000 labels	
PL (random init.)	53.34	30.49	40.57	55.90	11.19	17.62	75.62	40.39
RLPL w/o PL	83.20	34.54	48.48	59.60	71.25	85.54	89.00	67.66
RLPL (ours)	**84.64**	**48.93**	**52.45**	**65.69**	**72.12**	**88.39**	**92.78**	**72.14**

Table 4.3: Test accuracy (%) for ablation on methods.

Our evaluation methods primarily comprise the baseline model, BYOL, SimSiam, MoCo, Barlaw Twins, RLPL, and two additional semi-supervised algorithms, FixMatch [9], and MixMatch [10] on the considered datasets. In all our experiments, we re-implemented each algorithm on a ResNet18 backbone with identical hyperparameters to ensure a fair comparison.

4.5.4.1 Effect of Batch Size

To illustrate the effectiveness of RLPL with reduced batch sizes, we present the results in Figure 4.3. We started with a batch size of 8 for RLPL. Subsequently, we gradually increased the batch sizes for RLPL and others to evaluate their performances. To have a fair comparison, we applied the classification tasks only on the learned representation of RL, without any use of PL. As anticipated, the accuracy diminished with smaller batch

sizes. Remarkably, at a batch size of 64, RLPL attained an accuracy of 82.24%, surpassing BYOL's accuracy of 81.94% with a batch size of 128. All other methods, including Barlow Twins, MoCo, and SimSiam, achieve significantly lower accuracy in the small-scale implementation, with their performance further declining as batch size decreases. Although all methods exhibited a decline in accuracy with further reductions in batch sizes, RLPL consistently outperformed BYOL and all the others.

4.5.4.2 Classification Accuracy

Table 4.1 reports the classification accuracy on the STL-10 dataset. The ResNet18 classifier demonstrates challenges in reaching acceptable accuracy levels. For a fair comparison, all methods, including FixMatch and MixMatch, were implemented with a ResNet18 backbone and an identical batch size.

The results reveal that FixMatch struggles to achieve competitive accuracy, likely due to the limitations of pseudo-labeling techniques, which often require robust initialization and a deep backbone to perform effectively. While MixMatch shows considerable improvement, it still falls short of the performance attained by BYOL and RLPL. MoCo, SimSiam, and Barlow Twins achieve almost similar but lower accuracy. Notably, BYOL achieves an accuracy of 81.94%, whereas RLPL surpasses this with an accuracy of 84.64%, obtaining a **2.7%** improvement over BYOL.

Table 4.2 compares ResNet18, the four primary methods central to this study, and RLPL across varying training samples. For both datasets, all methods showed progressively higher accuracies with increasing sample sizes. We observe that our method uniquely achieves acceptable accuracy on CIFAR-10 with only 250 labels, whereas other methods struggle under the same conditions. For SVHN with 250 labels, only BYOL and RLPL reach satisfactory accuracy, while other methods perform notably worse. Notably, Notably, RLPL consistently achieved the highest accuracy across all datasets and under all varying

configurations, outperforming other methods in each case.

We include a column displaying the average test accuracy across all setups to provide a comprehensive view of the relative performance of each method. Only BYOL comes close to RLPL's performance; however, it still lags by a margin of **6.69%**. Nevertheless, RLPL consistently outperformed BYOL across all scenarios, particularly with smaller sample sizes, with improvement margins ranging from **2.79%** to **15.74%**.

4.5.4.3 Transfer to Other Classification Tasks

Method	CIFAR100	FashionMNIST	LFW	EuroSAT	OxfordFlowers102	Imagenette	Average
ResNet18	58.09	94.55	85.03	93.62	38.48	80.66	75.07
MoCo	62.50	90.54	**93.21**	95.00	35.00	79.88	76.69
SimSiam	33.88	92.63	80.41	79.38	26.12	76.82	64.54
Barlow Twins	58.75	94.38	89.19	94.62	27.88	80.38	74.87
BYOL	63.61	93.62	80.73	**96.28**	49.64	86.13	78.67
RLPL w/o PL	**68.08**	**96.01**	89.33	96.03	**51.67**	**87.94**	**81.51**

Table 4.4: Performance comparison (% test accuracy) of methods on various datasets.

We evaluated RLPL's generalization on diverse classification tasks, as shown in Table 4.4. This table compares RLPL's performance with baseline and other methods after pretraining on the STL-10 dataset, followed by the downstream tasks. For a fair comparison, we applied the pretrained RLPL model directly, without using PLs in the classification tasks. This approach highlights RLPL's standalone performance; notably, integrating PL strategies could likely enhance accuracy beyond the presented results.

RLPL achieves the highest accuracy in nearly all cases, except for MoCo on the Labeled Faces in the Wild (LFW) dataset and BYOL on the EuroSAT dataset. RLPL obtains an average accuracy of 81.51%, substantially outperforming methods like SimSiam and Barlow Twins. Moreover, RLPL obtains **2.84%** more accuracy than the closest best method, BYOL, across all the transfer learning tasks. This improvement highlights RLPL's transferability on unseen classification tasks.

4.5.5 Ablation Study

To validate our design choices and understand the contribution of each component, we conducted comprehensive ablation studies. We analyzed the impact of representation learning, pseudo-labeling, and their combination across different datasets and label regimes. Additionally, we investigated the effects of key hyperparameters like auxiliary loss weight and pseudo-label thresholds.

4.5.5.1 Framework Ablation



(a) Effect of the auxiliary loss weight, λ.

(b) Effect of the pseudo labels threshold, τ.

Figure 4.4: Effects of different hyperparameters on model performance.

We conduct extensive ablation studies to evaluate the effectiveness of our method against the PL algorithm with random initialization and RLPL without PLs. Results in Table 4.3 demonstrate the consistent superiority of RLPL across diverse datasets and label regimes. The PL with random initialization exhibits limited performance, particularly struggling with low-label scenarios (e.g., 30.49% and 11.19% accuracy with 250 labels), highlighting the importance of proper initialization for PL's reliability.

RLPL without pseudo labeling shows substantial improvements over the baseline,

achieving gains on STL-10 (83.20% vs 53.34%) and SVHN (71.25% vs 11.19%), validating the effectiveness of our representation learning strategy. The full RLPL framework, integrating both representation learning and pseudo labeling, consistently achieves the highest performance across all configurations, with particularly strong improvements in low-label settings (e.g., 48.93% on CIFAR-10 with 250 labels, an 18.44% improvement). This comprehensive performance advantage is reflected in the average accuracy across all settings, demonstrating RLPL's robust capability, especially in label-scarce scenarios where traditional approaches typically falter.

4.5.6 Ablation on Noisy Teacher

Method	Accuracy (%)
Noisy Student	84.54 ± 0.05
Noiseless Teacher	84.59 ± 0.02
Noisy Teacher	84.63 ± 0.02

Table 4.5: Input types ablation for pseudo labeling.

We investigate the impact of noisy samples (weakly augmented) in both teacher and student networks. Table 4.5 shows the average performance of five different runs for three configurations: the noisy student, the noiseless teacher, and our proposed noisy teacher method. While the differences are subtle, they reveal interesting patterns in model behavior. The noisy student achieves 84.54% accuracy with a standard deviation of 0.05, suggesting some variability in performance. When we remove noisy samples from the teacher network, we observe a marginal improvement to 84.59% with reduced variance. Our proposed approach achieves the highest accuracy at 84.63% with consistently low variance. These results suggest that weak augmentation in the teacher network inputs can provide additional regularization benefits.

4.5.7 Parameter Studies

We conduct parameter sensitivity studies to examine the impact of key hyperparameters on RLPL's performance, focusing on the auxiliary loss weight and pseudo-label threshold. These studies help validate our design choices and provide insights for optimal configuration.

4.5.7.1 Weight of the Auxiliary Loss

We modify the weight of auxiliary loss, λ, from 0.25 to 1.0 with an increment of 0.25. We observe that there is a strong effect of the weight on model performance. For weights other than 0.50, the test accuracy declines as we move further from this value. The outputs are shown in Figure 4.4a.

4.5.7.2 Threshold for Pseudo Labels

We vary the threshold, τ, from 0.85 to 1.0 with an increment of 0.05. We observe that the highest accuracy is obtained at 0.95, and it keeps decreasing for a lower threshold value. Again, the accuracy decreases for a threshold value of 1.0. For any threshold other than 0.95, the accuracy drops below 84.0%. The outputs are shown in Figure 4.4b.

4.5.8 Conclusion

We present RLPL, a novel semi-supervised learning framework that maximizes unlabeled data utility while addressing limitations in existing methods. RLPL achieves consistent improvements over SOTA methods with smaller batch sizes, enhancing efficiency in memory-constrained environments. Our experiments demonstrate substantial performance gains across multiple datasets, particularly with limited labeled data. RLPL also shows exceptional transferability across diverse downstream classification tasks without requiring

pseudo labels for adaptation. These advantages in data efficiency, robustness, and generalization make RLPL particularly valuable for applications demanding memory efficiency and cross-task adaptability.

4.6 Overall Findings

In this chapter, we have explored the challenge of maximizing unlabeled data utility in machine learning through advanced semi-supervised learning techniques. Our investigation has yielded several important findings that contribute to both the theoretical understanding and practical application of SSL methods.

First, we identified fundamental limitations in existing representation learning approaches, particularly their dependence on large batch sizes and inability to effectively leverage unlabeled data during downstream tasks. These limitations create barriers to deployment in resource-constrained environments and prevent full utilization of available data.

Our proposed RLPL framework addresses these limitations through a two-phase approach that combines improved representation learning with meta-pseudo-labeling. The key innovation in the representation learning phase is the incorporation of auxiliary loss functions that extract additional information from each training sample, enabling stable learning even with smaller batch sizes. This modification demonstrates that effective representation learning need not be dependent on massive computational resources, opening possibilities for broader deployment of SSL techniques.

The meta-pseudo-labeling component further enhances model performance by creating a feedback loop between teacher and student networks. This approach significantly improves the quality of pseudo-labels, particularly in low-supervision regimes where traditional pseudo-labeling methods often struggle. By combining strong initialization from

representation learning with refined pseudo-label generation, RLPL creates a synergistic effect that maximizes information extraction from unlabeled data.

Our extensive experimental evaluation confirms that RLPL consistently outperforms state-of-the-art methods across diverse datasets and supervision levels. The performance improvements are most pronounced in extremely label-scarce scenarios (e.g., CIFAR-10 with only 250 labels), where RLPL achieves up to 15.74% accuracy gains over the next best method. Additionally, RLPL demonstrates excellent transferability across heterogeneous downstream tasks without requiring task-specific adaptations.

The parameter sensitivity studies reveal that RLPL's performance is robust across a range of hyperparameter values, with optimal configurations for the auxiliary loss weight ($\lambda = 0.5$) and pseudo-label threshold ($\tau = 0.95$) providing consistent improvements. The ablation studies confirm that both components of our framework contribute meaningfully to the final performance, with their combination yielding the strongest results.

Beyond the specific technical contributions, this work highlights the immense potential of unlabeled data when appropriate methods are employed to extract its latent information. The demonstrated performance gains suggest that SSL approaches like RLPL can significantly reduce annotation requirements while maintaining high model accuracy, addressing a critical bottleneck in many real-world machine learning applications.

In conclusion, our findings demonstrate that the gap between supervised and unsupervised learning can be effectively bridged through carefully designed SSL frameworks that maximize information extraction from limited labeled data and abundant unlabeled examples. The principles and techniques presented in this chapter provide a foundation for developing more data-efficient, accessible machine learning systems capable of operating effectively in diverse real-world settings with varying levels of supervision.

Chapter 5

Conclusions and Future Work

5.1 Conclusions

In this thesis, we have introduced and explored novel representation learning methodologies designed to enhance model robustness and generalization capabilities in data-constrained and noisy environments. The primary goal has been to address critical challenges inherent in traditional machine learning, particularly the issues arising from limited labeled data, noisy inputs, and domain shifts. Our research has produced several key contributions, each demonstrating significant performance gains and practical applicability in the domains of wireless communication, few-shot learning, and semi-supervised learning.

Our first major contribution addresses automatic modulation classification (AMC) in wireless communication through three innovative approaches: NMformer and DenoMAE. NMformer leveraged the power of Vision Transformers (ViTs) to classify modulation schemes directly from constellation diagrams, achieving high accuracy across diverse noise conditions without explicit denoising processes. Building upon this foundation, DenoMAE introduced a multimodal denoising autoencoder framework that incorporates noise

as an explicit modality, significantly enhancing denoising capabilities and classification accuracy. These methodologies collectively advance the state-of-the-art by demonstrating robustness, data efficiency, and computational practicality.

In the realm of few-shot and meta-learning, we have introduced BEpiC, MetaRep, and Meta-Task to substantially improve generalization and regularization capabilities. BEpiC optimized episodic training by strategically selecting training samples to maximize inter-class variance, leading to improved generalization in binary classification scenarios. MetaRep further advanced meta-learning by learning episodic representations through unsupervised methods, significantly improving model performance, particularly in extremely low-data regimes. Additionally, Meta-Task introduced an effective regularization framework leveraging auxiliary reconstruction tasks, reducing overfitting and improving cross-task generalization.

Furthermore, we have explored the utilization of unlabeled data via semi-supervised learning through a novel framework combining representation learning and refined pseudo-labeling techniques. This method demonstrated exceptional performance with minimal labeled data and achieved substantial improvements in accuracy and computational efficiency compared to traditional methods.

Throughout this research, several key insights have emerged. Transformer-based architectures, particularly Vision Transformers, excel at capturing global patterns in noisy signal environments, highlighting their suitability for wireless communications. Our findings emphasize the importance of treating noise not merely as a distortion but as a modality offering valuable structural insights. Additionally, we observed that strategically combining multiple learning objectives, such as reconstruction and local patch classification, significantly enhances the learning process and final model robustness. In meta-learning, our work demonstrated that episodic representations learned from diverse, unsupervised tasks significantly improve generalization and adaptability to new tasks, highlighting the

value of episodic and task-based regularization strategies. For semi-supervised learning, we found that integrating pseudo-label refinement with representation learning substantially improves performance, even with very limited labeled data, reinforcing the potential of semi-supervised techniques in real-world applications.

5.2 Future Work

Building upon the contributions of this thesis, several promising research directions could further advance the fields of representation learning, wireless communication, meta-learning, and semi-supervised learning. The following avenues represent significant opportunities for extending our work:

Signal Representation and Denoising

- **Advanced Signal Representations:** Investigate time-frequency representations beyond constellation diagrams, such as wavelet scalograms, cyclostationary feature maps, and higher-order statistical transforms to capture subtle signal characteristics across varying channel conditions. These alternative representations could reveal discriminative features that remain robust under severe noise and interference scenarios.

- **Extending DenoMAE with Local and Global Objectives:** Future research will explore the further development and evaluation of DenoMAE, which integrates local patch classification with global reconstruction tasks. This approach has the potential to yield richer representations and greater robustness in challenging wireless environments. Future work could focus on systematically benchmarking DenoMAE against state-of-the-art methods, exploring its adaptability to real-world datasets, and investigating its scalability to more complex signal types and multi-antenna systems.

- **Real-World Denoising Validation:** Transition from synthetic to real-world datasets acquired from operational wireless networks, software-defined radios, and multi-antenna systems. This validation would address practical challenges including hardware impairments, non-Gaussian noise distributions, and realistic interference patterns, ultimately improving the operational readiness of our proposed methods.

Meta-Learning and Transfer Capabilities

- **Transformer-Based Meta-Learning:** Integrate our Meta-Task framework with Vision Transformers using specialized masked pretraining objectives tailored for signal processing tasks. This hybrid approach could leverage the global context capabilities of transformers while maintaining the adaptability benefits of meta-learning.

- **Few-Shot Representation Distillation:** Explore techniques to distill knowledge from complex meta-learned representations into more compact models suitable for deployment on resource-constrained devices, maintaining adaptation capabilities while reducing computational requirements.

Semi-Supervised Learning and Pseudo-Labeling

- **Confidence-Calibrated Pseudo-Labeling:** Design dynamic thresholding mechanisms that adapt to specific data characteristics and model confidence distributions, potentially incorporating Bayesian uncertainty estimates to create more reliable pseudo-labels even in highly imbalanced datasets.

- **Multi-Modal Semi-Supervised Learning:** Investigate the integration of multiple modalities, such as text and image data, to enhance representation learning and classification performance. This could involve leveraging cross-modal relationships to improve the robustness of pseudo-labeling techniques.

These research directions not only address current limitations but also position our frameworks to meet emerging challenges in intelligent wireless systems, adaptive learning with minimal supervision, and robust representation learning under real-world constraints.

Bibliography

[1] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton, "Imagenet classification with deep convolutional neural networks," *Advances in neural information processing systems*, vol. 25, 2012.

[2] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin, "Attention is all you need," *Advances in neural information processing systems*, vol. 30, 2017.

[3] Linglong Dai, Ruicheng Jiao, Fumiyuki Adachi, H Vincent Poor, and Lajos Hanzo, "Deep learning for wireless communications: An emerging interdisciplinary paradigm," *IEEE Wireless Communications*, vol. 27, no. 4, pp. 133–139, 2020.

[4] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al., "Gpt-4 technical report," *arXiv preprint arXiv:2303.08774*, 2023.

[5] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al., "An image is worth 16x16 words: Transformers for image recognition at scale," *arXiv preprint arXiv:2010.11929*, 2020.

[6] Timothy O'shea and Jakob Hoydis, "An introduction to deep learning for the physical layer," *IEEE Transactions on Cognitive Communications and Networking*, vol. 3, no. 4, pp. 563–575, 2017.

[7] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton, "A simple framework for contrastive learning of visual representations," in *International conference on machine learning*. PmLR, 2020, pp. 1597–1607.

[8] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick, "Momentum contrast for unsupervised visual representation learning," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2020, pp. 9729–9738.

[9] Kihyuk Sohn, David Berthelot, Nicholas Carlini, Zizhao Zhang, Han Zhang, Colin A Raffel, Ekin Dogus Cubuk, Alexey Kurakin, and Chun-Liang Li, "Fixmatch: Simplifying semi-supervised learning with consistency and confidence," *Advances in neural information processing systems*, vol. 33, pp. 596–608, 2020.

[10] David Berthelot, Nicholas Carlini, Ian Goodfellow, Nicolas Papernot, Avital Oliver, and Colin A Raffel, "Mixmatch: A holistic approach to semi-supervised learning," *Advances in neural information processing systems*, vol. 32, 2019.

[11] Diederik P Kingma, Max Welling, et al., "Auto-encoding variational bayes," 2013.

[12] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova, "Bert: Pre-training of deep bidirectional transformers for language understanding," in *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, 2019, pp. 4171–4186.

[13] Jake Snell, Kevin Swersky, and Richard Zemel, "Prototypical networks for few-shot learning," *Advances in neural information processing systems*, vol. 30, 2017.

[14] Chelsea Finn, Pieter Abbeel, and Sergey Levine, "Model-agnostic meta-learning for fast adaptation of deep networks," in *International conference on machine learning*. PMLR, 2017, pp. 1126–1135.

[15] Shadman Rahman Doha and Ahmed Abdelhadi, "Deep Learning in Wireless Communication Receiver: A Survey," *arXiv preprint arXiv:2501.17184*, 2025.

[16] Fatemeh Lotfi and Fatemeh Afghah, "Meta reinforcement learning approach for adaptive resource optimization in o-ran," *arXiv preprint arXiv:2410.03737*, 2024.

[17] E.E. Azzouz and A.K. Nandi, *Automatic Modulation Recognition of Communication Signals*, Springer, 1996.

[18] Ananthram Swami and Brian M Sadler, "Hierarchical digital modulation classification using cumulants," *IEEE Transactions on communications*, vol. 48, no. 3, pp. 416–429, 2000.

[19] Tevfik Yucek and Huseyin Arslan, "A survey of spectrum sensing algorithms for cognitive radio applications," *IEEE Communications Surveys & Tutorials*, vol. 11, no. 1, pp. 116–130, 2009.

[20] William A Gardner, *Cyclostationarity in Communications and Signal Processing*, IEEE Press, 1994.

[21] Sreeraj Rajendran, Wannes Meert, Domenico Giustiniano, Vincent Lenders, and Sofie Pollin, "Deep learning models for wireless signal classification with distributed low-cost spectrum sensors," *IEEE Transactions on Cognitive Communications and Networking*, vol. 4, no. 3, pp. 433–445, 2018.

[22] Timothy J O'Shea, Johnathan Corgan, and T Charles Clancy, "Convolutional radio modulation recognition networks," in *International Conference on Engineering Applications of Neural Networks*. Springer, 2016, pp. 213–226.

[23] Wei Wei and Jerry M. Mendel, "Maximum-Likelihood Classification for Digital Amplitude-Phase Modulations," *IEEE Transactions on Communications*, vol. 48, no. 2, pp. 189–193, 2000.

[24] Octavia A. Dobre, Ali Abdi, Yeheskel Bar-Ness, and Wei Su, "Survey of automatic modulation classification techniques: classical approaches and new trends," *IET Communications*, vol. 1, no. 2, pp. 137–156, 2007.

[25] W. A. Gardner, *Cyclostationarity in Communications and Signal Processing*, IEEE Press, 1994.

[26] Alharbi Hazza, Mobien Shoaib, Saleh A. Alshebeili, and Alturki Fahad, "An overview of feature-based methods for digital modulation classification," in *2013 1st International Conference on Communications, Signal Processing, and their Applications (ICCSPA)*, 2013, pp. 1–6.

[27] Dhamyaa H Al-Nuaimi, Ivan A Hashim, Intan S Zainal Abidin, Laith B Salman, and Nor Ashidi Mat Isa, "Performance of feature-based techniques for automatic digital modulation recognition and classification—A review," *Electronics*, vol. 8, no. 12, pp. 1407, 2019.

[28] Timothy J O'Shea, Johnathan Corgan, and T Charles Clancy, "Convolutional radio modulation recognition networks," in *Engineering Applications of Neural Networks: 17th International Conference, EANN 2016, Aberdeen, UK, September 2-5, 2016, Proceedings 17*. Springer, 2016, pp. 213–226.

[29] Thien Huynh-The, Cam-Hao Hua, Quoc-Viet Pham, and Dong-Seong Kim, "MC-Net: An Efficient CNN Architecture for Robust Automatic Modulation Classification," *IEEE Communications Letters*, vol. 24, no. 4, pp. 811–815, 2020.

[30] Nitin Priyadarshini Shankar, Deepsayan Sadhukhan, Nancy Nayak, Thulasi Tholeti, and Sheetal Kalyani, "Binarized ResNet: Enabling Robust Automatic Modulation Classification at the Resource-Constrained Edge," *IEEE Transactions on Cognitive Communications and Networking*, vol. 10, no. 5, pp. 1913–1927, 2024.

[31] Kaisheng Liao, Yaodong Zhao, Jie Gu, Yaping Zhang, and Yi Zhong, "Sequential convolutional recurrent neural networks for fast automatic modulation classification," *IEEE Access*, vol. 9, pp. 27182–27188, 2021.

[32] Ke Bu, Yuan He, Xiaojun Jing, and Jindong Han, "Adversarial transfer learning for deep learning based automatic modulation classification," *IEEE Signal Processing Letters*, vol. 27, pp. 880–884, 2020.

[33] Qinghe Zheng, Penghui Zhao, Yang Li, Hongjun Wang, and Yang Yang, "Spectrum interference-based two-level data augmentation method in deep learning for automatic modulation classification," *Neural Computing and Applications*, vol. 33, no. 13, pp. 7723–7745, 2021.

[34] Dong Wang, Meiyan Lin, Xiaoxu Zhang, Yonghui Huang, and Yan Zhu, "Automatic modulation classification based on CNN-transformer graph neural network," *Sensors*, vol. 23, no. 16, pp. 7281, 2023.

[35] Robertas Damaševičius, Darius Plonis, and Rytis Maskeliunas, "TFI–AMR: A Transformer-Based Forest-Inspired Approach for Automatic Modulation Recognition in Wireless Communication," in *Proc. IEEE 11th Workshop on Advances in Information, Electronic and Electrical Engineering (AIEEE)*, 2024.

[36] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby, "An Image is Worth 16×16 Words: Transformers for Image Recognition at Scale," in *International Conference on Learning Representations (ICLR)*, 2021.

[37] Mingyuan Shao, Dingzhao Li, Shaohua Hong, Jie Qi, and Haixin Sun, "IQFormer: A Novel Transformer-Based Model with Multi-Modality Fusion for Automatic Modulation Recognition," *IEEE Transactions on Cognitive Communications and Networking*, 2024.

[38] Yabo Liu, Yi Liu, and Cheng Yang, "Modulation Recognition with Graph Convolutional Network," *IEEE Wireless Communications Letters*, vol. 9, no. 5, pp. 624–627, 2020.

[39] Maher Marwani and Georges Kaddoum, "Graph neural networks approach for joint wireless power control and spectrum allocation," *IEEE Transactions on Machine Learning in Communications and Networking*, 2024.

[40] Chaoqi Chen, Yushuang Wu, Qiyuan Dai, Hong-Yu Zhou, Mutian Xu, Sibei Yang, Xiaoguang Han, and Yizhou Yu, "A survey on graph neural networks and graph transformers in computer vision: A task-oriented perspective," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.

[41] Qi Xuan, Jinchao Zhou, Kunfeng Qiu, Zhuangzhi Chen, Dongwei Xu, Shilian Zheng, and Xiaoniu Yang, "AvgNet: Adaptive visibility graph neural network and its application in modulation classification," *IEEE Transactions on Network Science and Engineering*, vol. 9, no. 3, pp. 1516–1526, 2022.

[42] Qinghe Zheng, Xinyu Tian, Zhiguo Yu, Yao Ding, Abdussalam Elhanashi, Sergio Saponara, and Kidiyo Kpalma, "MobileRaT: a lightweight radio transformer method for automatic modulation classification in drone communication systems," *Drones*, vol. 7, no. 10, pp. 596, 2023.

[43] Hongyun Fei, Baiyang Wang, Hongjun Wang, Ming Fang, Na Wang, Xingping Ran, Yunxia Liu, and Min Qi, "MobileAmcT: A Lightweight Mobile Automatic Modulation Classification Transformer in Drone Communication Systems," *Drones*, vol. 8, no. 8, pp. 357, 2024.

[44] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton, "A Simple Framework for Contrastive Learning of Visual Representations," in *International Conference on Machine Learning (ICML)*, 2020, pp. 1597–1607.

[45] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick, "Momentum Contrast for Unsupervised Visual Representation Learning," in *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 9729–9738.

[46] Diederik P. Kingma and Max Welling, "Auto-Encoding Variational Bayes," *International Conference on Learning Representations (ICLR)*, 2014.

[47] Jinwon An and Sungzoon Cho, "Variational Autoencoder Based Anomaly Detection Using Reconstruction Probability," in *Special Lecture on IE*, 2015, vol. 2, pp. 1–18.

[48] Zhiyuan Jiang, Yanqing Li, Zhenhua Yu, and Zhiyong Peng, "Semi-Supervised Learning Based Modulation Recognition with Variational Autoencoder," in *IEEE Global Communications Conference (GLOBECOM)*, 2019, pp. 1–6.

[49] Yanghong Chen, Xiaodong Xu, and Xiaowei Qin, "An Open-Set Modulation Recognition Scheme With Deep Representation Learning," *IEEE Communications Letters*, vol. 27, no. 3, pp. 851–855, 2023.

[50] Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al., "Bootstrap your own latent-a new approach to self-supervised learning," *Advances in neural information processing systems*, vol. 33, pp. 21271–21284, 2020.

[51] Xinlei Chen and Kaiming He, "Exploring simple siamese representation learning. In 2021 IEEE," in *CVF conference on computer vision and pattern recognition (CVPR)*, 2020, pp. 15745–15753.

[52] Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny, "Barlow twins: Self-supervised learning via redundancy reduction," in *International conference on machine learning*. PMLR, 2021, pp. 12310–12320.

[53] Hanlin Wang, Shuyuan Yang, Zhixi Feng, and Bincheng Huang, "Semi-Supervised Modulation Classification via An Ensemble SigMatch Method," *IEEE Internet of Things Journal*, 2024.

[54] Tauhidul Islam, Md Sadman Hafiz, Jamin Rahman Jim, Md Mohsin Kabir, and MF Mridha, "A systematic review of deep learning data augmentation in medical imaging: Recent advances and future research directions," *Healthcare Analytics*, p. 100340, 2024.

[55] Xiaowei Wu, Shengyun Wei, and Yan Zhou, "Deep multi-scale representation learning with attention for automatic modulation classification," in *2022 International Joint Conference on Neural Networks (IJCNN)*. IEEE, 2022, pp. 1–8.

[56] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick, "Masked Autoencoders Are Scalable Vision Learners," in *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 16000–16009.

[57] Daisuke Niizumi, Daiki Takeuchi, Yasunori Ohishi, Noboru Harada, and Kunio Kashino, "Masked spectrogram modeling using masked autoencoders for learning general-purpose audio representation," in *HEAR: Holistic Evaluation of Audio Representations*. PMLR, 2022, pp. 1–24.

[58] Fady Medhat, David Chesmore, and John Robinson, "Masked conditional neural networks for sound classification," *Applied Soft Computing*, vol. 90, pp. 106073, 2020.

[59] Yuan Yuan, Zhaojian Li, and Bin Zhao, "A Survey of Multimodal Learning: Methods, Applications, and Future," *ACM Computing Surveys*, 2025.

[60] Cem Akkus, Alara Kusetogullari, Burak Ercan, Ege Ozan Özyedek, Elif Ak, Enes Sadi Uysal, Furkan Kınlı, Hasan Alp Boz, İrem Sıla Kadıoğlu, Mehmet Arif Demirtas, Mehmet Fatih Akca, Mehmet Kerem Erol, Muhammed Yusuf Özkaya, Mustafa Mert Tunalı, Nadin Kokciyan, Özge Mercanoglu Sincan, and Refik Can Mallı, "Multimodal Deep Learning," 2023.

[61] Songtao Li and Hao Tang, "Multimodal Alignment and Fusion: A Survey," *arXiv preprint arXiv:2411.17040*, 2024.

[62] Xiao Liang, Erkun Yang, Cheng Deng, and Yanhua Yang, "CrossFormer: Cross-modal Representation Learning via Heterogeneous Graph Transformer," *ACM Transactions on Multimedia Computing, Communications and Applications*, vol. 20, no. 12, pp. 1–21, 2024.

[63] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever, "Learning Transferable Visual Models From Natural Language Supervision," in *Proceedings of the 38th International Conference on Machine Learning*. 18–24 Jul 2021, vol. 139 of *Proceedings of Machine Learning Research*, pp. 8748–8763, PMLR.

[64] Chao Jia, Yinfei Yang, Ye Xia, Yi-Ting Chen, Zarana Parekh, Hieu Pham, Quoc Le, Yun-Hsuan Sung, Zhen Li, and Tom Duerig, "Scaling up visual and vision-language representation learning with noisy text supervision," in *International conference on machine learning*. PMLR, 2021, pp. 4904–4916.

[65] Kunfeng Qiu, Shilian Zheng, Luxin Zhang, Caiyi Lou, and Xiaoniu Yang, "DeepSIG: A hybrid heterogeneous deep learning framework for radio signal classification," *IEEE Transactions on Wireless Communications*, vol. 23, no. 1, pp. 775–788, 2023.

[66] Dongwei Xu, Yutao Zhu, Yao Lu, Youpeng Feng, Yun Lin, and Qi Xuan, "MCLRL: A Multi-Domain Contrastive Learning with Reinforcement Learning Framework for Few-Shot Modulation Recognition," 2025.

[67] Xiang Li, He Huang, Cheng Yan, Yang Liu, and Fang Yang, "AMC-MLP: A Multimodal Attention-Based Deep Learning Method for Automatic Modulation Classification," *Frontiers in Energy Research*, vol. 10, 2022.

[68] Renjie Wu, Hu Wang, Hsiang-Ting Chen, and Gustavo Carneiro, "Deep Multimodal Learning with Missing Modality: A Survey," 2024.

[69] Abdelhamid Haouhat, Slimane Bellaouar, Attia Nehar, and Hadda Cherroun, "Modality Influence in Multimodal Machine Learning," 2023.

[70] Zejia Wang, Jiaqi Tang, Zhipeng Hu, Wenbin Wang, Zeren Sun, Qingli Li, and Zheng Wang, "Improving Discriminative Multi-Modal Learning with Large-Scale Pre-Trained Models," 2023.

[71] Yanpeng Sun, Qiang Chen, Shu Wu, Liang Wang, Yan Zhang, Jingjing Lv, Fan Zhang, and Jian Yang, "Improving Multi-modal Large Language Model through Boosting Vision Capabilities," 2024.

[72] Mike Wu and Noah Goodman, "Multimodal Generative Models for Scalable Weakly-Supervised Learning," 2018.

[73] Jinzhao Zhou, Yiqun Duan, Zhihong Chen, Yu-Cheng Chang, and Chin-Teng Lin, "Generalizing Multimodal Variational Methods to Sets," 2022.

[74] Baohang Zhou, Ying Zhang, Kehui Song, Wenya Guo, Guoqing Zhao, Hongbin Wang, and Xiaojie Yuan, "A span-based multimodal variational autoencoder for semi-supervised multimodal named entity recognition," in *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, 2022, pp. 6293–6302.

[75] Yilin Sun and Edward A Ball, "Automatic modulation classification using techniques from image classification," *IET Communications*, vol. 16, no. 11, pp. 1303–1314, 2022.

[76] Bijan G Mobasseri, "Digital modulation classification using constellation shape," *Signal processing*, vol. 80, no. 2, pp. 251–277, 2000.

[77] Ade Pitra Hermawan, Rizki Rivai Ginanjar, Dong-Seong Kim, and Jae-Min Lee, "CNN-based automatic modulation classification for beyond 5G communications," *IEEE Communications Letters*, vol. 24, no. 5, pp. 1038–1041, 2020.

[78] Fanfan Meng, Peng Chen, Linxiao Wu, and Xiaoyu Wang, "Automatic modulation classification: A deep learning enabled approach," *IEEE Transactions on Vehicular Technology*, vol. 67, no. 11, pp. 10760–10772, 2018.

[79] Yingkai Li, Shufei Wang, Yibin Zhang, Hao Huang, Yu Wang, Qianyun Zhang, Yun Lin, and Guan Gui, "Multi-Modal Fusion for Enhanced Automatic Modulation Classification," in *2024 IEEE 99th Vehicular Technology Conference (VTC2024-Spring)*. IEEE, 2024, pp. 1–5.

[80] Konstantinos Triaridis, Constantine Doumanidis, Nestor D. Chatzidiamantis, and George K. Karagiannidis, "MM-Net: A Multi-Modal Approach Toward Automatic Modulation Classification," *IEEE Communications Letters*, vol. 28, no. 2, pp. 328–331, 2024.

[81] Shengliang Peng, Hanyu Jiang, Huaxia Wang, Hathal Alwageed, and Yu-Dong Yao, "Modulation classification using convolutional neural network based deep learning model," in *2017 26th Wireless and Optical Communication Conference (WOCC)*. IEEE, 2017, pp. 1–5.

[82] Abdullah Samarkandi, Alhussain Almarhabi, Hatim Alhazmi, and Yu-Dong Yao, "Combined Signal Representations for Modulation Classification Using Deep Learning: Ambiguity Function, Constellation Diagram, and Eye Diagram," in *2023 32nd Wireless and Optical Communications Conference (WOCC)*, 2023, pp. 1–4.

[83] Thien-Thanh Dao, Dae-Il Noh, Mikio Hasegawa, Hiroo Sekiya, Quoc-Viet Pham, and Won-Joo Hwang, "VT-MCNet: High-Accuracy Automatic Modulation Classification Model based on Vision Transformer," *IEEE Communications Letters*, 2023.

[84] Shahab Hamidi-Rad and Swayambhoo Jain, "Mcformer: A transformer based deep neural network for automatic modulation classification," in *2021 IEEE Global Communications Conference (GLOBECOM)*. IEEE, 2021, pp. 1–6.

[85] Jingjing Cai, Fengming Gan, Xianghai Cao, and Wei Liu, "Signal modulation classification based on the transformer network," *IEEE Transactions on Cognitive Communications and Networking*, vol. 8, no. 3, pp. 1348–1357, 2022.

[86] Weisi Kong, Xun Jiao, Yuhua Xu, Bolin Zhang, and Qinghai Yang, "A transformer-based contrastive semi-supervised learning framework for automatic modulation recognition," *IEEE Transactions on Cognitive Communications and Networking*, 2023.

[87] Yunpeng Qu, Zhilin Lu, Rui Zeng, Jintao Wang, and Jian Wang, "Enhancing automatic modulation recognition through robust global feature extraction," *IEEE Transactions on Vehicular Technology*, 2024.

[88] Shengliang Peng, Hanyu Jiang, Huaxia Wang, Hathal Alwageed, Yu Zhou, Marjan Mazrouei Sebdani, and Yu-Dong Yao, "Modulation classification based on signal constellation diagrams and deep learning," *IEEE transactions on neural networks and learning systems*, vol. 30, no. 3, pp. 718–727, 2018.

[89] Fan Meng, Peng Chen, Lenan Wu, and Xianbin Wang, "Automatic Modulation Classification: A Deep Learning Enabled Approach," *IEEE Transactions on Vehicular Technology*, vol. 67, no. 11, pp. 10760–10772, 2018.

[90] Dehua Hong, Zilong Zhang, and Xiaodong Xu, "Automatic modulation classification using recurrent neural networks," in *2017 3rd IEEE International Conference on Computer and Communications (ICCC)*. IEEE, 2017, pp. 695–700.

[91] Sharan Ramjee, Shengtai Ju, Diyu Yang, Xiaoyu Liu, Aly El Gamal, and Yonina C Eldar, "Fast deep learning for automatic modulation classification," *arXiv preprint arXiv:1901.05850*, 2019.

[92] Randall Balestriero, Mark Ibrahim, Vlad Sobal, Ari Morcos, Shashank Shekhar, Tom Goldstein, Florian Bordes, Adrien Bardes, Gregoire Mialon, Yuandong Tian, Avi Schwarzschild, Andrew Gordon Wilson, Jonas Geiping, Quentin Garrido, Pierre Fernandez, Amir Bar, Hamed Pirsiavash, Yann LeCun, and Micah Goldblum, "A Cookbook of Self-Supervised Learning," 2023.

[93] Adam Roberts, Colin Raffel, Katherine Lee, Michael Matena, Noam Shazeer, Peter J Liu, Sharan Narang, Wei Li, and Yanqi Zhou, "Exploring the limits of transfer learning with a unified text-to-text transformer," *Google, Tech. Rep.*, 2019.

[94] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin, "Emerging properties in self-supervised vision transformers," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2021, pp. 9650–9660.

[95] Shilian Zheng, Shurun Chen, Tao Chen, Zhuang Yang, Zhijin Zhao, and Xiaoniu Yang, "Deep Learning-Based SNR Estimation," *IEEE Open Journal of the Communications Society*, 2024.

[96] Shahid Manzoor and Noor Shamsiah Othman, "Adaptive Modulation With CAZAC Preamble-Based Signal-to-Noise-Ratio Estimator in OFDM Cooperative Communication System," *IEEE Access*, vol. 10, pp. 126550–126560, 2022.

[97] Erma Perenda, Sreeraj Rajendran, Gerome Bovet, Sofie Pollin, and Mariya Zheleva, "Learning the unknown: Improving modulation classification performance in

unseen scenarios," in *IEEE INFOCOM 2021-IEEE Conference on Computer Communications*. IEEE, 2021, pp. 1–10.

[98] Yunhao Shi, Hua Xu, Yue Zhang, Zisen Qi, and Dan Wang, "GAF-MAE: A Self-supervised Automatic Modulation Classification Method Based on Gramian Angular Field and Masked Autoencoder," *IEEE Transactions on Cognitive Communications and Networking*, 2023.

[99] Roman Bachmann, David Mizrahi, Andrei Atanov, and Amir Zamir, "Multimae: Multi-modal multi-task masked autoencoders," in *European Conference on Computer Vision*. Springer, 2022, pp. 348–367.

[100] Roman Bachmann, Oğuzhan Fatih Kar, David Mizrahi, Ali Garjani, Mingfei Gao, David Griffiths, Jiaming Hu, Afshin Dehghan, and Amir Zamir, "4M-21: An Any-to-Any Vision Model for Tens of Tasks and Modalities," *arXiv preprint arXiv:2406.09406*, 2024.

[101] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick, "Masked autoencoders are scalable vision learners," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2022, pp. 16000–16009.

[102] Thien Huynh-The, Cam-Hao Hua, Quoc-Viet Pham, and Dong-Seong Kim, "MCNet: An efficient CNN architecture for robust automatic modulation classification," *IEEE Communications Letters*, vol. 24, no. 4, pp. 811–815, 2020.

[103] Shaogang Dai, Jianwei Xu, and Huaji Zhou, "Radio Signal Modulation Pattern Recognition Based on Time-Frequency Adaptive Decomposition and Hybrid Neural Network," *IEEE Internet of Things Journal*, pp. 1–1, 2025.

[104] Meng Zhang, Yuan Zeng, Zidong Han, and Yi Gong, "Automatic Modulation Recognition Using Deep Learning Architectures," in *2018 IEEE 19th International Workshop on Signal Processing Advances in Wireless Communications (SPAWC)*, 2018, pp. 1–5.

[105] Fugang Liu, Ziwei Zhang, and Ruolin Zhou, "Automatic modulation recognition based on CNN and GRU," *Tsinghua Science and Technology*, vol. 27, no. 2, pp. 422–431, 2021.

[106] Debbarni Sarkar, Yogita, Satyendra Singh Yadav, Linga Reddy Cenkeramaddi, and Om Jee Pandey, "TDRA: Transformer-Based Deep Recurrent Architecture for Automatic Modulation Classification Pertinent to Intelligent-Reflecting-Surface-Assisted Internet of Things Networks," *IEEE Internet of Things Journal*, vol. 11, no. 23, pp. 38907–38924, 2024.

[107] Mingyang Du, Jifei Pan, and Daping Bi, "A Contrastive Learner for Automatic Modulation Classification," *IEEE Transactions on Wireless Communications*, pp. 1–1, 2025.

[108] Weisi Kong, Xun Jiao, Yuhua Xu, Bolin Zhang, and Qinghai Yang, "A Transformer-Based Contrastive Semi-Supervised Learning Framework for Automatic Modulation Recognition," *IEEE Transactions on Cognitive Communications and Networking*, vol. 9, no. 4, pp. 950–962, 2023.

[109] Jacob Devlin, "Bert: Pre-training of deep bidirectional transformers for language understanding," *arXiv preprint arXiv:1810.04805*, 2018.

[110] Wenhui Wang, Hangbo Bao, Li Dong, Johan Bjorck, Zhiliang Peng, Qiang Liu, Kriti Aggarwal, Owais Khan Mohammed, Saksham Singhal, Subhojit Som, et al.,

"Image as a foreign language: Beit pretraining for all vision and vision-language tasks," *arXiv preprint arXiv:2208.10442*, 2022.

[111] David Mizrahi, Roman Bachmann, Oguzhan Kar, Teresa Yeo, Mingfei Gao, Afshin Dehghan, and Amir Zamir, "4m: Massively multimodal masked modeling," *Advances in Neural Information Processing Systems*, vol. 36, 2024.

[112] Van-Sang Doan, Thien Huynh-The, Cam-Hao Hua, Quoc-Viet Pham, and Dong-Seong Kim, "Learning constellation map with deep CNN for accurate modulation recognition," in *GLOBECOM 2020-2020 IEEE Global Communications Conference*. IEEE, 2020, pp. 1–6.

[113] Atik Faysal, Mohammad Rostami, Reihaneh Gh Roshan, Huaxia Wang, and Nikhil Muralidhar, "NMformer: A Transformer for Noisy Modulation Classification in Wireless Communication," in *2024 33rd Wireless and Optical Communications Conference (WOCC)*. IEEE, 2024, pp. 103–108.

[114] Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum, "Human-level concept learning through probabilistic program induction," *Science*, vol. 350, no. 6266, pp. 1332–1338, 2015.

[115] Yaqing Wang, Quanming Yao, James T Kwok, and Lionel M Ni, "Generalizing from a few examples: A survey on few-shot learning," *ACM Computing Surveys (CSUR)*, vol. 53, no. 3, pp. 1–34, 2020.

[116] Chelsea Finn, Pieter Abbeel, and Sergey Levine, "Model-Agnostic Meta-Learning for Fast Adaptation of Deep Networks," in *International Conference on Machine Learning (ICML)*, 2017.

[117] Hongyi Zhang and Michael Sabuncu, "MixUp: Beyond Empirical Risk Minimization," in *International Conference on Learning Representations (ICLR)*, 2017.

[118] Momin Abbas, Quan Xiao, Lisha Chen, Pin-Yu Chen, and Tianyi Chen, "Sharp-MAML: Sharpness-Aware Model-Agnostic Meta Learning," *arXiv preprint arXiv:2206.03996*, 2022.

[119] Manas Gogoi, Sambhavi Tiwari, and Shekhar Verma, "Perturbing the gradient for alleviating meta overfitting," *arXiv preprint arXiv:2405.12299*, 2024.

[120] Eren Ermis and Others, "Towards Robust Episodic Meta-Learning," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[121] Dong Bok Lee, Seanie Lee, Kenji Kawaguchi, Yunji Kim, Jihwan Bang, Jung-Woo Ha, and Sung Ju Hwang, "Self-supervised set representation learning for unsupervised meta-learning," in *The Eleventh International Conference on Learning Representations*, 2023.

[122] Kyle Hsu, Sergey Levine, and Chelsea Finn, "Unsupervised learning via meta-learning," *arXiv preprint arXiv:1810.02334*, 2018.

[123] Luke Metz, Nikhil Fu, and Chelsea Finn, "Meta-Learning Update Rules for Unsupervised Representation Learning," *arXiv preprint arXiv:1804.00222*, 2018.

[124] Eleni Triantafillou, Tyler Zhu, Vincent Dumoulin, Pascal Lamblin, Utku Evci, Kelvin Xu, Ross Goroshin, Carles Gelada, Kevin Swersky, Pierre-Antoine Manzagol, et al., "Meta-dataset: A dataset of datasets for learning to learn from few examples," *arXiv preprint arXiv:1903.03096*, 2019.

[125] Abhishek Gupta, Benjamin Eysenbach, Chelsea Finn, and Sergey Levine, "Unsupervised meta-learning for reinforcement learning," *arXiv preprint arXiv:1806.04640*, 2018.

[126] Junhoo Lee, Yearim Kim, Hyunho Lee, and Nojun Kwak, "Any-way meta learning," in *Proceedings of the AAAI Conference on Artificial Intelligence*, 2024, vol. 38, pp. 13400–13408.

[127] Burr Settles, "From theories to queries: Active learning in practice," in *Active learning and experimental design workshop in conjunction with AISTATS 2010*. JMLR Workshop and Conference Proceedings, 2011, pp. 1–18.

[128] Jihyeong Jung, Sangwoo Seo, Sungwon Kim, and Chanyoung Park, "Unsupervised episode generation for graph meta-learning," *arXiv preprint arXiv:2306.15217*, 2023.

[129] Dan Hendrycks, Norman Mu, Ekin D. Cubuk, Justin Gilmer, and Balaji Lakshminarayanan, "AugMix: A Simple Data Processing Method to Improve Robustness and Uncertainty," in *International Conference on Learning Representations (ICLR)*, 2020.

[130] Renkun Ni, Micah Goldblum, Amr Sharaf, Kezhi Kong, and Tom Goldstein, "Data augmentation for meta-learning," in *International Conference on Machine Learning*. PMLR, 2021, pp. 8152–8161.

[131] Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le, "Autoaugment: Learning augmentation policies from data," *arXiv preprint arXiv:1805.09501*, 2018.

[132] Huaxiu Yao, Long-Kai Huang, Linjun Zhang, Ying Wei, Li Tian, James Zou, Junzhou Huang, et al., "Improving generalization in meta-learning via task augmentation," in *International conference on machine learning*. PMLR, 2021, pp. 11887–11897.

[133] Antreas Antoniou, Harrison L. Edwards, and Amos J. Storkey, "How to train your MAML," in *Proceedings of the International Conference on Learning Representations (Workshop)*, 2019.

[134] Imtiaz Ziko, Jose Dolz, Eric Granger, and Ismail Ben Ayed, "Laplacian regularized few-shot learning," in *International conference on machine learning*. PMLR, 2020, pp. 11660–11670.

[135] Xingyu Zhu, Shuo Wang, Jinda Lu, Yanbin Hao, Haifeng Liu, and Xiangnan He, "Boosting Few-Shot Learning via Attentive Feature Regularization," in *Proceedings of the AAAI Conference on Artificial Intelligence*, 2024, vol. 38, pp. 1740–1747.

[136] Niels van der Heijden, Ekaterina Shutova, and Helen Yannakoudakis, "FewShotTextGCN: K-hop neighborhood regularization for few-shot learning on graphs," *arXiv preprint arXiv:2301.10481*, 2023.

[137] Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip HS Torr, and Timothy M Hospedales, "Learning to compare: relation network for few-shot learning. CoRR abs/1711.06025 (2017)," *arXiv preprint arXiv:1711.06025*, 2017.

[138] Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel, "A simple neural attentive meta-learner," *arXiv preprint arXiv:1707.03141*, 2017.

[139] Alex Nichol, Joshua Achiam, and John Schulman, "On first-order meta-learning algorithms," *arXiv preprint arXiv:1803.02999*, 2018.

[140] Aravind Rajeswaran, Chelsea Finn, Sham Kakade, and Sergey Levine, "Meta-Learning with Implicit Gradients," in *Advances in Neural Information Processing Systems*, 2019.

[141] Kwonjoon Lee, Subhransu Maji, Anirudh Ravichandran, Stefano Soatto, and Joshua Tenenbaum, "MetaOptNet: Meta-Learning with Differentiable Convex Optimization," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[142] Andrei A Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell, "Meta-learning with latent embedding optimization," *arXiv preprint arXiv:1807.05960*, 2018.

[143] Aniruddh Raghu, Maithra Raghu, Samy Bengio, and Oriol Vinyals, "Rapid learning or feature reuse? towards understanding the effectiveness of maml," *arXiv preprint arXiv:1909.09157*, 2019.

[144] Eunbyung Park and Junier B Oliva, "Meta-curvature," *Advances in neural information processing systems*, vol. 32, 2019.

[145] Fei Ye, Pin Wang, Ching-Yao Chan, and Jiucai Zhang, "Meta reinforcement learning-based lane change strategy for autonomous vehicles," in *2021 IEEE Intelligent Vehicles Symposium (IV)*. IEEE, 2021, pp. 223–230.

[146] Yinbo Chen, Zhuang Liu, Huijuan Xu, Trevor Darrell, and Xiaolong Wang, "Meta-Baseline: Exploring Simple Meta-Learning for Few-Shot Learning," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2021, pp. 9062–9071.

[147] Mark Sandler, Max Vladymyrov, Andrey Zhmoginov, Nolan Miller, Tom Madams, Andrew Jackson, and Blaise Agüera Y Arcas, "Meta-learning bidirectional update rules," in *International Conference on Machine Learning*. PMLR, 2021, pp. 9288–9300.

[148] Alex Nichol and John Schulman, "Reptile: a scalable metalearning algorithm," *arXiv preprint arXiv:1803.02999*, vol. 2, no. 3, pp. 4, 2018.

[149] Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li, "Meta-sgd: Learning to learn quickly for few-shot learning," *arXiv preprint arXiv:1707.09835*, 2017.

[150] Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip HS Torr, and Timothy M Hospedales, "Learning to compare: Relation network for few-shot learning," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018, pp. 1199–1208.

[151] Songcan Chen and Yulian Zhu, "Subpattern-based principle component analysis," *Pattern Recognition*, vol. 37, no. 5, pp. 1081–1083, 2004.

[152] Ethan Rublee, Vincent Rabaud, Kurt Konolige, and Gary Bradski, "ORB: An efficient alternative to SIFT or SURF," in *2011 International Conference on Computer Vision*, 2011, pp. 2564–2571.

[153] Amrith Setlur, Oscar Li, and Virginia Smith, "Is Support Set Diversity Necessary for Meta-Learning?," *CoRR*, vol. abs/2011.14048, 2020.

[154] Griffin, Holub, and Perona, "Caltech 256," Apr 2022.

[155] Chen Liu, Chengming Xu, Yikai Wang, Li Zhang, and Yanwei Fu, "An embarrassingly simple baseline to one-shot learning," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, 2020, pp. 922–923.

[156] Li, Andreeto, Ranzato, and Perona, "Caltech 101," Apr 2022.

[157] Felipe Petroski Such, Vashisht Madhavan, Edoardo Conti, Joel Lehman, Kenneth O Stanley, and Jeff Clune, "Deep neuroevolution: Genetic algorithms are a competitive alternative for training deep neural networks for reinforcement learning," *arXiv preprint arXiv:1712.06567*, 2017.

[158] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al., "Matching networks for one shot learning," *Advances in neural information processing systems*, vol. 29, 2016.

[159] Amrith Setlur, Oscar Li, and Virginia Smith, "Is support set diversity necessary for meta-learning?," *arXiv preprint arXiv:2011.14048*, 2020.

[160] Etienne Bennequin, Victor Bouvier, Myriam Tami, Antoine Toubhans, and Céline Hudelot, "Bridging few-shot learning and adaptation: new challenges of support-query shift," in *Machine Learning and Knowledge Discovery in Databases. Research Track: European Conference, ECML PKDD 2021, Bilbao, Spain, September 13–17, 2021, Proceedings, Part I 21*. Springer, 2021, pp. 554–569.

[161] Timothy Hospedales, Antreas Antoniou, Paul Micaelli, and Amos Storkey, "Meta-learning in neural networks: A survey," *IEEE transactions on pattern analysis and machine intelligence*, vol. 44, no. 9, pp. 5149–5169, 2021.

[162] Rujun Zhang and Qifan Liu, "Learning with few samples in deep learning for image classification, a mini-review," *Frontiers in Computational Neuroscience*, vol. 16, pp. 1075294, 2023.

[163] Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B Tenenbaum, and Phillip Isola, "Rethinking few-shot image classification: a good embedding is all you need?," in

Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XIV 16. Springer, 2020, pp. 266–282.

[164] Linus Ericsson, Henry Gouk, Chen Change Loy, and Timothy M. Hospedales, "Self-Supervised Representation Learning: Introduction, advances, and challenges," *IEEE Signal Processing Magazine*, vol. 39, no. 3, pp. 42–62, 2022.

[165] Bernhard Schölkopf, Francesco Locatello, Stefan Bauer, Nan Rosemary Ke, Nal Kalchbrenner, Anirudh Goyal, and Yoshua Bengio, "Toward Causal Representation Learning," *Proceedings of the IEEE*, vol. 109, no. 5, pp. 612–634, 2021.

[166] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei, "ImageNet Large Scale Visual Recognition Challenge," *International Journal of Computer Vision (IJCV)*, vol. 115, no. 3, pp. 211–252, 2015.

[167] Qianru Sun, Yaoyao Liu, Tat-Seng Chua, and Bernt Schiele, "Meta-transfer learning for few-shot learning," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019, pp. 403–412.

[168] Kihyuk Sohn, "Improved deep metric learning with multi-class n-pair loss objective," *Advances in neural information processing systems*, vol. 29, 2016.

[169] Janarthanan Rajendran, Alexander Irpan, and Eric Jang, "Meta-learning requires meta-augmentation," *Advances in Neural Information Processing Systems*, vol. 33, pp. 5705–5715, 2020.

[170] Yulin Wang, Xuran Pan, Shiji Song, Hong Zhang, Gao Huang, and Cheng Wu, "Implicit semantic data augmentation for deep networks," *Advances in Neural Information Processing Systems*, vol. 32, 2019.

[171] Yulin Wang, Gao Huang, Shiji Song, Xuran Pan, Yitong Xia, and Cheng Wu, "Regularizing deep networks with semantic data augmentation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 44, no. 7, pp. 3733–3748, 2021.

[172] John A Hartigan and Manchek A Wong, "Algorithm AS 136: A k-means clustering algorithm," *Journal of the royal statistical society. series c (applied statistics)*, vol. 28, no. 1, pp. 100–108, 1979.

[173] Qian Zhang, Yi Zhu, Ming Yang, Ge Jin, YingWen Zhu, and Qiu Chen, "Cross-to-merge training with class balance strategy for learning with noisy labels," *Expert Systems with Applications*, vol. 249, pp. 123846, 2024.

[174] Qian Zhang, Yi Zhu, Filipe R Cordeiro, and Qiu Chen, "PSSCL: A progressive sample selection framework with contrastive loss designed for noisy labels," *Pattern Recognition*, vol. 161, pp. 111284, 2025.

[175] Mixue Xie, Shuang Li, Kaixiong Gong, Yulin Wang, and Gao Huang, "Adapting across domains via target-oriented transferable semantic augmentation under prototype constraint," *International Journal of Computer Vision*, vol. 132, no. 4, pp. 1417–1441, 2024.

[176] Chaoqun Du, Yulin Wang, Shiji Song, and Gao Huang, "Probabilistic contrastive learning for long-tailed visual recognition," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.

[177] Siavash Khodadadeh, Ladislau Boloni, and Mubarak Shah, "Unsupervised meta-learning for few-shot image classification," *Advances in neural information processing systems*, vol. 32, 2019.

[178] Boris Oreshkin, Pau Rodríguez López, and Alexandre Lacoste, "Tadam: Task dependent adaptive metric for improved few-shot learning," *Advances in neural information processing systems*, vol. 31, 2018.

[179] Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto, "Meta-learning with differentiable convex optimization," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2019, pp. 10657–10665.

[180] Yulin Wang, Zanlin Ni, Yifan Pu, Cai Zhou, Jixuan Ying, Shiji Song, and Gao Huang, "InfoPro: Locally Supervised Deep Learning by Maximizing Information Propagation," *International Journal of Computer Vision*, pp. 1–31, 2024.

[181] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun, "Deep residual learning for image recognition," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 770–778.

[182] Luca Bertinetto, João F. Henriques, Philip H. S. Torr, and Andrea Vedaldi, "Meta-learning with differentiable closed-form solvers," *CoRR*, vol. abs/1805.08136, 2018.

[183] Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B. Tenenbaum, Hugo Larochelle, and Richard S. Zemel, "Meta-Learning for Semi-Supervised Few-Shot Classification," *CoRR*, vol. abs/1803.00676, 2018.

[184] Jannatul Nayem, Sayed Sahriar Hasan, Noshin Amina, Bristy Das, Md Shahin Ali, Md Manjurul Ahsan, and Shivakumar Raman, "Few shot learning for medical imaging: a comparative analysis of methodologies and formal mathematical framework," in *Data Driven Approaches on Medical Imaging*, pp. 69–90. Springer, 2023.

[185] Ali Rostami, Vaibhav Pandey, Nitish Nag, Vesper Wang, and Ramesh Jain, "Personal Food Model," in *Proceedings of the 28th ACM International Conference on Multimedia*. Oct. 2020, MM '20, ACM.

[186] Vaibhav Pandey, Ali Rostami, Nitish Nag, and Ramesh Jain, *Event Mining Driven Context-Aware Personal Food Preference Modelling*, p. 660–676, Springer International Publishing, 2021.

[187] Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li, "Meta-sgd: Learning to learn quickly for few-shot learning," *arXiv preprint arXiv:1707.09835*, 2017.

[188] Ruixiang Zhang, Tong Che, Zoubin Ghahramani, Yoshua Bengio, and Yangqiu Song, "Metagan: An adversarial approach to few-shot learning," *Advances in neural information processing systems*, vol. 31, 2018.

[189] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, koray kavukcuoglu, and Daan Wierstra, "Matching Networks for One Shot Learning," in *Advances in Neural Information Processing Systems*, D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, Eds. 2016, vol. 29, Curran Associates, Inc.

[190] Chelsea Finn, Pieter Abbeel, and Sergey Levine, "Model-agnostic meta-learning for fast adaptation of deep networks," in *International conference on machine learning*. PMLR, 2017, pp. 1126–1135.

[191] Anders Krogh and John Hertz, "A simple weight decay can improve generalization," *Advances in neural information processing systems*, vol. 4, 1991.

[192] Geoffrey E Hinton, Nitish Srivastava, Alex Krizhevsky, Ilya Sutskever, and Ruslan R Salakhutdinov, "Improving neural networks by preventing co-adaptation of feature detectors," *arXiv preprint arXiv:1207.0580*, 2012.

[193] Alessandro Achille and Stefano Soatto, "Information dropout: Learning optimal representations through noisy computation," *IEEE transactions on pattern analysis and machine intelligence*, vol. 40, no. 12, pp. 2897–2905, 2018.

[194] Naftali Tishby and Noga Zaslavsky, "Deep learning and the information bottleneck principle," in *2015 ieee information theory workshop (itw)*. IEEE, 2015, pp. 1–5.

[195] Mingzhang Yin, George Tucker, Mingyuan Zhou, Sergey Levine, and Chelsea Finn, "Meta-learning without memorization," *arXiv preprint arXiv:1912.03820*, 2019.

[196] Edwin Pan, Pankaj Rajak, and Shubham Shrivastava, "Meta-regularization by enforcing mutual-exclusiveness," *arXiv preprint arXiv:2101.09819*, 2021.

[197] Huaxiu Yao, Linjun Zhang, and Chelsea Finn, "Meta-learning with fewer tasks through task interpolation," *arXiv preprint arXiv:2106.02695*, 2021.

[198] Shin'ya Yamaguchi, Daiki Chijiwa, Sekitoshi Kanai, Atsutoshi Kumagai, and Hisashi Kashima, "Regularizing Neural Networks with Meta-Learning Generative Models," *arXiv preprint arXiv:2307.13899*, 2023.

[199] Jun Shu, Xiang Yuan, Deyu Meng, and Zongben Xu, "DAC-MR: Data Augmentation Consistency Based Meta-Regularization for Meta-Learning," *arXiv preprint arXiv:2305.07892*, 2023.

[200] Yichen Wu, Long-Kai Huang, and Ying Wei, "Adversarial task up-sampling for meta-learning," *Advances in Neural Information Processing Systems*, vol. 35, pp. 31102–31115, 2022.

[201] Yangbin Chen, Yun Ma, Tom Ko, Jianping Wang, and Qing Li, "Metamix: Improved meta-learning with interpolation-based consistency regularization," in *2020 25th International Conference on Pattern Recognition (ICPR)*. IEEE, 2021, pp. 407–414.

[202] Yingjun Du, Zehao Xiao, Shengcai Liao, and Cees Snoek, "ProtoDiff: learning to learn prototypical networks by task-guided diffusion," *Advances in Neural Information Processing Systems*, vol. 36, pp. 46304–46322, 2023.

[203] Davis Wertheimer, Luming Tang, and Bharath Hariharan, "Few-shot classification with feature map reconstruction networks," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2021, pp. 8012–8021.

[204] Sayak Nag, Dripta S Raychaudhuri, Sujoy Paul, and Amit K Roy-Chowdhury, "Reconstruction guided meta-learning for few shot open set recognition," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2023.

[205] Spyros Gidaris, Andrei Bursuc, Nikos Komodakis, Patrick Pérez, and Matthieu Cord, "Boosting few-shot visual learning with self-supervision," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2019, pp. 8059–8068.

[206] Shell Xu Hu, Da Li, Jan Stühmer, Minyoung Kim, and Timothy M Hospedales, "Pushing the limits of simple pipelines for few-shot learning: External data and fine-tuning make a difference," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 9068–9077.

[207] Haoxiang Wang, Yite Wang, Ruoyu Sun, and Bo Li, "Global convergence of maml and theory-inspired neural architecture search for few-shot learning," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2022, pp. 9797–9808.

[208] Sachin Ravi and Hugo Larochelle, "Optimization as a model for few-shot learning," in *International conference on learning representations*, 2017.

[209] Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel, "Meta-learning for semi-supervised few-shot classification," *arXiv preprint arXiv:1803.00676*, 2018.

[210] Boris Oreshkin et al., "TADAM: Task dependent adaptive metric for improved few-shot learning," in *Advances in Neural Information Processing Systems*, S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, Eds. 2018, vol. 31, Curran Associates, Inc.

[211] Horizon2333, "https://github.com/Horizon2333/imagenet-autoencoder/blob/main/models/resnet.py," 2021.

[212] Luca Bertinetto, Joao F Henriques, Philip HS Torr, and Andrea Vedaldi, "Meta-learning with differentiable closed-form solvers," *arXiv preprint arXiv:1805.08136*, 2018.

[213] Yanbin Liu, Juho Lee, Minseop Park, Saehoon Kim, Eunho Yang, Sung Ju Hwang, and Yi Yang, "Learning to propagate labels: Transductive propagation network for few-shot learning," *arXiv preprint arXiv:1805.10002*, 2018.

[214] Tsendsuren Munkhdalai, Xingdi Yuan, Soroush Mehri, and Adam Trischler, "Rapid adaptation with conditionally shifted neurons," in *International conference on machine learning*. PMLR, 2018, pp. 3664–3673.

[215] Aaron van den Oord, Yazhe Li, and Oriol Vinyals, "Representation learning with contrastive predictive coding," *arXiv preprint arXiv:1807.03748*, 2018.

[216] Joshua Robinson, Ching-Yao Chuang, Suvrit Sra, and Stefanie Jegelka, "Contrastive learning with hard negative samples," *arXiv preprint arXiv:2010.04592*, 2020.

[217] Pietro Morerio, Ruggero Ragonesi, and Vittorio Murino, "Model Debiasing by Learnable Data Augmentation," *arXiv preprint arXiv:2408.04955*, 2024.

[218] Nick Whiteley, Annie Gray, and Patrick Rubin-Delanchy, "Statistical exploration of the Manifold Hypothesis," *arXiv preprint arXiv:2208.11665*, 2022.

[219] Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli, "wav2vec 2.0: A framework for self-supervised learning of speech representations," *Advances in neural information processing systems*, vol. 33, pp. 12449–12460, 2020.

[220] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol, "Extracting and composing robust features with denoising autoencoders," in *Proceedings of the 25th international conference on Machine learning*, 2008, pp. 1096–1103.

[221] Thomas N Kipf and Max Welling, "Semi-supervised classification with graph convolutional networks," *arXiv preprint arXiv:1609.02907*, 2016.

[222] Will Hamilton, Zhitao Ying, and Jure Leskovec, "Inductive representation learning on large graphs," *Advances in neural information processing systems*, vol. 30, 2017.

[223] Avital Oliver, Augustus Odena, Colin A Raffel, Ekin Dogus Cubuk, and Ian Goodfellow, "Realistic evaluation of deep semi-supervised learning algorithms," *Advances in neural information processing systems*, vol. 31, 2018.

[224] Olivier Chapelle, Bernhard Scholkopf, and Alexander Zien, "Semi-supervised learning (chapelle, o. et al., eds.; 2006)[book reviews]," *IEEE Transactions on Neural Networks*, vol. 20, no. 3, pp. 542–542, 2009.

[225] Mehdi Sajjadi, Mehran Javanmardi, and Tolga Tasdizen, "Regularization with stochastic transformations and perturbations for deep semi-supervised learning," *Advances in neural information processing systems*, vol. 29, 2016.

[226] Samuli Laine and Timo Aila, "Temporal ensembling for semi-supervised learning," *arXiv preprint arXiv:1610.02242*, 2016.

[227] Antti Tarvainen and Harri Valpola, "Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results," *Advances in neural information processing systems*, vol. 30, 2017.

[228] Takeru Miyato, Shin-ichi Maeda, Masanori Koyama, and Shin Ishii, "Virtual adversarial training: a regularization method for supervised andsemi-supervised learning," *arXiv preprint arXiv:1704.03976*, 2017.

[229] Qizhe Xie, Zihang Dai, Eduard Hovy, Minh-Thang Luong, and Quoc V Le, "Unsupervised data augmentation," *arXiv preprint arXiv:1904.12848*, vol. 2, no. 6, pp. 7, 2019.

[230] David Berthelot, Nicholas Carlini, Ekin D Cubuk, Alex Kurakin, Kihyuk Sohn, Han Zhang, and Colin Raffel, "Remixmatch: Semi-supervised learning with distribution alignment and augmentation anchoring," *arXiv preprint arXiv:1911.09785*, 2019.

[231] Bowen Zhang, Yidong Wang, Wenxin Hou, Hao Wu, Jindong Wang, Manabu Okumura, and Takahiro Shinozaki, "Flexmatch: Boosting semi-supervised learning with curriculum pseudo labeling," *Advances in Neural Information Processing Systems*, vol. 34, pp. 18408–18419, 2021.

[232] Junnan Li, Caiming Xiong, and Steven CH Hoi, "Comatch: Semi-supervised learning with contrastive graph regularization," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2021, pp. 9475–9484.

[233] Liangxin Liu, Xuebo Liu, Lian Lian, Shengjun Cheng, Jun Rao, Tengfei Yu, Hexuan Deng, and Min Zhang, "Curriculum Consistency Learning for Conditional Sentence Generation," in *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 2024, pp. 13865–13881.

[234] Yu Sun, Xinhao Li, Karan Dalal, Jiarui Xu, Arjun Vikram, Genghan Zhang, Yann Dubois, Xinlei Chen, Xiaolong Wang, Sanmi Koyejo, et al., "Learning to (learn at test time): Rnns with expressive hidden states," *arXiv preprint arXiv:2407.04620*, 2024.

[235] Hengduo Li, Zuxuan Wu, Abhinav Shrivastava, and Larry S Davis, "Rethinking pseudo labels for semi-supervised object detection," in *Proceedings of the AAAI Conference on Artificial Intelligence*, 2022, vol. 36, pp. 1314–1322.

[236] Pengxiang Yan, Guanbin Li, Yuan Xie, Zhen Li, Chuan Wang, Tianshui Chen, and Liang Lin, "Semi-supervised video salient object detection using pseudo-labels," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2019, pp. 7284–7293.

[237] Fariborz Taherkhani, Ali Dabouei, Sobhan Soleymani, Jeremy Dawson, and Nasser M Nasrabadi, "Self-supervised Wasserstein pseudo-labeling for semi-supervised image classification," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021, pp. 12267–12277.

[238] Hao Wu and Saurabh Prasad, "Semi-supervised deep learning using pseudo labels for hyperspectral image classification," *IEEE Transactions on Image Processing*, vol. 27, no. 3, pp. 1259–1270, 2017.

[239] Loren Lugosch, Tatiana Likhomanenko, Gabriel Synnaeve, and Ronan Collobert, "Pseudo-labeling for massively multilingual speech recognition," in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2022, pp. 7687–7691.

[240] Eric Arazo, Diego Ortego, Paul Albert, Noel E O'Connor, and Kevin McGuinness, "Pseudo-labeling and confirmation bias in deep semi-supervised learning," in *2020 International Joint Conference on Neural Networks (IJCNN)*. IEEE, 2020, pp. 1–8.

[241] Ahmet Iscen, Giorgos Tolias, Yannis Avrithis, and Ondrej Chum, "Label propagation for deep semi-supervised learning," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2019, pp. 5070–5079.

[242] Mamshad Nayeem Rizve, Kevin Duarte, Yogesh S Rawat, and Mubarak Shah, "In defense of pseudo-labeling: An uncertainty-aware pseudo-label selection framework for semi-supervised learning," *arXiv preprint arXiv:2101.06329*, 2021.

[243] Chien-Chih Wang, Shaoyuan Xu, Jinmiao Fu, Yang Liu, and Bryan Wang, "KD-FixMatch: Knowledge distillation siamese neural networks," in *2023 IEEE International Conference on Image Processing (ICIP)*. IEEE, 2023, pp. 341–345.

[244] Qizhe Xie, Zihang Dai, Eduard Hovy, Thang Luong, and Quoc Le, "Unsupervised data augmentation for consistency training," *Advances in neural information processing systems*, vol. 33, pp. 6256–6268, 2020.

[245] Jang Hyun Cho and Bharath Hariharan, "On the efficacy of knowledge distillation," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2019, pp. 4794–4802.

[246] Mary Phuong and Christoph Lampert, "Towards understanding knowledge distillation," in *International conference on machine learning*. PMLR, 2019, pp. 5142–5151.

[247] Xinjiang Wang, Xingyi Yang, Shilong Zhang, Yijiang Li, Litong Feng, Shijie Fang, Chengqi Lyu, Kai Chen, and Wayne Zhang, "Consistent-teacher: Towards reducing inconsistent pseudo-targets in semi-supervised object detection," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 3240–3249.

[248] Lin Li, Jun Xiao, Hanrong Shi, Hanwang Zhang, Yi Yang, Wei Liu, and Long Chen, "Nicest: Noisy label correction and training for robust scene graph generation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.

[249] Durk P Kingma, Shakir Mohamed, Danilo Jimenez Rezende, and Max Welling, "Semi-supervised learning with deep generative models," *Advances in neural information processing systems*, vol. 27, 2014.

[250] Benjamin Devillers, Léopold Maytié, and Rufin VanRullen, "Semi-supervised multimodal representation learning through a global workspace," *IEEE Transactions on Neural Networks and Learning Systems*, 2024.

[251] Svetlana Kutuzova, Oswin Krause, Douglas McCloskey, Mads Nielsen, and Christian Igel, "Multimodal variational autoencoders for semi-supervised learning: In defense of product-of-experts," *arXiv preprint arXiv:2101.07240*, 2021.

[252] Ching-Yao Chuang, Joshua Robinson, Yen-Chen Lin, Antonio Torralba, and Stefanie Jegelka, "Debiased contrastive learning," *Advances in neural information processing systems*, vol. 33, pp. 8765–8775, 2020.

[253] Rizhao Fan, Matteo Poggi, and Stefano Mattoccia, "Contrastive learning for depth prediction," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2023, pp. 3226–3237.

[254] Armen Aghajanyan, Akshat Shrivastava, Anchit Gupta, Naman Goyal, Luke Zettlemoyer, and Sonal Gupta, "Better fine-tuning by reducing representational collapse," *arXiv preprint arXiv:2008.03156*, 2020.

[255] Filip Radenovic, Abhimanyu Dubey, Abhishek Kadian, Todor Mihaylov, Simon Vandenhende, Yash Patel, Yi Wen, Vignesh Ramanathan, and Dhruv Mahajan, "Filtering, distillation, and hard negatives for vision-language pre-training," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2023, pp. 6967–6977.

[256] Yannis Kalantidis, Mert Bulent Sariyildiz, Noe Pion, Philippe Weinzaepfel, and Diane Larlus, "Hard negative mixing for contrastive learning," *Advances in neural information processing systems*, vol. 33, pp. 21798–21809, 2020.

[257] Zhen Yang, Tinglin Huang, Ming Ding, Yuxiao Dong, Rex Ying, Yukuo Cen, Yangliao Geng, and Jie Tang, "Batchsampler: Sampling mini-batches for contrastive learning in vision, language, and graphs," in *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2023, pp. 3057–3069.

[258] Dong-Hyun Lee et al., "Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks," in *Workshop on challenges in representation learning, ICML*. Atlanta, 2013, vol. 3, p. 896.

[259] Qizhe Xie, Minh-Thang Luong, Eduard Hovy, and Quoc V Le, "Self-training with noisy student improves imagenet classification," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2020, pp. 10687–10698.

[260] Hardik Singh, Sweta Swagatika, Raavi Sai Venkat, and Sanjay Saxena, "Justification of stl-10 dataset using a competent cnn model trained on cifar-10," in *2019 3rd International conference on Electronics, Communication and Aerospace Technology (ICECA)*. IEEE, 2019, pp. 1254–1257.

[261] Tien Ho-Phuoc, "CIFAR10 to compare visual recognition performance between deep neural networks and humans," *arXiv preprint arXiv:1811.07270*, 2018.

[262] Pierre Sermanet, Soumith Chintala, and Yann LeCun, "Convolutional neural networks applied to house numbers digit classification," in *Proceedings of the 21st international conference on pattern recognition (ICPR2012)*. IEEE, 2012, pp. 3288–3291.

[263] Alex Krizhevsky and Geoffrey Hinton, "Learning Multiple Layers of Features from Tiny Images," Tech. Rep., University of Toronto, 2009.

[264] Han Xiao, Kashif Rasul, and Roland Vollgraf, "Fashion-MNIST: a Novel Image Dataset for Benchmarking Machine Learning Algorithms," *arXiv preprint arXiv:1708.07747*, 2017.

[265] Gary B. Huang, Manu Ramesh, Tamara Berg, and Erik Learned-Miller, "Labeled Faces in the Wild: A Database for Studying Face Recognition in Unconstrained Environments," Tech. Rep. 07-49, University of Massachusetts, Amherst, 2007.

[266] Patrick Helber, Benjamin Bischke, Andreas Dengel, and Damian Borth, "EuroSAT: A Novel Dataset and Deep Learning Benchmark for Land Use and Land Cover Classification," *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, vol. 12, no. 7, pp. 2217–2226, 2019.

[267] Maria-Elena Nilsback and Andrew Zisserman, "Automated Flower Classification over a Large Number of Classes," in *Indian Conference on Computer Vision, Graphics and Image Processing*, 2008.

[268] Jeremy Howard, "Imagenette: A Smaller Dataset for Image Classification Experiments," `https://github.com/fastai/imagenette`, 2019.

[269] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al., "Pytorch: An imperative style, high-performance deep learning library," *Advances in neural information processing systems*, vol. 32, 2019.

[270] Swarnambiga Ayyachamy, Varghese Alex, Mahendra Khened, and Ganapathy Krishnamurthi, "Medical image retrieval using Resnet-18," in *Medical imaging 2019: imaging informatics for healthcare, research, and applications*. SPIE, 2019, vol. 10954, pp. 233–241.

[271] Zijun Zhang, "Improved adam optimizer for deep neural networks," in *2018 IEEE/ACM 26th international symposium on quality of service (IWQoS)*. Ieee, 2018, pp. 1–2.

[272] Robert Mansel Gower, Nicolas Loizou, Xun Qian, Alibek Sailanbayev, Egor Shulgin, and Peter Richtárik, "SGD: General analysis and improved rates," in *International conference on machine learning*. PMLR, 2019, pp. 5200–5209.