

Developing for IBM i






with AI tools


Consuming AI

AI for RPGLE



AI for Db2 for IBM i


**Prompt
Engineering and
Enrichment**





API service







o 2023/01/23 - 11:18:37 1.0482

ollama.com

granite-code

A family of open foundation models by IBM for Code Intelligence

3b 8b 20b 34b

175.9K Pulls Updated 4 months ago


3b ▾ 162 Tags

ollama run granite-code

	Updated 4 months ago	becc94fe1876 · 2.0GB
model	arch llama · parameters 3.48B · quantization Q4_0	2.0GB
params	{ "stop": ["System:", "Question:", "Answer:"] }	43B
template	{{ if .Suffix }}<fim_prefix> {{ .Prompt }}<fim_suffix> {{ ... }}	679B
license	Apache License Version 2.0, January 2004	11kB

```
[barry@Liams-MBP ~ % ollama serve
2025/01/23 11:18:51 routes.go:1195: INFO server config env="map[HTTPS_PROXY: HTTP_PROXY: NO_PROXY: OLLAMA_DEBUG:false OLLAMA_FLASH_ATTENTION:false OLLAMA_GPU_OVERHEAD:0 OLLAMA_HOST:http://127.0.0.1:11434 OLLAMA_KEEP_ALIVE:5m0s OLLAMA_KV_CACHE_TYPE: OLLAMA_LLM_LIBRARY: OLLAMA_LOAD_TIMEOUT:5m0s OLLAMA_MAX_LOADED_MODELS:0 OLLAMA_MAX_QUEUE:512 OLLAMA_MODELS:/Users/barry/.ollama/models OLLAMA_MULTIUSER_CACHE:false OLLAMA_NOHISTORY:false OLLAMA_NOPRUNE:false OLLAMA_NUM_PARALLEL:0 OLLAMA_ORIGINS:[http://localhost https://localhost http://localhost:* https://localhost:* http://127.0.0.1 https://127.0.0.1 http://127.0.0.1:* https://127.0.0.1:* http://0.0.0.0 https://0.0.0.0 http://0.0.0.0:* https://0.0.0.0:* app:///* file:///* tauri:///* vscode-webview:///*] OLLAMA_SCHED_SPREAD:false OLLAMA_TMPDIR: http_proxy: https_proxy: no_proxy:]"
time=2025-01-23T11:18:51.384-05:00 level=INFO source=images.go:753 msg="total blobs: 5"
time=2025-01-23T11:18:51.384-05:00 level=INFO source=images.go:760 msg="total unused blobs removed: 0"
time=2025-01-23T11:18:51.385-05:00 level=INFO source=routes.go:1246 msg="Listening on 127.0.0.1:11434 (version 0.5.1)"
)
time=2025-01-23T11:18:51.392-05:00 level=INFO source=common.go:135 msg="extracting embedded files" dir=/var/folders/_3/4hxcf12x4mq5gl3y96cxn3fh0000gn/T/ollama1634341714/runners
time=2025-01-23T11:18:51.461-05:00 level=INFO source=common.go:49 msg="Dynamic LLM libraries" runners=[metal]
time=2025-01-23T11:18:51.490-05:00 level=INFO source=types.go:123 msg="inference compute" id=0 library=metal variant="" compute="" driver=0.0 name="" total="21.3 GiB" available="21.3 GiB"
[GIN] 2025/01/23 - 11:18:57 | 200 | 1.161458ms | 127.0.0.1 | HEAD | /
[GTIN] 2025/01/23 - 11:18:57 | 200 | 1.048208ms | 127.0.0.1 | GET | /api/tags"
```

```
Last login: Thu Jan 23 11:18:36 on ttys000
[barry@Liams-MBP ~ % ollama list
NAME                  ID          SIZE      MODIFIED
granite-code:8b      36c3c3b9683b    4.6 GB    6 weeks ago
barry@Liams-MBP ~ %
```



```
barry@Liams-MBP ~ % ollama run llama3.1:8b
>>> Hello
How can I help you today?



>>> What languages do you support?
I'm a multilingual AI and can understand and respond in many languages.
Here are some of the languages I support:

**Main languages:**

1. English (default)
2. Spanish
3. French
4. German
5. Italian
6. Portuguese
7. Dutch
8. Russian
9. Chinese (Simplified and Traditional)
10. Japanese

**Other languages:**

I can also understand and respond in many other languages, including but
```



Search CONTINUE

Ask anything, '@' to add context
Granite Chat @ [⌘ ⇧ @codebase](#) ↵ Enter

Last Session

Quickstart Best experience Local with Ollama

Install Ollama

<https://ollama.ai/download>

Download Chat model

ollama pull llama3.1:8b ✓

Download Autocomplete model

ollama pull qwen2.5-coder:1.5b ✓



Connect

This will update your [config file](#)

PROBLEMS TERMINAL OUTPUT DEBUG CONSOLE RUN AND DEBUG PORTS + ⌄ ... ⌈ ⌂ X

pulling manifest
pulling 667b0c1932bc... 100% | 4.9 GB
pulling 948af2743fc7... 100% | 1.5 KB
pulling 0ba8f0e314b4... 100% | 12 KB
pulling 56bb8bd477a5... 100% | 96 B
pulling 455f34728c9b... 100% | 487 B
verifying sha256 digest
writing manifest
success
barry@Liams-MBP ~ % ollama pull qwen2.5-coder:1.5b
pulling manifest
pulling 29d8c98fa6b0... 100% | 986 MB
pulling 66b9ea09bd5b... 100% | 68 B

⊗ 0 ⚛ 0 Continue





The screenshot shows a code editor interface with a large 'X' watermark in the center. The top bar includes standard OS X-style controls (red, yellow, green) and a search bar. Below the search bar is a toolbar with various icons. The left sidebar contains file-related commands: 'Show All Commands' (with keyboard shortcut ⌘P), 'Open File or Folder' (with keyboard shortcut ⌘O), 'Open Recent' (with keyboard shortcut ⌘R), and 'New Untitled Text File' (with keyboard shortcut ⌘N). The bottom left pane displays a terminal window with the following output:

```
PROBLEMS TERMINAL OUTPUT DEBUG CONSOLE RUN AND DEBUG PORTS + ⌄ ... ⌄ ⌄ x
writing manifest
success
● barry@Liams-MBP ~ % ollama pull qwen2.5-coder:1.5b
pulling manifest
pulling 29d8c98fa6b0... 100% 986 MB
pulling 66b9ea09bd5b... 100% 68 B
pulling e94a8ecb9327... 100% 1.6 KB
pulling 832dd9e00a68... 100% 11 KB
pulling 152cb442202b... 100% 487 B
verifying sha256 digest
writing manifest
success
○ barry@Liams-MBP ~ %
```

The right side of the interface features a large text area for a Q&A session with 'Llama 3.1 8B'. The first message asks 'What programming languages do you support?' followed by a reply: 'I can understand and generate code in a wide range of programming languages. Here are some examples:'. Below this, a section titled 'Supported languages:' lists nine items, each preceded by a numbered bullet point and a brief description.

- 1. **Python:** I have excellent support for Python, including popular libraries like NumPy, pandas, and scikit-learn.
- 2. **Java:** I'm familiar with Java syntax and can write Java code using standard libraries like Java Collections Framework and Java Stream API.
- 3. **JavaScript:** I can write JavaScript code using modern syntax and frameworks like Node.js, React, and Angular.
- 4. **C++:** While my C++ support is not as extensive as some other languages, I can still write basic C++ code and understand common libraries like STL (Standard Template Library).
- 5. **SQL:** I'm proficient in SQL syntax and can write queries using popular database management systems like MySQL, PostgreSQL, and SQLite.
- 6. **R:** I have knowledge of R programming language and can write R code for data analysis, visualization, and machine learning tasks.
- 7. **MATLAB:** While my MATLAB support is limited, I can still understand basic syntax and concepts, including matrix operations and plotting functions.
- 8. **C#:** I'm familiar with C# syntax and can write C# code using standard libraries like .NET Framework.
- 9. **Go:** I have knowledge of Go programming language (also known as Golang) and can write Go code for distributed systems.

At the bottom, there's a section titled 'Ask a follow-up' with a message from 'Llama 3.1 8B' and a 'Continue' button.



The screenshot shows the Visual Studio Code interface with the 'Extension Development Host' title bar. A search bar at the top right contains the text '[Extension Development Host] sql'. The main area displays the 'Continue - Codestral, Claude, and more' extension details. The extension icon is a hexagonal grid of black lines forming a cube-like shape. It has a rating of 370,224 and 5 stars. Below the icon, there are buttons for 'Disable' (with a dropdown arrow), 'Uninstall' (with a dropdown arrow), 'Switch to Release Version', and an 'AI' toggle switch. Below these buttons are tabs for 'DETAILS', 'FEATURES', and 'CHANGELOG', with 'DETAILS' currently selected. The 'DETAILS' tab shows a large image of the 'Continue' logo, which is a 3D cube with a hexagonal pattern. To the right of the image, there's a section titled 'Categories' with buttons for 'Programming Languages', 'Snippets', 'Machine Learning', 'Education', 'AI', and 'Chat'. Below this is a section titled 'Resources' with several small icons. At the bottom of the extension details is a text block: 'Continue is the leading open-source AI code assistant. You can connect any models and context to build custom autocomplete and chat'. The bottom navigation bar includes 'PROBLEMS', 'OUTPUT', 'DEBUG CONSOLE', 'TERMINAL' (which is selected and highlighted in red), and 'COMMENTS'. A terminal panel on the left shows the command line: '(base) ~/Documents/IBM/sandbox/oss/ai/sql'. On the right side of the screen, a modal dialog box is open with the title 'Add Chat model'. It contains fields for 'Provider' (set to 'IBM watsonx'), 'Model' (set to 'watsonx - Granite Code 20b'), 'watsonx URL' (with placeholder 'e.g. http://us-south.dataplatform.cloud.ibm.com'), 'watsonx Project ID' (with placeholder 'Enter your project ID'), 'watsonx API key' (with placeholder 'Enter your API key (SaaS) or ZenApiKey (Software)'), 'watsonx API version' (set to '2023-05-29'), and a large 'Connect' button at the bottom. A note below the 'Connect' button states 'This will update your config file'. The status bar at the bottom includes icons for Launchpad, Live Share, Go Live, Reload, and Continue.



CHAT + ⏪ ...

Ask Copilot

Sign in with GitHub to use GitHub Copilot, your AI pair programmer.

[Sign in to GitHub.com](#)

[Sign in with a GHE.com account](#)

Or explore the [Copilot walkthrough](#) to learn more!

Search

Show All Commands ⌘ P

Open File or Folder ⌘ O

Open Recent ⌘ R

New Untitled Text File ⌘ N

Open Chat ⌘ I

✖ 0 ⌛ 0



A promotional banner for GitHub Copilot in VS Code. It features a dark background with a purple-to-blue gradient. On the right side, there is a stylized, glowing version of the GitHub Copilot logo (a robot head) with a purple and blue glow. To the left of the logo, the text "GitHub Copilot in VS Code" is written in white, and below it, the word "FREE" is written in a large, bold, white font.



← → ⌂ Search ⌂ v 🔎 🔍

CHAT + ⏪ ⏴ ⏵

 worksofliam

What languages do you support?

 GitHub Copilot

I support a wide range of programming languages, including but not limited to:

- Python
- JavaScript
- TypeScript
- Java
- C#
- C++
- Ruby
- Go
- Swift
- Kotlin
- PHP
- HTML
- CSS
- SQL
- R
- MATLAB
- Bash/Shell scripting
- JSON
- YAML
- Markdown

What language should I use?

Ask Copilot @ ⌂ ⌂ GPT 4o ⏪ ⏵

Show All Commands ⌂ ⌂ P
Open File or Folder ⌂ O
Open Recent ⌂ R
New Untitled Text File ⌂ N
Open Chat ⌂ ⌂ I

✖

⊗ 0 △ 0 🔎 🔍



Docs Updates Blog API Extensions MCP FAQ Dev Days



Download

Join a [VS Code Dev Days event](#) near you to learn about AI-assisted development in VS Code.

The open source AI code editor



Download for macOS

[Web](#), [Insiders edition](#), or [other platforms](#)

By using VS Code, you agree to its [license](#) and [privacy statement](#).

What is context building?

chatgpt.com

Actions Overview and Usage

What are Actions? | Code for IBM i Docs

ChatGPT

An action is used to perform a task on a member, streamfile or other type of object. A comprehensive default set of actions is loaded directly from the extension. You can also easily change or add to actions—see View/Change/Add Actions, below.

Actions are defined commands used to perform tasks on members, streamfiles and other types of objects. For example, to compile a source file. Actions can be executed from two different places:

- As you're writing code. For example, to compile a program or module.
- When you right click on a member, streamfile or an object from the OBJECT BROWSER.

A comprehensive set of Actions is provided, but you can add more or change the ones provided.

Can you summarize an action in one sentence?

An action is a defined command that performs a specific task, such as compiling code, on members, streamfiles, or other objects, and can be executed from the editor or object browser.

Message ChatGPT

ChatGPT can make mistakes. Check important info.

What is context building?

The variable `taxPercentage` is used in the `calculateTotal` and `getTaxPercByCountry` functions. The value is gathered from a database statement that returns a row based on the country.

What is the purpose of the variable `taxPercentage`?

Additional context provided by extensions

```
function getTaxPercByCountry(country: string): number {
  const [row] = query(`SELECT tax_code FROM countries WHERE country = ${country}`);

  return row.tax_code;
}

function calculateTotal(input, country) {
  const taxPercentage = getTaxPercByCountry(country);

  return input * (1 + taxPercentage / 100);
}

// Example usage
const total = calculateTotal(100, 'UK');
```

User input

What is context building?

The references table 'countries' has 6 columns, but the important columns are tax_percent and country. Country is a character(2) column, where tax_percent is a decimal(3, 2) and is likely used to store the tax percentage for each country.

The variable taxPercentage is used in the calculateTotal and getTaxPercByCountry functions. The value is gathered from a database statement that returns a row based on the country.

What is the purpose of the variable taxPercentage?

Specific enrichment specific to this source

Additional context provided by extensions

User input

```
dcl-proc getTaxPercByCountry;
dcl-pi *n packed(3:2);
country char(2) const;
end-pi;

dcl-s taxPerc packed(3:2);

exec sql
...
select tax_percent
into :taxPerc
from counties
where country = :country;

return taxPerc;
end-proc;

dcl-proc calculateTotal;
dcl-pi *n;
amount packed(7:2) const;
country char(2) const;
end-pi;

dcl-s taxPercentage packed(3:2);

taxPercentage = getTaxPercByCountry(country);

return amount + (amount * taxPercentage / 100);
end-proc;
```

Prompting case study

GitHub-Copilot-Cobol-Extension

GitHub Copilot Cobol Extension

Description

This Visual Studio Code extension provides tools and utilities to assist with COBOL programming. It includes features for generating documentation, explaining code, and analyzing COBOL programs.

Features

- **Explain COBOL Program:** Generate detailed explanations for COBOL programs, including program info, data division, and procedure division.
- **Generate Documentation:** Automatically generate markdown documentation for COBOL programs.
- **Analyze COBOL Code:** Chunk COBOL code into divisions, sections, and paragraphs for detailed analysis.

Commands

The extension provides the following commands:

- `explain` : Explain the entire COBOL program.
- `info` : Extract and display information about the COBOL program.
- `data` : Explain the data division of the COBOL program.
- `procedure` : Explain the procedure division of the COBOL program.
- `gendoc` : Generate a markdown documentation file for the COBOL program.

```
export async function explainCode(
  code: string,
  stream: vscode.ChatResponseStream,
  request: vscode.ChatRequest,
  token: vscode.CancellationToken
) {
  stream.progress(`Analyzing code...`);

  const prompt = explainCodePrompt.replace(`{{code}}`, code);

  const msgs = [
    vscode.LanguageModelChatMessage.Assistant(systemPrompt),
    vscode.LanguageModelChatMessage.User(prompt),
  ];
  let contentResult = "";
  const result = await request.model.sendRequest(msgs, {}, token);
  for await (const fragment of result.text) {
    stream.markdown(fragment);
    contentResult += fragment;
  }
  return contentResult;
}
```

```
export const systemPrompt =
  "You are a useful Assistant that helps to generate docs for COBOL code, do not add code samples.";

export const explainCodePrompt = `
  Write an explanation for the COBOL program as paragraphs of text
  Do not insert source code inside explanation
  Do not generate or add examples
  Do not add consideration or comments

  Below is the code, do not add it to output:

  ### CODE
  \n  {{code}}
  ### END CODE
  `;
```

```

60
61 - 2: ...
62
63 ##### Diagram
64 mermaid_flow_diagram
65
66 ##### External Calls
67 - call_name
68 ##### Internal Calls
69 - perform_name
70
71
72
73 Below is the code, do not add it to output:
74
75 ### CODE
76 \n {{code}}
77 ### END CODE
78 `;
79 export const dataSectionPrompt = `list all variables, labels and constants at all nested levels as a bullet list, for each variable , label and constant at every level and nested level add a paragraph with description and data type
80 respect the hierarchy levels of the variables, labels and constants in the list and put level number in brackets after the constant and variable name like VARIABLE_NAME (level)
81 do not add any title like 'Variables, Labels, and Constants...' or similar
82 each bullet point should be like this:
83 - **VARIABLE_NAME (LEVEL_NUMBER)**
84 | - Description: Variable description.
85 | - Data Type: Variable data type.
86 If you dont find any variables, labels or constants just respond with 'none'
87 Below is the code, do not add it to output:
88
89
90 ### CODE
91 \n {{code}}
92 ### END CODE
93 `;
94
95 export const explainCodePrompt = `Write an explanation for the COBOL program as paragraphs of text
96 Do not insert source code inside explanation
97 Do not generate or add examples
98 Do not add consideration or comments
99
100 Below is the code, do not add it to output:
101
102
103 ### CODE
104 \n {{code}}
105 ### END CODE
106 `;

```

What about tools?

A screenshot of a web browser window showing the ChatGPT homepage at chatgpt.com. The browser interface includes standard Mac OS X controls (red, yellow, green buttons, back/forward arrows, search bar, and tabs). The ChatGPT header features a profile icon and a "Temporary" status indicator. The main content area displays the question "What can I help with?" and a central input field labeled "Ask anything". Below the input field are four buttons: a plus sign (+), "Search" (with a magnifying glass icon), "Reason" (with a lightbulb icon), and a three-dot menu button. A large, semi-transparent callout box is overlaid on the interface, containing two items: "Create image" (with a camera icon) followed by the text "Updated Visualize ideas and concepts" and "Canvas" (with a paintbrush icon) followed by the text "Collaborate on writing and code". At the bottom of the page, a footer note reads "ChatGPT can make mistakes. Check important info." and a question mark icon is in the bottom right corner.

chatgpt.com

ChatGPT

Temporary

Ask anything

+ Search Reason ...

Create image Updated
Visualize ideas and concepts

Canvas
Collaborate on writing and code

ChatGPT can make mistakes. Check important info.

list-usable-tables

Department Employee Counts

A

how many employees are in each department?

I'll help you find information about the number of employees in each department. Let me first check what tables are available in the database.

[View result from **list-usable-tables**](#) >

describe-table

I can see that there are DEPARTMENT and EMPLOYEE tables that likely contain the information you're looking for. Let me examine these tables to understand their structure.

[View result from **describe-table**](#) >

[View result from **describe-table**](#) >

run-sql-query

Now I'll run a query to count the number of employees in each department. I'll join with the DEPARTMENT table to show the department names as well.

[View result from **run-sql-query**](#) >

Here's the breakdown of how many employees are in each department:

Department Code	Department Name	Employee Count
A00	SPIFFY COMPUTER SERVICE DIV.	5
B01	PLANNING	1
C01	INFORMATION CENTER	4
D01	DEVELOPMENT CENTER	0
D11	MANUFACTURING SYSTEMS	11
D21	ADMINISTRATION SYSTEMS	7

list-usable-tables

```
select table_name from qsys2.sysfiles  
where table_schema = CURRENT SCHEMA
```

describe-table

```
call qsys2.generate_sql(CURRENT SCHEMA, :tableName)
```

Department Employee Counts

A how many employees are in each department?

I'll help you find information about the number of employees in each department. Let me first check what tables are available in the database.

View result from [list-usable-tables](#) ▾

```
{}
```

```
Usable tables: ['ACT', 'CL_SCHED', 'DELETEME', 'DEPARTMENT', 'EMPLOYEE',  
'EMPPROJECT', 'EMP_PHOTO', 'EMP_RESUME', 'IN_TRAY', 'ORG', 'PROJECT', 'PROJECT',  
'SALES', 'STAFF']
```

I can see that there are DEPARTMENT and EMPLOYEE tables that likely contain the information you're looking for. Let me examine these tables to understand their structure.

View result from [describe-table](#) ▾

```
{  
  `table_name`: `DEPARTMENT`  
}  
  
-- Generate SQL  
-- Version: V7R4M0 190621  
-- Generated on: 03/11/25 18:40:56
```

View result from [describe-table](#) ▶

Now I'll run a query to count the number of employees in each department. I'll join with the DEPARTMENT table to show the department names as well.

Department Employee Counts

Now I'll run a query to count the number of employees in each department. I'll join with the DEPARTMENT table to show the department names as well.

View result from [run-sql-query](#) ▾

```
`sql`:  
SELECT D.DEPTNO, D.DEPTNAME, COUNT(E.EMPNO) AS EMPLOYEE_COUNT  
FROM DEPARTMENT D  
LEFT JOIN EMPLOYEE E ON D.DEPTNO = E.WORKDEPT  
GROUP BY D.DEPTNO, D.DEPTNAME  
ORDER BY D.DEPTNO  
`
```

Here's the breakdown of how many employees are in each department:


Department Code	Department Name	Employee Count
A00	SPIFFY COMPUTER SERVICE DIV.	5
B01	PLANNING	1
C01	INFORMATION CENTER	4
D01	DEVELOPMENT CENTER	0
D11	MANUFACTURING SYSTEMS	11
D21	ADMINISTRATION SYSTEMS	7
E01	SUPPORT SERVICES	1
E11	OPERATIONS	7
E21	SOFTWARE SUPPORT	6
F22	BRANCH OFFICE F2	0
G22	BRANCH OFFICE G2	0



Model Context Protocol

modelcontextprotocol.io


Your tools implemented here



Client	<u>Resource</u>	<u>Prompts</u>	<u>Tools</u>	<u>Discovery</u>	<u>Sampling</u>	Roots	Notes
BeeAI Framework	✗	✗	✓	✗	✗	✗	Supports tools in agentic workflows.
Claude.ai	✓	✓	✓	✗	✗	✗	Supports tools, prompts, and resources for remote MCP servers.
Claude Code	✗	✓	✓	✗	✗	✗	Supports prompts and tools
Claude Desktop App	✓	✓	✓	✗	✗	✗	Supports tools, prompts, and resources for local and remote MCP servers.
Cline	✓	✗	✓	✓	✗	✗	Supports tools and resources.
Continue	✓	✓	✓	?	✗	✗	Supports tools, prompts, and resources.
Copilot-MCP	✓	✗	✓	?	✗	✗	Supports tools and resources.
Cursor	✗	✗	✓	✗	✗	✗	Supports tools.
TheiaAI/TheiaIDE	✗	✗	✓	?	✗	✗	Supports tools for Agents in Theia AI and the AI-powered Theia IDE
Zed	✗	✓	✗	✗	✗	✗	Prompts appear as slash commands

Agents

The AI glue





Studio

PENDING

agent ▾


Memory

Interrupts 1

New Thread ▾



Pretty ▾



New Thread

Submit your input to run the assistant



Input

Messages

+ Message

View Raw


Required


Submit


Manage Assistants

OUTPUT









```

export function getSimpleAgent(): AgentFlow {
  const agentFlow = new AgentFlow();


  agentFlow.addAgent({
    instructions: `Agent should be used when the user wants to hear a joke.`,
    id: `jokebot`,
    prompt: `You are a bot that tells jokes.`,
  });

  agentFlow.addAgent({
    instructions: `Agent should be used when wanting to turn a sentence into old English style writing.`,
    id: `oldEnglishBot`,
    prompt: `You are a bot that transforms sentences into old English style.`,
  });

  agentFlow.addAgent({
    instructions: `Agent should be used when the user wants to translate something into Spanish.`,
    id: `spanishSpeaker`,
    prompt: `You are a bot that translates sentences into Spanish.`,
  });

  return agentFlow;
}
  
```


How does this relate to IBM i?



AgentFlow

i need help understanding the employees program in the cwd. can you give me a list of the tables it uses and the fields they contain?

  Conversation with fileSystemAgent agent (3 messages)


  Conversation with rpgAgent agent (3 messages)

Sure! Based on the source you mentioned (`employees.pgm.sqlrpgle`) the program directly references **one table**:


Table	Fields referenced in the program
EMPLOYEE	EMPNO, FIRSTNME, LASTNAME, JOB

What this means

- The program declares a cursor that selects those four columns from the EMPLOYEE table.



**Db2 for IBM i,
AI for development**



/help What can you do?

@db2i Chat with the Db2 for i AI assistant

@

GPT 4o



CONTINUE


@


Files

Codebase

Db2i Db2 for i Context Provider

Add more context providers





User input _____

CONTINUE

+

@Db2i tell me about the columns in sample.employee

Autodetect (1) - granite3-dense... @

⌘ ⇣ @codebase

↔ Enter

▽ 2 context items

@ SYSTEM PROMPT system prompt context

@ New job (1)-SAMPLE-employee Schema and table information for employee

Additional context info _____

Response _____

The `sample.employee` table has the following columns:

1. `EMPNO` : A 6-character, not null column with data type CHAR.
2. `FIRSTNAME` : A 12-character, not null column with data type VARCHAR.
3. `MINIT` : A 1-character, not null column with data type CHAR.
4. `LASTNAME` : A 15-character, not null column with data type VARCHAR.
5. `WORKDEPT` : A 3-character, nullable column with data type CHAR and a constraint named 'RED'.
6. `PHONE NO` : A 4-character, nullable column with data type CHAR.
7. `HIRE DATE` : A DATE column with no null values.
8. `JOB` : An 8-character, nullable column with data type CHAR.
9. `EDLEVEL` : A small integer (SMALLINT) column with a scale of 0 and a precision of 4, not null.
10. `SEX` : A 1-character, nullable column with data type CHAR.
11. `BIRTH DATE` : A DATE column with no null values.
12. `SALARY` : A decimal column with a scale of 2 and a precision of 9, nullable.
13. `BONUS` : A decimal column with a scale of 2 and a precision of 9, nullable.
14. `COMM` : A decimal column with a scale of 2 and a precision of 9, nullable.

□ ⌘ ⌘ ⌘

Ask a follow-up

Autodetect (1) - granite3-dense... @

⌘ ⇣ @codebase

↔ Enter

This screenshot shows a Microsoft Visual Studio Code (VS Code) interface with an integrated AI extension. The top bar displays the title '[Extension Development Host] vscode'. The main area contains a code editor with the following SQL query:

```
SELECT E.EMPNO, E.FIRSTNME, E.LASTNAME, Untitled-1
1  SELECT E.EMPNO, E.FIRSTNME, E.LASTNAME, D.DEPTNAME
2  FROM EMPLOYEE E JOIN DEPARTMENT D ON E.WORKDEPT = D.DEPTNO;
3
```

The code editor includes standard VS Code navigation and search tools. Below the code editor is a toolbar with tabs: PROBLEMS, OUTPUT, DEBUG CONSOLE, TERMINAL, PORTS, IBM I (which is selected), GITLENS, and COMMENTS.

A large arrow points from the 'RESULTS' tab in the bottom-left corner towards the code editor, indicating the results of the executed query.

The results are displayed in a table:

EMPNO	FIRSTNME	LASTNAME	DEPTNAME
000010	CHRISTINE	HAAS	SPIFFY COMPUTER SERVICE DIV.
000110	VINCENZO	LUCCHESI	SPIFFY COMPUTER SERVICE DIV.
000120	SEAN	O'CONNELL	SPIFFY COMPUTER SERVICE DIV.
200010	DIAN	HEMMINGER	SPIFFY COMPUTER SERVICE DIV.
200120	GREG	ORLANDO	SPIFFY COMPUTER SERVICE DIV.
000020	MICHAEL	THOMPSON	PLANNING
000030	SALLY	KWAN	INFORMATION CENTER
000130	DELORES	QUINTANA	INFORMATION CENTER
000140	HEATHER	NICHOLLS	INFORMATION CENTER
200140	KIM	NATZ	INFORMATION CENTER
000060	IRVING	STERN	MANUFACTURING SYSTEMS
000150	BRUCE	ADAMSON	MANUFACTURING SYSTEMS
000160	ELIZABETH	PIANKA	MANUFACTURING SYSTEMS
000170	MASATOSHI	YOSHIMURA	MANUFACTURING SYSTEMS
000180	MARILYN	SCOUTTEN	MANUFACTURING SYSTEMS
000190	JAMES	WALKER	MANUFACTURING SYSTEMS
000200	DAVID	BROWN	MANUFACTURING SYSTEMS
000210	WILLIAM	JONES	MANUFACTURING SYSTEMS
000220	JENNIFER	LUTZ	MANUFACTURING SYSTEMS


To the right of the results, there is an AI chat interface. The user asks: '@Db2i how can I find the department name for each employee?'. The AI responds by providing the SQL query and explaining its purpose:


To find the department name for each employee in Db2 for i, you can use a SQL query that joins the EMPLOYEE and DEPARTMENT tables based on the WORKDEPT column. Here's an example query:

```
SELECT E.EMPNO, E.FIRSTNME, E.LASTNAME, D.DEPTNAME
FROM EMPLOYEE E JOIN DEPARTMENT D ON E.WORKDEPT = D.DEPTNO;
```

The AI also provides a follow-up section for asking more questions.

Prompt enrichment in play





← → 🔍 [Extension Development Host] sql

CHAT + ⏷ ⏵ ...

ajshedivy
@db2i write me an SQL statement that calculates the average employee salary in each department

Untitled-1:1-36

Db2 for i
Sure, here is an SQL statement that calculates the average employee salary in each department:

```
SELECT
    e.WORKDEPT AS Department,
    AVG(e.SALARY) AS AverageSalary
FROM
    SAMPLE.EMPLOYEE e
GROUP BY
    e.WORKDEPT;
```

This query groups the employees by their department and calculates the average salary for each department.

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL IBM I ...

RESULTS

DEPARTMENT	AVERAGESALARY
E11	21020
A00	40850
D21	25668.571428571428
C01	29722.5
E01	40175
D11	25147.272727272728

[Extension Development Host] sql

) FROM EMPLOYEE GROUP BY DEPT

CONTINUE

Untitled-2 (1-131)

```
{  
    "JOB_NAME": "683585/QUSER/QZDASOINIT",  
    "USER_NAME": "ASHEDIVY",  
    "REASON_CODE": null,  
    "LOGGED_TIME": "2024-10-21 18:46:15.831000",  
    "LOGGED_SQLSTATE": "42703",  
    "LOGGED_SQLCODE": -206,  
    "MATCHES": 1,  
    "STMTTEXT": "SELECT DEPT, COUNT(*) FROM EMPLOYEE GROUP BY DEPT",  
    "MESSAGE_TEXT": "Column or global variable &1 not found.",  
    "MESSAGE_SECOND_LEVEL_TEXT": "Cause . . . . : &1 was not  
found as a column of table &2 in &3 and was not found as a  
global variable in &2. If the table is *N, &1 is not a column  
of any table or view that can be referenced, or &1 is a special  
register that cannot be set in an atomic compound statement. ✓  
Recovery . . . : Do one of the following and try the request"}  
@Db2i break down this error for me
```

CONSOLE TERMINAL IBM I COMMENTS

variable DEPT not found.,

SQL ERROR LOGGING FACILITY (SELF)

- > **01545 (12)** Correlation without qualification occurred for column &1 to table &2.
- > **42703 (-206)** Column or global variable &1 not found.
 - Statement SELECT DEPT, COUNT(*) FROM EMPLOYEE GROUP BY DEPT
 - Job 683585/QUSER/QZDASOINIT
 - Client Name vscode-db2i 1.6.0
 - Client Program VSCode connector | Version 2.1.4
 - Object QSYS/QZDASRV (*SRVPGM, QZDASQL)
- > **42601 (-104)** Token &1 was not valid. Valid tokens: &2.

Let's take a closer look at the error message and stack trace.

Error Message:

Column or global variable &1 not found.

This is the actual error message, indicating that there's a problem with a column reference (&1) in the SQL statement.

SQL Statement:

SELECT DEPT, COUNT(*) FROM EMPLOYEE GROUP BY DEPT

The SQL statement being executed is a simple **SELECT** statement that groups results by department (DEPT) and counts the number of employees in each department. The error occurs because the column reference 'DEPT' is not properly qualified with a table name, causing the database to raise an error.

Tools for explaining results

CHAT + ⏱ ...

 worksofliam
@db2i how can i use the department name?

 Db2 for i
To use the department name from the `DEPARTMENT` table, you can write a SQL query to select it. Here is an example of how you can retrieve the department name:

```
SELECT DEPTNAME  
FROM SNDBX3.DEPARTMENT;
```

If you need to join it with another table, for example, the `EMPLOYEE` table to get the department name for each employee, you can use a JOIN:

```
SELECT E.EMPNO, E.FIRSTNME, E.LASTNAME, D.DEPTNAME  
FROM SNDBX3.EMPLOYEE E  
JOIN SNDBX3.DEPARTMENT D ON E.WORKDEPT = D.DEPTNO
```

This query retrieves the employee number, first name, last name, and department name for each employee.

⟳ ⏴ ⏵ ⏶

What are some objects related to department?

 worksofliam
@db2i can you please tell me the highest paid employee in each department? #result
▷ Run SQL statement

 Db2 for i Generating

Run SQL statement
Run this statement in your job?

```
SELECT E.WORKDEPT, E.EMPNO, E.FIRSTNME,  
E.LASTNAME, E.SALARY  
FROM SNDBX3.EMPLOYEE E  
JOIN SNDBX3.DEPARTMENT D ON E.WORKDEPT =  
D.DEPTNO  
WHERE E.SALARY = (  
SELECT MAX(SALARY)  
FROM SNDBX3.EMPLOYEE  
WHERE WORKDEPT = E.WORKDEPT  
)  
ORDER BY E.WORKDEPT;
```

Continue Cancel

 worksofliam
@db2i can you please tell me the highest paid employee in each department? #result
▷ Run SQL statement

 Db2 for i
✓ Running statement...
The result set contains information about employees, including their department, employee number, first name, last name, and salary. Here is a summary:

- A00:** Christine Haas, Employee No. 000010, Salary: 52750
- B01:** Dave Thompson, Employee No. 000020, Salary: 41250
- C01:** Sally Kwan, Employee No. 000030, Salary: 38250
- D11:** Hello Stern, Employee No. 000060, Salary: 32250
- D21:** Eva Pulaski, Employee No. 000070, Salary: 1003234
- E11:** John Geyer, Employee No. 000050, Salary: 40175
- E21:** Theodore Spenser, Employee No. 000100, Salary: 26150



codefori.github.io/docs

**Db2 for IBM i,
AI for applications**

 README

 GPL-3.0 license



WatsonX-SDK-Db2-IBMi

WatsonX client SDK for Db2 on IBM i

Usage

Login

```
call watsonx.logoutjob();
call watsonx.setapikeyforjob('x');
call watsonx.setprojectidforjob('y');

-- Should return Y
values watsonx.ShouldGetNewToken();

-- Should return Y
values watsonx.authenticate();

-- Should return N
values watsonx.ShouldGetNewToken();
```



WatsonX-SDK-Db2-IBMi

```
call watsonx.getmodels(); Untitled-1
```

1 call watsonx.getmodels();

PROBLEMS IBM I TERMINAL OUTPUT DEBUG CONSOLE RUN AND DEBUG PORTS COMMENTS ^ X

RESULTS

MODEL_ID	LABEL	PROVIDER	SHORT_DESCRIPTION
codellama/codellama-34b-instruct-hf	codellama-34b-instruct-hf	Code Llama	Code Llama is an AI model built on t...
cross-encoder/ms-marco-minilm-l-12-v2	ms-marco-minilm-l-12-v2	cross-encoder	Used for Information Retrieval: Enc...
google/flan-t5-xl	flan-t5-xl-3b	Google	A pretrained T5 - an encoder-decod...
google/flan-t5-xxl	flan-t5-xxl-11b	Google	flan-t5-xxl is an 11 billion parameter ...
google/flan-ul2	flan-ul2-20b	Google	flan-ul2 is an encoder decoder mod...
ibm/granite-13b-chat-v2	granite-13b-chat-v2	IBM	The Granite model series is a family...
ibm/granite-13b-instruct-v2	granite-13b-instruct-v2	IBM	The Granite model series is a family...
ibm/granite-20b-code-instruct	granite-20b-code-instruct	IBM	The Granite model series is a family...
ibm/granite-20b-multilingual	granite-20b-multilingual	IBM	The Granite model series is a family...
ibm/granite-3-2b-instruct	granite-3-2b-instruct	IBM	The Granite model series is a family...
ibm/granite-3-8b-instruct	granite-3-8b-instruct	IBM	The Granite model series is a family...
ibm/granite-34b-code-instruct	granite-34b-code-instruct	IBM	The Granite model series is a family...
ibm/granite-3b-code-instruct	granite-3b-code-instruct	IBM	The Granite model series is a family...
Loaded 42. End of data.		606512/QUSER/QZDASOINIT	

main* oss74dev Deploy New job (1) + Ln 1, Col 26 Spaces: 2 LF {} MS SQL

The screenshot shows a code editor interface with the following details:

- File:** a.sql
- Content:**

```
1 call watsonx.setapikeyforjob('EIdSiJwJyqC4FGFUBC7zpMrpo7Wggs8kH4a5FrSh-Qt6');
2 call watsonx.setprojectidforjob('f2872353-8bf4-4c8f-969d-04dcee0198ef');
3
4 -- Should return Y
5 values watsonx.authenticate();
```

- Execution Results:** The results are displayed in the "RESULTS" section of the interface.

 - Line 1:** 00001
 - Line 2:** Y (highlighted with a red arrow)
 - Message:** Loaded 1. End of data.
 - User ID:** 606512/QUSER/QZDASOINIT

- Bottom Status Bar:** Shows file status (main*), deployment status (oss74dev), job count (0), and other system information (Ln 5, Col 30 (29 selected), Spaces: 2, LF, MS SQL).

The screenshot shows a code editor interface with the following details:

- Title Bar:** WatsonX-SDK-Db2-IBMi
- File Tab:** a.sql (M)
- Code Editor:** Contains two lines of code:

```
1 values watsonx.generate('Hello world');
2 values watsonx.generate('Hello world', model_id => 'ibm/granite-3-8b-instruct');
```
- Toolbar:** Includes icons for file operations (New, Open, Save, etc.) and a search bar.
- Bottom Navigation:** PROBLEMS, IBM I (underlined), TERMINAL, OUTPUT, DEBUG CONSOLE, RUN AND DEBUG, PORTS, COMMENTS.
- RESULTS Panel:** Shows the output of the code execution:
 - Message: "00001" (highlighted in grey).
 - Text: "I'm a new AI, and I'm here to help you with any questions or tasks you may have. I'm still learning, so please bear with me if I make any mistakes."
 - Text: "Loaded 1. End of data."
 - User ID: 606512/QUSER/QZDASOINIT
- Bottom Status Bar:** Includes icons for main*, oss74dev, Deploy, New job (1), Ln 1, Col 39 (38 selected), Spaces: 2, LF, {}, MS SQL, and a refresh icon.

WatsonX-SDK-Db2-IBMi

a.sql M WATSONX.SQLRPGLE ...

LIAMA > QRPGLESRC > WATSONX.SQLRPGLE > ...

```
8
9  dcl-pr printf int(10) extproc('printf');
10 |   format pointer value options(*string);
11 end-pr;
12
13 inputPrompt = 'Hello world';
14
15 exec sql call watsonx.setapikeyforjob('');
16 exec sql call watsonx.setprojectidforjob('');
17 exec sql select watsonx.authenticate() into :authed from sysibm.sysdummy1;
18 ...
19 exec sql set :output = watsonx.generate(:inputPrompt);
20
21 printf(output);
22
```

PROBLEMS 1 IBM TERMINAL OUTPUT DEBUG CONSOLE RUN AND DEBUG PORTS COMMENTS Call program + ×

Library list: SAMPLE QTEMP QSYSINC LIAMA ILEASIC
Working directory: /home/LIAMA
Commands:
?CALL LIAMA/WATSONX

!

I'm a new AI, and I'm here to help you with any questions or tasks you may have. I'm still learning, so please bear with me if I make any *EVENTF not found in command string. Not fetching errors for LIAMA/WATSONX.

main* oss74dev Deploy New job (1) Ln 16, Col 43 Spaces: 2 LF RPGLE



**RPGLE,
AI for development**