

MobileNig Enterprise

MobileNig Enterprise API Collection is a collection of all endpoints that merchants and developers can take advantage of to build digital services solutions in Nigeria

Authentication

Key is sent with the header of every requests to authenticate user, the key to be used will be specified in each request.

Note



- All requests sent using `test key` will be process as `test` transactions.
- All requests sent using `live key` will be process as `live` transactions.
- Only registered internet protocols (IPs) on your account dashboard will be allowed to access this API endpoints (Visit https://enterprise.mobilenig.com/account/developer/register_ip to add IPs).
- You must have upgraded your account to `STANDARD` user before having accesss to our API endpoints (To upgrade your account, visit https://enterprise.mobilenig.com/account/upgrade/upgrade_account).
- Your API keys can be found on your account dashboard via https://enterprise.mobilenig.com/account/api_keys_and_webhook.
- Transaction ID (trans_id) must not be more than 15 digits

Response Codes

Success

- **200** (*OK*) - Transaction Successful
- **201** (*Created*) - Transaction Successful
- **202** - Transaction is processing

Error

- **PROG001** (*required*) - Programming error on platform. (Should contact MobileNig support)
- **PROG002** (*required*) - Our system is currently under maintenance, kindly contact support!
- **SEC001** (*string*) - Invalid request or key
- **SEC002** (*string*) - User has been suspended
- **SEC003** (*string*) - `public` key is required
- **SEC004** (*string*) - `secret` key is required
- **SEC005** (*string*) - `test` or `live` key is required
- **SEC006** (*string*) - You must be a `standard` user to access this API - kindly upgrade your account.
- **SEC007** (*string*) - Bad Request Method
- **SEC008** (*string*) - Invalid `Content-Type` - Must be `application/json`
- **SEC009** (*string*) - Unauthorized IP

- **SEC009** (*string*) - Unauthorized IP
- **SEC010** (*string*) - Request not available on `test` environment
- **EXC001** - Incomplete parameter(s)
- **EXC002** - Invalid data type
- **EXC003** - Transaction Id already exists
- **EXC004** - Insufficient wallet balance
- **EXC005** - An error occur, please contact MobileNig Customer Support
- **EXC006** - An error occur, service is currently unavailable
- **EXC007** - You are trying to change to your current subscription, kindly leave productCode empty.
- **EXC008** - Amount must not be less than minimum amount.
- **EXC009** - trans_id must not be greater than 15 characters.
- **EXC010** - The data you are looking for cannot be found
- **EXC011** - Service could not be found - Invalid service ID
- **EXC012** - Product code could not be found - Invalid ProductCode
- **EXC013** - Transaction ID could not be found
- **EXC014** - Duplicate order on phone number, please wait for approval
- **EXC015** - Limit reached for airtime purchases today
- **EXC016** - Phone number or Beneficiary must be 11 digits
- **EXC017** - Phone Number or Beneficiary is not a valid number
- **EXC020** - Transaction failed



Http Response Codes

Code	Message
200	OK - Transaction Successful
201	Created - Transaction Successful
202	Transaction is processing
400	Error - Bad request or invalid data type
401	Error - Unauthorised request or invalid key
403	Error - Request not available on test environment
402	Error - Insufficient wallet balance
404	Error - What you're looking for cannot be found
406	Error - The parameter value is not acceptable
409	Error - Already exists. Duplicate transaction
411	Error - Kindly meet the length requirement
417	Error - Transaction failed or cancelled
426	Error - Kindly upgrade your account

Webhook

Webhooks enable MobileNig to keep you informed of any updates related to transactions within your account.

At times, when you send a request to our API endpoint, you may receive a **Processing** response. This occurs when certain requests require additional processing time. In such cases, MobileNig will ensure you stay updated by sending transaction-related notifications.

To set up this notification system, please follow these steps:

1. Add a webhook URL where you'd like to receive updates. You can use this URL:
'https://enterprise.mobilenig.com/account/api_keys_and_webhook' We will send a POST request to this endpoint with JSON data.
2. Be ready to receive responses from the specified endpoint URL.



POST Webhook

Control

GET Unique Account Details



https://enterprise.mobilenig.com/api/v2/control/unique_account_details

To get your unique account details for wallet funding on live environment only. To fund your account on test environment, kindly contact MobileNig support.

NOTE: No parameter is required

AUTHORIZATION Bearer Token

Token	{{public_key}}
-------	----------------

HEADERS

Content-Type	application/json
--------------	------------------

Authorization	Bearer {{public_live_key}}
---------------	----------------------------

GET Check Balance



https://enterprise.mobilenig.com/api/v2/control/balance

To check the current balance on your account, so as to be notified to fund the account if the balance is low.

NOTE: No parameter is required

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}



GET Wallet History



https://enterprise.mobilenig.com/api/v2/control/wallet_history?page=1&per_page=10

Query Params

Name	Type	Description
page	Int	The page you wish to view.
per_page	Int	The number of data you wish to view per page.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

PARAMS

page	1
per_page	10

GET Search Wallet History



https://enterprise.mobilenig.com/api/v2/control/search_wallet_history?trans_id=4348234035

This is to search for the wallet history of a particular transaction with the use of the transaction ID (trans_id).

Query Params



Name	Type	Description
trans_id	String	Transaction Id.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

PARAMS

trans_id 4348234035

GET Services status



https://enterprise.mobilenig.com/api/v2/control/services_status?service_id=AKA

To get a specific service's status, kindly include the parameter below. To get all services, service_id will be **A11**

Query Params

Name	Type	Description
service_id	String	The service ID of the particular service you wish to check.
requestType	String	Service requestType e.g SME

Note: requestType is only required for airtime and data subscription

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_live_key}}

PARAMS

service_id AKA
To get all services, service_id will be **All**



Multichoice Gotv

Service ID: AKA

MultiChoice GOTv provide various options for making payments. Each of them will be described below with provided samples.

POST Validate Customer



https://enterprise.mobilenig.com/api/v2/services/proxy

This returns customer's details

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKA"
customerAccountId	String	Use smart card number.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}



Body raw

```
{
  "service_id": "AKA",
  "customerAccountId": "2005129242"
}
```

POST Get Due Date And Time



https://enterprise.mobilenig.com/api/v2/services/proxy

Returns the details needed to renew subscription

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKA"
customerAccountId	String	Use smart card number.
requestType	String	Hard-coded value "GET_DUE_DATE_AND_AMOUNT"

AUTHORIZATION Bearer Token

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AKA",
  "customerAccountId": "2005129242",
  "requestType": "GET_DUE_DATE_AND_AMOUNT"
}
```



POST Packages



https://enterprise.mobilenig.com/api/v2/services/packages

This returns the available packages for the service

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKA"

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AKA"
}
```

POST Recharge (Renew Subscription)



<https://enterprise.mobilenig.com/api/v2/services/>

Recharge (Renew Subscription)



RENEW option is a regular way of renewing an existing subscription. Outstanding amount for an existing subscription as well as due date for the payment can be retrieved from proxy call - GET_DUE_DATE_AND_AMOUNT. Customer is allowed to pay a different amount than the one retrieved in proxy method call.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKA"
trans_id	Number	Unique reference for the transaction.
customerNumber	String	Retrieved in smart card validation.
smartcardNumber	String	Customer's smartcard number.
customerName	String	Retrieved in smart card validation.
amount	Number	Amount Retrieved from "Get Due Date And Amount" proxy.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{  
  "service_id" : "AKA",  
  "trans_id" : 43034022993,  
  "customerNumber" : 291631845,  
  "smartcardNumber" : 2005129242,  
  "customerName" : "K AKINTIMEHIN",  
  "amount" : 800  
}
```

POST Recharge (Change Subscription)



<https://enterprise.mobilenig.com/api/v2/services/>



CHANGE SUBSCRIPTION option should be used only in case the customer would like to change the current package he/she is subscribed to at the moment. Product codes of new products MUST BE included in request in this case.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKA"
trans_id	Number	Unique reference for the transaction.
productCode	String	To be obtained from packages request.
customerNumber	String	Retrieved in smart card validation.
smartcardNumber	String	Customer's smartcard number.
customerName	String	Retrieved in smart card validation.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id" : "AKA",
  "trans_id" : 3451346098,
  "productCode" : "MBGSM",
  "customerNumber" : 291631845,
  "smartcardNumber" : 2005129242,
  "customerName" : "K AKINTIMEHIN",
  "amount" : 1100
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3451346098

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 3451346098

Multichoice Dstv

Service ID: AKC

MultiChoice DStv provide various options for making payments. Each of them will be described below with provided samples.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate Customer



https://enterprise.mobilenig.com/api/v2/services/proxy

This returns the details of the account holder



Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKC"
customerAccountId	String	Use smart card number.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AKC",
  "customerAccountId": "2005129242"
}
```

POST Get Due Date And Time



https://enterprise.mobilenig.com/api/v2/services/proxy

This returns the details needed to renew package

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKC"
customerAccountId	String	Use smart card number.
requestType	String	Hard-coded value "GET_DUE_DATE_AND_AMOUNT"

AUTHORIZATION Bearer Token



Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AKC",
  "customerAccountId": "2005129242",
  "requestType": "GET_DUE_DATE_AND_AMOUNT"
}
```

POST Packages



https://enterprise.mobilenig.com/api/v2/services/packages

This returns the available packages for the service

Body Params

Name	Type	Description
------	------	-------------

service_id	String	Hard-coded value "AKC"
------------	--------	------------------------

AUTHORIZATION Bearer Token

Token	{{public_key}}
-------	----------------

HEADERS

Content-Type	application/json
Authorization	Bearer {{public_key}}

Body	raw
------	-----



```
{
  "service_id": "AKC"
}
```

POST Recharge (Renew Subscription)

https://enterprise.mobilenig.com/api/v2/services/

RENEW option is a regular way of renewing an existing subscription. Outstanding amount for an existing subscription as well as due date for the payment can be retrieved from proxy call - GET_DUE_DATE_AND_AMOUNT. Customer is allowed to pay a different amount than the one retrieved in proxy method call.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKC".
trans_id	Number	Unique reference for the transaction.
customerNumber	String	Retrieved in smart card validation.
smartcardNumber	String	Customer's smartcard number.
customerName	String	Retrieved in smart card validation.
amount	Number	Amount Retrieved from "Get Due Date And Amount" proxy.

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AKC",
  "trans_id": 4343403343,
  "customerNumber": 491449315,
  "smartcardNumber": 3838348384,
  "customerName": "K AKINTIMEHIN",
  "amount": 800
}
```

POST Recharge (Change Subscription)



https://enterprise.mobilenig.com/api/v2/services/

CHANGE SUBSCRIPTION option should be used only in case the customer would like to change the current product he/she is subscribed to at the moment. Product codes of new products MUST BE included in request in this case.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKC".
trans_id	Number	Unique reference for the transaction.
productCode	String	To be obtained from packages request.
customerNumber	String	Retrieved in smart card validation.
smartcardNumber	String	Customer's smartcard number.
customerName	String	Retrieved in smart card validation.

amount	Number	Total transaction amount
--------	--------	--------------------------

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw



```
{
  "service_id": "AKC",
  "trans_id": 23455667954,
  "productCode": "MBDYB",
  "customerNumber": 275953782,
  "smartcardNumber": 4131953321,
  "customerName": "E INI OBONG BASSEY",
  "amount": 3500
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=23455667954

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Content-Type: application/json

Authorization: Bearer {{secret_key}}

PARAMS

trans_id: 23455667954

Startimes

Service ID: AKB

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

It is used to validate the customer account.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKB".
customerAccountId	String	Use smart card number.

AUTHORIZATION: Bearer Token

Token: {{public_key}}

HEADERS

Content-Type: application/json

Authorization: Bearer {{public_key}}

Body: raw

```
{
  "service_id": "AKB",
```

```
{  
  "customerAccountId": "02146131786"  
}
```

POST Packages



https://enterprise.mobilenig.com/api/v2/services/packages

This returns the available packages for the service

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKB".



AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{  
  "service_id": "AKB"  
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AKB".
trans_id	Number	Unique reference for the transaction.
productCode	String	To be obtained from packages request.
smartcardNumber	String	Customer's smartcard number.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token



Token `{{secret_key}}`

HEADERS

Content-Type `application/json`

Authorization `Bearer {{secret_key}}`

Body raw

```
{
  "service_id": "AKB",
  "trans_id": 347875487,
  "productCode": "MBSN",
  "smartcardNumber": "02027336692",
  "amount": 1500
}
```

GET Query



`https://enterprise.mobilenig.com/api/v2/services/query?trans_id=347875487`

Query Params

Name	Type	Description

trans_id	Number	The trans_id used to recharge.
----------	--------	--------------------------------

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 347875487



Smile Airtime

Service ID: ALA

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate the customer:

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ALA".
customerAccountId	String	Customer account ID.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{public_key}}

Body raw

```
{
  "service_id": "ALA",
  "customerAccountId": "1402000567"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "SMA".
trans_id	Number	Unique reference for the transaction.
productCode	String	To be obtained from packages request.
customerPhoneNumber	String	Customer's phone number.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token{{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{secret_key}}

Body raw

```
{
  "service_id": "ALA",
  "trans_id": 9290320934,
  "customerAccountId": 1402000567,
  "amount": 900
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=9290320934



Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 9290320934

Waec

Service ID: AJA

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Price



https://enterprise.mobilenig.com/api/v2/services/packages

A single proxy operation is available for this service. It is used to fetch the current pin price.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AJA".



AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AJA"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AJA".
trans_id	Number	Unique reference for the transaction.
quantity	Number	Total number of pins.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}



HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AJA",
  "trans_id": 3284322345,
  "quantity": 2,
  "amount": 7200
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3284322345

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 3284322345



Neco

Service ID: AJC

POST Price



https://enterprise.mobilenig.com/api/v2/services/packages

This returns the price of the service

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AJC".

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AJC"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params



Name	Type	Description
service_id	String	Hard-coded value "AJC".
trans_id	Number	Unique reference for the transaction.
quantity	Number	Total number of pins.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AJC",
  "trans_id": 328432345,
  "quantity": 3,
  "amount": 2400
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=328432345

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}



HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 328432345

Jamb

Service ID: AJB

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AJB".
confirmationCode	String	JAMB Confirmation Code.
serviceType	String	DE or UTME.

AUTHORIZATION Bearer Token

Token <token>

HEADERS



Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AJB",
  "confirmationCode": "9678528342",
  "requestType": "GET_CANDIDATE_NAMES_FOR_VENDING",
  "serviceType": "DE"
}
```

POST Price

https://enterprise.mobilenig.com/api/v2/services/packages

This returns the price of the service

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AJB".

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AJB"
}
```



POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AJB".
trans_id	Number	Unique reference for the transaction.
confirmationCode	String	JAMB Confirmation Code.
phoneNumber	String	Phone Number received in the "Validation" method response.
productCode	String	Received from "Price" method response.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{seret_key}}

Body raw

```
{  "service_id": "AJB",  "trans_id": 24534234343,  "confirmationCode": "873478473784",  "phoneNumber": "0804565438",  "productCode": "UTME",  "amount": 4000}
```

GET Query

🔒

https://enterprise.mobilenig.com/api/v2/services/query?trans_id=134567287

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token

{{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{secret_key}}

PARAMS

trans_id

134567287

Spectranet

Service ID: ALB

POST Packages



https://enterprise.mobilenig.com/api/v2/services/packages

A single proxy operation is available for this service. It is used to fetch the available pin denominations.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ALB".



AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "ALB"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ALB".
trans_id	Number	Unique reference for the transaction.
productCode	String	productCode received in the "Packages" method response.
quantity	Number	Total number of pins.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "ALB",
  "trans_id": 83924938493,
  "productCode": "MBSP0",
  "quantity": 1,
  "amount": 500
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=83924938493

Query Params

Name	Type	Description

trans_id	Number	The trans_id used to recharge.
----------	--------	--------------------------------

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 83924938493



Ikeja Electricity Bills

Service ID: AMB

This service covers paying bills for Ikeja Electric customers

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate customer.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AMB".
customerAccountId	String	Use customer number

AUTHORIZATION Bearer Token

Token {{pubic_key}}

HEADERS

Content-Type	application/json
Authorization	Bearer {{public_key}}

Body raw

```
{
  "service_id": "AMB",
  "customerAccountId": "0100388278"
}
```



POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AMB".
trans_id	Number	Unique reference for the transaction.
accountNumber	String	Account number. Use the account number received through customer validation response.
amount	Number	Total transaction amount.
phoneNumber	String	Customer's phone number. 11 digits.
email	String	Customer's email
customerName	String	Customer name received through customer validation response.
customerDtNumber	String	Customer DT number received through customer validation response.
customerAddress	String	Customer address received through customer validation response.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw



```
{
  "service_id": "AMB",
  "trans_id": 38382838323,
  "accountNumber": "0100388278",
  "amount": 100,
  "phoneNumber": "08012345678",
  "email": "ikeja@test.com",
  "customerName": "WAHAB IBRAHIM",
  "customerAddress": "10 OSAHON CRES ROBIYAN RD LAGOS",
  "customerAccountType": "NMD",
  "customerDtNumber": "1000290538",
  "contactType": "LANDLORD"
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=38382838323

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{secret_key}}

PARAMS

trans_id38382838323

Ikeja Electricity Token Purchase

Service ID: AMA



AUTHORIZATION Bearer Token

Token{{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used validate meter number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AMA".
customerAccountId	String	Use meter number

AUTHORIZATION Bearer Token

Token{{public_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{public_key}}

Body raw

```
{
  "service_id": "AMA",
  "customerAccountId": "04042404048"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/



Body Params

Name	Type	Description
service_id	String	Hard-coded value "AMA".
trans_id	Number	Unique reference for the transaction.
meterNumber	String	Meter number. Use the meter number received through customer validation response.
amount	Number	Total transaction amount.
phoneNumber	String	Customer's phone number. 11 digits.
email	String	Customer's email
customerName	String	Customer name received through customer validation response.
customerDtNumber	String	Customer DT number received through customer validation response.
customerAddress	String	Customer address received through customer validation response.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{secret_key}}

Body raw

```
{
  "service_id": "AMA",
  "trans_id": 83847389834,
  "meterNumber": "04042404048",
  "amount": 100,
  "phoneNumber": "08012345678",
  "email": "ikeja@test.com",
  "customerName": "TESTMETER1",
  "customerAddress": "ABULE - EGBA BU ABULE",
  "customerAccountType": "PRIME",
  "customerDtNumber": "007903312",
  "contactType": "TENANT"
}
```

GET Query

https://enterprise.mobilenig.com/api/v2/services/query?trans_id=83847389834

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token

{{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{secret_key}}

PARAMS

trans_id

83847389834

Eko Electricity Prepaid

Service ID: ANA

This service covers purchasing prepaid tokens Eko EDC customers. Maximum purchase amount is 100000, minimum amount is 1000 in case of no outstanding debt.

NOTE: In most cases the initial response will be a success response stating that the transaction is still pending (success Code: 202). In order to resolve the issue it is required to call the Query method. The transaction should be resolved within 2 minutes.



POST Validate

🔒

https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate the meter number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ANA".
customerAccountId	String	Use meter number

AUTHORIZATION Bearer Token

Token

{{public_key}}

HEADERS

Content-Type

application/json

Authorization

Bearer {{public_key}}

Body

raw

```
{
  "service_id": "ANA",
  "customerAccountId": "07080259851"
}
```

POST Recharge



<https://enterprise.mobilenig.com/api/v2/services/>

Body Params



Name	Type	Description
service_id	String	Hard-coded value "ANA".
trans_id	Number	Unique reference for the transaction.
customerAddress	String	Customer address. Use the customer address received through customer validation response.
customerDistrict	String	Customer district. Use the customer district received through customer validation response.
customerName	String	Customer name. Use the customer name received through customer validation response.
meterNumber	String	Meter number.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

```
{
  "service_id": "ANA",
  "trans_id": 238797492934,
  "customerAddress": "ODUDU STREET AGRIC, 14, SATTELITE",
  "customerDistrict": "FESTAC",
  "customerName": "OKIKA BENSON",
  "meterNumber": "07080259851",
  "amount": 100
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=238797492934

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 238797492934

Eko Electricity Postpaid

Service ID: ANB

This service covers paying bills for postpaid Eko EDC customers. Maximum purchase amount is 100000.

NOTE: In most cases the initial response will be a success response stating that the transaction is still pending (success Code: 202). In order to resolve the issue it is required to call the Query method. The transaction should be resolved within 2 minutes.

POST Validate

🔒

https://enterprise.mobilenig.com/api/v2/services/proxy

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ANB".
customerAccountId	String	Use customer reference



AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "ANB",
  "customerAccountId": "101512454501"
}
```

POST Recharge

🔒

https://enterprise.mobilenig.com/api/v2/services/

Body Params

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ANB".
trans_id	Number	Unique reference for the transaction.
customerReference	String	Account number of the customer.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}



HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "ANB",
  "trans_id": 437434474734,
  "customerReference": "101512454501",
  "amount": 100
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=437434474734

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 437434474734



Abuja Electricity Prepaid

Service ID: AHB

This service covers purchasing prepaid tokens for Abuja Electricity customers.

Total transaction amount must be at least #500.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate meter number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AHB".
customerAccountId	String	Use customer reference

AUTHORIZATION Bearer Token

Token{{public_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{public_key}}

Body raw

```
{
  "service_id": "AHB",
  "customerAccountId": "721045140"
}
```

POST Recharge

https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AHB".
trans_id	Number	Unique reference for the transaction.
customerReference	String	Account number of the customer.
amount	Number	Total transaction amount.
customerName	String	Customer name obtained from response during customer validation.
customerAddress	String	Customer address obtained from response during customer validation.

AUTHORIZATION Bearer Token

Token{{secret_key}}

HEADERS

Content-Type	application/json
Authorization	Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AHB",
  "trans_id": 3647824372323,
  "customerReference": "42328955339",
  "amount": 900,
  "customerName": "ENGR. ABENI",
  "customerAddress": "NYSC AREA 5 Und St. Garki 80"
}
```



GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3647824372323

Body Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token	{{secret_key}}
-------	----------------

HEADERS

Content-Type	application/json
Authorization	Bearer {{secret_key}}

PARAMS

trans_id	3647824372323
----------	---------------

Abuja Electricity Postpaid

Service ID: AHA

This service covers paying bills for postpaid Abuja Electricity customers.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate account number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AHA".
customerAccountId	String	Use customer reference

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AHA",
  "customerAccountId": "721045140"
```

```
{
  "customerAccountID": "21045140"
}
```

POST Recharge

🔒

https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AHA".
trans_id	Number	Unique reference for the transaction.
customerReference	String	Account number of the customer.
amount	Number	Total transaction amount.
customerName	String	Customer name obtained from response during customer validation.
customerAddress	String	Customer address obtained from response during customer validation.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AHA",
  "trans_id": 92392032123,
  "customerReference": "38985884389489",
  "amount": 100,
  "customerName": "ENGR. ABENI",
}
```

```
"customerAddress": "NYSC AREA 5 Und St. Garki 80"
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=92392032123

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 92392032123

Kaduna Electricity Prepaid

Service ID: AGB

This service covers purchasing prepaid tokens for Kaduna customers.

NOTE: In most cases the initial response will be a success response stating that the transaction is still pending (success Code: 202). In order to resolve the issue it is required to call the Query method. The transaction should be resolved within 2 minutes.



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate meter number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AGB".
customerAccountId	String	Use meter number

AUTHORIZATION Bearer Token



Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AGB",
  "customerAccountId": "04171254347"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Query

Name	Type	Description
service_id	String	Hard-coded value "AGB".
trans_id	Number	Unique reference for the transaction.
meterNumber	String	Account number of the customer.
amount	Number	Total transaction amount.
customerName	String	Customer name obtained from response during customer validation.
customerAddress	String	Customer address obtained from response during customer validation.
tariff	String	Tariff obtained from the response during customer validation.
customerMobileNumber	String	Customer's mobile number. 11 digits.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AGB",
  "trans_id": 8793242392,
  "meterNumber": "04171254347",
  "amount": 200,
  "customerName": "DEPT. FORESTRY FED",
  "customerAddress": "AGRIC QRTS OPP NAF. BASE MANDO KADUNA",
  "tariff": "R2S",
  "customerMobileNumber": "08000000000"
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3453473843

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 3453473843

Kaduna Electricity Postpaid

Service ID: AGA

This service covers paying bills for postpaid Kaduna customers.

NOTE: In most cases the initial response will be a success response stating that the transaction is still pending (success Code: 202). In order to resolve the issue it is required to call the Query method. The transaction should be resolved within 2 minutes.

AUTHORIZATION Bearer Token

Token {{public_key}}



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate account number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AGA".
customerAccountId	String	Use meter number

AUTHORIZATION Bearer Token



Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "AGA",
  "customerAccountId": "1173761"
}
```



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AGA".
trans_id	Number	Unique reference for the transaction.
meterNumber	String	Account number of the customer.
amount	Number	Total transaction amount.
customerName	String	Customer name obtained from response during customer validation.
customerAddress	String	Customer address obtained from response during customer validation.
tariff	String	Tariff obtained from the response during customer validation.
customerMobileNumber	String	Customer's mobile number. 11 digits.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AGA",
  "trans_id": 23456876543,
  "meterNumber": "1173761",
  "amount": 1000,
  "customerName": "IBRAHIM ADAMU",
  "customerAddress": "GUNTU LAYI",
  "customerMobileNumber": "08000000000",
  "tariff": " 29.81 N/KWh : : : "
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=23456876543

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 23456876543

Ibadan Electricity Prepaid

Service ID: AEA

This service covers purchasing prepaid tokens for Ibadan customers.

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate the meter number.

Body Params

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AEA".
customerAccountId	String	Use customer reference.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Authorization Bearer {{public_key}}

Content-Type application/json



Body raw

```
{
  "service_id": "AEA",
  "customerAccountId": "121501004001"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AEA".
trans_id	Number	Unique reference for the transaction.
customerName	String	Concatenated first and last name from customer validation step.
customerReference	String	Meter number.
thirdPartyCode	String	Value received from customer validation step.
serviceBand	String	Value received from customer validation step.
amount	Number	Total transaction amount.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AEA",
  "trans_id": 3778865445,
  "customerName": "TAIRU SULAIMON TAIRU SULAIMON",
  "customerReference": "1234567809",
  "customerType": "PREPAID",
  "thirdPartyCode": "ONLI",
  "serviceBand": "D8H",
  "amount": 500
}
```



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3778865445

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}



PARAMS

trans_id 3778865445

Ibadan Electricity Postpaid

Service ID: AEB

This service covers paying bills for postpaid Ibadan customers.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate the account number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AEB".
customerAccountId	String	Use customer reference.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}



Body raw

```
{
  "service_id": "AEB",
  "customerAccountId": "121501004001"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AEB".
trans_id	Number	Unique reference for the transaction.
customerName	String	Concatenated first and last name from customer validation step.
customerReference	String	Meter number.
thirdPartyCode	String	Value received from customer validation step.
serviceBand	String	Value received from customer validation step.
amount	Number	Total transaction amount.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AEB",
  "trans_id": 3453485893,
  "customerReference": "121501004001",
  "customerType": "POSTPAID",
  "customerName": "UNION PRODUT LTD.",
  "thirdPartyCode": "AKRN",
  "serviceBand": "D8H",
  "amount": 250
}
```



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3453485893

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}



PARAMS

trans_id 3453485893

Kano Electricity Distribution Prepaid

Service ID: AFA

This service covers purchasing prepaid tokens for Kano Electricity Distribution Company customers. Maximum purchase amount is 250000

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate customer:

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AFA".
customerAccountId	String	Use customer reference

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}



Body raw

```
{
  "service_id": "AFA",
  "customerAccountId": "321009000401"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AFA".
trans_id	Number	Unique reference for the transaction.
customerReference	String	Customer tariff code. Provided in during customer validation.
tariffCode	String	Account number of the customer.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw



```
{
  "service_id": "AFA",
  "trans_id": 89234423943,
  "customerReference": "321009000401",
  "tariffCode": "A7",
  "amount": 250
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=89234423943

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id89234423943

Kano Electricity Distribution Postpaid

Service ID: AFB

This service covers paying bills for postpaid Kano Electricity Distribution Company customers. Maximum purchase amount is 250000.

AUTHORIZATION Bearer Token



Token{{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate customer:

Body Params

Name	Type	Description
service_id	String	Hard-coded value "AFB".
customerAccountId	String	Use customer reference

AUTHORIZATION Bearer Token

Token{{public_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{public_key}}

Body raw

```
{
  "service_id": "AFB",
  "customerAccountId": "101512454501"
}
```

POST Recharge



<https://enterprise.mobilenig.com/api/v2/services/>

Body Params



Name	Type	Description
service_id	String	Hard-coded value "AFB".
trans_id	Number	Unique reference for the transaction.
customerReference	String	Customer tariff code. Provided in during customer validation.
tariffCode	String	Account number of the customer.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "AFB",
  "trans_id": 832093920042,
  "customerReference": "321009000401",
  "tariffCode": "A7",
}
```

```
"amount": 250
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=832093920042

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 832093920042

Port-Harcourt Prepaid

Service ID: ADB

This service covers purchasing prepaid tokens for Port Harcourt customers.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate meter number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ADB".
customerAccountId	String	Use customer number.

AUTHORIZATION Bearer Token



Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "ADB",
  "customerAccountId": "0124000161297"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ADB".
trans_id	Number	Unique reference for the transaction.
customerNumber	String	Meter number.
amount	Number	Total transaction amount.
customerDetails	String	Customer details obtained from response during customer validation.
customerEmail	String	Customer email provided by customer.
customerPhone	String	Customer's phone number provided by customer. 11 digits.
referenceId	String	Reference ID obtained from response during customer validation.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "ADB",
  "trans_id": 3434548736763,
  "customerNumber": "0124000161297",
  "amount": 100,
  "customerDetails": "CUSTOMER Name =>JOSEPH NWANKWO | ACCOUNT NO =>862133575901 | MOBILE NO",
  "customerEmail": "test@test.com",
  "customerPhone": "08000000000",
  "referenceId": "862133575901"
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3434548736763

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 3434548736763

Port-Harcourt Postpaid

Service ID: ADA

This service covers paying bills for postpaid Port Harcourt customers.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to validate meter number.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ADA".
customerAccountId	String	Use customer number.

AUTHORIZATION Bearer Token

Token {{public_key}}



HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "ADA",
  "customerAccountId": "841272045101"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body params

Name	Type	Description
service_id	String	Hard-coded value "ADA".
trans_id	Number	Unique reference for the transaction.
customerNumber	String	Meter number.
amount	Number	Total transaction amount.
customerDetails	String	Customer details obtained from response during customer validation.
customerEmail	String	Customer email provided by customer.
customerPhone	String	Customer's phone number provided by customer. 11 digits.
referenceId	String	Reference ID obtained from response during customer validation.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "ADA",
  "trans_id": 3434734834,
  "customerNumber": "0124000161297",
  "amount": 100,
  "customerDetails": "CUSTOMER Name =>JOSEPH NWANKWO | ACCOUNT NO =>862133575901 | MOBILE NO",
  "customerEmail": "test@test.com",
  "customerPhone": "08000000000",
  "referenceId": "862133575901"
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=3434734834

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 3434734834

Jos Electricity Prepaid

Service ID: ACB

This service covers purchasing prepaid tokens for JOS customers.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to fetch account information.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ACB".
customerAccountId	String	Use customer number.

AUTHORIZATION Bearer Token

Token {{public_key}}



HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "ACB",
  "customerAccountId": "111111111111"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ACB".
trans_id	Number	Unique reference for the transaction.
accessCode	String	Access code from customer validation.
customerPhoneNumber	String	Customer phone number.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token



Token `{{secret_key}}`

HEADERS

Content-Type `application/json`

Authorization `Bearer {{secret_key}}`

Body raw

```
{
  "service_id": "ACB",
  "trans_id": 43574358943,
  "accessCode": "5456035842879885",
  "customerPhoneNumber": "08000000000",
  "amount": 100
}
```

GET Query



`https://enterprise.mobilenig.com/api/v2/services/query?trans_id=43574358943`

Query Params

Name	Type	Description
------	------	-------------

trans_id	Number	The trans_id used to recharge.
----------	--------	--------------------------------

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 43574358943



Jos Electricity Postpaid

Service ID: ACA

This service covers purchasing postpaid tokens for JOS customers.

AUTHORIZATION Bearer Token

Token {{public_key}}

POST Validate



https://enterprise.mobilenig.com/api/v2/services/proxy

A single proxy operation is available for this service. It is used to fetch account information.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ACA".
customerAccountId	String	Use customer number.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "ACA",
  "customerAccountId": "0101100000133"
}
```

POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "ACA".
trans_id	Number	Unique reference for the transaction.
accessCode	String	Access code from customer validation.
customerPhoneNumber	String	Customer phone number.
amount	Number	Total transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{secret_key}}

Bodyraw

```
{
  "service_id": "ACA",
  "trans_id": 347383383,
  "accessCode": "8699686188451259",
  "customerPhoneNumber": "08000000000",
  "amount": 100
}
```

GETQuery

🔒

https://enterprise.mobilenig.com/api/v2/services/query?trans_id=347383383

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATIONBearer Token

Token{{secret_key}}

HEADERS

Content-Typeapplication/json

AuthorizationBearer {{secret_key}}

PARAMS

trans_id347383383

Airtime Standard

Standard is powered in affiliation, so it's a bit more expensive. But the VTU is the same with Premium

GET Get Status



`https://enterprise.mobilenig.com/api/v2/control/services_status?service_id=BAD&requestType=STANDARD`

Use to get the availability of the service.

Query Params



Name	Type	Description
service_id	String	The service ID of the particular service you wish to check.
requestType	String	Service requestType e.g <code>STANDARD</code>

Note: Use other network `service_id` value to check their status

AUTHORIZATION Bearer Token

Token `{{public_live_key}}`

HEADERS

Content-Type `application/json`

Authorization `Bearer {{public_live_key}}`

PARAMS

service_id `BAD`

requestType `STANDARD`

POST MtnVtu



Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAD"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value " STANDARD "
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAD",
  "trans_id": 49304904903,
  "service_type": "STANDARD",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

POST 9mobileVtu



Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAC"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value " STANDARD "
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAC",
  "trans_id": 9876543345678,
  "service_type": "STANDARD",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

POST GloVtu



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAB"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value " STANDARD "
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAB",
  "trans_id": 34832403388,
  "service_type": "STANDARD",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

POST AirtelVtu



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAA".
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value " STANDARD "
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAA",
  "trans_id": 2345665438,
  "service_type": "STANDARD",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=2345665438

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 2345665438



Airtime Premium

Premium is powered by MobileNig, so it is Discounted.

GET Get Status



https://enterprise.mobilenig.com/api/v2/control/services_status?service_id=BAD&requestType=PREMIUM

Use to get the availability of the service.

Query Params

Name	Type	Description
service_id	String	The service ID of the particular service you wish to check.
requestType	String	Service requestType e.g PREMIUM

Note: Use other network `service_id` value to check their status

AUTHORIZATION Bearer Token

Token {{public_live_key}}

HEADERS

Content-Type	application/json
Authorization	Bearer {{public_live_key}}

PARAMS

service_id	BAD
requestType	PREMIUM

POST Mtn Premium



https://enterprise.mobilenig.com/api/v2/services/

Premium is powered by MobileNig, so it is Discounted.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAD"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value " PREMIUM "
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token

Token	{{secret_key}}
-------	----------------

HEADERS

Content-Type	application/json
Authorization	Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAD",
  "trans_id": 4340490202,
  "service_type": "PREMIUM",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

POST Mtn Awuf



https://enterprise.mobilenig.com/api/v2/services/

MTN AWUF is an MTN offer that gives 400% airtime bonus on every recharge from N100 & above OR 275% on every recharge between N1 & N99.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAD"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value "AWUF"
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAD",
  "trans_id": 343425724734,
  "service_type": "AWUF",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

POST 9mobile Premium



https://enterprise.mobilenig.com/api/v2/services/



Premium is powered by MobileNig, so it is Discounted.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAC"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value " PREMIUM "
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAC",
  "trans_id": 932302394232,

  "service_type": "PREMIUM",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

POST Glo Premium



https://enterprise.mobilenig.com/api/v2/services/

Premium is powered by MobileNig, so it is Discounted.



Body Params

Name	Type	Description
service_id	String	Hard-coded value "BAB"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value " <code>PREMIUM</code> "
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAB",
  "trans_id": 89382929302,
  "service_type": "PRFMTIUM"
}
```

```
"phoneNumber": "08000000000",
```

```
"amount": 100
```

```
}
```

POST Airtel Premium



https://enterprise.mobilenig.com/api/v2/services/

Premium is powered by MobileNig, so it is Discounted.

Body Params



Name	Type	Description
service_id	String	Hard-coded value "BAA"
trans_id	Number	Unique reference for the transaction.
service_type	String	Hard-coded value "PREMIUM"
phoneNumber	String	Customer's phone number.
amount	Number	Transaction amount.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BAA",
  "trans_id": "685230320359",
  "service_type": "PREMIUM",
  "phoneNumber": "08000000000",
  "amount": 100
}
```

```
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=343425724734

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 343425724734

Mtn Data

Service ID: BCA

This service requires get status and get prices calls, the former is to get the availability of the service while the later is to get details for each value of data.

AUTHORIZATION Bearer Token

Token {{public_key}}

GET Get Status



https://enterprise.mobilenig.com/api/v2/control/services_status?service_id=BCA&requestType=SME

Use to get the availability of the service

Query Params

Name	Type	Description
service_id	String	Hard-coded value " BCA "
requestType	String	Hard-coded value " SME "

For Mtn Gifting, the requestType will be " GIFTING " this will return the availability of the service.

AUTHORIZATION Bearer Token



Token {{public_live_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_live_key}}

PARAMS

service_id BCA

requestType SME

POST Prices



https://enterprise.mobilenig.com/api/v2/services/packages

Used to get details for each value of data.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCA".
requestType	String	Hard-coded value "SME"

Note: For Mtn Gifting, the `requestType` will be " `GIFTING` " this will return the details for each value of data.

AUTHORIZATION Bearer Token

Token `{{public_key}}`

HEADERS

Content-Type `application/json`

Authorization `Bearer {{public_key}}`

Body raw



```
{
  "service_id": "BCA",
  "requestType": "SME"
}
```

POST Recharge



`https://enterprise.mobilenig.com/api/v2/services/`

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCA".
service_type	String	Hard-coded value "SME"
beneficiary	String	Beneficiary phone number
trans_id	Number	The trans_id used to recharge.
code	String	Code value from <code>get prices</code> call
amount	Number	Transaction cost from <code>get prices</code> call

Note: For Mtn Gifting, `service_type` will be " `GIFTING` ".

AUTHORIZATION Bearer Token

Token

{{secret_key}}

HEADERS

Content-Type

application/json

Authorization

Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BCA",
  "service_type": "SME",
  "beneficiary": "09039636737",
  "trans_id": "3293902390",
  "code": "MBMS500",
  "amount": "350"
}
```



GET Query

https://enterprise.mobilenig.com/api/v2/services/query?trans_id=2348293792

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token

{{secret_key}}

HEADERS

Content-Type

application/json

Authorization

Bearer {{secret_key}}

PARAMS

trans_id

2348293792

9mobile Data

Service ID: BCB

This service requires get status and get prices calls, the former is to get the availability of the service while the later is to get details for each value of data.

AUTHORIZATION Bearer Token



Token {{public_key}}

GET Get Status



https://enterprise.mobilenig.com/api/v2/control/services_status?service_id=BCB&requestType=SME

Use to get the availability of the service

Query Params

Name	Type	Description
service_id	String	Hard-coded value " BCB "
requestType	String	Hard-coded value " SME "

Note: For 9mobile Gifting, the `requestType` will be " `GIFTING` " this will return the availability of the service.

AUTHORIZATION Bearer Token

Token {{public_live_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_live_key}}

PARAMS

service_id	BCB
requestType	SME

POST Prices



https://enterprise.mobilenig.com/api/v2/services/packages

Used to get details for each value of data.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCB".
requestType	String	Hard-coded value "GIFTING"

Note: For 9mobileSme, the requestType will be " SME " this will return the details for each value of data.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "BCB",
  "requestType": "SME"
}
```

POST Recharge



Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCB".
service_type	String	Hard-coded value "SME"
beneficiary	String	Beneficiary phone number
trans_id	Number	The trans_id used to recharge.
code	String	Code value from get prices call
amount	Number	Transaction cost from get prices call



Note: For 9mobile Gifting, `service_type` will be " `GIFTING` ".

AUTHORIZATION Bearer Token

Token `{{secret_key}}`

HEADERS

Content-Type `application/json`

Authorization `Bearer {{secret_key}}`

Body raw

```
{
  "service_id": "BCB",
  "service_type": "SME",
  "beneficiary": "09039636737",
  "trans_id": "920920323",
  "code": "MBMS300",
  "amount": "46"
}
```



Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}



PARAMS

trans_id 920920323

Glo Data

Service ID: BCC

This service requires get status and get prices calls, the former is to get the availability of the service while the later is to get details for each value of data.

AUTHORIZATION Bearer Token

Token {{public_key}}

GET Get Status



https://enterprise.mobilenig.com/api/v2/control/services_status?service_id=BCC&requestType=SME

Use to get the availability of the service

Query Params

Query Params

Name	Type	Description
service_id	String	Hard-coded value " BCC "
requestType	String	Hard-coded value " SME "

AUTHORIZATION Bearer Token

Token {{public_live_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_live_key}}



PARAMS

service_id BCC

requestType SME

POST Prices



https://enterprise.mobilenig.com/api/v2/services/packages

Used to get details for each value of data.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCC".
requestType	String	Hard-coded value "SME"

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

HEADERS

Content-Type	application/json
Authorization	Bearer {{public_key}}

Body raw

```
{
  "service_id": "BCC",
  "requestType": "SME"
}
```



POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCC".
service_type	String	Hard-coded value "SME"
beneficiary	String	Beneficiary phone number
trans_id	Number	The trans_id used to recharge.
code	String	Code value from get prices call
amount	Number	Transaction cost from get prices call



AUTHORIZATION Bearer Token

Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

Body raw

```
{
  "service_id": "BCC",
  "service_type": "SME",
  "beneficiary": "09059689599",
  "trans_id": "594390897544",
  "code": "MBGG200",
  "amount": "50"
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=594390897544

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token

Token {{secret_key}}



HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 594390897544

Airtel Data

Service ID: BCD

This service requires get status and get prices calls, the former is to get the availability of the service while the later is to get details for each value of data.

AUTHORIZATION Bearer Token

Token {{public_key}}

GET Get Status



https://enterprise.mobilenig.com/api/v2/control/services_status?service_id=BCD&requestType=SME

Use to get the availability of the service

Query Params

Name	Type	Description
service_id	String	Hard-coded value " BCD "
requestType	String	Hard-coded value " SME "

Note: For Airtel Gifting, the `requestType` will be " GIFTING " this will return the availability of the service.

AUTHORIZATION Bearer Token

Token `{{public_live_key}}`



HEADERS

Content-Type `application/json`

Authorization `Bearer {{public_live_key}}`

PARAMS

`service_id` BCD

`requestType` SME

POST Prices



<https://enterprise.mobilenig.com/api/v2/services/packages>

Used to get details for each value of data.

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCD".
requestType	String	Hard-coded value "GIFTING"

Note: For AirtelSme, the `requestType` will be " SME " this will return the details for each value of data.

AUTHORIZATION Bearer Token

Token {{public_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{public_key}}

Body raw

```
{
  "service_id": "BCD",
  "requestType": "SME"
}
```



POST Recharge



https://enterprise.mobilenig.com/api/v2/services/

Body Params

Name	Type	Description
service_id	String	Hard-coded value "BCD".
service_type	String	Hard-coded value "GIFTING"
beneficiary	String	Beneficiary phone number
trans_id	Number	The trans_id used to recharge.
code	String	Code value from get prices call
amount	Number	Transaction cost from get prices call



Note: For AirtelSme, `service_type` will be "SME".

AUTHORIZATION Bearer Token

Token `{{secret_key}}`

HEADERS

Content-Type `application/json`

Authorization `Bearer {{secret_key}}`

Body raw

```
{
  "service_id": "BCD",
  "service_type": "SME",
  "beneficiary": "09045679834",
  "trans_id": "23743839298",
  "code": "MBAS300",
  "amount": "70"
}
```

GET Query



https://enterprise.mobilenig.com/api/v2/services/query?trans_id=23743839298

Query Params

Name	Type	Description
trans_id	Number	The trans_id used to recharge.

AUTHORIZATION Bearer Token



Token {{secret_key}}

HEADERS

Content-Type application/json

Authorization Bearer {{secret_key}}

PARAMS

trans_id 23743839298