

Visualisation

You are required to produce a **visualisation** of food hygiene ratings for different establishments across London.

Your visualisation should contain a map-based display of the ratings, placed according to their geolocation data. A user should be able to intuitively see which businesses are 'safe' to eat at, and those which have not scored so well.

You will supplement the map with additional charts and graphics that you deem appropriate to tell a coherent story from the data available.

Question 0

In this assignment, you will use Bokeh, in particular `WMTSTileSource` class to add points to a map. You will use a convenience package `bokeh.tile_providers` (http://bokeh.pydata.org/en/latest/docs/reference/tile_providers.html), which creates a `WMTSTileSource` (like used in the guided exercise) instance with the `url` and `attribution` already set. So, instead of manually creating a tile, you can just use one of the variables already created. See [the Bokeh source code](https://github.com/bokeh/bokeh/blob/master/bokeh/tile_providers.py) (https://github.com/bokeh/bokeh/blob/master/bokeh/tile_providers.py) to look at how they have done it.

The available tiles supported by Bokeh use *Web Mercator* (https://en.wikipedia.org/wiki/Web_Mercator), format to represent location, so a function `wgs84_to_web_mercator` to convert the two is provided.

Run the code in the cell below to set up the Notebook.

In [84]:

```

# You don't need to write anything here
# Set up MongoDB
from pymongo import MongoClient

client = MongoClient('mongodb://cpduser:M13pV5woDW@mongodb/health_data', 27017)
db = client.health_data

from nose.tools import *

# # Numpy, Pandas and Bokeh imports
import numpy as np
import pandas as pd
from bokeh.palettes import Spectral6
from bokeh.io import output_notebook, show
from bokeh.models.sources import ColumnDataSource
from bokeh.models import *
from bokeh.io import curdoc
from bokeh.tile_providers import *
from bokeh.models.tiles import WMTSTileSource
import ipywidgets
from ipywidgets import interact, interactive
from ipywidgets import HBox, Label, IntSlider

from bokeh.plotting import figure
from bokeh.models import TapTool, CustomJS

def wgs84_to_web_mercator(df, lon="lon", lat="lat"):
    """
    Converts decimal longitude/latitude to Web Mercator format
    Source https://github.com/bokeh/bokeh-notebooks/blob/master/tutorial/11%20-%20ge
    """
    k = 6378137
    df["x"] = df[lon] * (k * np.pi/180.0)
    df["y"] = np.log(np.tan((90 + df[lat]) * np.pi/360.0)) * k
    return df

# from ipywidgets import *
# from bokeh.layouts import *
from IPython.display import display
from bokeh.io import output_file, output_notebook, show, push_notebook

output_notebook()

```

(<http://bokeh.pydata.org/>) successfully loaded.

In [54]:

```
# You don't need to write anything here
# Check it's set up correctly
try:
    imports = [MongoClient, db, np, pd, output_notebook, show, ColumnDataSource,
               output_notebook, show, ColumnDataSource, STAMEN_TERRAIN, figure
               ]
    assert True
    print('Successfully imported required libraries')
except NameError as e:
    print(e)
    assert False
```

Successfully imported required libraries

Question 1: Create Map

In this question, you will create functions which will **return** the different objects required for the visualisation of a map on: A DataFrame (<http://pandas.pydata.org/pandas-docs/stable/generated/pandas.DataFrame.html>), a ColumnDataSource and a Figure.

Question 1(a) [4 marks]

Create a function `get_data()` to extract data from the MongoDB database for all institutions which are in the **London** region with the following constraints:

- The results should include: Lat, Lng, BusinessType, AddressLine1, BusinessName, RatingValue but **NOT** the `_id` field
- The results should **only include businesses which have a RatingValue** (N.B. A value of 0 is a RatingValue)
- The results returned should **only include businesses which have a Geocode**
- The returned values should be **limited to 200** institutions
- **Add fields `x` and `y` in Web Mercator format** to specify co-ordinates on the map
- **Return** the result as as DataFrame (<http://pandas.pydata.org/pandas-docs/stable/generated/pandas.DataFrame.html>).

Hint: Week 3, Guided Exercise 4, Cursors

Hint: Week 4, Guided Exercise 2, Importing Data

In [139]:

```

dff = db.uk.find({'Region' : 'london'})
listy = list(dff)
df1 = pd.DataFrame(listy).dropna(subset=[['Geocode', 'RatingValue']])
df2 = df1.head(200)
df3 = df2[['Lat', 'Lng', 'BusinessType', 'AddressLine1', 'BusinessName', 'RatingValue']]
print(df3)

```

	Lat	Lng	BusinessType \
0	51.406561	0.028132	Hospitals/Childcare/Caring Premises
1	51.431513	0.076540	Restaurant/Cafe/Canteen
2	51.411260	0.104858	Retailers - other
3	51.416480	-0.072576	Retailers - other
4	51.359719	0.072717	Retailers - other
5	51.369514	0.093848	Hospitals/Childcare/Caring Premises
6	51.406208	-0.015839	Hospitals/Childcare/Caring Premises
7	51.414499	0.007386	Hospitals/Childcare/Caring Premises
8	51.369514	0.093848	Hospitals/Childcare/Caring Premises
9	51.404352	-0.000290	Hospitals/Childcare/Caring Premises
10	51.369514	0.093848	Hospitals/Childcare/Caring Premises
11	51.369514	0.093848	Hospitals/Childcare/Caring Premises
12	51.404444	-0.012033	Hospitals/Childcare/Caring Premises
13	51.414901	0.008094	Hospitals/Childcare/Caring Premises
15	51.343307	0.031628	Retailers - other
16	51.416154	-0.072978	Restaurant/Cafe/Canteen
17	51.378695	0.101438	Retailers - other
18	51.384779	-0.022270	Hospitals/Childcare/Caring Premises
19	51.371260	0.006720	Hospitals/Childcare/Caring Premises

In [140]:

```
cursor = db.uk.find({'Region' : 'london', 'Geocode' : {'$ne' : None }, 'RatingValue' : 1, 'AddressLine1' : 1, 'Lat' : 1, 'Lng' : 1, 'BusinessType' : 1, 'AddressLine1' : 1, 'BusinessName' : 1})

listy = list(cursor)
#rating_values = pd.DataFrame())[ 'RatingValue' ]
#cursor.
#df = wgs84_to_web_mercator(df, 'lon', 'lat')
first_200 = pd.DataFrame(listy)
#dropna(subset=[ 'RatingValue', 'Geocode' ]])

print(first_200)
#first_200[first_200[ 'RatingValue' ] != None]
#f200 = fi_200[fi_200[ 'Geocode' ] > -1]
#first_200[[ 'Geocode', 'Lat', 'Lng', 'BusinessType', 'AddressLine1', 'BusinessName',
```

```

                                AddressLine1 \
0                                Bromley
1                                The 19th Hole Cafe
2                                80 Grovelands Road
3                                61 Anerley Road
4                                143 High Street
5                                10 Tower Road
6                                114 Bromley Road
7                                118 London Road
8                                18 Tower Road
9                                20 Shortlands Road
10                               22 Tower Road
11                               24 Tower Road
12                               8 Oakwood Avenue
13                               Abbeyfield House
14                               Vale Farm
15                               112 - 114 Anerley Road
16                               138 High Street
17                               29 South Eden Park Road
18                               112 - 114 Anerley Road

```

In []:

```

states = []
lons = []
lats = [] #리스트 작성하기
# The sample data is in a slightly difficult format, so we will change it to be in a
# We don't mind about the State being repeated, as long as we have all the latitudes
#
#   Lat      Lon      State
# 0 -82.88318  -82.88318  FL
# 1 -82.87484  -82.87484  FL
# 2 -82.86562  -82.86562  FL

for s in us_states: #US에서 시작
    # The amount of longitudes is the same as the latitudes, so this is safe
    # Iterate through each lat/lon pair

    for data in range(len(us_states[s]['lons'])):
        #범위 또는 길이는 우리가 여기에 있는 수 또는 길이를 기반으로 한다.
        states.append(s)
        lons.append(us_states[s]['lons'][data]) #경도 데이터 추가
        lats.append(us_states[s]['lats'][data]) #위도 데이터 추가

# We created 3 lists of equal length, now we create a
df = pd.DataFrame({'state': states, 'lat': lats, 'lon': lons})#dict(state=states, lon=lons, lat=lats)
df.head()

df = wgs84_to_web_mercator(df, 'lon', 'lat')
df.head()

```

In [141]:

```
def get_data():
    dff = db.uk.find({'Region' : 'london'})
    listy = list(dff)
    df1 = pd.DataFrame(listy).dropna(subset=[ 'Geocode', 'RatingValue' ])
    df2 = df1.head(200)
    df3 = df2[['Lat', 'Lng', 'BusinessType', 'AddressLine1', 'BusinessName', 'RatingValue']]
    df = wgs84_to_web_mercator(df3, 'Lng', 'Lat')

    return df

#return businesses (RV와 Geocode가 존재하고 200개 기관으로 제한 되어있어야함 비즈니스만 +데이터)
raise NotImplementedError()

get_data().head()
```

/opt/conda/lib/python3.5/site-packages/ipykernel/__main__.py:36: SettingWithCopyWarning:

A value is trying to be set on a copy of a slice from a DataFrame.

Try using .loc[row_indexer,col_indexer] = value instead

See the caveats in the documentation: <http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy> (<http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy>)

/opt/conda/lib/python3.5/site-packages/ipykernel/__main__.py:37: SettingWithCopyWarning:

A value is trying to be set on a copy of a slice from a DataFrame.

Try using .loc[row_indexer,col_indexer] = value instead

See the caveats in the documentation: <http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy> (<http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy>)

Out[141]:

	Lat	Lng	BusinessType	AddressLine1	BusinessName	Rating
0	51.406561	0.028132	Hospitals/Childcare/Caring Premises	Bromley	118 Widmore Road	3.0
1	51.431513	0.076540	Restaurant/Cafe/Canteen	The 19th Hole Cafe	19th Hole Cafe	1.0
2	51.411260	0.104858	Retailers - other	80 Grovelands Road	A & A Stores	2.0
3	51.416480	-0.072576	Retailers - other	61 Anerley Road	A Butterfly	3.0
4	51.359719	0.072717	Retailers - other	143 High Street	Aambal Local Store	3.0

In [85]:

```
def get_data():
    dff = db.uk.find({'Region' : 'london', 'Geocode' : {'$ne' : None }, 'RatingValue' : {'Lat' : 1, 'Lng' : 1, 'BusinessType' : 1, 'AddressLine1' : 1,

    listy = list(dff)
    df1 = pd.DataFrame(listy)
    df = wgs84_to_web_mercator(df1, 'Lng', 'Lat')

    return df

#return businesses (RV와 Geocode가 존재하고 200개 기관으로 제한 되어있어야함 비즈니스만 +데이터)
raise NotImplementedError()
get_data().head()
```

Out[85]:

	AddressLine1	BusinessName	BusinessType	Lat	Lng	Rating
0	Bromley	118 Widmore Road	Hospitals/Childcare/Caring Premises	51.406561	0.028132	3
1	The 19th Hole Cafe	19th Hole Cafe	Restaurant/Cafe/Canteen	51.431513	0.076540	1
2	80 Grovelands Road	A & A Stores	Retailers - other	51.411260	0.104858	2
3	61 Anerley Road	A Butterfly	Retailers - other	51.416480	-0.072576	3
4	143 High Street	Aambal Local Store	Retailers - other	51.359719	0.072717	3

In [56]:

```
# You don't need to write anything here
test_data = get_data()
assert_equal(type(test_data),pd.DataFrame)

for index, row in test_data.iterrows():
    try:
        i = int(row['RatingValue'])
    except:
        raise AssertionError('There is a row which is not an integer. '
                               'Make sure you exclude all those without a RatingValue')
    assert False

#print('All tests passed successfully')
assert_equal(len(test_data.index), 200)
print('All tests passed successfully')
```

All tests passed successfully

Question 1(b) [2 marks]

Create a function **get_source** which takes a **DataFrame** as a parameter and manipulates it to prepare for addition to the plot. The function should:

- **Contain a column Colour**, which contains a hex string of the colour with which to display the establishment on the map, e.g., #d53e4f. This should be used to distinguish different RatingValue values of the businesses.
- **RatingValues will be displayed by different colours** using an appropriate palette such as **Spectral16** from the standard Bokeh palettes (<http://bokeh.pydata.org/en/latest/docs/reference/palettes.html>).
- The function should **accept an integer** as a number to filter the businesses by RatingValue.
- If the rating value is equal to **-1**, then **all businesses should be included**. Otherwise, the data should be filtered to only include businesses with a RatingValue of the value passed.
- The function should **return** the result as a **DataFrame**

Hint: Week 5, Guided Exercise 2, Data Sources

In [201]:

```

Colour = Spectral6
Colour1 = []
test_source = get_data()
#test_source['RatingValue'] =
#test_source
test_source[colour1]

Colour1 = Spectral6
test_source = pd.DataFrame({'Colour': [1,2,3,4,5], 'RatingValue' : [1,2,3,4,5], 'x':
#test_source['RatingValue'] =
i = 0
#print(test_source)
for s in Colour1:
    test_source['Colour'][i] = Colour1[i]
    i += 1

print(test_source)

#R = 1 -> 빨 2-> 주 ..
#rating_value_1 = test_source.loc[test_source['RatingValue'] == 1]
##rating_value_2 = test_source.loc[test_source['RatingValue'] == 2]
rating_value_3 = test_source.loc[test_source['RatingValue'] == 3]
#rating_value_4 = test_source.loc[test_source['RatingValue'] == 4]
#rating_value_5 = test_source.loc[test_source['RatingValue'] == 5]
#print(rating_value_1)
#print(rating_value_2)
print(rating_value_3)
print(rating_value_3['Colour'].values[0])
#print(rating_value_4)
#print(rating_value_5)
#fields = test_source.columns.values
#print(fields)

```

/opt/conda/lib/python3.5/site-packages/ipykernel/__main__.py:36: SettingWithCopyWarning:

A value is trying to be set on a copy of a slice from a DataFrame.
Try using .loc[row_indexer,col_indexer] = value instead

See the caveats in the documentation: <http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy> (<http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy>)

/opt/conda/lib/python3.5/site-packages/ipykernel/__main__.py:37: SettingWithCopyWarning:

A value is trying to be set on a copy of a slice from a DataFrame.
Try using .loc[row_indexer,col_indexer] = value instead

See the caveats in the documentation: <http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy> (<http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy>)

	Colour	RatingValue	x	y
0	#3288bd	1	1	1
1	#99d594	2	2	2
2	#e6f598	3	3	3
3	#fee08b	4	4	4
4	#fc8d59	5	5	5
	Colour	RatingValue	x	y
2	#e6f598	3	3	3
	#e6f598			

/opt/conda/lib/python3.5/site-packages/ipykernel/__main__.py:13: SettingWithCopyWarning:

A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation: <http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy> (<http://pandas.pydata.org/pandas-docs/stable/indexing.html#indexing-view-versus-copy>)

In [5]:

```
Colour2 = Spectral6
test_source = get_data()
test_source['Colour'] = '#ffffff'
#test_source['RatingValue'] =
#test_source
for e in range(len(test_source)):
    RV = test_source['RatingValue'][e]
    Colour = ''
    if RV == 0:
        test_source['Colour'] == Colour2[0]
    elif RV == 1.0:
        test_source['Colour'] == Colour2[1]
    elif RV == 2.0:
        test_source['Colour'] == Colour2[2]
    elif RV == 3.0:
        test_source['Colour'] == Colour2[3]
    elif RV == 4.0:
        test_source['Colour'] == Colour2[4]
    elif RV == 5.0:
        test_source['Colour'] == Colour2[5]
    elif test_source['RatingValue'] == -1.0:
        pass
test_source.loc[test_source['RatingValue'] == 0, 'Colour'] = Colour2[0]
test_source.loc[test_source['RatingValue'] == 1, 'Colour'] = Colour2[1]
test_source.loc[test_source['RatingValue'] == 2, 'Colour'] = Colour2[2]
test_source.loc[test_source['RatingValue'] == 3, 'Colour'] = Colour2[3]
test_source.loc[test_source['RatingValue'] == 4, 'Colour'] = Colour2[4]
test_source.loc[test_source['RatingValue'] == 5, 'Colour'] = Colour2[5]
test_source.head()
```

Out[5]:

	AddressLine1	BusinessName	BusinessType	Lat	Lng	Rating
0	Bromley	118 Widmore Road	Hospitals/Childcare/Caring Premises	51.406561	0.028132	3
1	The 19th Hole Cafe	19th Hole Cafe	Restaurant/Cafe/Canteen	51.431513	0.076540	1
2	80 Grovelands Road	A & A Stores	Retailers - other	51.411260	0.104858	2
3	61 Anerley Road	A Butterfly	Retailers - other	51.416480	-0.072576	3
4	143 High Street	Aambal Local Store	Retailers - other	51.359719	0.072717	3

In [86]:

```
def get_source(df, data_filter=-1):
    # YOUR CODE HERE
    Colour2 = Spectral6
    df['Colour'] = '#ffffff'
    for e in range(len(df)):
        RV = df['RatingValue'][e]
        Colour = ''
        if RV == 0:
            df['Colour'] == Colour2[0]
        elif RV == 1.0:
            df['Colour'] == Colour2[1]
        elif RV == 2.0:
            df['Colour'] == Colour2[2]
        elif RV == 3.0:
            df['Colour'] == Colour2[3]
        elif RV == 4.0:
            df['Colour'] == Colour2[4]
        elif RV == 5.0:
            df['Colour'] == Colour2[5]

    df.loc[df['RatingValue'] == 0, 'Colour'] = Colour2[0]
    df.loc[df['RatingValue'] == 1, 'Colour'] = Colour2[1]
    df.loc[df['RatingValue'] == 2, 'Colour'] = Colour2[2]
    df.loc[df['RatingValue'] == 3, 'Colour'] = Colour2[3]
    df.loc[df['RatingValue'] == 4, 'Colour'] = Colour2[4]
    df.loc[df['RatingValue'] == 5, 'Colour'] = Colour2[5]

    if data_filter == -1:
        return df
    else:
        filter1 = df['RatingValue'] == data_filter
        filter2 = df[filter1]

    return filter2

raise NotImplementedError()
get_source(get_data(), data_filter=5).head()
```

Out[86]:

	AddressLine1	BusinessName	BusinessType	Lat	Lng	Ratin
6	114 Bromley Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.406208	-0.015839	5
7	118 London Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.414499	0.007386	5
9	20 Shortlands Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.404352	-0.000290	5
12	8 Oakwood Avenue	Abbeyfield	Hospitals/Childcare/Caring Premises	51.404444	-0.012033	5
13	Abbeyfield House	Abbeyfield Bromley Society Limited	Hospitals/Childcare/Caring Premises	51.414901	0.008094	5

In [58]:

```
# You don't need to write anything here
test_source = get_source(get_data())
assert_equal(type(test_source), pd.DataFrame)
# Check the colours are different
rating_value_1 = test_source.loc[test_source['RatingValue'] == 1]
rating_value_2 = test_source.loc[test_source['RatingValue'] == 2]
rating_value_3 = test_source.loc[test_source['RatingValue'] == 3]
rating_value_4 = test_source.loc[test_source['RatingValue'] == 4]
rating_value_5 = test_source.loc[test_source['RatingValue'] == 5]

colour_list = [rating_value_1['Colour'].values[0],
               rating_value_2['Colour'].values[0],
               rating_value_3['Colour'].values[0],
               rating_value_4['Colour'].values[0],
               rating_value_5['Colour'].values[0]]
# If they are all different, then the length of the set should be 5
assert_equal(len(set(colour_list)), 5)

fields = test_source.columns.values
assert 'x' in fields
assert 'y' in fields

# Test that the x and y are the correct web mercator format
test_lng = rating_value_1['Lng'].values[0]
test_lat = rating_value_1['Lat'].values[0]

test_x = rating_value_1['x'].values[0]
test_y = rating_value_1['y'].values[0]

k = 6378137
# print(test_lat * (k * np.pi/180.0))

assert_equal(test_x, test_lng * (k * np.pi/180.0))
assert_equal(test_y, np.log(np.tan((90 + test_lat) * np.pi/360.0)) * k)
print('All tests passed successfully')
```

All tests passed successfully

Question 1(c) [2 marks]

Create a function **get_map**, which **returns** a map of London using the STAMEN TERRAIN (http://bokeh.pydata.org/en/latest/docs/reference/tile_providers.html#bokeh.tile_providers.STAMEN_TERRAIN).
tile

- The function should **return** a **type** Figure
- The figure should include **all** the available **Pan/Drag tools** (http://bokeh.pydata.org/en/latest/docs/user_guide/tools.html#pan-drag-tools), the **reset** tool, and the **mouse wheel zoom** tool
- The map should display London, at an appropriate zoom level for the data

Hint: To get the x, y values surrounding London, look at the smallest and largest x and y values in the data

Hint: Week 4, Guided Exercise 3, Residual Analysis (attributes)

Hint: Week 5, Guided Exercise 2, Data Sources (Bokeh Map Tiling)

In [248]:

```
test1 = get_source(get_data())
print(test1['y'].max())
print(test1['y'].min())
test2 = test1.loc[test1['RatingValue'] == 1 ]
print(test2)
```

6699112.66832

6675917.19275

	AddressLine1	BusinessName \
1	The 19th Hole Cafe	19th Hole Cafe
45	4 - 6 Market Parade	Aqua Bar And Grill
46	23 Genoa Road	Archangels Montessori Day Nursery
61	305 Upper Elmers End Road	Auntie May's
63	33 Rodway Road	Avis Hotel
75	32 East Street	Bar Du Vin
83	251 Croydon Road	Beckenham Charcoal Grill
94	205 High Street	Belash Tandoori
97	59 Beckenham Road	Belleberry Deli
136	113 Croydon Road	Biter's
146	101 High Street	Blue Bengal
155	53 Beckenham Road	Bon Appetit Cafe
180	49 Chislehurst Road	Bridges Fish & Chips

BusinessType	Lat	Lng	RatingV
Restaurant/Cafe/Canteen	51.431513	0.076540	
Restaurant/Cafe/Canteen	51.407575	0.016300	
Hospitals/Childcare/Caring Premises	51.409998	-0.059058	
Takeaway/sandwich shop	51.392033	-0.037639	
Hotel/bed & breakfast/guest house	51.412501	0.023161	
Restaurant/Cafe/Canteen	51.407131	0.016468	
Takeaway/sandwich shop	51.402668	-0.036839	
Restaurant/Cafe/Canteen	51.413343	-0.050906	
Takeaway/sandwich shop	51.408289	-0.038496	
Restaurant/Cafe/Canteen	51.398829	-0.042323	
Restaurant/Cafe/Canteen	51.376692	-0.020003	
Restaurant/Cafe/Canteen	51.408289	-0.038496	
Takeaway/sandwich shop	51.407255	0.055900	

x	y	Colour
8520.393825	6.697981e+06	#99d594
1814.507700	6.693708e+06	#99d594
-6574.306487	6.694141e+06	#99d594
-4189.954314	6.690935e+06	#99d594
2578.270726	6.694587e+06	#99d594

```

75 1833.209374 6.693629e+06 #99d594
83 -4100.898721 6.692833e+06 #99d594
94 -5666.829998 6.694738e+06 #99d594
97 -4285.355118 6.693836e+06 #99d594
136 -4711.374809 6.692147e+06 #99d594
146 -2226.723774 6.688199e+06 #99d594
155 -4285.355118 6.693836e+06 #99d594
180 6222.759535 6.693651e+06 #99d594

```

In [105]:

```

url = 'http://a.basemaps.cartocdn.com/STAMEN_TERRAIN/{Z}/{X}/{Y}.png'
x_range,y_range = ((-8123.87379911,15202.9028576), (6675917.19275,6699112.66832))
fig = figure(tools='pan, reset, wheel_zoom', x_range=x_range, y_range=y_range)
fig.add_tile(WMTSTileSource(tiles = STAMEN_TERRAIN))
show(fig)

```

```

-----
-----
AttributeError                                Traceback (most recent call
last)
<ipython-input-105-c890be898621> in <module>()
      2 x_range,y_range = ((-8123.87379911,15202.9028576), (6675917.19
275,6699112.66832))
      3 fig = figure(tools='pan, reset, wheel_zoom', x_range=x_range,
y_range=y_range)
----> 4 fig.add_tile(WMTSTileSource(tiles = STAMEN_TERRAIN))
      5 show(fig)

/opt/conda/lib/python3.5/site-packages/bokeh/model.py in __init__(sel
f, **kwargs)
    143         self._id = kwargs.pop("id", make_id())
    144         self._document = None
--> 145         super(Model, self).__init__(**kwargs)
    146         default_theme.apply_to_model(self)
    147

/opt/conda/lib/python3.5/site-packages/bokeh/core/has_props.py in __in
it__(self, **properties)
    220
    221         for name, value in properties.items():
--> 222             setattr(self, name, value)
    223
    224         def __setattr__(self, name, value):

/opt/conda/lib/python3.5/site-packages/bokeh/core/has_props.py in __se
tattr__(self, name, value)
    256
    257         raise AttributeError("unexpected attribute '%s' to
%s, %s attributes are %s" %
--> 258             (name, self.__class__.__name__, text, nice_joi
n(matches)))
    259
    260         def __str__(self):

AttributeError: unexpected attribute 'tiles' to WMTSTileSource, simila
r attributes are tile_size

```

In [87]:

```


from bokeh.io import output_file, show
from bokeh.layouts import column
from bokeh.plotting import figure

def get_map(data):
    """
    In this function you return a figure with a map background. The background shows
    on London at an appropriate zoom level
    """
    # YOUR CODE HERE
    url = 'http://tile.stamen.com/terrain/{z}/{x}/{y}.jpg'
    x_range, y_range = ((-8123.87379911, 15202.9028576), (6675917.19275, 6699112.66832))
    fig = figure(tools='pan, reset, wheel_zoom', x_range=x_range, y_range=y_range)
    fig.add_tile(WMTSTileSource(url = url))

    return fig
    raise NotImplementedError()

show(get_map(get_source(get_data())))

```



Question 1(d) [3 marks]

Write code which creates and shows a figure `london_map` using the `get_map()` function, obtains a data source for the figure using `get_data()`, then uses the `circle` method to add the data to the map.

- You should call the output of the `circle` function `data_points`.
- The dots you add to the map should have a size of 10, no border, and a `fill_alpha` of 0.8
- You should call your map `london_map`
- Your code should contain a variable name for the dots added to the map

N.B. You are not being asked to create a function for this question

Hint: Week 4, Guided Exercise 3, Fitting a Model - Residual Analysis

Hint: Week 5, Guided Exercise 2, Widgets

In [26]:


```
get_source(get_data())
```

Out[26]:

	AddressLine1	BusinessName	BusinessType	Lat	Lng	RatingValue	x
0	Bromley	118 Widmore Road	Hospitals/Childcare/Caring Premises	51.406561	0.028132	3	3131
1	The 19th Hole Cafe	19th Hole Cafe	Restaurant/Cafe/Canteen	51.431513	0.076540	1	8520
2	80 Grovelands Road	A & A Stores	Retailers - other	51.411260	0.104858	2	1167
3	61 Anerley Road	A Butterfly	Retailers - other	51.416480	-0.072576	3	-8079
4	143 High Street	Aambal Local Store	Retailers - other	51.359719	0.072717	3	8094
5	10 Tower	Abbevillefield	Hospitals/Childcare/Caring	51.369514	0.093848	4	1044


In [158]:

```
fig1 = get_map(get_source(get_data()))
test1 = get_source(get_data())
data = test1.loc[test1['RatingValue'] == 1]
colour = test1.loc[test1['RatingValue'] == 1]['Colour'].iloc[0]
ca = fig1.patch(data['x'], data['y'], fill_color= colour)
show(fig1)
```



In [177]:

```
fig1 = get_map(get_source(get_data()))
test1 = get_source(get_data())
#for i in range(0):
data = test1.loc[test1['RatingValue'] == 3]
colour = test1.loc[test1['RatingValue'] == 3]['Colour'].iloc[0]
ca = fig1.circle(test1['x'], test1['y'], size = 10, color = colour)
show(fig1)
```




In [25]:

```
london_map = get_map(get_source(get_data()))
data = get_source(get_data())

source = data.loc[data['RatingValue'] == 3]
Colour = data.loc[test1['RatingValue'] == 3]['Colour'].iloc[0]
k = london_map.circle(source['x'], source['y'], size = 10, color = Colour, fill_alp


show(london_map)
```



In [35]:

```
london_map = get_map(get_source(get_data()))
test1 = get_source(get_data())
for i in range(1,6):
    data = test1.loc[test1['RatingValue'] == i]
    colour = test1.loc[test1['RatingValue'] == i]['Colour'].iloc[0]
    data_points = london_map.circle(data['x'], data['y'], size = 10, color = colour)

london_map.axis.visible = False
show(london_map)
```




In [167]:

```
source = get_source(get_data())
london_map = get_map(source)

data_points = london_map.circle(source = source, x = 'x', y = 'y',
                                fill_color = 'Colour', fill_alpha = 0.8, size = 10,

london_map.axis.visible = False
show(london_map)
```



In [75]:

```
fig_source = london_map.select(GlyphRenderer)[0].data_source
#print(vars(fig_source))
assert_equal(fig_source.data['x'][0], source['x'][0])
assert_equal(fig_source.data['y'][0], source['y'][0])
assert_equal(fig_source.data['Colour'][0], source['Colour'][0])
#assert_equal(fig_source.data['fill_color'][0], ds.data['Colour'][0])

glyph = london_map.select(GlyphRenderer)[0].glyph
assert_equal(glyph.line_color, None)
assert_equal(glyph.size, 10)
assert_equal(glyph.fill_alpha, 0.8)
#glyph.fill_color == (ds.data['Colour'][0])
print('All tests passed successfully')
```

All tests passed successfully

Question 2: Make it Interactive

Question 2(a) [2 marks]

Create a function **callback** for later use, which updates the visible businesses on the map according to their **RatingValue**. The function should have parameter **rating** which specifies the value to filter by, calling **get_source**. Use the **source** variable from Question 1(d) to update the map.

Hint: Week 4, Guided Exercise 2, Bokeh Charts

Hint: Week 5, Guided Exercise 2, Data Sources - Widgets (update figure)

In [169]:

```
source = get_source(get_data())
london_map = get_map(source)

data = source.loc[source['RatingValue'] == 1]
data_points.data_source.data['x'] = data['x']
data_points.data_source.data['y'] = data['y']
colour = source.loc[test1['RatingValue'] == 1]['Colour'].iloc[0]
data_points = london_map.circle(source = source, x = 'x', y = 'y',
                                fill_color = 'Colour', fill_alpha = 0.8, size = 10,

push_notebook()
london_map.axis.visible = False
show(london_map)
```

```
/opt/conda/lib/python3.5/site-packages/bokeh/models/sources.py:81: Bok
ehUserWarning: ColumnDataSource's columns must be of the same length
  lambda: warnings.warn("ColumnDataSource's columns must be of the sam
e length", BokehUserWarning))
/opt/conda/lib/python3.5/site-packages/bokeh/models/sources.py:81: Bok
ehUserWarning: ColumnDataSource's columns must be of the same length
  lambda: warnings.warn("ColumnDataSource's columns must be of the sam
e length", BokehUserWarning))
```

```
-----
-----
NameError                                Traceback (most recent call
last)
<ipython-input-169-cac1a65ef2cb> in <module>()
      5 data_points.data_source.data['x'] = data['x']
      6 data_points.data_source.data['y'] = data['y']
----> 7 colour = source.loc[test1['RatingValue'] == 1]['Colour'].iloc[
0]
      8 data_points = london_map.circle(source = source, x = 'x', y =
'y',
      9                                fill_color = 'Colour', fill_alp
ha = 0.8, size = 10, line_color = None)

NameError: name 'test1' is not defined
```


In [171]:

```
def callback(rating):  
    # YOUR CODE HERE  
    source = get_source(get_data())  
    london_map = get_map(source)  
  
    data = source.loc[source['RatingValue'] == rating]  
    colour = source.loc[source['RatingValue'] == rating]['Colour'].iloc[0]  
    data_points = london_map.circle(source = source, x = 'x', y = 'y',  
                                    fill_color = colour, fill_alpha = 0.8, size = 10,  
  
    data_points.data_source.data['x'] = data['x']  
    data_points.data_source.data['y'] = data['y']  
    push_notebook()  
    london_map.axis.visible = False  
    show(london_map, notebook_handle=True)  
    return london_map  
    raise NotImplementedError()
```

In [172]:

callback(1)

```

/opt/conda/lib/python3.5/site-packages/bokeh/models/sources.py:81: BokehUserWarning: ColumnDataSource's columns must be of the same length
  lambda: warnings.warn("ColumnDataSource's columns must be of the same length", BokehUserWarning))
/opt/conda/lib/python3.5/site-packages/bokeh/models/sources.py:81: BokehUserWarning: ColumnDataSource's columns must be of the same length
  lambda: warnings.warn("ColumnDataSource's columns must be of the same length", BokehUserWarning))
/opt/conda/lib/python3.5/site-packages/bokeh/io.py:578: UserWarning: Cannot find a last shown plot to update. Call output_notebook() and show(..., notebook_handle=True) before push_notebook()
  warnings.warn("Cannot find a last shown plot to update. Call output_notebook() and show(..., notebook_handle=True) before push_notebook()")

```



Out [172]:

Figure(id = '14dd3e02-375c-4823-addc-7cbb2d149a9f', ...)

Question 2(b) [2 marks]

Using **ipywidgets**, create an interactive (<http://ipywidgets.readthedocs.io/en/latest/examples/Using%20Interact.html>) `IntSlider` widget, which calls the **callback** function when it updates.

Return the interactive widget in the function **set_interactive()**

Hint: Week 5, Guided Exercise 2, Widgets


In [162]:

```
def set_interactive():
    # YOUR CODE HERE
    i = interactive(callback, rating=3)
    i

    return i
    raise NotImplementedError()
```

set_interactive()

```
/opt/conda/lib/python3.5/site-packages/bokeh/models/sources.py:81: BokehUserWarning: ColumnDataSource's columns must be of the same length
  lambda: warnings.warn("ColumnDataSource's columns must be of the same length", BokehUserWarning))
/opt/conda/lib/python3.5/site-packages/bokeh/models/sources.py:81: BokehUserWarning: ColumnDataSource's columns must be of the same length
  lambda: warnings.warn("ColumnDataSource's columns must be of the same length", BokehUserWarning))
/opt/conda/lib/python3.5/site-packages/bokeh/io.py:578: UserWarning: Cannot find a last shown plot to update. Call output_notebook() and show(..., notebook_handle=True) before push_notebook()
  warnings.warn("Cannot find a last shown plot to update. Call output_notebook() and show(..., notebook_handle=True) before push_notebook()")
```



Figure(id = '154b6642-fd86-4331-aa0b-1f9cf2389c96', ...)

In [145]:

```
# You don't need to write anything here
old_callback = callback
del callback

try:
    set_interactive()
except NameError as e:
    pass
else:
    raise AssertionError('You have not called the callback function in your code')
finally:
    callback = old_callback
    del old_callback
assert_equal(type(set_interactive()), ipywidgets.widgets.widget_box.Box)
```

Question 3: Extend the Visualisation

Applying question 2 solutions

Now you have created an initial visualisation, you are going to add the following components to it:

- **Hover** text, so that each dot will give information about the business when you hover
- A **drop down menu** to limit the type of business

You will also be asked to explain a possible use-case for this chart, and offer a suggestion as to how it could be improved.

NOTE: There are discretionary marks available for good visualisation practice

Question 3(a) [5 marks]

Create a function **get_hover**, which returns a [HoverTool](http://bokeh.pydata.org/en/latest/docs/user_guide/tools.html#hover-tool) (http://bokeh.pydata.org/en/latest/docs/user_guide/tools.html#hover-tool) to be added to the map. When the cursor hovers over any circle, the following information should be displayed:

- The **name** of the establishment
- The **type** of the establishment
- The **RatingValue** of the establishment

Your function should **return** the [HoverTool](http://bokeh.pydata.org/en/latest/docs/user_guide/tools.html#hover-tool) (http://bokeh.pydata.org/en/latest/docs/user_guide/tools.html#hover-tool).

N.B You may need to read the documentation available to ensure that you match a suitable title for the **field** with the **field value** using **@**.

Hint: Week 5, Guided Exercise 2, Tools


In [168]:

```
def get_hover():
    # YOUR CODE HERE
    hover_tool = HoverTool(
        tooltips=[
            ( 'BusinessName',    '@BusinessName'          ),
            ( 'BusinessType',    '@BusinessType' ), # use @{ } for field names with spaces
            ( 'RatingValue',    '@RatingValue'          )
        ],

        # display a tooltip whenever the cursor is vertically in line with a glyph
        mode='vline'
    )

    return hover_tool
    raise NotImplementedError()

london_map.add_tools(get_hover())
show(london_map)
```



In [165]:

```

from bokeh.plotting import Figure
tools_fig_1 = Figure(tools=[HoverTool(
    tooltips=[
        ( 'BusinessName',    '@BusinessName'          ),
        ( 'BusinessType',    '@BusinessType' ), # use @{ } for field names with spaces
        ( 'RatingValue',    '@RatingValue'          )
    ],

    # display a tooltip whenever the cursor is vertically in line with a glyph
    mode='vline'
    ), BoxSelectTool()], height=100)
show(tools_fig_1)

```

(http

Question 3(b) [5 marks]

Using [interactive](http://ipywidgets.readthedocs.io/en/latest/examples/Using%20Interact.html) (<http://ipywidgets.readthedocs.io/en/latest/examples/Using%20Interact.html>), create a **dropdown menu** which allows the user to choose between different **types of business**. The map should update automatically as you select.

- You should create two functions **filter_business_types**, which the dropdown menu will call when it changes. This function should update the data source
- You will need to obtain a list of the different types of business in the database
- You should **return** an **interactive** object, which should call the function **filter_business_types**, which updates the **source** variable accordingly

N.B. Should you use the original data set?

Hint: Week 5, Guided Exercise 2, Data Sources - Tools

In [315]:

```

#source.loc[source['BusinessType'] == 'Retailers - other']
source['BusinessType'].drop_duplicates()
j = source['BusinessType'].drop_duplicates()
listie = j[0], j[1], j[2], j[24], j[26], j[28], j[39], j[40], j[63], j[78], j[189]
print(listie)

```

```

('Hospitals/Childcare/Caring Premises', 'Restaurant/Cafe/Canteen', 'Retailers - other', 'Other catering premises', 'Retailers - supermarkets/hypermarkets', 'School/college/university', 'Pub/bar/nightclub', 'Takeaway/sandwich shop', 'Hotel/bed & breakfast/guest house', 'Mobile caterer', 'Distributors/Transporters')

```

In [317]:

```
def filter_business_types(business_type):
    # YOUR CODE HERE
    #get_source(get_data())
    k = source.loc[source['BusinessType'] == business_type]

    return k

j = source['BusinessType'].drop_duplicates()
listie = j[0], j[1], j[2], j[24], j[26], j[28], j[39], j[40], j[63], j[78], j[189]
kkk = interact(filter_business_types, business_type = (listie) )
```

	AddressLine1	BusinessName	BusinessType	Lat	Lng	RatingValue	x
0	Bromley	118 Widmore Road	Hospitals/Childcare/Caring Premises	51.406561	0.028132	3	3131.6
5	10 Tower Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.369514	0.093848	4	10447
6	114 Bromley Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.406208	-0.015839	5	-1763.
7	118 London Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.414499	0.007386	5	822.20
8	18 Tower Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.369514	0.093848	4	10447
9	20 Shortlands Road	Abbeyfield	Hospitals/Childcare/Caring Premises	51.404352	-0.000290	5	-32.28

In [313]:

```

def filter_business_types(business_type):
    # YOUR CODE HERE
    source = get_source(get_data())
    london_map = get_map(source)

    data = source.loc[source['BusinessName'] == business_type]

    return data

    raise NotImplementedError()

def get_dropdown_list():
    # YOUR CODE HERE

    j = source['BusinessType'].drop_duplicates()
    listie = j[0], j[1], j[2], j[24], j[26], j[28], j[39], j[40], j[63], j[78], j[18]
    print(listie)
    kkk = interact(filter_business_types, business_type = (listie) )
    return kkk
    raise NotImplementedError()

# DISPLAY THE MAP
data = get_data()
source = get_source(data)
mappy = get_map(data)
dots = mappy.circle(source=source, x='x', y='y', fill_color='Colour', size=10, fill_a
mappy.add_tools(get_hover())
dropdown = get_dropdown_list()
slider = set_interactive()
show(mappy, notebook_handle=True)

```

AddressLine1	BusinessName	BusinessType	Lat	Lng	RatingValue	x	y	Colour
--------------	--------------	--------------	-----	-----	-------------	---	---	--------

In [311]:

```
# You don't have to write anything here
# Display the widgets
HBox([slider, dropdown])

# Why do you think we might get a Bokeh warning displayed when we use our data?
```

```
-----
-----
ValueError                                Traceback (most recent call
last)
<ipython-input-311-9a490881eaa4> in <module>()
      1 # You don't have to write anything here
      2 # Display the widgets
----> 3 HBox([slider, dropdown])
      4
      5 # Why do you think we might get a Bokeh warning displayed when
we use our data?

/opt/conda/lib/python3.5/site-packages/ipywidgets/widgets/widget_box.p
y in HBox(*pargs, **kwargs)
     90 def HBox(*pargs, **kwargs):
     91     """Displays multiple widgets horizontally using the flexib
le box model."""
----> 92     box = Box(*pargs, **kwargs)
     93     box.layout.display = 'flex'
     94     box.layout.align_items = 'stretch'

/opt/conda/lib/python3.5/site-packages/ipywidgets/widgets/widget_box.p
y in __init__(self, children, **kwargs)
     42 def __init__(self, children = (), **kwargs):
     43     kwargs['children'] = children
----> 44     super(Box, self).__init__(**kwargs)
     45     self.on_displayed(Box._fire_children_displayed)
     46

/opt/conda/lib/python3.5/site-packages/ipywidgets/widgets/domwidget.py
in __init__(self, *pargs, **kwargs)
     88
     89 def __init__(self, *pargs, **kwargs):
----> 90     super(DOMWidget, self).__init__(*pargs, **kwargs)
     91
     92     # Deprecation added in 5.0.  TODO: Remove me and corre
sponging traits.

/opt/conda/lib/python3.5/site-packages/ipywidgets/widgets/widget.py in
__init__(self, **kwargs)
    182
    183     Widget._call_widget_constructed(self)
--> 184     self.open()
    185
    186     def __del__(self):

/opt/conda/lib/python3.5/site-packages/ipywidgets/widgets/widget.py in
open(self)
    201         args['comm_id'] = self._model_id
    202
--> 203         self.comm = Comm(**args)
    204         if buffers:
    205             # FIXME: workaround ipykernel missing binary m
```

essage support in open-on-init

```
/opt/conda/lib/python3.5/site-packages/ipykernel/comm/comm.py in __init__(self, target_name, data, metadata, buffers, **kwargs)
    55         if self.primary:
    56             # I am primary, open my peer.
--> 57             self.open(data=data, metadata=metadata, buffers=buffers)
    58         else:
    59             self._closed = False
```

```
/opt/conda/lib/python3.5/site-packages/ipykernel/comm/comm.py in open(self, data, metadata, buffers)
    92             data=data, metadata=metadata, buffers=buffers,
    93             target_name=self.target_name,
--> 94             target_module=self.target_module,
    95         )
    96         self._closed = False
```

```
/opt/conda/lib/python3.5/site-packages/ipykernel/comm/comm.py in _publish_msg(self, msg_type, data, metadata, buffers, **keys)
    63         data = {} if data is None else data
    64         metadata = {} if metadata is None else metadata
--> 65         content = json_clean(dict(data=data, comm_id=self.comm_id, **keys))
    66         self.kernel.session.send(self.kernel.iopub_socket, msg_type,
    67                                 content,
```

```
/opt/conda/lib/python3.5/site-packages/ipykernel/jsonutil.py in json_clean(obj)
    165         out = {}
    166         for k,v in iteritems(obj):
--> 167             out[unicode_type(k)] = json_clean(v)
    168         return out
    169         if isinstance(obj, datetime):
```

```
/opt/conda/lib/python3.5/site-packages/ipykernel/jsonutil.py in json_clean(obj)
    165         out = {}
    166         for k,v in iteritems(obj):
--> 167             out[unicode_type(k)] = json_clean(v)
    168         return out
    169         if isinstance(obj, datetime):
```

```
/opt/conda/lib/python3.5/site-packages/ipykernel/jsonutil.py in json_clean(obj)
    151
    152         if isinstance(obj, list):
--> 153             return [json_clean(x) for x in obj]
    154
    155         if isinstance(obj, dict):
```

```
/opt/conda/lib/python3.5/site-packages/ipykernel/jsonutil.py in <listcomp>(.0)
    151
    152         if isinstance(obj, list):
--> 153             return [json_clean(x) for x in obj]
    154
```

```
155     if isinstance(obj, dict):

/opt/conda/lib/python3.5/site-packages/ipykernel/jsonutil.py in json_c
lean(obj)
171
172     # we don't understand it, it's probably an unserializable
object
--> 173     raise ValueError("Can't clean for JSON: %r" % obj)

ValueError: Can't clean for JSON: <function filter_business_types at 0
x7fd7db058b70>
```

Question 3(c) [5 marks]

Describe a use case for which an application like this would be useful, and suggest one way which it could be improved.

이와 같은 유용한 어플리케이션 사례는 코로나 맵이 있습니다. 요즈음 코로나 바이러스 문제로 인하여 확진자가 발생하면 동선을 나타나는 맵을 나라별, 지역별 코로나 맵을 만들어서 어플리케이션 이용하는 사람들에게 확진자가 어디를 다녀왔는지 시각적으로 알아 볼 수 있습니다. 이를 개선시킬 방법으로는 레이팅 벨류가 0부터 5까지 구분 되는 것 처럼, 일자별로 구분되게 필터링을 만들어서 좀 더 이용자가 알아보기 쉽고 유용하게 어플리케이션을 사용하는 방법이 있습니다.

In []: