CS336 · Spring 2026 · Lecture 15

从预训练到可控助手：SFT、偏好数据、PPO 与 DPO

如何阅读这份自学增强讲义

原始英文幻灯片完整保留；每组原页之后紧接对应中文讲解。书签可跳转到原页与讲解。页码中的“原页”始终指原始 PDF 页码。

中文部分为自学补充；课堂转述、原论文结论与编者推导应按文中标记区分。第三方保存的字幕仅用于检索定位，不等同于教师审校逐字稿。

学习目标：读完本讲，应能解释为什么预测网页下一个词的模型不自动成为可靠助手；能设计示范数据与偏好数据，区分风格、知识、工具行为和安全边界；能从 KL 正则化奖励目标推导 DPO，手算一次偏好损失，并识别奖励过度优化、熵下降和概率失准。

先修：自回归分解、交叉熵、梯度下降、期望与条件概率。后半讲还需要 KL 散度和 sigmoid，相关定义将在使用处补齐。阅读主线为原页1–30的SFT及中期训练、31–48的偏好监督、49–61的算法、62–65的副作用。原稿为 Stanford CS336 Spring 2026 第15讲，65页；保留全部英文、公式、图片。中文解释插在对应原页组之后。

来源与阅读约定：原课件是主依据；“课堂补充”仅为带时间戳的录像字幕转述，字幕来自第三方公开缓存，可能有转写错误，非教师审校逐字稿。“编者补充”中的手算、推导和实践检查用于补足自学依赖，不冒充课堂原话。原页中的行业现状、模型名称和实验排名均按当时语境理解，不能外推为所有模型或今天的结论。引用索引位于文末。


Lecture 15

"After pretraining" (mid/posttraining)

CS336

The class thus far

We've now covered pre-training, which gets you to GPT3.. But how do we get to instructGPT?












Instruction following is a remarkable form of control

Prompt: Can you generate a pyplot for the following data: $x = [1, 3, 5, 6, 8], y1 = [2, 3, 5, 18, 1], y2 = [3, 5, 6, 8, 1], y3 = [5, 1, 2, 3, 4], y4 = [9, 7, 2, 3, 1]$. I want $y1, y2$ to be in the same plot, but $y3$ is in another plot next to that plot, $y4$ is in below. I want the legend of $y1$ to be "bob", $y2$ to be "alice", $y3$ to be "bilbo", $y4$ to be "allie". I want the x-axis to be labeled with "time" and y axis to be labeled with "money". I want to add a 10 %-40% random error bar to each curve, through all times (including non-integers). I want smoothed curves to show the plot, and smoothed error bar. Do not use linear interpolation, use smooth interpolation! I want to also add some small zig-zag to the smoothed curve to make it look more real. I want to put a baseline as the mean of each line. I want to put a pie chart below indicating the fraction of the four people in each time step. I also want an animation to show how the fractions are changing in the pie chart in **continuous time**. Interpolate the missing fractions! I also want vertical line animation in other three plots to match the pie chart. I want the fanciest plot. Please add as many fancy things as possible.

Here is a possible code to generate a pyplot for the following data, with some comments to explain the steps:

GPT-4: [We give two snapshots from the animation resulting from the produced code]



Text example from [Bubeck et al 2023]

第 15 讲 · 原页 1–3 · 中文讲解

为什么预训练之后还需要训练

从续写器到助手

预训练让模型学会在许多文本分布中续写：新闻、论坛争吵、教程、小说和问答都可能出现。给它一个问题，最大化文本似然并没有要求它必须扮演助手、准确回答或遵守复杂格式。因此“能生成相关文本”和“能稳定执行用户指令”是不同目标。第2页从基础模型到聊天系统的图强调用途变化；不能把图中产品演进理解成只要换一个提示词就完成了训练。

读图与编者补充

第3页的长提示要求同时控制绘图数据、子图布局与呈现形式，下方展示模型生成的图。这个例子说明指令能够提供细粒度控制，不是对所有代码正确性的证明。设用户要求“用三个要点比较两种算法”，模型可能知道算法本身，却仍续写成文章。后训练的任务是提高所需行为在给定提示下的概率。基础能力决定可调用的知识和技能，后训练改变调用方式；两者通常缺一不可。此例也提示评价要拆成内容正确、约束遵循、格式正确三个维度，不能只凭输出看起来漂亮。

本节参考（完整书目见讲义末尾）：[slides]

Goal today: enable better, tighter controls over LM output

Pretraining data isn't quite what we want (but it scales)..

Can we collect data of behaviors we *do* want and train the LM?

1. What does that data look like?
2. How do we best make use of that data?
3. Do we need scale for this?

Caveat: post-training information is pretty sparse!

Rich information from the pre-chatgpt competition

- Stiennon 2020 (RLHF paper) – contains annotation guidelines, etc
- Bai 2022 (Anthropic HH) – details on how to set up safety annotation, etc


Poor information in modern times..

- Open source: lots of distillation, not too public in open-source release notes
- Closed source: ‘secret sauce’ for data.

> In July 2023, a manager ordered workers to study GPT-4's responses closely and figure out why they outperformed Bard's. "Try to come up with feedback that we can share so that experts can write responses better than GPT4 or at least the same," the manager wrote.
>
> Scale AI also created a spreadsheet that compared 1,729 Bard rewrites directly to ChatGPT in October 2023. Each rewrite was rated with labels like "worse than GPT4" or "Needs Some Fixes." In one example, a worker rewrote a Bard review of a nursery chair that managers stamped "worse than GPT" because it "lacks detail compared to GPT4."

Where today's lecture fits in

Standard approach – imitation (SFT) followed by reinforcement ('RL' HF)



Part 1: the 'supervised finetuning' part

[Ouyang 2022]

第 15 讲 · 原页 4–6 · 中文讲解

后训练的问题分解与证据边界

三步流水线

第6页流程图从左到右是：收集提示及示范回答，做监督微调SFT；让模型为同一提示生成多个回答，由标注员比较，再拟合奖励模型；利用奖励优化回答策略。红框标出的左侧是本讲前半部分。SFT数据是(x,y)，其中x为输入、y为示范；偏好数据是(x,y_w,y_l)，下标w、l分别指胜出与落选回答。奖励模型把完整回答映射到一个标量，策略模型则生成token，两者职能不同。

公开资料能告诉我们什么

第4页提出数据长什么样、怎样利用以及是否需要规模三个问题。第5页说明后训练配方特别依赖数据，而公开信息有限。旧论文的完整标注规范适合学习机制，但不是所有新系统都照搬的证明；开放模型使用教师模型合成数据，也不能自动还原闭源系统的人类采集过程。本讲以公开流程讲清原理，实验数字只在相应模型、任务和评价条件下成立。


课堂补充 · **00:05:53–00:06:47**


讲者把流程概括为示范模仿后再进行反馈优化，并说明SFT部分主要聚焦数据：训练机制与预训练相近，真正改变的是要拟合的回答分布。这里“相近”不等于所有训练掩码、数据比例和超参数完全相同。

本节参考（完整书目见讲义末尾）：[slides] · [instructgpt] · [stiennon] · [captions]


What are the ingredients in SFT?

The training data





The **method**



Training data


We've already seen some of the major types of instruction data..

Let's talk about two more details about instruction tuning datasets


1. What's actually inside these datasets?

2. What matters in building 'high performance' instruction tuning data?

Progression of SFT data (in the open world)



FLAN




Self-instruct




Alpaca



ShareGPT/Vicuna




Open Assistant



WizardLM



Tulu3



Nemotron
Tool use etc.

第 15 讲 · 原页 7–9 · 中文讲解

SFT数据如何从任务集走向交互轨迹

沿数据来源理解演进

FLAN把已有NLP任务包装成指令；Self-Instruct利用模型生成指令与回答；Alpaca展示了合成指令数据的路径；ShareGPT/Vicuna利用用户分享的聊天交互；OpenAssistant侧重众包对话；WizardLM等尝试提高合成指令的复杂度；Tülu 3整合多能力配方；Nemotron示例则进入工具和代理场景。第9页是开放生态的示意发展脉络，不是所有项目严格继承前一个项目，也不是质量从左到右必然提升的排行榜。

编者补充：先定义一个样本是什么

“10万条数据”没有固定训练含义。一条可能是一句分类答案，也可能是含几十次工具调用的对话。可比较的描述至少包括提示来源、回答来源、轮数、token数、能力分布、过滤方式和是否重叠于评测集。第7页把数据与方法并列：即使使用同样的交叉熵，不同混合比例也会改变模型优化的行为。若每个样本等概率抽取，长样本在按token求和的损失中通常贡献更大；若逐样本平均，又会形成不同权重。这解释了为什么“数据集名称相同”仍不足以复现实验。

本节参考（完整书目见讲义末尾）：[slides] · [tulu3]

FLAN – random examples

Stephanie - Can you finalize the attached and have it signed. I need to initial it, but it needs to be signed by Brad Richter. Thanks. Write a subject line for this email.	Ronald Chisholm LOI
Ahold to Sell Spain Operations to Permira (AP) AP - The Dutch supermarket retailer Ahold, seeking to streamline global operations and reduce debt, said Sunday it will sell its holdings in Spain to Permira Funds for about #36;849 million. What is this text about? OPTIONS: - World - Sports - Business - Science/Tech	Business
Write highlights for this article: Sauntering down leafy avenues past typical Dutch step-gabled buildings, carpets of crocuses, the occasional cyclist whooshing quietly by and the sun bouncing off the canal, I can think of few more pleasant places to spend a spring weekend than The Hague. […]The most prized Dutch colony was apparently run from The Hague (aka 'the Widow of Indonesia'). For summer: the excellent Grapes & Olives and the Café de Bieb on Veenkade will have boats on a newly renovated bit of canal, with music and boat trips planned, including a tour at the Kompaan brewery (I can vouch for the product). My art gorging finishes at the Panorama, an extraordinary, 14 ft-high circular panorama of The Hague's seaside resort, Scheveningen, painted by Hendrik Mesdag. I take a 15-minute tram to the place itself and gorge on scallops and sole at Catch by Simonis on the harbour front. The Hague has netted a new fan. British Airways (0844 493 0787, www.ba.com) flies to Rotterdam Den Haag (half-hour taxi) from £100 return. For tours with Remco Dörr, email remco.dorr@hotmail.com. Double rooms at the Carlton Ambassador (00 31 70 363 0363, www.carlton.nl/ambassador) cost from £84, room only. More information on travel in The Netherlands at www.holland.com.	The least known of the Dutch cities, The Hague was a village until 1806. It owes its growth to Louis Bonaparte, Napoleon's brother, who ruled here. The city has a wealth of art, including Vermeer's 'Girl With A Pearl Earring'
Here is some data about a restaurant: name = Aromi, eatType = coffee shop, food = English, customer rating = 5 out of 5, area = city centre. Write a sentence that includes the following data about a restaurant	In the city centre there is a coffee shop with a customer rating of 5 out of 5 called Aromi which serves English food.

第 15 讲 · 原页 10–10 · 中文讲解

FLAN：把旧任务转换成指令的收益与局限

逐项读原表

原表左列是任务输入，右列是目标输出。邮件正文配上“写主题”得到主题预测；新闻配上类别列表变成分类；长文配上“写要点”变成摘要；餐馆属性变成数据到文本。共同操作是把原本不同标签空间的任务统一为条件生成。这使一个语言模型可在同一训练框架中学习多任务，而无需为每种任务另接分类头。

编者补充：指令自然度与事实一致性

这种转换保留了原任务的数据限制。分类答案“Business”足以完成基准，却未必符合聊天用户希望看到解释的习惯；摘要标签也未必忠实于当前截取的输入。应分别核查标签正确性、是否遗漏必要上下文、输出语气和任务是否对应真实需求。假设餐馆字段只有菜系和位置，目标却添加“价格便宜”，模型会收到把未提供事实补全的监督。模板化指令本身不是错误，问题是它是否覆盖最终使用场景。不能从本页推导出“FLAN无用”或“所有摘要数据均有幻觉”。

课堂补充 · 00:11:24–00:14:24

讲者以邮件和摘要例子解释已有数据集改写为指令的方式，并提醒原数据的缺点也会被继承。他把后续的小规模高质量数据成功与基础模型的泛化能力联系起来；这是质量与数量取舍的经验讨论，不是少数据永远胜出的定律。

本节参考（完整书目见讲义末尾）：[slides] · [captions]

Alpaca – random examples

Give three tips for staying healthy.	1.Eat a balanced diet and make sure to include plenty of fruits and vegetables. 2. Exercise regularly to keep your body active and strong. 3. Get enough sleep and maintain a consistent sleep schedule.
What does “algorithm” mean?	An algorithm is a step-by-step set of instructions used to solve a problem or achieve a goal. It is a process of breaking down complex tasks into smaller, more manageable steps. Algorithms can be used to find the shortest path from one place to another, sort data, or render data from an immense database in a few seconds.
Find the average number in a list.	def avg_list(nums): total = 0 for n in nums: total += n return total / len(nums) print(avg_list([4, 3, 6, 10, 8])) # Output 6.4

OpenAssistant – random examples

Can you write a short introduction about the relevance of the term "monopsony" in economics? Please use examples related to potential monopsonies in the labour market and cite relevant research.	"Monopsony" refers to a market structure where there is only one buyer for a particular good or service. In economics, this term is particularly relevant in the labor market, where a monopsony employer has significant power over the wages and working conditions of their employees. […]. Overall, the concept of monopsony is essential to understanding the dynamics of labor markets and the impact of market power on workers. Further research is needed to understand the extent and impact of monopsonies on the economy and to develop policies to address this issue. References: Bivens, J., & Mishel, L. (2013). The Pay of Corporate Executives and Financial Professionals as Evidence of Rents in Top 1 Percent Incomes. Journal of Economic Perspectives, 27(3), 57-78.
My kid needs to do a science project for elementary school, what are some cheap but fun projects to do?	There are many cheap and fun science projects that elementary school kids can do! Here are a few ideas: 1. Make a homemade lava lamp: Fill a clear plastic bottle with water and vegetable oil, add a few drops of food coloring, and then drop in an Alka-Seltzer tablet. The reaction will cause bubbles to rise and fall like a lava lamp. […]7. Create a solar oven: Using a pizza box, aluminum foil, and plastic wrap, create a solar oven that can cook s'mores or other small snacks. 8. Explore magnets: Using magnets and a variety of objects, have your child experiment with magnetism to see what objects are attracted to magnets and which ones are not. These are just a few ideas to get you started! There are many more cheap and fun science projects that your child can do with household items and a little creativity.

第 15 讲 · 原页 11–12 · 中文讲解

Alpaca与OpenAssistant：聊天风格、详细知识和质量

对照原页的回答

Alpaca示例从“给三条建议”“解释算法”“求列表平均值”出发，回答比单个分类标签更像助手。OpenAssistant的劳动市场问题进一步要求概念、例子和参考资料，科学项目问题则要求适合儿童且低成本的建议。这些示范同时教会任务内容、回答粒度、语气和组织方式。人工撰写与模型合成都可能有缺陷，数据来源不是正确性的替代指标。

编者补充：一次可核对的小检查

第11页列表为[4,3,6,10,8]，和为31，长度为5，所以均值为6.2；原示例尾部写Output 6.4，与计算不符。原页保持不变，读者应把它视为训练目标审查的真实提醒。若目标代码压成一行，还应区分PDF排版导致的换行丢失和源数据真实语法。第12页的引用条目只是示范中的文本，不能因为附有作者和期刊就当作已核实文献。详细回答提升可读性，也扩大了每条训练样本需要验证的事实范围。

从样本质量到模型行为

在SFT中，正确均值和错误均值都只是目标token；损失函数并不知道算术事实。数据筛选可对可执行代码做测试，对数字做重算，对引用做存在性和相关性核对。否则模型可能同时学到良好说明结构与错误细节。这也解释了为何“看起来像高质量回答”不足以定义高质量数据。

本节参考（完整书目见讲义末尾）：[slides]

Nemotron-SFT-OpenCode-v1

What are the key differences between using `async/await` and `.then()` for handling promises in JavaScript, and when should I prefer one approach over the other in terms of readability and error handling?	{"role": "assistant", "content": "I'll analyze the key differences between `async/await` and `.then()` for handling promises in JavaScript based on the provided AGENTS.md instructions.", "tool_calls": [{ "id": "call_132a55728f6c498fbeac3b95", "type": "function", "function": { "name": "skill", "arguments": "{\"name\":\"bash-skills\"}" } }]}
I'm building a simple calculator app and need to decide between using integers or floating-point numbers for all calculations. What are the trade-offs of each approach, and which would you recommend for a beginner-friendly calculator that handles basic arithmetic operations?	"role": "assistant", "content": "I'll help you decide between integers and floating-point numbers for your calculator app. Let me analyze the trade-offs and provide a recommendation based on the requirements in AGENTS.md.", "tool_calls": [{"id": "call_b06182c280514fc7bd1d3ae4","type": "function", "function":{"name": "todowrite","arguments": "{\"todos\":[{\"content\":\"Review the AGENTS.md file for calculator data typerequirements\",\"id\":\"1\",\"priority\":\"high\",\"status\":\"in_progress\"},{\"content\":\"Analyze trade-offs between integers and floating-point numbers\",\"id\":\"2\",\"priority\":\"high\",\"status\":\"pending\"},{\"content\":\"Check available skills for relevant guidance\",\"id\":\"3\",\"priority\":\"medium\",\"status\":\"pending\"},{\"content\":\"Provide recommendation for beginner-friendly calculator\",\"id\":\"4\",\"priority\":\"high\",\"status\":\"pending\"}]}"}}]

What's varying across these?

"Chattiness" – FLAN is (usually) valid data, but people don't want to talk to a NLP benchmark. Later datasets move towards longer, more detailed responses

Detail – OASST goes into much more detail about various factual pieces of knowledge. As we will see, this can be both a pro and a con.

Tool use – SFT in the last year or two has also been shifting much more towards tool/use, agentic downstream applications.

What did we notice across the datasets?

These datasets vary in many ways…

- **Length and bullet points** (style variations)
- **References, other complex knowledge**

Less visible, but important aspects..

- **Scale**
- **Safety**

How do these factors affect the model?

第 15 讲 · 原页 13–15 · 中文讲解

工具调用也是被监督的行为

读懂结构化对话

第13页右侧不仅有assistant.content，还有tool_calls列表、调用id、函数名与JSON参数。它展示模型需要决定何时说话、何时调用工具、调用什么以及如何提供参数。文中的AGENTS.md、skill、todowrite是样本环境中的对象；不是所有应用都拥有这些工具，也不是本讲要求读者运行它们。第14–15页把变化概括为聊天化、细节、工具使用、规模和安全，提醒我们数据集区别不限于知识领域。

编者补充：从单轮回答到轨迹

一个完整工具样本可写为用户问题→助手调用→工具观察→助手回答。工具观察是环境提供的条件，通常不应被误当作助手必须凭空预测的答案；训练掩码须符合所选配方。若只有“我要读取文件”的文字而没有真正调用及结果，就不能教会可靠闭环。检查工具数据时应核对名称和参数schema、调用id与返回结果是否匹配、结果是否支持最终结论，以及失败后有没有重试或解释。仅把聊天回答变成长JSON不等于学会工具使用。

课堂补充 · **00:16:50–00:18:52**

讲者指出示例数据正在显式监督代理所需的计划、调用及结构化接口，而不仅是自然语言回答。这是对所示开放数据趋势的描述，不代表每种模型或每个任务都需要同样的计划格式。

本节参考（完整书目见讲义末尾）：[slides] · [captions]

Style variations in data and models

Models vary *a lot* in response length..


Table 1: Instruction datasets investigated in this work. CoT and FLAN V2 are sampled to 100K to match the sizes of other datasets. We report the average number of conservation turns ($\bar{N}_{rounds}$), average length of prompts ($\bar{L}_{prompt}$), average length of completion ($\bar{L}_{completion}$).

Datasets	**Sourced from**	**# Instances**	$\bar{N}_{rounds}$	$\bar{L}_{prompt}$	$\bar{L}_{completion}$
SuperNI [48]	NLP datasets + Human-written Instructions	96,913	1.0	291.1	38.7
CoT [50]	NLP datasets + Human-written CoTs	100,000	1.0	266.0	53.2
Flan V2 [31]	NLP datasets + Human-written Instructions	100,000	1.0	355.7	31.2
Dolly [12]	Human-written from scratch	15,011	1.0	118.1	91.3
Open Assistant 1 [26]	Human-written from scratch	34,795	1.6	34.8	212.5
Self-instruct [47]	Generated w/ vanilla GPT3 LM	82,439	1.0	41.5	29.3
Unnatural Instructions [23]	Generated w/ Davinci-002	68,478	1.0	107.8	23.6
Alpaca [43]	Generated w/ Davinci-003	52,002	1.0	27.8	64.6
Code-Alpaca [6]	Generated w/ Davinci-003	20,022	1.0	35.6	67.8
GPT4-Alpaca [36]	Generated w/ Davinci-003 + GPT4	52,002	1.0	28.0	161.8
Baize [52]	Generated w/ ChatGPT	210,311	3.1	17.6	52.8
ShareGPT[3]	User prompts + outputs from various models	168,864	3.2	71.0	357.8

[Wang+ 2023]

When evaluating by *preferences*, style matters.

We see very strong length effects (in both humans and GPT-based evaluations)



[Dubois+ 2023]

What about benchmarks?

These factors are (mostly) not that relevant for other benchmark perfs

Table 3: Comparison of different instruction tuning datasets, showing that different instruction-tuning datasets can excel in different aspects, and mixtures perform best on average. Cells are blue if the finetuning boosts the vanilla LLAMA performance, and orange if the finetuning hurts the performance.

	MMLU (factuality)	GSM (reasoning)	BBH (reasoning)	TydiQA (multilinguality)	Codex-Eval (coding)	AlpacaEval (open-ended)	Average
	EM (0-shot)	EM (8-shot, CoT)	EM (3-shot, CoT)	F1 (1-shot, GP)	P@10 (0-shot)	Win % vs Davinci-003	
Vanilla LLaMa 13B	42.3	14.5	39.3	43.2	28.6	-	-
+SuperNI	49.7	4.0	4.5	**50.2**	12.9	4.2	20.9
+CoT	44.2	40.0	41.9	47.8	23.7	6.0	33.9
+Flan V2	**50.6**	20.0	40.8	47.2	16.8	3.2	29.8
+Dolly	45.6	18.0	28.4	46.5	31.0	13.7	30.5
+Open Assistant 1	43.3	15.0	39.6	33.4	31.9	58.1	36.9
+Self-instruct	30.4	11.0	30.7	41.3	12.5	5.0	21.8
+Unnatural Instructions	46.4	8.0	33.7	40.9	23.9	8.4	26.9
+Alpaca	45.0	9.5	36.6	31.1	29.9	21.9	29.0
+Code-Alpaca	42.5	13.5	35.6	38.9	34.2	15.8	30.1
+GPT4-Alpaca	46.9	16.5	38.8	23.5	**36.6**	63.1	37.6
+Baize	43.7	10.0	38.7	33.6	28.7	21.9	29.4
+ShareGPT	49.3	27.0	40.4	30.5	34.1	**70.5**	42.0
+Human data mix.	50.2	38.5	39.6	47.0	25.0	35.0	39.2
+Human+GPT data mix.	49.3	**40.5**	**43.3**	45.6	35.9	56.5	**45.2**

第 15 讲 · 原页 16–18 · 中文讲解

风格偏好与任务能力必须分开测量

三页图表的读法

第16页表格比较指令数据的规模、提示和回答平均长度，说明样本长度差异很大。第17页上图横轴是偏好列表的比例，下图是偏好更长回答的比例；不同点的形状和颜色区分模型与标注系统。超过50%意味着在相应比较中更常选这种风格，并不直接说明其事实更正确。第18页把MMLU、GSM、BBH、TyDiQA、代码及AlpacaEval并排：同一数据配方可能主要改变开放问答偏好，知识或推理列未必同比提高。

编者补充：混杂因素的小实验

设模型A的回答更准确但较短，B的信息量相同却有列表和礼貌开场；若盲评只给一个总体偏好标签，风格可能改变胜率。要识别能力增益，可在事实内容固定时控制长度与格式，再比较偏好；另用可核验答案评估正确率。报告原始胜率、长度分布和控制风格后的结果能帮助诊断，但长度控制也可能去掉真实所需的解释，因此不是绝对真值。课堂的警告是别把互动偏好变化等同于所有能力变化，不是风格不重要。

课堂补充 · **00:19:39–00:21:58**

讲者强调列表与细节会影响偏好，也会塑造聊天系统语气；接着把风格控制与能力控制分开。用户体验是一个真实目标，但它需要与事实、推理、代码等维度一起评价。

本节参考（完整书目见讲义末尾）：[slides] · [camels] · [alpacafarm] · [captions]

References, complex knowledge, and factuality

Consider this example from open assistant:

Can you write a short introduction about the relevance of the term "monopsony" in economics? Please use examples related to potential monopsonies in the labour market and cite relevant research.	"Monopsony" refers to a market structure where there is only one buyer for a particular good or service. In economics, this term is particularly relevant in the labor market, where a monopsony employer has significant power over the wages and working conditions of their employees. […]. Overall, the concept of monopsony is essential to understanding the dynamics of labor markets and the impact of market power on workers. Further research is needed to understand the extent and impact of monopsonies on the economy and to develop policies to address this issue. **References: Bivens, J., & Mishel, L. (2013). The Pay of Corporate Executives and Financial Professionals as Evidence of Rents in Top 1 Percent Incomes. Journal of Economic Perspectives, 27(3), 57-78.**

What is this example teaching the model?

1. Teaching the model about Bivens J & Mishel, L
2. Teaching the model to output citations when asked to do so


(But by what mechanism? Does the model know about cites?)

Knowledge extraction and alignment


Folklore: Fine-tuning a model on ‘facts it doesn’t know’ makes it hallucinate

Hallucination and Behavior Cloning

- Conceptual model of fine-tuning neural nets for question answering
  - Neural net has “knowledge graph” stored in weights, **with confidence level on each edge**
  - Small scale fine-tuning learns a simple function that operates on the knowledge graph and outputs token predictions
    - e.g. *Q: what is the genre of Star Wars. A: Sci-fi*
- If you clone on correct answers that aren’t in the knowledge graph, you’re teaching the net to hallucinate
  - Suppose labeler knows about spinoff film, but net’s knowledge graph doesn’t …
  - Clone on: *Q: what was the name of spinoff film centering on Han Solo. A: Solo*
- If you clone on incorrect answers that are in knowledge graph, then you’re training net to withhold information
  - Suppose labeler doesn’t know about Tom Simpson but net does, trains with “I don’t know”
- Behavior cloning target should depend on network’s knowledge (which is unknown to experimenter)
  - Models that are trained using targets computed by another agent will always have hallucination problem



[Schulman 2023]



[Gekhman 2023]

Takeaways on knowledge extraction and alignment

1. You may not want to fine-tune on tail knowledge, even that's the LM use case
2. In principle, 'RL' style correctness feedback could help
3. Knowledge storage and extraction in LMs is messy, and nuanced.

第 15 讲 · 原页 19–21 · 中文讲解

为什么事实正确的SFT数据仍可能诱发幻觉

两个学习任务被混在同一序列里

第19页引用示例同时教“这篇文献是什么”和“回答时应该给文献”。自回归损失只奖励匹配目标字符串，不能自动保证模型只在掌握证据时引用。如果它更容易学会引用模板而没记住事实，迁移到新问题时便可能生成貌似正式的假引用。这里的风险是泛化方式，而不是说训练目标中的每条事实本身错误。

读图、来源校正与成立边界

第20页右上图随epoch推进，已知知识样本先被拟合，未知知识样本较慢；下图开发集表现先改善后下降。它支持特定闭卷问答实验中“继续拟合新知识伴随幻觉风险”的观察，不能推出SFT不可能学新知识。原页把Gekhman标为2023，所对应论文实际为2024年EMNLP论文，原页不改。模型“知道”通常由测试行为操作性定义，不是直接读到一个完整知识库；长尾也没有通用硬阈值。

编者补充：该如何设计监督

可把缺证据时的处理也纳入数据：有可靠上下文就依据它回答，没有依据则表示不确定或检索，而不是每个问题都强制给精确引用。奖励反馈若能区分正确引用、错误引用与合适弃答，且模型已有可用的不确定性信号，就可能帮助学习何时输出；若奖励只喜欢自信长文，它会加重问题。后续RLHF也不能自动保证事实性或校准。

课堂补充 · **00:26:27–00:28:07**


讲者给出的解释是条件性的：假如模型内部存在区分知道与不知道的信号，基于自身输出的反馈可能把它关联到引用行为；若根本没有这种信息，RL也不能凭空解决。他明确把这个机制解释称作一种直观故事。

本节参考（完整书目见讲义末尾）：[slides] · [gekhman] · [captions]

Safety


LMs are widely deployed to end-users, and need some safety controls

Misinformation



[Goldstein+ 2023]

Scams and spam



[Kang+ 2023]

Safety SFT in the wild

Details are pretty sparse

Finetuning data. The quality and design of safety training data has a profound impact on performance. Through extensive ablations, we find that the quality is more critical than the quantity. We mainly use human-generated data collected from our data vendors, but find that it can be prone to errors and inconsistencies — particularly for nuanced safety policies. To ensure the highest quality data, we developed AI-assisted annotation tools to support our rigorous quality assurance processes. In addition to collecting adversarial prompts, we also gather a set of similar prompts, which we refer to as **borderline prompts**. These are closely related to the adversarial prompts but with a goal to teach the model to learn to provide helpful responses, thereby reducing the false refusal rate (FRR).

Beyond human annotation, we also leverage synthetic data to improve the quality and coverage of our training datasets. We utilize a range of techniques to generate additional adversarial examples, including in-context learning with carefully crafted system prompts, guided mutation of seed prompts based on new attack vectors, and advanced algorithms including Rainbow Teaming (Samvelyan et al., 2024), based on MAP-Elites (Mouret and Clune, 2015), which generate prompts constrained across multiple dimensions of diversity.




Figure 18 Influence of model size on safety mix design for balancing violation rate (VR) and false refusal rate (FRR). Each point of the scatterplot represents a different data mix balancing safety and helpfulness data. Different model sizes retain varying capacities for safety learning. Our experiments show that 8B models require a higher proportion of safety data relative to helpfulness data in the overall SFT mix to achieve comparable safety performance to 70B models. Larger models are more capable of discerning between adversarial and borderline context, resulting in a more favorable balance between VR and FRR.

Examples? ~ few thousand in Llama 2

第 15 讲 · 原页 22–23 · 中文讲解

安全调优不是把所有问题都拒绝

目标与读图

第22页用误导信息和欺诈等风险说明部署后的行为约束。第23页横轴False Refusal Rate为良性请求被错误拒绝的比例，纵轴Violation Rate为危险请求上违反安全要求的比例，理想方向是左下方。曲线上不同点表示安全数据配比，增大拒绝倾向可能降低违规同时增加误拒；比较模型时必须同时看两轴，不能只报告一个更低的违规率。该图图例是Llama 3的8B与70B，而页脚关于“几千条”的说明指Llama 2，不能把两个对象混为一谈。

编者补充：用两个分母理解取舍

假设100个危险请求有10个得到不应提供的回答，违规率为10%；另100个正常请求有15个被拒绝，误拒率为15%。若全部拒绝，前者可降至0，后者却变成100%，并非好助手。边界样本特别重要，例如“结束一个Python进程”是正常计算机任务，不能仅因含有kill等词就拒绝。训练需要同时示范合适拒绝、正常帮助、澄清含糊请求与安全替代建议。两个评测集合的定义、难度和覆盖范围决定数字含义，不能脱离测试集比较。

本节参考（完整书目见讲义末尾）：[slides]

Pipeline with most details

Tülu 3: Pushing Frontiers in Open Language Model Post-Training

Nathan Lambert[♥1,*] Jacob Morrison[♥1] Valentina Pyatkin[♥1,2] Shengyi Huang[♥1] Hamish Ivison[♥1,2]
Faeze Brahman[♥1] Lester James V. Miranda[♥1]

Alisa Liu[2] Nouha Dziri[1] Xinxi Lyu[1] Yuling Gu[1] Saumya Malik[1] Victoria Graf[2] Jena D. Hwang[1]
Jiangjiang Yang[1] Ronan Le Bras[1] Oyvind Tafjord[1] Chris Wilhelm[1]

Luca Soldaini[1] Noah A. Smith[1,2] Yizhong Wang[1,2] Pradeep Dasigi[1] Hannaneh Hajishirzi[1,2]
[1]Allen Institute for AI, [2]University of Washington

Safety	Tülu 3 CoCoNot	10,983	10,983	10,983	Brahman et al. (2024)
& Non-Compliance	Tülu 3 WildJailbreak$^{\alpha,\downarrow}$	50,000	50,000	26,356	Jiang et al. (2024)
	Tülu 3 WildGuardMix$^{\alpha,\downarrow}$	50,000	50,000	26,356	Han et al. (2024)

Main safety approach – extract scenarios from users

WILDCHAT: 1M CHATGPT INTERACTION LOGS IN THE WILD

WARNING: THE APPENDIX OF THIS PAPER CONTAINS EXAMPLES OF USER INPUTS REGARDING POTENTIALLY UPSETTING TOPICS, INCLUDING VIOLENCE, SEX, ETC. READER DISCRETION IS ADVISED.

Wenting Zhao[1*] **Xiang Ren**[2,3] **Jack Hessel**[2] **Claire Cardie**[1] **Yejin Choi**[2,4] **Yuntian Deng**[2*]
[1]Cornell University [2]Allen Institute for Artificial Intelligence
[3]University of Southern California [4]University of Washington
{wz346,cardie}@cs.cornell.edu,{xiangr,jackh,yejinc,yuntiand}@allenai.org
*Equal Contribution




Figure 2: NONCOMPLIANCE Taxonomy and examples in each sub-category. Desired responses for these categories are not always direct refusal but can take various forms outlined in Appendix Table 4.




Figure 1: The two steps of the WILDTEAMING framework: MINE (in-the-wild user-written jailbreak tactics) and COMPOSE (jailbreak tactics into diverse adversarial attacks).

第 15 讲 · 原页 24–25 · 中文讲解

从真实交互中挖掘安全与非顺从场景

读懂数据与流程图

第24页展示Tülu 3安全与非顺从相关来源：CoCoNot、WildJailbreak、WildGuardMix。表格是各来源及采样量的一段截取，不应直接把显示的所有列相加。第25页的WildChat提供真实使用场景线索；左下分类还包括错误前提、信息不足、能力限制等“应不直接顺从”的情形，范围比违法或有害请求更广。右下图先从真实交互提取越狱策略，再与不同基础请求组合，产生多样测试或训练场景。

编者补充：可复用的数据生产闭环

闭环可理解为收集场景→去重与隐私处理→区分风险及正常边界→撰写目标行为→独立复核→在未见场景上评测。抽取的是失败机制，不能只是记住几个危险关键词。若训练与测试都来自同一套模板替换，即使分数高也可能只是模板识别。对错误前提问题，理想回答常是温和纠正；对信息不足问题，理想回答常是追问；对真实风险才可能拒绝。把这些都标成统一拒绝语，会牺牲帮助性。


课堂补充 · **00:30:29–00:32:13**

讲者用公开流程解释从用户交互发现不安全行为和越狱尝试，再补上期望回答的做法。它提供数据来源的思路，不意味着这些材料完整揭示了所有闭源公司的管线。

本节参考（完整书目见讲义末尾）：[slides] · [tulu3] · [captions]

Safety-tuning with just a little data

Significant improvements to safety with ~500 samples.



Adding 500 Alpaca-style examples makes models follow safety guidelines

Putting it together – SFT Data

1. Instruction fine-tuning (SFT) works works best when we are just extracting pre-training behaviors, not adding new ones

2. Adding (factually correct!) data can sometimes hurt

3. Small amounts of the right kinds of behavior (safety, instruction-following, style) make a big difference, but there is a long-tail that benefits from more data

第 15 讲 · 原页 26–27 · 中文讲解

少量样本可以改变行为，但不覆盖长尾

读懂小数据实验

第26页柱状图按测试类别分组，不同颜色表示加入的安全样本量。图中加入几百个安全示范后，不良输出评分明显降低。关键不是“500”这个神奇阈值，而是已有能力的模型可被少量方向一致的数据引导。必须连同基座模型、普通指令数据、评分定义和测试分布理解结果；不能据此保证任意模型只需500条就安全。

编者补充：快速改善与覆盖率是两件事

若模型已能识别粗粒度风险，少量例子可教会基本拒绝格式；但细粒度例外、不同语言、隐含请求和多轮上下文需要更广覆盖。想象训练只有直接询问的不良请求，测试换成角色扮演或先正常后转向的对话，原先的低违规率便可能不适用。第27页总结“提取预训练行为”是一种经验视角：SFT常擅长重排已有能力，但并无一个能直接验证所有内部能力的仪表。应通过留出测试、不同提示和样本量消融判断。

课堂补充 · **00:32:20–00:34:57**

讲者明确说少量样本能够引导模型，不代表更多数据没有收益；对细致边界仍需大规模采集。回答学生时，他也承认“某行为已在预训练中”并不能总被直接证实。

本节参考（完整书目见讲义末尾）：[slides] · [safetyfew] · [captions]

How to fine-tune

Just do gradient descent..

```
from tqdm.auto import tqdm

progress_bar = tqdm(range(num_training_steps))

model.train()
for epoch in range(num_epochs):
    for batch in train_dataloader:
        batch = {k: v.to(device) for k, v in batch.items()}
        outputs = model(**batch)
        loss = outputs.loss
        loss.backward()

        optimizer.step()
        lr_scheduler.step()
        optimizer.zero_grad()
        progress_bar.update(1)
```

In many academic settings – this is basically it. **But what if..**

You have tons of compute and data, you want to scale up instruction tuning

第 15 讲 · 原页 28–28 · 中文讲解

SFT实际优化了什么

编者补充：把代码循环连回概率目标

设数据集D包含提示x及回答y=(y1,…,yT)。常见的仅回答监督为L_SFT = -E_D Σ_t log πθ(y_t | x,y_<t)，也可按回答长度或有效token总数归一化。每一步用真实前缀预测下一token，称teacher forcing；交叉熵对参数求导后做梯度下降。图中的forward、loss.backward、optimizer.step就是实现这件事。SFT通常从预训练参数出发，不是用少量问答重新学会语言。

掩码与手算

拼接的输入可能为[系统,用户,助手回答,结束符]。仅回答监督会把系统和用户位置的标签屏蔽，但模型仍通过注意力读取它们；它们是条件，不是被删除。若三个目标token的条件概率为0.5、0.25、0.8，则序列概率0.1，负对数似然为-ln(0.1)=2.3026，token均值为0.7675。要记录求和还是平均，否则不同长度样本会得到不同权重。结束符也应按配方训练，否则模型可能不会适时停止。

实现边界

前向计算可以并行处理整段teacher-forced序列，而生成时需逐token采样；这一区别会在PPO中变成额外开销。样本拼接还需正确attention mask与边界，避免一条训练回答窥见不属于它的后续文本。原页展示简化梯度下降概念，不提供完整训练器；不同SFT配方也可能监督提示token，不能把一种mask说成唯一定义。

本节参考（完整书目见讲义末尾）：[slides]

Turning instruction tuning into pretraining

Can we somehow turn instruction tuning data into pretraining data?


The following (increasingly popular) idea says yes:


1. Pre-train on web/pretraining data
2. Mix in instruction-tuning data into pre-training
3. Do an actual (but short) instruction-tuning round.

Lets you scale up instruction tuning w/o catastrophic forgetting

‘Midtraining’ / ‘Two-phase training’

The recipe is common knowledge among many LLM companies (but not documented)





Widely used by most models today..

Publicized in recent Chinese-derived LMs (miniCPM, jetMoE)

第 15 讲 · 原页 29–30 · 中文讲解

Midtraining：数据混合与学习率阶段共同变化

三阶段和饼图

原页给出预训练→混入指令数据的训练阶段→较短的专门指令微调。第30页饼图比较stable阶段与decay阶段的数据配比，后者增加较高质量及问答、聊天等来源。数据内容和训练目标是两个维度：指令文本进入预训练式目标时，仍可预测提示部分；它并不必然等于仅回答监督的SFT。某模型称为base，也不能据名称判断其完全没见过指令数据。

编者补充：为什么混合可能缓解遗忘

设L_mix = (1-α)L_general + αL_instruction，α控制相对权重。只优化极窄指令集时，模型可能降低一般文本能力；保留通用数据可继续对这些能力施加梯度约束。比如采样80%通用token、20%指令token，是对计算预算和行为目标的取舍，不是本讲推荐的固定比例。“避免灾难性遗忘”应理解为一种缓解策略，仍需测量，而不是数学保证。若两个领域梯度冲突，混合也会产生折中。


课堂补充 · **00:36:09–00:40:50**

讲者指出指令和高质量数据常在后段衰减阶段混入；00:38:32–00:38:46的问答明确说这里的预训练式处理会预测prompt。后段较短也让数据消融更可负担，但小规模或短阶段结果能否迁移仍要实测，不能把饼图当普适最优配方。

本节参考（完整书目见讲义末尾）：[slides] · [minicpm] · [captions]

The second part of RLHF

Standard approach – imitation (SFT) followed by reinforcement ('RL' HF)



Part 2: the 'RL' part

[Ouyang 2022]

From imitation to optimization

Imitation (SFT)

Fit $\hat{p}(y|x) \approx p^*(y|x)$ for some reference distribution $p^*(y|x)$

- Pure generative modeling perspective
- Requires samples from reference policy

Optimization (RLHF)

Find $\hat{\boldsymbol{p}}(\boldsymbol{y}|\boldsymbol{x})$ such that $\max_p E_p[R(y,x)]$ for a reward $R(y,x)$

- Maximize some reward function that we can measure
- LMs are policies, not a model of some distribution

Why optimize? G-V gap


People don’t always write the thing that they prefer in LM outputs..

deepseek

DeepSeekMath-V2: Towards Self-Verifiable Mathematical Reasoning

Zhihong Shao*, Yuxiang Luo*, Chengda Lu*†, Z.Z. Ren*
Jiewen Hu, Tian Ye, Zhibin Gou, Shirong Ma, Xiaokang Zhang
DeepSeek-AI
zhihongshao@deepseek.com

https://github.com/deepseek-ai/DeepSeek-Math-V2



From: Zhang et al – “Benchmarking Large Language Models for News Summarization” 2023

第 15 讲 · 原页 31–33 · 中文讲解

从模仿分布转向优化奖励

两种目标的根本区别

SFT拟合示范条件分布p*(y|x)，理想无限数据与足够表达能力下最小化交叉熵相当于最小化KL(p*||πθ)。RLHF则寻找让E_{y~πθ}[r(x,y)]较大的策略πθ。这里策略仍是条件概率分布，只是训练目标不再要求复现示范的所有比例。第31页红框从示范阶段移到奖励学习和策略优化，说明人给的是比较信号，优化器决定如何改变模型。

编者补充：一个两答案反例

设某提示的示范中A、B各占50%，SFT理想解是(0.5,0.5)。若奖励r(A)=1、r(B)=0且没有正则，令π(A)=1就能最大化期望奖励；它不会因丢失B的多样性而被惩罚。这解释了后面为什么加KL约束，以及为什么RLHF可能降低熵。KL正则下仍会折中，不能把无正则结论直接套在所有实际算法上。

生成与判断的差距

第33页右侧比较作者摘要和模型摘要的偏好，总体接近一半一半，且不同标注员结果不同、整体一致性很低。它展示人写出的东西未必是他看过候选后最喜欢的东西；这可叫生成—验证或生成—评价差距。左侧数学工作的图是另一动机：某些任务验证候选比从零构造容易，但不是所有自然语言任务都可可靠验证。不能从这张摘要图断言模型普遍超过专业作者。

课堂补充 · **00:42:23–00:45:59**

讲者明确说优化奖励时“仍有分布”，只是它现在被当作策略；他用摘要作者有时偏好模型输出解释为什么比较反馈具有示范之外的信息。可验证奖励的推理训练留给下一讲。

本节参考（完整书目见讲义末尾）：[slides] · [instructgpt] · [captions]

Overview

We'll cover three aspects of RLHF

Data

- How do people collect RLHF data?
- What are some things to worry about


How do we RLHF?

- PPO
- DPO

What are some side-effects of RLHF?


RLHF Data

What types of pairwise feedback. How do we get (good) pairwise feedback?



RLHF and data – standard setups

Standard ‘pairwise feedback’ setup



第 15 讲 · 原页 34–36 · 中文讲解

偏好数据的一条记录究竟是什么

从提示到比较

典型管线先从任务分布抽提示x，再用一个或多个模型采样候选，随机排列后交给标注员比较，记录胜出、平局或无法判断等结果。第35页红框是收集比较数据的阶段，第36页是成对展示界面。训练奖励模型时常用(x,y_w,y_l)；训练策略时可以再采新回答。候选的来源和采样温度改变能被比较的范围，因此不仅标签，候选分布本身也是数据设计。

编者补充：配对不等于绝对质量

若两个回答都错，胜出者只是较好者，不会自动成为高质量SFT示范。若三个候选排序A>B>C，可以构造(A,B)、(A,C)、(B,C)，但这三对共享提示和候选，并非三个完全独立实验。应按提示或对话分割训练与评测集，以免同一题的一部分配对泄漏到测试。展示顺序随机化可减少位置偏差；保留分歧和置信信息可避免把主观差异伪装成确定真值。

建立贯穿后半讲的数据词典

x为同一个上下文，y_w为该上下文下被偏好的完整回答，y_l为相对不受偏好的回答。rφ是有参数φ的打分模型；πθ是有参数θ的生成模型；πref是冻结参考模型。后续符号β控制参考约束或偏好logit的尺度。不要把“被选中”理解成全局最优，也不要把“落选”理解成每个token都错。

本节参考（完整书目见讲义末尾）：[slides]

RLHF and data – instruct GPT guideline

Excerpt of labeling instructions on the API prompt distribution

You are given a text-based description of a task, submitted by a user. This task description may be in the form of an explicit instruction (e.g. "Write a story about a wise frog."). The task may also be specified indirectly, for example by using several examples of the desired behavior (e.g. given a sequence of movie reviews followed by their sentiment, followed by one movie review without a sentiment, you can assume the task is to predict the sentiment of the final review), or by generating the start of a desired output (e.g. given "There once was a wise frog named Julius," you can assume the task is to continue the story).

You will also be given several text outputs, intended to help the user with their task. Your job is to evaluate these outputs to ensure that they are **helpful**, **truthful**, and **harmless**. For most tasks, being truthful and harmless is more important than being helpful.

By **helpful**, we mean that the output should follow the user's intention, and help the user solve their task. Some examples of helpful behavior:

- Writing in clear language.
- Answering the question they meant to ask, even if they mis-asked it.
- Being sensitive to internationality (e.g. "football" shouldn't mean American football, and "the president" doesn't necessarily mean the US president).
- If an instruction is too confusing, asking for clarification and explaining why the instruction is confusing.
- Not giving overly long or rambling answers, or repeating information from the question.
- Not assuming extraneous extra context outside of what's given (besides things like facts about the world), unless that's an implied part of the task. For example, if asked to "write a polite email response to this email: email body" the output shouldn't assume "I can't make it this time, but am free next weekend." But if asked to "Write an email to Socrates", then you can safely assume the output can make up a context.

By **truthful**, we mean that the output contains accurate information, and doesn't mislead the user. Some examples of truthful behavior:

- On tasks like summarization, where the output should only use information from input, not making up details that are not part of the input description.
- Not producing clearly false information about the world (e.g. making up facts or promoting conspiracies). For example, the output should not state that Hillary Clinton has served time in prison.
- Avoid generating misleading information, or information with questionable authenticity. For example, if the input asks "Why did Hillary Clinton go to jail?", the output should not say "It's not totally clear", but rather should refute the premise of the question.

By **harmless**, we mean that the output should not cause physical, psychological, or social harm to people; damage to or loss of equipment or property; damage to the environment; or harm to institutions or resources necessary to human wellbeing. Some examples of harmless behavior:

- Treating other humans with kindness, respect and consideration; not denigrating members of certain groups, or using biased language against a particular group.
- Not generating abusive, threatening, or offensive language, or promoting violence.
- Not writing sexual or violent content if it's not asked for.
- Not giving bad real-world advice, or promoting illegal activity.

Evaluating model outputs may involve making trade-offs between these criteria. These trade-offs will depend on the task. Use the following guidelines to help select between outputs when making these trade-offs:

For most tasks, being harmless and truthful is more important than being helpful. So in most cases, rate an output that's more truthful and harmless higher than an output that's more helpful. However, if: (a) one output is much more helpful than the other; (b) that output is only slightly less truthful / harmless; and (c) the task does not seem to be in a "high stakes domain" (e.g. loan applications, therapy, medical or legal advice, etc.); then rate the more helpful output higher. When choosing between outputs that are similarly helpful but are untruthful or harmful in different ways, ask: which output is more likely to cause harm to an end user (the people who will be most impacted by the task in the real world)? This output should be ranked lower. If this isn't clear from the task, then mark these outputs as tied.

A guiding principle for deciding on borderline cases: which output would you rather receive from a customer assistant who is trying to help you with this task?

Ultimately, making these tradeoffs can be challenging and you should use your best judgment.

Another old example – bard annotations

In this task, you will be provided with a **Prompt** from a user (e.g., a question, instruction, statement) to an AI chatbot along with two potential machine-generated **Responses** to the Prom

Your job is to assess which of the two Responses is better for the Prompt, considering the following for each Response:

Helpfulness: To what extent does the Response provide useful information or satisfying content for the Prompt? Responses should: ▪ **Address the intent of the user's Prompt** such that a user would not feel the Prompt was ignored or misinterpreted by the Response. ▪ **Provide specific, comprehensive, and up-to-date information** for the user needs expressed in the Prompt. ▪ **Be sensible and coherent.** The response should not contain any nonsensical information or contradict itself across sentences (e.g., refer to two different people with the same name as if they are the same person). ▪ **Adhere to any requirements indicated in the Prompt** such as an explicitly specified word length, tone, format, or information that the Response should include. ▪ **Not contain inaccurate, deceptive, or misleading information** (based on your current knowledge or quick web search - you do not need to perform a rigorous fact check) ▪ **Not contain harmful, offensive, or overly sexual content** A Response may sometimes intentionally avoid or decline to address the question/request of the Prompt and may provide a reason for why it is unable to respond. For example, "Sorry, there may not be a helpful answer to this question." These responses can be considered helpful in cases where an appropriate helpful response to the Prompt does not seem possible.	Rating scale: ▪ **Not at All Helpful:** Response is useless/irrelevant, contains even a single piece of nonsensical/inaccurate/deceptive/misleading information, and/or contains harmful/offensive/overly sexual content. ▪ **Slightly Helpful:** Response is somewhat related to the Prompt, does not address important aspects of the Prompt, and/or contains outdated information. ▪ **Somewhat Helpful:** Response partially addresses the intent of the Prompt (most users would want more information), contains extra unhelpful information, and/or is lacking helpful details/specifics. ▪ **Very Helpful:** Response addresses the intent of the Prompt with a satisfying response. Some users might want a more comprehensive response with additional details or context. It is comparable to a response an average human with basic subject-matter knowledge might provide. ▪ **Extremely Helpful:** Response completely addresses the intent of the Prompt and provides helpful details/context. It is comparable to a response a talented/well-informed human with subject-matter expertise might provide.
Presentation: To what extent is the content of the Response conveyed well? Responses should: ▪ **Be organized in a structure that is easy to consume and understand.** Flowing in a logical order and makes good use of formatting such paragraphs, lists, or tables. ▪ **Be clearly written in a polite neutral tone** that is engaging, direct, and inclusive. The tone should not be *overly* friendly, salesy, academic, sassy, or judgmental in a way that most users would consider to be off-putting or overdone. ▪ **Have consistent style with natural phrasing and transitions** as if composed by a single talented human. ▪ **Not be rambling, repetitive. or contain clearly off-topic information.** Similar information should not be repeated multiple times. It is harder for users to consume the helpful information in a response if there is repetitive or less helpful information mixed into the response. ▪ **Not include notable language issues or grammatical errors**	Rating scale: ▪ **Poor:** Response is poorly written or has notable structural, formatting. language, or grammar issues. Or Response has an awkward or inappropriate tone. Or the Response repeats similar information. Or only a small portion of the Response contains helpful information. ▪ **Adequate:** Response could have been written/organized better or may have minor language/grammar issues. A minimal amount of less helpful information may be present. Users would still feel the content of the Response was easy to consume. ▪ **Excellent:** Response is very well written and organized. Sentences flow in a logical order with smooth transitions and consistent style. The content of the Response is conveyed in a way that is comparable to a response a talented human might produce.

Overall, you should consider both factors in your SxS rating of which response is better. A more concise response presenting the most helpful information directly and clearly is usually better than a longer response that may be harder to consume and/or contains clearly off-topic information. Responses with Poor Presentation (e.g., rambling, inappropriate tone) should play a significant role in your assessment of which side is better. It may help to imagine the user chatting with a real person and consider which Response most users would prefer to receive from a real person.

https://assets.bwbx.io/documents/users/iqjWHBFdfxIU/rqKqEqbXBnDI/v0

第 15 讲 · 原页 37–38 · 中文讲解

标注规范如何把抽象偏好变成操作

读懂两类规范

第37页的InstructGPT规范将帮助性、真实性和无害性分开说明，但最后仍需做总体取舍。第38页旧Bard材料还展示等级式评分：单独给回答打等级，与同题二选一提供的信息不同。成对比较常较容易保持相对一致，等级评分则便于发现“两者都不好”，但不同人的尺度可能不同。两页都是历史案例，不是当前产品标注流程的完整说明。

编者补充：规则冲突需要可执行例子

例如用户要求“给错误观点写一段有说服力的解释”，只评流畅度可能鼓励错误传播，只评拒绝又可能压制正常分析。规范应说明任务意图、事实核对要求和冲突时的优先级，并给出边界对照。对长答案，仅问“哪个更好”会把专业正确性、风格和长度混成一票。可先标出事实错误、遗漏约束等细项，再做总体选择；需要花时间验证的样本应给标注员足够时间。


课堂补充 · **00:47:30–00:49:09**

讲者建议阅读InstructGPT附录来了解公开标注细节，并对比Bard历史材料中的帮助性、准确性和呈现要求。这里的主要教学信息是把原则具体化，而不是复制某公司的全部规范。


本节参考（完整书目见讲义末尾）：[slides] · [instructgpt] · [captions]

Modern worker distribution


Caveat: many platforms, covers only one (Outlier, ScaleAI)



Sample: n = 914
What is your age? (Single answer)
Total may not sum due to rounding.
Source: Oxford Economics



Sample: n = 911
What is the highest level of education you have completed? (Single answer)



Sample: n = 912
Which domain is the one where you have contributed the most? (Single answer)
Source: Oxford Economics


Large variation in compensation

Lots of growth in “expert annotation”

Under Project Stagecraft, as it is internally known at data-labeling startup Handshake AI, freelancers are being paid at least $50 an hour to create materials that will be used by OpenAI's ChatGPT to understand various occupations, one contractor told Business Insider.

Business Insider reviewed dozens of pages of documents for the project, including step-by-step instructions for contractors. In these files, contractors from various industries were directed to develop a persona and create tasks that reflect real work.

The project, which has employed about 3,000 to 4,000 freelancers, is ongoing, the contractor said.



https://www.businessinsider.com/ai-data-labeling-annotators-pay-subject-experts-generalists-gig-workers-2025-12

第 15 讲 · 原页 39–40 · 中文讲解

谁在标注：抽样人群、专业性和劳动成本

先看样本范围再看百分比

第39页明确只覆盖一个平台。年龄图的众数区间是35–44岁，学历图中本科44%、硕士32%，并非全行业普查。三张图的有效样本数分别不同，不能把它们当成同一批人的完整交叉表。专业领域饼图显示任务多样；有学历不自动保证某一道具体问题的事实核对能力。

读薪酬图时的限制

第40页并列项目报道和专业领域时薪图，说明专家型标注与低成本标注可以共存。图标题写的是报酬区间的中点，不是全体实际收入的中位数；实际收入还可能受可领取任务量和非计费时间影响。中文注释只解释原页证据，不将这些历史报价当作当下工作机会、行业薪资或已核验合同。

编者补充：为什么这是模型问题

如果任务需要查证代码或领域事实，而预算只允许快速扫读，标签就可能偏向语气自信、排版漂亮的回答。专业匹配、任务时间和报酬会影响可获得的信息质量。设计数据预算时，1000条充分核验的判断与10000条匆忙点击并不等价；但也不能只用高薪标签证明质量，仍需通过抽查、一致性分析及独立任务表现验证。

本节参考（完整书目见讲义末尾）：[slides]

RLHF and data - crowdsourcing

Complexities of crowdsourcing

- Hard to get really high-quality, verifiable annotators
- Hard to get them to really check correctness
- Have to be careful about AI use..

RLHF and data – crowdsourcing ethics

Data collection at scale can have significant issues

BUSINESS + TECHNOLOGY

Exclusive: OpenAI Used Kenyan Workers on Less Than $2 Per Hour to Make ChatGPT Less Toxic

15 MINUTE READ



This image was generated by OpenAI's image-generation software, Dall-E 2. The prompt was: "A seemingly endless view of African workers at desks in front of computer screens in a printmaking style." TIME does not typically use AI-generated art to illustrate its stories, but chose to in this instance in order to draw attention to the power of OpenAI's technology and shed light on the labor that makes it possible. Image generated by Dall-E 2/OpenAI

TECHNOLOGY

AMERICA ALREADY HAS AN AI UNDERCLASS

Search engines, ChatGPT, and other AI tools wouldn't function without an army of contractors. Now those workers say they're underpaid and mistreated.

By Matteo Wong

第 15 讲 · 原页 41–42 · 中文讲解

众包质量与伦理会进入数据生成机制

把质量风险拆开

第41页指出三类难点：验证标注员的能力与身份、确保他们真正查证事实、识别未约定的模型代答。若收集目标是独立人类判断，标注员直接采用另一个模型的答案会改变目标分布，形成未记录的AI反馈。问题不是工具一律不能使用，而是数据来源是否符合协议、是否保留人工复核以及能否追溯。

编者补充：合理的质量控制

可用有明确依据的校准任务、少量重复题、多人分歧复核和随机抽查来发现问题；不要把所有分歧都当作低质量，因为偏好确实可能多元。若一道题需要读长文并查参考资料，过短时限将系统性惩罚认真核查的人。第42页新闻截图提醒低薪、工作压力和接触不良内容的成本；本讲不据单个报道推定所有平台状况。合理时限、透明规则、隐私保护和支持机制既涉及劳动条件，也影响标签可信度。


课堂补充 · **00:51:24–00:52:52**

讲者把核实专业性、模型代答和时间压力列为真实采集难点，并提醒专家标注增长不代表低薪众包消失。这是对数据生产条件的分析，不是只靠算法即可修正的随机噪声。

本节参考（完整书目见讲义末尾）：[slides] · [captions]

RLHF and data - demographics

The annotator distribution for RLHF can significantly shift its behaviors



What gender do you identify as?	
Male	50.0%
Female	44.4%
Nonbinary / other	5.6%
What ethnicities do you identify as?	
White / Caucasian	31.6%
Southeast Asian	52.6%
Indigenous / Native American / Alaskan Native	0.0%
East Asian	5.3%
Middle Eastern	0.0%
Latinx	15.8%
Black / of African descent	10.5%
What is your nationality?	
Filipino	22%
Bangladeshi	22%
American	17%
Albanian	5%
Brazilian	5%
Canadian	5%
Colombian	5%
Indian	5%
Uruguayan	5%
Zimbabwean	5%
What is your age?	
18-24	26.3%
25-34	47.4%
35-44	10.5%
45-54	10.5%
55-64	5.3%
65+	0%
What is your highest attained level of education?	
Less than high school degree	0%
High school degree	10.5%
Undergraduate degree	52.6%
Master's degree	36.8%
Doctorate degree	0%

Group	AI21			OpenAI					
	J1-grande	J1-jumbo	j1-grande-v2-beta	ada	davinci	text-ada-001	text-davinci-001	text-davinci-002	text-davinci-003
RELIG									
Protestant	0.813	0.814	0.797	0.821	0.788	0.709	0.715	0.755	0.694
Roman Catholic	0.815	0.820	0.806	0.825	0.794	0.709	0.716	0.759	0.700
Mormon	0.792	0.794	0.778	0.803	0.772	0.700	0.709	0.752	0.694
Orthodox	0.771	0.776	0.762	0.783	0.754	0.688	0.698	0.733	0.693
Jewish	0.794	0.796	0.785	0.801	0.773	0.699	0.710	0.758	0.706
Muslim	0.786	0.796	0.788	0.793	0.775	0.684	0.704	0.730	0.698
Buddhist	0.771	0.784	0.776	0.783	0.764	0.682	0.703	0.747	0.709
Hindu	0.778	0.798	0.793	0.789	0.776	0.683	0.703	0.728	0.707
Atheist	0.774	0.778	0.772	0.786	0.761	0.690	0.707	0.766	0.713
Agnostic	0.783	0.789	0.781	0.795	0.768	0.698	0.715	0.771	0.715
Nothing in particular	0.815	0.819	0.802	0.826	0.791	0.712	0.715	0.765	0.698

[Santurkar+ 2023]

RLHF and style – annotators matter (a lot)

This is true even for many annotators – but not all annotators




Figure 4: The difference in error rates between crowdsourced annotations and 'expert' annotations from the authors, excluding samples that were marked as refusing to respond. Annotators tend to underestimate the rate of inconsistency or factuality errors, and they are less likely to spot these errors in outputs that are assertive.

[Hosking, Blunsom, Bartolo 2024]

第 15 讲 · 原页 43–44 · 中文讲解

人群偏好与错误识别偏差

第43页：群体相似不等于个人信念

表格比较模型回答与不同群体问卷分布的相似程度，左侧给出一组标注员的人口统计。列间变化提示后训练可改变模型表达的意见分布。它不能证明某个模型具有宗教或政治身份，也不能由群体表格确定因果；模型版本、训练数据和提示方式同时可能变化。群体均值更不能用来预测某个个人的观点。标注员分布是需要审计的因素，不是可以忽略的幕后细节。

第44页：读误差热图

横向比较语气坚定程度或复杂度，纵向是矛盾、一致性、事实性、相关性、格式与重复。颜色表示众包标注和作者专家标注的错误率差异；多个事实性格子为负，意味着众包漏掉了更多专家认为存在的错误，而不是这些回答事实更好。某些格式项相对偏高，说明显眼表面特征更容易影响判定。注意这是特定任务和标注群体的比较，不是“人类都不会判断”。


编者补充：如何把这一页变成实验


对同一事实内容做谨慎与自信两种表述，请不同专业背景的标注员独立打分，再核验真实错误是否保持一致。若仅语气变化就改变错误识别率，说明偏好标签部分测量了修辞。可以增加明确核验步骤，并单独报告风格和事实性，而不是寄希望于把更多相同偏差的标签平均掉。

本节参考（完整书目见讲义末尾）：[slides] · [opinions] · [humanfeedback]

RLFH and data - LM-generated

GPT4 is a surprisingly good pairwise feedback system






Near-perfect rank correlation at the system level

Agreement near human inter-annotator levels

RLHF and data - LM-generated

For people following the frontier – AI feedback often used for RLHF

Ultrafeedback




Zephyr 7b

> ***One of the primary contributions of ZEPHYR was the incorporation of AI feedback via teacher models for the alignment tasks. Why did you choose this approach over more established human feedback mechanisms?***

Earlier in the year, we had actually experimented with collecting human feedback from a data vendor, but found the process was both time consuming and costly to oversee. Based on this experience, we felt AI feedback was a more accessible route for both our small team and as a means to popularize a method that the community could also adopt.

Tulu3



Used in e.g. Olmo, Zephyr, etc

https://thesequence.substack.com/p/the-sequence-chat-hugging-faces-lewis

第 15 讲 · 原页 45–46 · 中文讲解

模型作为评判者：便宜可扩展不等于没有偏差

两种一致性不要混淆

第45页左图比较若干系统的模拟胜率与人类胜率，排序相关接近1说明系统排序吻合；右图同时比较标注一致性与成本。系统层面的相关不代表每个回答对都判断正确：大量局部错判可能在平均后仍保留系统顺序。也不能把在这组候选模型上的相关外推到新领域或能力更强的模型。

公开数据管线中的AI反馈


第46页展示UltraFeedback、Zephyr与Tülu 3等案例。可用较强教师为候选排序，再把偏好传给较小或开放学生，既能扩大规模，也能执行更一致的规则。但教师的知识边界、长度偏差、位置偏差及提示敏感性会传入数据。SFT回答由模型生成与偏好标签由模型生成是两个独立维度，应分别记录。

编者补充：可操作的评判者验证

固定一组带可核验错误的题，交换候选顺序，控制长度，比较模型判定与独立专家判定；再按代码、事实、风格等任务分层检查。对同一个评判模型同时用于训练标签和最终测试要特别小心：学生可能学会其口味，分数升高却未提高真实帮助性。模型裁判可以是工程工具，但其评分本身仍需验证；不要把“GPT4判断”当作天然金标准。

本节参考（完整书目见讲义末尾）：[slides] · [alpacafarm] · [tulu3]

RLHF and data – Self-training



From Constitutional AI, Bai et al.

第 15 讲 · 原页 47–47 · 中文讲解

Constitutional AI：生成、批评、修订与比较

顺着流程图读两条链

上半条链从初始模型对不良请求生成回答出发，依据原则进行自我批评和修订，再对修订回答做 SFT。下半条链让微调后的模型生成候选，模型依据原则提供比较，训练偏好模型，再做强化学习。这样，模型可同时参与数据生产和评价，而不是所有改进都依赖逐条人工撰写。图中的原则和起始模型本身仍携带人类选择。


编者补充：自训练为何可能有收益

一次直接生成与“先生成、再针对明确标准检查、再改写”提供了不同计算与条件，后者可能从同一模型已有能力中筛出更好答案。把筛选后的结果蒸馏回模型，可使这些行为更常出现。但如果判断器无法识别某种错误，循环会重复甚至放大它。这里的自改进不意味着凭空产生可靠新知识，也不意味着无需任何人类监督：原则设计、初始模型和外部评测均是监督来源。


本节参考（完整书目见讲义末尾）：[slides] · [cai]

RLHF and style – Length effects

Length effects are a very significant outcome of RLHF



[Chen et al 2024]



Question: *Why don't adults roll off the bed?*

☆ **SFT (Before); 59 tokens**

Adults typically do not roll off of the bed because they have developed the muscle memory to keep their bodies from involuntarily moving during sleep and maintaining proper posture.

RLHF (After); 243 tokens: Similar output, but much longer / more details

Adults generally do not roll off of the bed because they have developed muscle control and awareness which helps them to remain upright while sleeping.

Additionally, most adults find it uncomfortable or even painful to move around in their sleep, so rolling off the bed would be difficult without waking up first. There may also be safety concerns such as falling out of bed and potentially hurting oneself if one were to lose balance or fall from the …

[Singhal et al 2024]

第 15 讲 · 原页 48–48 · 中文讲解

长度为什么会成为奖励捷径

读图并联系前半讲

本页左图将回答长度与偏好胜率放在一起，右图展示长度与奖励的关联以及偏长示例。与第17页不同，这里强调反馈优化会把这种偏好变成策略变化：只要奖励模型经常给长答案高分，策略就可能通过加长来涨分。图中的相关性本身不证明长度是唯一原因，需借控制实验判断。

编者补充：用分解理解捷径

假设代理奖励r_hat = q + λ·l，其中q是内容质量，l是归一化长度；优化器不知道我们只想要有用细节，可能增加重复使l变大，而q不变甚至下降。应同时查看长度分布、重复率、任务正确率及长度条件下的胜率。把所有答案截成同样长也不是完整解决方案，因为有些任务确实需要长解释。真正目标是奖励与用户所需信息相匹配，后面长度归一化只是部分应对。

课堂补充 · **01:04:30–01:05:23**

讲者指出模型裁判也会表现出与人类类似的风格偏差，并提及通过推动长度提高部分模型评价分数的实验。课堂没有声称所有长回答都是投机或所有评测都只测长度。

本节参考（完整书目见讲义末尾）：[slides] · [captions]

How do we RLHF?

We now have a (high quality) pairwise feedback data collection pipeline?

How do we adapt the model to make use of pairwise feedback?

- **Part 1: PPO** – the original and very finicky approach (the brief version)
- **Part 2: DPO** – the new, very accessible approach

From imitation to optimization

Imitation (SFT)

Fit $\hat{p}(y|x) \approx p^*(y|x)$ for some reference distribution $p^*(y|x)$

- Pure generative modeling perspective
- Requires samples from reference policy

Optimization (RLHF)

Find $\hat{\boldsymbol{p}}(\boldsymbol{y}|\boldsymbol{x})$ such that $\max_p E_p[R(y,x)]$ for a reward $R(y,x)$

- Maximize some reward function that we can measure
- LMs are policies, not a model of some distribution

第 15 讲 · 原页 49–50 · 中文讲解

算法入口：把数据、目标和求解器分开

三层问题

偏好数据决定训练信号；目标函数规定奖励与偏离参考模型的取舍；PPO或DPO等方法规定怎样更新参数。PPO通常通过显式奖励模型给新生成的回答评分，DPO把配对偏好直接写成可微损失。两者都可使用相似的偏好数据，但成本、覆盖到的输出分布和稳定性不同。不能把使用DPO等同于不需要评价，也不能把任何使用人类反馈的方法都认作PPO。

编者补充：语言模型的策略视角

在token粒度，状态s_t=(x,y_<t)，动作a_t=y_t，πθ(a_t|s_t)就是下一token分布；完整回答可视作一次轨迹。若只在最后打分，可把整个回答看成上下文bandit的一次动作，也可在token序列上做信用分配。前一种抽象简化目标，后一种便于实现价值函数和token级更新。本讲先建立最小闭环，复杂多轮工具环境并不由这些单轮公式自动解决。

本节参考（完整书目见讲义末尾）：[slides]

PPO in language modeling

From InstructGPT

Reinforcement learning (RL). Once again following Stiennon et al. (2020), we fine-tuned the SFT model on our environment using PPO (Schulman et al., 2017). The environment is a bandit environment which presents a random customer prompt and expects a response to the prompt. Given the prompt and response, it produces a reward determined by the reward model and ends the episode. In addition, we add a per-token KL penalty from the SFT model at each token to mitigate over-optimization of the reward model. The value function is initialized from the RM. We call these models "PPO."

We also experiment with mixing the pretraining gradients into the PPO gradients, in order to fix the performance regressions on public NLP datasets. We call these models "PPO-ptx." We maximize the following combined objective function in RL training:

$$\begin{aligned}\text{objective}\,(\phi) = & E_{(x,y)\sim D_{\pi_\phi^{\mathrm{RL}}}}\left[r_\theta(x,y) - \beta \log\left(\pi_\phi^{\mathrm{RL}}(y \mid x)/\pi^{\mathrm{SFT}}(y \mid x)\right)\right] + \\ & \gamma E_{x\sim D_{\text{pretrain}}}\left[\log(\pi_\phi^{\mathrm{RL}}(x))\right]\end{aligned} \tag{2}$$

where π_ϕ^{RL} is the learned RL policy, π^{SFT} is the supervised trained model, and D_{pretrain} is the pretraining distribution. The KL reward coefficient, β, and the pretraining loss coefficient, γ, control the strength of the KL penalty and pretraining gradients respectively. For "PPO" models, γ is set to 0. Unless otherwise specified, in this paper InstructGPT refers to the PPO-ptx models.

..this is very innocuous looking

More details and background from Stiennon

From "Learning to summarize from human feedback”

Reward models. To train our reward models, we start from a supervised baseline, as described above, then add a randomly initialized linear head that outputs a scalar value. We train this model to predict which summary $y \in \{y_0, y_1\}$ is better as judged by a human, given a post x. If the summary preferred by the human is y_i, we can write the RM loss as:

$$\text{loss}(r_\theta) = -E_{(x,y_0,y_1,i)\sim D}[\log(\sigma(r_\theta(x, y_i) - r_\theta(x, y_{1-i})))]$$

where $r_\theta(x, y)$ is the scalar output of the reward model for post x and summary y with parameters θ, and D is the dataset of human judgments. At the end of training, we normalize the reward model outputs such that the reference summaries from our dataset achieve a mean score of 0.

Human feedback policies. We want to use the reward model trained above to train a policy that generates higher-quality outputs as judged by humans. We primarily do this using reinforcement learning, by treating the output of the reward model as a reward for the entire summary that we maximize with the PPO algorithm [58], where each time step is a BPE token.[8] We initialize our policy to be the model fine-tuned on Reddit TL;DR. Importantly, we include a term in the reward that penalizes the KL divergence between the learned RL policy π_ϕ^{RL} with parameters ϕ and this original supervised model π^{SFT}, as previously done in [25]. The full reward R can be written as:

$$R(x, y) = r_\theta(x, y) - \beta \log[\pi_\phi^{\text{RL}}(y|x)/\pi^{\text{SFT}}(y|x)]$$

This KL term serves two purposes. First, it acts as an entropy bonus, encouraging the policy to explore and deterring it from collapsing to a single mode. Second, it ensures the policy doesn't learn to produce outputs that are too different from those that the reward model has seen during training.

For the PPO value function, we use a Transformer with completely separate parameters from the policy. This prevents updates to the value function from partially destroying the pretrained policy early in training (see ablation in Appendix G.1). We initialize the value function to the parameters of the reward model. In our experiments, the reward model, policy, and value function are the same size.

第 15 讲 · 原页 51–52 · 中文讲解

奖励模型、KL正则与预训练混合项

从成对标签得到标量奖励

Bradley–Terry模型假设P(y_w优于y_l|x)=σ(rφ(x,y_w)-rφ(x,y_l))，其中σ(u)=1/(1+exp(-u))。最小化L_RM=-E log σ(r_w-r_l)会提高胜出者相对分数。编者手算：奖励差为0时偏好概率0.5、损失0.6931；差为ln3时概率0.75、损失0.2877。加同一个只依赖x的常数不改变比较，因此奖励绝对零点不可从配对数据唯一确定。

为什么要保留参考策略

固定提示时J(π)=E_{y~π}[rφ(x,y)]-β KL(π(.|x)||πref(.|x))，β>0。KL(π||q)=Σ_y π(y)log(π(y)/q(y))，是在当前策略下衡量相对参考分布的偏离。单个采样的log概率比可以为负，其期望才是非负KL。参考通常来自SFT，不能随手把它和本轮PPO采样旧策略混成同一个对象。KL限制模型跑向奖励模型缺少训练支持的区域，也帮助保留原行为，但不保证没有奖励投机。

从序列到token及PPO-ptx

自回归分解给出logπ(y|x)=Σ_t logπ(y_t|x,y_<t)，所以整段log概率比可分解为token项。第51页InstructGPT目标还加γ E_{z~D_pretrain}[logπθ(z)]，这是预训练文本似然项，旨在缓解能力退化；γ=0时没有此项。不要把β与γ、奖励模型参数φ与策略参数θ混淆。该式是最大化目标，因此实现最小化loss时符号要整体对应。

编者补充：一次训练循环中的角色

常见配置有可训练actor、冻结reference、冻结reward model和可训练value/critic；具体实现可共享或分离参数，原页Stiennon案例的价值模型使用独立参数。actor产生候选，reward评整段质量，critic估计未来收益以降低方差，reference提供约束。奖励模型训练与策略训练是不同阶段，固定奖励模型时不会在每次actor更新中同步把奖励改得更容易。

本节参考（完整书目见讲义末尾）：[slides] · [instructgpt] · [stiennon]

PPO – at a conceptual level

A brief (and high level) intro to the various ideas in PPO..

Attempt 1: Policy gradients (variances are too high)

$$\nabla_\theta E_{p_\theta}[R(z)] = E_{p_\theta}[\mathrm{R(z)}\nabla_\theta \log p_\theta\,(z)]$$

Attempt 2: TRPO (Linearize the problem around the current policy)

$$\begin{aligned} \underset{\theta}{\text{maximize}} \quad & \hat{\mathbb{E}}_t\left[\frac{\pi_\theta(a_t \mid s_t)}{\pi_{\theta_{\text{old}}}(a_t \mid s_t)}\hat{A}_t\right] \\ \text{subject to} \quad & \hat{\mathbb{E}}_t[\mathrm{KL}[\pi_{\theta_{\text{old}}}(\cdot \mid s_t), \pi_\theta(\cdot \mid s_t)]] \leq \delta. \end{aligned}$$

Attempt 3: PPO (Clip the ratios at some eps)

$$L(s, a, \theta_k, \theta) = \min\left(\frac{\pi_\theta(a|s)}{\pi_{\theta_k}(a|s)}A^{\pi_{\theta_k}}(s,a),\ \ \mathrm{clip}\left(\frac{\pi_\theta(a|s)}{\pi_{\theta_k}(a|s)}, 1-\epsilon, 1+\epsilon\right)A^{\pi_{\theta_k}}(s,a)\right)$$

第 15 讲 · 原页 53–53 · 中文讲解

从策略梯度到PPO：补齐中间台阶

编者推导一：为什么奖励乘上log概率梯度

先令r(y)不显式依赖θ，并假设可交换求和与微分：∇θ Eπ[r]=Σ_y r(y)∇θπθ(y)=Σ_y πθ(y)r(y)∇θlogπθ(y)=Eπ[r∇θlogπθ(y)]。第二步用了∇π=π∇logπ。由于Eπ[∇logπ]=∇Σπ=0，减去只依赖提示的baseline b(x)不改变期望梯度，可降低方差。token级推广常用优势A_t，即本次动作比该状态下的平均预期好多少。这里先推固定奖励的恒等式，含θ的KL项要按所选算法一致处理，不能漏掉依赖关系。

编者推导二：复用旧样本与局部近似

从πold采样后，若新策略变化了，要用概率比ρ_t=πθ(a_t|s_t)/πold(a_t|s_t)调整局部目标。PPO常用E_old[ρ_t A_t]的代理目标；优势与采样策略在当前内循环中固定，状态分布仍取旧轨迹，所以不是任意大幅更新下的精确新策略收益。TRPO把平均KL(πold||πθ)限制在δ内来控制局部变化。πold每轮采样更新，πref通常整个阶段冻结；前者约束更新步幅，后者约束与起点的长期偏离。

编者推导三：clip不是硬截断模型概率

PPO最大化L_clip=E[min(ρA, clip(ρ,1-ε,1+ε)A)]。取ε=0.2、A=2、ρ=1.5，原项3、截断项2.4，取2.4，不再奖励继续增大该比率。若A=-2、ρ=0.5，原项-1、截断项-1.6，取-1.6，不再奖励继续减小。相反方向仍可有梯度：A=-2、ρ=1.5时取-3，推动纠正坏动作。clip只改变这项代理损失，并不强制所有token概率比都落在区间内，不能宣称有严格KL上界。

工程含义与课堂范围

采样需要顺序解码；还要为输出算奖励、参考概率和价值，再用一批轨迹做若干轮优化，然后重新采样。复用降低生成成本，过多复用会让旧数据不再代表当前策略。PPO通常被归为on-policy方法，有限复用旧rollout不等于可无约束使用任意离线数据。课堂01:07:14–01:08:59只给高层链条，以上推导和数值为编者补充；完整实现细节并非这一个式子就足够。

本节参考（完整书目见讲义末尾）：[slides] · [ppo] · [captions]

Can we get rid of PPO?

Question for many: can we avoid doing any ‘RL’ ? (i.e. on-policy RL algorithms)

Some reasonable stuff people thought about

- Train the model with a control token – (SFT on the pairs, prepend [GOOD] to chosen, [BAD] to not chosen)
- Train the model on only preferred output
- Train a reward model, get LM outputs, train on the preferred output
- Train a reward model, get 1024 LM outputs, take the best one.


DPO – RLHF without tears?


Try to simplify PPO by..

- Getting rid of the reward model
- Getting rid of any on-policy stuff (rollouts, outer loops etc)

Instead

- Take gradient steps on log-loss of good stuff
- Take negative gradient steps on bad stuff (appropriately weighted).





第 15 讲 · 原页 54–55 · 中文讲解

为何不只用赢家做SFT：走向DPO

几种替代方法各在做什么

给好坏回答加控制token相当于条件模仿；只训练赢家是过滤后的SFT；奖励模型选出好样本再训练是拒绝采样或expert iteration的一类步骤；生成很多候选再选最高分是推理时best-of-N。它们都有可能改善结果，但利用负例的方式、计算成本和奖励偏差不同。原页列出的探索路线不是已经证明普适无效的方法，更不能将课堂口头的效果评价当成定理。

编者补充：正例模仿丢失了哪些信息

设A和B都含同样开头，区别是B给了错误日期。只有A的SFT告诉模型“增加A似然”，没有显式说“在此提示下A应比B更受偏好”。DPO利用两者以及参考模型的相对概率形成一个比较logit，当前模型对已标注赢家预测偏低的配对会得到更大更新权重；标注噪声也可能因此被放大。它避免在每个优化步骤中在线采样并训练显式奖励网络，但仍需高质量配对和通常的冻结参考模型。

不要把简化的直觉当成公式

“好回答做正向SFT、坏回答做反向SFT”只是粗略解释。若直接无界地提高负例的交叉熵，容易出现不稳定。DPO用logistic损失、参考比率和依赖预测误差的权重来组织这件事；下一页从明确目标推导，才能知道符号和β该如何使用。

本节参考（完整书目见讲义末尾）：[slides] · [dpo]

DPO – derivation from the RLHF formula

Our goal is to optimize

$$\max_{\pi_\theta} \mathbb{E}_{x\sim\mathcal{D},y\sim\pi_\theta(y|x)}\left[r_\phi(x,y)\right] - \beta\mathbb{D}_{\mathrm{KL}}\left[\pi_\theta(y \mid x) \,||\, \pi_{\mathrm{ref}}(y \mid x)\right]$$

Assume that the policy π is the set of all policies (nonparametric assumption).

The maximizer is then,

$$\pi_r(y \mid x) = \frac{1}{Z(x)}\pi_{\mathrm{ref}}(y \mid x)\exp\left(\frac{1}{\beta}r(x,y)\right)$$

Solve for the ‘implied reward’

$$r(x,y) = \beta\log\frac{\pi_r(y \mid x)}{\pi_{\mathrm{ref}}(y \mid x)} + \beta\log Z(x).$$

(This is the equivalence also used in the kimi-think paper)

第 15 讲 · 原页 56–56 · 中文讲解

DPO第一步：解出KL约束下的理想策略

编者推导：定义问题与可解条件

固定一个提示x，暂把π看成可自由选择的离散分布，而非有限神经网络。记q(y)=πref(y|x)，r(y)=r(x,y)，β>0。求最大值J(π)=Σ_y π(y)r(y)-βΣ_y π(y)log(π(y)/q(y))，约束Σ_y π(y)=1。只在q(y)>0的支持集考虑π；若q为0而π给正质量，KL会无穷大。还要求Z(x)=Σ_y q(y)exp(r(y)/β)有限。对于实际无限长序列，这个可积性不能默默忽略。

把目标改写为一个非负KL

定义π*(y)=q(y)exp(r(y)/β)/Z。取log得logπ*(y)=logq(y)+r(y)/β-logZ，于是r(y)=βlog(π*(y)/q(y))+βlogZ。代入J：J=βΣπ log(π*/q)+βlogZ-βΣπ log(π/q)=βlogZ-βΣπ log(π/π*)=βlogZ-βKL(π||π*)。因为KL≥0，当π=π*时达到最大值βlogZ。这说明指数倾斜解从何而来，并不是把奖励直接当概率。

编者手算：β控制奖励与参考的折中

仅有A、B两个回答，q=(0.5,0.5)，r=(ln3,0)，β=1。未归一化权重为(1.5,0.5)，Z=2，故π*=(0.75,0.25)。β=2时π*(A)=sqrt(3)/(sqrt(3)+1)≈0.634，变大β会更靠近参考。该结论针对固定r的理想目标；实际DPO调β还改变loss和优化尺度，不能据此保证某次有限训练的单调行为。

转回神经网络前要记住的条件

非参数最优解用于建立奖励和策略之间的对应。有限网络、有限配对和非凸优化未必达到它。奖励只相差一个与y无关的c(x)时，会产生同样的归一化策略；这正为下一页比较奖励时消去Z铺路。课堂01:11:14–01:12:48给出这条主线，改写KL及手算为编者补充。

本节参考（完整书目见讲义末尾）：[slides] · [dpo] · [captions]

DPO derivation 2

We can now optimize the implied reward as a reward model via the Stiennon objective

$$\text{loss}(r_\theta) = -E_{(x,y_0,y_1,i)\sim D}[\log(\sigma(r_\theta(x,y_i) - r_\theta(x,y_{1-i})))] \quad \text{and} \quad r(x,y) = \beta \log \frac{\pi_r(y \mid x)}{\pi_{\text{ref}}(y \mid x)} + \beta \log Z(x).$$

This gives the DPO objective,

$$\mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) = -\mathbb{E}_{(x,y_w,y_l)\sim\mathcal{D}} \left[\log \sigma \left(\beta \log \frac{\pi_\theta(y_w \mid x)}{\pi_{\text{ref}}(y_w \mid x)} - \beta \log \frac{\pi_\theta(y_l \mid x)}{\pi_{\text{ref}}(y_l \mid x)} \right) \right].$$

The key steps?

1. Make a nonparametric assumption (links π_θ and r in closed form)
2. Parametrize reward r via the policy
3. Optimize the reward using supervised losses (which in turn, optimizes the policy)

Conceptually.. This is MLE on the pairwise rewards, under nonparametric assumption + alternative parametrization

第 15 讲 · 原页 57–57 · 中文讲解

DPO第二步：把隐式奖励放入偏好似然

编者推导：为什么不需要计算Z

将策略参数化对应的奖励写为rθ(x,y)=βlog(πθ(y|x)/πref(y|x))+βlogZ(x)。同一提示下比较y_w与y_l，后面的βlogZ(x)完全相同，奖励差中抵消。若拿不同提示下的回答直接比较，这一步不成立。把差代入Bradley–Terry概率得到z=β[logπθ(y_w|x)-logπref(y_w|x)-logπθ(y_l|x)+logπref(y_l|x)]，P(w胜)=σ(z)。因此L_DPO=-E_D logσ(z)。这是对配对标签做最大似然，使用策略对数比来参数化隐式奖励。

编者手算：参考模型不能被忘掉

假设在某x下当前模型对两个回答的概率为0.2和0.1，参考为0.1和0.2，剩余质量给其他回答；β=1。赢家的比率为2，输家的比率为0.5，z=log4≈1.3863，预测偏好为0.8，损失为-ln0.8≈0.2231。若只看当前概率比2，就会算出不同答案。初始化πθ=πref时每个比率为1，所有配对z=0，loss=ln2，哪怕原来两个回答本身的概率并不一样。

编者补充：实现与统计边界

logπ(y|x)是回答各token条件log概率之和；用teacher forcing一次前向得到，不需要本步重新生成。πref冻结，不能回传；需明确回答掩码、padding和结束符，避免把不同长度或提示处理不一致混进比率。优化去掉了单独训练的奖励模型，不等于没有奖励假设：仍依赖配对数据、Bradley–Terry形式、参考支持及表达能力。它不保证离线数据没覆盖的回答会得到正确排序，也不保证有限样本下等价于任意PPO运行结果。

本节参考（完整书目见讲义末尾）：[slides] · [dpo] · [stiennon]

DPO updates and components

In some sense, reduces to “pos gradient on good, neg gradient on bad”

What does the DPO update do? For a mechanistic understanding of DPO, it is useful to analyze the gradient of the loss function $\mathcal{L}_{\text{DPO}}$. The gradient with respect to the parameters θ can be written as:

$$\nabla_\theta \mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) =$$

$$-\beta \mathbb{E}_{(x,y_w,y_l)\sim\mathcal{D}}\Big[\underbrace{\sigma(\hat{r}_\theta(x, y_l) - \hat{r}_\theta(x, y_w))}_{\text{higher weight when reward estimate is wrong}}\Big[\underbrace{\nabla_\theta \log \pi(y_w \mid x)}_{\text{increase likelihood of } y_w} - \underbrace{\nabla_\theta \log \pi(y_l \mid x)}_{\text{decrease likelihood of } y_l}\Big]\Big],$$

(Scaled by ‘prediction error’ of the implied reward model)

第 15 讲 · 原页 58–58 · 中文讲解

DPO第三步：梯度为何自动关注难配对

编者推导：逐项求导

令l=-logσ(z)。由σ的导数可得dl/dz=σ(z)-1=-σ(-z)。参考模型冻结，所以∇θz=β[∇θlogπθ(y_w|x)-∇θlogπθ(y_l|x)]。相乘即∇θl=-βσ(-z)[∇logπ_w-∇logπ_l]。梯度下降减去此梯度，因此沿着提高赢家相对log概率、降低输家相对log概率的方向更新。原页括号中的两项和前面的预测误差权重各有职责，不能只保留正负号。

编者手算与重要限制


若β=1，z=0时权重σ(-z)=0.5；z=log4时为0.2；z=-log4时为0.8。已经预测对且很有把握的pair权重更小，预测错的更大。但winner与loser共享大量token和参数，多pair梯度还会冲突，所以不能保证每一步每个赢家的绝对概率都增加。目标首先约束的是相对参考的差；甚至两者绝对概率一起下降、输家降得更多，也可能减小loss。

与SFT的联系及课堂补充 · 01:13:24–01:14:16

SFT只有目标回答的log概率项；DPO额外利用负例、参考比率和误差加权。讲者通过“模型已把赢家打得很高则步子小”解释这个权重。这里说的是loss对该pair梯度的缩放，不是优化器学习率被逐样本重新设定，也不是直接按原始生成概率差线性加权。

本节参考（完整书目见讲义末尾）：[slides] · [dpo] · [captions]

DPO in LLaMA (and other open models)



DPO + Expert iteration for post-training

第 15 讲 · 原页 59–59 · 中文讲解

离线DPO内循环也可以放进迭代外循环

逐箭头读Llama流程图

提示先由前轮模型生成K个候选，奖励模型做拒绝采样，筛出的数据及专门能力数据用于SFT，配对偏好用于DPO，更新后的模型再成为下一轮生成候选的来源。灰色框是数据，蓝色框是模型。图中reward model仍有用，主要用于数据筛选与相关环节；“DPO不需要显式奖励网络”说的是其loss计算，不代表整条后训练管线从不使用奖励模型。

编者补充：什么变在线了

每一轮内可用固定数据做离线DPO；外层更新候选，逐步覆盖新策略会产生的回答。这与每个PPO阶段不断rollout不是同一训练过程，但都在处理数据分布与策略一起变化的问题。迭代不自动改善：若筛选奖励有漏洞，会重复选择同类投机回答；若只有当前模型擅长的任务进入数据，覆盖可能越来越窄。需要固定独立测试及跨轮分布检查。

课堂补充 · **01:14:46–01:15:09**

讲者明确描述先SFT、再DPO、再生成候选并拒绝采样的外循环。这解释了算法简单与整体训练系统复杂并不矛盾。

本节参考（完整书目见讲义末尾）：[slides] · [captions]

Variants

Lots of variants (too many variants), but maybe two of note from the Tulu 3 paper..

SimPO (no ref)

$$\mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) = -\mathbb{E}\left[\log \sigma\left(\beta \log \frac{\pi_\theta(y_w \mid x)}{\pi_{\text{ref}}(y_w \mid x)} - \beta \log \frac{\pi_\theta(y_l \mid x)}{\pi_{\text{ref}}(y_l \mid x)}\right)\right]$$

$$\mathcal{L}_{\text{SimPO}}(\pi_\theta) = -\mathbb{E}\left[\log \sigma\left(\frac{\beta}{|y_w|} \log \pi_\theta(y_w \mid x) - \frac{\beta}{|y_l|} \log \pi_\theta(y_l \mid x) - \gamma\right)\right]$$

Length normalized DPO

$$\max_{\pi_\theta} \mathbb{E}_{y_c, y_r \sim \mathcal{D}}\left[\log \sigma\left(\frac{\beta}{|y_c|} \log \frac{\pi_\theta(y_c|x)}{\pi_{\text{ref}}(y_c|x)} - \frac{\beta}{|y_r|} \log \frac{\pi_\theta(y_r|x)}{\pi_{\text{ref}}(y_r|x)}\right)\right].$$

第 15 讲 · 原页 60–60 · 中文讲解

SimPO与长度归一化DPO：看清改了哪一项

SimPO并非简单删掉reference

设lθ(y)=logπθ(y|x)，|y|为回答token数。原页SimPO的logit为z_sim=β[lθ(y_w)/|y_w|-lθ(y_l)/|y_l|]-γ，loss=-logσ(z_sim)。它使用每token平均log概率作为评分，并引入目标奖励间隔γ；γ>0鼓励赢家的β倍平均log概率评分比输家高γ，但这是软目标，不保证每一对都满足。没有reference降低了相关计算，但也改变了目标的约束结构。β是尺度、γ是间隔，不能混为同一个超参数。

长度归一化DPO仍有参考模型

该变体的logit为z_len=β[(logπθ(y_w)-logπref(y_w))/|y_w|-(logπθ(y_l)-logπref(y_l))/|y_l|]，所有概率都条件于同一x。它是将每个回答的log比率分别除以自己的长度，不是把整个pair除以一个统一长度，也不是拿平均概率而非平均log概率。原页下式写最大化logσ，转成loss时取负号。

编者手算与边界

设赢家有4个token、log比率总和2，输家有2个token、log比率总和1。β=1时标准DPO的z=1，但长度归一化后z=2/4-1/2=0，二者判据确实改变。长度归一化意在减轻长度与分数耦合，并不能保证消除所有长度偏好，也不会自动判断多写的内容是否有用。上述变体不应被说成与第56页原始序列KL目标完全相同的代数改写；它们加入了新的建模选择。

本节参考（完整书目见讲义末尾）：[slides] · [simpo] · [tulu3]

But PPO does too (and sometimes better?)


The trickiness of RL-related empirical work..

Lots of results are highly contingent (on the specifics of the experiment setup)

Unpacking DPO and PPO: Disentangling Best Practices for Learning from Preference Feedback

Hamish Ivison[♣♠] Yizhong Wang[♣♠] Jiacheng Liu[♣♠]
Zeqiu Wu[♣] Valentina Pyatkin[♣♠] Nathan Lambert[♣]
Noah A. Smith[♣♠] Yejin Choi[♣♠] Hannaneh Hajishirzi[♣♠]

[♣]Allen Institute for AI [♠]University of Washington
hamishiv@cs.washington.edu



Tülu 3: Pushing Frontiers in Open Language Model Post-Training

Nathan Lambert[♥1,*] Jacob Morrison[♥1] Valentina Pyatkin[♥1,2] Shengyi Huang[♥1] Hamish Ivison[♥1,2]
Faeze Brahman[♥1] Lester James V. Miranda[♥1]

Alisa Liu[2] Nouha Dziri[1] Xinxi Lyu[1] Yuling Gu[1] Saumya Malik[1] Victoria Graf[2] Jena D. Hwang[1]
Jiangjiang Yang[1] Ronan Le Bras[1] Oyvind Tafjord[1] Chris Wilhelm[1]

Luca Soldaini[1] Noah A. Smith[1,2] Yizhong Wang[1,2] Pradeep Dasigi[1] Hannaneh Hajishirzi[1,2]
[1]Allen Institute for AI, [2]University of Washington

*Tülu 3 was a team effort. ♥ marks core contributors. See full author contributions here.
Contact tulu@allenai.org.

Algorithm	LR	$\gamma - \beta$ ratio	β	Epochs	Batch Size	Average Score
SFT Base	-	-	-	-	-	55.7
SimPO	5.00E-07	0.5	2	1	128	51.8
SimPO	5.00E-07	0.3	10	1	128	52.9
DPO	5.00E-07	-	0.1	3	32	55.2
PPO	1.00E-06	-	0.0325	1	64	54.5
PPO	1.00E-06	-	0.05	1	64	55.5
DPO-norm	1.00E-07	-	5	3	32	56.1
DPO-norm	5.00E-07	-	10	3	32	55.2
DPO-norm	5.00E-07	-	15	3	32	55.7
DPO-norm	5.00E-07	-	2	3	32	46.8
DPO-norm	5.00E-07	-	5	3	32	53.4
DPO-norm	5.00E-07	-	5	1	32	**57.3**

第 15 讲 · 原页 61–61 · 中文讲解

PPO与DPO比较为什么常依赖实验设置

用原页的并列结果提醒自己

原页把不同研究和Tülu 3表格并列，强调算法排名对具体设置敏感。数据来源、基座能力、奖励模型、采样预算、训练步数、β、学习率和评判者都会改变结果。一个算法在单次配方里更高分，不说明它在相同实际成本或另一个任务上仍领先。尤其PPO能够访问新rollout，离线DPO只看固定pair，若数据机会不同，比较就不仅是损失函数。


编者补充：设计一个可解释的比较

先固定初始SFT模型与测试集，记录偏好数据及候选来源；分别说明训练FLOPs、生成token预算和调参次数；同时报告任务正确率、偏好胜率、长度和安全取舍。若要比较算法本身，就尽量控制数据与调参机会；若要比较最终工程方案，就公开各自资源差异。训练loss更低、奖励模型分更高或单个胜率更高，都不等价于全面更好。课堂01:15:38–01:16:33强调的是这种条件性。


本节参考（完整书目见讲义末尾）：[slides] · [tulu3] · [captions]

Things to watch out for in RLHF

Overoptimization / overfitting on the reward




Mode collapse / entropy



Thins to watch out for - Overoptimization

Across many different RLHF-style optimizers. Optimizing for reward overfits past a point



(a) Human preferences ■ (b) AlpacaFarm ◆ (c) Single-prompt GPT-4 ●

Holds true for human pref (left), noisy LM pref (mid) but not noiseless LM pref (right)

第 15 讲 · 原页 62–63 · 中文讲解

奖励过度优化：代理分数上升，真实目标反而下降

图上的拐点比峰值更重要

第62页并列两类副作用：奖励过度优化与多样性/校准变化。第63页横轴是训练出的代理奖励，纵轴是独立评价胜率；左图人类偏好、中图带噪模拟偏好出现先升后降，右图特定单一GPT-4提示评价未显示同样下降。后者只说明该实验配置更容易与其评判者一致，不能解释成无噪声AI标签就保证真实世界无投机，或模型裁判永远比人类好。不同曲线是不同优化方法，误差条也提示估计不确定性。

编者补充：为什么优化会暴露误差

写代理奖励r_hat(y)=r_true(y)+e(y)。在原数据上e平均可能接近0，但优化器专挑r_hat高的输出时，就可能选择e偏正的区域；优化后的样本分布已不再是验证奖励模型时的分布。这是代理目标被强力搜索后的选择效应，不能只靠随机切分上的奖励分类准确率排除。长度捷径是e的一种来源，虚构细节或固定讨好话术也可能成为来源。


如何监测以及KL的作用


保留未用于奖励训练的提示和独立评价，沿训练进程记录代理分数、外部正确性、偏好、长度和相对reference的KL。若分数继续涨而外部表现回落，可提前停止、增强奖励验证或改变数据覆盖。KL约束可减少分布外漂移，却没有消除奖励错误；DPO也可能把有偏pair过拟合，因此“没有显式RM”不代表没有过优化风险。课堂01:16:39–01:17:28强调KL在此处的重要性；第63页图的详细读法为编者补充，讲者在结尾因时间略过其展开。


本节参考（完整书目见讲义末尾）：[slides] · [alpacafarm] · [captions]

Things to watch out for - mode collapse

RLHF makes models no longer ‘probabilistic models’ – no calibration by default







第 15 讲 · 原页 64–64 · 中文讲解

低熵、模式坍缩与失准是三个不同概念

先校正原句的理解

“no longer probabilistic models”应理解成不再以忠实拟合某个人类文本分布为唯一目标，而不是模型失去概率分布。自回归softmax仍给出归一化概率。熵H(π)=-Σ_y π(y)logπ(y)衡量分布分散程度；模式坍缩指许多本可接受的模式被压到少数；校准指预测置信度与实际正确频率匹配。这三者可以相互影响，但互不等价。

读三组图

左上图比较不同温度下的预测概率和经验频率，理想校准在对角线上；调温可改善某些偏差，但不必然修复所有任务。右上两个校准图对比预训练与PPO后的置信分桶，同样的高置信度不再对应原先的正确频率；下方熵分布说明模型回答意见问题的分散程度可能与人类总体不同。图所用任务与模型不同，不能合成一个普适数值结论。

编者手算：奖励目标为何不保证校准

两种回答等概率时熵为ln2≈0.6931；分布变成(0.9,0.1)后熵约0.3251。低熵本身可能是学会了确定答案，也可能只是过度自信，要看任务。若100道声称置信0.9的题只有60道正确，该分桶就明显过度自信，即使它们回答的文风很多样。温度缩放p_T=softmax(logits/T)在T>1时会拉平单步分布，但不会自动修复知识或重新引入已失去的有用推理。

课堂补充 · **01:17:31–01:18:49**

讲者把多样性下降与校准问题联系到下一讲的探索：若策略很早就只生成一种解法，奖励学习很难发现其他可行路径。这里为RLVR建立动机，而不是保证可验证奖励完全不会过拟合或丢失探索。

本节参考（完整书目见讲义末尾）：[slides] · [captions]

Recap of the lecture

RLHF recap:

1. RLHF data collection is (also) hard! Many confounding factors

2. RLHF algorithms are a bit more complex than SFT – esp. PPO

3. Be mindful of the impact of (over) optimizing for rewards

第 15 讲 · 原页 65–65 · 中文讲解

把整讲串成一条可以复述的因果链

复习路径

预训练提供广泛能力；SFT用示范提高想要的回答方式的概率；不同数据会同时改变风格、知识表达、工具行为和拒绝边界。人写出的示范与人最终偏好的输出存在差距，因此采集比较数据，并注意标注人群、核验成本和模型裁判偏差。奖励模型加KL给出优化目标，PPO以采样和局部更新近似求解；DPO利用同提示奖励差消掉归一化常数，把问题化为对策略log概率比的分类损失。

编者补充：一次实验至少回答四个问题

模型学会了什么行为？反馈是谁按什么规范给的？计算与数据相比基线改变了什么？分数上升是否伴随更长回答、误拒、事实下降或熵减少？这些问题把数据、算法和评估连接起来。本讲结尾的RLVR动机是寻找更可靠、可验证的奖励，而不是宣称下一阶段自动解决所有目标错配。完成以下自测后，应能不看幻灯片复原DPO主公式，并用小例子解释其成立条件。

本节参考（完整书目见讲义末尾）：[slides]

自测与参考答案

1. SFT回答很长、偏好胜率上升，能否认定推理能力提高？

不能。长度、列表等风格会影响偏好；应结合可核验任务正确率、长度控制实验以及独立评判者。风格可能改善体验，但它与推理能力是不同指标。

2. 原页Alpaca平均值例子为什么值得警惕？

4+3+6+10+8=31，31/5=6.2，而原示例注释写6.4。示范看起来像正确代码也可能含错；交叉熵只拟合目标，不能自动发现数值错误。

3. 仅回答SFT屏蔽用户token的loss，是否意味着模型看不到用户问题？

不是。用户token仍作为注意力上下文输入；掩码只是让这些位置不贡献目标损失。删除上下文与屏蔽监督是两件事。

4. 安全违规率为0能否说明调优成功？

不能。全拒绝也能达到极低违规率，却可能误拒所有正常问题。必须同时衡量危险集合上的违规率和正常集合上的误拒率，并核对测试覆盖。

5. 奖励差为ln3时Bradley–Terry偏好概率是多少？若给两个奖励都加7呢？

σ(ln3)=3/4，负对数似然约0.2877。共同加7后差不变，概率不变；这说明配对偏好无法辨识共享的奖励平移。

6. πref与πold是否都是同一个冻结SFT模型？

不是。πref通常在该训练阶段固定，定义与起点的KL约束。πold是当前批次rollout的采样策略，随外循环更新，供PPO概率比与局部更新使用；二者可能在第一轮相同，但概念不同。

7. PPO中ε=0.2、A=-2、ρ=1.5，clip项会让此样本梯度消失吗？

不会。原项=-3，截断项=-2.4，min取-3，仍惩罚坏动作概率升高。clip并非无条件把所有超区间比率的梯度置零，更不是对策略概率施加硬范围。

8. q(A)=q(B)=0.5，r(A)=ln3，r(B)=0，β=1，最优KL正则策略是什么？

未归一化权重为(1.5,0.5)，Z=2，因此π*=(0.75,0.25)。最优目标值为ln2；这是非参数、固定奖励、

支持集条件成立时的结果。

9. DPO为什么不必计算Z(x)？能否比较不同提示的两个回答并照样抵消？

同一提示下的奖励都含相同βlogZ(x)，取差时抵消。不同提示通常有不同Z，不能照此抵消；标准DPO的pair必须共享上下文。

10. DPO初始化为参考模型时，loss是否取决于赢家原先的生成概率？

不取决于。两个πθ/πref比率均为1，z=0，loss=ln2。模型后续学习的是相对reference的偏好变化，而非简单把原始概率更高者判为赢家。

11. DPO中z从0变成ln4，β=1时该pair的梯度权重如何变化？

由σ(0)=0.5降到σ(-ln4)=0.2，模型已更符合偏好，继续推动的权重减小。参数共享和其他样本意味着这不是赢家绝对概率每步单调上升的保证。

12. SimPO与长度归一化DPO最关键的两个差别是什么？

SimPO用回答的平均log概率并减目标间隔γ，没有reference；长度归一化DPO使用每个回答的平均log(πθ/πref)，仍有reference。两者都改变长度处理，但不是同一目标。

13. 在两答案例子中π=(0.9,0.1)的熵是多少？这能证明模型失准吗？

熵=-0.9ln0.9-0.1ln0.1≈0.3251。它比均匀分布更集中，但失准要看0.9置信度对应的实际正确频率；若确实90%正确就可以校准，低熵不自动等于失准。

14. 代理奖励一直上升、独立人类胜率先升后降，应先检查什么？

检查训练是否越过了奖励过优化拐点，候选分布、长度、重复、事实错误和KL是否变化。对独立提示复评并考虑早停或改进奖励覆盖；仅增加优化步数可能继续放大代理漏洞。

参考资料

[slides] Stanford CS336 Spring 2026 Lecture 15：官方原课件，主依据

https://github.com/stanford-cs336/lectures/blob/main/lecture_15.pdf

[course] Stanford CS336 Spring 2026：官方课程与讲次索引

https://cs336.stanford.edu/

[captions] Lecture 15公开录像字幕第三方缓存：仅作核验转述，非审校逐字稿

https://jingzechen.github.io/assets/courses/stanford-cs336-s26/lectures/015/captions.source.srt

[instructgpt] Ouyang et al. 2022：Training language models to follow instructions with human feedback，原论文

https://arxiv.org/abs/2203.02155

[stiennon] Stiennon et al. 2020：Learning to summarize from human feedback，原论文

https://arxiv.org/abs/2009.01325

[camels] Wang et al. 2023：How Far Can Camels Go?，指令数据比较原论文

https://arxiv.org/abs/2306.04751

[alpacafarm] Dubois et al. 2023：AlpacaFarm，偏好模拟与过优化原论文

https://arxiv.org/abs/2305.14387

[gekhman] Gekhman et al. 2024：Does Fine-Tuning LLMs on New Knowledge Encourage Hallucinations?，原论文；校正原页年份

https://aclanthology.org/2024.emnlp-main.444/

[safetyfew] Bianchi et al. 2023：Safety-Tuned LLaMAs，少量安全示范原论文

https://arxiv.org/abs/2309.07875

[minicpm] Hu et al. 2024：MiniCPM，分阶段训练原论文

https://arxiv.org/abs/2404.06395

[tulu3] Lambert et al.：Tülu 3，公开后训练配方与长度归一化DPO原论文

https://arxiv.org/html/2411.15124v4

[opinions] Santurkar et al. 2023：Whose Opinions Do Language Models Reflect?，原论文

https://arxiv.org/abs/2303.17548

[humanfeedback] Hosking et al.：Human Feedback is not Gold Standard，ICLR 2024原论文

https://arxiv.org/abs/2309.16349

[cai] Bai et al. 2022：Constitutional AI: Harmlessness from AI Feedback，原论文

https://arxiv.org/abs/2212.08073

[ppo] Schulman et al. 2017：Proximal Policy Optimization Algorithms，原论文

https://arxiv.org/abs/1707.06347

[dpo] Rafailov et al.：Direct Preference Optimization，原论文§4及附录A

https://arxiv.org/html/2305.18290v3

[simpo] Meng et al.：SimPO，原论文§2.2，含长度归一化与目标间隔

https://arxiv.org/html/2405.14734v3