
Global Parameters

Parameter	Value
VCC Pin	20
GND Pin	10
VCC Voltage	[5]
Input Low	[0.8]
Input High	[2]
Output Low	[0.4]
Output High	[3.7]

Tests: **IC FAIL 4/6**

Buffer 1 Disabled: FAIL

Inputs		Outputs/Results							
1	2, 4, 6, 8	18		16		14		12	
H	X	Z	1.68 (U)	Z	1.68 (U)	Z	1.68 (U)	Z	1.68 (U)

Buffer 1 A=L -> Y=L: PASS

Inputs		Outputs/Results							
1	2, 4, 6, 8	18		16		14		12	
L	L	L	0.15 (L)	L	0.09 (L)	L	0.09 (L)	L	0.09 (L)

Buffer 1 A=H -> Y=H: PASS

Inputs		Outputs/Results							
1	2, 4, 6, 8	18		16		14		12	
L	H	H	4.92 (H)	H	4.94 (H)	H	4.95 (H)	H	4.95 (H)

Buffer 2 Disabled: FAIL

Inputs		Outputs/Results							
19	11, 13, 15, 17	9		7		5		3	
H	X	Z	1.7 (U)	Z	1.68 (U)	Z	1.68 (U)	Z	1.68 (U)

Buffer 2 A=L -> Y=L: *PASS*

Inputs		Outputs/Results							
19	11, 13, 15, 17	9		7		5		3	
L	L	L	0.1 (L)	L	0.09 (L)	L	0.09 (L)	L	0.09 (L)

Buffer 2 A=H -> Y=H: *PASS*

Inputs		Outputs/Results							
19	11, 13, 15, 17	9		7		5		3	
L	H	H	4.87 (H)	H	4.95 (H)	H	4.95 (H)	H	4.95 (H)