ORB-SLAM with a Generalized Camera

3D Vision Project Proposal Supervised by: Peidong Liu and Dominik Honegger March 14, 2016

GROUP MEMBERS

Lukas Bischofberger



Marius Grimm



Leonard Schai



Tobias Ulrich



I. DESCRIPTION OF THE PROJECT

ORB-SLAM [3] is one of the state-of-the-art feature based simultaneous localization and mapping (SLAM) algorithms. It currently supports monocular and stereo configurations. However, due to the limited field of view (FoV) of the cameras, it would be beneficial for environment perceptions if we can have 360-degrees FoV.

The idea for this project is to extend the current ORB-SLAM algorithm to support a generalized camera [5]. A sensor board with up to eight synchronized global-shutter cameras is currently under construction and is hoped to be ready by the end of the semester to be used as a generalized camera to provide 360-degress FoV. For now data from the V-charge car project with 4 fisheye cameras is available.

II. WORK PACKAGES AND TIMELINE

- a) Change current camera distortion model to fisheye cameras and convert fisheye data
- 1) 2D-2D motion estimation with generalized camera model (4/8 cameras) ([4], [2], [5])
- 2) 3D-2D NPnP (non-perspective n points) pose estimation ([4], [2], [1])
- 3) ORB-SLAM: ([4], [2], [3])
 - a) Tracking part
 - i) Replace current monocular 2D-2D motion estimation for initialization with 1)
 - ii) Replace 3D-2D pose estimation for re-localization with 2)
 - b) Mapping part
 - i) Modify current monocular triangulation method to support generalized camera
 - c) Other common technical issues
 - i) Modify Frame, KeyFrame, Map classes etc. to support generalized camera
 - ii) Modify Bundle-Adjustment cost function to support new feature position parametrization with Plucker line
 - iii) etc.

At the very beginning we first have to adjust the camera distortion model of the SLAM-algorithm since currently pinhole-cameras are assumed. However, we only have fisheye data at our disposal.

The minimum requirements for the system to work are modifications of the current monocular SLAM under part 3) but also the implementation of the 2D-2D motion estimation with a generalized camera under 1).

After those parts are working the replacement of the 3D-2D pose estimation for re-localization under 3a) (with 2.) is going to be implemented next.

Since the different work packages are all interlinked it is difficult to divide the responsibilities. Yet, Tobias and Marius are going to start working on the Tracking part while Lukas and Leonard work on the Mapping part. After those work packages are completed the group will collectively modify other common technical issues. Those

minimum requirements are planned to be working by the end of April.

The monocular SLAM algorithm is provided and implemented in C++ and ROS and the operating system of our choice is Linux. For the modifications towards a generalized SLAM algorithm the library OpenGV is going to be used.

III. OUTCOMES AND DEMONSTRATION

The outcome of the project is planned to be a real-time running algorithm which is able to localize, track and map more stable and with higher precision than the monocular algorithm.

As offline presentation we have rosbags available with recorded data of a monocular camera. For the fisheye cameras we first have to record the data in rosbags ourselves.

We will present our algorithm offline with the image data from multiple fisheye cameras. If already available at this point in time, also the 8-camera-system could be demonstrated offline or even online.

REFERENCES

- [1] L. Kneip, P. Furgale, and R. Siegwart. Using multi-camera systems in robotics: Efficient solutions to the npnp problem. In *Robotics and Automation (ICRA)*, 2013 IEEE International Conference on, pages 3770–3776, May 2013.
- [2] Hongdong Li, R. Hartley, and Jae hak Kim. A linear approach to motion estimation using generalized camera models. In *Computer Vision and Pattern Recognition*, 2008. CVPR 2008. IEEE Conference on, pages 1–8, June 2008.
- [3] R. Mur-Artal, J. M. M. Montiel, and J. D. Tardos. Orb-slam: A versatile and accurate monocular slam system. *IEEE Transactions on Robotics*, 31(5):1147–1163, Oct 2015.
- [4] R. Pless. Using many cameras as one. In Computer Vision and Pattern Recognition, 2003. Proceedings. 2003 IEEE Computer Society Conference on, volume 2, pages II–587–93 vol.2, June 2003.
- [5] Henrik Stewenius, D. Nistér, Magnus Oskarsson, and Karl Åström. Solutions to minimal generalized relative pose problems. 2005.