



## SILVER DYNAMIC AGM





- Start-Stop
- VARTA AGM (Absorbent Gla Mat)
- – 20% 20%  
ecosteps®
- PowerFrame®

: [www.varta-automotive.com](http://www.varta-automotive.com)

|      |                   |
|------|-------------------|
| ETN: | 595 901 085       |
| :    | 595 901 085 D85 2 |
| :    | G14               |
| :    | 4016987144527     |
| UK : | 019AGM            |
| :    | 1                 |
| :    | 36                |

|         |     |      |        |
|---------|-----|------|--------|
| [ ]:    | 12  | :    | B13    |
| [ ]:    | 95  | :    | 0      |
| EN [ ]: | 850 | :    | 1      |
| [ ]:    | 353 | :    | H8/LN5 |
| [ ]:    | 175 | ( ): | 26,4   |
| [ ]:    | 190 |      |        |



### VARTA SILVER DYNAMIC

### AGM

- Проектиран с усъвършенствана технология Absorbent Glass Mat (AGM)
- Технологията AGM предотвратява корозия, дължаща се на киселинно разслояване
- Максимална мощност, изключителна циклична устойчивост и защита от пропитане
- Електролитът, попит в сепаратор от пътна стъкленовлакнеста тъкан, упражнява равномерно, високо контактно налягане

Херметичен капак с обезопасяващи клапани и едноочково вентилиране



**SILVER dynamic AGM****BLUE dynamic EFB**

|   |                           |                                |
|---|---------------------------|--------------------------------|
|   | 5                         | 5                              |
|   | Start-Stop                | Start-Stop                     |
|   | CCA 135 %                 | CCA 115 %                      |
|   | AGM – Absorbent Glass Mat | EFB – Enhanced Flooded battery |
| / | PowerFrame® /             | PowerFrame® /                  |
|   | OE                        | OE                             |
|   | 3x *                      | 2x *                           |
|   | *                         | *                              |

\*