Here comes the title page that you can download from Plato

"The author gives permission to make this master dissertation available for consultation and to copy parts of this master dissertation for personal use. In all cases of other use, the copyright terms have to be respected, in particular with regard to the obligation to state explicitly the source when quoting results from this master dissertation."

Ghent, June [year]
[Name]

Preface

[Preface]

Title

[Name]

Supervisor:
Counsellors:

Master's dissertation submitted in order to obtain the academic degree of
Master of Science in Electromechanical Engineering

Departement of Electromechanical, Systems and Metal Engineering
Chair:
Faculty of Engineering and Architecture
Ghent University
Academic year 2025–2026

Summary

Keywords:

MASTER THESIS 20xx-20xx
Research group Sustainable Thermo-Fluid Energy Systems
Department of Electromechanical, Systems and Metal Engineering – Ghent University, UGent

TITLE

Student 1, Student 2, Supervisor 1, Supervisor 2, Promoter
Department of Electromechanical, Systems and Metal Engineering
Ghent University
Sint-Pietersnieuwstraat 41, B9000 Gent, Belgium
E-mail: E-mail

ABSTRACT

The abstract of your paper should be located here. It should be a single paragraph and complete in itself (no references or equations). It should indicate the subjects dealt with in the paper and state the objectives of the investigation in about 200 words. Newly observed facts and conclusions of the experiment or argument discussed in the paper must be stated in summary form.

INTRODUCTION

This document is a LaTeX [1] template for the paper that should be included in the master thesis of the students of the research group Applied Thermodynamics and Heat Transfer. A similar template is available for MS Word documents. The length of the paper should be six pages, double column.

CONTENTS

The first section of the paper is the abstract. The content required for the abstract is discussed in this section.

On the first page and on top of the right column, the table with the nomenclature used in the paper should be visible. All symbols used in the text should be placed in alphabetic order in this table, together with their respective unit and explanation. A separate section is provided for special characters (Greek, cursive, ...). A final section is available for the used subscripts.

The first section of the main text is the introduction. This part explains the global context of the research. Related research works are referenced and used to explain why this work is unique, needed or necessary.

The next sections typically consists three main parts, however the division in sections is up to the author and does not have to be strictly related to the three parts. In a first part, the manner of execution of the research in described. This can be the equations used for modelling, the set-up design for experiments, etc. The second part is displaying the results of the work, usually in the form of figures and graphs. After the results, a discussion is made regarding the results. Explain if the results are expected or unexpected, concur with the current premises in literature or not, etc. This last part can also be combined with the second part.

At the end of the main text, a conclusion is added. In the conclusion, the main results of the work are repeated. It should consist of the main ideas, principles, etc. that a reader should remember after having read the paper.

The last part of the paper are the references. The IEEE style is used in this paper. The references are numbered and ordered chronologically as they appear in the text. Referencing in the text is done by adding the number of the respective paper in between square brackets in or at the end of a sentence.

NOMENCLATURE

D	$[m]$	Diameter
f	$[-]$	Friction factor
Nu	$[-]$	Nusselt number
Pr	$[-]$	Prandtl number
Re	$[-]$	Reynolds number
v	$[m/s]$	Flow velocity
Special characters		
ν	$[m^2/s]$	Kinematic viscosity
Subscripts		
d		Darcy
h		Hydraulic

TEXT FORMATTING

The paper formatting should remain the same as in the template (A4 paper, double column, 10pt font size). Please do not number the pages of your paper. The body of the text is justified. Footnotes should be

avoided.

The section titles are used as defined in the template, do not number them. The main section title is 10pt upper-case bold. The subsection title is 10pt bold. Do not use further subdivisions in the text, this should be avoided in scientific papers.

Equations are entered using the standard equation environment or equivalent environments in LaTeX. Arabic numerals are used to number the equations, enclosed between parentheses and right-aligned, as shown in equations 1 and 2. Equations are referenced as shown in the previous sentence. All the symbols and notation must be defined where they are first used in the text, as well as in the nomenclature. Physical quantities must be expressed in the SI (metric) units.

$$Re = \frac{vD_h}{\nu} \tag{1}$$

$$Nu = \frac{(f_d/8)(Re - 1000)Pr}{1 + 12.7(f_d/8)^{1/2}(Pr^{2/3} - 1)} \tag{2}$$

Equation 1 defines the Reynolds number Re, using the flow velocity v, the hydraulic diameter D_h and the kinematic viscosity ν. Equation 2 is the Gnielinski correlation for internal turbulent flow, forced convective heat transfer [2]. The symbols used are the Nusselt number Nu, the Darcy friction factor f_d and the Prandtl number Pr.

Figures and tables are placed in the text using the standard figure and table environments or equivalent environments, as shown in figure 1 and table 1. Figures and tables are referred to as shown in the previous sentence. The figures and tables themselves as well as their captions are centered.

Figure 1: This is the caption of an example figure.



Table 1: This is the caption of an example table.

	Attribute A	Attribute B
Experiment 1	1 m	2 s
Experiment 2	2 m	5 s

The caption for figures should be located below the figure. Make sure the all lines are clearly visible and that there is a clear color or formatting contrast between different lines. Axis labels and legends should be large enough (approximately the same size as the body text) to be legible. The quality of the figures should be high enough to have clear and sharp images.

The caption of a table is located above the table. The font size and style of the text in tables should be similar to that of the body text. The table borders can be chosen freely.

CONCLUSION

This document provides a template for master thesis students to make a paper using LaTeX. It explains what is expected of the content and of the formatting of the paper.

REFERENCES

[1] "LaTeX - a document preparation system." URL: https://www.latex-project.org/. Accessed: 2017-04-25.

[2] V. Gnielinski, "New equations for heat and mass-transfer in turbulent pipe and channel flow," *International chemical engineering*, vol. 16, no. 2, pp. 359–368, 1976.

Contents

Preface **3**

Abstract **4**

Extended Abstract **5**

Table of Contents **7**

List of Figures **9**

List of Tables **10**

Nomenclature **11**

1 Introduction **14**
1.1 The imperative for decarbonization in the building sector 14
1.2 The role of heat pumps and challenges in refurbishment 14
1.3 The Transition to Renewable Heat Supply: Challenges and Solutions 15
1.3.1 Flexibility through Electrification and Storage 15
1.4 The design gap: From static rules to dynamic optimization 15
1.5 Thesis Objective 16
1.5.1 Case Study Application: Transitioning M-accent from Gas to Hybrid Electrification 16

2 Literature review **17**
2.1 Modeling methods of complex energy systems 17
2.1.1 Non-Linear Programming 17
2.1.2 Heuristic and Meta-heuristic Algorithms 17
2.1.3 Stochastic and Hybrid Modeling Methods 18
2.1.4 Why MILP is the Preferred Method for This Study 19
2.1.5 MILP-based design optimisation framework. 20
2.2 Mixed-Integer Linear Programming (MILP) 22
2.2.1 MILP algorithm 22
2.2.2 Parallel Processing and Pruning 24
2.2.3 MILP advantages 24
2.2.4 Optimization Objective Functions in MILP 25
2.2.5 epsilon constrained method to create pareto front 26
2.3 Component Modeling in Optimization Frameworks 27
2.3.1 Component model requiremnts 27
2.3.2 Lorentz Heat Pump Model Implementation 28
2.3.3 Linearization for MILP: 29
2.3.4 Thermal Energy Storage (TES) Modeling 29

2.3.5 Photovoltaic (PV) System modeling . . . 33
2.3.6 Battery Energy Storage Systems (BESS) . . . 35
2.3.7 Inverter modeling . . . 36
2.3.8 Part-Load Operation HTHP . . . 38
2.4 Conclusion . . . 39

3 Methodology **40**
3.1 Input Data and Pre-Processing . . . 40
3.2 Component Models . . . 40
3.2.1 High-Temperature Heat Pump (HTHP) . . . 41
3.2.2 Photovoltaic (PV) Array . . . 43
3.2.3 Battery Energy Storage System (BESS) . . . 43
3.2.4 Thermal Energy Storage (TES) . . . 43
3.2.5 Electric Boiler (Auxiliary Heater) . . . 43
3.3 System Energy Balance Constraints . . . 43
3.4 Objective Function . . . 43
3.5 Solver Configuration and Solution Strategy . . . 43

Bibliography **46**

A Datasheet HTHP Daikin EWYE-CZ **47**

B Title appendix B **49**

List of Figures

2.1 Overview of the proposed MILP-based design optimisation framework. 21
2.2 Energy system schematic of the studied commercial building configuration, showing the electricity and thermal energy flows between all components. Dashed arrows indicate technologies to be replaced; solid orange arrows denote electricity flows; solid red arrows denote thermal flows. 22
2.3 Schematic of the Solution approach of MILP [23] 23
2.4 Schematic pareto Front[26] 27
2.5 Schematic of the simplified 2-zone model of a stratified thermal storage with constant hot (T_{H}) and cold (T_{C}) temperature regions [13]. 31
2.6 Comparison of storage content decay over time (left) and heat losses versus actual storage content (right) for a simple thermal storage model and stratified thermal storage models of different nominal capacities (30 MWh, 65 MWh, and 90 MWh) [13]. 33
2.7 Inverter Part-Load Efficiency. This graph illustrates how inverter efficiency varies with the load fraction, showing different nominal efficiencies and a comparison to PVWatts V1. 37

List of Tables

2.1 Comparative overview of TES technologies considered for HTHP-coupled building applications. 30
2.2 PV Model Variables and Base Values 34
2.3 Empirically determined coefficients used to predict PV module back surface temperature (Extracted from source data) [34]. 34

3.1 Complete HTHP constraint set embedded in the MILP. $\kappa(t)$ and COP(t) are pre-computed parameter arrays; all other symbols are MILP variables. 43

Nomenclature

Abbreviations

ANF Annuity Factor

BESS Battery Energy Storage System

COP Coefficient of Performance (HP efficiency metric)

DER Distributed Energy Resource

DHW Domestic Hot Water

HPS Heat Pump System

HP Heat Pump

MILP Mixed-Integer Linear Programming

MINLP Mixed-Integer Non-Linear Programming

OP Operation Point (for linearization reference)

PV Photovoltaic

PWL Piecewise Linear (approximation)

SH Space Heating

TES Thermal Energy Storage

TRY Test Reference Year (used for clustered data)

Greek Symbols

$\boldsymbol{\alpha}$ User preference factor (Weighting factor for cost) [-]

$\boldsymbol{\beta}$ Weighting factor for comfort ($\alpha + \beta = 1$) (EWH) [-]

$\boldsymbol{\Delta\tau}$ Longer discretization period for TES/Supply [s]

$\boldsymbol{\Delta t}$ Time step size for heat generation [s]

$\boldsymbol{\delta(t)}$ Auxiliary variable for PWL approximation (binary) [-]

$\boldsymbol{\eta}_{\mathrm{HP}}$ HP efficiency factor [-]

$\boldsymbol{\eta}$ Efficiency (General) [-]

$\boldsymbol{\gamma}_{\mathrm{pdc}}$ Temperature coefficient of power (PV) [%/°C]

$\boldsymbol{\gamma}$ Coefficient for TES lateral surface loss

$\boldsymbol{\kappa}$ Electricity price [€/kWh]

$\boldsymbol{\lambda}$ Thermal conductivity of water [W/(m K)]

$\boldsymbol{\mu}$ Scale factor (EWH objective function) [°C/€]

$\boldsymbol{\rho_w}$ Water density [kg/m^3]

$\boldsymbol{\theta}$ Time step ratio ($\Delta\tau/\Delta t$) [-]

Letters

$\boldsymbol{\dot{Q}_{HP}}$ Heat output of HP [W]

$\boldsymbol{A}_{\text{ref.}}$ Surface area of one PV module (reference)

$\boldsymbol{c_w}$ Specific heat capacity of water [J/(kg K)]

$\boldsymbol{CC}$ Cooling Capacity during defrost operation [W]

$\boldsymbol{C}$ Electricity Cost [€]

$\boldsymbol{DT}$ Acceptable Water Temperature Differential [°C]

$\boldsymbol{D}$ Comfort Index (Quantifies thermal discomfort) [°C]

$\boldsymbol{d}$ TES diameter

$\boldsymbol{FD}$ Fluid Density [g/L]

$\boldsymbol{f}$ Objective function (Total minimized cost/discomfort)

$\boldsymbol{G}_{\text{POA}}$ Solar irradiance in the Plane of Array [W/m^2]

$\boldsymbol{h}$ Height of TES

$\boldsymbol{MDD}$ Max Defrost Duration [s]

$\boldsymbol{P_0}$ Rated heating power of EWH [W]

$\boldsymbol{P}_{\text{DC}}$ DC power output of PV system [W]

$\boldsymbol{P}_{\text{STC}}$ Nominal DC power for one PV module [W]

$\boldsymbol{P_{el,HP}}$ Electric power consumed by HP [W]

$\boldsymbol{Q}_{\text{N}}$ Nominal capacity of TES

$\boldsymbol{Q_t}$ Stored energy in TES at time t

$\boldsymbol{R}$ Water heater thermal resistance [K·day/kWh]

$\boldsymbol{SH}$ Specific Heat of fluid [J/(g·°C)]

$\boldsymbol{T}_{\text{amb}}$ Ambient outdoor air temperature (OAT) [°C]

$\boldsymbol{T}_{\text{biv}}$ Bivalence temperature (Reference design point) [K]

$\boldsymbol{T}_{\text{cell}}$ PV cell temperature [°C]

$\boldsymbol{T}_{\text{exp}}$ Most desirable tap water temperature [°C]

$\boldsymbol{T}_{\text{High,mean}}$ Mean temp. of delivered hot water [K]

$\boldsymbol{T}_{\text{inlet}}$ Temperature of cold water flowing into the tank [°C]

$\boldsymbol{T_{cw}}$ Temperature of cold mixing water [°C]

$\boldsymbol{T_{in}}$ Water temperature in EWH/TES tank [°C]

$\boldsymbol{T_{max}}$ Maximum temperature EWH tank can withstand [°C]

$\boldsymbol{T_{ref}}$ Reference temperature [°C]

$\boldsymbol{T_{tap}}$ Current tap water temperature [°C]

$\boldsymbol{u(t)}$ On/off status variable of EWH (binary) [-]

$\boldsymbol{v}_{\text{wind}}$ Wind velocity [m/s]

$\boldsymbol{x(t)}$ Switch-on signal of EWH (binary) [-]

$\boldsymbol{y(t)}$ Switch-off signal of EWH (binary) [-]

$\boldsymbol{y_{HP,TES}}$ Binary on/off status of HP for a given TES [-]

Chapter 1

Introduction

1.1 The imperative for decarbonization in the building sector

The global energy transition is increasingly focused on the urgent need to reduce greenhouse gas emissions and mitigate climate change. A critical battleground in this transition is the building sector, which remains a significant contributor to energy use and carbon emissions. For instance, in Belgium alone, the building sector[1] is responsible for approximately 20% of total carbon dioxide (CO_2) emissions in 2022 [1]. To meet ambitious climate goals, such as those outlined by the European Union, there is a pressing need to decarbonize the heat supply for buildings. Under the *European Climate Law*, the EU is legally committed to a progressive decarbonization pathway: a net greenhouse gas (GHG) emissions reduction of at least 55% by 2030 (compared to 1990 levels), an intermediate target of 90% by 2040, and the ultimate goal of climate neutrality by 2050 [2, 3]. For the building sector specifically, the revised *Energy Performance of Buildings Directive* (EPBD) mandates that all new buildings must be Zero-Emission Buildings (ZEB) by 2030, with a complete phase-out of fossil-fuel-based heating systems required by 2040 [4]. The significance of the building sector in this context stems largely from the high carbon intensity of thermal energy demands. Space heating (SH) and domestic hot water heating (DHW) account for approximately 77,6% of the total energy consumption in residential buildings in Belgium in 2023 [5]. Because much of this demand is currently met through the direct combustion of fossil fuels, such as natural gas and heating oil, the thermal energy share is the primary driver of the sector's operational CO_2 emissions. This transition relies heavily on shifting away from fossil-fuel-based systems, such as gas boilers, toward electrification using renewable energy sources (RES) [6] [7].

1.2 The role of heat pumps and challenges in refurbishment

Heat pump systems (HPSs) have emerged as a key technology for electrifying space heating (SH) and domestic hot water (DHW) production[7]. Their ability to generate thermal energy efficiently from electricity makes them a cornerstone of sustainable building energy systems. However, the widespread adoption of heat pumps faces significant economic barriers, particularly in the refurbishment of existing buildings. In these scenarios, heat pumps often compete with gas boilers, which traditionally have lower investment costs. Furthermore, older buildings often utilize radiator heating systems requiring high flow temperatures (up to $70°C$), unlike modern underfloor heating. Consequently, heat pumps for elevated temperatures are essential for these applications to ensure comfort without extensive renovations. To increase market penetration and motivate homeowners to switch to low-carbon solutions, HPSs must become more

[1] In this context, the building sector definition follows the European climate reporting categories, which encompass direct emissions from fossil fuel combustion in residential and tertiary (commercial/institutional) buildings, as well as energy-related emissions from the agriculture and fishery sectors.

economically competitive. The Flemish government and the heat pump sector have recently established a collaborative framework to address these economic barriers and accelerate the deployment of HPSs [8]. To shift the market from a 10% adoption rate toward a 70% target for renovations, the strategy focuses on three primary economic levers. First, capital barriers are mitigated through substantial direct subsidies, where premiums can reach up to €8,000 per installation. Furthermore, the provision of interest-free or low-interest renovation loans allows for the pre-financing of the high upfront costs, aligning the investment with long-term energy savings. Second, a strategic energy tax shift is being implemented to reduce the price of electricity relative to fossil fuels, ensuring that HPSs remain the most cost-effective solution for daily operation. Finally, the industry has committed to a "Heat Pump Charter" to enhance installation quality and provide standardized technical guidance, ensuring that systems are optimized for the specific flow requirements of refurbished buildings [8].

1.3 The Transition to Renewable Heat Supply: Challenges and Solutions

The urgent need to reduce dependence on fossil fuels has accelerated the integration of Renewable Energy Sources (RES), such as Photovoltaic (PV) systems, into the built environment. This shift is a cornerstone of sustainable development, yet the transition toward a fully renewable heat supply introduces a fundamental challenge: the intermittency of sources like solar and wind. Unlike fossil fuels, where energy supply is constant and dispatchable, the generation of RES fluctuates based on weather conditions. This stochastic nature poses a direct risk to grid stability and the security of energy supply.

1.3.1 Flexibility through Electrification and Storage

To mitigate these fluctuations and ensure reliability, the electrification of heat demand must be supported by intelligent control and storage technologies. The following components are essential to framing this transition:

- **Demand Side Management (DSM):** This strategy steers electrical loads to match the availability of renewable generation, optimizing the timing of consumption.
- **Thermal Energy Storage (TES):** By coupling TES units with heat pumps, heat generation can be decoupled from immediate demand. This provides the necessary flexibility to shift electrical loads to periods when renewable electricity is abundant or cheaper.
- **Electrical Storage (Batteries):** Integrating battery systems alongside PV generation further stabilizes the grid by maximizing self-consumption and reducing peak loads on the distribution network.

While the synergy between PV systems, heat pumps, and storage technologies offers a robust path toward a fossil-free future, it introduces significant layers of control complexity. The primary challenge lies in balancing the maximization of energy savings and grid support with the non-negotiable requirement of maintaining user comfort, such as consistent domestic hot water temperatures and a stable indoor climate.

1.4 The design gap: From static rules to dynamic optimization

Despite the clear benefits of hybrid energy systems, current design practices remain a bottleneck. European normative standards for dimensioning HPSs (such as EN 15450 [9]) typically rely on static rules and single operating points. These procedures often determine the size of individual

components sequentially, neglecting the complex interdependencies between the heat pump, storage sizing, and control strategies. This static approach can lead to sub-optimal designs. Furthermore, the optimal size of a system is heavily dependent on its operation; a system designed without considering its control strategy may be oversized and economically inefficient [10]. Therefore, to achieve a truly optimal and sustainable design, dimensioning and operation must be optimized simultaneously. By optimizing the system, we can reduce investment costs significantly about 45% in comparison to normative standards, while maintaining security of supply and not increasing electrical energy consumption[11].

1.5 Thesis Objective

This thesis aims to bridge this gap by developing a comprehensive design tool in Python using MILP. The tool will determine the optimal economic sizing of a hybrid energy system comprising a High-Temperature Heat Pump (HTHP), Photovoltaics (PV), Battery storage, and Thermal Energy Storage (TES). By incorporating detailed modeling of system dynamics and component interdependencies, this work seeks to provide a solution that is not only economically viable but also environmentally sustainable, accelerating the decarbonization of the residential heating sector.

1.5.1 Case Study Application: Transitioning M-accent from Gas to Hybrid Electrification

The practical necessity for advanced optimization is exemplified by the M-accent case study, which currently relies on two 80 kW gas boilers for its primary heat supply. Decarbonizing such a system requires a transition to a hybrid energy architecture. To replace the existing 160 kW fossil-fuel capacity, this thesis proposes a system integrating a High-Temperature Heat Pump (HTHP), Photovoltaics (PV), Battery Energy Storage Systems (BESS), and Thermal Energy Storage (TES).

The integration of these technologies presents a complex sizing problem that exceeds the capabilities of static design standards like EN 15450 [9]. Specifically, the design tool developed in this work addresses the following technical challenges identified in literature:

- **HTHP Performance:** Unlike traditional boilers, the capacity and Coefficient of Performance (COP) of HTHPs are highly dependent on source and sink temperatures. Following the methodology of Krützfeldt et al. [11], the tool utilizes MILP to account for these non-linearities through piecewise linear approximations or regressive modeling based on manufacturer data, such as the Daikin EWYE-CZ.

- **Storage Synergies:** The tool optimizes the trade-off between electrochemical (Battery) and thermal (TES) storage. While batteries facilitate PV self-consumption, TES allows for the decoupling of heat production from demand, which is crucial for managing the peak loads previously handled by the 80 kW boilers [12, 13].

- **Economic Dispatch:** By utilizing MILP, the tool simultaneously determines the optimal investment (sizing) and the hourly operational strategy (dispatch) to minimize the Total Cost of Ownership (TCO), accounting for fluctuating electricity prices and Belgian climate targets [1].

Ultimately, this tool serves as a bridge between high-level decarbonization goals and the engineering reality of the M-accent project, providing a robust mathematical framework to ensure that the replacement of gas-fired assets results in both economic and environmental gains.

Chapter 2

Literature review

2.1 Modeling methods of complex energy systems

2.1.1 Non-Linear Programming

These methods are used when the system's physical laws are mathematically non-linear and an exact representation is preferred over the linearization required by MILP.

- **Mixed-Integer Non-Linear Programming (MINLP)**: The direct alternative to MILP. It allows for **non-linear expressions** (like squares or products of variables) while retaining binary variables to model discrete decisions (e.g., component sizing or on/off status).
- **Non-Linear Programming (NLP)**: Similar to MINLP but excludes integer variables. It is faster than MINLP but cannot be used for sizing problems. Used for **operational optimization** after component sizing is fixed.
- **Dynamic Programming (DP)**: Breaks down a complex problem into a sequence of simpler subproblems. It is often used for energy storage dispatch problems (Battery, TES) to find the global optimum over a large time horizon.

2.1.2 Heuristic and Meta-heuristic Algorithms

These methods use iterative search techniques and do **not guarantee a globally optimal solution**, but can handle highly complex, non-linear, and non-convex problems that MILP and MINLP struggle with.

- **Genetic Algorithms (GA)**: Inspired by natural selection, it evolves a population of solutions (designs) based on a fitness function (cost/emissions). Often used for simultaneous **sizing and scheduling** of hybrid renewable systems (PV-BESS).

  Simple analogy: A GA works like a breeding programme for solutions. It starts with a random population of candidate designs (e.g. different combinations of PV capacity, battery size, and dispatch schedule). In each generation, the fittest individuals i.e. those with the lowest cost or emissions, are selected to "reproduce": their parameters are combined (*crossover*) and slightly perturbed (*mutation*) to produce offspring. Over many generations, the population converges toward near-optimal solutions, much like how selective breeding improves a trait in animals over successive generations.

  Example: Mahesh and Sandhu [14] applied a GA to optimally size a grid-connected PV–wind–battery hybrid system. Each individual in the population encodes the number of PV modules, wind turbines, and battery units. The fitness function minimises the total

system cost while satisfying a reliability constraint (battery state of charge and power-balance). The GA converges to a Pareto-optimal sizing configuration that outperforms classical rule-based approaches in both cost and reliability.

- **Particle Swarm Optimization (PSO)**: Iteratively improves a candidate solution based on the movement of particles in the search space. Used for sizing optimization.

  Simple analogy: Imagine a flock of birds searching a field for the best patch of food. Each bird (particle) remembers the best location it has personally visited, and also knows the best location found by any bird in the flock. At each time step, every bird adjusts its velocity ,moving partly toward its own best-known spot and partly toward the swarm's global best, gradually converging on the optimal location. In an energy system context, each particle encodes a candidate sizing solution (e.g. PV capacity, battery size), and the "food" is the minimum cost or maximum reliability.

  Example: Mohamed et al. [15] applied PSO to optimally size a grid-connected hybrid PV–wind–battery–diesel system for remote areas in Saudi Arabia. Each particle represents a combination of component sizes, and the fitness function minimises the *Loss of Load Probability* (LOLP) and total cost simultaneously. A smart-grid load-shifting strategy was integrated to reshape the demand profile, further reducing required storage capacity.

- **Simulated Annealing (SA)**: A probabilistic technique used to approximate the global optimum of a non-convex objective function by iteratively exploring the solution space and occasionally accepting worse solutions to escape local optima.

  Simple analogy: SA is inspired by the physical process of slowly cooling molten metal. A blacksmith heats steel until the atoms move freely, then cools it gradually so they settle into a low-energy, stable crystalline structure. If cooled too quickly, defects are trapped; if cooled slowly, the atoms find near-perfect arrangements. In optimization, the "temperature" controls how willing the algorithm is to accept a worse solution. At high temperature, the algorithm explores broadly and accepts bad moves freely — avoiding entrapment in local optima. As the temperature is gradually reduced (*cooling schedule*), the algorithm becomes increasingly selective, eventually converging on a near-global optimum. This makes SA particularly suited to the **non-linear, non-convex** sizing problems typical of hybrid renewable energy systems.

  Example: Ekren and Ekren [16] applied SA to size a stand-alone PV–wind–battery hybrid system for a campus in Turkey. The decision variables were PV array size, wind turbine rotor swept area, and battery capacity. The objective function minimised total system cost subject to a reliability constraint.

2.1.3 Stochastic and Hybrid Modeling Methods

These methods address the inherent limitations of deterministic MILP related to computational load and parameter certainty.

- **Stochastic Programming (SP)**: Integrates **uncertainty** (e.g., volatile electricity prices, uncertain PV output) into the optimization by using multiple scenarios with associated probabilities. Used to determine a system size that is optimal for the *expected cost*.

- **Robust Design Optimization (RDO)**: A specific type of SP that aims to minimize the sensitivity of the solution to external parameters, ensuring the design performs well even under "worst-case" scenarios.

- **Hybrid Optimization Algorithm (HOA)**: Combines the strength of accurate MILP for sizing over *representative days* with a faster heuristic or data-driven model for calcu-

lating the *actual annual operating costs*. This offers a major speed advantage, addressing the core computational bottleneck of full-year MILP models.

- **Simulation-Based Optimization**: Couples an accurate black-box simulator (like TRNSYS) with an external meta-heuristic algorithm (GA or PSO) to iteratively search for the optimal design within the simulator's bounds.

2.1.4 Why MILP is the Preferred Method for This Study

Several modelling paradigms exist for the analysis and design of energy systems. Ringkjøb et al. provide an extensive review of 75 modelling tools and classify them along two independent axes: *purpose* (investment decision support, operation decision support, scenario analysis, power system analysis) and *methodology* (simulation, linear programming, mixed-integer linear programming, non-linear programming, and heuristic optimisation) [17]. This classification underscores that the choice of modelling method is primarily driven by the research objective rather than by system complexity alone; complexity acts as a secondary constraint that determines which methods remain computationally tractable.

The preceding overview of optimization methods reveals a clear hierarchy of suitability when the objective is to simultaneously size and schedule a multi-technology energy system for a commercial building. This section argues why MILP is the most appropriate framework for the specific system under study, comprising a high-temperature heat pump (HTHP), photovoltaic (PV) system, battery energy storage system (BESS), and thermal energy storage (TES).

Global Optimality and Determinism

The most fundamental advantage of MILP over heuristic and meta-heuristic methods (GA, PSO, SA) is its guarantee of a **globally optimal solution**. As established before, methods such as GA and PSO do not guarantee global optimality; they converge on near-optimal solutions whose quality depends on population size, tuning parameters, and random initialisation. MILP, by contrast, is a **deterministic** method: given the same input data, it always returns the same certified optimal solution within a defined optimality gap[1]. This is a critical requirement for an investment decision tool, where the result must be defensible and reproducible [18].

Simultaneous Sizing and Scheduling

The energy system in this study requires **coupled sizing and operational optimization**: the optimal capacity of the BESS and TES depends directly on how they are dispatched, and vice versa. MILP naturally handles this coupling in a single mathematical formulation. Binary decision variables represent discrete on/off states of the HTHP and charging/discharging modes of storage, while continuous variables represent energy flows and component capacities. This avoids the sequential, decoupled approach common in simulation-based methods (e.g., TRNSYS-coupled GA), which may yield suboptimal designs because sizing and scheduling are not optimized simultaneously [19].

Native Modeling of Mixed Continuous and Discrete Decisions

Commercial building energy systems inherently involve both continuous variables (e.g., power flows, state of charge) and discrete decisions (e.g., whether the heat pump is operating, whether

[1] The optimality gap is the relative difference between the best feasible integer solution found (upper bound) and the lower bound on the objective value, expressed as a percentage. The lower bound is obtained via *LP relaxation*: binary variables are temporarily allowed to take fractional values, yielding an easier continuous problem whose objective is always at least as good as any integer-feasible solution. A gap of 0% certifies global optimality; in practice, solvers such as Gurobi terminate when the gap falls below a user-defined tolerance (e.g. 0.01%).

the battery is charging or discharging). MILP handles this mixed structure natively, whereas NLP cannot represent discrete decisions, and MINLP while theoretically capable remains computationally intractable for reasonably sized building energy models [20]. This makes MILP the standard framework in the literature for building-level multi-energy system optimization [18].

Suitability for TES and HTHP Modeling

TES introduces particular modeling challenges: the storage state of charge must be tracked across time steps, charging and discharging cannot occur simultaneously, and heat losses must be accounted for. All of these constraints are naturally expressed as linear equality and inequality constraints in MILP. [19] demonstrated that MILP can model TES with dual temperature sections, enabling the coupling of a heat pump as a charging technology directly analogous to the HTHP–TES configuration in this study. Furthermore, [20] showed that MILP-based optimization frameworks with reduced-complexity TES models solve significantly faster than dedicated simulation tools such as TRNSYS, while retaining sufficient accuracy for investment decisions.

Integration of Time-of-Use Electricity Pricing

A key economic driver for the BESS and TES in a commercial building is **price arbitrage**: charging storage when electricity is cheap and discharging when it is expensive. MILP is inherently well-suited to this, as time-varying electricity prices enter linearly into the objective function. [18] explicitly note that MILP integrates seamlessly with demand response programs and variable electricity tariffs, making it the most effective framework for cost minimization in building energy systems with flexible loads and storage.

Limitations Acknowledged

MILP requires **linearization** of any non-linear physical relationships. The coefficient of performance (COP) of the HTHP, for example, is in reality a non-linear function of source and sink temperatures. In this study, the COP is treated as a fixed parameter, representing a standard linearization assumption that is widely applied in the literature [19, 20]. This is a deliberate trade-off: the loss of physical accuracy is accepted in exchange for the computational tractability and global optimality guarantees that MILP provides — and which are essential for a design tool intended to evaluate investment decisions across a range of scenarios.

2.1.5 MILP-based design optimisation framework.

The proposed design tool follows a four-stage workflow, illustrated in Figure 2.1. In the first stage, five hourly time-series datasets covering a full calendar year (8 760 time steps) are assembled: day-ahead electricity spot prices $\lambda(t)$ [€/kWh], solar irradiation $G(t)$ [W/m^2] and ambient temperature $T_{\text{amb}}(t)$ derived from a typical meteorological year (TMY) file, the building's thermal heat demand $Q_{\text{dem}}(t)$ [kW], its electrical demand $P_{\text{dem}}(t)$ [kW] (both representative of a commercial building profile), and the applicable grid connection constraints including the maximum import/export power $P_{\max}$ and network tariffs.

In the second stage the raw time series are normalised, validated, and aligned to a common hourly resolution. Representative operational periods (seasonal, peak, and off-peak) are subsequently identified to characterise the building's energy-use pattern throughout the year.

The third stage formulates a Mixed-Integer Linear Programme (MILP). The objective function minimises the total annualised system cost, comprising capital expenditure (CAPEX) and operational expenditure (OPEX):

$$\min_{\mathbf{x},\,\mathbf{u}(t)} \ \text{CAPEX}(\mathbf{x}) + \text{OPEX}(\mathbf{u}(t)) \tag{2.1}$$



Figure 2.1: Overview of the proposed MILP-based design optimisation framework.

subject to the electricity and thermal energy balances, state-of-charge (SOC) bounds, component power limits, binary on/off decisions, and grid capacity constraints, enforced for every time step $t \in \{1, \ldots, 8760\}$. The programme is solved using an open-source Branch-and-Bound solver (CBC) or the commercial solver Gurobi, implemented in Python via PuLP [**?**] or Pyomo [**?**], with a relative optimality gap tolerance of 0.1 % and a time limit of 3600 s.

The fourth and final stage returns the cost-optimal installed capacities of four storage and conversion technologies: the BESS capacity E^* [kWh] and rated power P^* [kW], the HTHP thermal output Q^*_{hp} [kW], the PV array area A^*_{pv} [m^2], and the TES tank volume V^*_{tes} [m^3].

The energy system under study is depicted in Figure 2.2. The commercial building is characterised by a simultaneous electrical demand $P_{\text{dem}}(t)$ and thermal heat demand $Q_{\text{dem}}(t)$, both resolved at an hourly resolution over a full calendar year. Thermal supply is currently provided by a gas boiler (supplying $Q_{\text{boiler}}(t)$), which is designated for replacement by the optimised system.

Four technologies constitute the candidate system. On the electrical side, a photovoltaic (PV) array of panel area A^*_{pv} [m^2] generates power from incident solar irradiation $G(t)$ at ambient temperature $T_{\text{amb}}(t)$. A Battery Energy Storage System (BESS) with capacity E^* [kWh] and rated power P^* [kW] enables temporal shifting of electrical energy through charge and discharge cycles. Residual electrical demand is balanced by import from, or export to, the electricity grid at power $P_{\text{grid}}(t)$ [kW], subject to the network connection limits.

On the thermal side, a High-Temperature Heat Pump (HTHP) converts electrical energy into heat at a rated thermal output Q^*_{hp} [kW], with performance characterised by its coefficient of performance (COP) as a function of $T_{\text{amb}}(t)$. An electric boiler (E-Boiler) provides supplementary thermal output Q^*_{eb} [kW] to cover peak demands or periods when the heat pump alone is insufficient. Thermal energy can be buffered in a Thermal Energy Storage (TES) tank of volume V^*_{tes} [m^3], decoupling heat generation from instantaneous demand. Together, these four technologies BESS, HTHP, PV, and TES form the decision space of the MILP optimisation described in Equation 2.1, with their optimal capacities returned as the primary output of the design tool



Figure 2.2: Energy system schematic of the studied commercial building configuration, showing the electricity and thermal energy flows between all components. Dashed arrows indicate technologies to be replaced; solid orange arrows denote electricity flows; solid red arrows denote thermal flows.

2.2 Mixed-Integer Linear Programming (MILP)

MILP is widely recognized in academic and industrial literature as the state-of-the-art methodology for optimizing the design and scheduling of energy systems[21] [22].To understand the advantages of MILP, it is first necessary to understand the underlying computational mechanism used by modern solvers (e.g., Gurobi, CPLEX).

2.2.1 MILP algorithm

A **Mixed-Integer Linear Programming (MILP)** model is a mathematical optimization model where the objective function and all constraints are linear, but some, or all, of the decision variables are restricted to be integers (which can include binary, or 0-1, variables). The standard form of an MILP problem is:

$$\begin{aligned} \text{Minimize (or Maximize)} \quad & \mathbf{c}^T\mathbf{x} + \mathbf{d}^T\mathbf{y} \\ \text{Subject to} \quad & \mathbf{A}\mathbf{x} + \mathbf{B}\mathbf{y} \leq \mathbf{b} \\ & \mathbf{x} \geq 0, \quad \mathbf{x} \in \mathbb{R}^n \\ & \mathbf{y} \geq 0, \quad \mathbf{y} \in \mathbb{Z}^m \end{aligned} \tag{2.2}$$

Where:

- $\mathbf{x}$ is a vector of **continuous** decision variables.
- $\mathbf{y}$ is a vector of **integer** decision variables (often binary variables are used to model yes/no decisions).
- $\mathbf{c}$ and $\mathbf{d}$ are vectors of coefficients for the objective function.
- $\mathbf{A}$ and $\mathbf{B}$ are matrices of coefficients for the constraints.

- **b** is a vector of right-hand side values for the constraints.

Key Components

- **Linear Objective Function:** The goal (e.g., minimizing cost or maximizing profit) is expressed as a linear combination of the variables. For example, `Minimize Cost = c1*x1 + c2*x2 + ....`
- **Linear Constraints:** The limitations and requirements of the problem (e.g., resource availability, demand, capacity) are expressed as linear equations or inequalities. Non-linear expressions like `x1*x2` are not allowed, though some can be linearized using specific modeling techniques.
- **Mixed Variables:** The defining characteristic is the presence of both continuous variables (which can take any real value) and integer variables (which are restricted to whole numbers).

Solution Approach

MILP problems are generally NP-hard and more difficult to solve than pure linear programming problems. Solvers (such as CPLEX, Gurobi, or SCIP) typically use algorithms like **Branch and Bound** or **Branch and Cut**. These methods work by:

1. Solving a relaxed version of the problem (ignoring the integer constraints) to get a lower bound on the optimal solution.
2. Systematically exploring a search tree (branching) and adding constraints (cutting planes) to find an optimal integer-feasible solution.

Example



Figure 2.3: Schematic of the Solution approach of MILP [23]

The Branching Decision (Example: PV Investment)

Consider the binary variable for investing in PV system capacity, denoted $y_{\text{PV}} \in \{0, 1\}$.

- **Initial Problem Node (Root Node):** $\min C_{\text{total}}$ with $0 \leq y_{\text{PV}} \leq 1$.
- **Branching Operation:** The solver partitions the original problem into two mutually exclusive subproblems:

$$\text{Subproblem 1 (Assigned to Core 1):} \quad \begin{aligned} &\min C_{\text{total}} \\ &\text{subject to } y_{\text{PV}} = 1 \quad \text{(PV is Purchased)} \end{aligned}$$

$$\text{Subproblem 2 (Assigned to Core 2):} \quad \begin{aligned} &\min C_{\text{total}} \\ &\text{subject to } y_{\text{PV}} = 0 \quad \text{(PV is Not Purchased)} \end{aligned}$$

2.2.2 Parallel Processing and Pruning

- **Parallel Execution:** Core 1 searches for the best design *assuming* PV is bought, while Core 2 searches for the best design *assuming* PV is not bought.
- **Global Update:** If Core 1 quickly finds a feasible solution with total cost $\boldsymbol{C}_{\text{Upper}} = \mathbf{\$10,000}$, this value is immediately broadcasted as the new **Global Upper Bound** on the final cost.
- **Pruning:** If Core 2 finds that the theoretical minimum cost in its branch (its Lower Bound) is $\boldsymbol{L}_{\text{Subproblem 2}} = \mathbf{\$10,500}$, Core 2 can immediately **prune** its entire branch because it cannot contain a solution better than the already known $\boldsymbol{C}_{\text{Upper}} = \mathbf{\$10,000}$.

2.2.3 MILP advantages

Guarantee of Global Optimality

As a deterministic mathematical programming technique, MILP is fundamentally designed to find the exact best possible outcome for a given objective function. It guarantees finding a globally optimal solution when the problem converges [22], a critical advantage over heuristic methods (such as Genetic Algorithms or Particle Swarm Optimization), which can only guarantee finding acceptable solutions or local optima.

Integration of Discrete and Continuous Decisions

MILP is essential for system design and sizing because it effectively integrates the two necessary classes of variables:

- **Integer/Binary Variables:** These are necessary to model structural and commitment decisions, such as the selection of a technology (e.g., using a Heat Pump or not), the existence of a component, the integer number of units to install, or the binary on/off status of a component at each time step.
- **Continuous Variables:** These model the operational schedule and energy flow, such as the electrical power being dispatched or the continuous volume of a storage unit.

This dual capability allows MILP to perform the required co-optimization of investment and operation simultaneously [24].

Handling Non-Linearity via Linearization

While the presence of complex, high-order non-linear models (e.g., in thermodynamics or equipment performance curves) presents a challenge, MILP addresses this through robust techniques. The primary method is **Piecewise Linear (PWL) approximation**. This technique simplifies non-linear functions (like the thermal dynamics of an Electric Water Heater or the variable efficiency of an inverter) into a series of linear segments. By converting the problem into a strictly linear form, the overall optimization process can be performed by commercially available solvers (e.g., CPLEX, Gurobi) efficiently, providing an "efficiently solvable model" for these complex problems. MILP's use of this technique is why it remains the preferred approach over complex Mixed-Integer Non-Linear Programming (MINLP) problems, which often have higher computational requirements [22, 25].

2.2.4 Optimization Objective Functions in MILP

Cost Minimization (Economic)

The minimization of total cost is the most common objective, aiming for the economically optimal design and operation.

- **Objective:** Minimize Total Annual Cost (C_{total}) or Lifetime Cost.
- **Key Components:** Total costs comprise Investment Costs (C_{invest}) and Operational Costs (C_{op}).
  1. **Investment Costs (C_{invest}):** The annualized cost is spread over the component's lifetime using an Annuity Factor (ANF). Non-linear cost functions are typically addressed by using discrete equipment sizes or linear approximations.
  $$C_{\text{invest}} = \sum_i ANF^{-1} \cdot (C_{\text{inv_fix},i} + c_{\text{inv_cap},i} \cdot cap_i^{m_i})$$
  2. **Operational Costs (C_{op}):** Includes energy costs (based on constant or variable electricity prices, e.g., time-of-use tariffs) and maintenance costs.
  $$\min C_{\text{total}} = C_{\text{op}} + ANF^{-1} \cdot C_{\text{invest}}$$

CO_2 Emissions Minimization (Environmental)

This objective focuses on reducing the system's environmental impact.

- **Objective:** Minimize Total $\mathbf{CO_2}$ Emissions.
- **Key Components:** Emissions are calculated by weighing the consumption of electricity and other fuels by their respective $\mathbf{CO_2}$ emission factors. This often aims to shift electricity consumption to periods when the grid's carbon intensity is lower. Primary Energy Consumption (PEC) is sometimes used as a related metric.

Mathematical Formulation

The overall objective function is the sum of operational and amortized embodied CO_2 emissions:

$$\min \mathrm{C}_{\mathrm{CO_2}}^{\mathrm{Total}} = \mathrm{C}_{\mathrm{CO_2}}^{\mathrm{Op}} + \mathrm{C}_{\mathrm{CO_2}}^{\mathrm{Emb}}$$

1. Operational Emissions ($\mathbf{C}_{\mathbf{CO_2}}^{\mathbf{Op}}$) - Minimizing Grid Carbon Intensity

$$\min \mathrm{C}_{\mathrm{CO_2}}^{\mathrm{Op}} = \sum_{t \in T} \left(\sum_{i \in I} \mathrm{E}_{\mathrm{CO_2},i,t}^{\mathrm{Op}} \cdot \mathrm{P}_{i,t}^{\mathrm{Cons}} \cdot \Delta t \right) \tag{2.3}$$

Multi-Criteria Optimization

To balance conflicting objectives like cost minimization and Co2 emmisions minimization, multi-criteria optimization is applied.

- **Approach:** The most common method is the **weighted summation method**, which combines normalized objectives into a single linear objective function using weighting factors (α, β).
- **Weighted Sum Objective:**

$$\min f = \alpha(\mu C) + \beta D$$

  where C is the cost, D is a discomfort index (or other non-cost objective), and α and β ($\alpha + \beta = 1$) are the user's preference factors. μ is a scaling factor for normalization.

2.2.5 epsilon constrained method to create pareto front

The ϵ-constraint method is highly effective for visualizing the **trade-off** between two conflicting objectives in a **Mixed-Integer Linear Programming (MILP)** problem, such as minimizing the **Total Annual Cost** (f_{Cost}) and minimizing the **Total Life Cycle CO_2 Emissions** (f_{CO_2}).

ϵ-Constraint Method in MILP for Cost vs. CO_2

In this specific case, the Multi-Objective Problem (MOP) is to simultaneously minimize both f_{Cost} and f_{CO_2}:

$$\min\left[f_{\text{Cost}}(\mathbf{x}), f_{CO_2}(\mathbf{x})\right] \text{s.t. } \mathbf{x} \in \mathcal{X}$$

The solution vector $\mathbf{x}$ includes both continuous variables (e.g., operational energy flows $\mathrm{P}_{i,t}$) and integer/binary variables (e.g., component sizing Z_j, on/off status $u(t)$). The feasible region $\mathcal{X}$ is defined by constraints, such as:

1. **Investment Constraints:** Component capacities (Z_j) are non-negative and often discrete (MILP is applicable for incorporating discrete decisions).
2. **Energy Balance:** Supply must meet demand in every time step.
3. **Physical Limits:** Component models (e.g., Heat Pump COP, TES energy balance) must be satisfied.

1. Transformation to Single-Objective Problem (SOP)

The ϵ-constraint method selects one objective as the primary optimization target. If we choose to **minimize Total Annual Cost** (f_{Cost}), the **CO_2** objective (f_{CO_2}) is converted into a constraint bounded by a user-defined threshold, ϵ_{CO_2} (the Greek letter ϵ gives the method its name).

The resulting **SOP** solved by the **MILP** solver is:

$$\min f_{\text{Cost}}(\mathbf{x}) \text{s.t. } f_{CO_2}(\mathbf{x}) \leq \epsilon_{CO_2} \mathbf{x} \in \mathcal{X}$$

2. Generating the Pareto Front (Trade-off Curve)

The **Pareto front** the set of non-dominated solutions where no objective can be improved without worsening the other is generated by systematically varying ϵ_{CO_2} and solving the MILP for each step.

1. **Determine CO_2 Range (Boundary Solutions):**

- **Max CO_2 / Min Cost Point:** Solve the MILP to **only** minimize f_{Cost}.
- The resulting total CO_2 emissions, $f_{CO_2}^{\max}$, defines the largest ϵ_{CO_2} needed.
- This solution usually involves the cheapest, but most CO_2-intensive technologies (e.g., large Auxiliary Heater, small Heat Pump, minimal storage).
- **Min CO_2 / Max Cost Point:** Solve the MILP to **only** minimize f_{CO_2}.
- The resulting total CO_2 emissions, $f_{CO_2}^{\min}$, defines the most restrictive ϵ_{CO_2} limit (which might require the largest or most expensive set of components, e.g., large **PV** and **Battery**).

2. **Discretization:** The range $\left[f_{CO_2}^{\min}, f_{CO_2}^{\max}\right]$ is divided into a discrete number of steps N.
3. Each step defines a new, tighter ϵ_{CO_2} value.
4. **Iteration and Output:** For each ϵ_{CO_2} step, the SOP is solved.
5. The optimal annual cost f_{Cost}^{*} is recorded.

This yields a set of points $(f_{CO_2}, f_{\text{Cost}}^{*})$, which when plotted, visually represents the **cost-optimal system design** for every level of **CO_2 reduction** desired. The steepness of the curve indicates the marginal cost of achieving further environmental improvement.



Figure 2.4: Schematic pareto Front[26]

2.3 Component Modeling in Optimization Frameworks

2.3.1 Component model requiremnts

To be implemented within a Mixed-Integer Linear Programming (MILP) framework, a component model must fundamentally adhere to strict mathematical constraints regarding linearity to ensure the problem remains solvable by standard optimization algorithms [11]. Specifically, both the equality and inequality constraints defining the component's behavior, as well as the objective function, must be linear formulations involving real and integer decision variables [27]. Since the actual thermodynamic dynamics of components such as the temperature-dependent Coefficient of Performance (COP) of heat pumps or the mixing processes in water heaters are inherently nonlinear and complex, they cannot be directly processed by MILP solvers [27, 11].

Consequently, these models must undergo linearization or simplification, such as using piecewise linear approximation methods [27], Taylor polynomial approximations [11], or simplifying thermal storage to a homogeneous capacity to avoid endogenous optimization problems [12]. Furthermore, the physical system must be linearized temporally through time discretization, breaking continuous operations into distinct time steps to allow for the simultaneous optimization of design and operation [11].

2.3.2 Lorentz Heat Pump Model Implementation

In energyPRO [28], a simple *Lorentz heat pump model* is implemented for calculating the theoretical Coefficient of Performance (COP). This model is based on the Carnot cycle, modified to account for the temperature variation during heat transfer by using mean temperatures.

Theoretical COP Calculation

The theoretical COP is calculated using the following thermodynamic relationship, where temperatures are expressed in Kelvin (K):

$$\mathrm{COP} = \frac{T_{\mathrm{High,mean}}}{T_{\mathrm{High,mean}} - T_{\mathrm{Low,mean}}}$$

Mean Temperature of Delivered Hot Water ($T_{\mathrm{High,mean}}$)

The mean temperature of the delivered hot water is computed using the logarithmic mean temperature over the condensor:

$$T_{\mathrm{High,mean}} = \frac{T_{\mathrm{High,out}} - T_{\mathrm{High,in}}}{\ln\left(\dfrac{T_{\mathrm{High,out}} + 273.15}{T_{\mathrm{High,in}} + 273.15}\right)}$$

where:

- $T_{\mathrm{High,out}}$ is the outlet water temperature (°C),
- $T_{\mathrm{High,in}}$ is the inlet water temperature (°C).

Mean Temperature of the Heat Source ($T_{\mathrm{Low,mean}}$)

$$T_{\mathrm{Low,mean}} = \frac{T_{\mathrm{Low,out}} - T_{\mathrm{Low,in}}}{\ln\left(\dfrac{T_{\mathrm{Low,out}} + 273.15}{T_{\mathrm{Low,in}} + 273.15}\right)}$$

where:

- $T_{\mathrm{Low,out}}$ is the initial temperature of the heat source (°C),
- $T_{\mathrm{Low,in}}$ is the cooled-down temperature of the heat source (°C).

Actual COP and Heat Capacity Calculation

The heat pump efficiency factor η_{HP} is computed from the stated COP and the theoretical COP under specification conditions (this efficiency can be derived from manufacturers data as in appendix A):

$$\eta_{\mathrm{HP}} = \frac{\mathrm{COP}_{\mathrm{stated}}}{\mathrm{COP}_{\mathrm{theoretical,spec}}}$$

At each timestep, the actual COP becomes:

$$\mathrm{COP}_{\mathrm{actual}} = \mathrm{COP}_{\mathrm{theoretical,actual}} \cdot \eta_{\mathrm{HP}}$$

The resulting heat capacity is:

$$\dot{Q}_{\mathrm{heat}} = \mathrm{COP}_{\mathrm{actual}} \cdot \dot{E}_{\mathrm{elec}}$$

Limitation on Heat Capacity

2.3.3 Linearization for MILP:

When the $T_{\mathrm{High,out}}$ is considered a decision varible in the MILP optimization we cannot simply us the method desribed in 2.3.2 we then need to linearize the equation as done by Krutzefeldt et al. [29]. The resulting non-linear energy relation ($P_{el} = Q_{HP}/COP$) is transformed into a linear constraint by applying a multi-dimensional **Taylor polynomial approximation** around a fixed operation point (OP). The linear approximation $f(x) \approx f(a) + \nabla f(a) \cdot (x - a)$ for the electric power $P_{el,HP,t}$ (function f) with state vector $x = (\dot{Q}_{HP,t}, COP_t)$ and fixed operation point $a = (\dot{Q}_{OP}, COP_{OP})$ yields the constraint:

$$\begin{aligned} P_{el,HP,t} = & \frac{\dot{Q}_{OP}}{COP_{OP}} + \frac{1}{COP_{OP}} \cdot (\dot{Q}_{HP,t} - \dot{Q}_{OP}) \\ & - \frac{\dot{Q}_{OP}}{COP_{OP}^2} \cdot (COP_t - COP_{OP}) \end{aligned} \tag{2.4}$$

This process enables the inclusion of realistic, state-dependent COP in the MILP model while maintaining linearity. Note that this approach is only needed when het COP contains a decision variable that is used in MILP, only then the equation ($P_{el} = Q_{HP}/COP$) is non-linear(in the decision variables). In this master thesis we assume $T_{\mathrm{High,out}}$ as a given so we can use the method as described in 2.3.2.

2.3.4 Thermal Energy Storage (TES) Modeling

Thermal Energy Storage (TES) Technology Selection

Thermal Energy Storage (TES) systems can be implemented using several distinct technologies, each offering a different trade-off between volumetric energy density, cost, complexity, and operating temperature range. The three most relevant categories for building-scale applications are sensible heat storage (typically water tanks), latent heat storage (Phase Change Materials, PCM), and thermochemical storage.

Sensible heat storage using water tanks is the most mature and widely deployed technology. Water has a high specific heat capacity ($c_p \approx 4.18\,\mathrm{kJ/kg{\cdot}K}$), is inexpensive, non-toxic, and compatible with a broad range of heating and cooling systems. However, the volumetric energy density is relatively low: storing a meaningful quantity of thermal energy requires large tank volumes, which can be a limiting factor in space-constrained commercial building contexts [30]. Water tanks are typically operated between 40 °C and 95 °C for heating applications and are well-suited to coupling with high-temperature heat pumps (HTHPs).

Latent heat storage using Phase Change Materials (PCMs) exploits the energy absorbed or released during a phase transition (typically solid-to-liquid). PCMs can achieve volumetric energy densities 5–14 times higher than water for the same temperature lift, depending on the material selected [31]. This significantly reduced footprint makes LTES particularly attractive when available installation space is limited. The primary drawbacks are higher material and encapsulation costs, lower thermal conductivity (requiring enhanced heat exchanger designs),

and sensitivity to the operating temperature window of the phase transition, which must be aligned with the supply temperature of the coupled heat source or sink [32]. For HTHP-coupled systems, PCMs with melting points in the range of 55–80 °C, such as fatty acids or paraffin waxes, are typically considered.

Thermochemical storage offers the highest theoretical energy density but remains largely at the research and pilot scale, with limited commercial availability and significant engineering complexity. It is therefore not considered further in this work.

A comparative summary of the relevant TES technologies is provided in Table 2.1.

Table 2.1: Comparative overview of TES technologies considered for HTHP-coupled building applications.

Property	**Water tank**	**PCM (LTES)**	**Thermochemical**
Volumetric energy density	Low	Medium–High	Very High
Capital cost	Low	Medium–High	High
Technology readiness	High	Medium	Low
Required volume	High	Low–Medium	Very Low
Thermal conductivity	High	Low	Variable
Temperature flexibility	High	Narrow window	High

Selected Technology and Volume Constraint

Given the space constraints typical of commercial building retrofits, this work models **Latent Thermal Energy Storage (LTES)** as the primary TES technology when there is limited space available. Its higher volumetric energy density allows more thermal capacity to be installed within the available footprint, making it well-suited for situations where installation space is a binding constraint.

To capture this spatial limitation within the optimization, the MILP model incorporates an optional maximum volume constraint on the TES unit:

$$V_{\text{TES}} \leq V_{\text{TES,max}} \tag{2.5}$$

where V_{TES} [m^3] is the optimally determined storage volume and $V_{\text{TES,max}}$ [m^3] is a user-defined upper bound reflecting the physical space available at the installation site. When no space restriction applies, $V_{\text{TES,max}}$ can be set to an arbitrarily large value, leaving the optimizer free to select the cost-optimal storage capacity. Conversely, setting $V_{\text{TES,max}}$ to a finite value forces the MILP algorithm to respect the spatial constraint during sizing, potentially shifting the optimal solution toward more aggressive peak shaving via the HTHP or BESS rather than thermal storage.

The proposed optimization framework utilizes a linear model for thewater Thermal Energy Storage (TES) unit, representing a simplified or ideal stratified storage to maintain the tractability of the Mixed-Integer Linear Programming (MILP) problem [13]. This approach balances accuracy with computational speed, as the detailed modeling of stratification, though more physically precise, significantly increases computation time. Studies show that the simplified model is often sufficiently accurate for operation optimization, as model overestimations and underestimations of temperature changes tend to compensate for each other, thus ensuring thermal comfort constraints are met [29].

The selection of a TES model for a Mixed-Integer Linear Programming (MILP) optimization tool involves a trade-off between **computational tractability** (simplicity) and **physical accuracy** (complexity) [13]. The chosen model must accurately reflect real-world constraints, especially when coupled with temperature-sensitive technologies like Heat Pumps (HPs).

Rule-of-Thumb Dimensioning

In conventional planning, sizing the TES often relies on a **rule of thumb** to ensure reliability:

- **Principle:** The storage should be able to provide its **peak thermal power** for a fixed duration, typically **6 to 7 hours** [13]. This method is mainly used for preliminary heuristic sizing within the overall MILP design.

Constant (Size-Independent) Losses

For basic MILP operational models, thermal losses ($\dot{E}_{\text{loss}}$) can be simplified to be either neglected or represented by a **constant factor (δ)** that is independent ofthe physical size (Q_{N}) [13].

$$Q_t = Q_{t-1} - \delta + \dot{Q}_{\text{in},t}\eta_{\text{in}}\Delta t - \frac{\dot{Q}_{\text{out},t}}{\eta_{\text{out}}}\Delta t, \tag{2.6}$$

with

$$\delta = U(2 * \frac{\pi d^2}{4} + \pi dh)\left(\Delta T_{\text{H0}} + \Delta T_{\text{C0}}\right)/2$$

- **Energy Balance:** This approach uses the core energy balance equation, but simplifies the loss terms to depend minimally on dynamic state or size [**?**].
- **Rationale:** This maintains strict linearity and computational speed, though it is the least physically accurate, as actual losses depend heavily on the temperature differential with the ambient environment.

Stratified Thermal Storage (STS) 2-Zone Model

The model implements a simplified **2-zone-model** of a large-scale sensible heat storage with ideal stratification for energy system optimization (see Figure 1 [13]). This model assumes a cylindrical storage of diameter d and height h containing two perfectly separated bodies of water: a hot zone (T_{H}) and a cold zone (T_{C}). The temperatures are fixed to the feed-in/return temperatures of the heating system. When charging/discharging, the thermocline moves up or down. For investment problems, the diameter is typically fixed, and the height is adjusted to maintain linearity in the capacity calculation [13].



Figure 2.5: Schematic of the simplified 2-zone model of a stratified thermal storage with constant hot (T_{H}) and cold (T_{C}) temperature regions [13].

Energy Balance

The equation describing the storage content at time step t is the following:

$$Q_t = Q_{t-1}(1-\beta) - \gamma Q_\mathrm{N} - \delta + \dot{Q}_{\mathrm{in},t}\eta_\mathrm{in}\Delta t - \frac{\dot{Q}_{\mathrm{out},t}}{\eta_\mathrm{out}}\Delta t, \tag{2.7}$$

with

$$\begin{aligned}
Q_N &= \rho V c \Delta T_\mathrm{HC} \\
V &= \frac{\pi d^2}{4} h \\
\beta &= U \frac{4}{d\rho c}\Delta t \\
\gamma &= U \frac{4}{d\rho c \Delta T_\mathrm{HC}} \Delta T_\mathrm{C0} \\
\delta &= U \frac{\pi d^2}{4} \left(\Delta T_\mathrm{H0} + \Delta T_\mathrm{C0}\right) \\
U &= \left(\frac{1}{\alpha_\mathrm{in}} + \frac{t_\mathrm{isolation}}{\lambda_\mathrm{isolation}} + \frac{1}{\alpha_\mathrm{out}}\right)^{-1}
\end{aligned}$$

The three terms represent:

- δ: Constant heat losses through the top and bottom surfaces.
- $\gamma \cdot Q_\mathrm{N}$: Losses through the total lateral surface assuming the storage to be empty (storage is at T_C, and ΔT_C0 is the driving temperature difference), dependent on the height of the storage.
- $\beta \cdot Q_{t-1}$: Additional losses through the lateral surface that belong to the hot part of the water body, dependent on the state of charge.

The diameter d is given and the height can be adapted to adapt the nominal capacity of the storage. With this assumption, **all relations stay linear**.

Because of the space that diffuser plates for charging/discharging take up, it is assumed that the storage can neither be fully charged nor discharged, which is parametrised as a minimal/maximal storage level (indicated by the dotted lines in 2.5).

Capacity and Boundary Constraints

The model is constrained by the physical capacity of the storage and boundary conditions required for optimization:

- **Cycle Constraint:** To model continuous operation, such as in a rolling horizon or repeated operation schedule, the stored energy at the last time step (t_last) must equal the stored energy at the initial time step (t_zero) of the **full** simulation.

$$Q_{t-1} = Q_t \tag{10}$$

- **Capacity Limit:** The instantaneous stored energy is bound by the nominal capacity to ensure physical realism.

$$0 \leq Q_t \leq Q_N \tag{11}$$

The use of this simplified model is advantageous for design and operational optimization due to its robustness and linearity within the MILP framework.

Comparison simple thermal storage vs stratified thermal storage



Figure 2.6: Comparison of storage content decay over time (left) and heat losses versus actual storage content (right) for a simple thermal storage model and stratified thermal storage models of different nominal capacities (30 MWh, 65 MWh, and 90 MWh) [13].

2.6 shows that the simpler TES models neglects the dependence of thermal losses on storage tank size, justifying the choice of the (slightly more complicated) stratified approach for our work. The evident difference in both the absolute loss calculation and the decay of stored energy confirms that the **simple model is inadequate** for accurately simulating the TES unit's performance, especially for applications like heat pump coupling where temperature and heat loss dependency are critical for economic optimization [29]. Therefore, the **stratified model is chosen** to ensure the MILP predictions are grounded in realistic thermal dynamics [29].

2.3.5 Photovoltaic (PV) System modeling

The electrical energy generated by the photovoltaic (PV) system is a crucial input for the overall Mixed-Integer Linear Programming (MILP) optimization framework. For the sake of generality, the PV generation is modeled as a function of environmental conditions and component characteristics, rather than relying exclusively on a specific measured dataset.

Choice of PV Modeling Approach

For a geographically generic design tool, two primary methods for obtaining PV data are considered:

1. **Measured Data:** Utilize historical, on-site PV generation data and corresponding weather conditions collected at a specific location (e.g., the M-Accent site in Eeklo). This method provides highly accurate, site-specific input.

2. **Model-Based Data:** Employ a publicly validated physical model, such as the widely accepted PVWatts model [33], to calculate the DC power output based on standard meteorological inputs (e.g., solar irradiance, ambient temperature, and wind speed). This approach is highly flexible and enables the tool to be applied to any arbitrary location for which standard weather data is available.

To ensure the developed optimization tool remains *generic* and *widely applicable* to residential buildings in Belgium, the model-based approach is adopted for the core PV simulation. This decouples the core optimization framework from the physical constraints of a single measurement site.

PV Model Implementation

The PVWatts model converts the Plane-of-Array (POA) irradiance into DC power (P_{DC}) by accounting for cell temperature effects. The fundamental equation, derived from the PVWatts framework, relates the instantaneous DC power output to instantaneous POA irradiance (G_{POA}) and cell temperature (T_{cell}):

$$P_{\mathrm{DC}}\left[\frac{\mathrm{W}}{\mathrm{m}^2}\right] = \frac{G_{\mathrm{POA}}}{1,000\left[\frac{\mathrm{W}}{\mathrm{m}^2}\right]} P_{\mathrm{PV}}\left(1 + \frac{\gamma_{\mathrm{pdc}}}{100}\left(T_{\mathrm{cell}} - T_{\mathrm{ref}}\right)\right) \tag{2.8}$$

with

$$\begin{aligned} P_{\mathrm{DC,\ PV}}[\frac{\mathrm{W}}{\mathrm{m}^2}] &= \frac{A_{\mathrm{PV}}}{A_{\mathrm{ref.}}} P_{\mathrm{STC}} \\ T_{\mathrm{cell}}[^\circ\mathrm{C}] &= T_{\mathrm{module}} + \frac{G_{\mathrm{POA}}}{1,000\left[\frac{\mathrm{W}}{\mathrm{m}^2}\right]} \Delta T \\ T_{\mathrm{module}}[^\circ\mathrm{C}] &= G_{\mathrm{POA}} e^{a + b \cdot v_{\mathrm{wind}}(10\mathrm{m})} + T_{\mathrm{ambient}} \end{aligned}$$

The instantaneous calculation of DC power output is dependent on the following variables and module specifications:

Table 2.2: PV Model Variables and Base Values

Variable	**Unit**	**Description**	**Standard Condition**
$A_{\mathrm{ref.}}$	m^2	Surface area of one PV module.	N/A
P_{STC}	W	**Nominal DC power** for one module.	$1,000\,\mathrm{W/m}^2$
γ_{pdc}	%/°C	**Temperature coefficient of power**.	-0,5
$v_{\mathrm{wind(10m)}}$	m/s	**Wind velocity** measured at a height of 10 m.	N/A
G_{POA}	$\mathrm{W/m}^2$	**Solar irradiance** in the plane of the array.	N/A
T_{ambient}	°C	**Ambient outside air temperature**.	25

The characteristic parameters a, b, and ΔT are empirical and depend on the physical setup. These properties can be retrieved from publicly available data sets, such as those provided by the California Energy Commission [34].

Table 2.3: Empirically determined coefficients used to predict PV module back surface temperature (Extracted from source data) [34].

Module Type	**Mount**	**a**	**b**	**ΔT (°C)**
Glass/cell/glass	Open rack	−3.47	−.0594	3
Glass/cell/glass	Close roof mount	−2.98	−.0471	1
Glass/cell/polymer sheet	Open rack	−3.56	−.0750	3
Glass/cell/polymer sheet	Insulated back	−2.81	−.0455	0
Polymer/thin-film/steel	Open rack	−3.58	−.113	3
22X Linear Concentrator	Tracker	−3.23	−.130	13

2.3.6 Battery Energy Storage Systems (BESS)

Battery Energy Storage Systems (BESS) are critical components that, when coupled with generation (like PV), provide flexibility to shift electrical loads and enhance a system's self-sufficiency.[29]

- **Role in MILP:** BESS are considered alongside other DER technologies (PV, Combined Heat and Power - CHP) within Mixed-Integer Linear Programming (MILP) optimization frameworks.
- **Application:** MILP models are used for the **optimal operation, configuration, and sizing** of BESS alongside residential heat pump and PV systems, focusing on economic and self-consumption goals.
- **Modeling:** Modeling a BESS in an optimization framework typically involves formulating constraints for:
  1. **Energy balance** and State-of-Charge (SoC) tracking over time.
  2. **Capacity limits** (maximum and minimum allowable SoC).
  3. **Power flow limits** and **efficiency** (charging/discharging losses).

Mathematical Formulation

The BESS model within the MILP framework uses the following variables and constraints across a set of discrete time periods $t \in T$:

Variables:

- SOC_t: State of Charge (energy stored) at the end of time period t [kWh] (continuous variable).
- P_t^{ch}: Power charged into the battery during period t [kW] (continuous variable).
- P_t^{dis}: Power discharged from the battery during period t [kW] (continuous variable).
- U_t: Binary variable, equals 1 if the battery is charging in period t, and 0 otherwise. This ensures the battery cannot charge and discharge simultaneously.

Constraints:

1. Energy Balance and SoC Dynamics: The SoC at time t is determined by the previous period's SoC, adjusted by the energy charged and discharged, factoring in charging (η^{ch}) and discharging (η^{dis}) efficiencies, and the time step duration (Δt).

$$SOC_t = SOC_{t-1} + P_t^{ch} \cdot \eta^{ch} \cdot \Delta t - \frac{P_t^{dis}}{\eta^{dis}} \cdot \Delta t \quad \forall t \in T \tag{2.9}$$

2. SoC Capacity Limits: The SoC must remain within a defined minimum (SOC_{min}) and maximum (SOC_{max}) capacity to ensure operational limits are respected.

$$SOC_{min} \leq SOC_t \leq SOC_{max} \quad \forall t \in T \tag{2.10}$$

3. Mutual Exclusion: The definition of **binary variables** that specify whether the battery is charging or discharging isn't needed here, resulting in a consequent saving of **computational time** [35]. This simplification is valid because the battery's **charging/discharging efficiency is lower than 1**. Consequently, the optimization process is able to automatically select the most appropriate operating mode of the battery at each time step, since the energy lost from simultaneously charging and discharging would have a greater influence than the chosen MIP gap [35].

The solver first solves the linear programming (LP) relaxation of the problem by removing the integer constraints. This provides a theoretical "best possible" bound on the objective value (a lower bound for minimization, an upper bound for maximization). The solver then finds the best feasible integer solution it can, which is called the incumbent. The MIP gap is calculated from the difference between these two values.

4. Power Flow Limits The charging and discharging power flows are limited by the nominal power capacity of the battery (P^{Nom}) at each time step t:

$$\dot{P}_t^c \leq P^{Nom} \tag{2.11}$$

$$\dot{P}_t^d \leq P^{Nom} \tag{2.12}$$

5. Initial Conditions: The initial state of charge (SOC_0) is set as a known parameter at the beginning of the optimization horizon.

$$SOC_0 = \text{Initial SoC Value} \tag{2.13}$$

These linear constraints and mixed-integer variables allow the optimization framework to dispatch the battery effectively to meet the objective function (e.g., minimizing operational cost or maximizing self-consumption).

6. Cycle Aging Proxy: Cycle degradation can be implemented in the following manner:

$$SOC_t = SOC_{t-1} \cdot (1 - \eta^{SD}) + P_t^{ch} \cdot \eta^{ch} \cdot \Delta t - \frac{P_t^{dis}}{\eta^{dis}} \cdot \Delta t \quad \forall t \in T \tag{2.14}$$

Implication for Lifetime Analysis: While this simplification is valid for short-term operational scheduling, it should be noted that neglecting self-discharge (and detailed capacity degradation) will result in an overestimation of the battery's true performance when extrapolating the operational strategy over the entire lifetime of the installation. Consequently, this simple model may lead to an underdimensioning of the required BESS capacity in a lifetime economic analysis.

2.3.7 Inverter modeling

Modeling the **inverter efficiency** in a **Mixed-Integer Linear Programming (MILP) model** is crucial for accurately calculating energy losses and finding the true economic optimum, especially for systems including Photovoltaic (PV) or Battery Energy Storage Systems (BESS). Since inverter efficiency is non-linear—it varies significantly with the input power load—you must use **linearization techniques** to keep the problem solvable with MILP.The most common and effective method is **Piecewise Linear (PWL) Approximation**.

PWL Approximation for Inverters

The core idea is to approximate the smooth, non-linear efficiency curve of the inverter with a series of straight-line segments. This converts the overall non-linear problem into a solvable MILP formulation by introducing auxiliary variables and constraints.

1. The Need for Linearization

- **The Problem:** Inverter output power (P_{ac}) is the result of input DC power (P_{dc}) multiplied by efficiency (η): $P_{ac} = P_{dc} \cdot \eta(P_{dc})$. Since η itself is a function of P_{dc}. Consider for means of example the PVwatt model [33].

$$\eta = \frac{\eta_{\text{nom}}}{\eta_{\text{ref}}} - 0.0162 \cdot \zeta - \frac{0.0059}{\zeta} + 0.9858 \quad \text{where} \quad \zeta = \frac{P_{\text{dc}}}{P_{\text{dc0}}} \quad \text{and} \quad P_{\text{dc0}} = \frac{P_{\text{ac0}}}{\eta_{\text{nom}}} \tag{2.15}$$

  this equation is **non-linear** and incompatible with linear programming (LP) and standard MILP solvers.



Figure 2.7: Inverter Part-Load Efficiency. This graph illustrates how inverter efficiency varies with the load fraction, showing different nominal efficiencies and a comparison to PVWatts V1.

- **The Trade-off:** Assuming a constant efficiency (a simple linear model) is fast but leads to modeling inaccuracies and suboptimal economic results. PWL modeling offers a better balance between **accuracy** and **computational complexity**.

2. Implementation Steps

The **Piecewise Linear Approximation (PWL)** transforms the curve into a set of linear functions, typically using the **Multiple Choice/Convex Combination approach** (also known as the λ-method or Special Ordered Sets of Type 2, SOS2):

1. **Define Segments/Breakpoints:** The non-linear curve is divided into N linear segments defined by $N + 1$ known points (breakpoints) along the input power axis. The accuracy increases with the number of segments, but so does the computational time.

2. **Introduce Binary Variables (for segments):** You assign auxiliary binary variables (δ_s) to identify which segment is active at any given time step.

3. **Use Convex Combination (λ-method):** The actual power flow point on the curve is represented as a convex combination of the segment breakpoints. This uses additional continuous variables (λ_i) whose sum must equal 1.

- $P_{dc} = \sum_i \lambda_i P_{dc,i}$ (The actual power is a weighted average of the breakpoint powers).
- $\eta(P_{dc}) = \sum_i \lambda_i \eta_i$ (The calculated efficiency is a weighted average of the breakpoint efficiencies).

Constraints ensure that only two adjacent λ values (or their corresponding segment binary variables) can be non-zero simultaneously, forcing the solution to lie on a defined segment.

2.3.8 Part-Load Operation HTHP

Inverter modulated model

The performance of a heat pump at a given temperature depends on its operating regime, which in turn alters the effective coefficient of performance. The effective COP, denoted as $\mathrm{COP}^\star(\Delta T)$, is defined by 2.16 based on different operating conditions [36]:

$$\mathrm{COP}^\star(\Delta T) = \begin{cases} \mathrm{COP}^{\mathrm{FL}}(\Delta T_{\mathrm{HP}}), & \text{if } T_{\mathrm{out}} \leq T_{\mathrm{biv}} \\ \mathrm{COP}^{\mathrm{PL}}(\Delta T_{\mathrm{HP}}), & \text{if } T_{\mathrm{biv}} \leq T_{\mathrm{out}} \leq T_{\mathrm{biv},2} \\ \mathrm{COP}^{0/1}(\Delta T), & \text{if } T_{\mathrm{out}} \geq T_{\mathrm{biv},2} \end{cases} \tag{2.16}$$

The core operational principle of modern high-temperature heat pumps (HTHPs), such as the Daikin EWYE-CZ, relies on inverter technology (Variable Frequency Drive or VFD) to modulate power and maintain efficiency at partial load conditions. While this modulating behavior leads to higher realistic performance ($\mathrm{COP}^{\mathrm{PL}}$) by minimizing efficiency losses associated with frequent on/off cycling, its full integration into a design-and-operation Mixed-Integer Linear Program (MILP) introduces a significant modeling challenge. Precisely modeling regimes such as $\mathrm{COP}^\star(\Delta T)$ which transition from full load ($\mathrm{COP}^{\mathrm{FL}}$) to inverter-controlled ($\mathrm{COP}^{\mathrm{PL}}$) and eventually to on/off cycles ($\mathrm{COP}^{0/1}$) requires defining the non-linear performance curve using Piecewise Linear (PWL) approximations or introducing a matrix of auxiliary binary decision variables to select the active operating segment at every time step of the simulation. This drastic increase in discrete variables would expand the combinatorial search space of the MILP exponentially, making the computational problem intractable and violating the requirement for a functional, fast optimization tool. Therefore, for the sake of model simplicity and computational feasibility, the HP operation for all regimes, including the inverter-modulated segment, is conservatively simplified to a single on/off (full-load) switching mechanism, acknowledging that this design choice inherently leads to an underestimation of the HP's true seasonal performance (SCOP).

Simplified model

The estimation of Part Load (PL) performance for the heat pump assumes adherence to the EN 14511: 2022 standard, as detailed in relevant literature [37].

$$\mathrm{COPPL}[-] = (1 - C\mathrm{d}(1 - \mathrm{PLR}))\mathrm{COP} \quad \text{with} \quad \mathrm{PLR}[-] = \frac{\min(\dot{Q}\mathrm{demand}, \dot{Q}\mathrm{duty})}{\dot{Q}_{\mathrm{duty}}} \tag{2.17}$$

In eq. (2.17) , $C_{\mathrm{d}}(-)$ represents the degradation coefficient, assigned a value of 0.25 for air-to-water HP systems [37].The $\mathrm{PLR}(-)$ variable quantifies the part load ratio by comparing the required heating output against the maximum possible theoretical output under prevailing weather conditions.This maximum output is termed the duty $\dot{Q}_{\mathrm{duty}}(\mathrm{W})$, while the load actually required by the building is the heat demand $\dot{Q}_{\mathrm{demand}}(\mathrm{Wh/h\ or\ W})$, which may also be the effective heat to be provided.The duty is derived from the Lorenz COP and the nominal power use, as defined by the sizing and setpoint temperature in eq. (2.18).

$$\dot{Q}\mathrm{duty}[\mathrm{W}] = \mathrm{COPLorenz}\frac{\dot{Q}\mathrm{HP}, \mathrm{nom}}{\mathrm{COPnom}} \tag{2.18}$$

In eq. (2.18), $\dot{Q}_{\mathrm{HP,nom}}(\mathrm{W})$ is the sizing parameter used for HPs and $\mathrm{COP}_{\mathrm{nom}}(-)$ represents the nominal COP linked to the system's target setpoint temperature. Finally, the electrical power drawn by the HP and the net heat provided to the load are calculated using the duty cycle, as shown in 2.19.

$$P_{\mathrm{HP}}[\mathrm{W}] = \min\left(\frac{\dot{Q}\mathrm{demand}}{\mathrm{COPPL}}, \frac{\dot{Q}\mathrm{duty}}{\mathrm{COPPL}}\right) \quad \text{and} \quad \dot{Q}\mathrm{HP}[\mathrm{W}] = \mathrm{COPPL}P_{\mathrm{HP}} \tag{2.19}$$

2.4 Conclusion

The literature reviewed in this chapter establishes a robust methodological foundation for the design and operation of complex, hybrid energy systems. As the building sector shifts toward decarbonization, it is evident that static, rule-of-thumb dimensioning standards (such as EN 15450) are insufficient for systems integrating High-Temperature Heat Pumps (HTHPs), Photovoltaics (PV), Battery Energy Storage Systems (BESS), and Thermal Energy Storage (TES). Achieving both economic viability and grid stability requires the simultaneous optimization of component sizing and operational scheduling.

Several key takeaways emerge from the evaluation of energy system modeling methodologies:

- **The Suitability of MILP:** Mixed-Integer Linear Programming (MILP) stands out as the most appropriate mathematical framework for this application. Unlike heuristic methods (e.g., Genetic Algorithms or Particle Swarm Optimization) that only offer near-optimal approximations, MILP guarantees a deterministic, globally optimal solution. It natively handles the combination of continuous variables (e.g., energy flows, state of charge) and discrete binary decisions (e.g., investment choices, on/off operational states) required for co-optimizing system design and dispatch.

- **Balancing Accuracy and Tractability:** The primary limitation of MILP is its strict requirement for linear constraints. However, the literature demonstrates that complex, non-linear thermodynamic behaviors can be successfully integrated without causing computational bottlenecks. Techniques such as Piecewise Linear (PWL) approximations for inverter efficiencies, stratified 2-zone models for TES, and Lorentz-based or simplified part-load COP models for HTHPs provide the necessary balance between physical realism and solver efficiency.

- **Evaluating Trade-offs:** Multi-objective optimization, specifically utilizing the ϵ-constraint method, provides a vital mechanism for evaluating competing goals. It allows for the clear visualization of trade-offs between minimizing the Total Cost of Ownership (TCO) and reducing life-cycle CO_2 emissions via Pareto fronts.

Ultimately, these modeling strategies validate the approach taken in this thesis. By utilizing a MILP-based framework with carefully selected component linearizations, the proposed design tool is well-equipped to navigate the complex interdependencies of hybrid energy systems. This methodology will directly enable the cost-optimal and environmentally sound transition from gas boilers to electrified heating for commercial applications like the M-accent case study.

Chapter 3

Methodology

The preceding chapters established the problem context and the theoretical foundation for this work. Chapter 1 identified the core challenge: replacing the two 80 kW gas boilers at the M-accent commercial building with an electrified hybrid system comprising a High-Temperature Heat Pump (HTHP), Photovoltaic (PV) array, Battery Energy Storage System (BESS), and Thermal Energy Storage (TES) — while simultaneously minimising the Total Cost of Ownership (TCO). Chapter 2 reviewed the available optimisation paradigms and concluded that Mixed-Integer Linear Programming (MILP) is the most appropriate framework for this application: it guarantees a globally optimal solution, natively handles the mixed continuous-and-discrete decision structure inherent to energy systems, and integrates seamlessly with the time-varying electricity tariffs that drive economic dispatch decisions.

Building on those foundations, this chapter presents the complete mathematical formulation of the MILP design tool developed in this thesis. The model co-optimises two interrelated decision layers: the *investment layer*, which determines the optimal installed capacities of the HTHP, PV array, BESS, and TES; and the *operational layer*, which determines the cost-optimal hourly dispatch of every technology over a representative full calendar year (8 760 time steps). These two layers cannot be solved independently: the economic value of storage, for instance, depends on how it is operated, and the optimal operating strategy in turn depends on the installed capacity. The MILP formulation resolves this coupling in a single unified optimisation problem.

The chapter is structured as follows. Section 3.1 describes the input data pipeline: the climatic, tariff, and load profiles that drive the model. Sections 3.2.1–3.2.4 develop the linearised component models for each technology, detailing the physical constraints and the linearisation choices required for MILP compatibility. Section 3.3 states the system-level energy balance constraints that couple all components at every time step. Section 3.4 defines the objective function, which minimises the annualised total system cost comprising CAPEX and OPEX. Finally, Section 3.5 documents the solver configuration and solution strategy.

3.1 Input Data and Pre-Processing

3.2 Component Models

This section presents the linearised mathematical models for each technology in the candidate system. All models are formulated as linear equality and inequality constraints suitable for direct embedding in the MILP problem.

3.2.1 High-Temperature Heat Pump (HTHP)

The High-Temperature Heat Pump (HTHP) is the primary source of thermal energy in the system, converting electrical power into heat at supply temperatures up to 75 °C, making it suitable for the existing radiator circuit of the M-accent building without requiring hydronic renovation. The specific unit modelled is the Daikin EWYE-CZ air-to-water heat pump; its full manufacturer datasheet is reproduced in Appendix A.

Two ambient-temperature-dependent effects must be captured simultaneously: the change in thermodynamic *efficiency* (COP) and the change in physically *available capacity* (rated thermal output). These are treated as two separate pre-computed parameter arrays, described next, which are then embedded as fixed coefficients in the MILP constraints.

Pre-Processing Step 1: Lorentz COP Time Series

As established in Section 2.3.2, the Lorentz model expresses the ideal COP of a heat pump in terms of the log-mean temperatures on the condenser (sink) side and the evaporator (source) side. With a fixed supply temperature T_{sup} [°C] and fixed return temperature T_{ret} [°C], the log-mean condenser temperature is a constant:

$$T_{\text{h,lm}} = \frac{T_{\text{sup}} - T_{\text{ret}}}{\ln\left(\dfrac{T_{\text{sup}} + 273.15}{T_{\text{ret}} + 273.15}\right)} \quad [\text{K}]. \tag{3.1}$$

The heat source is outdoor air at the hourly ambient temperature $T_{\text{amb}}(t)$ [°C], converted to Kelvin as $T_{\text{src}}(t) = T_{\text{amb}}(t) + 273.15$ [K]. The ideal Lorentz COP at each hour is therefore:

$$\text{COP}_{\text{Lorenz}}(t) = \frac{T_{\text{h,lm}}}{T_{\text{h,lm}} - T_{\text{src}}(t)}. \tag{3.2}$$

The actual COP is obtained by scaling with the Lorentz efficiency factor η_{HP}, calibrated from manufacturer performance data (Appendix A) at the reference operating point:

$$\text{COP}(t) = \eta_{\text{HP}} \cdot \text{COP}_{\text{Lorenz}}(t), \qquad \eta_{\text{HP}} = 0.361. \tag{3.3}$$

Because both $T_{\text{h,lm}}$ and η_{HP} are constants, and $T_{\text{amb}}(t)$ is a known input time series, $\text{COP}(t)$ is fully determined before the optimisation begins. It is passed to Gurobi as a *scalar parameter* at each time step, making every constraint in which it appears linear.

Pre-Processing Step 2: Capacity-Fraction Linear Regression

At low ambient temperatures an air-source heat pump cannot deliver its rated thermal output: the refrigerant mass-flow rate decreases as the evaporator pressure drops. This effect is *separate* from the COP variation and must be modelled independently as a reduction in the *available* capacity.

A **linear regression** is fitted to the heating-capacity data extracted from the Daikin EWYE-CZ manufacturer simulation at full load and a fixed condenser leaving water temperature of 55 °C (eight points from −15 °C to +7 °C plus one high-temperature point at +20 °C). The regression is forced through the reference point ($T_{\text{ref}} = 7\,°\text{C},\ \kappa = 1.0$), yielding:

$$\kappa(t) = 1 + k\big(T_{\text{amb}}(t) - T_{\text{ref}}\big), \quad k = 0.02106\,°\text{C}^{-1}, \quad T_{\text{ref}} = 7\,°\text{C}, \tag{3.4}$$

clipped to the manufacturer operating envelope: $\kappa(t) \in [0.537,\ 1.274]$ (corresponding to $T_{\text{amb}} \in [-15\,°\text{C},\ +20\,°\text{C}]$). The fit achieves $R^2 = 0.997$. Like $\text{COP}(t)$, the array $\kappa(t)$ is pre-computed and enters the MILP as a fixed coefficient.

Physical interpretation. A value $\kappa < 1$ means the unit can deliver less than its nameplate output at cold conditions; a value $\kappa > 1$ means it can slightly exceed nameplate at mild conditions. The effective weather-derated capacity at any hour is therefore $Q^*_{\text{hp}} \cdot \kappa(t)$ [kW].

MILP Decision Variables

The MILP introduces the following variables for the HTHP:

- $Q^*_{\text{hp}} \in [0,\ Q^*_{\text{hp,max}}]$ [kW$_{\text{th}}$] — continuous sizing variable (rated thermal output at reference conditions).
- $u_{\text{HP}}(t) \in \{0, 1\}$ — binary on/off commitment at time step t.
- $\tilde{Q}_{\text{hp}}(t) \geq 0$ [kW$_{\text{th}}$] — auxiliary continuous variable equal to Q^*_{hp} when $u_{\text{HP}}(t) = 1$ and zero otherwise (linearises the product $Q^*_{\text{hp}} \cdot u_{\text{HP}}(t)$).
- $Q_{\text{HP}}(t) \geq 0$ [kW$_{\text{th}}$] — actual thermal output delivered.
- $P_{\text{el,HP}}(t) \geq 0$ [kW$_{\text{el}}$] — electrical power consumed.

On/Off Linearisation (Big-M)

The auxiliary variable $\tilde{Q}_{\text{hp}}(t)$ linearises the bilinear product $Q^*_{\text{hp}} \cdot u_{\text{HP}}(t)$ via the standard three-constraint big-M formulation:

$$\tilde{Q}_{\text{hp}}(t) \leq Q^*_{\text{hp,max}}\, u_{\text{HP}}(t) \tag{3.5}$$

$$\tilde{Q}_{\text{hp}}(t) \leq Q^*_{\text{hp}} \tag{3.6}$$

$$\tilde{Q}_{\text{hp}}(t) \geq Q^*_{\text{hp}} - Q^*_{\text{hp,max}} \big(1 - u_{\text{HP}}(t)\big). \tag{3.7}$$

When $u_{\text{HP}}(t) = 0$, constraints (3.5) and (3.7) together force $\tilde{Q}_{\text{hp}}(t) = 0$. When $u_{\text{HP}}(t) = 1$, constraints (3.6) and (3.7) together force $\tilde{Q}_{\text{hp}}(t) = Q^*_{\text{hp}}$.

Thermal Output Bounds

The actual thermal output is bounded by the weather-derated capacity from above and by a minimum load fraction $f_{\min}$ from below (set to 0.222 from manufacturer data):

$$Q_{\text{HP}}(t) \leq \tilde{Q}_{\text{hp}}(t) \cdot \kappa(t) \tag{3.8}$$

$$Q_{\text{HP}}(t) \geq f_{\min}\, \tilde{Q}_{\text{hp}}(t) \cdot \kappa(t). \tag{3.9}$$

Since $\kappa(t)$ is a pre-computed scalar, both constraints remain linear in the decision variables $Q_{\text{HP}}(t)$ and $\tilde{Q}_{\text{hp}}(t)$. The lower bound prevents unrealistically shallow cycling; the electric boiler covers any residual demand that the HTHP cannot meet at minimum load.

Electrical Power with On/Off Cycling Penalty

A purely ideal model would set $P_{\text{el,HP}}(t) = Q_{\text{HP}}(t)/\text{COP}(t)$. However, on/off cycling incurs compressor restart losses that cause the unit to consume some electrical power even below its minimum thermal output. Following the EN 14511 part-load degradation approach reviewed in Section 2.3.8, this is captured by a degradation coefficient C_{d} that splits the electrical draw into a fixed fraction proportional to the *derated rated capacity* and a variable fraction proportional to the *actual output*:

$$P_{\mathrm{el,HP}}(t) \cdot \mathrm{COP}(t) = C_{\mathrm{d}}\, \tilde{Q}_{\mathrm{hp}}(t) \cdot \kappa(t) + \big(1 - C_{\mathrm{d}}\big)\, Q_{\mathrm{HP}}(t), \quad C_{\mathrm{d}} = 0.10. \tag{3.10}$$

Because $\mathrm{COP}(t)$ and $\kappa(t)$ are fixed parameters, the right-hand side is linear in $\tilde{Q}_{\mathrm{hp}}(t)$ and $Q_{\mathrm{HP}}(t)$, and the left-hand side is linear in $P_{\mathrm{el,HP}}(t)$. The constraint is therefore directly embeddable in the MILP.

To verify consistency: at full load ($Q_{\mathrm{HP}} = \tilde{Q}_{\mathrm{hp}} \cdot \kappa$) equation (3.10) reduces to $P_{\mathrm{el,HP}} \cdot \mathrm{COP} = \tilde{Q}_{\mathrm{hp}} \cdot \kappa = Q_{\mathrm{HP}}$, i.e. $P_{\mathrm{el,HP}} = Q_{\mathrm{HP}}/\mathrm{COP}$, recovering the ideal relation. At output below rated, the C_{d} term adds a fixed overhead that reduces the effective part-load COP, consistent with the cycling-loss mechanism described in Section 2.3.8.

Summary of HTHP Constraints

Table 3.1 collects all HTHP constraints, the pre-computed parameters they use, and their role in the MILP.

Table 3.1: Complete HTHP constraint set embedded in the MILP. $\kappa(t)$ and $\mathrm{COP}(t)$ are pre-computed parameter arrays; all other symbols are MILP variables.

Label	**Constraint**	**Role**
(3.5)–(3.7)	Big-M on $\tilde{Q}_{\mathrm{hp}}(t)$	Links sizing variable to on/off binary
(3.8)	$Q_{\mathrm{HP}}(t) \leq \tilde{Q}_{\mathrm{hp}}(t)\, \kappa(t)$	Weather-derated upper capacity
(3.9)	$Q_{\mathrm{HP}}(t) \geq f_{\min}\, \tilde{Q}_{\mathrm{hp}}(t)\, \kappa(t)$	Minimum load fraction
(3.10)	$P_{\mathrm{el}}\, \mathrm{COP}(t) = C_{\mathrm{d}} \tilde{Q} \kappa + (1 - C_{\mathrm{d}}) Q_{\mathrm{HP}}$	Electrical draw with cycling penalty

3.2.2 Photovoltaic (PV) Array

3.2.3 Battery Energy Storage System (BESS)

3.2.4 Thermal Energy Storage (TES)

3.2.5 Electric Boiler (Auxiliary Heater)

3.3 System Energy Balance Constraints

3.4 Objective Function

3.5 Solver Configuration and Solution Strategy

Bibliography

[1] European Commission. EU Climate Action Progress Report 2023 – Belgium Factsheet, October 2023. Accessed: 2025-11-19.

[2] Regulation (EU) 2021/1119 of the European Parliament and of the Council of 30 June 2021 establishing the framework for achieving climate neutrality and amending Regulations (EC) No 401/2009 and (EU) 2018/1999 ('European Climate Law'). *Official Journal of the European Union*, L 243:1–17, 2021.

[3] European Commission. Communication from the Commission to the European Parliament and the Council: Europe's 2040 climate target and path to climate neutrality by 2050. Com(2024) 63 final, European Commission, 2024.

[4] Directive (EU) 2024/1275 of the European Parliament and of the Council of 24 April 2024 on the energy performance of buildings (recast). *Official Journal of the European Union*, L, 2024.

[5] Eurostat. Energy consumption in households, 2023. Accessed: 2026-02-24.

[6] EnergyVille. Residential & Commercial Sector – PATHS2050 Main Edition 2025, April 2025. Accessed: 2025-11-19.

[7] H. Esen, M. Inalli, and M. Esen. Technoeconomic appraisal of a ground source heat pump system for a heating season in eastern turkey. *Energy Conversion and Management*, 47(9):1281–1297, 2006.

[8] Vlaams Energie- en Klimaatagentschap (VEKA). Vlaamse overheid en warmtepompsector slaan handen in elkaar om warmtepompen breed uit te rollen in vlaanderen, 2026. Accessed: February 26, 2026.

[9] Heating systems in buildings – Design of heat pump heating systems (EN 15450:2007). Standard, European Committee for Standardization (CEN), October 2007.

[10] Matteo Dongellini, Claudia Naldi, and Gian Luca Morini. Sizing effects on the energy performance of reversible air-source heat pumps for office buildings. *Applied Thermal Engineering*, 114:1073–1081, 2017.

[11] Hannah Krützfeldt, Christian Vering, Philipp Mehrfeld, and Dirk Müller. Milp design optimization of heat pump systems in german residential buildings. *Energy and Buildings*, 249:111204, 2021.

[12] David Steen, Michael Stadler, Gonçalo Cardoso, Markus Groissböck, Nicholas DeForest, and Chris Marnay. Modeling of thermal storage systems in milp distributed energy resource models. *Applied Energy*, 137:782–792, 2015.

[13] oemof developer community. Stratified thermal storage. `https://oemof-thermal.readthedocs.io/en/latest/stratified_thermal_storage.html`, 2024. Accessed: March 31, 2026.

[14] Aeidapu Mahesh and Kanwarjit Singh Sandhu. A genetic algorithm based improved optimal sizing strategy for solar-wind-battery hybrid system using energy filter algorithm. *Frontiers in Energy*, 14(1):139–151, 2020.

[15] Mohamed A. Mohamed, Ali M. Eltamaly, and Abdulrahman I. Alolah. PSO-based smart grid application for sizing and optimization of hybrid renewable energy systems. *PLOS ONE*, 11(8):e0159702, 2016.

[16] Orhan Ekren and Banu Y. Ekren. Size optimization of a PV/wind hybrid energy conversion system with battery storage using simulated annealing. *Applied Energy*, 87(2):592–598, 2010.

[17] Hans-Kristian Ringkjøb, Peter M. Haugan, and Ida Marie Solbrekke. A review of modelling tools for energy and electricity systems with large shares of variable renewables. *Renewable and Sustainable Energy Reviews*, 96:440–459, 2018.

[18] Tobias Beck, Hendrik Kondziella, Gerald Huard, and Thomas Brückner. Optimal operation, configuration and sizing of generation and storage technologies for residential heat pump systems integrating photovoltaic and electrolysis. *Energy*, 208:118339, 2021.

[19] Gonçalo Cardoso, Chris Marnay, Markus Groissböck, Nicholas DeForest, and Michael Stadler. Modeling of thermal storage systems in MILP distributed energy resource models. *OSTI Technical Report, Lawrence Berkeley National Laboratory*, 2014. LBNL-6757E.

[20] Leander Kotzur, Peter Markewitz, Martin Robinius, and Detlef Stolten. Impact of different time series aggregation methods on optimal energy system design. *Renewable and Sustainable Energy Reviews*, 99:177–185, 2018.

[21] S. Stinner, M. Nuchter, L. Schiefelbein, B. Urbanucci, and D. Müller. Design optimization of multi-energy systems using milp: Which model complexity and level of detail is sufficient? *Energy*, 230:120894, 2021.

[22] B. Urbanucci. Limits and potentials of mixed integer linear programming methods for optimization of polygeneration energy systems. *Applied Energy*, 216:489–502, 2018.

[23] Shuhan Du, Junbo Tong, and Wenhui Fan. Learning efficient branch-and-bound for solving mixed integer linear programs. *Applied Soft Computing*, 172:112863, 2025.

[24] C. Bordin, S. Cordiner, and L. D'Anzi. A milp algorithm for the optimal sizing of an off-grid hybrid renewable energy system in south tyrol. *Energy*, 195:117006, 2020.

[25] R. Fuso, S. Lilli, and S. Cordiner. Economic–energy–environmental optimization of a multi-energy system in a university district. *Energies*, 18:413, 2025.

[26] Estíbaliz Pérez Iribarren, Iker González Pino, Zaloa Azkorra Larrinaga, Moisés Odriozola Maritorena, and Ignacio Santiago Gómez Arriaran. A mixed integer linear programming-based simple method for optimizing the design and operation of space heating and domestic hot water hybrid systems in residential buildings. *Energy Conversion and Management*, 292:117326, 2023.

[27] Mei Wu, Yu-Qing Bao, Jinlong Zhang, and Tongzhou Ji. Multi-objective optimization for electric water heater using mixed integer linear programming. *Journal of Modern Power Systems and Clean Energy*, 7(5):1256–1266, 2019.

[28] EMD International A/S. Cop and heat capacity. EnergyPRO Technical Documentation.

[29] Hannah Krützfeldt, Christian Vering, Philipp Mehrfeld, and Dirk Müller. Milp design optimization of heat pump systems in german residential buildings. *Energy and Buildings*, 249:111204, 2021.

[30] Ibrahim Dinçer and Marc A. Rosen. *Thermal Energy Storage: Systems and Applications*. John Wiley & Sons, Chichester, UK, 3rd edition, 2021.

[31] Atul Sharma, V.V. Tyagi, C.R. Chen, and D. Buddhi. Review on thermal energy storage with phase change materials and applications. *Renewable and Sustainable Energy Reviews*, 13(2):318–345, 2009.

[32] Luisa F. Cabeza, Albert Castell, Camila Barreneche, Alvaro de Gracia, and A.I. Fernández. Materials used as PCM in thermal energy storage in buildings: A review. *Renewable and Sustainable Energy Reviews*, 15(3):1675–1695, 2011.

[33] Aron Dobos. PVWatts Version 5 Manual. Technical Report NREL/TP-6A20-62641, National Renewable Energy Laboratory (NREL), 2014. Accessed: March 31, 2026.

[34] Aron Dobos. An Improved Coefficient Calculator for the California Energy Commission 6 Parameter Photovoltaic Module Model. *Journal of Solar Energy Engineering, Transactions of the ASME*, 134:021011, 2012. Accessed: March 31, 2026.

[35] Paolo Gabrielli, Matteo Gazzani, and Marco Mazzotti. Electrochemical conversion technologies for optimal design of decentralized multi-energy systems: Modeling framework and technology assessment. *Applied Energy*, 221:557–575, 2018.

[36] Antoine Rogeau, Julien Vieubled, Louis Ruche, and Robin Girard. A generic methodology for mapping the performance of various heat pumps configurations considering part-load behavior. *Energy and Buildings*, 318:114490, 2024.

[37] Walter Grassi. *Heat Pumps: Fundamentals and Applications*. Green Energy and Technology. Springer International Publishing AG, Cham, Switzerland, 2018.

Appendix A

Datasheet HTHP Daikin EWYE-CZ

Technical data

				Model 01	Model 02	Model 03	Model 04	Model 05	Model 06	Model 07	Model 08	Model 09
Cooling performance 12/7 35°C	Cooling capacity		kW	16.8	20.8	24.5	28.7	31.3	41.6	49.1	54.3	63.5
	Capacity control	Type		Inverter Controlled								
	Unit power input		kW	4.7	6.7	8.6	9.4	10.8	13.3	17.1	19.0	21.7
	EER			3.55	3.12	2.85	3.06	2.90	3.13	2.86	2.86	2.93
Heating performance 40/45 7°C	Heating capacity		kW	19.0	23.5	27.6	32.0	34.9	47.2	55.3	62.0	70.0
	Unit power input	Heating	kW	5.6	7.0	8.4	9.5	10.9	14.2	17.0	19.7	22.0
	COP			3.40	3.36	3.28	3.36	3.21	3.32	3.25	3.13	3.17
Heating performance 60/70 -15°C	Heating capacity		kW	13.4	21.2	23.6	25.6	27.1	42.5	47.3	50.3	54.3
	Unit power input	Heating	kW	9.6	12.0	13.6	14.4	15.5	24.3	27.5	29.4	31.0
	COP			1.39	1.76	1.73	1.78	1.75	1.75	1.72	1.71	1.75
Water heat exchanger heating	Water flow rate		l/s	0.9	1.1	1.3	1.5	1.7	2.3	2.7	3.0	3.4
	Water pressure drop		kPa	9.8	14.2	18.9	19.0	22.2	12.8	17.2	21.1	13.8
Water heat exchanger cooling	Water flow rate		l/s	0.8	1.0	1.2	1.4	1.5	2.0	2.3	2.6	3.0
	Water pressure drop		kPa	7.7	11.3	15.2	15.5	18.2	9.9	13.5	16.2	11.3
Air heat exchanger	Type			Al Fins & Cu Tubes								
Water heat exchanger				Brazed Plate								
Fan	Type			Axial								
	Drive			VFD								
	Quantity		N°	1			2				3	4
	Speed		rpm	700	800	900	800	800	800	900	900	800
Dimensions	Height		mm	1878								
	Width		mm	1152			1752		2306		2906	3506
	Length		mm	802					814			
Compressor	Type			Scroll - Vapor Injection								
	Quantity		N°	1					2			
	Economizer		N°	1					2			

Preliminary information, subject to change. Final data will be released at product launch.

Appendix B

Title appendix B

This is the PDF of appendix B.