Investigating Pretrained Language Models for Graph-to-Text Generation

Leonardo F. R. Ribeiro[†], Martin Schmitt[‡], Hinrich Schütze[‡] and Iryna Gurevych[†]

[†]Research Training Group AIPHES and UKP Lab, Technische Universität Darmstadt [‡]Center for Information and Language Processing (CIS), LMU Munich

www.ukp.tu-darmstadt.de

Abstract

Graph-to-text generation, a subtask of data-totext generation, aims to generate fluent texts from graph-based data. Many graph-to-text models have shown strong performance in this task employing specialized graph encoders. However, recent approaches employ large pretrained language models (PLMs) achieving state-of-the-art results in data-to-text generation. In this paper, we aim to investigate the impact of large PLMs in graph-to-text generation. We present a study across three graph domains: meaning representations, Wikipedia knowledge graphs (KGs) and scientific KGs. Our analysis shows that PLMs such as BART and T5 achieve state-of-the-art results in graphto-text benchmarks without explicitly encoding the graph structure. We also demonstrate that task-adaptive pretraining strategies are beneficial to the target task, improving even further the state of the art in two benchmarks for graph-to-text generation. In a final analysis, we investigate possible reasons for the PLMs' success on graph-to-text tasks. We find evidence that their knowledge about the world gives them a big advantage, especially when generating texts from KGs.1

1 Introduction

Graphs are important structures in natural language processing (NLP) as they represent complex relations between a set of objects. For example, syntactic and semantic structures of sentences can be represented using different graph representations (Bastings et al., 2017; Banarescu et al., 2013) and Knowledge Graphs (KGs) are used to encode factual knowledge in the form of relations between entities (Gardent et al., 2017).


Graph-to-text generation, a subtask of data-to-text generation (Gatt and Krahmer, 2018), aims to

create meaningful and coherent natural language text to describe an input graph. Recent efforts for graph-to-text generation (Song et al., 2018; Damonte and Cohen, 2019; Ribeiro et al., 2019, 2020) focus on effectively encoding the input graph, employing graph encoders usually built upon Graph Neural Networks (GNN) (Kipf and Welling, 2017; Hamilton et al., 2017) or Transformers (Vaswani et al., 2017). These models better represent input graphs than standard text-to-text models where input graphs are linearized, neglecting structural graph information (Konstas et al., 2017; Colin and Gardent, 2018). In graph-to-text models, the encoder computes representations for a graph-based input that should be invariant to the node order, whereas the decoder generates text as a linear chain structure. The complex nature of graphs increases the difficulty of defining alignments between the source nodes/edges and the target tokens, broadening the structural gap between the encoder and decoder (Zhao et al., 2020a).

Transfer learning has become ubiquitous in NLP and pretrained Transformer-based architectures considerably have outperformed prior state of the art (Devlin et al., 2019; Liu et al., 2020; Radford et al., 2019). Following this trend, very recent work (Mager et al., 2020; Harkous et al., 2020; Kale, 2020; Radev et al., 2020) apply transfer learning for data-to-text generation, where a language model is first pretrained on massive corpora before being fine-tuned on the target task. More interestingly, some of these approaches are successfully employed in graph-to-text generation, even though they do not explicitly encode the graph structure.

In this paper, we investigate pretrained language model (PLM) approaches for graph-to-text generation. We present a study across three graph domains (meaning representations, Wikipedia KGs and scientific KGs) and show strong results even though the models do not encode any graph-

¹We will release our code, datasets and pretrained models upon publication.



Text: As his children, we feel very terrible now.

Input: (feel :ARG0 (we) :ARG1 (terrible :degree (very)) :time
(now) :ARG1-of (cause :ARG0 (have-rel-role :ARG0 we :ARG1 (he)
:ARG2 (child))))

Text: Alan Bean graduated from UT Austin in 1955 with a Bachelor of Science degree. He was hired by NASA in 1963 and served as a test pilot. Apollo 12's backup pilot was Alfred Worden and was commanded by David Scott.

Input: <H> Apollo 12 <R> backup pilot <T> Alfred Worden <H> Alan Bean <R> was a crew member of <T> Apollo 12 <H> Apollo 12 <R> operator <T> NASA <H> Alan Bean <R> occupation <T> Test pilot <H> Apollo 12 <R> commander <T> David Scott <H> Alan Bean <R> alma Mater <T> UT Austin B.S. 1955

Figure 1: Examples of (a) AMR and (b) WebNLG graphs, the reference texts and the input for the graph-to-text models.

specific structural bias. In particular, we examine two recent text-to-text models: BART (Lewis et al., 2020) and T5 (Raffel et al., 2019). Those architectures are suitable for conditional text generation as they both follow a Transformer encoder-decoder architecture. Their main differences are different pretraining strategies and the datasets, on which they were trained.

Our contributions are three fold:

- We execute extensive experiments with BART and T5 and show that PLMs consistently outperform recent specialized graph-to-text models on three benchmarks for graph-to-text generation.
- We collect additional task-specific data and propose a supervised and unsupervised taskadaptive pretraining, which further improves the performance on two graph-to-text benchmarks. Additionally, we will release these datasets.
- We show that even though encoding the structural graph bias improves results in previous models that were trained from scratch, PLMs even perform well when trained on a shuffled version of the graph input. In further analysis, we show that the knowledge acquired during pretraining gives PLMs such a significant advantage on certain graph-to-text benchmarks that they do not need to understand the input graph structure for good performance.

2 Related Work

Graph-to-text generation can be divided into two main tasks: (i) MR-to-text generation - generating text from meaning representations (Konstas et al., 2017) and (ii) KG-to-text generation - generating text from knowledge graphs (KG) (Gardent et al., 2017).

AMR-to-Text Generation. Abstract Meaning Representation (AMR; Banarescu et al. (2013)) is a semantic formalism that represents the meaning of a sentence as a rooted directed graph expressing "who is doing what to whom". In an AMR graph, nodes represent concepts and edges represent semantic relations. Various neural models have been proposed to generate sentences from AMR graphs. Konstas et al. (2017) propose the first neural approach for AMR-to-text generation that uses a linearized input graph. Song et al. (2018) and Beck et al. (2018) propose GNNs based on recurrent mechanisms to directly encode the AMR graph structure. Damonte and Cohen (2019) investigate combinations of graph convolutional networks (GCN) and LSTMs in order to encode the AMR nodes. Ribeiro et al. (2019) develop a graph encoder that computes a top-down and a bottom-up representation of the AMR graph whereas Guo et al. (2019) employ dense connections between GNN layers. Recent methods (Zhu et al., 2019; Cai and Lam, 2020; Wang et al., 2020; Song et al., 2020) employ Transformers to learn node representations injecting the graph structure into the self-attention

aggregation.

KG-to-Text Generation. Recent neural approaches for KG-to-text generation linearize the KG triples ignoring the graph structure (Moryossef et al., 2019; Castro Ferreira et al., 2019). Trisedya et al. (2018) develop an LSTM encoder that encodes relationships within and between triples. Marcheggiani and Perez Beltrachini (2018) propose to employ GNNs to capture node contexts, and demonstrate superior performance compared to LSTMs. Koncel-Kedziorski et al. (2019) propose a Transformer-based approach which encodes the input graph by computing node representations based on the node context of direct neighbors. Recently, Ribeiro et al. (2020) propose a unified Graph Attention Network (GAT) framework that encodes both global and node contexts in order to better capture the graph topology.

Pretrained Models. Pretraining Transformerbased methods, such as BERT (Devlin et al., 2019), GPT-2 (Radford et al., 2019), XLNet (Yang et al., 2019), or RoBERTa (Liu et al., 2020), have established a qualitatively new level of baseline performance for many widely used Natural Language Understanding (NLU) benchmarks, including the popular GLUE (Wang et al., 2018). Mager et al. (2020) is the first approach that employs a pretrained Transformer-based language model (GPT-2) for AMR-to-text generation. Very recently, Harkous et al. (2020) and Kale (2020) demonstrate state-ofthe-art results in different data-to-text benchmarks, employing GPT-2 and T5 models respectively. Concurrent to our work, Radev et al. (2020) propose DART, a large dataset for data-to-text generation, and employ BART in the WebNLG dataset, augmenting the training data with DART and achieving good performance in the out-of-domain setting.

3 Fine-tuning Pretrained Models

In this paper, we investigate two PLMs based on the Transformer encoder-decoder architecture (Vaswani et al., 2017): BART and T5. The main differences between these two models are how they are trained and the input corpora for pretraining. Our main motivation for using BART and T5 is that their encoder-decoder architectures are particularly flexible and thus likely well-suited for conditioned text generation tasks.

BART. BART (Lewis et al., 2020) is pretrained as a text-to-text denoising autoencoder. In par-

ticular, in BART, ReLU activation functions are replaced by GeLUs. The pretraining stage has two phases. First, the input text is corrupted with an arbitrary noising function, and, second, a text-to-text model is learned in order to reconstruct the original text. The model is pretrained on a combination of books and Wikipedia data. In our experiments, we evaluate the impact of the model capacity with two versions: *base* with 140M parameters and *large* with 400M parameters.

T5. The T5 (Raffel et al., 2019) model aims to convert different problems into a text-to-text format. T5 follows the original Transformer architecture with a modification regarding the positional embeddings. Instead of using a fixed embedding for each position, they employ a simplified form of position embeddings where each embedding is simply a scalar that is added to the corresponding logit used for computing the attention weights. T5 is pretrained on a clean up version of Common Crawls web and demonstrated state-of-the-art performance on datasets such as CNN/Daily Mail (Chen et al., 2016) and SuperGLUE (Wang et al., 2019). We experiment with T5 models with different capacities: small with 60M, base with 220M, and large with 770M parameters.

Fine-tuning. In order to explore transfer learning with large PLMs for graph-to-text generation, we train BART and T5 for some epochs on a supervised downstream dataset, in a process referred to as fine-tuning. We also experiment with an intermediate pretraining step before the fine-tuning phase. In this intermediate pretraining step, we train the models with additional task-specific data, employing supervised and unsupervised approaches (see Section 6). For T5, in the supervised setup, we add a prefix "translate from Graph to Text:" before the graph input. We add this prefix to imitate the setup used during T5's original pretraining, when translating between different languages. The motivation for adding this kind of prefix is that it could help the model to identify the new task as a form of translation and to better distinguish between graphs and natural language texts.

4 Datasets

In this work, we evaluate text-to-text pretrained models in three graph-to-text benchmarks: AMR17 (LDC2017T10²), WebNLG (Gardent et al., 2017),

²Downloaded from https://amr.isi.edu/download.html.

Model	BLEU	METEOR	chrF++	BS (F1)	MS	BT
Damonte and Cohen (2019)	23.30	-	50.40	-	-	-
Ribeiro et al. (2019)	27.87	33.21	-	-	-	-
Zhu et al. (2019)	31.82	36.38	64.05	-	-	-
Guo et al. (2019)	27.60	-	57.30	-	-	-
Cai and Lam (2020)	29.80	35.10	59.40	-	-	-
Zhao et al. (2020b)	32.46	36.78	-	-	-	-
Yao et al. (2020)	34.10	38.10	65.60	-	-	-
based on pretrained language models						
Mager et al. (2020)	33.02	37.68	63.89	-	-	-
Harkous et al. (2020)	37.70	38.90	-	-	-	-
BART-Base	36.43	36.95	64.24	94.15	54.55	45.64
BART-Large	43.72	41.27	71.27	95.59	62.92	55.01
T5-Small	39.15	38.98	66.39	94.64	58.64	48.37
T5-Base	43.37	40.43	69.22	95.12	60.87	50.75
T5-Large	43.18	40.10	66.79	95.20	61.01	52.28

Table 1: Results on AMR-to-text generation for the AMR17 test set. BS, MS and BT stands for BertScore, MoverScore and BLEURT, respectively.

	#train	#dev	#test
AGENDA	38,720	1,000	1,000
WebNLG	18,102	872	971
AMR17	36,521	1,368	1,371

Table 2: Data statistics.

and AGENDA (Koncel-Kedziorski et al., 2019). Table 2 shows statistics for each dataset.

AMR17. The LDC2017T10 corpus contains instances with a sentence annotated with its corresponding AMR graph. The AMR graphs are processed and represented using PENMAN notation (see Figure 1) as it was shown to have better performance compared to other processing techniques (Mager et al., 2020). We use the preprocessing script by Ribeiro et al. (2019) to linearize the graph.

WebNLG. Each instance of WebNLG contains a KG extracted from DBPedia³ (Auer et al., 2007) in the form of triples and a target text, consisting of one or multiple sentences, describing the graph. The test set is divided into three partitions: *seen*, which contains only DBPedia categories presented in the train set; *unseen*, which covers categories never seen during training; and *all*, which includes categories from both seen and unseen sets. Similarly to previous work (Harkous et al., 2020; Kale, 2020), we linearize the triples adding special tokens. In particular, we prepend the tokens $\langle H \rangle$,

 $\langle R \rangle$, and $\langle T \rangle$ before the head entity, the relation and tail entity of a triple, respectively.

AGENDA. This dataset is constructed from the scientific AI domain. In particular, KGs are paired with scientific abstracts extracted from proceedings of 12 top AI conferences. Each sample contains the paper title, a KG and the corresponding paper abstract. A KG contains entities corresponding to scientific terms, which are often multi-word expressions, and the edges represent relations between the entities. This dataset has loose alignments between the input graph and the corresponding text as the graphs were automatically generated by employing an information extraction system (Koncel-Kedziorski et al., 2019). The input for the models is a text containing the title, a sequence of all KG entities, and the linearized triples. The target text is the paper abstract. We add special tokens into the triples in the same way as for WebNLG. In contrast to WebNLG, we had to list all entities given in the input additionally to listing all the triples because AGENDA contains a lot of instances with isolated entities, i.e., entities that do not occur in any triple. In WebNLG, this is never the case.

5 Experiments

We develop our experiments based on BART and T5 pretrained models released by Wolf et al. (2019). We use Adam optimization (Kingma and Ba, 2015) as the optimizer with an initial learning rate of 3×10^{-5} . We do not employ warm-up in our learning rate schedule. For decoding,

³DBPedia is constructed extracting structured content from Wikipedia.

		BLEU		N	IETEO	R		chrF++	
Model	A	S	U	A	S	U	A	S	U
Melbourne	45.13	54.52	33.27	37.00	41.00	33.00	-	-	-
Trisedya et al. (2018)	37.10	54.00	29.20	31.00	37.00	28.00	-	-	-
Castro Ferreira et al. (2019)	51.68	56.35	38.92	32.00	41.00	21.00	-	-	-
Moryossef et al. (2019)	47.24	53.30	34.41	39.00	44.00	37.00	-	-	-
Schmitt et al. (2020)	-	59.39	-	-	42.83	-	-	74.68	-
Ribeiro et al. (2020)	-	63.69	-	-	44.47	-	-	76.66	-
Zhao et al. (2020a)	52.78	64.42	38.23	41.00	46.00	37.00	-	-	-
based on pretrained language mod	dels								
Harkous et al. (2020)	52.90	-	-	42.40	-	-	-	-	-
Kale (2020)	57.10	63.90	52.80	44.00	46.00	41.00	-	-	-
BART-Base	49.81	58.71	38.47	39.20	42.94	35.05	67.65	73.30	61.50
BART-Large	49.49	62.46	35.87	41.47	45.68	36.92	71.08	77.92	63.61
T5-Small	55.02	62.53	45.83	41.86	44.78	38.57	71.54	76.20	66.46
T5-Base	57.46	62.93	50.88	43.05	44.99	40.81	73.31	76.57	69.75
T5-Large	59.29	63.06	54.69	43.99	45.35	42.41	74.54	76.89	71.98

Table 3: Results on WebNLG test set. A, S and U stands for all, seen and unseen partitions of the WebNLG test sets, respectively.

we use beam search with the beam sizes of 5, 3, and 5 for AMR17, WebNLG, and AGENDA, respectively. Following previous works, we evaluate the results using BLEU (Papineni et al., 2002), METEOR (Denkowski and Lavie, 2014) and CHRF++ (Popović, 2015) automatic metrics.⁴ We also evaluate the results using Mover-Score (Zhao et al., 2019), BERTScore (Zhang et al., 2020) and BLEURT (Sellam et al., 2020) metrics, as they employ contextual embeddings to incorporate semantic knowledge. We report the test results when the BLEU score on development set is optimal.

5.1 Results on AMR-to-Text

Table 1 shows the results of our experiments and several recent results reported on the AMR17 test set. Note that we also report results from models that leverage PLMs. Mager et al. (2020) and Harkous et al. (2020) employ the GPT-2 model in their approaches. Note whereas GPT-2 is a Transformer-based decoder, our approaches employ BART and T5 that follow a Transformer-based encoder-decoder architecture. T5-Large achieves a considerable improvement of 5.48 BLEU and 1.2 METEOR scores over the previous state-of-the-art model that uses GPT2. BART achieves the new state-of-the-art BLEU score of 43.72, 15.9%

higher. Note that the semantic metrics follow similar trends.

5.2 Results on WebNLG

We compare the performance of our experiments with many state-of-the-art results reported on this dataset. Table 3 shows the results for the WebNLG test set. Melbourne is one of the best competitors in the WebNLG challenge. Moryossef et al. (2019) and Castro Ferreira et al. (2019) develop neural pipeline approaches with explicit intermediate steps in the generation process and achieve strong performance in the unseen dataset. On the other hand, fully end-to-end models (Ribeiro et al., 2020; Schmitt et al., 2020) have strong performance on seen dataset and usually perform poorly in unseen data. A very recent model (Zhao et al., 2020a) achieves the best performance in the seen test set. However, this model leverages additional information about the order that the triples are realized into the target text. T5 achieves 59.29 and 54.69 BLEU points on all seen and unseen datasets. Note that Kale (2020) also employ T5 in this benchmark. In particular, in our T5 setup, we add a prefix before the input graph (see section 3). BART performs much worse than T5 on this dataset, with around 10 BLEU points lower compared to T5 in all seen partition.

5.3 Results on AGENDA

In Table 4 we show the results for the AGENDA test set. We compare our approaches against sev-

⁴For BLEU, we use the multi-BLEU script from the MOSES decoder suite (Koehn et al., 2007). For ME-TEOR, we use the original meteor-1.5.jar script (https://github.com/cmu-mtlab/meteor)

Model	BLEU	METEOR	chrF++	BS (F1)	MS	BT
Koncel-Kedziorski et al. (2019)	14.30	18.80	-	-	-	-
An (2019)	15.10	19.50	-	-	-	-
Schmitt et al. (2020)	17.33	21.43	44.53	-	-	-
Ribeiro et al. (2020)	18.01	22.23	46.37	-	-	-
BART-Base	22.01	23.54	48.02	89.36	34.33	-13.02
BART-Large	23.65	25.19	50.44	88.74	32.24	-10.93
T5-Small	20.22	21.62	44.91	88.56	30.25	-24.10
T5-Base	20.73	21.88	48.14	88.81	31.33	-21.03
T5-Large	22.15	23.73	48.14	89.60	35.23	-13.96

Table 4: Results on AGENDA test set. BS, MS and BT stands for BertScore, MoverScore and BLEURT, respectively.




Figure 2: Task-adaptive pretraining with additional data. We experiment employing supervised and unsupervised approaches.

eral recent results reported on this dataset. It is worth mentioning that AGENDA graphs are incomplete regarding the target text. In contrast to WebNLG, this dataset is from scientific domain and the KGs and texts are extracted from the AI domain (Koncel-Kedziorski et al., 2019). The models also have strong performance on this dataset. We believe that their capacity to generate fluent text helps when generating paper abstracts, even though they were not pretrained in the scientific domain. We note that an intermediate task-adaptive pretraining can enable the models to achieve better performance. Finally, note that BART has impressive performance with its large variant achieving a score of 23.65 BLEU points, 5.6 points higher than the previous state of the art.

6 Task-adaptive Pretraining

Following recent previous work (Gururangan et al., 2020), we would like to investigate whether leveraging additional task-specific data can further improve the performance on graph-to-text generation. Task-specific data refers to a smaller pretraining corpus that is more task-relevant. In order to lever-

age the task-specific data, we add an intermediate pretraining step between the original pretraining and fine-tuning phases for graph-to-text generation. Figure 2 shows the proposed training pipeline strategy.

More precisely, we first continue pretraining BART and T5 using an unsupervised or supervised training. In the supervised approach, we use pairs of graphs and corresponding texts collected from the same or similar domain as the target task. In the unsupervised approach, we follow BART and T5 pretraining strategies, corrupting the target text. Note that we do not use the graphs in the unsupervised pretraining, but only the target text of our task-specific data collections. In particular, we randomly mask text spans, replacing 15% of the tokens.⁵ Finally, we fine-tune the models using the original training set.

We employ this strategy for two graph domains: meaning representations (AMR17) and scientific data (AGENDA), in which we collected additional task-specific data.

AMR Silver Data. In order to generate additional data for AMR, we sample 200K Gigaword⁶ sentences and use JAMR⁷ (Flanigan et al., 2016) to parse them into AMR graphs. Note that the newswire data in Gigaword is also one of the data sources in the AMR17 benchmark. We use the 200K silver graphs to pretrain the models in a supervised way before fine-tuning them on gold AMR graphs. For the unsupervised pretraining, we only use the sentences.

Semantic Scholar AI Data. We collect titles and abstracts of around 190K scientific papers from the

⁵Please, refer to Lewis et al. (2020) and Raffel et al. (2019) for details about the unsupervised pretraining strategies.

⁶https://catalog.ldc.upenn.edu/LDC2003T05.

⁷https://github.com/jflanigan/jamr.

	Title	Abstract	KG
Vocab	48K	173K	113K
Tokens	2.1M	31.7M	9.6M
Entities	-	-	3.7M
Avg Length	11.1	167.1	-
Avg #Nodes	-	-	19.9
Avg #Edges	-	-	9.4

Table 5: Statistics for KGAIA. Averages are computed per instance.

AMR17					
Model	BLEU	METEOR	chrF++		
BART	43.72	41.27	71.27		
BART-TSU	43.94	41.15	71.14		
BART-TSS	45.54	42.50	72.78		
T5	43.18	40.10	66.79		
T5-TSU	45.91	41.82	71.19		
T5-TSS	48.85	43.12	73.10		
AGENDA					
Model	BLEU	METEOR	chrF++		
BART	23.65	25.19	50.44		
BART-TSU	25.30	25.54	51.33		

BART-TSU BART-TSS	25.30 25.66	25.54 25.74	51.33 51.63
T5	22.15	23.73	48.14
T5-TSU	22.92	24.40	49.37
T5-TSS	23.69	24.92	50.27

Table 6: Impact of additional task-adaptive pretraining of BART-Large and T5-Large on AMR17 and AGENDA datasets. TSU and TSS refer to unsupervised and supervised pretraining on the additional task-specific data.

Semantic Scholar (Ammar et al., 2018) taken from the proceedings of 36 top Computer Science/AI conferences. We construct KGs from the paper abstracts employing DyGIE++ (Wadden et al., 2019), an automatic information extraction system. Note that the AGENDA dataset was constructed using the SciIE system (Luan et al., 2018), which also extracts KGs from AI scientific papers. However, in our new dataset, the domain is broader as we collected data from 36 conferences compared to 12 from AGENDA. Furthermore, to prevent data leakage, all AGENDA samples used for performance evaluation are removed from the dataset. We will call this dataset KGAIA (KGs from AI Abstracts). Table 5 shows the dataset statistics.

6.1 Results

Table 6 compares the models' performance with either no additional pretraining, with additional un-

Pretrained on	Evaluated on	BLEU
None	AGENDA	22.01
KGAIA	AGENDA	23.48
WebNLG	AGENDA	21.98
None	WebNLG-Seen	58.71
KGAIA	WebNLG-Seen	63.20
AGENDA	WebNLG-Seen	61.25

Table 7: Impact of cross-domain supervised pretraining for BART-Base on KG-to-text generation.

supervised pretraining solely on the target texts of the respective in-domain corpus (TSU), and with additional task-adaptive supervised pretraining (TSS), before being fine-tuned on the respective train sets. Unsupervised pretraining helps less than supervised pretraining but also brings gains in most cases. This suggests that the performance increases after additional supervised pretraining do not only come from seeing more task-specific target texts but that the models learn how to handle graphs and the graph-to-text correspondence. Also note that we use the same number of datapoints for unsupervised and supervised experiments. It is probable that unsupervised pretraining on larger amounts of in-domain data would improve the models even more.

AMR17. When fine-tuned directly after the original pretraining, BART has better performance than T5. However, when pretraining on the task-specific data, T5 outperforms BART by 3.3 BLEU points, achieving 48.85 BLEU points, the new state of the art for the AMR-to-text generation.

AGENDA. BART benefits more from the task-adaptive pretraining, achieving the new state of the art of 25.66 BLEU points, a gain of 2 BLEU points. The improvements from task-adaptive pretraining are not as large as in the AMR dataset. We believe that this is due to the fact that the input graphs do not completely cover the target text, making this dataset more challenging.

6.2 Cross-domain Pretraining

We also investigate how cross-domain pretraining affects the performance after fine-tuning. Table 7 shows the results executed using BART. While the target texts in KGAIA and AGENDA share the domain of scientific abstracts, texts in WebNLG are more general. The graphs in all three datasets are KGs, but WebNLG graphs do not share any relations with the other KGs. Nevertheless, super-

T/F		Input Fact		order	shuf
(1) F (2) F	· Ohio · United States	· is Part Of · is Part Of	· Cleveland · Amarillo, Texas	Ohio is part of Cleveland. Amarillo, Texas is part of the United States.	Cleveland is part of Ohio. Amarillo, Texas is part of the United States.
(3) F	· Leinster	$\cdot \text{ is Part Of }$	· Dublin	Leinster is part of Dublin.	Leinster is part of Dublin.
(4) F (5) T (6) F (7) T	· Rome · Italy · rome · italy	capitalcapitalcapitalcapital	· Italy · Rome · italy · rome	Romes capital is Italy. Italys capital is Rome. The capital of rome is italy. Italys capital is rome.	Rome is the capital of Italy. Rome is the capital of Italy. Italy is the capital of rome. Italys capital is rome.

Table 8: Example generations from corrupted (F) and true (T) WebNLG dev set facts by T5-Small models fine-tuned on correctly ordered nodes (order) and randomly shuffled nodes (shuf) from the WebNLG training set. · denotes the separator tag.

vised pretraining increases the performance in the cross-domain setting in most of the cases. Only pretraining on the smaller WebNLG does not help for the larger AGENDA.

In general, the experiments suggest that exploring additional pretraining for graph-to-text generation tasks can improve the models' performance even if the data do not come from the same domain. Therefore, we hope that our newly collected datasets will be valuable for future work on graph-to-text generation.

7 Graph Structure and Pretrained Models

7.1 Bag of Entities and Relations

To further examine to what extent the graph structure is used by the pretrained models, we conduct additional experiments where the graph structure is only encoded by the order of node labels, i.e., we remove parentheses in AMRs and replace $\langle H \rangle$, $\langle R \rangle$, and $\langle T \rangle$ tags by neutral separators for KGs. In this way, the graph structure is completely obscured if we shuffle the node labels. In particular, we investigate two model variants: a T5 model finetuned on ordered nodes, and another one finetuned on shuffled nodes. In Table 9, we compare the effects on the performance of the T5 models when the graph structure is lost during training or evaluation.

We observe that the AMR-to-text performance drops significantly when the graph structure is missing. KG-to-text performance, however, does not decrease much, indicating that most of the PLMs' success in this task stems from their language modeling rather than their graph encoding capabilities. It has recently been argued that large PLMs acquire a certain amount of world knowledge during pretraining (Petroni et al., 2019). We hypothesize

AMR17						
Train	Eval	BLEU	METEOR	chrF++		
order shuf	order order	36.83 17.02	38.17 27.79	65.57 51.00		
order shuf	shuf shuf	05.18 15.56	19.63 27.23	39.97 50.20		
WebNLG-Seen						
Train	Eval	BLEU	METEOR	chrF++		
order shuf	order order	63.41 61.54	44.98 44.19	76.56 75.55		

1	1	10.06	01.70	44.00		
Train	Eval	BLEU	METEOR	chrF++		
	AGENDA					
shuf	shuf	61.07	44.26	75.58		
order	shuf	54.08	40.63	70.77		
Silui	order	01.34	44.19	13.33		

Train	Eval	BLEU	METEOR	chrF++
order	order	19.86	21.73	44.90
shuf	order	19.03	21.40	44.31
order	shuf	19.04	21.53	44.60
shuf	shuf	19.08	21.49	44.37

Table 9: Impact of using a bag of entities and relations (shuf) as input for training or evaluation on AMR17, WebNLG-Seen, and AGENDA datasets. T5-Small was used for this experiment.

that this knowledge makes it easier to recover KG facts based on a set of entities and relations than reconstructing a corrupted AMR.

7.2 Qualitative Analysis

To further test our hypothesis that pretrained models make use of their world knowledge during KG-to-text generation, we take example facts from the WebNLG dev set, corrupt them, and feed them to the two T5 models introduced in the previous section. Table 8 shows the generations.

Note that the model trained on correctly ordered nodes inside the triples has learned a bit more to rely on the input graph structure. The false fact in example (1) is reliably transferred to the text by

order but not by shuf, which silently corrects it. But even *order* is not completely free from its world knowledge bias, as illustrated in example (2) where both models refuse to generate an incorrect fact. This indicates that world knowledge is a strong guide during text generation even for models that were fine-tuned with the graph structure clearly marked. Interestingly, neither model corrects the wrong input in (3). The fact that Leinster is a region in Ireland and not, e.g., a neighborhood of the city Dublin is probably unknown to T5. It seems that T5 falls back to the order of words in the input in such a case. Examples (4)–(7) also illustrate this behavior nicely. While the well-known entities "Rome" and "Italy" produce a similar behavior as "Ohio" and "Cleveland", i.e., order complies with generating a false statement and shuf rather follows its world knowledge, lowercasing the entity names changes that. In case of the unknown entities "rome" and "italy", both models fall back to the order of the input to produce their texts.

8 Conclusion

We have studied the problem of generating text from graphs, employing two PLMs: BART and T5. Interestingly, these models achieve state-of-theart results on different graph-to-text benchmarks, even though they do not explicitly encode the graph structure. Second, we demonstrate that taskadaptive pretraining improves the performance of PLMs for graph-to-text generation. Third, we examine to what extent the graph structure is considered for the text generation process, and our experiments suggest that prior world knowledge is a strong guide for these models. Future work should explore ways to inject the graph structure more intimately into large PLMs, thus possibly both leveraging their strong language modeling capabilities and keeping the output more faithful to the input.

References

Waleed Ammar, Dirk Groeneveld, Chandra Bhagavatula, Iz Beltagy, Miles Crawford, Doug Downey, Jason Dunkelberger, Ahmed Elgohary, Sergey Feldman, Vu Ha, Rodney Kinney, Sebastian Kohlmeier, Kyle Lo, Tyler Murray, Hsu-Han Ooi, Matthew Peters, Joanna Power, Sam Skjonsberg, Lucy Wang, Chris Wilhelm, Zheng Yuan, Madeleine van Zuylen, and Oren Etzioni. 2018. Construction of the literature graph in semantic scholar. In *Proceedings of the 2018 Conference of the North American Chap-*

ter of the Association for Computational Linguistics: Human Language Technologies, Volume 3 (Industry Papers), pages 84–91, New Orleans - Louisiana. Association for Computational Linguistics.

Bang An. 2019. Repulsive bayesian sampling for diversified attention modeling. In 4th workshop on Bayesian Deep Learning (NeurIPS 2019).

Sören Auer, Christian Bizer, Georgi Kobilarov, Jens Lehmann, Richard Cyganiak, and Zachary Ives. 2007. Dbpedia: A nucleus for a web of open data. In *Proceedings of the 6th International The Semantic Web and 2nd Asian Conference on Asian Semantic Web Conference*, ISWC07/ASWC07, page 722735, Berlin, Heidelberg. Springer-Verlag.

Laura Banarescu, Claire Bonial, Shu Cai, Madalina Georgescu, Kira Griffitt, Ulf Hermjakob, Kevin Knight, Philipp Koehn, Martha Palmer, and Nathan Schneider. 2013. Abstract meaning representation for sembanking. In *Proceedings of the 7th Linguistic Annotation Workshop and Interoperability with Discourse*, pages 178–186, Sofia, Bulgaria. Association for Computational Linguistics.

Joost Bastings, Ivan Titov, Wilker Aziz, Diego Marcheggiani, and Khalil Sima'an. 2017. Graph convolutional encoders for syntax-aware neural machine translation. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 1957–1967, Copenhagen, Denmark. Association for Computational Linguistics.

Daniel Beck, Gholamreza Haffari, and Trevor Cohn. 2018. Graph-to-sequence learning using gated graph neural networks. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 273–283, Melbourne, Australia. Association for Computational Linguistics.

Deng Cai and Wai Lam. 2020. Graph transformer for graph-to-sequence learning. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 7464–7471. AAAI Press.

Thiago Castro Ferreira, Chris van der Lee, Emiel van Miltenburg, and Emiel Krahmer. 2019. Neural data-to-text generation: A comparison between pipeline and end-to-end architectures. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 552–562, Hong Kong, China. Association for Computational Linguistics.

Danqi Chen, Jason Bolton, and Christopher D. Manning. 2016. A thorough examination of the

- CNN/daily mail reading comprehension task. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2358–2367, Berlin, Germany. Association for Computational Linguistics.
- Emilie Colin and Claire Gardent. 2018. Generating syntactic paraphrases. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 937–943, Brussels, Belgium. Association for Computational Linguistics.
- Marco Damonte and Shay B. Cohen. 2019. Structural neural encoders for AMR-to-text generation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 3649–3658, Minneapolis, Minnesota. Association for Computational Linguistics.
- Michael Denkowski and Alon Lavie. 2014. Meteor universal: Language specific translation evaluation for any target language. In *Proceedings of the Ninth Workshop on Statistical Machine Translation*, pages 376–380, Baltimore, Maryland, USA. Association for Computational Linguistics.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Jeffrey Flanigan, Chris Dyer, Noah A. Smith, and Jaime Carbonell. 2016. CMU at SemEval-2016 task 8: Graph-based AMR parsing with infinite ramp loss. In *Proceedings of the 10th International Workshop on Semantic Evaluation (SemEval-2016)*, pages 1202–1206, San Diego, California. Association for Computational Linguistics.
- Claire Gardent, Anastasia Shimorina, Shashi Narayan, and Laura Perez-Beltrachini. 2017. The WebNLG challenge: Generating text from RDF data. In *Proceedings of the 10th International Conference on Natural Language Generation*, pages 124–133, Santiago de Compostela, Spain. Association for Computational Linguistics.
- Albert Gatt and Emiel Krahmer. 2018. Survey of the state of the art in natural language generation: Core tasks, applications and evaluation. *Journal of Artificial Intelligence Research*, 61(1):65170.
- Zhijiang Guo, Yan Zhang, Zhiyang Teng, and Wei Lu. 2019. Densely connected graph convolutional networks for graph-to-sequence learning. *Transactions of the Association for Computational Linguistics*, 7:297–312.

- Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. 2020. Don't stop pretraining: Adapt language models to domains and tasks. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8342–8360, Online. Association for Computational Linguistics.
- Will Hamilton, Zhitao Ying, and Jure Leskovec. 2017.
 Inductive representation learning on large graphs. In
 I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach,
 R. Fergus, S. Vishwanathan, and R. Garnett, editors,
 Advances in Neural Information Processing Systems
 30, pages 1024–1034. Curran Associates, Inc.
- Hamza Harkous, Isabel Groves, and Amir Saffari. 2020. Have your text and use it too! end-to-end neural data-to-text generation with semantic fidelity. *arXiv e-prints*.
- Mihir Kale. 2020. Text-to-text pre-training for data-to-text tasks. *arXiv e-prints*.
- Diederik P. Kingma and Jimmy Ba. 2015. Adam: A method for stochastic optimization. In 3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings.
- Thomas N. Kipf and Max Welling. 2017. Semi-Supervised Classification with Graph Convolutional Networks. In *Proceedings of the 5th International Conference on Learning Representations*, ICLR 2017.
- Philipp Koehn, Hieu Hoang, Alexandra Birch, Chris Callison-Burch, Marcello Federico, Nicola Bertoldi, Brooke Cowan, Wade Shen, Christine Moran, Richard Zens, Chris Dyer, Ondřej Bojar, Alexandra Constantin, and Evan Herbst. 2007. Moses: Open source toolkit for statistical machine translation. In Proceedings of the 45th Annual Meeting of the ACL on Interactive Poster and Demonstration Sessions, ACL '07, pages 177–180, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Rik Koncel-Kedziorski, Dhanush Bekal, Yi Luan, Mirella Lapata, and Hannaneh Hajishirzi. 2019. Text Generation from Knowledge Graphs with Graph Transformers. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 2284–2293, Minneapolis, Minnesota. Association for Computational Linguistics.
- Ioannis Konstas, Srinivasan Iyer, Mark Yatskar, Yejin Choi, and Luke Zettlemoyer. 2017. Neural amr: Sequence-to-sequence models for parsing and generation. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 146–157, Vancouver, Canada. Association for Computational Linguistics.

- Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. 2020. BART: Denoising sequence-to-sequence pretraining for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7871–7880, Online. Association for Computational Linguistics.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Roberta: A robustly optimized bert pretraining approach. *arXiv e-prints*.
- Yi Luan, Luheng He, Mari Ostendorf, and Hannaneh Hajishirzi. 2018. Multi-task identification of entities, relations, and coreference for scientific knowledge graph construction. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3219–3232, Brussels, Belgium. Association for Computational Linguistics.
- Manuel Mager, Ramón Fernandez Astudillo, Tahira Naseem, Md Arafat Sultan, Young-Suk Lee, Radu Florian, and Salim Roukos. 2020. GPT-too: A language-model-first approach for AMR-to-text generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1846–1852, Online. Association for Computational Linguistics.
- Diego Marcheggiani and Laura Perez Beltrachini. 2018. Deep graph convolutional encoders for structured data to text generation. In *Proceedings of the 11th International Conference on Natural Language Generation*, pages 1–9, Tilburg University, The Netherlands. Association for Computational Linguistics.
- Amit Moryossef, Yoav Goldberg, and Ido Dagan. 2019. Step-by-step: Separating planning from realization in neural data-to-text generation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2267–2277, Minneapolis, Minnesota. Association for Computational Linguistics.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: A method for automatic evaluation of machine translation. In *Proceedings of* the 40th Annual Meeting on Association for Computational Linguistics, ACL '02, pages 311–318, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. 2019. Language models as knowledge bases? In Proceedings of the 2019 Conference on Empirical Methods in Natural Language

- Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 2463–2473, Hong Kong, China. Association for Computational Linguistics.
- Maja Popović. 2015. chrF: character n-gram f-score for automatic MT evaluation. In *Proceedings of the Tenth Workshop on Statistical Machine Translation*, pages 392–395, Lisbon, Portugal. Association for Computational Linguistics.
- Dragomir Radev, Rui Zhang, Amrit Rau, Abhinand Sivaprasad, Chiachun Hsieh, Nazneen Fatema Rajani, Xiangru Tang, Aadit Vyas, Neha Verma, Pranav Krishna, Yangxiaokang Liu, Nadia Irwanto, Jessica Pan, Faiaz Rahman, Ahmad Zaidi, Murori Mutuma, Yasin Tarabar, Ankit Gupta, Tao Yu, Yi Chern Tan, Xi Victoria Lin, Caiming Xiong, and Richard Socher. 2020. Dart: Open-domain structured data record to text generation. arXiv e-prints.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2019. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv e-prints*.
- Leonardo F. R. Ribeiro, Claire Gardent, and Iryna Gurevych. 2019. Enhancing AMR-to-text generation with dual graph representations. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3183–3194, Hong Kong, China. Association for Computational Linguistics.
- Leonardo F. R. Ribeiro, Yue Zhang, Claire Gardent, and Iryna Gurevych. 2020. Modeling global and local node contexts for text generation from knowledge graphs. *Transactions of the Association for Computational Linguistics*.
- Martin Schmitt, Leonardo F. R. Ribeiro, Philipp Dufter, Iryna Gurevych, and Hinrich Schtze. 2020. Modeling graph structure via relative position for better text generation from knowledge graphs. *arXiv e-prints*.
- Thibault Sellam, Dipanjan Das, and Ankur Parikh. 2020. BLEURT: Learning robust metrics for text generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7881–7892, Online. Association for Computational Linguistics.
- Linfeng Song, Ante Wang, Jinsong Su, Yue Zhang, Kun Xu, Yubin Ge, and Dong Yu. 2020. Structural information preserving for graph-to-text generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*,

- pages 7987–7998, Online. Association for Computational Linguistics.
- Linfeng Song, Yue Zhang, Zhiguo Wang, and Daniel Gildea. 2018. A graph-to-sequence model for AMR-to-text generation. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1616–1626, Melbourne, Australia. Association for Computational Linguistics.
- Bayu Distiawan Trisedya, Jianzhong Qi, Rui Zhang, and Wei Wang. 2018. GTR-LSTM: A triple encoder for sentence generation from RDF data. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1627–1637, Melbourne, Australia. Association for Computational Linguistics.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems 30*, pages 5998–6008. Curran Associates, Inc.
- David Wadden, Ulme Wennberg, Yi Luan, and Hannaneh Hajishirzi. 2019. Entity, relation, and event extraction with contextualized span representations. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 5784–5789, Hong Kong, China. Association for Computational Linguistics.
- Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. 2019. Superglue: A stickier benchmark for general-purpose language understanding systems. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, Advances in Neural Information Processing Systems 32, pages 3266–3280. Curran Associates, Inc.
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. 2018. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pages 353–355, Brussels, Belgium. Association for Computational Linguistics.
- Tianming Wang, Xiaojun Wan, and Hanqi Jin. 2020. Amr-to-text generation with graph transformer. *Transactions of the Association for Computational Linguistics*, 8:19–33.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rmi Louf, Morgan Funtowicz,

- and Jamie Brew. 2019. Huggingface's transformers: State-of-the-art natural language processing.
- Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le.
 2019. Xlnet: Generalized autoregressive pretraining for language understanding. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, Advances in Neural Information Processing Systems 32, pages 5753–5763. Curran Associates, Inc.
- Shaowei Yao, Tianming Wang, and Xiaojun Wan. 2020. Heterogeneous graph transformer for graph-to-sequence learning. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7145–7154, Online. Association for Computational Linguistics.
- Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. Bertscore: Evaluating text generation with bert. In *International Conference on Learning Representations*.
- Chao Zhao, Marilyn Walker, and Snigdha Chaturvedi. 2020a. Bridging the structural gap between encoding and decoding for data-to-text generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 2481–2491, Online. Association for Computational Linguistics.
- Wei Zhao, Maxime Peyrard, Fei Liu, Yang Gao, Christian M. Meyer, and Steffen Eger. 2019. MoverScore: Text generation evaluating with contextualized embeddings and earth mover distance. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 563–578, Hong Kong, China. Association for Computational Linguistics.
- Yanbin Zhao, Lu Chen, Zhi Chen, Ruisheng Cao, Su Zhu, and Kai Yu. 2020b. Line graph enhanced AMR-to-text generation with mix-order graph attention networks. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 732–741, Online. Association for Computational Linguistics.
- Jie Zhu, Junhui Li, Muhua Zhu, Longhua Qian, Min Zhang, and Guodong Zhou. 2019. Modeling graph structure in transformer for better AMR-to-text generation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5459–5468, Hong Kong, China. Association for Computational Linguistics.