

dwd

Sam Wozniak

April 2, 2018

```
data <- read.csv("C:\\Users\\User\\Documents\\GitHub\\thesis\\fuels_guide\\jp\\dwd\\dwd.csv", header = 1)

data_ph1 <- subset(data, subset = sp_phase == 1)
data_ph2 <- subset(data, subset = sp_phase == 2)
data_ph3 <- subset(data, subset = sp_phase == 3)

dwd_ph1 <- data_ph1 %>%
  group_by(treatment) %>%
  summarise(n(),
    "min_10h" = round(min(dwd_fuel_10h, na.rm = TRUE)*0.00044609, 2),
    "max_10h" = round(max(dwd_fuel_10h, na.rm = TRUE)*0.00044609, 2),
    "mean_10h" = round(mean(dwd_fuel_10h, na.rm = TRUE)*0.00044609, 2),
    "min_100h" = round(min(dwd_fuel_100h, na.rm = TRUE)*0.00044609, 2),
    "max_100h" = round(max(dwd_fuel_100h, na.rm = TRUE)*0.00044609, 2),
    "mean_100h" = round(mean(dwd_fuel_100h, na.rm = TRUE)*0.00044609, 2),
    "min_1000hS" = round(min(dwd_fuel_1000h_s, na.rm = TRUE)*0.00044609, 2),
    "max_1000hS" = round(max(dwd_fuel_1000h_s, na.rm = TRUE)*0.00044609, 2),
    "mean_1000hS" = round(mean(dwd_fuel_1000h_s, na.rm = TRUE)*0.00044609, 2),
    "min_1000hR" = round(min(dwd_fuel_1000h_r, na.rm = TRUE)*0.00044609, 2),
    "max_1000hR" = round(max(dwd_fuel_1000h_r, na.rm = TRUE)*0.00044609, 2),
    "mean_1000hR" = round(mean(dwd_fuel_1000h_r, na.rm = TRUE)*0.00044609, 2))

dwd_ph1

## # A tibble: 4 x 14
##   treatment `n()` min_10h max_10h mean_10h min_100h max_100h mean_100h
##   <fct>      <int>   <dbl>   <dbl>   <dbl>   <dbl>   <dbl>   <dbl>
## 1 BM          14  0.120    1.22    0.460     0     2.41    0.840
## 2 CO          14  0.140    0.790    0.360    0.150    1.87    0.690
## 3 FI          12  0.170    0.520    0.340     0     0.930   0.520
## 4 ME          11  0.0700    1.67    0.600    0.300    2.36    1.12
## # ... with 6 more variables: min_1000hS <dbl>, max_1000hS <dbl>,
## #   mean_1000hS <dbl>, min_1000hR <dbl>, max_1000hR <dbl>,
## #   mean_1000hR <dbl>

#remove column 'n()'
dwd_ph1 <- dwd_ph1[-2]

#reformat table
d <- gather(dwd_ph1, key = fuel_class, value = "value", -treatment)
e <- d %>% separate(col = fuel_class, into = c('stat', 'fclass'), sep = "_")
f <- e %>% unite(col = 'stat', treatment, stat)
g <- f %>% spread(key = stat, value = value)
h <- arrange(g, desc(fclass))
i <- h[c('fclass', 'CO_min', 'CO_max', 'CO_mean', 'FI_min', 'FI_max', 'FI_mean', 'ME_min', 'ME_max', 'ME_mean')]
j <- i
j$fclass <- c("10h", "100h", "1000h sound", "1000h rotten")
colnames(j) <- c("Fuel Class", "Min", "Max", "Mean", "Min", "Max", "Mean", "Min", "Max", "Mean", "Min", "Max", "Mean", "Min", "Max", "Mean")
View(j)
```

```
dwd_jp <- kable(j, format = "latex") %>%
  kable_styling(c("striped", "bordered")) %>%
  add_header_above(c("", 'Control' = 3, 'Prescribed Fire' = 3, 'Cutting' = 3, 'Mastication' = 3))
dwd_jp
```

Fuel Class	Control			Prescribed Fire			Cutting			Mastication		
	Min	Max	Mean	Min	Max	Mean	Min	Max	Mean	Min	Max	Mean
10h	0.14	0.79	0.36	0.17	0.52	0.34	0.07	1.67	0.60	0.12	1.22	0.46
100h	0.15	1.87	0.69	0.00	0.93	0.52	0.30	2.36	1.12	0.00	2.41	0.84
1000h sound	0.00	1.37	0.21	0.00	0.61	0.19	0.00	2.47	0.73	0.00	0.80	0.20
1000h rotten	0.00	0.52	0.15	0.00	0.34	0.08	0.00	0.29	0.08	0.00	0.32	0.08