

Web 开发

WPC

2026 年 3 月 3 日

目录

1	web 开发	2
1.1	环境配置	2
1.2	开发部署	4

1 web 开发

1.1 环境配置

node

```
sudo apt update && sudo apt -y upgrade
sudo apt install -y npm nodejs
sudo npm install -g n
sudo n stable
```

yarn

```
sudo corepack enable
corepack use yarn@latest
```

vite

```
# Don't use Rolldown
yarn create vite frontend --template react-swc-ts
rm -rf package.json yarn.lock .pnpm.cjs .yarn
cd frontend
# Delete src/assets, App.css, index.css
corepack use yarn@latest
yarn
```

react

```
yarn add @mui/icons-material @mui/material @emotion/styled @emotion/react
yarn add react-router jotai react-hook-form
```

IDE

```
# zed
yarn dlx @yarnpkg/sdks base
ctrl+shift+p: settings
{
  "lsp": {
    "vtsls": {
      "settings": {
        "typescript": { "tsdk": ".yarn/sdks/typescript/lib" },
      },
    },
  },
}

# vscode
yarn dlx @yarnpkg/sdks vscode
ctrl+shift+p
Select TypeScript Version
```

1.2 开发部署

```
/etc/nginx/sites-enabled/default

sudo apt install -y nginx
server {
    listen 80 default_server;
    listen [::]:80 default_server;

    root /var/www/dist;

    index index.html index.htm index.nginx-debian.html;

    server_name your-domain.com;

    location / {
        try_files $uri $uri/ /index.html;
    }

    # 将 /api/auth/ 的请求转发到 keycloak.com/auth/
    location /api/auth/ {
        rewrite ~/api/auth/(.*)$ /auth/$1 break;

        proxy_pass https://keycloak.com;

        proxy_set_header Host keycloak.com;
        proxy_set_header X-Real-IP $remote_addr;
    }

    # 将 /api/v2/ 的请求转发到 data.com/
    location /api/v2/ {
        proxy_pass https://data.com;

        proxy_set_header Host data.com;
        proxy_set_header X-Real-IP $remote_addr;
    }
}
```