Great Graphics Using Proc Sgplot, Proc Sgscatter, and ODS Graphics for SAS®/Stat Procedures

Kathy Welch CSCAR

The University of Michigan MSUG Meeting, Tuesday April 27, 2010

What we will Cover

- Introduction to Statistical Graphics Procedures
 - Proc Sgplot
 - Proc Sgscatter
 - Proc Sgpanel
- Editing ODS graphics files
- Examples of ODS graphics with Statistical Procedures
 - Proc ttest
 - Proc Reg
 - Proc GLM
 - Proc Logistic


Statistical Graphics Using Proc Sgplot, Proc Sgscatter and Proc Sgpanel

- Statistical graphics plots use ODS (output delivery system) graphics
- Statistical graphics are easy to produce, look nice, and are more intuitive than traditional SAS/Graph graphics
- Statistical Graphics can be edited (to some extent) interactively

Where are my graphs?


- Graphs created with ODS graphics will be in Results Window, not in Graph Window
- Double-click on the graphics icon to view the file, using local windows graphics viewer.
- Graphs will be automatically be saved as .png files in current SAS folder
- png (portable network graphics) files are
 - Raster graphics
 - Compact format
 - Usable in most windows applications

Getting Started




Boxplots

proc sgplot data=mylib.employee;
vbox salary; run;




Boxplots for Categories

proc sgplot data=mylib.employee;
vbox salary/ category=gender; run;




Paneled Boxplots

```
proc sgpanel data=mylib.employee;
panelby jobcat / rows=1 columns=3;
vbox salary / category= gender; run;
```




Barcharts

proc sgplot data=mylib.employee;
vbar jobcat ; run;




Stacked Barcharts

proc sgplot data=mylib.employee; vbar jobcat /group=Gender; run;




Barcharts with Means and Error Bars

proc sgplot data=mylib.employee;
 vbar jobcat / response=salary limitstat = stddev
 limits = upper stat=mean; run;




Barcharts of Proportions

proc sgplot data=afifi;
 vbar shoktype / response=died stat=mean;
 format shoktype shokfmt.; run;




Paneled Barcharts

```
proc sgpanel data=mylib.employee;
  panelby gender;
  vbar jobcat / response=salary limitstat = stddev
  limits = upper stat=mean; run;
```




Histograms

```
proc sgplot data=mylib.employee;
histogram salary;
density salary;
density salary / type=kernel;
keylegend / location=inside position=topright;
```




Overlaid Histograms

proc sgplot data=mylib.employee;
histogram salbegin;
histogram salary / transparency = .5; run;




Note: Transparency = 0 is opaque. Transparency = 1.0 is fully transparent.

Scatterplots




Scatterplot with Regression Line

```
proc sgplot data=mylib.employee;
where jobcat=1;
scatter x=prevexp y=salary / group=gender;
reg x=prevexp y=salary / cli clm nomarkers; run;
```




Regression Lines for Subgroups

```
proc sgplot data=mylib.employee;
where jobcat=1;
reg x=prevexp y=salary / group=gender; run;
```




Paneled Scatterplot with Loess Fit

```
proc sgpanel data=mylib.employee;
  panelby jobcat / columns=3;
  scatter x=jobtime y=salary / group=gender;
  loess x=jobtime y=salary nomarkers; run;
```




Scatterplot Matrix



Series Plots proc sgpanel data=autism; panelby sicdegp /columns=3; series x=age y=vsae / group=Childid markers legendlabel=" " lineattrs=(pattern=1

color=black).




Generate Means

```
proc sort data=autism;
by sicdegp age;
run;
proc means data=autism noprint;
 by sicdegp age;
 output out=meandat mean(VSAE)=mean VSAE;
run;
data autism2;
 merge autism meandat(drop=_type_ _freq_);
 by sicdegp age;
run;
```

Mean Plots Overlaid on Raw Data

```
proc sgplot data=autism2;
series x=age y=mean_VSAE / group=SICDEGP;
scatter x=age y=VSAE; run;
```




Formats Make Graphs More Readable

```
proc format;
value jobcat 1="Clerical"
2="Custodial"
3="Manager";
value $Gender "f"="Female"
"m"="Male";
run;
```

Formats Make Graphs More

Readable 2
proc sgpanel data=mylib.employee;
panelby jobcat / rows=1 columns=3 novarname;
vbox salary / category= gender;
format gender \$gender. jobcat jobcat; run;




Editing ODS Graphics

- Use "sgedit", or "sgedit on" to enable ODS graphics editor
 - Submit in command dialog box
- Two outputs will be created for each graph.
 - .png file
 - .sge (SAS Graphics Editor) file
- Edit the .sge file, and save as a .png to use in other applications.

Some of the Things you can Edit with the ODS Graphics Editor

- Title, footnote
- Axis labels, colors, fonts, symbols, text boxes
- Graph Style (Try them)
 - Listing (the default, colors)
 - Analysis (color scheme)
 - Journal (grayscale)
 - Journal2 (black and white)
 - Statistical (color scheme)

SAS Graphics Editor Window




Creating PDF Output

- Send output to a pdf file
- Similar for HTML or rtf file output

```
ods pdf style=journal2;
ods pdf file = "testing.pdf";
ods listing close;
title "PDF Output";
proc sgpanel data=mylib.employee;
  panelby jobcat;
  scatter x=jobtime y=salary / group=gender;
  loess x=jobtime y=salary / nomarkers; run;
ods pdf close;
ods listing;
```

PDF Output will be in the Results Viewer Window



Where to Get Help for Statistical Graphics Procedures


- SAS Help and Documentation > Contents > SAS Products > SAS/Graph > SAS/Graph 9.2 Statistical Procedures Guide > SAS/Graph Statistical Graphics Procedures
- Once you find it, it's really helpful.

ODS Graphics in SAS/Stat Procedures

- ODS graphics are available for statistical procedures
- Submit "ods graphics on;" before the procedure
- Submit "ods graphics off;" after the procedure
- Graphs are .png files, as for Proc Sgplot, Sgscatter and Sgpanel.
- ODS graphics show up after "drilling down" in the Results window for the procedure.
- Check SAS documentation for available ODS graphics for each procedure


Proc ttest


```
ods graphics on;
proc ttest data=mylib.afifi;
class survive;
var sbp1;
run;
ods graphics off;
```



Proc Reg


```
ods graphics on;
title "Regression with Default Plots";
proc reg data=mylib.afifi;
  model sbp2 = sbp1 sex age/partial;
run; quit;
ods graphics off;
```






Proc Reg Unpack Graphics

proc reg plots(only)=DiagnosticsPanel(unpack);






Proc GLM

```
ods graphics on;
title "Anova with Plots";
proc glm data=mylib.afifi;
class shoktype;
model sbp1 = shoktype;
lsmeans shoktype / pdiff adjust=tukey;
run; quit;
ods graphics off;
```


Proc GLM DiffPlot




Proc Logistic

```
ods graphics on;
proc logistic data = mylib.afifi descending
plots(only)=(effect roccurve);
 class shoktype;
 model survive = sbp1 shoktype;
 output out=preddat p=predict reschi=rchi
resdev=rdev
     h=leverage;
run; quit;
ods graphics off;
```

Proc Logistic ROC Curve and Effect Plot





Thank you!

- Try some of these graphs using your data.
- They're easy and fun!