


# **Arrow Function**





## **Lecture CheckList**



- Introduction to Arrow functions.
- Arrow Function Syntax.
- Why should developers use arrow functions?



## **Introduction to Arrow Functions**



Arrow functions, introduced in ES6, is a straightforward and compact way of writing JavaScript functions. They improve the structure and readability of our code by providing a more concise syntax.



## **Arrow Function Syntax.**



Arrow functions use a simplified syntax with the "=>" arrow. They don't require the function keyword, and if the function body contains only a single expression, the curly braces and "return" statements can be omitted. If the function has a single parameter, the parentheses around the parameter can be omitted.

```
(parameter1, parameter2, ..., parameterN )=>{
// function body
return expression; // optional
}
```



## Examples of arrow function



```
// 1. One parameter, and a single return statement
```

```
const square = x => x * x;
```

0 0 0 -

// 2. Multiple parameters, and a single return expression

```
const sumOftwoNumbers = (x, y) \Rightarrow x + y;
```

// 3. Multiple statements in function expression

```
const sum = (x, y) => {
  console.log(`Adding ${x} and ${y}`);
  return x + y;
};
```

const sumAndDifference = (x, y) => ({
sum: x + y, difference: x - y });

// 4. Returning an object



# Features of Arrow Function Syntax



- Parentheses are optional in the case of a single parameter.
- Must use parentheses in case of multiple parameters.
- The return keyword is not required for a single return expression in the function body.
- The return keyword is required in case of multiple statements in the function.
- To return an object notation, wrap it with parentheses.



# Limitation for arrow function



- Arrow functions cannot access the argument object.
- Arrow functions do not have the prototype property
- Arrow functions cannot be used with the new keyword.
- Arrow functions cannot be used as constructors.
- These functions are anonymous, and it is hard to debug the code



# Arrow function vs regular function



#### Syntax:

- Regular Function: Defined using the function keyword followed by a name, parameter list, and function body.
- Arrow function: Defined using a concise syntax with the "=>" arrow operator, omitting the function keyword and using a more compact structure.

#### **Arguments object**

- Regular function: Has access to the arguments object, which contains all the arguments passed to the function.
- Arrow function: Does not have its own arguments object instead it inherits the arguments object from the enclosing scope.

### Binding of "this"

- Regular function: Has its, own "this" value, which is determined by how the function is called. The value of "this" can change dynamically depending on the context of invocation.
- Arrow function: Inherits the "this" value from the enclosing lexical scope. It does not have it's own "this" binding and captures the "this" value of the surrounding context.

#### **Use for new keyword**

- Regular function: can be used as constructor function with the new keyword to create an instance of objects
- Arrow function cannot be used as a constructor function Attention to use new with an arrow function will result in a runtime error.



# THANS