

APPENDIX B3 – WARNING SIGNS AND OBJECT MARKERS DIMENSION DESCRIPTIONS

Table of Contents

Sign Designation	Sign Name	Section- Page Number
Warning Signs and Object Markers		
W1-1	Horizontal Alignment - Turn.....	B3-1
W1-2	Horizontal Alignment - Curve	B3-2
W1-3	Horizontal Alignment - Reverse Turn.....	B3-3
W1-4	Horizontal Alignment - Reverse Curve.....	B3-4
W1-5	Horizontal Alignment - Winding Road.....	B3-5
W1-6	Large Arrow (1-direction).....	B3-6
W1-7	Large Arrow (2-direction).....	B3-7
W1-8	Chevron Alignment.....	B3-8
W1-10	Combination Horizontal Alignment/Intersection.....	B3-9
W1-10a	Combination Horizontal Alignment/Intersection.....	B3-10
W1-10b	Combination Horizontal Alignment/Intersection.....	B3-11
W1-10c	Combination Horizontal Alignment/Intersection.....	B3-12
W1-10d	Combination Horizontal Alignment/Intersection.....	B3-13
W1-10e	Combination Horizontal Alignment/Intersection.....	B3-14
W1-11	Hairpin Curve	B3-15
W1-13	Truck Rollover	B3-16
W1-15	270-degree Curve.....	B3-17
W2-1	Intersection Warning - Crossroad	B3-18
W2-2	Intersection Warning - Side Road	B3-19
W2-3	Intersection Warning - Oblique Side Road (Obtuse)	B3-20
W2-4	Intersection Warning - T-Intersection	B3-22
W2-5	Intersection Warning - Y-Intersection	B3-23
W2-6	Intersection Warning - Circular.....	B3-24
W2-7	Intersection Warning - Offset Side Roads.....	B3-25
W2-8	Intersection Warning - Side Roads.....	B3-26
W3-1	Stop Ahead.....	B3-29
W3-2	Yield Ahead	B3-30
W3-3	Signal Ahead.....	B3-31
W3-4	Be Prepared to Stop	B3-32
W3-5	Reduced Speed Limit Ahead.....	B3-33
W3-5a	XX MPH Speed Zone Ahead.....	B3-34
W3-6	Draw Bridge.....	B3-37
W3-7	Ramp Meter Ahead	B3-38
W3-8	Ramp Metered When Flashing	B3-39
W4-1	Merge.....	B3-41
W4-2	Lane Ends	B3-42
W4-3	Added Lane.....	B3-43
W4-4P	Cross Traffic Does Not Stop (plaque).....	B3-44
W4-4aP	Traffic From Left (Right) Does Not Stop (plaque)	B3-45
W4-4bP	Oncoming Traffic Does Not Stop (plaque).....	B3-46
W4-5	Entering Roadway Merge	B3-47
W4-5aP	No Merge Area (plaque)	B3-48
W4-6	Entering Roadway Added Lane	B3-49
W5-1	Road Narrows	B3-52

W5-2	Narrow Bridge	B3-53
W5-3	One Lane Bridge.....	B3-55
W5-4	Ramp Narrows	B3-57
W5-4a	Path Narrows	B3-58
W6-1	Divided Highway	B3-59
W6-2	Divided Highway Ends.....	B3-60
W6-3	Two-Way Traffic.....	B3-61
W7-1	Hill	B3-64
W7-1a	Hill with Grade	B3-65
W7-2P	Use Low Gear (plaque).....	B3-66
W7-2bP	Trucks Use Lower Gear (plaque).....	B3-67
W7-3P	XX% Grade (plaque)	B3-68
W7-3aP	Next XX Miles (plaque)	B3-69
W7-3bP	XX% Grade XX Miles (plaque)	B3-70
W7-4	Runaway Truck Ramp XX Miles.....	B3-71
W7-4b	Runaway Truck Ramp Entrance Direction with Arrow	B3-72
W7-4c	Truck Escape Ramp	B3-73
W7-4dP	Sand (plaque)	B3-74
W7-4eP	Gravel (plaque)	B3-75
W7-4fP	Paved (plaque)	B3-76
W7-5	Hill (Bicycle)	B3-77
W7-6	Hill Blocks View.....	B3-78
W8-1	Bump.....	B3-79
W8-2	Dip	B3-80
W8-3	Pavement Ends.....	B3-81
W8-4	Soft Shoulder	B3-82
W8-5	Slippery When Wet	B3-83
W8-5P	When Wet (plaque)	B3-84
W8-5aP	Ice (plaque)	B3-85
W8-5bP	Steel Deck (plaque).....	B3-86
W8-5cP	Excess Oil (plaque).....	B3-87
W8-6	Truck Crossing.....	B3-88
W8-7	Loose Gravel.....	B3-89
W8-8	Rough Road	B3-90
W8-9	Low Shoulder.....	B3-91
W8-10	Bicycle Surface Condition	B3-92
W8-10P	Slippery When Wet (plaque).....	B3-93
W8-11	Uneven Lanes	B3-94
W8-12	No Center Line.....	B3-95
W8-13	Bridge Ices Before Road.....	B3-96
W8-14	Fallen Rocks	B3-97
W8-15	Grooved Pavement.....	B3-98
W8-15aP	Motorcycle (plaque).....	B3-99
W8-16	Metal Bridge Deck.....	B3-100
W8-17	Shoulder Drop-Off.....	B3-101
W8-17P	Shoulder Drop-Off (plaque).....	B3-102
W8-18	Road May Flood	B3-103
W8-19	Depth Gauge	B3-104
W8-21	Gusty Winds Area	B3-105
W8-22	Fog Area.....	B3-106
W8-23	No Shoulder	B3-107

W8-25	Shoulder Ends.....	B3-108
W9-1	Right (Left) Lane Ends	B3-111
W9-6	Pay Toll XX Miles Cars (price)	B3-115
W9-6a	Stop Ahead Pay Toll Cars (price).....	B3-116
W9-6bP	Pay Toll XX Miles Cars (price) (plaque).....	B3-117
W9-6cP	Stop Ahead Pay Toll (plaque)	B3-118
W9-7	Right (Left) Lane for Exit Only Ahead.....	B3-124
W10-1	Grade Crossing Advance Warning	B3-125
W10-1aP	Exempt (plaque).....	B3-126
W10-2	Grade Crossing Advance Warning - Crossroad with Grade Crossing	B3-127
W10-3	Grade Crossing Advance Warning - Side Road with Grade Crossing	B3-128
W10-4	Grade Crossing Advance Warning - T-Intersection with Grade Crossing	B3-129
W10-5	Low Ground Clearance.....	B3-130
W10-5P	Low Ground Clearance (plaque).....	B3-131
W10-7	Light Rail Activated Blank-Out	B3-132
W10-8	Trains May Exceed 80 mph	B3-133
W10-9	No Train Horn.....	B3-134
W10-9P	No Train Horn (plaque).....	B3-135
W10-11	Storage Space.....	B3-136
W10-11a	Storage Space Ahead	B3-137
W10-11b	Storage Space Behind	B3-138
W10-12	Skewed Crossing.....	B3-139
W10-13P	No Gates or Lights (plaque).....	B3-140
W10-14aP	Use Next Crossing (plaque)	B3-141
W10-14P	Next Crossing (plaque)	B3-142
W10-15P	Rough Crossing (plaque)	B3-143
W11-1	Bicycle	B3-147
W11-2	Pedestrian.....	B3-148
W11-3	Large Animal - Deer	B3-149
W11-4	Large Animal - Cattle.....	B3-150
W11-5	Farm Vehicle	B3-151
W11-6	Snowmobile	B3-152
W11-7	Equestrian	B3-153
W11-8	Emergency Vehicle	B3-154
W11-9	Handicapped	B3-155
W11-10	Truck.....	B3-156
W11-11	Golf Cart	B3-157
W11-12P	Emergency Signal Ahead (plaque).....	B3-158
W11-14	Horse-Drawn Vehicle.....	B3-159
W11-15	Trail Crossing.....	B3-160
W11-15P	Trail Crossing (plaque)	B3-161
W11-15a	Trail Crossing.....	B3-162
W11-16	Large Animal - Bear.....	B3-163
W11-17	Large Animal - Sheep	B3-164
W11-18	Large Animal - Bighorn Sheep	B3-165
W11-19	Large Animal - Donkey	B3-166
W11-20	Large Animal - Elk	B3-167
W11-21	Large Animal - Moose	B3-168
W11-22	Large Animal - Wild Horse.....	B3-169
W12-1	Double Arrow	B3-170
W12-2	Low Clearance Advance	B3-171

W12-2a	Low Clearance Overhead.....	B3-172
W13-1P	Advisory Speed (plaque)	B3-174
W13-2	Advisory Exit Speed	B3-176
W13-3	Advisory Ramp Speed.....	B3-177
W13-6	Combination Horizontal Alignment/ Advisory Exit Speed - 270-degree Loop.....	B3-178
W13-7	Combination Horizontal Alignment/ Advisory Ramp Speed - 270-degree Loop.....	B3-179
W13-20	Vehicle Speed Feedback	B3-186
W14-1	Dead End	B3-188
W14-1a	Dead End (with arrow)	B3-189
W14-2	No Outlet	B3-190
W14-2a	No Outlet (with arrow)	B3-191
W14-3	No Passing Zone	B3-192
W15-1	Playground.....	B3-193
W16-2P	XX Feet (2-line plaque).....	B3-196
W16-2aP	XX Ft (1-line plaque).....	B3-197
W16-3P	XX Miles (2-line plaque).....	B3-198
W16-3aP	XX Miles (1-line plaque).....	B3-199
W16-4P	Next XX Feet (plaque).....	B3-200
W16-5P	Directional Arrow (plaque).....	B3-201
W16-6P	Advance Turn Arrow (plaque)	B3-202
W16-7P	Downward Diagonal Arrow (plaque).....	B3-203
W16-8P	Advance Street Name (1-line plaque).....	B3-205
W16-8aP	Advance Street Name (2-line plaque).....	B3-206
W16-9P	Ahead (plaque).....	B3-207
W16-10P	Photo Enforced (symbol plaque)	B3-208
W16-10aP	Photo Enforced (plaque)	B3-209
W16-11P	High-Occupancy Vehicles (plaque)	B3-210
W16-12P	Traffic Circle (plaque)	B3-211
W16-12aP	Roundabout (plaque).....	B3-212
W16-13P	When Flashing (plaque).....	B3-213
W16-15P	New (plaque).....	B3-214
W16-16P	Last Exit Before Toll (1-line plaque)	B3-215
W16-17P	Toll (plaque).....	B3-217
W16-18P	NOTICE (plaque)	B3-218
W17-1	Speed Hump.....	B3-222
W18-1	No Traffic Signs.....	B3-223
W19-1	Freeway Ends XX Miles	B3-224
W19-2	Expressway Ends XX Miles	B3-225
W19-3	Freeway Ends	B3-226
W19-4	Expressway Ends	B3-227
W19-5	All Traffic Must Exit.....	B3-228
W23-2	New Traffic Pattern Ahead.....	B3-229
W25-1	Oncoming Traffic Has Extended Green.....	B3-231
W25-2	Oncoming Traffic May Have Extended Green	B3-232
OM1-1	Object Marker Type 1	B3-234
OM1-2	Object Marker Type 1	B3-235
OM1-3	Object Marker Type 1	B3-236
OM2-1V	Object Marker Type 2	B3-237
OM2-1H	Object Marker Type 2	B3-238
OM2-2V	Object Marker Type 2	B3-239
OM2-2H	Object Marker Type 2	B3-240

OM3-R	Object Marker Type 3	B3-241
OM3-C	Object Marker Type 3	B3-242
OM3-L	Object Marker Type 3	B3-243
OM4-1	Object Marker Type 4	B3-244
OM4-2	Object Marker Type 4	B3-245
OM4-3	Object Marker Type 4	B3-246

W1-1: Horizontal Alignment

W1-1R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the right edge of the vertical section of the arrow shaft.
- F is the width of the arrow shaft.
- G is the distance from the horizontal center of the sign to the base of the arrow shaft.
- H is the distance from the horizontal center of the sign to the top of the of the horizontal section of the arrow shaft.
- J is the radius of the outer bend in the arrow shaft.
- K is the radius of the inner bend in the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the of the horizontal section of the arrow shaft.
- M is the distance from the horizontal center of the sign to the tip of the arrowhead.
- N is the width of the arrowhead.
- P is the corner radius.

W1-1L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the left edge of the vertical section of the arrow shaft.
- F is the width of the arrow shaft.
- G is the distance from the horizontal center of the sign to the base of the arrow shaft.
- H is the distance from the horizontal center of the sign to the top of the of the horizontal section of the arrow shaft.
- J is the radius of the outer edge of the bend in the arrow shaft.
- K is the radius of the inner edge of the bend in the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the of the horizontal section of the arrow shaft.
- M is the distance from the horizontal center of the sign to the tip of the arrowhead.
- N is the width of the arrowhead.
- P is the corner radius.

W1-2: Horizontal Alignment – Curve

W1-2R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the arrow tip.
- E is the distance from the vertical center of the sign to the arrow tip.
- F is the width of the arrow shaft.
- G is the radius of the centerline of the curve in the arrow.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow.
- K is the distance from the vertical center of the sign to the centerline of the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the arrow symbol.
- M is the width of the arrowhead.
- N is the corner radius.

W1-2L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the arrow tip.
- E is the distance from the vertical center of the sign to the arrow tip.
- F is the width of the arrow shaft.
- G is the radius of the centerline of the curve in the arrow.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow.
- K is the distance from the vertical center of the sign to the centerline of the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the arrow symbol.
- M is the width of the arrowhead.
- N is the corner radius.

W1-3: Horizontal Alignment – Reverse Turn

W1-3R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the distance from the vertical center of the sign to the left edge of the upper vertical portion of the arrow shaft.
- H is the radius of the inner edge of the curves in the arrow shaft.
- J is the radius of the outer edge of the curves in the arrow shaft.
- K is the distance from the vertical center of the sign to the right edge of the lower vertical portion of the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the arrow symbol.
- M is the distance from the horizontal center of the sign to the top of the upper horizontal edge of the arrow shaft.
- N is the width of the arrowhead.
- P is the corner radius.

W1-3L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the distance from the vertical center of the sign to the right edge of the upper vertical portion of the arrow shaft.
- H is the radius of the inner edge of the curves in the arrow shaft.
- J is the radius of the outer edge of the curves in the arrow shaft.
- K is the distance from the vertical center of the sign to the left edge of the lower vertical portion of the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the arrow symbol.
- M is the distance from the horizontal center of the sign to the top of the upper horizontal edge of the arrow shaft.
- N is the width of the arrowhead.
- P is the corner radius.

W1-4: Horizontal Alignment – Reverse Curve

W1-4R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the arrow tip.
- E is the distance from the vertical center of the sign to the arrow tip.
- F is the distance from the vertical center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the first curve in the arrow shaft.
- K is the length of the first straight section in the arrow shaft.
- L is the distance from the vertical center of the sign to the vertex of the angle of the first curve in the arrow shaft.
- M is the radius of each curve in the centerline of the arrow shaft.
- N is the width of the arrowhead.
- P is the corner radius.

W1-4L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the arrow tip.
- E is the distance from the vertical center of the sign to the arrow tip.
- F is the distance from the vertical center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the first curve in the arrow shaft.
- K is the length of the first straight section in the arrow shaft.
- L is the distance from the vertical center of the sign to the vertex of the angle of the first curve in the arrow shaft.
- M is the radius of each curve in the centerline of the arrow shaft.
- N is the width of the arrowhead.
- P is the corner radius.

W1-5: Horizontal Alignment – Winding Road

W1-5R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the tip of the arrowhead.
- E is the distance from the tip of the arrowhead to the center of the last curve.
- F is the distance from the vertical center of the sign to the vertex of the angle of the fourth curve.
- G is the radius of each curve in the centerline of the arrow shaft.
- H is the distance from the vertex of the angle of the third curve to the vertex of the angle of the fourth curve.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the third curve.
- K is the distance from the vertical center of the sign to vertex of the angle of the third curve.
- L is the length of the diagonal straight section between the second and third curves.
- M is the distance from the horizontal center of the sign to the vertex of the angle of the second curve.
- N is the distance from the vertical center of the sign to the vertex of the angle of the second curve.
- P is the distance from the center radius of the second curve to the vertex of the angle of the first curve.
- Q is the length of the first vertical straight section of the arrow shaft.
- R is the width of the arrow shaft.
- S is the width of the arrowhead.
- T is the corner radius.

W1-5L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the tip of the arrowhead.
- E is the distance from the tip of the arrowhead to the center of the last curve.
- F is the distance from the vertical center of the sign to the center of the last curve.
- G is the radius of each curve in the centerline of the arrow shaft.
- H is the distance from the vertex of the angle of the third curve to the top of the fourth curve.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the third curve.
- K is the distance from the vertical center of the sign to vertex of the angle of the third curve.
- L is the length of the diagonal straight section between the second and third curves.

- M is the distance from the horizontal center of the sign to the vertex of the angle of the second curve.
- N is the distance from the vertical center of the sign to the vertex of the angle of the second curve.
- P is the distance from the center radius of the second curve to the vertex of the angle of the first curve.
- Q is the length of the first vertical straight section of the arrow shaft.
- R is the width of the arrow shaft.
- S is the width of the arrowhead.
- T is the corner radius.

W1-6: Large Arrow (1-direction)

W1-6R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the tip of the arrowhead to the top and bottom of the sign.
- F is the distance from the vertical center of the sign to the left and right edges of the arrow symbol.
- G is the arrowhead width.
- H is the corner radius.

W1-6L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the tip of the arrowhead to the top and bottom of the sign.
- F is the distance from the vertical center of the sign to the left and right edges of the arrow symbol.
- G is the arrowhead width.
- H is the corner radius.

W1-7: Large Arrow (2-direction)

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the tips of each arrowhead to the top and bottom of the sign.
- F is the distance from the vertical center of the sign to the tips of the arrowheads.
- G is the width of each arrowhead.
- H is the corner radius.

W1-8: Chevron Alignment

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the distance from each edge of the chevron symbol to the adjacent edge of the sign.
- D is the distance from the horizontal center of the sign to the top and bottom of the chevron symbol.
- E is the distance from the vertical center of the sign to the left and right edges of the chevron symbol and the width of the black lines forming the chevron.
- F is the corner radius.

W1-10: Combination Horizontal Alignment/Intersection

W1-10R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow shaft.
- K is the distance from the vertical center of the sign to the centerline of the first straight section of the arrow shaft.
- L is the distance from the horizontal center of the arrow to the bottom of the arrow shaft.
- M is the width of the arrowhead.
- N is the distance from the absolute center of the sign to the centerline of the 45-degree line at the horizontal center of the sign.
- P is the distance from the horizontal center of the sign to the upper end of the 45-degree line.
- Q is the width of the 45-degree line.
- R is the corner radius.

W1-10L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow shaft.
- K is the distance from the vertical center of the sign to the centerline of the first straight section of the arrow shaft.
- L is the distance from the horizontal center of the arrow to the bottom of the arrow shaft.
- M is the width of the arrowhead.
- N is the distance from the center of the sign to the centerline of the 45-degree line at the horizontal center of the sign.

- P is the distance from the horizontal center of the sign to the upper end of the 45-degree line.
- Q is the width of the 45-degree line.
- R is the corner radius.

W1-10a: Combination Horizontal Alignment/Intersection

W1-10aR

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow.
- K is the distance from the horizontal center of the arrow to the centerline of the first straight section of the arrow shaft.
- L is the distance from the vertical center of the sign to the right edge of the horizontal line.
- M is the distance from the centerline of the first straight section of the arrow shaft to the left edge of the horizontal line.
- N is the distance from the horizontal center of the sign to the bottom of the arrow shaft.
- P is the distance from the horizontal center of the sign to the top of the horizontal line.
- Q the width of the horizontal line.
- R is the distance from the bottom of the horizontal line to the bottom of the arrow shaft.
- S is the width of the arrowhead.
- T is the corner radius.

W1-10aL

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow.
- K is the distance from the horizontal center of the arrow to the centerline of the first straight section of the arrow shaft.
- L is the distance from the vertical center of the sign to the left edge of the horizontal line.
- M is the distance from the centerline of the first straight section of the arrow shaft to the right edge of the horizontal line.

- N is the distance from the horizontal center of the sign to the bottom of the arrow shaft.
- P is the distance from the horizontal center of the sign to the top of the horizontal line.
- Q the width of the horizontal line.
- R is the distance from the bottom of the horizontal line to the bottom of the arrow shaft.
- S is the width of the arrowhead.
- T is the corner radius.

W1-10b: Combination Horizontal Alignment/Intersection

W1-10bR

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow.
- K is the distance from the vertical center of the sign to the centerline of the first straight section of the arrow.
- L is the distance from the horizontal center of the sign to the bottom of the arrow.
- M is the distance from the horizontal center of the sign to the top of the vertical line that merges with the arrow.
- N is the width of the line vertical line that merges with the arrow.
- P is the width of the arrowhead.
- Q is the corner radius.

W1-10bL

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow.
- K is the distance from the vertical center of the sign to the centerline of the first straight section of the arrow.
- L is the distance from the horizontal center of the sign to the bottom of the arrow.
- M is the distance from the horizontal center of the sign to the top of the vertical line that merges with the arrow.
- N is the width of the line vertical line that merges with the arrow.
- P is the width of the arrowhead.
- Q is the corner radius.

W1-10c: Combination Horizontal Alignment/Intersection

W1-10cR

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow shaft.
- K is the distance from the vertical center of the sign to the centerline of the vertical straight section of the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the arrow shaft.
- M is the distance from the vertical center of the sign to the top left corner of the diagonal line that merges with the arrow.
- N is the distance from the horizontal center of the sign to the top left corner of the diagonal line that merges with the arrow.
- P is the width of the diagonal line that merges with the arrow.
- Q is the width of the arrowhead.
- R is the corner radius.

W1-10cL

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the width of the arrow shaft.
- G is the radius of the curve in the centerline of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- J is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow shaft.
- K is the distance from the vertical center of the sign to the centerline of the first straight section of the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the arrow shaft.
- M is the distance from the vertical center of the sign to the top right corner of the diagonal line that merges with the arrow.
- N is the distance from the horizontal center of the sign to the top right corner of the diagonal line that merges with the arrow.

- P is the width of the diagonal line that merges with the arrow.
- Q is the width of the arrowhead.
- R is the corner radius.

W1-10d: Combination Horizontal Alignment/Intersection

W1-10dR

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the arrow tip.
- E is the distance from the vertical center of the sign to the arrow tip.
- F is the distance from the vertical center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- K is the length of the first straight section in the arrow shaft.
- L is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow shaft.
- M is the radius of each curve in the centerline of the arrow shaft.
- N is the width of the arrowhead.
- P is the distance from the horizontal center of the sign to the top end of the diagonal straight line measured at its centerline.
- Q is the distance from the vertical center of the sign to the top end of the diagonal straight line measured at its centerline.
- R is the width of the straight line.
- S is the corner radius.

W1-10dL

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the arrow tip.
- E is the distance from the vertical center of the sign to the arrow tip.
- F is the distance from the vertical center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the arrow shaft.
- K is the length of the first straight section in the arrow shaft.
- L is the distance from the vertical center of the sign to the vertex of the angle of the curve in the arrow shaft.
- M is the radius of each curve in the centerline of the arrow shaft.

- N is the width of the arrowhead.
- P is the distance from the horizontal center of the sign to the top end of the diagonal straight line measured at its centerline.
- Q is the distance from the vertical center of the sign to the top end of the diagonal straight line measured at its centerline.
- R is the width of the straight line.
- S is the corner radius.

W1-10e: Combination Horizontal Alignment/Intersection

W1-10eR

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the distance from the vertical center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the first curve in the arrow shaft.
- K is the length of the first vertical straight section of the arrow shaft.
- L is the distance from the vertical center of the sign to the vertex of the angle of the first curve in the arrow shaft.
- M is the radius of each curve in the centerline of the arrow shaft.
- N is the width of the arrowhead.
- P is the distance from the horizontal center of the sign to the top end of the diagonal straight line measured at its centerline.
- Q is the distance from the vertical center of the sign to the top end of the diagonal straight line measured at its centerline.
- R is the width of the diagonal straight line.
- S is the distance from the horizontal center of the sign to the bottom end of the diagonal straight line measured at its centerline.
- T is the distance from the vertical center of the sign to the bottom end of the diagonal straight line measured at its centerline.
- U is the corner radius.

W1-10eL

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the vertical center of the sign to the tip of the arrowhead.
- F is the distance from the vertical center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the vertex of the angle of the second curve in the arrow shaft.
- J is the distance from the horizontal center of the sign to the vertex of the angle of the first curve in the arrow shaft.

- K is the length of the first vertical straight section of the arrow shaft.
- L is the distance from the vertical center of the sign to the vertex of the angle of the first curve in the arrow shaft.
- M is the radius of each curve in the centerline of the arrow shaft.
- N is the width of the arrowhead.
- P is the distance from the horizontal center of the sign to the top end of the diagonal straight line measured at its centerline.
- Q is the distance from the vertical center of the sign to the top end of the diagonal straight line measured at its centerline.
- R is the width of the diagonal straight line.
- S is the distance from the horizontal center of the sign to the bottom end of the diagonal straight line measured at its centerline.
- T is the distance from the vertical center of the sign to the bottom end of the diagonal straight line measured at its centerline.
- U is the corner radius.

W1-11: Hairpin Curve

W1-IIR

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the is the outer radius of the curve in the arrow shaft, measured from the absolute center of the sign.
- E is the distance from the vertical center of the sign to the centerline of the vertical arrow shaft and to the arrowhead tip, the radius of the curve in the centerline of the arrow shaft, and the distance from the horizontal center of the sign to the bottom of the arrow symbol.
- F is the inner radius of the curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the base of the arrowhead.
- J is the width of the arrowhead.
- K is the corner radius.

W1-IIL

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the is the outer radius of the curve in the arrow shaft, measured from the absolute center of the sign.
- E is the distance from the vertical center of the sign to the centerline of the vertical arrow shaft and to the arrowhead tip, the radius of the curve in the arrow shaft at its centerline, and the distance from the horizontal center of the sign to the bottom of the arrow symbol.
- F is the inner radius of the curve in the arrow shaft.
- G is the width of the arrow shaft.
- H is the distance from the horizontal center of the sign to the base of the arrowhead.
- J is the width of the arrowhead.
- K is the corner radius.

W1-13: Truck Rollover

W1-13R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the radius of the outer edge of the arrow shaft.
- E is the radius of the centerline of the arrow shaft.
- F is the radius of the inner edge of the arrow shaft.
- G is the width of the arrow shaft.
- H is the length of straight arrow shaft from the end of the curve to the base of the arrowhead.
- J is the distance from the vertical center of the sign to the center of the curve in the arrow shaft.
- K is the distance from the horizontal center of the sign to the beginning of the curve in the arrow shaft, which is aligned with the center of the curve in the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the vertical section of the arrow shaft.
- M is distance from the top of the road surface line to the roof of the cargo box of the truck measured along the tilted left edge of the cargo box.
- N is the distance from the horizontal center of the sign to the bottom of the truck symbol.
- P is the distance from the horizontal center of the sign to the centerline of the horizontal road surface line.
- Q is the width of the horizontal road surface line.
- R is the distance from the vertical center of the sign to the left and right edges of the horizontal road surface line.
- S is the arrowhead width
- T is the corner radius.

W1-13L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the radius of the outer edge of the arrow shaft.
- E is the radius of the centerline of the arrow shaft.
- F is the radius of the inner edge of the arrow shaft.
- G is the width of the arrow shaft.
- H is the length of straight arrow shaft from the end of the curve to the base of the arrowhead.
- J is the distance from the vertical center of the sign to the center of the curve in the arrow shaft.
- K is the distance from the horizontal center of the sign to the beginning of the curve in the arrow shaft, which is aligned with the center of the curve in the arrow shaft.
- L is the distance from the horizontal center of the sign to the bottom of the vertical section of the arrow shaft.
- M is distance from the top of the road surface line to the roof of the cargo box of the truck measured along the tilted right edge of the cargo box.
- N is the distance from the horizontal center of the sign to the bottom of the truck symbol.
- P is the distance from the horizontal center of the sign to the centerline of the horizontal road surface line.
- Q is the width of the horizontal road surface line.

- R is the distance from the vertical center of the sign to the left and right edges of the horizontal road surface line.
- S is the arrowhead width
- T is the corner radius.

W1-15: 270-degree Curve

W1-15R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the center of the first section of the spiral curve.
- E is the radius of the first section of the spiral curve, measured along the arrow shaft centerline, from the top of the vertical section of the arrow shaft through an angle of 165 degrees clockwise.
- F is the horizontal distance from the center of the first section of the spiral curve to the end of the spiral curve in the arrow shaft.
- G is the distance from the horizontal center of the sign to the center of the second section of the spiral curve in the arrow shaft.
- H is the radius of the second section of the spiral curve, measured along the arrow shaft centerline, from the end of the first section of the spiral curve of the arrow shaft through an angle of 105 degrees clockwise and ending horizontal.
- J is the distance from the horizontal center of the sign to the centerline of the arrow shaft at the end of the spiral curve.
- K is the distance from the vertical center of the sign to the tip of the arrowhead.
- L is the width of the arrowhead.
- M is the length of the horizontal section of the arrow shaft from the end of the spiral curve to the base of the arrowhead.
- N is the length of the vertical section of the arrow shaft.
- P is the width of the arrow shaft.
- Q is the corner radius.

W1-15L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the center of the first section of the spiral curve.
- E is the radius of the first section of the spiral curve, measured along the arrow shaft centerline, from the top of the vertical section of the arrow shaft through an angle of 165 degrees counterclockwise.
- F is the horizontal distance from the center of the first section of the spiral curve to the end of the spiral curve in the arrow shaft.
- G is the distance from the horizontal center of the sign to the center of the second section of the spiral curve in the arrow shaft.
- H is the radius of the second section of the spiral curve, measured along the arrow shaft centerline, from the end of the first section of the spiral curve of the arrow shaft through an angle of 105 degrees counterclockwise and ending at horizontal.
- J is the distance from the horizontal center of the sign to the centerline of the arrow shaft at the end of the spiral curve.
- K is the distance from the vertical center of the sign to the tip of the arrowhead.
- L is the width of the arrowhead.

- M is the length of the horizontal section of the arrow shaft from the end of the spiral curve to the base of the arrowhead.
- N is the length of the vertical section of the arrow shaft.
- P is the width of the arrow shaft.
- Q is the corner radius.

W2-1: Intersection Warning – Crossroad

- A is the length of each edge of the sign
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the left and right edges of the vertical black line and from the horizontal center of the sign to the top and bottom edges of the horizontal black line.
- E is the distance from the center of the sign to the end of each black line.
- F is the corner radius.

W2-2: Intersection Warning – Side Road

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the centerline of the vertical line to its left and right edges and the distance from the horizontal center of the sign to the top and bottom of the horizontal line. The right edge of the vertical line is aligned with the vertical center of the sign.
- E is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- F is the distance from the vertical center of the sign to the right edge of the symbol.
- G is the corner radius.

W2-3: Intersection Warning – Oblique Side Road (Obtuse)

W2-3R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the top end of the diagonal line at its centerline.
- E is the distance from horizontal center of the sign to the top and bottom edges of the vertical line.
- F is the distance from the vertical center of the sign to the left edge of the vertical line.
- G is the distance from the vertical center of the sign to the right edge of the vertical line.
- H is the distance from the centerline of the diagonal line to the left and right edges of the diagonal line.
- J is the distance from the horizontal center of the sign to the top end of the diagonal line at its centerline.
- K is the distance from the horizontal center of the sign to the intersection of the diagonal line's centerline with the vertical center of the sign.
- L is the corner radius.

W2-3L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the top end of the diagonal line at its centerline.
- E is the distance from horizontal center of the sign to the top and bottom edges of the vertical line.
- F is the distance from the vertical center of the sign to the right edge of the vertical line.
- G is the distance from the vertical center of the sign to the left edge of the vertical line.
- H is the distance from the centerline of the diagonal line to the left and right edges of the diagonal line.
- J is the distance from the horizontal center of the sign to the top end of the diagonal line at its centerline.
- K is the distance from the horizontal center of the sign to the intersection of the diagonal line's centerline with the vertical center of the sign.
- L is the corner radius.

W2-3a: Intersection Warning - Oblique Side Road Acute

W2-3aR

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the horizontal distance from the vertical center of the sign to the centerline of the branch at its base in the lower-right quadrant of the sign.
- E is the distance from the horizontal center of the sign to the top and bottom ends of the vertical line.
- F is the distance from the vertical center of the sign to the left edge of the vertical line.
- G is the distance from the vertical center of the sign to the right edge of the vertical line.
- H is the distance from the centerline of the branch to the left and right edges of the branch.
- J is the distance from the horizontal center of the sign to the centerline of the branch at its base.
- K is the distance from the horizontal center of the sign to the intersection of the branch's centerline with the vertical center of the sign.
- L is the corner radius.

W2-3aL

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the horizontal distance from the vertical center of the sign to the centerline of the branch at its base in the lower-left quadrant of the sign.
- E is the distance from the horizontal center of the sign to the top and bottom ends of the vertical line.
- F is the distance from the vertical center of the sign to the right edge of the vertical line.
- G is the distance from the vertical center of the sign to the left edge of the vertical line.
- H is the distance from the centerline of the branch to the left and right edges of the branch.
- J is the distance from the horizontal center of the sign to the centerline of the branch at its base.
- K is the distance from the horizontal center of the sign to the intersection of the branch's centerline with the vertical center of the sign.
- L is the corner radius.

W2-4: Intersection Warning – T-Intersection

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the centerline of the horizontal black line of the “T” to the top and bottom edges of the line and the distance from the vertical center of the sign to the left and right edges of the vertical black line of the “T.”
- E is the distance from the vertical center of the sign to the left and right edges of the symbol.
- F is the distance from the horizontal center of the sign to the top of the symbol.
- G is the distance from the horizontal center of the sign to the bottom of the symbol.
- H is the corner radius.

W2-5: Intersection Warning – Y-Intersection

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the top of the centerline of the left upper branch of the Y-shaped symbol.
- E is the distance from the vertical center of the sign to the top of the centerline of the right upper branch of the Y-shaped symbol.
- F is the distance from the horizontal center of the sign to the top of the centerline of the upper branches of the Y-shaped symbol.
- G is the distance from the horizontal center of the sign to the intersection of the centerlines of the branches of the Y-shaped symbol.
- H is the distance from the intersection of the centerlines of the branches of the Y-shaped symbol to the bottom of the symbol.
- J is the distance from the centerline of each branch to the left and right edges of each branch of the Y-shaped symbol.
- K is the corner radius.

W2-6: Intersection Warning - Circular

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the top of the symbol to the top of the sign.
- E is the distance from the horizontal center of the sign to the top of the symbol.
- F is the distance from the horizontal center of the sign to the bottom of the symbol.
- G is the distance from the bottom of the symbol to the bottom of the sign.
- H is the distance from the left edge of the symbol to the left edge of the sign.
- J is the distance from the vertical center of the sign to the left edge of the symbol.
- K is the distance from the vertical center of the sign to the right edge of the symbol.
- L is the distance from the right edge of the symbol to the right edge of the sign.
- M is the distance from the horizontal center of the sign to the horizontal center of the symbol.
- N is the distance from the vertical center of the sign to the vertical center of the symbol.
- P is the corner radius.

W2-7: Intersection Warning – Offset Side Roads

W2-7R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the centerline of each line to its parallel edges.
- E is the distance from the horizontal center of the sign to the top of the vertical line.
- F is the distance from the horizontal center of the sign to the bottom of the vertical line.
- G is the distance from the vertical center of the sign to the left end of the upper horizontal line.
- H is the distance from the vertical center of the sign to the right end of the lower horizontal line.
- J is the distance from the horizontal center of the sign to the bottom of the upper horizontal line.
- K is the distance from the horizontal center of the sign to the top of the lower horizontal line.
- L is the corner radius.

W2-7L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the centerline of each line to its parallel edges.
- E is the distance from the horizontal center of the sign to the top of the vertical line.
- F is the distance from the horizontal center of the sign to the bottom of the vertical line.
- G is the distance from the vertical center of the sign to the right end of the upper horizontal line.
- H is the distance from the vertical center of the sign to the left end of the lower horizontal line.
- J is the distance from the horizontal center of the sign to the bottom of the upper horizontal line.
- K is the distance from the horizontal center of the sign to the top of the lower horizontal line.
- L is the corner radius.

W2-8: Intersection Warning – Side Roads

W2-8R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the top portion of the vertical line.
- E is the width of each horizontal line.
- F is the distance from the horizontal center of the sign to the bottom of the upper horizontal line.
- G is the distance from the horizontal center of the sign to the top of the lower horizontal line.
- H is the distance from the vertical center of the sign to the left edge of the vertical line.
- J is the distance from the vertical center of the sign to the right edge of the vertical line.
- K is the distance from the vertical center of the sign to the end of each horizontal line.
- L is the corner radius.

W2-8L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the top portion of the vertical line.
- E is the width of each horizontal line.
- F is the distance from the horizontal center of the sign to the bottom of the upper horizontal line.
- G is the distance from the horizontal center of the sign to the top of the lower horizontal line.
- H is the distance from the vertical center of the sign to the right edge of the vertical line.
- J is the distance from the vertical center of the sign to the left edge of the vertical line.
- K is the distance from the vertical center of the sign to the end of each horizontal line.
- L is the corner radius.

W2-10: Traffic Entering When Flashing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the first and second lines and between the third and fourth lines.
- F is the distance from the horizontal center of the sign to the bottom of the second line.
- G is the distance from the horizontal center of the sign to the top of the third line.
- H is the distance from the vertical center of the sign to the left edge of the first line.
- J is the distance from the vertical center of the sign to the right edge of the first line.
- K is the distance from the vertical center of the sign to the left edge of the second line.
- L is the distance from the vertical center of the sign to the right edge of the second line.
- M is the distance from the vertical center of the sign to the left edge of the word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the third line.
- P is the distance from the vertical center of the sign to the left edge of the fourth line.
- Q is the distance from the vertical center of the sign to the right edge of the fourth line.
- R is the corner radius.

W2-11: Traffic Approaching When Flashing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first, third, and fourth lines.
- E is the space between the first and second lines and between the third and fourth lines.
- F is the letter height and FHWA standard font for the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the horizontal center of the sign to the top of the third line.
- J is the distance from the vertical center of the sign to the left edge of the first line.
- K is the distance from the vertical center of the sign to the right edge of the first line.
- L is the distance from the vertical center of the sign to the left edge of the second line.
- M is the distance from the vertical center of the sign to the right edge of the second line.
- N is the distance from the vertical center of the sign to the left edge of the third line.
- P is the distance from the vertical center of the sign to the right edge of the third line.
- Q is the distance from the vertical center of the sign to the left edge of the fourth line.
- R is the distance from the vertical center of the sign to the right edge of the fourth line.
- S is the corner radius.

W3-1: Stop Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the arrow symbol.
- E is the distance from the bottom of the arrow symbol to the top of the octagon.
- F is the distance from the horizontal center of the sign to the top of the octagon.
- G is the distance from the horizontal center of the sign to the bottom of the octagon.
- H is the border width of the octagon.
- J is the distance from the vertical center of the sign to the left edge of the octagon.
- K is the distance from the vertical center of the sign to the right edge of the octagon.
- L is the distance from the vertical center of the sign to the bottom left vertex of the octagon.
- M is the distance from the vertical center of the sign to the bottom right vertex of the octagon.
- N is the sign corner radius.

W3-2: Yield Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the arrow symbol.
- E is the distance from the bottom of the arrow symbol to the top of the triangle.
- F is the distance from the vertical center of the sign to the top left and right corners of the red triangle ignoring the corner radius.
- G is the red triangle border width.
- H is the distance from the horizontal center of the sign to the top of the red triangle.
- J is the distance from the horizontal center of the sign to the top of the white triangle.
- K is the corner radius of the white triangle.
- L is the corner radius of the red triangle.
- M is the length of each edge of the red triangle ignoring the corner radius.
- N is the sign corner radius.

W3-3: Signal Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D the distance from the vertical center of the sign to the left and right edges of the symbol, the distance from the top of the symbol to the center of the red circle, and the distance from the center of the green circle to the bottom of the symbol.
- E is the distance from the horizontal center of the sign to the centers of the red circle and the green circle. The center of the yellow circle is aligned with the center of the sign.
- F is the radius of each circle on the symbol.
- G is the corner radius.

W3-4: Be Prepared to Stop

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- L is the width of the first word on the third line.
- M is the space between the words on the third line.
- N is the distance from the vertical center of the sign to the left edge of the second word on the third line.
- P is the distance from the vertical center of the sign to the right edge of the second word on the third line.
- Q is the corner radius.

W3-5: Reduce Speed Limit Ahead

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the arrowhead.
- E is the distance from the barbs of the arrowhead to the bottom of the arrow symbol.
- F is the distance from the bottom of the arrow symbol to the top of the white panel.
- G is the distance from the top of the first line on the white panel to the top of the panel and from the bottom of the last line on the white panel to the bottom of the panel.
- H is the letter height and FHWA standard font for the first and second lines.
- J is the space between the first, second, and third lines. The bottom of the second line is aligned with the horizontal center of the sign.
- K is the letter height and FHWA standard font for the third line.
- L is the inset from the edge of the white panel to the panel's border.
- M is the border width of the white panel.
- N is the corner radius of the white panel.
- P is the distance from the vertical center of the sign to the left edge of the word on the first line.
- Q is the distance from the vertical center of the sign to the right edge of the word on the first line.
- R is the distance from the vertical center of the sign to the left edge of the word on the second line.
- S is the distance from the vertical center of the sign to the right edge of the word on the second line.
- T is the distance from the vertical center of the sign to the left and right edges of word on the third line.
- U is the distance from the vertical center of the sign to the left and right edges of the white panel.
- V is the sign corner radius.

W3-5a: XX MPH Speed Zone Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top and bottom of the second line.
- G is the width of the first word on the first line.
- H is the space between the words on the first line.
- J is the width of the second word on the first line.
- K is width of the first word on the second line. The right edge of the word is aligned with the vertical center of the sign.
- L is the space between the words on the second line.
- M is the width of the second word on the second line.
- N is the distance from the vertical center of the sign to the left edge of the word on the third line.
- P is the distance from the vertical center of the sign to the right edge of the word on the third line.
- Q is the corner radius.

W3-5b: Variable Speed Zone Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the letter height and FHWA standard font for the second and third lines.
- J is the distance from the vertical center of the sign to the left edge of the word on the first line.
- K is the distance from the vertical center of the sign to the right edge of the word on the first line.
- L is the width of the first word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- N is the width of the second word on the second line.
- P is the distance from the vertical center of the sign to the left edge of the word on the third line.
- Q is the distance from the vertical center of the sign to the right edge of the word on the third line.
- R is the corner radius.

W3-5c: XX MPH Speed Zone Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first, third, and fourth lines.
- E is the space between the first and second lines and between the third and fourth lines, the space between the words on the first line, and the distance from the vertical center of the sign to the left edge of the second word on the third line.
- F is the letter height and FHWA standard font for the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the horizontal center of the sign to the top of the third line.
- J is the width of the first word on the first line.
- K is the width of the second word on the first line.
- L is the distance from the vertical center of the sign to the left edge of the word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the word on the second line.
- N is the width of the first word on the third line.
- P is the width of the second word on the third line.
- Q is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- R is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- S is the corner radius.

W3-6: Draw Bridge

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first word.
- F is the distance from the horizontal center of the sign to the top of the second word.
- G is the distance from the vertical center of the sign to the left edge of the first word.
- H is the distance from the vertical center of the sign to the right edge of the first word.
- J is the distance from the vertical center of the sign to the left edge of the second word.
- K is the distance from the vertical center of the sign to the right edge of the second word.
- L is the corner radius.

W3-7: Ramp Meter Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top and bottom of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- K is the distance from the vertical center of the sign to the left edge of the word on the third line.
- L is the distance from the vertical center of the sign to the right edge of the word on the third line.
- M is the corner radius.

W3-8: Ramp Metered When Flashing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first, second, and third lines. The top of the third line is aligned with the horizontal center of the sign.
- E is the space between lines.
- F is the letter height and FHWA standard font for the fourth line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- K is the distance from the vertical center of the sign to the left edge of the word on the third line.
- L is the distance from the vertical center of the sign to the right edge of the word on the third line.
- M is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- N is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- P is the corner radius.

W3-9: Traffic Using Shoulder

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first and second lines.
- G is the space between the first, second, and third lines.
- H is the letter height and FHWA standard font for the third line.
- J is the space between the third and fourth lines.
- K is the letter height and FHWA standard font for the fourth and fifth lines.
- L is the space between the fourth and fifth lines.
- M is the distance from the bottom of the last line to the bottom of the sign.
- N is the distance from the vertical center of the sign to the left edge of the word on the first line.
- P is the distance from the vertical center of the sign to the right edge of the word on the first line.
- Q is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- R is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- S is the distance from the vertical center of the sign to the left and right edges of the fourth line.
- T is the width of the words on the fourth line.
- U is the width of each hyphen and the space between the words and the hyphens on the fourth and fifth lines.
- V is the distance from the vertical center of the sign to the left and right edges of the fifth line.
- W is the width of the words on the fifth line.
- X is the corner radius.

W4-1: Merge

W4-1R

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the horizontal center of the sign to the base of the arrow shaft.
- F is the width of the arrow shaft.
- G is the shaft width of the curved branch.
- H is the radius of the first section of the branch.
- J is the radius of the second section of the branch.
- K is the distance from the vertical center of the sign to the vertex of the curve angle of the second section of the branch.
- L is the distance from the vertical center of the sign to the vertex of the curve angle of the first section of the branch.
- M is the distance from the horizontal center of the sign to the vertex of the curve angle of the second section of the branch.
- N is the distance from the horizontal center of the sign to the vertex of the curve angle of the second section of the branch.
- P is the width of the base of the arrowhead.
- Q is the corner radius.

W4-1L

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the arrowhead.
- E is the distance from the horizontal center of the sign to the base of the arrow shaft.
- F is the width of the arrow shaft.
- G is the shaft width of the curved branch.
- H is the radius of the first section of the branch.
- J is the radius of the second section of the branch.
- K is the distance from the vertical center of the sign to the vertex of the curve angle of the second section of the branch.
- L is the distance from the vertical center of the sign to the vertex of the curve angle of the first section of the branch.
- M is the distance from the horizontal center of the sign to the vertex of the curve angle of the second section of the branch.
- N is the distance from the horizontal center of the sign to the vertex of the curve angle of the second section of the branch.
- P is the width of the base of the arrowhead.
- Q is the corner radius.

W4-2: Lane Ends

W4-2R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the length of the right edge of the upper vertical portion of the bent line.
- E is the vertical distance from the left vertex to the right vertex of each bend in the line on the right side of the sign. The left vertex of the lower bend is aligned with the horizontal center of the sign.
- F is the vertical distance from the left vertex of the upper bend to the right vertex of the lower bend in the line on the right side of the sign.
- G is the distance from the horizontal center of the sign to the top and bottom of the vertical line in the left side of the sign and to the bottom of the bent line in the right side of the sign.
- H is the length of the each segment in the vertical dashed line.
- J is the space between the segments.
- K is the width of the left vertical line and the right bent line.
- L is the space between the dashed line and the lower vertical section of the bent line.
- M is the width of the dashed line.
- N is the distance from the vertical center of the sign to the left edge of the dashed line.
- P is the distance from the vertical center of the sign to the right edge of the straight vertical line.
- Q is the corner radius.

W4-2L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the length of the left edge of the upper vertical portion of the bent line.
- E is the vertical distance from the right vertex to the left vertex of each bend in the line on the left side of the sign. The right vertex of the lower bend is aligned with the horizontal center of the sign.
- F is the vertical distance from the right vertex of the upper bend to the left vertex of the lower bend in the line on the left side of the sign.
- G is the distance from the horizontal center of the sign to the top and bottom of the vertical line in the right side of the sign and to the bottom of the bent line in the left side of the sign.
- H is the length of the each segment in the vertical dashed line.
- J is the space between the segments.
- K is the width of the right vertical line and the left bent line.
- L is the space between the dashed line and the lower vertical section of the bent line.
- M is the width of the dashed line.
- N is the distance from the vertical center of the sign to the right edge of the dashed line.
- P is the distance from the vertical center of the sign to the left edge of the straight vertical line.
- Q is the corner radius.

W4-3: Added Lane

W4-3R

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of each arrowhead and to the base of the left arrow.
- E is the vertical distance from the horizontal center of the sign to the center of the base of the right arrow.
- F is the vertical distance from the center of the base of the right arrow to the center of the base of the parallel dividing line.
- G is the vertical distance from the base of the left arrow to the base of the left dividing line.
- H is the distance from the vertical center of the sign to the tip of each arrowhead.
- J is the length of each dashed segment of the dividing line and the distance from the horizontal center of the sign to the end of the first segment.
- K is the space between the segments of the dividing line.
- L is the offset distance from the centerline of the curved shaft to the centerline of the right branch of the dividing line.
- M is the radius of the curve in the right arrow shaft
- N is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the right arrow shaft and to the end of the curve.
- P is the width of each arrow shaft.
- Q is the width of each arrowhead.
- R is the width of each branch in the dividing line.
- S is the corner radius.

W4-3L

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of each arrowhead and to the base of the right arrow.
- E is the vertical distance from the horizontal center of the sign to the center of the base of the left arrow.
- F is the vertical distance from the center of the base of the left arrow to the center of the base of the parallel dividing line.
- G is the vertical distance from the base of the right arrow to the base of the right dividing line.
- H is the distance from the vertical center of the sign to the tip of each arrowhead.
- J is the length of each dashed segment of the dividing line and the distance from the horizontal center of the sign to the end of the first segment.
- K is the space between the segments of the dividing line.

- L is the offset distance from the centerline of the curved shaft to the centerline of the left branch of the dividing line.
- M is the radius of the curve in the left arrow shaft
- N is the distance from the horizontal center of the sign to the vertex of the angle of the curve in the left arrow shaft and to the end of the curve.
- P is the width of each arrow shaft.
- Q is the width of each arrowhead.
- R is the width of each branch in the dividing line.
- S is the corner radius.

W4-4P: Cross Traffic Does Not Stop (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the width of the first word on the first line.
- J is the space between the words on each line.
- K is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- L is the distance from the vertical center of the plaque to the right edge of the second word on the first line.
- M is the width of the first word on the second line.
- N is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- P is the distance from the vertical center of the plaque to the right edge of the second word on the second line.
- Q is the width of the third word on the second line.
- R is the corner radius.

W4-4aP: Traffic From Left (Right) Does Not Stop (plaque)

W4-4aPR

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the width of the first word on the first line.
- K is the space between the words on the first line.
- L is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- M is the distance from the vertical center of the plaque to the right edge of the second word on the first line.
- N is the width of the third word on the first line.
- P is the width of the first word on the second line.
- Q is the space between the words on the second line.
- R is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- S is the distance from the vertical center of the plaque to the right edge of the second word on the second line.
- T is the width of the third word on the second line.
- U is the corner radius.

W4-4aPL

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the width of the first word on the first line.
- K is the space between the words on the first line.
- L is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- M is the distance from the vertical center of the plaque to the right edge of the second word on the first line.
- N is the width of the third word on the first line.
- P is the width of the first word on the second line.
- Q is the space between the words on the second line.
- R is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- S is the distance from the vertical center of the plaque to the right edge of the second word on the second line.
- T is the width of the third word on the second line.
- U is the corner radius.

W4-4bP: Oncoming Traffic Does Not Stop

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left edge of the first word on the first line.
- K is the distance from the vertical center of the plaque to the right edge of the first word on the first line.
- L is the space between the words on the first line.
- M is the width of the second word on the first line.
- N is the width of the first word on the second line.
- P is the space between the words on the second line.
- Q is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- R is the distance from the vertical center of the plaque to the right edge of the second word on the second line.
- S is the width of the third word on the second line.
- T is the corner radius.

W4-5: Entering Roadway Merge

W4-5R

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the tip of the arrowhead.
- E is the distance from the horizontal center of the sign to the tip of the arrowhead.
- F is the distance from the horizontal center of the sign to the vertex of the curve angle for the second curved section of the branch.
- G is the distance from the vertical center of the sign to the vertex of the curve angle for second curved section of the branch.
- H is radius of the second curved section of the branch.
- J is the radius of the first curved section of the branch.
- K is the shaft width of the curved branch.
- L is the distance from the vertical center of the sign to the centerline of the arrow shaft at its base.
- M is the shaft width of the straight arrow.
- N is the distance from the horizontal center of the sign to the centerline of the arrow shaft at its base.
- P is the distance from the horizontal center of the sign to the bottom of the symbol.
- Q is the width of the arrowhead.
- R is the corner radius.

W4-5L

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the vertical center of the sign to the tip of the arrowhead.
- E is the distance from the horizontal center of the sign to the tip of the arrowhead.
- F is the distance from the horizontal center of the sign to the vertex of the curve angle for the second curved section of the branch.
- G is the distance from the vertical center of the sign to the vertex of the curve angle for second curved section of the branch.
- H is radius of the second curved section of the branch.
- J is the radius of the first curved section of the branch.
- K is the shaft width of the curved branch.
- L is the distance from the vertical center of the sign to the centerline of the arrow shaft at its base.
- M is the shaft width of the straight arrow.
- N is the distance from the horizontal center of the sign to the centerline of the arrow shaft at its base.
- P is the distance from the horizontal center of the sign to the bottom of the symbol.
- Q is the width of the arrowhead.
- R is the corner radius.

W4-5aP: No Merge Area (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first and third lines.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- L is the distance from the vertical center of the plaque to the left and right edges of the word on the second line.
- M is the distance from the vertical center of the plaque to the left edge of the word on the third line.
- N is the distance from the vertical center of the plaque to the right edge of the word on the third line.
- P is the corner radius.

W4-6: Entering Roadway Added Lane

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the vertical distance from the tip of the left arrowhead to the tip of the right arrowhead.
- E is the distance from the horizontal center of the sign to the tip of the right arrowhead.
- F is the distance from the horizontal center of the sign to the base of the right arrow shaft.
- G is the vertical distance from the center of the base of the left dividing line to the base of the right dividing line.
- H is the vertical distance from the center of the base of the left arrow to the center of the base of the left dividing line.
- J is the distance from the horizontal center of the sign to the center of the base of the left arrow shaft.
- K is the horizontal distance from the vertical center of the sign to the tip of the left arrowhead.
- L is the horizontal distance from the tip of the left arrowhead to the center of the end of the dividing line.
- M is the length of each dashed segment of the dividing line.
- N is the space between the dashed segments of the dividing line.
- P is the distance from the vertical center of the sign to the centerline of the vertical section of the right arrow shaft.
- Q is the radius of the curve in the centerline of the right arrow shaft.
- R is the distance from the horizontal center of the sign to the start of the curve in the right arrow shaft and to the vertex of its curve angle.
- S is the width of each arrow shaft.
- T is the horizontal distance from the center of the base of the left arrow shaft to the center of the base of the left branch of the dividing line.
- W is the width of each branch of the dividing line.
- X is the width of each arrowhead.
- Y is the corner radius.

W4-7: Heavy Merge From Right (Left)

W4-7R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first and fourth lines.
- E is the space between the first and second lines and between the third and fourth lines.
- F is the letter height and FHWA standard font for the second and third lines.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the horizontal center of the sign to the top of the third line.
- J is the distance from the vertical center of the sign to the left edge of the word on the first line.
- K is the distance from the vertical center of the sign to the right edge of the word on the first line.
- L is the distance from the vertical center of the sign to the left edge of the word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the word on the second line.
- N is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- P is the distance from the vertical center of the sign to the left edge of the fourth word on the line.
- Q is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- R is the corner radius.

W4-7L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first and fourth lines.
- E is the space between the first and second lines and between the third and fourth lines.
- F is the letter height and FHWA standard font for the second and third lines.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the horizontal center of the sign to the top of the third line.
- J is the distance from the vertical center of the sign to the left edge of the word on the first line.
- K is the distance from the vertical center of the sign to the right edge of the word on the first line.
- L is the distance from the vertical center of the sign to the left edge of the word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the word on the second line.

- N is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- R is the corner radius.
- S is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- T is the distance from the vertical center of the sign to the right edge of the word on the fourth line.

W4-8: Single-Lane Transition

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the second bend in each outer vertical line to the ends of the lines, measured along the outer edges of each line.
- E is the vertical distance from the first bend to the second bend in each outer vertical line, measured along the outer edge of each line, and the distance from the top end of the top segment of the inner line to the second bend of each outer vertical line, measured along the inner edge of the vertical line.
- F is the distance from the horizontal center of the sign to the first bend in each outer line, measure along the outer edges of the vertical lines.
- G is the distance from the horizontal center of the sign to the bottom of the symbol.
- H is the line width of the outer lines.
- J is the distance from the vertical center of the sign to the inner edges of the outer lines above the second bend.
- K is the distance from the vertical center of the sign to the left and right edges of the vertical dashed line.
- L is the distance from the horizontal center of the sign to the top end of the top segment of the vertical dashed line.
- M is the distance from the horizontal center of the sign to the bottom end of the top segment of the vertical dashed line.
- N is the space between the segments of the vertical dashed line.
- P is the length of the bottom two segments of the vertical dashed line.
- Q is the distance from the vertical center of the sign to the left and right inner edges of the outer lines, measured at their bases.
- R is the corner radius

W5-1: Road Narrows

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W5-2: Narrow Bridge

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- K is the corner radius.

W5-2a: Narrow Underpass

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- L is the corner radius

W5-3: One Lane Bridge

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line. The bottom of the first line is aligned with the horizontal center of the sign.
- E is the space between the lines and the space between the words on the first line.
- F is the width of the first word on the first line.
- G is the width of the second word on the first line. The left edge of the second word is aligned with the vertical center of the sign.
- H is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- J is the corner radius.

W5-3a: One Lane Underpass

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the letter height and FHWA standard font for the second line.
- H is the width of the first word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the first word on the first line.
- K is the width of the second word on the first line.
- L is the distance from the vertical center of the sign to the left edge of the word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the word on the second line.
- N is the corner radius.

W5-4: Ramp Narrows

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W5-4a: Path Narrows

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line. The top of the second line is aligned with the horizontal center of the sign.
- E is the space between the lines.
- F is the distance from the vertical center of the sign to the left edge of the word on the first line.
- G is the distance from the vertical center of the sign to the right edge of the word on the first line.
- H is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- J is the corner radius.

W6-1: Divided Highway

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the right arrowhead.
- E is the distance from the horizontal center of the sign to the vertex of the first curve angle and to the start of the first curve in the right arrow shaft.
- F is the length of the first straight section of each arrow.
- G is the distance from the horizontal center of the sign to the tip of the left arrowhead.
- H is the distance from the horizontal center of the sign to the base of the left arrow shaft.
- J is the distance from the base of the left arrow shaft to the top of the traffic island symbol and to the vertex of the major curve angle for the curved edges of the traffic island.
- K is the distance from the vertical center of the sign to the left and right edges of the traffic island symbol.
- L is the radius of the major curve that forms the left- and right-side edges of the traffic island.
- M is the radius of the minor curve that forms the left- and right-bottom edges of the traffic island.
- N is the distance from the horizontal center of the sign to the vertex of the second curve angle and to the end of the second curve.
- P is the distance from the vertical center of the sign to the vertex of the second curve angle and to the end of the second curve.
- Q is the radius of the centerline of each curve in each arrow shaft.
- R is the distance from the vertical center of the sign to the tip of the left arrowhead and to the centerline of the first straight section of the right arrow shaft.
- S is the width of each arrowhead.
- T is the length of the second straight section of each arrow.
- U is the corner radius.

W6-2: Divided Highway Ends

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the left arrowhead.
- E is the distance from the horizontal center of the sign to the vertex of the first curve angle and to the start of the first curve in the left arrow shaft.
- F is the length of the first straight section of each arrow.
- G is the distance from the horizontal center of the sign to the tip of the right arrowhead.
- H is the distance from the horizontal center of the sign to the base of the right arrow shaft.
- J is the distance from the base of the right arrow shaft to the bottom of the traffic island symbol and to the vertex of the major curve angle for the side edges of the traffic island.
- K is the distance from the vertical center of the sign to the right and left edges of the traffic island symbol.
- L is the radius of the major curve that forms the right- and left-side edges of the traffic island.
- M is the radius of the minor curve that forms the right- and left-top edges of the traffic island.
- N is the distance from the horizontal center of the sign to the vertex of the second curve angle and to the end of the second curve.
- P is the distance from the vertical center of the sign to the vertex of the second curve angle and to the end of the second curve.
- Q is the radius of the centerline of each curve in each arrow shaft.
- R is the distance from the vertical center of the sign to the tip of the right arrowhead and to the centerline of the first straight section of the left arrow shaft.
- S is the width of each arrowhead.
- T is the length of the second straight section of each arrow.
- U is the corner radius.

W6-3: Two-Way Traffic

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of each arrowhead.
- E is the distance from the horizontal center of the sign to the base of each arrow.
- F is the distance from the vertical center of the sign to the centerline of each arrow.
- G is the width of each arrowhead.
- H is the corner radius.

W6-5: Two-Way Traffic (3-Lane)

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tip of the right arrow.
- E is the distance from the horizontal center of the sign to the base of the right arrow.
- F is the distance from the horizontal center of the sign to the tips of the left and middle arrows.
- G is the distance from the horizontal center of the sign to the bases of the left and middle arrows.
- H is the distance from the vertical center of the sign to the tip of the right arrowhead.
- J is the width of the left and middle arrow shafts.
- K is the distance between the left and middle arrowhead tips.
- L is the distance from the vertical center of the sign to the tip of the middle arrowhead.
- M is the width of the right arrow shaft.
- N is the width of the left and middle arrowheads.
- P is the width of the arrowhead.
- Q is the corner radius.

W6-5a: Two-Way Traffic (3-Lane)

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the tips of the middle and right arrowheads.
- E is the distance from the horizontal center of the sign to the base of the middle and right arrow shafts.
- F is the distance from the horizontal center of the sign to the tip of the left arrowhead.
- G is the distance from the horizontal center of the sign to the base of the left arrow shaft.
- H is the distance from the vertical center of the sign to the tip of the right arrowhead.
- J is the width of the left arrow shaft.
- K is the distance from the centerline of the left arrow to the centerline of the middle arrow.
- L is the distance from the vertical center of the sign to the centerline of the middle arrow.
- M is the width of the middle and right arrow shafts.
- N is the width of the left arrowhead.
- P is the width of the middle and right arrowheads.
- Q is the corner radius.

W7-1: Hill

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W7-1a: Hill with Grade

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the space between the symbol and the word.
- G is the letter height and FHWA standard font for the number.
- H is the distance from the vertical center of the sign to the left edge of the symbol.
- J is the distance from the vertical center of the sign to the left and right edges of the percentage.
- K is the width of the number in the percentage.
- L is the space between the number and the percent symbol in the percentage.
- M is the width of the percent symbol.
- N is the corner radius.

W7-2P: Use Low Gear (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the width of the first word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the first word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- L is the width of the second word on the first line.
- M is the distance from the vertical center of the plaque to the left and right edges of the word on the second line.
- N is the corner radius.

W7-2bP: Trucks Use Lower Gear (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- K is the width of the first word on the second line.
- L is the space between the words on the second line.
- M is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- N is the distance from the vertical center of the plaque to the right edge of the second word on the second line.
- P is the distance from the vertical center of the plaque to the left edge of the word on the third line.
- Q is the distance from the vertical center of the plaque to the right edge of the word on the third line.
- R is the corner radius.

W7-3P: XX% Grade (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left and right edges of the percentage on the first line.
- J is the width of the number in the percentage on the first line.
- K is the space between the number and the percent symbol on the first line.
- L is the width of the percent symbol on the first line.
- M is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- M is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- P is the corner radius.

W7-3aP: Next XX Miles (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the left and right edges of the second line.
- L is the width of the number on the second line.
- M is the space between the number and the word on the second line.
- N is the width of the word on the second line.
- P is the corner radius.

W7-3bP: XX% Grade XX Miles (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque, the space between the lines, and the distance from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the distance from the vertical center of the sign to the left and right edges of the first line.
- H is the width of the number on the first line.
- J is the space between the number and the percent symbol on the first line.
- K is the width of the percent symbol on the first line.
- L is the space between the percent symbol and the word on the first line and between the number and the word on the second line.
- M is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- N is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- P is the distance from the vertical center of the plaque to the left and right edges of the second line.
- Q width of the number on the second line.
- R is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- S is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- T is the corner radius.

W7-4: Runaway Truck Ramp XX Miles

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first and second lines.
- G is the space between the first and second lines.
- H is the space between the second and third lines.
- J is the distance from the top of the number to the top of the word on the third line and from the bottom of the word to the bottom of the number on the third line.
- K is the letter height and FHWA standard font for the word on the third line.
- L is the distance from the bottom of the last line to the bottom of the sign.
- M is the letter height and FHWA standard font for the number on the third line.
- N is the distance from the vertical center of the sign to the left edge of the word on the first line.
- P is the distance from the vertical center of the sign to the right edge of the word on the first line.
- Q is the width of the first word on the second line.
- R is the distance from the vertical center of the sign to the right edge of the first word on the second line.
- S is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- T is the width of the second word on the second line.
- U is the width of the number on the third line.
- V is the space between the number and the word on the third line.
- W is the distance from the vertical center of the sign to the left edge of the word on the third line.
- X is the distance from the vertical center of the sign to the right edge of the word on the third line.
- Y is the corner radius.

W7-4b: Runaway Truck Ramp Entrance Direction with Arrow

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first and second lines.
- G is the space between the lines.
- H is the distance from the bottom of the arrow symbol to the bottom of the sign.
- J is the distance from the vertical center of the sign to the left edge of the word on the first line.
- K is the distance from the vertical center of the sign to the right edge of the word on the first line.
- L is the width of the first word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the first word on the second line.
- N is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- P is the width of the second word on the second line.
- Q is the distance from the vertical center of the sign to the left and right edges of the arrow symbol on the third line.
- R is the arrowhead width.
- S is the corner radius.

W7-4c: Truck Escape Ramp

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the distance from the vertical center of the sign to the left edge of the word on the third line.
- M is the distance from the vertical center of the sign to the right edge of the word on the third line.
- N is the corner radius.

W7-4dP: Sand (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left and right edges of the word.
- H is the corner radius.

W7-4eP: Gravel (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left and right edges of the word.
- H is the corner radius.

W7-4fP: Paved (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left and right edges of the word.
- H is the corner radius.

W7-5: Hill (Bicycle)

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the ramp.
- E is the distance from the horizontal center of the sign to the bottom of the ramp.
- F is the distance from the vertical center of the sign to the left edge of the bicycle.
- G is the distance from the vertical center of the sign to the right edge of the bicycle.
- H is the height of the bicycle perpendicular to the slope.
- J is the distance from the vertical center of the sign to the left and right edges of the slope.
- K is the corner radius.

W7-6: Hill Blocks View

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top and bottom of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the distance from the vertical center of the sign to the left edge of the word on the third line.
- M is the distance from the vertical center of the sign to the right edge of the word on the third line.
- N is the corner radius.

W8-1: Bump

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the line.
- E is the distance from the vertical center of the sign to the left edge of the line.
- F is the distance from the vertical center of the sign to the right edge of the line.
- G is the letter height and FHWA standard font for the line.
- H is the corner radius.

W8-2: Dip

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the word.
- E is the distance from the vertical center of the sign to the left edge of the word.
- F is the distance from the vertical center of the sign to the right edge of the word.
- G is the letter height and FHWA standard font for the line.
- H is the corner radius.

W8-3: Pavement Ends

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the first line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the space between the lines.
- G is the letter height and FHWA standard font for each line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W8-4: Soft Shoulder

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the sign to the left edge of the word on the first line.
- K is the distance from the vertical center of the sign to the right edge of the word on the first line.
- L is the distance from the vertical center of the sign to the left edge of the word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the word on the second line.
- N is the corner radius.

W8-5: Slippery When Wet

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom edges of the symbol.
- E is the distance from the vertical center of the sign to the left edge of the symbol.
- F is the distance from the vertical center of the sign to the right edge of the symbol.
- G is the corner radius.

W8-5P: When Wet (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- M is the corner radius.

W8-5aP: Ice (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the word to the top of the plaque and from the bottom of the word to the bottom of the plaque.
- F is the letter height and FHWA standard font for the word.
- G is the distance from the vertical center of the plaque to the left edge of the word.
- H is the distance from the vertical center of the plaque to the right edge of the word.
- J is the corner radius.

W8-5bP: Steel Deck (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- M is the corner radius.

W8-5cP: Excess Oil (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- M is the corner radius.

W8-6: Truck Crossing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the vertical center of the sign to the left edge of the word on the first line.
- G is the distance from the vertical center of the sign to the right edge of the word on the first line.
- H is the distance from the vertical center of the sign to the left edge of the word on the second line.
- J is the distance from the vertical center of the sign to the right edge of the word on the second line.
- K is the corner radius.

W8-7: Loose Gravel

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the letter height and FHWA standard font for the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W8-8: Rough Road

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first word.
- F is the distance from the horizontal center of the sign to the top of the second word.
- G is the distance from the vertical center of the sign to the left edge of the first word.
- H is the distance from the vertical center of the sign to the right edge of the first word.
- J is the distance from the vertical center of the sign to the left edge of the second word.
- K is the distance from the vertical center of the sign to the right edge of the second word.
- L is the corner radius.

W8-9: Low Shoulder

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- K is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- L is the corner radius.

W8-10: Bicycle Surface Condition

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- E is the distance from the vertical center of the sign to the left and right edges of the symbol.
- F is the corner radius.

W8-10P: Slippery When Wet (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines and the corner radius.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left and right edges of the word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the first word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the first word on the second line.
- M is the space between the words on the second line.
- N is the width of the second word on the second line.

W8-11: Uneven Lanes

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- H is the distance from the vertical center of the sign to the left edge of the word on the second line.
- J is the distance from the vertical center of the sign to the right edge of the word on the second line.
- K is the corner radius.

W8-12: No Center Line

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- N is the corner radius.

W8-13: Bridge Ices Before Road

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first and third lines.
- E is the space between the lines.
- F is the letter height and FHWA standard font for the second line.
- G is the distance from the horizontal center of the sign to the top of the second line.
- H is the distance from the horizontal center of the sign to the bottom of the second line.
- J is the distance from the vertical center of the sign to the left edge of the word on the first line.
- K is the distance from the vertical center of the sign to the right edge of the word on the first line.
- L is the width of the first word on the second line.
- M is the space between the words on the second line.
- N is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- P is the distance from the vertical center of the sign to the right edge of the second word on the second line.
- Q is the distance from the vertical center of the sign to the left edge of the word on the third line.
- R is the distance from the vertical center of the sign to the right edge of the word on the third line.
- S is the corner radius.

W8-14: Fallen Rocks

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W8-15: Grooved Pavement

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W8-15aP: Motorcycle (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the symbol to the top of the plaque and from the bottom of the symbol to the bottom of the plaque.
- F is the distance from the vertical center of the plaque to the top and bottom of the symbol.
- G is the distance from the vertical center of the plaque to the left and right edges of the symbol.
- H is the corner radius.

W8-16: Metal Bridge Deck

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines and the distance from the horizontal center of the sign to the bottom of the second line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the distance from the vertical center of the sign to the left edge of the word on the third line.
- M is the distance from the vertical center of the sign to the right edge of the word on the third line.
- N is the corner radius.

W8-17: Shoulder Drop-Off

W8-17R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W8-17L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the right edge of the symbol.
- G is the distance from the vertical center of the sign to the left edge of the symbol.
- H is the corner radius.

W8-17P: Shoulder Drop-Off (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left and right edges of the word on the first line.
- K is the width of the first word on the second line.
- L is the distance from the vertical center of the line to the right edge of the first word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the hyphen on the second line.
- N is the width of the hyphen and the space between the hyphen and the second word on the second line.
- P is the width of the second word on the second line.
- Q is the corner radius.

W8-18: Road May Flood

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the word on the third line.
- P is the corner radius.

W8-19: Depth Gauge

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the border width.
- D is the inset from the edge of the sign to the border.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the first and second lines.
- H is the letter height and FHWA standard font for the second, third, fourth, fifth, and sixth lines.
- J is the space between the second, third, fourth, fifth and sixth lines.
- K is the distance from the bottom of the last line to the bottom of the sign.
- L is the distance from the bottom of the lowest tick marks to the bottom of the sign.
- M is the width of the tick marks.
- N is the space between the tick marks.
- P is the distance from the top of the highest tick marks to the bottom of the first line.
- Q is the distance from the bottom of the first line to the top of the sign.
- R is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- S is the distance from the vertical center of the sign to the left edge of the number on the second, fourth, and fifth lines.
- T is the distance from the vertical center of the sign to the right edge of the number on the second, fourth, and fifth lines.
- U is the distance from the vertical center of the sign to the left edge of the number on the third line.
- V is the distance from the vertical center of the sign to the right edge of the number on the third line.
- W is the distance from the vertical center of the sign to the left and right edges of the word on the sixth line.
- X is the space between the vertical center of the sign and the major tick marks.
- Y is the length of the major tick marks.
- Z is the space between the vertical center of the sign and the minor tick marks.
- AA is the length of the minor tick marks.
- BB is the corner radius.

W8-21: Gusty Winds Area

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- N is the corner radius.

W8-22: Fog Area

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- K is the corner radius.

W8-23: No Shoulder

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W8-25: Shoulder Ends

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W8-26: Road Ends Advance

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the number on the third line and to the right edge of the word on the third line.
- N is the width of the number on the third line.
- P is the space between the number and the word on the third line.
- Q is the width of the word on the third line
- R is the corner radius.

W8-26a: Street Ends Advance

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first line.
- E is the space between the lines.
- F is the letter height and FHWA standard font for the second and third lines.
- G is the distance from the horizontal center of the sign to the top of the second line.
- H is the distance from the horizontal center of the sign to the bottom of the second line.
- J is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the number on the third line and to the right edge of the word on the third line.
- N is the width of the number on the third line.
- P is the space between the number and the word on the third line.
- Q is the width of the word on the third line
- R is the corner radius.

W9-1: Right (Left) Lane Ends

W9-1R

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the word on the third line.
- P is the corner radius.

W9-1L

- A is the length of each side of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the word on the third line.
- P is the corner radius.
- Q is the distance from the vertical center of the sign to the left edge of the word on the first line.
- R is the distance from the vertical center of the sign to the right edge of the word on the first line.

W9-4: Lanes Merge

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W9-5: Bicycle Lane Ends

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the bicycle symbol.
- E is the space between the first and second lines.
- F is the letter height and FHWA standard font for the second and third lines.
- G is the distance from the horizontal center of the sign to the top of the second line.
- H is the distance from the horizontal center of the sign to the bottom of the second line.
- J is the space between the second and third lines.
- K is the distance from the vertical center of the sign to the left and right edges of the bicycle symbol.
- L is the distance from the vertical center of the sign to the left edge of the word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the word on the second line.
- N is the distance from the vertical center of the sign to the left edge of the word on the third line.
- P is the distance from the vertical center of the sign to the right edge of the word on the third line.
- Q is the corner radius.

W9-5a: Bicycles Merging

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the bicycle symbol.
- E is the distance from the horizontal center of the sign to the bottom of the bicycle symbol.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the letter height and FHWA standard font for the second line.
- H is the distance from the vertical center of the sign to the left edge of the bicycle symbol.
- J is the distance from the vertical center of the sign to the right edge of the bicycle symbol.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W9-6: Pay Toll XX Miles Cars (price)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for number on the second line.
- J is the distance from the top of the number on the second line to the top of the plaque.
- K is the width of the first word on the first line.
- L is the distance from the vertical center of the plaque to the right edge of the first word on the first line.
- M is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- N is the width of the second word on the first line.
- P is the distance from the vertical center of the sign to the left and right edges of the second line.
- Q is the width of the number on the second line.
- R is the space between the number and the word on the second line.
- S is the width of the word on the second line.
- T is the distance from the vertical center of the sign to the left and right edges of the second line.
- U is the width of the word on the second line.
- V is the space between the word and the number on the second line.
- W is the width of the number and cents symbol on the second line.
- X is the corner radius.

W9-6a: Stop Ahead Pay Toll Cars (price)

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the width of the first word on the first line.
- J is the space between the words on the first line.
- K is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- L is the distance from the vertical center of the sign to the right edge of the second word on the first line.
- M is the width of the first word on the second line.
- N is the distance from the vertical center of the sign to the right edge of the first word on the second line.
- P is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- Q is the width of the second word on the second line.
- R is the distance from the vertical center of the sign to the left and right edges of the third line.
- S is the width of the first word on the third line.
- T is the space between the words on the third line.
- U is the width of the second word on the third line.
- V is the corner radius.

W9-6bP: Pay Toll XX Miles Cars (price) (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each word and the second number.
- H is the width of the first word.
- J is the space between the first and second words.
- K is the width of the second word.
- L is the space between the second word and the first number.
- M is the width of the first number.
- N is the space between the third and fourth words.
- P is the letter height and FHWA standard font for the first number.
- Q is the distance from the vertical center of the plaque to the left edge of the third word.
- R is the distance from the vertical center of the plaque to the right edge of the third word.
- S is the space between the hyphen and the third and fourth words.
- T is the width of the hyphen.
- U is the width of the fourth word.
- V is the space between the fourth word and the second number.
- W is the width of the second number with the cents symbol.
- X is the corner radius.

W9-6cP: Stop Ahead Pay Toll (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the width of the first word.
- H is the space between the first and second words and between the third and forth words.
- J is the distance from the vertical center of the sign to the left edge of the second word.
- K is the distance from the vertical center of the sign to the right edge of the second word.
- L is the width of the hyphen and the space between the hyphen and the second and third words.
- M is the width of the third word.
- N is the width of the fourth word
- P is the corner radius.

W9-6dP: Stop Ahead Pay Toll (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the width of the first word on the first line.
- J is the space between the words on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- L is the distance from the vertical center of the plaque to the right edge of the second word on the first line.
- M is the width of the first word on the second line.
- N is the distance from the vertical center of the plaque to the right edge of the first word on the second line.
- P is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- Q is the width of the second word on the second line.
- R is the corner radius.

W9-6e: Take Ticket XX Miles

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the word on the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for the first line and for the word on the second line.
- G is the space between the lines.
- H is the distance from the bottom of the number on the second line to the bottom of the sign.
- J is the letter height and FHWA standard font for the number on the second line.
- K is the width of the first word on the first line.
- L is the space between the words on the first line.
- M is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- N is the distance from the vertical center of the sign to the right edge of the second word on the first line.
- P is the distance from the vertical center of the sign to the left and right edges of the second line.
- Q is the width of the number on the second line.
- R is the space between the number and the word on the second line.
- S is width of the word on the second line.
- T is the corner radius.

W9-6f: Stop Ahead Take Ticket

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the width of the first word on the first line.
- J is the space between the words on each line.
- K is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- L is the distance from the vertical center of the sign to the right edge of the second word on the first line.
- M is the width of the first word on the second line.
- N is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- P is the distance from the vertical center of the sign to the right edge of the second word on the second line.
- Q is the corner radius.

W9-6gP: Take Ticket XX Miles (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque, the distance from the bottom of the line to the bottom of the plaque, and the space between the first and second words.
- F is the letter height and FHWA standard font for the line.
- G is the letter height and FHWA standard font for the number.
- H is the distance from the top of the number to the top of the plaque and from the bottom of the number to the bottom of the plaque.
- J is the distance from the vertical center of the sign to the left and right edges of the line.
- K is the width of the first word.
- L is the width of the second word.
- M is the space between the second word and the number.
- N is the width of the number.
- P is the width of the fourth word.
- Q is the corner radius.

W9-6hP: Stop Ahead Take Ticket (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the width of the first word.
- H is the space between the first and second words and between the third and fourth words.
- J is the width of the second word.
- K is the distance between the hyphen and the second and third words.
- L is the distance from the vertical center of the sign to the left edge of the hyphen.
- M is the distance from the vertical center of the sign to the right edge of the hyphen.
- N is the width of the third word.
- P is the width of the fourth word.
- Q is the corner radius.

W9-7: Right (Left) Lane for Exit Only Ahead

W9-7R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign, the space between the lines, and the distance from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the width of the first word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the first word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- K is the width of the second word on the first line.
- L is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- M is the width of the first word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the first word on the third line.
- P is the width of the second word on the third line. The left edge of the word is aligned with the vertical center of the sign.
- Q is the corner radius.

W9-7L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign, the space between the lines, and the distance from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the width of the first word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the first word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- K is the width of the second word on the first line.
- L is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- M is the width of the first word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the first word on the third line.
- P is the width of the second word on the third line. The left edge of the word is aligned with the vertical center of the sign.
- Q is the corner radius.

W10-1: Grade Crossing Advance Warning

- A is the vertical and horizontal dimension of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the top and bottom of the letters to the top and bottom of the sign.
- E is the distance from the horizontal center of the sign to the top and bottom of the letter.
- F is the letter height and FHWA standard font for the letters.
- G is the distance from the vertical center of the sign to the left edge of the letter in the left quadrant.
- H is the distance from the vertical center of the sign to the left edge of the letter in the right quadrant.
- J is the width of each perpendicular line.

W10-1aP: Exempt (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the word to the top of the plaque and from the bottom of the word to the bottom of the plaque.
- F is the letter height and FHWA standard font for the word.
- G is the distance from the vertical center of the plaque to the left edge of the word.
- H is the distance from the vertical center of the plaque to the right edge of the word.
- J is the corner radius.

W10-2: Grade Crossing Advance Warning – Crossroad with Grade Crossing

W10-2R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the length of the top, left, and bottom legs of the intersection.
- E is the distance from the horizontal center of the sign to the top and bottom edges of the horizontal line and the distance from the vertical center of the sign to the right edge of the vertical legs of the intersection and to the left edge of the cutout.
- F is the width of the vertical legs and central area of the intersection and the length of the horizontal section of road to the right of the cutout.
- G is the distance from the right edge of the railroad track symbol to the right edge of the cutout.
- H is the width of the railroad track symbol.
- J is the distance from the left edge of the railroad track symbol to the left edge of the cutout.
- K is the corner radius.

W10-2L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the length of the top, right, and bottom legs of the intersection.
- E is the distance from the horizontal center of the sign to the top and bottom edges of the horizontal line and the distance from the vertical center of the sign to the left edge of the vertical legs of the intersection and to the right edge of the cutout.
- F is the width of the vertical legs and central area of the intersection and the length of the horizontal section of road to the left of the cutout.
- G is the distance from the left edge of the railroad track symbol to the left edge of the cutout.
- H is the width of the railroad track symbol.
- J is the distance from the right edge of the railroad track symbol to the right edge of the cutout.
- K is the corner radius.

W10-3: Grade Crossing Advance Warning – Side Road with Grade Crossing

W10-3R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the length of each vertical leg of the intersection.
- E is the distance from the horizontal center of the sign to the top and bottom edges of the horizontal line and the distance from the vertical center of the sign to the right edge of the vertical legs of the intersection and to the left edge of the cutout.
- F is the width of the vertical legs and central area of the intersection and the length of the horizontal section of road to the right of the cutout.
- G is the distance from the right edge of the railroad track symbol to the right edge of the cutout.
- H is the width of the railroad track symbol.
- J is the distance from the left edge of the railroad track symbol to the left edge of the cutout.
- K is the corner radius.

W10-3L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the length of each vertical leg of the intersection.
- E is the distance from the horizontal center of the sign to the top and bottom edges of the horizontal line and the distance from the vertical center of the sign to the left edge of the vertical legs of the intersection and to the right edge of the cutout.
- F is the width of the vertical legs and central area of the intersection and the length of the horizontal section of road to the left of the cutout.
- G is the distance from the left edge of the railroad track symbol to the left edge of the cutout.
- H is the width of the railroad track symbol.
- J is the distance from the right edge of the railroad track symbol to the right edge of the cutout.
- K is the corner radius.

W10-4: Grade Crossing Advance Warning – T-Intersection with Grade Crossing

W10-4R

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the width of the horizontal and vertical lines.
- E is the length of the vertical leg of the intersection.
- F is the length of the horizontal section of road to the right of the cutout.
- G is the distance from the right edge of the cutout to the right edge of the railroad track symbol.
- H is the width of the railroad track symbol.
- J is the distance from the left edge of the railroad track symbol to the left edge of the cutout in the left road.
- K is the distance from the vertical center of the sign to the left edge of the cutout.
- L is the distance from the vertical center of the sign to the right edge of the vertical leg of the intersection.
- M is the length of the left horizontal leg of the intersection.
- N is the corner radius.

W10-4L

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the width of the horizontal and vertical lines.
- E is the length of the vertical leg of the intersection.
- F is the length of the horizontal section of road to the left of the cutout.
- G is the distance from the left edge of the cutout to the left edge of the railroad track symbol.
- H is the width of the railroad track symbol.
- J is the distance from the right edge of the railroad track symbol to the right edge of the cutout in the right road.
- K is the distance from the vertical center of the sign to the right edge of the cutout.
- L is the distance from the vertical center of the sign to the left edge of the vertical leg of the intersection.
- M is the length of the right horizontal leg of the intersection.
- N is the corner radius.

W10-5: Low Ground Clearance

- A is the length of each edge of the sign
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W10-5P: Low Ground Clearance (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the width of the first word on the first line.
- K is the space between the words on the first line.
- L is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- M is the distance from the vertical center of the plaque to the right edge of the second word on the first line.
- N is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- P is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- Q is the corner radius.

W10-7: Light Rail (activated blank-out)

- A is the length of each edge of the sign.
- B is the distance from the top of the symbol to the top of the sign and from the bottom of the symbol to the bottom of the sign.
- C is the height of the symbol.

W10-8: Trains May Exceed 80 mph

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for the first and second lines and the number on the third line.
- E is the space between the lines and the distance from the horizontal center of the sign to the top and bottom of the second line.
- F is the letter height and FHWA standard font for the word on the third line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the width of the first word of the second line.
- K is the space between the words on the second line.
- L is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the second word on the second line.
- N is the width of the number on the third line.
- P is the space between the number and the word on the third line.
- Q is the distance from the vertical center of the sign to the left edge of the word on the third line.
- R is the distance from the vertical center of the sign to the right edge of the word on the third line.
- S is the corner radius.

W10-9: No Train Horn

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second word.
- G is the distance from the horizontal center of the sign to the bottom of the second word.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- L is the distance from the vertical center of the sign to the left edge of the word on the third line.
- M is the distance from the vertical center of the sign to the right edge of the word on the third line.
- N is the corner radius.

W10-9P: No Train Horn (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left and right edges of the word on the first line.
- K is the width of the first word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the first word on the second line.
- M is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- N is the width of the second word on the second line.
- P is the corner radius.

W10-11: Storage Space

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the length of each horizontal leg of the intersection.
- E is the distance from the vertical center of the sign to the left and right edges of the vertical leg of the intersection, the distance from the horizontal center of the sign to the bottom edge of the horizontal legs of the intersection and to the top of the cutout.
- F is the width of the horizontal legs of the intersection and central area of the intersection and the length of the vertical section of road below the cutout.
- G is the distance from the bottom edge of the bottom of the railroad track symbol to the bottom of the cutout.
- J is the distance from the top of the cutout to the top of the railroad track symbol.
- H is the height of the railroad track symbol.
- K is the corner radius.

W10-11a: Storage Space Ahead

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for the first, second, and fourth lines.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the third line.
- J is the distance from the vertical center of the sign to the left and right edges of the first line.
- K is the width of the number on the first line.
- L is the space between the number and the word on the first line and between the words on the third line.
- M is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- N is the distance from the vertical center of the sign to the right edge of the second word on the first line.
- P is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- Q is the distance from the vertical center of the sign to the left edge of the first word on the third line.
- R is the distance from the vertical center of the sign to the right edge of the first word on the third line.
- S is the width of the second word on the third line.
- T is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- U is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- V is the corner radius.

W10-11b: Storage Space Behind

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for the first, second, fourth, and fifth lines.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the third line.
- J is the distance from the vertical center of the sign to the left and right edges of the first line.
- K is the width of the first word on the first line.
- L is the space between the words on the first line.
- M is the width of the second word on the first line.
- N is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- P is the distance from the vertical center of the sign to the left edge of the first word on the third line.
- Q is the distance from the vertical center of the sign to the right edge of the first word on the third line.
- R is the space between the words on the third line.
- S is the width of the second word on the third line.
- T is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- U is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- V is the distance from the vertical center of the sign to the left edge of the first word on the fifth line.
- W is the distance from the vertical center of the sign to the right edge of the first word on the fifth line.
- X is the space between the words on the fifth line.
- Y is the width of the second word on the fifth line.
- Z is the corner radius.

W10-12: Skewed Crossing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- E is the shorter distance from the top and bottom of the symbol to the intersection with the edge of the railroad track yellow background.
- F is the length of the railroad track.
- G is the longer distance from the top and bottom of the symbol to the intersection with the edge of the railroad track yellow background.
- H is the distance from the vertical center of the sign to the left and right edges of the vertical line.
- J is the distance, in the lower half of the sign, from the vertical center of the sign to the top corner of the top rail of the railroad track.
- K is the distance, in the lower half of the sign, from the horizontal center of the sign to the bottom corner of the bottom rail of the railroad track.
- L is the width of the railroad track.
- M is the corner radius.

W10-13P: No Gates or Lights (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the width of the first word on the first line.
- K is the space between the words on the first line.
- L is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- M is the distance from the vertical center of the sign to the right edge of the second word on the first line.
- N is the width of the first word on the second line.
- P is the space between words on the second line.
- Q is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- R is the distance from the vertical center of the sign to the right edge of the second word on the second line.
- S is the corner radius.

W10-14aP: Use Next Crossing (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the width of the first word on the first line.
- K is the distance from the vertical center of the plaque to the right edge of the first word on the first line.
- L is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- M is the width of the second word on the first line.
- N is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- P is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- Q is the corner radius.

W10-14P: Next Crossing (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- L is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- M is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- N is the corner radius.

W10-15P: Rough Crossing (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left and right edges of the word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- M is the corner radius.

W10-16: Another Train Coming (Blank-Out)

- A is the length of each edge of the sign.
- B is the distance from the top of the first line to the top of the sign, the space between the lines, and the distance from the bottom of the last line to the bottom of the sign.
- C is the letter height and FHWA standard font for the first line.
- D is the letter height and FHWA standard font for the second and third lines.
- E is the distance from the vertical center of the sign to the left edge of the word on the first line.
- F is the distance from the vertical center of the sign to the right edge of the word on the first line.
- G is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the third line.
- J is the distance from the vertical center of the sign to the right edge of the word on the third line.

W10-21: Busway Crossing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W10-21aP: Signal Ahead (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line
- J is the distance from the vertical center of the plaque to the left and right edges of the word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- M is the corner radius.

W11-1: Bicycle

- A is the length of each edge of the sign
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the corner radius.

W11-2: Pedestrian

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-3: Large Animal – Deer

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-4: Large Animal – Cattle

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-5: Farm Vehicle

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-6: Snowmobile

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the corner radius.

W11-7: Equestrian

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-8: Emergency Vehicle

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- E is the corner radius.

W11-9: Handicapped

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- E is the corner radius

W11-10: Truck

- A is the length of each edge of the sign
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the corner radius.

W11-11: Golf Cart

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the golf cart chassis.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-12P: Emergency Signal Ahead (plaque)

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for the first, second, and third lines.
- G is the space between the lines.
- H is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the distance from the vertical center of the sign to the left edge of the word on the third line.
- M is the distance from the vertical center of the sign to the right edge of the word on the third line.
- N is the corner radius.

W11-14: Horse-Drawn Vehicle

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-15: Trail Crossing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of the bicycle symbol.
- E is the distance from the horizontal center of the sign to the bottom of the bicycle symbol.
- F is the distance from the horizontal center of the sign to the top of the pedestrian symbol.
- G is the distance from the horizontal center of the sign to the bottom of the pedestrian symbol.
- H is the distance from the vertical center of the sign to the left edge of the pedestrian symbol.
- J is the distance from the vertical center of the sign to the right edge of the pedestrian symbol.
- K is the distance from the vertical center of the sign to the left edge of the bicycle symbol.
- L is the distance from the vertical center of the sign to the right edge of the bicycle symbol.
- M is the corner radius.

W11-15P: Trail Crossing (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- K is the width of the first letter on the second line.
- L is the space between the first letter and the hyphen on the second line and the width of the hyphen.
- M is the distance from the vertical center of the sign and the right edge of the hyphen on the second line.
- N is the distance from the vertical center of the plaque to the left edge of the “ING” part of the word on the second line.
- P is the width of the “ING” part of the word on the second line.
- Q is the corner radius.

W11-15a: Trail Crossing

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance between the horizontal center of the sign and the bottom of the first line.
- F is the distance from the vertical center of the sign to the left edge of the first line.
- G is the distance from the vertical center of the sign to the right edge of the first line.
- H is the distance from the vertical center of the sign to the left edge of the second line.
- J is the distance from the vertical center of the sign to the right edge of the second line.
- K is the corner radius.

W11-16: Large Animal – Bear

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from horizontal center of the sign to the top and bottom of the symbol.
- E is the corner radius.

W11-17: Large Animal – Sheep

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from horizontal center of the sign to the top and bottom of the symbol.
- E is the corner radius.

W11-18: Large Animal – Bighorn Sheep

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W11-19: Large Animal – Donkey

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- E is the corner radius.

W11-20: Large Animal – Elk

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- E is the distance from the vertical center of the sign to the left edge of the symbol.
- F is the distance from the vertical center of the sign to the right edge of the symbol.
- G is the corner radius.

W11-21: Large Animal – Moose

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top and bottom of the symbol.
- E is the distance from the vertical center of the sign to the left edge of the symbol.
- F is the distance from the vertical center of the sign to the right edge of the symbol.
- G is the corner radius.

W11-22: Large Animal – Wild Horse

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the distance from the vertical center of the sign to the left edge of the symbol.
- G is the distance from the vertical center of the sign to the right edge of the symbol.
- H is the corner radius.

W12-1: Double Arrow

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the arrows.
- E is the distance from the horizontal center of the sign to the bottom of the arrows.
- F is the distance from the vertical center of the sign to the left and right tips of the arrowheads.
- G is the length of the arrows.
- H is the width of the arrowheads.
- J is the corner radius.

W12-2: Low Clearance Advance

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the height of each arrow symbol.
- E is the space between the line and each arrow symbol.
- F is the distance from the horizontal center of the sign to the top and bottom of the line.
- G is the letter height and FHWA standard font for the line.
- H is the distance from the vertical center of the sign to the left and right edges of the line.
- J is the width of the first number on the line.
- K is the space between the first number and the feet symbol and between the second number and the inches symbol.
- L is the width of the feet symbol on the line.
- M is the space between the feet symbol and the hyphen on the line.
- N is the width of the hyphen on the line.
- P is the space between the hyphen and the second number on the line.
- Q is the width of the second number on the line.
- R is the width of the inches symbol on the line.
- S is the corner radius.

W12-2a: Low Clearance Overhead

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the sign and from the bottom of the line to the bottom of the sign.
- F is the distance from the top of the numbers to the top of the letters.
- G is the letter height and FHWA standard font for the letters.
- H is the letter height and FHWA standard font for the numbers.
- J is the distance from the vertical center of the sign to the left and right edges of the line.
- K is the width of the first number.
- L is the space between the first number and word and between the second number and word.
- M is the width of the first word.
- N is the space between the first word and the second number.
- P is the width of the second number.
- Q is the width of the second word.
- R is the corner radius.

W12-2b: Low Clearance – Lane Overhead

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the sign and from the bottom of the line to the bottom of the sign.
- F is the distance from the top of the numbers to the top of the letters and the space between the numbers, words, and symbol.
- G is the letter height and FHWA standard font for the letters.
- H is the letter height and FHWA standard font for the numbers.
- J is the distance from the top of the arrow symbol to the top of the sign and from the bottom of the arrow symbol to the bottom of the sign.
- K is the length of the arrow.
- L is the distance from the vertical center of the sign to the left and right edges of the line and from the left edge of the first word to the right edge of the last word. L is a variable dimension.
- M is the width of the numbers.
- N is the width of the first word.
- P is the width of the arrow symbol.
- Q is the width of the second word.
- R is the corner radius.

W13-1P: Advisory Speed (plaque)

- A is the length of each edge of the plaque.
- B is the inset from the edge of the plaque to the border.
- C is the border width.
- D is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- E is the letter height and FHWA standard font for the first line.
- F is the space between the lines.
- G is the letter height and FHWA standard font for the second line.
- H is the distance from the vertical center of the plaque to the left and right edges of the word on the first line.
- J is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- K is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- L is the corner radius.

W13-1aP: Advisory Speed Confirmation (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the word.
- G is the distance from the top of the number to the top of the plaque and from the bottom of the number to the bottom of the plaque.
- H is the letter height and FHWA standard font for the number.
- J is the distance from the vertical center of the plaque to the left and right edges of the line.
- K is the width of the number.
- L is the space between the number and the word.
- M is the width of the word.
- N is the corner radius.

W13-2: Advisory Exit Speed

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the second line.
- J is the letter height and FHWA standard font for the second line.
- K is the space between the second and third lines.
- L is the letter height and FHWA standard font for the third line.
- M is the distance from the bottom of the last line to the bottom of the sign.
- N is the distance from the vertical center of the sign to the left edge of the word on the first line.
- P is the distance from the vertical center of the sign to the right edge of the word on the first line.
- Q is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- R is the distance from the vertical center of the sign to the left edge of the word on the third line.
- S is the distance from the vertical center of the sign to the right edge of the word on the third line.
- T is the corner radius.

W13-3: Advisory Ramp Speed

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the second line.
- J is the letter height and FHWA standard font for the second line.
- K is the space between the second and third lines.
- L is the letter height and FHWA standard font for the third line.
- M is the distance from the bottom of the last line to the bottom of the sign.
- N is the distance from the vertical center of the sign to the left edge of the word on the first line.
- P is the distance from the vertical center of the sign to the right edge of the word on the first line.
- Q is the distance from the vertical center of the sign to the left and right edges of the word on the second line.
- R is the distance from the vertical center of the sign to the left edge of the word on the third line.
- S is the distance from the vertical center of the sign to the right edge of the word on the third line.
- T is the corner radius.

W13-6: Combination Horizontal Alignment/ Advisory Exit Speed – 270-degree Loop

W13-6R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the second and third lines.
- L is the letter height and FHWA standard font for the third line.
- M is the space between the third and fourth lines.
- N is the letter height and FHWA standard font for the fourth line.
- P is the distance from the bottom of the last line to the bottom of the sign.
- Q is the distance from the vertical center of the sign to the left edge of the word on the first line.
- R is the distance from the vertical center of the sign to the right edge of the word on the first line.
- S is the distance from the vertical center of the sign to the left edge of the arrow symbol.
- T is the distance from the vertical center of the sign to the right edge of the arrow symbol.
- U is the width of the arrow shaft.
- V is the length of the vertical section of the arrow shaft.
- W is the distance from the top of the vertical section of the arrow shaft to the tip of the arrowhead.
- X is the radius of the first and second sections of the spiral curve. The first section subtends an angle of 90 degrees clockwise from the top of the vertical section of the arrow shaft to the vertical center of the sign, and the second section subtends an additional 75 degrees.
- Y is the distance from the vertical center of the sign to the end of the spiral curve.
- Z is the distance from the center of the third section of the spiral curve in the arrow shaft to the top of the sign.
- AA is the radius of the third section of the spiral curve in the arrow shaft, which subtends an angle of 105 degrees.
- BB is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- CC is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- DD is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- EE is the width of the arrowhead.
- GG is the corner radius.

W13-6L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.

- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the second and third lines.
- L is the letter height and FHWA standard font for the third line.
- M is the space between the third and fourth lines.
- N is the letter height and FHWA standard font for the fourth line.
- P is the distance from the bottom of the last line to the bottom of the sign.
- Q is the distance from the vertical center of the sign to the left edge of the word on the first line.
- R is the distance from the vertical center of the sign to the right edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the arrow symbol.
- T is the distance from the vertical center of the sign to the left edge of the arrow symbol.
- U is the width of the arrow shaft.
- V is the length of the vertical section of the arrow shaft.
- W is the distance from the top of the vertical section of the arrow shaft to the tip of the arrowhead.
- X is the radius of the first and second sections of the spiral curve. The first section subtends an angle of 90 degrees clockwise from the top of the vertical section of the arrow shaft to the vertical center of the sign, and the second section subtends an additional 75 degrees.
- Y is the distance from the vertical center of the sign to the end of the spiral curve.
- Z is the distance from the center of the third section of the spiral curve in the arrow shaft to the top of the sign.
- AA is the radius of the third section of the spiral curve in the arrow shaft, which subtends an angle of 105 degrees.
- BB is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- CC is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- DD is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- EE is the width of the arrowhead.
- GG is the corner radius.

W13-7: Combination Horizontal Alignment/ Advisory Ramp Speed – 270-degree Loop

W13-7R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the second and third lines.
- L is the letter height and FHWA standard font for the third line.
- M is the space between the third and fourth lines.
- N is the letter height and FHWA standard font for the fourth line.
- P is the distance from the bottom of the last line to the bottom of the sign.
- Q is the distance from the vertical center of the sign to the left edge of the word on the first line.
- R is the distance from the vertical center of the sign to the right edge of the word on the first line.
- S is the distance from the vertical center of the sign to the left edge of the arrow symbol.
- T is the distance from the vertical center of the sign to the right edge of the arrow symbol.
- U is the width of the arrow shaft.
- V is the length of the vertical section of the arrow shaft.
- W is the distance from the top of the vertical section of the arrow shaft to the tip of the arrowhead.
- X is the radius of the first and second sections of the spiral curve. The first section subtends an angle of 90 degrees clockwise from the top of the vertical section of the arrow shaft to the vertical center of the sign, and the second section subtends an additional 75 degrees.
- Y is the distance from the vertical center of the sign to the end of the spiral curve.
- Z is the distance from the center of the third section of the spiral curve in the arrow shaft to the top of the sign.
- AA is the radius of the third section of the spiral curve in the arrow shaft, which subtends an angle of 105 degrees.
- BB is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- CC is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- DD is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- EE is the width of the arrowhead.
- GG is the corner radius.

W13-7L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.

- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the second and third lines.
- L is the letter height and FHWA standard font for the third line.
- M is the space between the third and fourth lines.
- N is the letter height and FHWA standard font for the fourth line.
- P is the distance from the bottom of the last line to the bottom of the sign.
- Q is the distance from the vertical center of the sign to the left edge of the word on the first line.
- R is the distance from the vertical center of the sign to the right edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the arrow symbol.
- T is the distance from the vertical center of the sign to the left edge of the arrow symbol.
- U is the width of the arrow shaft.
- V is the length of the vertical section of the arrow shaft.
- W is the distance from the top of the vertical section of the arrow shaft to the tip of the arrowhead.
- X is the radius of the first and second sections of the spiral curve. The first section subtends an angle of 90 degrees clockwise from the top of the vertical section of the arrow shaft to the vertical center of the sign, and the second section subtends an additional 75 degrees.
- Y is the distance from the vertical center of the sign to the end of the spiral curve.
- Z is the distance from the center of the third section of the spiral curve in the arrow shaft to the top of the sign.
- AA is the radius of the third section of the spiral curve in the arrow shaft, which subtends an angle of 105 degrees.
- BB is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- CC is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- DD is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- EE is the width of the arrowhead.
- GG is the corner radius.

W13-8: Combination Horizontal Alignment/ Advisory Exit Speed - 180-degree Loop

W13-8R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the intersection of the vertical center of the sign and the centerline of the arrow at the top of the curve.
- J is the radius of the centerline of the curve in the arrow shaft, from the base of the curve to the end of the curve, and the vertical distance from the apex of the curve centerline to the base of the arrowhead.
- K is the height of the length of the arrowhead.
- L is the space between the second and third lines.
- M is the letter height and FHWA standard font for the third line.
- N is the space between the third and fourth lines.
- P is the letter height and FHWA standard font for the fourth line.
- Q is the distance from the bottom of the last line to the bottom of the sign.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance to the left from the vertical center of the sign to the center of the curve in the arrow.
- U is the width of the arrow shaft.
- V is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- W is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- X is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- Y is the width of the arrowhead.
- Z is the corner radius.

W13-8L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.

- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the intersection of the vertical center of the sign and the centerline of the arrow at the top of the curve.
- J is the radius of the centerline of the curve in the arrow shaft, from the base of the curve to the end of the curve, and the vertical distance from the apex of the curve centerline to the base of the arrowhead.
- K is the height of the length of the arrowhead.
- L is the space between the second and third lines.
- M is the letter height and FHWA standard font for the third line.
- N is the space between the third and fourth lines.
- P is the letter height and FHWA standard font for the fourth line.
- Q is the distance from the bottom of the last line to the bottom of the sign.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance to the right from the vertical center of the sign to the center of the curve in the arrow.
- U is the width of the arrow shaft.
- V is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- W is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- X is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- Y is the width of the arrowhead.
- Z is the corner radius.

W13-9: Combination Horizontal Alignment/ Advisory Ramp Speed - 180-degree Loop

W13-9R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the intersection of the vertical center of the sign and the centerline of the arrow at the top of the curve.
- J is the radius of the centerline of the curve in the arrow shaft, from the base of the curve to the end of the curve, and the vertical distance from the apex of the curve centerline to the base of the arrowhead.
- K is the height of the length of the arrowhead.
- L is the space between the second and third lines.
- M is the letter height and FHWA standard font for the third line.
- N is the space between the third and fourth lines.
- P is the letter height and FHWA standard font for the fourth line.
- Q is the distance from the bottom of the last line to the bottom of the sign.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance to the left from the vertical center of the sign to the center of the curve in the arrow.
- U is the width of the arrow shaft.
- V is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- W is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- X is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- Y is the width of the arrowhead.
- Z is the corner radius.

W13-9L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.

- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the intersection of the vertical center of the sign and the centerline of the arrow at the top of the curve.
- J is the radius of the centerline of the curve in the arrow shaft, from the base of the curve to the end of the curve, and the vertical distance from the apex of the curve centerline to the base of the arrowhead.
- K is the height of the length of the arrowhead.
- L is the space between the second and third lines.
- M is the letter height and FHWA standard font for the third line.
- N is the space between the third and fourth lines.
- P is the letter height and FHWA standard font for the fourth line.
- Q is the distance from the bottom of the last line to the bottom of the sign.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance to the right from the vertical center of the sign to the center of the curve in the arrow.
- U is the width of the arrow shaft.
- V is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- W is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- X is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- Y is the width of the arrowhead.
- Z is the corner radius.

W13-10: Combination Horizontal Alignment/ Advisory Exit Speed - Turn

W13-10R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the base of the arrow and the word on the last line.
- L is the letter height and FHWA standard font for the word on the last line.
- M is the distance from the bottom of the word on the last line to the bottom of the sign.
- N is the space between the number on the third line and the word on the last line.
- P is the letter height and FHWA standard font for the number on the third line.
- Q is the distance from the top of the number to the bottom barb of the arrowhead.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance from the vertical center of the sign to the left edge of the arrow shaft.
- U is the distance from the vertical center of the sign to the tip of the arrowhead.
- V is the outer radius of the curve in the arrow shaft.
- W is the inner radius of the curve in the arrow shaft.
- X is the distance from the vertical center of the content on the last two lines to the left and right edges of the number on the third line.
- Y is the distance from the vertical center of the content on the last two lines to the left edge of the word on the last line.
- Z is the distance from the vertical center of the content on the last two lines to the right edge of the word on the last line.
- AA is the width of the arrow shaft.
- BB is the width of the arrowhead.
- CC is the distance from the vertical center of the sign to the vertical center of the content on the last two lines.
- DD is the corner radius.

W13-10L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.

- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the base of the arrow and the word on the last line.
- L is the letter height and FHWA standard font for the word on the last line.
- M is the distance from the bottom of the word on the last line to the bottom of the sign.
- N is the space between the number on the third line and the word on the last line.
- P is the letter height and FHWA standard font for the number on the third line.
- Q is the distance from the top of the number to the bottom barb of the arrowhead.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance from the vertical center of the sign to the right edge of the arrow shaft.
- U is the distance from the vertical center of the sign to the tip of the arrowhead.
- V is the outer radius of the curve in the arrow shaft.
- W is the inner radius of the curve in the arrow shaft.
- X is the distance from the vertical center of the content on the last two lines to the left and right edges of the number on the third line.
- Y is the distance from the vertical center of the content on the last two lines to the left edge of the word on the last line.
- Z is the distance from the vertical center of the content on the last two lines to the right edge of the word on the last line.
- AA is the width of the arrow shaft.
- BB is the width of the arrowhead.
- CC is the distance from the vertical center of the sign to the vertical center of the content on the last two lines.
- DD is the corner radius.

W13-11: Combination Horizontal Alignment/ Advisory Ramp Speed - Turn

W13-11R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the base of the arrow and the word on the last line.
- L is the letter height and FHWA standard font for the word on the last line.
- M is the distance from the bottom of the word on the last line to the bottom of the sign.
- N is the space between the number on the third line and the word on the last line.
- P is the letter height and FHWA standard font for the number on the third line.
- Q is the distance from the top of the number to the bottom barb of the arrowhead.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance from the vertical center of the sign to the left edge of the arrow shaft.
- U is the distance from the vertical center of the sign to the tip of the arrowhead.
- V is the outer radius of the curve in the arrow shaft.
- W is the inner radius of the curve in the arrow shaft.
- X is the distance from the vertical center of the content on the last two lines to the left and right edges of the number on the third line.
- Y is the distance from the vertical center of the content on the last two lines to the left edge of the word on the last line.
- Z is the distance from the vertical center of the content on the last two lines to the right edge of the word on the last line.
- AA is the width of the arrow shaft.
- BB is the width of the arrowhead.
- CC is the distance to the right from the vertical center of the sign to the vertical center of the content on the last two lines.
- DD is the corner radius.

W13-11L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.

- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom edge of the dividing line to the top of the arrow symbol.
- J is the height of the arrow symbol.
- K is the space between the base of the arrow and the word on the last line.
- L is the letter height and FHWA standard font for the word on the last line.
- M is the distance from the bottom of the word on the last line to the bottom of the sign.
- N is the space between the number on the third line and the word on the last line.
- P is the letter height and FHWA standard font for the number on the third line.
- Q is the distance from the top of the number to the bottom barb of the arrowhead.
- R is the distance from the vertical center of the sign to the left edge of the word on the first line.
- S is the distance from the vertical center of the sign to the right edge of the word on the first line.
- T is the distance from the vertical center of the sign to the right edge of the arrow shaft.
- U is the distance from the vertical center of the sign to the tip of the arrowhead.
- V is the outer radius of the curve in the arrow shaft.
- W is the inner radius of the curve in the arrow shaft.
- X is the distance from the vertical center of the content on the last two lines to the left and right edges of the number on the third line.
- Y is the distance from the vertical center of the content on the last two lines to the left edge of the word on the last line.
- Z is the distance from the vertical center of the content on the last two lines to the right edge of the word on the last line.
- AA is the width of the arrow shaft.
- BB is the width of the arrowhead.
- CC is the distance to the left from the vertical center of the sign to the vertical center of the content on the last two lines.
- DD is the corner radius.

W13-12: Combination Horizontal Alignment/ Advisory Exit Speed - Truck Rollover

W13-12R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol on the second line.
- J is the distance from the base of the curve to the top of the arrow symbol on the second line.
- K is the length of the straight vertical section of the arrow shaft at its base.
- L is the distance from the bottom of the arrow shaft to the top of the road surface line.
- M is the width of the road surface line.
- N is the distance from the bottom of the road surface line to the top of the number on the third line.
- P is the letter height and FHWA standard font for the third line.
- Q is the space between the third and fourth lines.
- R is the letter height and FHWA standard font for the fourth line.
- S is the distance from the bottom of the last line to the bottom of the sign.
- T is the distance from the bottom of the tractor-trailer symbol to the tip of the arrowhead.
- U is the length of the straight section of the arrow shaft from the end of the curve to the base of the arrowhead.
- V is the distance from the vertical center of the sign to the left edge of the word on the first line.
- W is the distance from the vertical center of the sign to the right edge of the word on the first line.
- X is the distance to the right from the vertical center of the sign to the right edge of the arrow symbol.
- Y is the distance from the bottom of the right outer tire to the top right corner of the tractor-trailer.
- Z is the radius of the curve at the centerline of the arrow shaft.
- AA is width of the arrow shaft.
- BB is the distance from the vertical center of the sign to the top left corner of the tractor-trailer.
- CC is the distance from the vertical center of the sign to the left edge of the road surface line.
- DD is the distance from the vertical center of the sign to the right edge of the road surface line.

- EE is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- FF is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- GG is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- HH is the width of the arrowhead.
- JJ is the corner radius.

W13-12L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol on the second line.
- J is the distance from the base of the curve to the top of the arrow symbol on the second line.
- K is the length of the straight vertical section of the arrow shaft at its base.
- L is the distance from the bottom of the arrow shaft to the top of the road surface line.
- M is the width of the road surface line.
- N is the distance from the bottom of the road surface line to the top of the number on the third line.
- P is the letter height and FHWA standard font for the third line.
- Q is the space between the third and fourth lines.
- R is the letter height and FHWA standard font for the fourth line.
- S is the distance from the bottom of the last line to the bottom of the sign.
- T is the distance from the bottom of the tractor-trailer symbol to the tip of the arrowhead.
- U is the length of the straight section of the arrow shaft from the end of the curve to the base of the arrowhead.
- V is the distance from the vertical center of the sign to the left edge of the word on the first line.
- W is the distance from the vertical center of the sign to the right edge of the word on the first line.
- X is the distance to the left from the vertical center of the sign to the left edge of the arrow symbol.
- Y is the distance from the bottom of the right outer tire to the top right corner of the tractor-trailer.
- Z is the radius of the curve at the centerline of the arrow shaft.
- AA is width of the arrow shaft.

- BB is the distance from the vertical center of the sign to the top left corner of the tractor-trailer.
- CC is the distance from the vertical center of the sign to the left edge of the road surface line.
- DD is the distance from the vertical center of the sign to the right edge of the road surface line.
- EE is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- FF is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- GG is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- HH is the width of the arrowhead.
- JJ is the corner radius.

W13-13: Combination Horizontal Alignment/ Advisory Ramp Speed - Truck Rollover

W13-13R

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol on the second line.
- J is the distance from the base of the curve to the top of the arrow symbol on the second line.
- K is the length of the straight vertical section of the arrow shaft at its base.
- L is the distance from the bottom of the arrow shaft to the top of the road surface line.
- M is the width of the road surface line.
- N is the distance from the bottom of the road surface line to the top of the number on the third line.
- P is the letter height and FHWA standard font for the third line.
- Q is the space between the third and fourth lines.
- R is the letter height and FHWA standard font for the fourth line.
- S is the distance from the bottom of the last line to the bottom of the sign.
- T is the distance from the bottom of the tractor-trailer symbol to the tip of the arrowhead.
- U is the length of the straight section of the arrow shaft from the end of the curve to the base of the arrowhead.
- V is the distance from the vertical center of the sign to the left edge of the word on the first line.
- W is the distance from the vertical center of the sign to the right edge of the word on the first line.
- X is the distance to the right from the vertical center of the sign to the right edge of the arrow symbol.
- Y is the distance from the bottom of the right outer tire to the top right corner of the tractor-trailer.
- Z is the radius of the curve at the centerline of the arrow shaft.
- AA is width of the arrow shaft.
- BB is the distance from the vertical center of the sign to the top left corner of the tractor-trailer.
- CC is the distance from the vertical center of the sign to the left edge of the road surface line.
- DD is the distance from the vertical center of the sign to the right edge of the road surface line.

- EE is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- FF is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- GG is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- HH is the width of the arrowhead.
- JJ is the corner radius.

W13-13L

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width and the width of the dividing line.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the distance from the bottom of the first line to the top edge of the dividing line.
- H is the distance from the bottom of the dividing line to the top of the arrow symbol on the second line.
- J is the distance from the base of the curve to the top of the arrow symbol on the second line.
- K is the length of the straight vertical section of the arrow shaft at its base.
- L is the distance from the bottom of the arrow shaft to the top of the road surface line.
- M is the width of the road surface line.
- N is the distance from the bottom of the road surface line to the top of the number on the third line.
- P is the letter height and FHWA standard font for the third line.
- Q is the space between the third and fourth lines.
- R is the letter height and FHWA standard font for the fourth line.
- S is the distance from the bottom of the last line to the bottom of the sign.
- T is the distance from the bottom of the tractor-trailer symbol to the tip of the arrowhead.
- U is the length of the straight section of the arrow shaft from the end of the curve to the base of the arrowhead.
- V is the distance from the vertical center of the sign to the left edge of the word on the first line.
- W is the distance from the vertical center of the sign to the right edge of the word on the first line.
- X is the distance to the left from the vertical center of the sign to the left edge of the arrow symbol.
- Y is the distance from the bottom of the right outer tire to the top right corner of the tractor-trailer.
- Z is the radius of the curve at the centerline of the arrow shaft.
- AA is width of the arrow shaft.

- BB is the distance from the vertical center of the sign to the top left corner of the tractor-trailer.
- CC is the distance from the vertical center of the sign to the left edge of the road surface line.
- DD is the distance from the vertical center of the sign to the right edge of the road surface line.
- EE is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- FF is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- GG is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- HH is the width of the arrowhead.
- JJ is the corner radius.

W13-20: Vehicle Speed Feedback

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the first and second lines.
- H is the letter height and FHWA standard font for the second line.
- J is the space between the second and third lines.
- K is the height of the black panel on the third line.
- L is the distance from the bottom of the black panel to the bottom of the sign.
- M is the distance from the vertical center of the sign to the left edge of the word on the first line.
- N is the distance from the vertical center of the sign to the right edge of the word on the first line.
- P is the distance from the vertical center of the sign to the left edge of the word on the second line.
- Q is the distance from the vertical center of the sign to the right edge of the word on the second line.
- R is the distance from the vertical center of the sign to the left and right edges of the black panel on the third line.
- S is the distance from the vertical center of the sign to the left and right edges of the number on the third line.
- T is the height of the number on the third line.
- U is the corner radius.

W13-20aP: Vehicle Speed Feedback (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the first line and the panel.
- H is the distance from the vertical center of the sign to the left and right edges of the panel.
- J is the distance from the bottom of the panel to the bottom of the plaque.
- K is the width of the first word on the first line.
- L is the distance from the vertical center of the plaque to the right edge of the first word on the first line.
- M is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- N is the width of the second word on the first line.
- P is the is the distance from the vertical center of the plaque to the left and right edges of the number in the panel.
- Q is the letter height and FHWA standard font for the number in the panel.
- R is the corner radius.

W14-1: Dead End

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W14-1a: Dead End (with arrow)

W14-1aL

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the sign and from the bottom of the line to the bottom of the sign.
- F is the letter height and FHWA standard font for the line.
- G is the length of the arrow.
- H is the space between the arrow and the first word and between the words.
- J is the distance from the vertical center of the sign to the left edge of the first word.
- K is the distance from the vertical center of the sign to the right edge of the first word.
- L is the width of the second word.
- Q is the width of the arrowhead.
- R is the corner radius.

W14-1aR

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the sign and from the bottom of the line to the bottom of the sign.
- F is the letter height and FHWA standard font for the line.
- G is the length of the arrow.
- H is the space between the words and between the second word and the arrow.
- M is the width of the first word.
- N is the distance from the vertical center of the sign to the left edge of the second word.
- P is the distance from the vertical center of the sign to the right edge of the second word.
- Q is the width of the arrowhead.
- R is the corner radius.

W14-2: No Outlet

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the corner radius.

W14-2a: No Outlet (with arrow)

W14-2aR

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the sign and from the bottom of the line to the bottom of the sign.
- F is the letter height and FHWA standard font for the line.
- G is the length of the arrow.
- H is the space between the words and between the second word and the arrow.
- J is the width of the first word.
- N is the distance from the vertical center of the sign to the left edge of the second word.
- P is the distance from the vertical center of the sign to the right edge of the second word.
- Q is the width of the arrowhead.
- R is the corner radius.

W14-2aL

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the sign and from the bottom of the line to the bottom of the sign.
- F is the letter height and FHWA standard font for the line.
- G is the length of the arrow.
- H is the space between the arrow and the first word and between the words.
- J is the width of the first word.
- K is the distance from the vertical center of the sign to the right edge of the first word.
- L is the distance from the vertical center of the sign to the left edge of the second word.
- M is the width of the second word.
- Q is the width of the arrowhead.
- R is the corner radius.

W14-3: No Passing Zone

- A is the dimension of the top and bottom diagonal edges of the sign as measured between the intersections of lines extending from the each edge of the sign.
- B is the dimension of the vertical edge of the sign as measured between the intersections of lines extending from the each edge of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the letter height and FHWA standard font for the second line.
- H is the letter height and FHWA standard font for the third line.
- J is the space between each line.
- K is the distance from the left edge of the sign to the left edge of each word.
- L is the width of the word on the first line.
- M is the width of the word on the second line.
- N is the width of the word on the third line.
- P is the corner radius.

W15-1: Playground

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the distance from the horizontal center of the sign to the top of the symbol.
- E is the distance from the horizontal center of the sign to the bottom of the symbol.
- F is the corner radius.

W16-1P: In Road (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the first line.
- J is the distance from the vertical center of the plaque to the right edge of the first line.
- K is the distance from the vertical center of the plaque to the left and right edges of the second line.
- L is the corner radius.

W16-1aP: In Street (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the first line.
- J is the distance from the vertical center of the plaque to the right edge of the first line.
- K is the distance from the vertical center of the plaque to the left and right edges of the second line.
- L is the corner radius.

W16-2P: XX Feet (2-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the sign to the left and right edges of the number on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W16-2aP: XX Ft (1-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left and right edges of the line.
- H is the space between the number and the word.
- J is the width of the word.
- K is the corner radius.

W16-3P: XX Miles (2-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first and second lines.
- G is space between the lines.
- H is the distance from the vertical center of the sign to the left and right edges of the number on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W16-3aP: XX Miles (1-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left and right edges of the line.
- H is the width of the number.
- J is the space between the number and the word.
- K is the width of the word.
- L is the corner radius.

W16-4P: Next XX Feet (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left and right edges of the word on the first line.
- J is the distance from the vertical center of the plaque to the left and right edges of the second line.
- K is the width of the first word on the second line.
- L is the space between the words on the second line.
- M is the width of the second word on the second line.
- N is the corner radius.

W16-5P: Directional Arrow (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is distance from the top of the arrow shaft to the top of the plaque.
- F is arrow shaft width.
- G is the distance from the bottom of the arrow shaft to the bottom of the plaque.
- H is the distance from the tip of the arrowhead to the top and bottom of the plaque
- J is the distance from the vertical center of the plaque to the base of the arrow shaft on the first plaque and to the tip of the arrowhead of the second plaque.
- K is the distance from the vertical center of the plaque to the tip of the arrow on the second plaque and to the base of the arrow shaft on the second sign.
- L is the arrowhead width.
- M is the corner radius.

W16-6P: Advance Turn Arrow (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the arrow symbol to the top of the plaque.
- F is the distance from the top of the horizontal portion of the arrow shaft to the top of the arrow symbol
- G is the distance from the base of the arrow shaft to the top horizontal edge of the shaft.
- H is the distance from the base of the shaft to the bottom of the plaque.
- J is the distance from the vertical center of the plaque to the tip of the arrowhead.
- K is the distance from the vertical center of the plaque to the vertical edge of the arrow shaft.
- L is the width of the arrow shaft.
- M is the radius of the outer corner of the bend in the arrow shaft.
- N is the radius of the inner corner of the bend in the arrow shaft.
- P is the distance from the vertical center of the plaque to the inner edge of the arrow shaft.
- Q is the width of the arrowhead.
- R is the sign corner radius.

W16-7P: Downward Diagonal Arrow (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the tip of the arrowhead to the bottom of the plaque.
- F is the distance from the vertical center of the plaque to the tip of the arrowhead.
- G is the length of the arrow.
- J is the angle of the arrow from horizontal.
- K is the corner radius.

W16-7aP: Dual Downward Diagonal Arrow (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the plaque to the intersection of the vertical center of the plaque with the arrow centerlines.
- F is the distance from the tips of the arrowheads to the intersection of the vertical center of the sign with the arrow centerlines, and the distance from the vertical center of the plaque to the left and right tips of the arrowheads.
- G is the distance from the bottom of the arrows to the bottom of the plaque
- H is the width of the arrow shaft.
- J is the corner radius.

W16-8P: Advance Street Name (1-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the left edge of the first word to the left edge of the plaque and from the right edge of the second word to the right edge of the plaque.
- H is the width of the first word.
- J is the space between the words.
- K is the width of the second word.
- L is the corner radius.

W16-8aP: Advance Street Name (2-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the words on the first line and the arrow symbol on the second line and between the words on the second line and the arrow symbol on the first line.
- H is the height of each arrow symbol.
- J is the distance from the tip of the arrowhead on the first line to the left edge of the plaque.
- K is the width of each arrow symbol.
- L is the space between the arrow and the words on each line.
- M is the width of the first word on the first line.
- N is the space between the words on each line.
- P is the width of the second word on the first line.
- Q is the distance from the right edge of the second word on the first line to the right edge of the plaque.
- R is the distance from the left edge of the first word on the second line to the left edge of the plaque and from the right edge of the first word on the second line to the right edge of the plaque.
- S is the width of the first word on the second line.
- T is the width of the second word on the second line.
- U is the corner radius.

W16-9P: Ahead (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the sign to the left edge of the word on the line.
- H is the distance from the vertical center of the sign to the right edge of the word on the line.
- J is the corner radius.

W16-10P: Photo Enforced (symbol plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the symbol to the top of the plaque.
- F is the height of the symbol.
- G is the distance from the bottom of the symbol to the bottom of the plaque
- H is the corner radius.

W16-10aP: Photo Enforced (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- L is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- M is the corner radius.

W16-11P: High-Occupancy Vehicles (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the word on the line.
- G is the distance from the vertical center of the plaque to the left edge of the word on the line.
- H is the distance from the vertical center of the plaque to the right edge of the word on the line.
- J is the corner radius.

W16-12P: Traffic Circle (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- L is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- M is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- N is the corner radius.

W16-12aP: Roundabout (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left edge of the word on the line.
- H is the distance from the vertical center of the plaque to the right edge of the word on the line.
- J is the corner radius.

W16-13P: When Flashing (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the second line.
- J is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- K is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- L is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- M is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- N is the corner radius.

W16-15P: New (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left and right edges of the line.
- H is the corner radius.

W16-16P: Last Exit Before Toll (1-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque, the distance from the bottom of the line to the bottom of the plaque, and the space between the words.
- F is the letter height and FHWA standard font for the line.
- G is the width of the first word.
- H is the width of the second word.
- J is the distance from the vertical center of the plaque to the left edge of the third word.
- K is the distance from the vertical center of the plaque to the right edge of the third word.
- L is the width of the fourth word.
- M is the corner radius.

W16-16aP: Last Exit Before Toll (2-line plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the width of the first word on the first line.
- J is the distance from the vertical center of the plaque to the right edge of the first word on the first line.
- K is the distance from the vertical center of the plaque to the left edge of the second word on the first line.
- L is the width of the second word on the first line.
- M is the distance from the vertical center of the plaque to the left edge of the first word on the second line.
- N is the distance from the vertical center of the plaque to the right edge of the first word on the second line.
- P is the space between the words on the second line.
- Q is the width of the second word on the second line.
- R is the corner radius.

W16-17P: Toll (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left edge of the word.
- H is the distance from the vertical center of the plaque to the right edge of the word.
- J is the corner radius.

W16-18P: Notice (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the line to the top of the plaque and from the bottom of the line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the line.
- G is the distance from the vertical center of the plaque to the left and right edges of the word.
- H is the corner radius.

W16-19P: Last In Corridor (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines and between the words on the first line.
- H the letter height and FHWA standard font for the second line
- J is the distance from the vertical center of the plaque to the left edge of the first word on the first line.
- K is the distance from the vertical center of the plaque to the right edge of the first word the first line.
- L is the width of the second word on the first line.
- M is the distance from the vertical center of the plaque to the left edge of the word on the second line.
- N is the distance from the vertical center of the plaque to the right edge of the word on the second line.
- P is the corner radius.

W16-20P: Except Bicycles (Plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque, the distance from the bottom of the last line to the bottom of the plaque, and the space between the lines.
- F is the letter height and FHWA standard font for each line.
- G is the distance from the vertical center of the plaque to the left edge of the word on the first line.
- H is the distance from the vertical center of the plaque to the right edge of the word on the first line.
- J is the distance from the vertical center of the plaque to the left and right edges of the word on the second line.
- K is the corner radius.

W16-21P: 2-Way Bicycle Cross Traffic (plaque)

- A is the horizontal dimension of the plaque.
- B is the vertical dimension of the plaque.
- C is the inset from the edge of the plaque to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the plaque and from the bottom of the last line to the bottom of the plaque.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the width of the number on the first line.
- J is the space between the number and the hyphen on the first line.
- K is the width of the hyphen on the first line.
- L is the space between the hyphen and the first word on the first line.
- M is the width of the first word on the first line.
- N is the distance from the vertical center of the plaque to the right edge of the first word on the first line and the corner radius.
- P is the width of the second word on the first line.
- Q is the width of the first word on the second line.
- R is the space between the words on the second line.
- S is the distance from the vertical center of the plaque to the left edge of the second word on the second line.
- T is the distance from the vertical center of the plaque to the right edge of the second word on the second line.

W17-1: Speed Hump

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W18-1: No Traffic Signs

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines.
- F is the distance from the horizontal center of the sign to the top of the second line.
- G is the distance from the horizontal center of the sign to the bottom of the second line.
- H is the distance from the vertical center of the sign to the left edge of the word on the first line.
- J is the distance from the vertical center of the sign to the right edge of the word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the word on the third line.
- P is the corner radius.

W19-1: Freeway Ends XX Miles

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line and for the word on the second line.
- G is the space between the lines.
- H is the space between the words and number and the distance from the bottom of the word on the last line to the bottom of the sign.
- J is the distance from the bottom of the number on the last line to the bottom of the sign.
- K is the letter height and FHWA standard font for the number on the second line.
- L is the distance from the vertical center of the sign to the left edge of the first word on the first line.
- M is the distance from the vertical center of the sign to the right edge of the first word on the first line.
- N is the width of the second word on the first line.
- P is the distance from the vertical center of the sign to the left and right edges of the second line.
- Q is the width of the number on the second line
- R is the width of the word on the second line.
- S is the corner radius.

W19-2: Expressway Ends XX Miles

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign.
- F is the letter height and FHWA standard font for the first line.
- G is the space between the lines.
- H is the letter height and FHWA standard font for the word on the second line.
- J is the space between the words and number and the distance from the bottom of the word on the last line to the bottom of the sign.
- K is the distance from the bottom of the number on the last line to the bottom of the sign.
- L is the letter height and FHWA standard font for the number on the second line.
- M is the distance from the vertical center of the sign to the left edge of the first word on the first line.
- N is the distance from the vertical center of the sign to the right edge of the first word on the first line.
- P is the width of the second word on the first line.
- Q is the distance from the vertical center of the sign to the left and right edges of the second line.
- R is the width of the number on the second line
- S is the width of the word on the second line.
- T is the corner radius.

W19-3: Freeway Ends

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the top of the first line.
- F is the distance from the horizontal center of the sign to the bottom of the first line.
- G is the space between the lines.
- H is the distance from the vertical center of the sign to the left and right edges of the first line.
- J is the distance from the vertical center of the sign to the left edge of the second line.
- K is the distance from the vertical center of the sign to the right edge of the second line.
- L is the corner radius.

W19-4: Expressway Ends

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the distance from the horizontal center of the sign to the top and bottom of the first line.
- F is the space between the lines.
- G is the distance from the vertical center of the sign to the left edge of the word on the first line.
- H is the distance from the vertical center of the sign to the right edge of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the corner radius.

W19-5: All Traffic Must Exit

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines and the space between the words on the first line.
- H is the width of the first word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the second word on the first line.
- K is the distance from the vertical center of the sign to the right edge of the second word on the first line.
- L is the width of the first word on the second line.
- M is the distance from the vertical center of the sign to the right edge of the first word on the second line.
- N is the distance from the vertical center of the sign to the left edge of the second word on the second line.
- P is the width of the second word on the second line.
- Q is the corner radius.

W23-2: New Traffic Pattern Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font on each line. The top of the word on the third line is aligned with the horizontal center of the sign.
- E is the space between the lines.
- F is the distance from the vertical center of the sign to the left edge of the word on the first line.
- G is the distance from the vertical center of the sign to the right edge of the word on the first line.
- H is the distance from the vertical center of the sign to the left edge of the word on the second line.
- J is the distance from the vertical center of the sign to the right edge of the word on the second line.
- K is the distance from the vertical center of the sign to the left edge of the word on the third line.
- L is the distance from the vertical center of the sign to the right edge of the word on the third line.
- M is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- N is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- P is the corner radius.

W23-2a: New Signal Operation Ahead

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines and the distance from the horizontal center of the sign to the bottom of the second line.
- F is the distance from the vertical center of the sign to the left edge of the word on the first line.
- G is the distance from the vertical center of the sign to the right edge of the word on the first line.
- H is the distance from the vertical center of the sign to the left edge of the word on the second line.
- J is the distance from the vertical center of the sign to the right edge of the word on the second line.
- K is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- L is the distance from the vertical center of the sign to the left edge of the word on the fourth line.
- M is the distance from the vertical center of the sign to the right edge of the word on the fourth line.
- N is the corner radius.

W25-1: Oncoming Traffic Has Extended Green

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the distance from the vertical center of the sign to the left and right edges of the word on the third line.
- M is the distance from the vertical center of the sign to the left and right edges of the word on the fourth line.
- N is the distance from the vertical center of the sign to the left and right edges of the word on the fifth line.
- P is the corner radius.

W25-2: Oncoming Traffic May Have Extended Green

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the inset from the edge of the sign to the border.
- D is the border width.
- E is the distance from the top of the first line to the top of the sign and from the bottom of the last line to the bottom of the sign.
- F is the letter height and FHWA standard font for each line.
- G is the space between the lines.
- H is the distance from the vertical center of the sign to the left and right edges of the word on the first line.
- J is the distance from the vertical center of the sign to the left edge of the word on the second line and the width of the first word on the third line.
- K is the distance from the vertical center of the sign to the right edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the first word on the third line.
- M is the distance from the vertical center of the sign to the left edge of the second word on the third line.
- N is the width of the second word on the third line.
- P is the distance from the vertical center of the sign to the left and right edges of the word on the fourth line.
- Q is the distance from the vertical center of the sign to the left and right edges of the word on the fifth line.
- R is the corner radius.

W26-1: Watch For Stopped Traffic

- A is the length of each edge of the sign.
- B is the inset from the edge of the sign to the border.
- C is the border width.
- D is the letter height and FHWA standard font for each line.
- E is the space between the lines and the distance from the horizontal center of the sign to the bottom of the first line.
- F is the distance from the vertical center of the sign to the left edge of the first word on the first line.
- G is the distance from the vertical center of the sign to the right edge of the first word on the first line.
- H is the space between the words on the first line.
- J is the width of the second word on the first line.
- K is the distance from the vertical center of the sign to the left edge of the word on the second line.
- L is the distance from the vertical center of the sign to the right edge of the word on the second line.
- M is the distance from the vertical center of the sign to the left edge of the word on the third line.
- N is the distance from the vertical center of the sign to the right edge of the word on the third line.
- P is the corner radius.

OM1-1: Object Marker Type 1

- A is the length of each edge of the sign.
- B is the height of each horizontal line of circles and the width of each vertical line of circles.
- C is the vertical space between the horizontal lines of circles and the horizontal space between the vertical lines of circles.
- D is the distance from the vertical center of the sign to the left and right edges of the circles on the third vertical line, the distance from the horizontal center of the sign to the top and bottom of the circles on the third vertical line, and the corner radius.

OM1-2: Object Marker Type 1

- A is the length of each edge of the sign.
- B is the height of each horizontal line of circles and the width of each vertical line of circles.
- C is the vertical space between the horizontal lines of circles and the horizontal space between the vertical lines of circles.
- D is the distance from the vertical center of the sign to the left and right edges of the circles on the third vertical line, the distance from the horizontal center of the sign to the top and bottom of the circles on the third vertical line, and the corner radius.

OM1-3: Object Marker Type 1

- A is the length of each edge of the sign.
- B is the corner radius.

OM2-1V: Object Marker Type 2

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the distance from the top of the first circle to the top of the sign, the space between the circles, and the distance from the bottom of the third circle to the bottom of the sign.
- D is the height of each circle.
- E is the distance from the horizontal center of the sign to the top and bottom of the second circle and the radius of each circle.
- F is the corner radius.

OM2-1H: Object Marker Type 2

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the distance from the left edge of the first circle to the left edge of the sign, the space between the circles, and the distance from the right edge of the third circle to the right edge of the sign.
- D is the width of each circle.
- E is the distance from the vertical center of the sign to the left and right edges of the second circle and the radius of each circle.
- F is the corner radius.

OM2-2V: Object Marker Type 2

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign
- C is the corner radius.

OM2-2H: Object Marker Type 2

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the corner radius.

OM3-R: Object Marker Type 3

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the vertical distance from the top of the sign to the right end of the centerline of the third black stripe.
- D is the vertical distance between the centerlines of the third and fourth black stripes.
- E is the vertical distance between the centerlines of the first and second black stripes and between the fourth, fifth, and sixth black stripes.
- F is the vertical distance from the right end of the centerline of the sixth black stripe to the bottom of the sign.
- G is the vertical distance from the left end of the centerline of the first black stripe to the top of the sign.
- H is the width of each black stripe.
- J is the space between each black stripe.
- K is the corner radius.

OM3-C: Object Marker Type 3

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign
- C is the distance from the top of the sign to the right end of the centerline of the first chevron.
- D is the vertical distance between the centerlines of the first and second chevrons.
- E is the vertical distance between the centerlines of the second, third, and fourth chevrons.
- F is the vertical distance from the right end of the centerline of the fourth chevron to the peak of the centerline of the fifth chevron.
- G is the distance from the peak of the centerline of the fifth chevron to the bottom of the sign.
- H is the width of each black line in each chevron.
- J is the space between the chevrons, measured perpendicular to the their edges.
- K is the corner radius.

OM3-L: Object Marker Type 3

- A is the horizontal dimension of the sign.
- B is the vertical dimension of the sign.
- C is the vertical distance from the top of the sign to the left end of the centerline of the third black stripe.
- D is the vertical distance between the centerlines of the third and fourth black stripes.
- E is the vertical distance between the centerlines of the first and second black stripes and between the fourth, fifth, and sixth black stripes.
- F is the vertical distance from the left end of the centerline of the sixth black stripe to the bottom of the sign.
- G is the vertical distance from the top of the sign to the right end of the centerline of the first black stripe.
- H is the width of each black stripe.
- J is the space between each black stripe.
- K is the corner radius.

OM4-1: Object Marker Type 4

- A is the length of each edge of the sign.
- B is the height of each horizontal line of circles and the width of each vertical line of circles.
- C is the vertical space between the horizontal lines of circles and the horizontal space between the vertical lines of circles.
- D is the distance from the vertical center of the sign to the left and right edges of the circles on the third vertical line, the distance from the horizontal center of the sign to the top and bottom of the circles on the third vertical line, and the corner radius.

OM4-2: Object Marker Type 4

- A is the length of each edge of the sign.
- B is the height of each horizontal line of circles and the width of each vertical line of circles.
- C is the vertical space between the horizontal lines of circles and the horizontal space between the vertical lines of circles.
- D is the distance from the vertical center of the sign to the left and right edges of the circles on the third vertical line, the distance from the horizontal center of the sign to the top and bottom of the circles on the third vertical line, and the corner radius.

OM4-3: Object Marker Type 4

- A is the length of each edge of the sign.
- B is the corner radius.