查表

`use mysql;`

`select Host,User,Password,Select_priv,Grant_priv from user;`

```
mysql> use mysql
Database changed
mysql> select Host,User,Password,Select_priv,Grant_priv from user;
+-----------+------+-------------------------------------------+-------------+--
----------+
| Host      | User | Password                                  | Select_priv | G
rant_priv |
+-----------+------+-------------------------------------------+-------------+--
----------+
| localhost | root | *6BB4837EB74329105EE4568DDA7DC67ED2CA2AD9 | Y           | Y
          |
| %         | root | *6BB4837EB74329105EE4568DDA7DC67ED2CA2AD9 | Y           | Y
          |
+-----------+------+-------------------------------------------+-------------+--
----------+
2 rows in set (0.00 sec)
```

更改密码

`update user set password=password<'123456'> where user='root';`

`flush privileges;`

```
mysql> update user set password=password('123456') where user='root';
Query OK, 0 rows affected (0.00 sec)
Rows matched: 2  Changed: 0  Warnings: 0

mysql> flush privileges;
Query OK, 0 rows affected (0.00 sec)
```

删除空用户

`delete from user where user='';`

`flush privileges;`

```
mysql>
mysql> delete from user where user='';
Query OK, 0 rows affected (0.00 sec)

mysql> flush privileges;
Query OK, 0 rows affected (0.00 sec)
```

看user表

`desc user;`

```
mysql> desc user;
+-----------------------+---------------------------------+------+-----+-----
----+-------+
| Field                 | Type                            | Null | Key | Defa
ult | Extra |
+-----------------------+---------------------------------+------+-----+-----
----+-------+
| Host                  | char(60)                        | NO   | PRI |
    |       |
| User                  | char(16)                        | NO   | PRI |
    |       |
| Password              | char(41)                        | NO   |     |
    |       |
| Select_priv           | enum('N','Y')                   | NO   |     | N
    |       |
| Insert_priv           | enum('N','Y')                   | NO   |     | N
    |       |
| Update_priv           | enum('N','Y')                   | NO   |     | N
    |       |
| Delete_priv           | enum('N','Y')                   | NO   |     | N
    |       |
| Create_priv           | enum('N','Y')                   | NO   |     | N
    |       |
| Drop_priv             | enum('N','Y')                   | NO   |     | N
    |       |
```

查看db表

`desc db`

```
mysql> use mysql;
Database changed
mysql> desc db;
+-----------------------+---------------+------+-----+---------+-------+
| Field                 | Type          | Null | Key | Default | Extra |
+-----------------------+---------------+------+-----+---------+-------+
| Host                  | char(60)      | NO   | PRI |         |       |
| Db                    | char(64)      | NO   | PRI |         |       |
| User                  | char(16)      | NO   | PRI |         |       |
| Select_priv           | enum('N','Y') | NO   |     | N       |       |
| Insert_priv           | enum('N','Y') | NO   |     | N       |       |
| Update_priv           | enum('N','Y') | NO   |     | N       |       |
| Delete_priv           | enum('N','Y') | NO   |     | N       |       |
| Create_priv           | enum('N','Y') | NO   |     | N       |       |
| Drop_priv             | enum('N','Y') | NO   |     | N       |       |
| Grant_priv            | enum('N','Y') | NO   |     | N       |       |
| References_priv       | enum('N','Y') | NO   |     | N       |       |
| Index_priv            | enum('N','Y') | NO   |     | N       |       |
| Alter_priv            | enum('N','Y') | NO   |     | N       |       |
| Create_tmp_table_priv | enum('N','Y') | NO   |     | N       |       |
| Lock_tables_priv      | enum('N','Y') | NO   |     | N       |       |
| Create_view_priv      | enum('N','Y') | NO   |     | N       |       |
| Show_view_priv        | enum('N','Y') | NO   |     | N       |       |
| Create_routine_priv   | enum('N','Y') | NO   |     | N       |       |
| Alter_routine_priv    | enum('N','Y') | NO   |     | N       |       |
```

查看host表

与DB表结合使用在一个较好层次上控制特定主机对数据库的访问权限，这可能比单独使用DB好些。这个表不受GRANT和REVOKE语句的影响。

`desc host;`

```
mysql> desc host;
+-----------------------+---------------+------+-----+---------+-------+
| Field                 | Type          | Null | Key | Default | Extra |
+-----------------------+---------------+------+-----+---------+-------+
| Host                  | char(60)      | NO   | PRI |         |       |
| Db                    | char(64)      | NO   | PRI |         |       |
| Select_priv           | enum('N','Y') | NO   |     | N       |       |
| Insert_priv           | enum('N','Y') | NO   |     | N       |       |
| Update_priv           | enum('N','Y') | NO   |     | N       |       |
| Delete_priv           | enum('N','Y') | NO   |     | N       |       |
| Create_priv           | enum('N','Y') | NO   |     | N       |       |
| Drop_priv             | enum('N','Y') | NO   |     | N       |       |
| Grant_priv            | enum('N','Y') | NO   |     | N       |       |
| References_priv       | enum('N','Y') | NO   |     | N       |       |
| Index_priv            | enum('N','Y') | NO   |     | N       |       |
| Alter_priv            | enum('N','Y') | NO   |     | N       |       |
| Create_tmp_table_priv | enum('N','Y') | NO   |     | N       |       |
| Lock_tables_priv      | enum('N','Y') | NO   |     | N       |       |
| Create_view_priv      | enum('N','Y') | NO   |     | N       |       |
| Show_view_priv        | enum('N','Y') | NO   |     | N       |       |
| Create_routine_priv   | enum('N','Y') | NO   |     | N       |       |
| Alter_routine_priv    | enum('N','Y') | NO   |     | N       |       |
| Execute_priv          | enum('N','Y') | NO   |     | N       |       |
| Trigger_priv          | enum('N','Y') | NO   |     | N       |       |
+-----------------------+---------------+------+-----+---------+-------+
```

创建test用户，随后删除

`grant all privileges on *.* to test@localhost identified by 'test' with grant option;`

`select User,Password from user;`

`*.*` 意味着“所有数据库、所有表”。`with grant option` 表示它具有grant权限。用grant语句创建权限是不需要再手工刷新授权表的，因为它已经自动刷新了。

```
mysql>
mysql> grant all privileges on *.* to test@localhost identified by 'test' with g
rant option;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> select User,Password from user;
+------+-------------------------------------------+
| User | Password                                  |
+------+-------------------------------------------+
| root | *6BB4837EB74329105EE4568DDA7DC67ED2CA2AD9 |
| test | *94BDCEBE19083CE2A1F959FD02F964C7AF4CFC29 |
| root | *6BB4837EB74329105EE4568DDA7DC67ED2CA2AD9 |
+------+-------------------------------------------+
3 rows in set (0.00 sec)
```

删除

删除权限

`revoke all on *.* from test@localhost;`

```
mysql> revoke all on *.* from test@localhost;
Query OK, 0 rows affected (0.00 sec)
```

删除用户

`delete from user where user='test';`

```
mysql> delete from user where user='test';
Query OK, 1 row affected (0.00 sec)

mysql> flush privileges;
Query OK, 0 rows affected (0.00 sec)
```