

11-ansible-vault 加密

ansible-vault 针对于任何文件进行加密，比如 playbook、比如变量文件、比如 jinja2 模板文件

是个文件就能加密

Bash | 复制

```
[root@adsl-172-10-0-153 ansible]# ansible-vault --help
usage: ansible-vault [-h] [--version] [-v] {create,decrypt,edit,view,encrypt,encrypt_string,rekey} ...

encryption/decryption utility for Ansible data files

positional arguments:
  {create,decrypt,edit,view,encrypt,encrypt_string,rekey}
    create              Create new vault encrypted file
    decrypt             Decrypt vault encrypted file
    edit               Edit vault encrypted file
    view              View vault encrypted file
    encrypt            Encrypt YAML file
    encrypt_string     Encrypt a string
    rekey             Re-key a vault encrypted file

optional arguments:
  --version            show program's version number, config file location, configured module search
                     path, module location, executable location and exit
  -h, --help          show this help message and exit
  -v, --verbose       Causes Ansible to print more debug messages. Adding multiple -v will increase
                     the verbosity, the builtin plugins currently evaluate up to -vvvvvv. A
                     reasonable level to start is -vvv, connection debugging might require -vvvv.

See 'ansible-vault <command> --help' for more information on a specific command.
```

一旦使用 ansible 对文件加密了，千万不用通过编辑工具直接去编辑内容，因为会造成文件内容丢失

只能够通过 ansible-vault 命令进行编辑加密的文件