

# Recent upgrades and improvements of WRF 4D-Var system

Xin Zhang      Ning Pan    Qiang Cheng  
Xiang-Yu Huang   Junmei Ban

NCAR Earth System Laboratory

91st AMS Annual Meeting, Seattle, WA

NCAR is sponsored by the National Science Foundation



# Current WRF 4D-Var

- WRF 4D-Var was firstly released in April, 2009 with V3.1.



# Current WRF 4D-Var

- WRF 4D-Var was firstly released in April, 2009 with V3.1.
- WRF adjoint and tangent linear codes (WRFPLUS) were developed based on WRF V2.0.2 around 2005.



# Current WRF 4D-Var

- WRF 4D-Var was firstly released in April, 2009 with V3.1.
- WRF adjoint and tangent linear codes (WRFPLUS) were developed based on WRF V2.0.2 around 2005.
- Multiple Program Multiple Data (MPMD) framework, needs 3 executables: WRFDA, WRFNL and WRFPLUS.



# Current WRF 4D-Var

- WRF 4D-Var was firstly released in April, 2009 with V3.1.
- WRF adjoint and tangent linear codes (WRFPLUS) were developed based on WRF V2.0.2 around 2005.
- Multiple Program Multiple Data (MPMD) framework, needs 3 executables: WRFDA, WRFNL and WRFPLUS.
- Simplified physical packages: surface drag, large scale condensation and a cumulus parameterization schemes ( Q. Xiao).



# Current WRF 4D-Var

- WRF 4D-Var was firstly released in April, 2009 with V3.1.
- WRF adjoint and tangent linear codes (WRFPLUS) were developed based on WRF V2.0.2 around 2005.
- Multiple Program Multiple Data (MPMD) framework, needs 3 executables: WRFDA, WRFNL and WRFPLUS.
- Simplified physical packages: surface drag, large scale condensation and a cumulus parameterization schemes ( Q. Xiao).
- Weak constraint with digital filter.



# Why upgrade ?

- Numerous bug fixes, upgrades and improvements in WRF model since 2005. V3.3 is coming....



# Why upgrade ?

- Numerous bug fixes, upgrades and improvements in WRF model since 2005. V3.3 is coming....
- Particularly, WRF infrastructure changes invalid some interfaces in WRFPLUS, such as the boundary variables can not be read in anymore.



# Why upgrade ?

- Numerous bug fixes, upgrades and improvements in WRF model since 2005. V3.3 is coming....
- Particularly, WRF infrastructure changes invalid some interfaces in WRFPLUS, such as the boundary variables can not be read in anymore.
- MPMD WRF 4D-Var is too complicate, most of the community users could not get it run without help.



# Why upgrade ?

- Numerous bug fixes, upgrades and improvements in WRF model since 2005. V3.3 is coming....
- Particularly, WRF infrastructure changes invalid some interfaces in WRFPLUS, such as the boundary variables can not be read in anymore.
- MPMD WRF 4D-Var is too complicate, most of the community users could not get it run without help.
- Very high disk IO overhead associated with the number of processors.



# Why upgrade ?

- Numerous bug fixes, upgrades and improvements in WRF model since 2005. V3.3 is coming....
- Particularly, WRF infrastructure changes invalid some interfaces in WRFPLUS, such as the boundary variables can not be read in anymore.
- MPMD WRF 4D-Var is too complicate, most of the community users could not get it run without help.
- Very high disk IO overhead associated with the number of processors.
- Only runs good on IBM machines; unstable on other platforms and compilers.



# Why upgrade ?

- Numerous bug fixes, upgrades and improvements in WRF model since 2005. V3.3 is coming....
- Particularly, WRF infrastructure changes invalid some interfaces in WRFPLUS, such as the boundary variables can not be read in anymore.
- MPMD WRF 4D-Var is too complicate, most of the community users could not get it run without help.
- Very high disk IO overhead associated with the number of processors.
- Only runs good on IBM machines; unstable on other platforms and compilers.
- 4D-Var support for Prepbufr and radiance bufr data is not clear.



# Why upgrade ?

- Numerous bug fixes, upgrades and improvements in WRF model since 2005. V3.3 is coming....
- Particularly, WRF infrastructure changes invalid some interfaces in WRFPLUS, such as the boundary variables can not be read in anymore.
- MPMD WRF 4D-Var is too complicate, most of the community users could not get it run without help.
- Very high disk IO overhead associated with the number of processors.
- Only runs good on IBM machines; unstable on other platforms and compilers.
- 4D-Var support for Prepbufr and radiance bufr data is not clear.
- Hard to do a complete adjoint check due to initial design of framework.



# Upgrading WRFPLUS

- New WRF adjoint and tangent linear codes based on the latest WRF repository codes.



# Upgrading WRFPLUS

- New WRF adjoint and tangent linear codes based on the latest WRF repository codes.
- Constructed interfaces through which other applications can call WRF adjoint and tangent linear model directly.



# Upgrading WRFPLUS

- New WRF adjoint and tangent linear codes based on the latest WRF repository codes.
- Constructed interfaces through which other applications can call WRF adjoint and tangent linear model directly.
- Testing the code on various platforms and compilers ( IBM, Linux, Mac : xlf, g95, pgi, intel, gfortran).



# Upgrading WRFPLUS

- New WRF adjoint and tangent linear codes based on the latest WRF repository codes.
- Constructed interfaces through which other applications can call WRF adjoint and tangent linear model directly.
- Testing the code on various platforms and compilers ( IBM, Linux, Mac : xlf, g95, pgi, intel, gfortran).
- Capability to do tangent linear and adjoint test over any length of time window.



# Upgrading WRFPLUS

- New WRF adjoint and tangent linear codes based on the latest WRF repository codes.
- Constructed interfaces through which other applications can call WRF adjoint and tangent linear model directly.
- Testing the code on various platforms and compilers ( IBM, Linux, Mac : xlf, g95, pgi, intel, gfortran).
- Capability to do tangent linear and adjoint test over any length of time window.
- New WRFPLUS can be used as a standalone tool or as a component in 4D-Var system.



# Sample Tangent Linear and Adjoint Check of WRFPLUS

## Tangent linear check: 6 hours

```
alpha_m=.1000E+00  coef=  0.98186174930325E+00  val_n= 0.3725210E+11  val_l= 0.3794027E+11
alpha_m=.1000E-01  coef=  0.99807498026522E+00  val_n= 0.3786723E+09  val_l= 0.3794027E+09
alpha_m=.1000E-02  coef=  0.99970559707666E+00  val_n= 0.3792910E+07  val_l= 0.3794027E+07
alpha_m=.1000E-03  coef=  0.99992019503144E+00  val_n= 0.3793724E+05  val_l= 0.3794027E+05
alpha_m=.1000E-04  coef=  0.10000447262220E+01  val_n= 0.3794196E+03  val_l= 0.3794027E+03
alpha_m=.1000E-05  coef=  0.99999981575068E+00  val_n= 0.3794026E+01  val_l= 0.3794027E+01
alpha_m=.1000E-06  coef=  0.99999998152933E+00  val_n= 0.3794027E-01  val_l= 0.3794027E-01
alpha_m=.1000E-07  coef=  0.99999990980017E+00  val_n= 0.3794026E-03  val_l= 0.3794027E-03
alpha_m=.1000E-08  coef=  0.99999956711797E+00  val_n= 0.3794025E-05  val_l= 0.3794027E-05
alpha_m=.1000E-09  coef=  0.10000030220656E+01  val_n= 0.3794038E-07  val_l= 0.3794027E-07
alpha_m=.1000E-10  coef=  0.99996176999678E+00  val_n= 0.3793882E-09  val_l= 0.3794027E-09
```

## Adjoint check: 6 hours

```
ad_check: VAL_TL:    0.42476489986911E+11
ad_check: VAL_AD:    0.42476489986912E+11
```



## Single executable 4D-Var

WRFPLUS includes WRF NL, AD and TL model and they are used as a subroutine in WRF 4D-Var, other than being called via shell scripts.

### Nonlinear call

```
old      call da_system ("da_run_wrf_nl.ksh")
new      call da_nl_model
```

### Tangent linear call

```
old      call da_system ("da_run_wrfplus_tl.ksh")
new      call da_tl_model
```

### Adjoint call

```
old      call da_system ("da_run_wrfplus_ad.ksh")
new      call da_ad_model
```



# Memory exchange

The information (TL perturbation, adjoint forcing, basic states and gradient) is exchanged via linked lists.

Read basic states

```
call domain_clock_get( grid, current_timestr=timestr )
call da_read_basicstates ( xbx, grid, ... )
```

Save TL perturbation

```
call push_tl_pert (timestr)
```


Save AD forcing

```
call push_ad_forcing (timestr)
```




## Parallel run using all processors

4D-Var is a sequential algorithm. However, the current parallel WRF 4D-Var constructed on the Multiple Program Multiple Data mode, which have to split the total processors into 3 subsets for DA, NL and AD/TL. Lots of CPU time are wasted




## Parallel run using all processors

Benefit from the single executable framework, every CPU is working at any time. No IDLE any more.



# Performance improvement WRF 4DVar framework only

- 270x180x41@20km, 6h window, 1h obs\_bin, 10 iterations
- 10 iterations FGAT, NCAR bluefire (IBM P6)



# Consider Lateral boundary condition as control variable

$$J = J_b + J_o + J_c + \textcolor{red}{J}_{lbc}$$

$$\begin{aligned} J_{lbc} &= \frac{1}{2}(\mathbf{x}(t_k) - \mathbf{x}_b(t_k))^T \mathbf{B}^{-1} (\mathbf{x}(t_k) - \mathbf{x}_b(t_k)) \\ &= \frac{1}{2} \delta \mathbf{x}(t_k)^T \mathbf{B}^{-1} \delta \mathbf{x}(t_k) \end{aligned}$$

$J_{lbc}$  is the  $J_b$  at the end of the assimilation window  
lateral boundary control is obtained through


$$\frac{\partial \delta \mathbf{x}_{lbc}}{\partial t} = \frac{\delta \mathbf{x}(t_k) - \delta \mathbf{x}(t_0)}{t_k - t_0}$$



# Single observation experiments

- Initial time: 2000\_01\_25\_00 : 00 : 00
- Ending time: 2000\_01\_25\_06 : 00 : 00
- Observation: 500 mb Temperature at **ending time**  
 $O - B = -1.168K$
- To investigate the difference at **ending time** between the forecast from analysis and from background.






## Remarks

Forecasted 500mb T difference  
(DA forecast - reference  
forecast)

- $\star$  is the location of obs. at the ending time (6h).
- JcDF is turned on
- LBC control is turned on
- Initial perturbation is on the upstream of the obs.
- Evolved perturbation at 6h hit the obs. location





## Remarks

Forecasted 500mb T difference  
(DA forecast - reference  
forecast)

- ★ is the location of obs.  
at the ending time (6h).
- JcDF is turned on
- LBC control is turned off




# Additional experiments design

## Observation close to boundary

To investigate the impact of including boundary condition in data assimilation, the 6h observation is close to boundary and downstream of the boundary, we expect that the analysis response at 0h should be in boundary condition other than initial condition.






## Remarks

Forecasted 500mb T difference  
(DA forecast - reference  
forecast)

- $\star$  is the location of obs. at the ending time (6h).
- JcDF is turned on
- $O - B = -0.95K$
- LBC control is turned on
- Main initial perturbation is in the boundary condition other than in the initial condition ( south boundary, invisible here)
- Evolved perturbation is coming from boundary





## Remarks

Forecasted 500mb T difference  
(DA forecast - reference  
forecast)

- $\star$  is the location of obs. at the ending time (6h).
- JcDF is turned on
- LBC control is **turned off**
- Main Initial perturbation is in the location of the obs., it is fake
- Evolved perturbation at 6h is moving out from the obs. location



# An OSSE radar data assimilation with WRF 4D-Var

(Yongrun Guo and Jenny Sun)

- TRUTH — Initial condition from TRUTH (13-h forecast initialized at 2002061212Z from AWIPS 3-h analysis) run cutted by ndown, boundary condition from NCEP GFS data.



# An OSSE radar data assimilation with WRF 4D-Var

(Yongrun Guo and Jenny Sun)

- TRUTH — Initial condition from TRUTH (13-h forecast initialized at 2002061212Z from AWIPS 3-h analysis) run cutted by ndown, boundary condition from NCEP GFS data.
- NODA — Both initial condition and boundary condition from NCEP GFS data.



# An OSSE radar data assimilation with WRF 4D-Var

(Yongrun Guo and Jenny Sun)

- TRUTH — Initial condition from TRUTH (13-h forecast initialized at 2002061212Z from AWIPS 3-h analysis) run cutted by ndown, boundary condition from NCEP GFS data.
- NODA — Both initial condition and boundary condition from NCEP GFS data.
- 3DVAR — 3DVAR analysis at 2002061301Z used as the initial condition, and boundary condition from NCEP GFS. Only Radar radial velocity at 2002061301Z assimilated (total data points = 97,033), 3 outer loops.





# An OSSE radar data assimilation with WRF 4D-Var

(Yongrun Guo and Jenny Sun)

- TRUTH — Initial condition from TRUTH (13-h forecast initialized at 2002061212Z from AWIPS 3-h analysis) run cutted by ndown, boundary condition from NCEP GFS data.
- NODA — Both initial condition and boundary condition from NCEP GFS data.
- 3DVAR — 3DVAR analysis at 2002061301Z used as the initial condition, and boundary condition from NCEP GFS. Only Radar radial velocity at 2002061301Z assimilated (total data points = 97,033), 3 outer loops.
- 4DVAR — 4DVAR analysis at 2002061301Z used as initial condition, and boundary condition from NCEP GFS. The radar radial velocity at 4 times: 200206130100, 05, 10, and 15, are assimilated (total data points =



# OSSE 3rd hour precipitation simulation



## Remarks

- Obviously, 4DVar reproduce the best squall line precipitation band.



# Remarks

- Obviously, 4DVar reproduce the best squall line precipitation band.
- However, the coverage and intensity of the precipitation are more than the observation.



## Remarks

- Obviously, 4DVar reproduce the best squall line precipitation band.
- However, the coverage and intensity of the precipitation are more than the observation.
- Possible reason: The new WRFPLUS is a dynamic-only model, PBL and microphysics are needed.



# Summary

- The single executable WRF 4DVar system was developed and has showed promising performance.  
Poster 541: "Evaluation of WRFDA 4D-VAR through Month-long Run and Case Study" by Xiaoyan Zhang et al.



# Summary

- The single executable WRF 4DVar system was developed and has showed promising performance.  
Poster 541: "Evaluation of WRFDA 4D-VAR through Month-long Run and Case Study" by Xiaoyan Zhang et al.
- The new WRF 4DVar system has the capability to assimilate conventional observational data (little\_r or prepbufr format),radiance in bufr format and radar data.



# Summary

- The single executable WRF 4DVar system was developed and has showed promising performance.  
Poster 541: "Evaluation of WRFDA 4D-VAR through Month-long Run and Case Study" by Xiaoyan Zhang et al.
- The new WRF 4DVar system has the capability to assimilate conventional observational data (little\_r or prepbufr format), radiance in bufr format and radar data.
- The new WRF 4DVar system is able to consider lateral boundary condition as control variable and digital filter can be used as a weak constraint to suppress the high frequency noise.



# Under development

- Add simplified physics packages into WRFPLUS: surface drag, large scale condensation, a simplified moist cumulus scheme, as well as a radiation scheme.



# Under development

- Add simplified physics packages into WRFPLUS: surface drag, large scale condensation, a simplified moist cumulus scheme, as well as a radiation scheme.
- Parallelization of WRF tangent linear code has been done. We are working on the parallelization of WRF adjoint codes.



# Thank You

The NESL Mission is:

To advance understanding of weather, climate, atmospheric composition and processes;

To provide facility support to the wider community; and,

To apply the results to benefit society.

NCAR is sponsored by the National Science Foundation

