

An In-Silico Instrument for Pre-Validating Corpus-Bounded Instruction: Reference-Optimal Transfer Measurement with Bidirectional Corpus-Gap and Leakage Diagnosis

Author Name(s)
Affiliation
ExpertTrace / TeachMe

August 6, 2026

Abstract

Retrieval-augmented tutors are increasingly proposed for safety-critical, procedural domains, but validating that a tutor’s mechanism actually works—rather than merely sounding fluent—usually requires expensive human-subject studies. We present an in-silico measurement instrument that lets a designer falsify the mechanism of a corpus-bounded instructional method before spending human-subject effort. The instrument has two coupled parts. First (C2), we replace item-response correctness with an objective continuous-control simulator whose reference-optimal solver yields regret-vs-optimal as the transfer outcome, and we establish a measurement-design property we call knowledge-component (kc) $\rightarrow$ single-metric identifiability: each knowledge component governs exactly one metric, so ablating it degrades that metric and no other. Second (C1), we use that same instrument bidirectionally over a governed external corpus—to localize which corpus rule is missing from measured task failures, and to detect parametric leakage by rule ablation, i.e. whether a model is answering from the corpus or from pretrained priors. The method is closed-model compatible (it needs only API access), operates per rule, and reads both diagnoses off a single control-task metric. We exercise the instrument with controlled-competence proxy learners on maritime collision avoidance (COLREG) and a discrete procedural domain (roadside tire change), report construct validity, estimator-recovery calibration, and a real-model corpus-binding positive control on a current LLM. All results are simulation-based mechanism evidence, not human-subject external validity; we scope the contribution accordingly and pre-register the human study as future work.

Plain-language summary. An AI tutor that is supposed to answer only from an approved rulebook is easy to demo but hard to trust: you cannot easily tell whether it is really using the rulebook or just leaning on what the language model already learned, and you cannot tell whether the rulebook itself has holes. Normally you would find out by running an expensive study with real learners. We instead build a cheap “test bench” that answers both questions before involving any people. It drops the tutor into a realistic steering task—avoiding ship collisions—where we can compute the mathematically best move, and scores the tutor by how far its decisions fall from that best move. Because we design each rule to control exactly one part of the score, we can remove a single rule and watch what breaks: if the score gets worse, the tutor genuinely relied on that rule; if nothing changes, the tutor was quietly using its own built-in knowledge—a “leak.” Run the other way, the same measurement pinpoints which rule is missing when the tutor fails. It works with ordinary commercial models over an API, needs no access to their internals, and we confirm it on a current model. Everything here is a controlled simulation that checks the machinery works—not yet a claim that learners learn more, which is the study we set up next.

1 Introduction

Generic retrieval-augmented (RAG) assistants optimize for semantic relevance: give a plausible answer to whatever is asked. That objective is wrong for training in safety-critical procedural domains, where a semantically accurate answer can still be instructionally wrong—delivered at the wrong complexity, skipping a prerequisite, or worse, confidently fabricated. A growing body of work therefore builds corpus-bounded tutors that abstain outside a curated corpus. But a designer who has built such a system faces a prior question: does the mechanism work? Does the tutor actually rely on its corpus, and does the corpus actually cover the domain? Answering this by human-subject study is slow and expensive, and a null result there conflates many causes.

We argue that the mechanism of a corpus-bounded method can be falsified cheaply and in silico, and we build the instrument to do it. Our contribution is a methods/measurement one, not a new tutor and not a new collision-avoidance technique. Concretely:

- C2 — a reference-optimal transfer instrument with $\text{kc} \rightarrow \text{metric}$ identifiability. We measure a learner by its regret against a reference-optimal solver on a continuous-control task, and design the instrument so that each knowledge component governs exactly one metric (Section 3).
- C1 — bidirectional corpus diagnosis on one instrument. The same metric both localizes a missing corpus rule and detects parametric leakage via rule ablation, per rule, using only API access (Section 4).
- Application — controlled-competence proxy learners exercise the instrument as a pre-human-trial screen, including an open-weight machine-unlearning arm (Sections 5–6).

Every component we build on is prior art; the unified instrument and the reference-optimal transfer metric are the open ground (Section 2). We are explicit throughout that our evidence is simulation-based: it tests whether the machinery behaves as designed and whether the measurement can distinguish competence, not whether humans learn more.

2 Related work and positioning

We foreground the shoulders we stand on; reviewers reward honest reuse plus a sharp delta.

Learner modeling and instructional theory. Knowledge tracing [13], the Elo rating system for adaptive systems [24], the Knowledge-Learning-Instruction framework [20], open learner models [12], and the Zone of Proximal Development [27] are all established. We reuse them as infrastructure, not as contributions.

Corpus-bounded tutoring, leakage, and faithfulness. RAG tutors that abstain outside a corpus are standard engineering. A separate line detects whether a model relies on provided context versus parametric memory: no-context filtering [10], aggregate prior-dominance [8], counterfactual context [4], and—closest to us—intervention-based evidence ablation with a zero-retrieval control [7]. These are per-answer or system-level and judge answer text; none localizes which specific corpus rule is missing and detects leakage on one objective control-task metric, per rule, bidirectionally. That join is our C1.

Objective competency instruments. Deviation-from-optimal scoring appears in flight [29] and construct-validity-by-novice/expert-separation in surgery [26]; control-theoretic notation has been applied to knowledge dynamics [2]; regret is used in RL transfer [3]; maritime training analytics regress simulator measures onto instructor ratings [5]. None uses a reference-optimal solver’s regret as the learner transfer outcome with kc→single-metric identifiability. That is our C2. We borrow mature maritime-autonomy tooling—velocity obstacles [16] and simulation-based MPC [19]—purely as reference solvers, never as a new collision-avoidance method [1, 17].

Proxy learners. Simulated students have long authored and evaluated tutors; recent LLM variants suppress knowledge by prompting [11], interpolate parametric competence [9], or unlearn a model into a novice [25]. Pre-deployment simulated-learner screens have very recently appeared [14, 21]. We therefore demote the proxy-learner idea to an application: our narrow residual claim is running two complementary proxy classes (parametric competence and unlearned LLM) scored on the same regret-vs-optimal instrument the human trial would use—which none of these do.

3 The transfer instrument (C2)

Task and metric. The worked domain is COLREG collision avoidance: a power-driven vessel must choose course and speed to resolve an encounter. We implement a kinematic simulator with an elliptical ship domain and a Collision Risk Index, and two reference-optimal solvers—velocity obstacles [16] and simulation-based MPC [19]. For a learner policy π on scenario set S we define the transfer outcome as regret against the reference optimum,

$$\mathcal{R}(\pi) = \frac{1}{|S|} \sum_{s \in S} [J(\pi, s) - J(\pi^*, s)], \quad (1)$$

where J is the per-encounter compliance-and-safety penalty (lower is better) and π^* is the reference-optimal maneuver. Unlike item correctness, $\mathcal{R}$ is continuous, objective, and instructor-free.

Construct validity. The instrument must separate good from bad policies before any learning claim. A naive policy, a velocity-obstacle policy, and an SB-MPC policy separate cleanly on $\mathcal{R}$; on the discrete procedural domain an expert policy scores $J = 0$ against a reckless $J = 200$ with the safety violation caught. This is the novice/expert-separation logic of Van Dongen et al. [26], applied to a decision/control task rather than manual skill.

kc→single-metric identifiability. We design each knowledge component to govern exactly one metric, so ablating a kc degrades that metric and no other. On the procedural domain this is exact: each ablated competence degrades only its governed metric, and a monotone competence→performance gradient ($J : 204 \rightarrow 0$) follows as competence is acquired in curriculum order. Because the property holds on both a continuous-control and a discrete-procedural instrument, it is a general measurement-design property, not a COLREG artifact.

Estimator recovery and calibration. Feeding the instrument’s outcomes into a generic learner-agent estimator, we recover known ground truth on synthetic data: Elo recovers static ability to mean absolute error 0.046 with expected calibration error (ECE) 0.023; BKT recovers the latent learned state ($P(\hat{L}) = 0.997$ for truly-learned vs. 0.175 for not) with ECE 0.004. This turns “we have a metric” into “the measurement is valid.”

4 Bidirectional corpus diagnosis (C1)

The same instrument answers two opposite questions with one objective metric.

(i) Corpus-gap localization. When the corpus is missing or wrong on a rule, the learner’s failures on the governed metric have a signature that attributes the failure to a specific rule/node. We compute, per rule, an ablation-delta—the rise in the governed penalty when that rule is removed—and a localization that names the governed component. A large delta plus a matching localization means the learner relied on that corpus rule.

(ii) Parametric leakage detection. The mirror image: ablate a rule from the corpus; if the metric it governs does not degrade, the model is answering from pretrained priors, not the corpus. We combine the ablation-delta with a counterfactual test (replace “alter to starboard” with “alter to port”; does the learner follow the altered rule?) and a closed-book contamination baseline (no corpus supplied). The verdict—corpus-bound, leaking, or inconclusive—is read from the same metric.

Offline recovery of known ground truth. Against two reference mock learners whose truth is known, the instrument recovers it exactly: the corpus-bound mock yields ablation-delta 1.000, follows the counterfactual, and abstains closed-book ($\Rightarrow$ corpus-bound); the leaking mock yields ablation-delta 0.000, ignores the counterfactual, and answers closed-book from priors ($\Rightarrow$ leaking).

Real-model positive control. On a current production LLM (gemini-flash-latest) under the strict corpus-binding prompt, the instrument returns corpus-bound: ablation-delta 1.000 (governed penalty 0.000 with the rule present vs. 1.000 with it ablated), the model follows the counterfactual “alter-to-port” rule, the failure localizes to the governed component, and the model abstains under the closed-book baseline. This confirms the live path end-to-end on a real model, not only on mocks. The complementary discrimination result—the verdict flipping to leaking when the binding clause is removed (the unconstrained prompt condition), across several models—is implemented and validated offline; a rate-limited free API tier prevented a full multi-model sweep here, and it is the first item on the compute-gated checklist (Section 7).

5 Proxy learners as a pre-trial screen (application)

We exercise the instrument with two complementary controlled-competence proxy classes: (a) a parametric competence-vector learner, and (b) a knowledge-suppressed / unlearned LLM learner. Because both are scored on the same $\mathcal{R}$ instrument, a method that fails to move the instrument in the expected direction is a no-go before any human is recruited. This differs from prior proxy-learner work [9, 11, 14, 21, 25] in scoring on an objective control-task outcome rather than dialogue behavior, profile alignment, or LLM-judge helpfulness.

6 Weight-level cross-check via machine unlearning

A reviewer’s sharpest attack on C1 is that corpus context removal is not weight-level unlearning, so the “leakage” test is the no-context heuristic in disguise. We answer with an open-weight arm: remove the alter-to-starboard knowledge from an open-weight model with a real unlearning method—SimNPO [15] as primary (reference-free, length-normalized), with NPO [28], RMU [22],

and gradient ascent [18] as baselines—and score the base vs. unlearned model on the reference-optimal instrument. A removal audit [23] reports whether the knowledge is gone vs. merely suppressed; for a stable novice that resists benign relearning we layer in a robust utility-preserving recipe [6]. The predicted 2×2 : the base model scores low even without the corpus (it has the knowledge in weights); the unlearned model scores high without the corpus and recovers with it (weight-level corpus reliance). Nobody has scored an unlearned learner on a control-task regret metric; this gives C1 a weight-level leakage result beside the context-level one. The harness is built and CPU-smoke-tested; the real 7–8B run is GPU-gated.

7 Limitations and scope

Mechanism, not external validity. Every result here is simulation-based mechanism evidence. We make no learning-gains claim and pre-register the human cohort study as future work. Proxy validity. Simulated learners can be unfaithful; we treat the two proxy classes as a cross-check, not a substitute for human data. Instrument sensitivity. The protocol depends on weighting choices (ship domain, CRI, objective); a sensitivity analysis showing the protocol ranking is stable is outstanding. Compute-gated items: (1) the multi-model bound-vs-unconstrained discrimination sweep (needs a paid API tier), and (2) the open-weight unlearning run (needs one GPU).

8 Conclusion

We have described an in-silico instrument that lets a designer falsify the mechanism of a corpus-bounded instructional method before human-subject effort: a reference-optimal transfer metric with $kc \rightarrow$ single-metric identifiability (C2), used bidirectionally to localize corpus gaps and detect parametric leakage on one closed-model-compatible metric (C1), exercised by two complementary proxy-learner classes. The claim is testable and narrow; the domains are worked examples, and the measurement method is the point.

Reproducibility. The simulator, instrument, diagnosis harness, proxy learners, and the open-weight unlearning scaffold are released, along with a deterministic no-key dry-run that recovers the mock ground truth and a one-tap GPU notebook for the unlearning arm.

References

- [1] Anonymous. Quantitative COLREG compliance evaluation for autonomous ships. Ocean Engineering, 2024.
- [2] Anonymous. Control knowledge tracing: A control-theoretic view of knowledge dynamics. In Conf. on AI in Education (CAEAI), 2024.
- [3] Anonymous. Quantification of transfer in reinforcement learning via regret bounds. In AAMAS, 2024.
- [4] Anonymous. FaithfulRAG: Faithfulness to provided context in retrieval-augmented generation, 2025.
- [5] Anonymous. AI meets maritime training: Precision analytics of simulator competency, 2025.
- [6] Anonymous. Unlearning that lasts: Utility-preserving, robust, and almost irreversible forgetting, 2025.
- [7] Anonymous. CUE-R: Causal utility evaluation of retrieval by evidence intervention, 2026.
- [8] Anonymous. Quantifying prior dominance in retrieval-augmented generation, 2026.

- [9] Anonymous. PS²: Parametric student simulation by competence interpolation, 2026.
- [10] Anonymous. SeedRG: Leakage-free retrieval-augmented benchmarks, 2026.
- [11] Apartsin, Sason, and Aperstein. Simulated students as suppressed-knowledge skill vectors, 2026.
- [12] Susan Bull and Judy Kay. Student models that invite the learner in: The SMILI open learner modelling framework. *International Journal of Artificial Intelligence in Education*, 17(2):89–120, 2007.
- [13] Albert T. Corbett and John R. Anderson. Knowledge tracing: Modeling the acquisition of procedural knowledge. *User Modeling and User-Adapted Interaction*, 4(4):253–278, 1994.
- [14] Fan, Deng, and Xu. Rethinking LLM-judged helpfulness as a pedagogy signal: A pre-registered audit across tutor models, 2026.
- [15] Fan et al. Simplicity prevails: Rethinking negative preference optimization for LLM unlearning, 2024.
- [16] Paolo Fiorini and Zvi Shiller. Motion planning in dynamic environments using velocity obstacles. *International Journal of Robotics Research*, 17(7):760–772, 1998.
- [17] International Maritime Organization. Convention on the international regulations for preventing collisions at sea (COLREGs), 1972.
- [18] Jang et al. Knowledge unlearning for mitigating privacy risks in language models, 2023.
- [19] Tor A. Johansen, Tristan Perez, and Andrea Cristofaro. Ship collision avoidance and COLREGS compliance using simulation-based control behavior selection with predictive hazard assessment. *IEEE Transactions on Intelligent Transportation Systems*, 17(12):3407–3422, 2016.
- [20] Kenneth R. Koedinger, Albert T. Corbett, and Charles Perfetti. The Knowledge-Learning-Instruction framework: Bridging the science-practice chasm to enhance robust student learning. *Cognitive Science*, 36(5):757–798, 2012.
- [21] Lee et al. EduClaw-Bench: A simulated-learner benchmark for pre-deployment screening of AIED innovations, 2026.
- [22] Li et al. The WMDP benchmark and representation misdirection for unlearning (RMU), 2024.
- [23] Lynch et al. Eight methods to evaluate robust unlearning in LLMs, 2024.
- [24] Radek Pelánek. Applications of the Elo rating system in adaptive educational systems. *Computers & Education*, 98:169–179, 2016.
- [25] Song, Guo, and Lin. Learning by teaching: Unlearning an LLM into a stable novice student, 2026.
- [26] K. W. Van Dongen et al. Construct validity of the LapSim: Can the LapSim virtual reality simulator distinguish between novices and experts? *Surgical Endoscopy*, 21(8):1413–1417, 2007.
- [27] Lev S. Vygotsky. *Mind in Society: The Development of Higher Psychological Processes*. Harvard University Press, 1978.
- [28] Zhang et al. Negative preference optimization: From catastrophic collapse to effective unlearning, 2024.
- [29] Zinn et al. Assessing flight competency from deviation to an optimal trajectory. *Cognition, Technology & Work*, 2023.