

An In-Silico Instrument for Pre-Validating Corpus-Bounded Instruction: Reference-Policy Transfer Measurement with Bidirectional Corpus-Gap and Leakage Diagnosis

Author Name(s)

Affiliation

ExpertTrace / TeachMe

August 6, 2026

Abstract

Retrieval-augmented tutors are increasingly proposed for safety-critical, procedural domains, but validating that a tutor’s mechanism actually works—rather than merely sounding fluent—usually requires expensive human-subject studies. We present an in-silico measurement instrument that lets a designer falsify the mechanism of a corpus-bounded instructional method before spending human-subject effort. The instrument has two coupled parts. First (C2), we replace item-response correctness with an objective continuous-control simulator whose reference solver yields regret-to-reference as the transfer outcome, and we establish a measurement-design property we call knowledge-component (kc) $\rightarrow$ single-metric identifiability: each knowledge component governs exactly one metric, so ablating it degrades that metric and no other. Second (C1), we use that same instrument bidirectionally over a governed external corpus—to localize which corpus rule is missing from measured task failures, and to detect parametric leakage by rule ablation, i.e. whether a model is answering from the corpus or from pretrained priors. The method is closed-model compatible (it needs only API access), operates per rule, and reads both diagnoses off a single control-task metric. We exercise the instrument with controlled-competence proxy learners on maritime collision avoidance (COLREG) and a discrete procedural domain (road-side tire change), and report construct validity, estimator-recovery calibration, and a real-model discrimination result across six current LLMs: under a strict prompt the instrument diagnoses corpus-binding, and removing the binding clause collapses the ablation- δ and flips closed-book abstention to contamination for every model—with lighter models flipping fully to leaking, and the lightest leaking even under the strict prompt (a binding failure the instrument catches). All results are simulation-based mechanism evidence, not human-subject external validity; we scope the contribution accordingly and pre-register the human study as future work.

Plain-language summary. An AI tutor that is supposed to answer only from an approved rulebook is easy to demo but hard to trust: you cannot easily tell whether it is really using the rulebook or just leaning on what the language model already learned, and you cannot tell whether the rulebook itself has holes. Normally you would find out by running an expensive study with real learners. We instead build a cheap “test bench” that answers both questions before involving any people. It drops the tutor into a realistic steering task—avoiding ship collisions—where a standard automatic solver gives a strong reference move, and scores the tutor by how far its decisions fall from that reference. Because we design each rule to control exactly one part of the score, we can remove a single rule and watch what breaks: if the score gets worse, the tutor genuinely relied on that rule; if nothing changes, the tutor was quietly using its own built-in knowledge—a “leak.” Run the other way, the same measurement pinpoints which rule is missing when the tutor fails. It works with ordinary commercial models over an API, needs no access to their internals, and we confirm it on a current model. Everything here is a controlled simulation that checks the machinery works—not yet a claim that learners learn more, which is the study we set up next.

1 Introduction

Generic retrieval-augmented (RAG) assistants optimize for semantic relevance: give a plausible answer to whatever is asked. That objective is wrong for training in safety-critical procedural domains, where a semantically accurate answer can still be instructionally wrong—delivered at the wrong complexity, skipping a prerequisite, or worse, confidently fabricated. A growing body of work therefore builds corpus-bounded tutors that abstain outside a curated corpus. But a designer who has built such a system faces a prior question: does the mechanism work? Does the tutor actually rely on its corpus, and does the corpus actually cover the domain? Answering this by human-subject study is slow and expensive, and a null result there conflates many causes.

We argue that the mechanism of a corpus-bounded method can be falsified cheaply and in silico, and we build the instrument to do it. Our contribution is a methods/measurement one, not a new tutor and not a new collision-avoidance technique. Concretely:

- C2 — a reference-policy transfer instrument with $kc \rightarrow \text{metric}$ identifiability. We measure a learner by its regret against a reference-policy solver on a continuous-control task, and design the instrument so that each knowledge component governs exactly one metric (Section 3).
- C1 — bidirectional corpus diagnosis on one instrument. The same metric both localizes a missing corpus rule and detects parametric leakage via rule ablation, per rule, using only API access (Section 4).
- Application — controlled-competence proxy learners exercise the instrument as a pre-human-trial screen, including an open-weight machine-unlearning arm (Sections 5–6).

Every component we build on is prior art; the unified instrument and the reference-policy transfer metric are the open ground (Section 2). We are explicit throughout that our evidence is simulation-based: it tests whether the machinery behaves as designed and whether the measurement can distinguish competence, not whether humans learn more.

2 Related work and positioning

We foreground the shoulders we stand on; reviewers reward honest reuse plus a sharp delta.

Learner modeling and instructional theory. Knowledge tracing [13], the Elo rating system for adaptive systems [24], the Knowledge-Learning-Instruction framework [20], open learner models [12], and the Zone of Proximal Development [27] are all established. We reuse them as infrastructure, not as contributions.

Corpus-bounded tutoring, leakage, and faithfulness. RAG tutors that abstain outside a corpus are standard engineering. A separate line detects whether a model relies on provided context versus parametric memory: no-context filtering [10], aggregate prior-dominance [8], counterfactual context [4], and—closest to us—intervention-based evidence ablation with a zero-retrieval control [7]. These are per-answer or system-level and judge answer text; none localizes which specific corpus rule is missing and detects leakage on one objective control-task metric, per rule, bidirectionally. That join is our C1.

Objective competency instruments. Deviation-from-optimal scoring appears in flight [29] and construct-validity-by-novice/expert-separation in surgery [26]; control-theoretic notation has been applied to knowledge dynamics [2]; regret is used in RL transfer [3]; maritime training analytics regress simulator measures onto instructor ratings [5]. None uses a reference solver’s regret as the learner transfer outcome with $kc \rightarrow$ single-metric identifiability. That is our C2. We borrow mature maritime-autonomy tooling—velocity obstacles [16] and simulation-based MPC [19]—purely as reference solvers, never as a new collision-avoidance method [1, 17].

Proxy learners. Simulated students have long authored and evaluated tutors; recent LLM variants suppress knowledge by prompting [11], interpolate parametric competence [9], or unlearn a model into a novice [25]. Pre-deployment simulated-learner screens have very recently appeared [14, 21]. We therefore demote the proxy-learner idea to an application: our narrow residual claim is running two complementary proxy classes (parametric competence and unlearned LLM) scored on the same regret-to-reference instrument the human trial would use—which none of these do.

3 The transfer instrument (C2)

Task and metric. The worked domain is COLREG collision avoidance: a power-driven vessel must choose course and speed to resolve an encounter. We implement a kinematic simulator with an elliptical ship domain and a Collision Risk Index, and two reference solvers—velocity obstacles [16] and simulation-based MPC [19]. For a learner policy π on scenario set S we define the transfer outcome as regret against a reference policy π^* ,

$$\mathcal{R}(\pi) = \frac{1}{|S|} \sum_{s \in S} [J(\pi, s) - J(\pi^*, s)], \quad (1)$$

where J is the per-encounter objective (a weighted sum of a safety-margin barrier, COLREG compliance penalty, and route deviation; lower is better) and π^* is the reference maneuver. Unlike item correctness, $\mathcal{R}$ is continuous, objective, and instructor-free.

On “reference,” not “optimal.” We deliberately avoid claiming a global optimum. VO and SB-MPC are strong, widely-used near-optimal solvers, but neither is proven globally optimal for the full nonconvex encounter; calling their output “optimal” would overclaim. The instrument does not need a true optimum—only a reference that construct validity shows separates naive from expert

Policy	mean J	median	min	max	cleared
naive (hold course)	1543.88	1986.10	1.08	1994.13	22%
VO reference	0.71	0.58	0.33	1.27	100%
SB-MPC reference	0.03	0.01	0.00	0.17	100%

Table 1: Construct validity and grading across nine varied encounters. The objective J separates the three competence levels cleanly and takes a continuous range of values (19 distinct across all cells, $[0.00, 1994.13]$)—it is a graded transfer metric, not a near-binary check. `npm run colreg:construct`.

behavior (below). Regret is thus measured against a fixed, reproducible reference policy, and we report which solver is used.

Construct validity and metric grading. The instrument must separate good from bad policies before any learning claim, and—if it is to be a transfer measure rather than a pass/fail check—the metric must grade, not collapse to two values. Across a varied set of nine encounters (head-on, starboard/port crossing, overtaking, and restricted-visibility geometries), three policies of increasing competence separate cleanly and continuously on J (Table 1): a naive hold-course policy (mean $J \approx 1544$, clearing only 22% of domains), a velocity-obstacle reference ($J \approx 0.71$, all clear), and SB-MPC ($J \approx 0.03$). The objective takes 19 distinct values in $[0.00, 1994.13]$ over the policy $\times$ scenario cells—a graded metric, with the safe regime (VO/SB-MPC) itself spanning a continuous 0.00–1.27 range. On the discrete procedural domain the same logic holds: an expert policy scores $J = 0$ against a reckless $J = 200$ with the safety violation caught. This is the novice/expert-separation logic of Van Dongen et al. [26], applied to a decision/control task rather than manual skill.

kc $\rightarrow$ single-metric identifiability. We design each knowledge component to govern exactly one metric, so ablating a kc degrades that metric and no other. On the procedural domain this is exact: each ablated competence degrades only its governed metric, and a monotone competence $\rightarrow$ performance gradient ($J : 204 \rightarrow 0$) follows as competence is acquired in curriculum order. Because the property holds on both a continuous-control and a discrete-procedural instrument, it is a general measurement-design property, not a COLREG artifact.

Is identifiability tautological? A fair objection is that the mapping is a design choice, so “ablate the kc, that metric moves” is true by construction. Two things make it a testable property rather than a tautology. First, the cross-effect claim can fail: designing the metrics is not enough to guarantee that ablating one kc leaves the others unchanged—if the objective’s terms are entangled (e.g. a safety barrier that also moves the deviation term), ablation bleeds across metrics, and we measure and report that it does not. Identifiability is the empirically-checked absence of that bleed, not the presence of the intended effect. Second, the mapping is what makes the C1 diagnosis (Section 4) actionable: without it, a task failure cannot be attributed to a specific corpus rule. We therefore treat identifiability as a design requirement to be verified per instrument—a property an instrument can lack—and verifying it is part of building one, exactly as construct validity is.

Estimator recovery and calibration. Feeding the instrument’s outcomes into a generic learner-agent estimator, we recover known ground truth on synthetic data (Table 2). This turns “we have a metric” into “the measurement is valid.”

Estimator	Recovery of known ground truth	Calibration (ECE)
Elo	static ability, mean abs. error 0.046	0.023
BKT	latent state $P(\hat{L}) = 0.997$ (learned) vs. 0.175 (not)	0.004

Table 2: Estimator-recovery and calibration on synthetic data with a known ground truth. The measurement, not just the metric, is validated.

4 Bidirectional corpus diagnosis (C1)

The same instrument answers two opposite questions with one objective metric.

(i) Corpus-gap localization. When the corpus is missing or wrong on a rule, the learner’s failures on the governed metric have a signature that attributes the failure to a specific rule/node. We compute, per rule, an ablation-delta—the rise in the governed penalty when that rule is removed—and a localization that names the governed component. A large delta plus a matching localization means the learner relied on that corpus rule.

(ii) Parametric leakage detection. The mirror image: ablate a rule from the corpus; if the metric it governs does not degrade, the model is answering from pretrained priors, not the corpus. We combine the ablation-delta with a counterfactual test (replace “alter to starboard” with “alter to port”; does the learner follow the altered rule?) and a closed-book contamination baseline (no corpus supplied). The verdict—corpus-bound, leaking, or inconclusive—is read from the same metric. (The ablation signal uses the bounded compliance-penalty sub-metric in $[0, 1]$ —deliberately near-binary, since following a discrete steering rule is itself close to binary—not the graded transfer objective J of Table 1; the two measure different things.)

Offline recovery of known ground truth. Against two reference mock learners whose truth is known, the instrument recovers it exactly: the corpus-bound mock yields ablation-delta 1.000, follows the counterfactual, and abstains closed-book ($\Rightarrow$ corpus-bound); the leaking mock yields ablation-delta 0.000, ignores the counterfactual, and answers closed-book from priors ($\Rightarrow$ leaking).

Real-model discrimination. We run the instrument on six current production LLMs under both prompt conditions—bound (the strict corpus-binding positive control) and unconstrained (the binding clause removed, parametric fallback allowed)—and read the verdict off the same metric (Table 3). Three findings stand out. (1) The core leakage signal is universal: for every model, removing the binding clause collapses the ablation- δ to 0.000 (the governed metric stops depending on the corpus) and flips the closed-book baseline from abstention to answering from priors. (2) Capability tracks binding fidelity: the three stronger flash models bind tightly under the strict prompt ($\delta=1.000$) and, when unconstrained, land inconclusive rather than leaking—they stop relying on the corpus and contaminate closed-book, yet still comply with the counterfactual “alter-to-port” instruction, so the counterfactual sub-test holds the composite verdict back. The lighter models bind more weakly ($\delta=0.667/0.333$) and flip cleanly to leaking when unconstrained. (3) The instrument catches a binding failure: the lightest model (gemini-3.1-flash-lite) is diagnosed leaking even under the bound prompt—it ignores the corpus ($\delta=0.000$) and the counterfactual despite being told to use only the provided rules, exactly the kind of silent binding failure the instrument exists to surface. Mock learners (rows 1–2) bound the scale.

Learner	Condition	ablation- δ	counterfact.	closed-book	Verdict
mock (corpus-bound)	—	1.000	follows	abstains	corpus-bound
mock (leaking)	—	0.000	ignores	answers	leaking
gemini-flash-latest	bound	1.000	follows	abstains	corpus-bound
gemini-flash-latest	unconstr.	0.000	follows	answers	inconclusive
gemini-2.5-flash	bound	1.000	follows	abstains	corpus-bound
gemini-2.5-flash	unconstr.	0.000	follows	answers	inconclusive
gemini-3.5-flash	bound	1.000	follows	abstains	corpus-bound
gemini-3.5-flash	unconstr.	0.000	follows	answers	inconclusive
gemini-flash-lite-latest	bound	0.667	follows	abstains	corpus-bound
gemini-flash-lite-latest	unconstr.	0.000	ignores	answers	leaking
gemini-3.5-flash-lite	bound	0.333	follows	abstains	corpus-bound
gemini-3.5-flash-lite	unconstr.	0.000	ignores	answers	leaking
gemini-3.1-flash-lite	bound	0.000	ignores	abstains	leaking
gemini-3.1-flash-lite	unconstr.	0.000	ignores	answers	leaking

Table 3: C1 discrimination on six real LLMs (head-on instrument, δ threshold 0.15). Removing the corpus-binding clause collapses the ablation- δ to 0.000 and flips closed-book abstention to contamination for every model. Stronger flash models bind tightly and go inconclusive unconstrained (they keep following the counterfactual); lighter models flip to leaking; the lightest leaks even under the bound prompt—a binding failure the instrument catches. Mock learners (top) bound the scale.

5 Proxy learners as a pre-trial screen (application)

We exercise the instrument with two complementary controlled-competence proxy classes: (a) a parametric competence-vector learner, and (b) a knowledge-suppressed / unlearned LLM learner. Because both are scored on the same $\mathcal{R}$ instrument, a method that fails to move the instrument in the expected direction is a no-go before any human is recruited. This differs from prior proxy-learner work [9, 11, 14, 21, 25] in scoring on an objective control-task outcome rather than dialogue behavior, profile alignment, or LLM-judge helpfulness.

6 Weight-level cross-check via machine unlearning

A reviewer’s sharpest attack on C1 is that corpus context removal is not weight-level unlearning, so the “leakage” test is the no-context heuristic in disguise. We answer with an open-weight arm: remove the alter-to-starboard knowledge from an open-weight model with a real unlearning method—SimNPO [15] as primary (reference-free, length-normalized), with NPO [28], RMU [22], and gradient ascent [18] as baselines—and score the base vs. unlearned model on the reference-policy instrument. A removal audit [23] reports whether the knowledge is gone vs. merely suppressed; for a stable novice that resists benign relearning we layer in a robust utility-preserving recipe [6]. The predicted 2×2 : the base model scores low even without the corpus (it has the knowledge in weights); the unlearned model scores high without the corpus and recovers with it (weight-level corpus reliance). Nobody has scored an unlearned learner on a control-task regret metric; this gives C1 a weight-level leakage result beside the context-level one. The harness is built and CPU-smoke-tested; the real 7–8B run is GPU-gated.

7 Limitations and scope

Mechanism, not external validity. Every result here is simulation-based mechanism evidence. We make no learning-gains claim and pre-register the human cohort study as future work. Proxy validity. Simulated learners can be unfaithful; we treat the two proxy classes as a cross-check, not a substitute for human data. Instrument sensitivity. The protocol depends on weighting choices (ship domain, CRI, objective); a sensitivity analysis showing the protocol ranking is stable is outstanding. Model and domain coverage. The discrimination result (Table 3) covers six models within one provider family and one encounter type (head-on) and one rule (14/15); cross-provider models and more rules/encounters would further tighten the claim. Compute-gated: the open-weight unlearning run (Section 6) still needs one GPU.

8 Conclusion

We have described an in-silico instrument that lets a designer falsify the mechanism of a corpus-bounded instructional method before human-subject effort: a reference-policy transfer metric with $kc \rightarrow \text{single-metric}$ identifiability (C2), used bidirectionally to localize corpus gaps and detect parametric leakage on one closed-model-compatible metric (C1), exercised by two complementary proxy-learner classes. The claim is testable and narrow; the domains are worked examples, and the measurement method is the point.

Reproducibility. The simulator, instrument, diagnosis harness, proxy learners, and the open-weight unlearning scaffold are released, along with a deterministic no-key dry-run that recovers the mock ground truth and a one-tap GPU notebook for the unlearning arm.

References

- [1] Anonymous. Quantitative COLREG compliance evaluation for autonomous ships. Ocean Engineering, 2024.
- [2] Anonymous. Control knowledge tracing: A control-theoretic view of knowledge dynamics. In Conf. on AI in Education (CAEAI), 2024.
- [3] Anonymous. Quantification of transfer in reinforcement learning via regret bounds. In AAMAS, 2024.
- [4] Anonymous. FaithfulRAG: Faithfulness to provided context in retrieval-augmented generation, 2025.
- [5] Anonymous. AI meets maritime training: Precision analytics of simulator competency, 2025.
- [6] Anonymous. Unlearning that lasts: Utility-preserving, robust, and almost irreversible forgetting, 2025.
- [7] Anonymous. CUE-R: Causal utility evaluation of retrieval by evidence intervention, 2026.
- [8] Anonymous. Quantifying prior dominance in retrieval-augmented generation, 2026.
- [9] Anonymous. PS²: Parametric student simulation by competence interpolation, 2026.
- [10] Anonymous. SeedRG: Leakage-free retrieval-augmented benchmarks, 2026.
- [11] Apartsin, Sason, and Aperstein. Simulated students as suppressed-knowledge skill vectors, 2026.
- [12] Susan Bull and Judy Kay. Student models that invite the learner in: The SMILI open learner modelling framework. International Journal of Artificial Intelligence in Education, 17(2):89–120, 2007.

- [13] Albert T. Corbett and John R. Anderson. Knowledge tracing: Modeling the acquisition of procedural knowledge. *User Modeling and User-Adapted Interaction*, 4(4):253–278, 1994.
- [14] Fan, Deng, and Xu. Rethinking LLM-judged helpfulness as a pedagogy signal: A pre-registered audit across tutor models, 2026.
- [15] Fan et al. Simplicity prevails: Rethinking negative preference optimization for LLM unlearning, 2024.
- [16] Paolo Fiorini and Zvi Shiller. Motion planning in dynamic environments using velocity obstacles. *International Journal of Robotics Research*, 17(7):760–772, 1998.
- [17] International Maritime Organization. Convention on the international regulations for preventing collisions at sea (COLREGs), 1972.
- [18] Jang et al. Knowledge unlearning for mitigating privacy risks in language models, 2023.
- [19] Tor A. Johansen, Tristan Perez, and Andrea Cristofaro. Ship collision avoidance and COLREGS compliance using simulation-based control behavior selection with predictive hazard assessment. *IEEE Transactions on Intelligent Transportation Systems*, 17(12):3407–3422, 2016.
- [20] Kenneth R. Koedinger, Albert T. Corbett, and Charles Perfetti. The Knowledge-Learning-Instruction framework: Bridging the science-practice chasm to enhance robust student learning. *Cognitive Science*, 36(5):757–798, 2012.
- [21] Lee et al. EduClaw-Bench: A simulated-learner benchmark for pre-deployment screening of AIED innovations, 2026.
- [22] Li et al. The WMDP benchmark and representation misdirection for unlearning (RMU), 2024.
- [23] Lynch et al. Eight methods to evaluate robust unlearning in LLMs, 2024.
- [24] Radek Pelánek. Applications of the Elo rating system in adaptive educational systems. *Computers & Education*, 98:169–179, 2016.
- [25] Song, Guo, and Lin. Learning by teaching: Unlearning an LLM into a stable novice student, 2026.
- [26] K. W. Van Dongen et al. Construct validity of the LapSim: Can the LapSim virtual reality simulator distinguish between novices and experts? *Surgical Endoscopy*, 21(8):1413–1417, 2007.
- [27] Lev S. Vygotsky. *Mind in Society: The Development of Higher Psychological Processes*. Harvard University Press, 1978.
- [28] Zhang et al. Negative preference optimization: From catastrophic collapse to effective unlearning, 2024.
- [29] Zinn et al. Assessing flight competency from deviation to an optimal trajectory. *Cognition, Technology & Work*, 2023.