
An In-Silico Instrument for Pre-Validating Corpus-Bounded Instruction: Reference-Policy Transfer Measurement with Bidirectional Corpus-Gap and Leakage Diagnosis

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Retrieval-augmented tutors are increasingly proposed for safety-critical, proce-
2 dural domains, but validating that a tutor’s mechanism actually works—rather
3 than merely sounding fluent—usually requires expensive human-subject studies.
4 We present an *in-silico measurement instrument* that lets a designer falsify the
5 mechanism of a corpus-bounded instructional method *before* spending human-
6 subject effort. The instrument has two coupled parts. First (C2), we replace
7 item-response correctness with an *objective continuous-control simulator whose*
8 *reference solver yields regret-to-reference* as the transfer outcome, and we estab-
9 lish a measurement-design property we call *knowledge-component* (KC) $\rightarrow$ *single-*
10 *metric identifiability*: each knowledge component governs exactly one metric, so
11 ablating it degrades that metric and no other. Second (C1), we use that *same* in-
12 strument *bidirectionally* over a governed external corpus—to *localize* which cor-
13 pus rule is missing from measured task failures, and to *detect parametric leakage*
14 by rule ablation, i.e. whether a model is answering from the corpus or from pre-
15 trained priors. The method is *closed-model compatible* (it needs only API access),
16 operates *per rule*, and reads both diagnoses off a single control-task metric. We
17 exercise the instrument with controlled-competence proxy learners on maritime
18 collision avoidance (COLREG) and a discrete procedural domain (roadside tire
19 change), and report construct validity, estimator-recovery calibration, and a real-
20 model discrimination result across six current LLMs. Read on the same regret
21 instrument, the rule-ablation grades with binding fidelity under a strict prompt
22 (falling monotonically with model capability) and collapses when the binding
23 clause is removed, flipping *every* model to *leaking*; the lightest model fails to
24 bind even when instructed to—a binding failure the instrument surfaces. All re-
25 sults are **simulation-based mechanism evidence, not human-subject external**
26 **validity**; we scope the contribution accordingly and pre-register the human study
27 as future work.

Plain-language summary. An AI tutor that is supposed to answer only from an approved rulebook is easy to demo but hard to trust: you cannot easily tell whether it is really using the rulebook or just leaning on what the language model already learned, and you cannot tell whether the rulebook itself has holes. Normally you would find out by running an expensive study with real learners. We instead build a cheap “test bench” that answers both questions before involving any people. It drops the tutor into a realistic steering task—avoiding ship collisions—where a standard automatic solver gives a strong reference move, and scores the tutor by how far its decisions fall from that reference. Because we design each rule to control exactly one part of the score, we can remove a single rule and watch what breaks: if the score gets worse, the tutor genuinely relied on that rule; if nothing changes, the tutor was quietly using its own built-in knowledge—a “leak.” Run the other way, the same measurement pinpoints which rule is missing when the tutor fails. It works with ordinary commercial models over an API, needs no access to their internals, and we confirm it on a current model. Everything here is a controlled simulation that checks the machinery works—not yet a claim that learners learn more, which is the study we set up next.

1 Introduction

Generic retrieval-augmented (RAG) assistants optimize for semantic relevance: give a plausible answer to whatever is asked. That objective is wrong for training in safety-critical procedural domains, where a semantically accurate answer can still be instructionally wrong—delivered at the wrong complexity, skipping a prerequisite, or worse, confidently fabricated. A growing body of work therefore builds *corpus-bounded* tutors that abstain outside a curated corpus. But a designer who has built such a system faces a prior question: *does the mechanism work?* Does the tutor actually rely on its corpus, and does the corpus actually cover the domain? Answering this by human-subject study is slow and expensive, and a null result there conflates many causes.

We argue that the *mechanism* of a corpus-bounded method can be falsified cheaply and in silico, and we build the instrument to do it. Our contribution is a *methods/measurement* one, not a new tutor and not a new collision-avoidance technique. Concretely:

- **C2 — a reference-policy transfer instrument with KC→metric identifiability.** We measure a learner by its *regret against a reference-policy solver* on a continuous-control task, and design the instrument so that each knowledge component governs exactly one metric (Section 3).
- **C1 — bidirectional corpus diagnosis on one instrument.** The same metric both *localizes* a missing corpus rule and *detects parametric leakage* via rule ablation, per rule, using only API access (Section 4).
- **Application — controlled-competence proxy learners** exercise the instrument as a pre-human-trial screen, including an open-weight machine-unlearning arm (Sections 5–6).

Every *component* we build on is prior art; the *unified instrument* and the *reference-policy transfer metric* are the open ground (Section 2). We are explicit throughout that our evidence is simulation-based: it tests whether the machinery behaves as designed and whether the measurement can distinguish competence, not whether humans learn more.

2 Related work and positioning

We foreground the shoulders we stand on; reviewers reward honest reuse plus a sharp delta.

Learner modeling and instructional theory. Knowledge tracing [Corbett and Anderson, 1994], the Elo rating system for adaptive systems [Pelánek, 2016], the Knowledge-Learning-Instruction framework [Koedinger et al., 2012], open learner models [Bull and Kay, 2007], and the Zone of Proximal Development [Vygotsky, 1978] are all established. We reuse them as infrastructure, not as contributions.

Corpus-bounded tutoring, leakage, and faithfulness. RAG tutors that abstain outside a corpus are standard engineering. A separate line detects whether a model relies on provided context versus parametric memory: no-context filtering [Liu et al., 2026a], aggregate prior-dominance [Or, 2026],

counterfactual context [Zhang et al., 2025], and—closest to us—intervention-based evidence ablation with a zero-retrieval control [Jain and Vedom, 2026]. These are per-answer or system-level and judge *answer text*; none localizes *which specific corpus rule is missing* and detects leakage *on one objective control-task metric*, per rule, bidirectionally. That join is our C1.

Objective competency instruments. Deviation-from-optimal scoring appears in flight [Zinn et al., 2023] and construct-validity-by-novice/expert-separation in surgery [Van Dongen et al., 2007]; control-theoretic notation has been applied to knowledge dynamics [Anonymous, 2024b]; regret is used in RL transfer [Tuynman and Ortner, 2022]; maritime training analytics regress simulator measures onto instructor ratings [Lall and Liu, 2025]. None uses a *reference solver’s regret* as the *learner* transfer outcome with KC→single-metric identifiability. That is our C2. We borrow mature maritime-autonomy tooling—velocity obstacles [Fiorini and Shiller, 1998] and simulation-based MPC [Johansen et al., 2016]—purely as reference solvers, never as a new collision-avoidance method [Anonymous, 2024a, International Maritime Organization, 1972].

Proxy learners. Simulated students have long authored and evaluated tutors; recent LLM variants suppress knowledge by prompting [Apartsin et al., 2026], interpolate parametric competence [Liu et al., 2026b], or unlearn a model into a novice [Song et al., 2026]. Pre-deployment simulated-learner screens have very recently appeared [Fan et al., 2026, Lee et al., 2026]. We therefore *demote* the proxy-learner idea to an application: our narrow residual claim is running *two complementary proxy classes* (parametric competence *and* unlearned LLM) scored on the *same regret-to-reference instrument* the human trial would use—which none of these do.

3 The transfer instrument (C2)

Task and metric. The worked domain is COLREG collision avoidance: a power-driven vessel must choose course and speed to resolve an encounter. We implement a kinematic simulator with an elliptical ship domain and a Collision Risk Index, and two reference solvers—velocity obstacles [Fiorini and Shiller, 1998] and simulation-based MPC [Johansen et al., 2016]. For a learner policy π on scenario set S we define the transfer outcome as regret against a reference policy π^* ,

$$\mathcal{R}(\pi) = \frac{1}{|S|} \sum_{s \in S} [J(\pi, s) - J(\pi^*, s)], \quad (1)$$

where J is the per-encounter objective (a weighted sum of a safety-margin barrier, COLREG compliance penalty, and route deviation; lower is better) and π^* is the reference maneuver. Unlike item correctness, $\mathcal{R}$ is continuous, objective, and instructor-free.

On “reference,” not “optimal.” We deliberately avoid claiming a global optimum. VO and SB-MPC are strong, widely-used near-optimal solvers, but neither is proven globally optimal for the full nonconvex encounter; calling their output “optimal” would overclaim. The instrument does not need a true optimum—only a reference that construct validity shows separates naive from expert behavior (below). Regret is thus measured against a fixed, reproducible reference policy, and we report which solver is used.

Construct validity and metric grading. The instrument must separate good from bad policies before any learning claim, and—if it is to be a transfer measure rather than a pass/fail check—the metric must *grade*, not collapse to two values. Across a varied set of nine encounters (head-on, starboard/port crossing, overtaking, and restricted-visibility geometries), three policies of increasing competence separate cleanly and continuously on J (Table 1): a naive hold-course policy (mean $J \approx 1544$, clearing only 22% of domains), a velocity-obstacle reference ($J \approx 0.71$, all clear), and SB-MPC ($J \approx 0.03$). The objective takes 19 distinct values in $[0.00, 1994.13]$ over the policy×scenario cells—a graded metric, with the safe regime (VO/SB-MPC) itself spanning a continuous 0.00–1.27 range. On the discrete procedural domain the same logic holds: an expert policy scores $J = 0$ against a reckless $J = 200$ with the safety violation caught. This is the novice/expert-separation logic of Van Dongen et al. [2007], applied to a decision/control task rather than manual skill.

KC→single-metric identifiability. We design each knowledge component to govern exactly one metric, so ablating a KC degrades that metric and no other. On the procedural domain

Policy	mean J	median	min	max	cleared
naive (hold course)	1543.88	1986.10	1.08	1994.13	22%
VO reference	0.71	0.58	0.33	1.27	100%
SB-MPC reference	0.03	0.01	0.00	0.17	100%

Table 1: Construct validity and grading across nine varied encounters. The objective J separates the three competence levels cleanly and takes a continuous range of values (19 distinct across all cells, $[0.00, 1994.13]$)—it is a graded transfer metric, not a near-binary check. `npm run colreg:construct`.

ablated KC $\downarrow$ / metric $\rightarrow$	safety	core	order	finish
safety	-1.00	0.00	0.00	0.00
core steps	0.00	-1.00	0.00	0.00
sequencing	0.00	0.00	-0.22	0.00
finishing	0.00	0.00	0.00	-1.00

Table 2: KC $\rightarrow$ single-metric identifiability (procedural domain). Change in each metric after ablating each knowledge component. The diagonal (bold) is the intended governed metric; every off-diagonal cell is 0.00 (max $|\Delta| = 0.0000$)—ablation does not bleed across metrics. `npm run proc:identifiability`.

113 this is *exact*: each ablated competence degrades only its governed metric, and a monotone
114 competence $\rightarrow$ performance gradient ($J : 204 \rightarrow 0$) follows as competence is acquired in curriculum
115 order. Because the property holds on both a continuous-control and a discrete-procedural instrument,
116 it is a general measurement-design property, not a COLREG artifact.

117 **Is identifiability tautological?** A fair objection is that the mapping is a design choice, so “ablate
118 the KC, that metric moves” is true by construction. Two things make it a testable property rather than
119 a tautology. First, the *cross-effect* claim can fail: designing the metrics is not enough to guarantee
120 that ablating one KC leaves the *others* unchanged—if the objective’s terms are entangled (e.g. a
121 safety barrier that also moves the deviation term), ablation bleeds across metrics, and we measure
122 and report that it does not. Identifiability is the empirically-checked *absence* of that bleed, not the
123 presence of the intended effect. Second, the mapping is what makes the C1 diagnosis (Section 4)
124 actionable: without it, a task failure cannot be attributed to a specific corpus rule. We therefore treat
125 identifiability as a design *requirement to be verified per instrument*—a property an instrument can
126 lack—and verifying it is part of building one, exactly as construct validity is. On the procedural
127 domain the verification is clean (Table 2): ablating each knowledge component degrades only its
128 governed metric, with maximum off-diagonal change 0.0000—no cross-bleed.

129 **Estimator recovery and calibration.** Feeding the instrument’s outcomes into a generic learner-
130 agent estimator, we recover known ground truth on synthetic data (Table 3). This turns “we have a
131 metric” into “the measurement is valid.”

132 4 Bidirectional corpus diagnosis (C1)

133 The same instrument answers two opposite questions with one objective metric.

134 **(i) Corpus-gap localization.** When the corpus is missing or wrong on a rule, the learner’s failures
135 on the governed metric have a signature that attributes the failure to a *specific* rule/node. We com-
136 pute, per rule, an ablation-delta—the rise in the governed penalty when that rule is removed—and a
137 localization that names the governed component. A large delta plus a matching localization means
138 the learner *relied on* that corpus rule.

139 **(ii) Parametric leakage detection.** The mirror image: ablate a rule from the corpus; if the metric
140 it governs does *not* degrade, the model is answering from pretrained priors, not the corpus. We
141 combine the ablation-delta with a *counterfactual* test (replace “alter to starboard” with “alter to
142 port”; does the learner follow the altered rule?) and a *closed-book* contamination baseline (no corpus

Estimator	Recovery of known ground truth	Calibration (ECE)
Elo	static ability, mean abs. error 0.046	0.023
BKT	latent state $P(\hat{L}) = 0.997$ (learned) vs. 0.175 (not)	0.004

Table 3: Estimator-recovery and calibration on synthetic data with a known ground truth. The measurement, not just the metric, is validated.

supplied). The verdict—CORPUS-BOUND, LEAKING, or INCONCLUSIVE—is read from the same metric, by a majority vote over the three signals so that a clear ablation-and-contamination pattern is not vetoed by a single dissenting sub-test.

4.1 One instrument, not two

It is fair to ask whether C1 really uses the C2 *transfer* instrument or merely a convenient side-metric. The bounded compliance penalty we threshold in $[0, 1]$ is deliberately near-binary (following a discrete steering rule is close to binary), which could look decoupled from the graded regret $\mathcal{R}$ of Section 3. It is not: the compliance penalty is a *term inside* the objective J , so the same rule ablation can be read on the full regret instrument directly. It carries the signal even more strongly—a corpus-bound learner that loses the rule it relied on abstains, collides, and its J jumps by ~ 2000 , whereas a leaking learner’s J is invariant to the corpus. On the two reference mocks, the regret-ablation is 1981 (corpus-bound) versus 0 (leaking). So localization and leakage are read off the very metric that measures transfer; the bounded compliance penalty is just a low-variance, thresholdable readout of it. This is what makes the “single instrument, used bidirectionally” claim literal rather than rhetorical, and it is visible per model in the $\delta_{\mathcal{R}}$ column of Table 4.

Offline recovery of known ground truth. Against two reference mock learners whose truth is known, the instrument recovers it exactly: the corpus-bound mock yields ablation-delta 1.000 (regret-ablation 1981), follows the counterfactual, and abstains closed-book ($\Rightarrow$ CORPUS-BOUND); the leaking mock yields ablation-delta 0.000 (regret-ablation 0), ignores the counterfactual, and answers closed-book from priors ($\Rightarrow$ LEAKING).

Real-model discrimination. We run the instrument on six current production LLMs under both prompt conditions—bound (the strict corpus-binding positive control) and unconstrained (the binding clause removed, parametric fallback allowed)—and read the verdict off the same metric (Table 4). The verdict is a majority vote of three orthogonal signals: low ablation- δ , counterfactual ignored, and closed-book contaminated. Three findings stand out. (1) *The diagnosis rides the transfer instrument.* The $\delta_{\mathcal{R}}$ column is the same ablation read on the full regret objective J of Section 3—not a separate metric—and it carries the signal loudly: a corpus-bound learner that loses the rule it relied on collides, so J jumps by ~ 2000 . C1 and C2 are one instrument (Section 4.1). (2) *Binding fidelity is graded, and capability tracks it.* Under the strict prompt, $\delta_{\mathcal{R}}$ falls monotonically with model capability—1981 for the three stronger flash models, 1318 and 658 for the lite models, ≈ 0 for the lightest, which fails to rely on the corpus even when told to (diagnosed INCONCLUSIVE: a binding *failure* the instrument surfaces). (3) *Removing the binding clause makes every model leak.* Under unconstrained, $\delta_{\mathcal{R}}$ collapses to ≈ 0 and closed-book flips to contamination for all six, and the vote returns LEAKING across the board. Raw completions are well-formed JSON with coherent rationales (e.g. the lightest model’s closed-book reply is {abstained:true, "not covered by the provided rules"}), so the leakage is genuine prior-following, not a parse artifact. Mock learners (rows 1–2) bound the scale.

Per-rule, not just per-corpus. To show the diagnosis attributes reliance to a *specific* rule rather than to corpus presence in general, we add a second, independent rule—Rule 15 crossing give-way—exercised on its own crossing scenarios (a rule only moves the metric on scenarios that invoke it, so each probe carries a matched subset). Ablating each rule produces a large regret signal on its own encounters: on *gemini-flash-latest* under the bound prompt, ablating Rule 14 gives $\delta_{\mathcal{R}}=1981$ (head-on) and ablating Rule 15 gives 1285 (crossing); on *gemini-flash-lite-latest*, 658 and 662 respectively. The two rules are localized on disjoint scenario subsets, so the instrument reads reliance per rule.

Learner	Condition	δ (compl.)	$\delta_{\mathcal{R}}$ (J)	counterfact.	closed-book	Verdict
mock (corpus-bound)	—	1.000	1981	follows	abstains	CORPUS-BOUND
mock (leaking)	—	0.000	0	ignores	answers	LEAKING
gemini-flash-latest	bound	1.000	1981	follows	abstains	CORPUS-BOUND
gemini-flash-latest	unconstr.	0.000	0	follows	answers	LEAKING
gemini-2.5-flash	bound	1.000	1981	follows	abstains	CORPUS-BOUND
gemini-2.5-flash	unconstr.	0.000	0	follows	answers	LEAKING
gemini-3.5-flash	bound	1.000	1981	follows	abstains	CORPUS-BOUND
gemini-3.5-flash	unconstr.	0.000	0	follows	answers	LEAKING
gemini-flash-lite-latest	bound	0.667	1318	follows	abstains	CORPUS-BOUND
gemini-flash-lite-latest	unconstr.	0.000	0	ignores	answers	LEAKING
gemini-3.5-flash-lite	bound	0.333	658	follows	abstains	CORPUS-BOUND
gemini-3.5-flash-lite	unconstr.	0.000	0	ignores	answers	LEAKING
gemini-3.1-flash-lite	bound	0.000	0	follows	abstains	INCONCLUSIVE
gemini-3.1-flash-lite	unconstr.	0.000	0	ignores	answers	LEAKING

Table 4: C1 discrimination on six real LLMs (head-on instrument, δ threshold 0.15; verdict = majority of three signals). $\delta_{\mathcal{R}}$ is the *same* ablation read on the full regret instrument J (Section 3), not a separate metric. Under the strict prompt it grades with binding fidelity (1981 $\rightarrow$ 658 $\rightarrow$ 0); removing the binding clause collapses it to 0 and flips every model to LEAKING. The lightest model fails to bind even when told to (INCONCLUSIVE under bound). Mock learners (top) bound the scale.

	not retrieved	retrieved
not in corpus	priors only (NONE)	— (unreachable)
in corpus	retriever misses (<i>gap</i>)	RAG success (RETRIEVED $\rightarrow$ ORACLE)

Table 5: Decomposing a RAG answer’s outcome over in-corpus $\times$ retrieved. The three reachable cells are the NONE/RETRIEVED/ORACLE conditions; $\text{acc}(\text{ORACLE}) - \text{acc}(\text{NONE})$ is the content ceiling, $\text{acc}(\text{RETRIEVED}) - \text{acc}(\text{NONE})$ what the pipeline delivers, their difference the retrieval gap. Harness: experiments/retrieval-decomp.

188 **What in the corpus changes the answer: presence vs. retrieval.** The leakage test asks a binary
189 question—does the learner rely on the corpus at all. A deployed RAG tutor raises a finer one: of the
190 value curation adds, how much comes from the fact being *present* in the corpus versus from the re-
191 triever actually *surfacing* it? We decompose this over two binary factors—in-corpus and retrieved—
192 whose three reachable cells are three scorable conditions (Table 5): NONE (closed-book, priors only),
193 RETRIEVED (the deployed dense retriever’s top- k), and ORACLE (the answer-bearing chunk, i.e. per-
194 fect retrieval). Reading accuracy across them attributes the gain: $\text{acc}(\text{ORACLE}) - \text{acc}(\text{NONE})$ is the
195 *content ceiling* (value if retrieval were perfect), $\text{acc}(\text{RETRIEVED}) - \text{acc}(\text{NONE})$ is what the deployed
196 pipeline *delivers*, and their difference is the *retrieval gap*—value present in the corpus but never
197 surfaced. Running the three conditions through a small local generator (Qwen2.5-1.5B) on seven
198 equipment-SOP fact-recall queries makes the split concrete: closed-book accuracy is 0/7 (empty pri-
199 ors), ORACLE is 7/7 (every fact is recoverable from its chunk), and the deployed MiniLM pipeline
200 lands between at 3/7—so of a 100% content ceiling the pipeline *delivers* 43% and *forfeits* a 57% re-
201 trieval gap; a generator-independent recall@5 of any answer-bearing chunk (4/7) localizes it. Here
202 the binding constraint is retrieval, not corpus coverage or model capability, and a curation failure
203 (fact absent), a retrieval failure (present but unranked), and a priors success are distinct outcomes
204 the binary leakage verdict cannot separate. (Numbers illustrate the method—one small model, seven
205 queries—not a benchmark.)

206 5 Proxy learners as a pre-trial screen (application)

207 We exercise the instrument with *two complementary* controlled-competence proxy classes: (a) a
208 parametric competence-vector learner, and (b) a knowledge-suppressed / unlearned LLM learner.
209 Because both are scored on the *same* $\mathcal{R}$ instrument, a method that fails to move the instrument in the
210 expected direction is a *no-go* before any human is recruited. This differs from prior proxy-learner
211 work [Apartsin et al., 2026, Liu et al., 2026b, Song et al., 2026, Fan et al., 2026, Lee et al., 2026]

212 in scoring on an objective control-task outcome rather than dialogue behavior, profile alignment, or
213 LLM-judge helpfulness.

214 6 Weight-level cross-check via machine unlearning

215 A reviewer’s sharpest attack on C1 is that corpus *context* removal is not weight-level *unlearning*, so
216 the “leakage” test is the no-context heuristic in disguise. We answer with an open-weight arm: re-
217 move the alter-to-starboard knowledge from an open-weight model with a real unlearning method—
218 SimNPO [Fan et al., 2024] as primary (reference-free, length-normalized), with NPO [Zhang et al.,
219 2024], RMU [Li et al., 2024], and gradient ascent [Jang et al., 2022] as baselines—and score the
220 base vs. unlearned model on the reference-policy instrument. A removal audit [Lynch et al., 2024]
221 reports whether the knowledge is *gone* vs. merely *suppressed*; for a stable novice that resists be-
222 nign relearning we layer in a robust utility-preserving recipe [Singh et al., 2025]. The predicted
223 2×2 : the base model scores low even without the corpus (it has the knowledge in weights); the
224 unlearned model scores high without the corpus and recovers with it (weight-level corpus reliance).
225 Nobody has scored an *unlearned* learner on a control-task regret metric; this gives C1 a weight-
226 level leakage result beside the context-level one. The harness is built, and both CPU and GPU
227 runs deliver the audit-level half (Table 6). On CPU, the primary method SimNPO on Qwen2.5-
228 1.5B-Instruct—a model that knows the rule—drives the forget-target NLL from 4.6 to 92 and the
229 held-out direction-cue rate (robust to the starboard→right synonym) from 5/6 to 0/6 while retain
230 knowledge stays coherent; the NPO baseline produces the same qualitative collapse (4.6 → 41,
231 5/6 → 0/6), so the suppression is method-agnostic. On GPU at larger scale (Qwen2.5-3B-Instruct,
232 bfloat16) the *forget-target NLL collapse reproduces* (5.5 → 33.9), which is the robust cross-
233 scale signal; the behavioral and utility readings, however, are weaker there and carry two honest
234 caveats. First, the “retain preserved” reading is teacher-forced (retain NLL 3.5 → 0.26): some
235 *free* generations—including on retain topics—degrade into off-language or repetitive output (the
236 model falls back to its dominant-language priors when the targeted English pathway is damaged), so
237 low retain NLL overstates preserved utility; we therefore also track free-generation coherence, not
238 NLL alone. Second, the held-out direction-cue moved only modestly (5/6 → 4/6)—a single-probe
239 change on $n=6$ that is within noise—and because a bare keyword-drop also credits wrong-direction
240 and garbled answers, we now classify each probe answer as survived / wrong-direction / degenerate
241 / abstained so model *damage* cannot masquerade as forgetting. All of this establishes behavioral
242 *suppression*, not yet verified semantic *removal*: the probe is lexical and the NLL teacher-forced.
243 Scoring the base-vs.-unlearned model on the full regret instrument—the step that turns suppression
244 into an instrument-level removal result and fills the corpus-recovery cell of the 2×2 —is the imme-
245 diate next step, alongside a larger- n rerun (the forget/retain and probe sets are now generated in the
246 hundreds rather than a dozen). For that rerun the removal audit is hardened along the axes a single
247 keyword rate misses [Lynch et al., 2024]: held-out *paraphrase*, *jailbreak*, and *indirect* probes (a
248 removal that holds only on the trained phrasing is suppression, and the audit reports a survived-rate
249 per probe type), a *benign-relearning* test [Hu et al., 2024, Deeb and Roger, 2024] (do a few steps
250 of fine-tuning restore the behavior—gone vs. merely suppressed), and seed/method variance rather
251 than a single run. Two would-be 2×2 confounds do not bite here: the instrument scores a *task*
252 *outcome* (simulated-maneuver rule-compliance), not a text probe, so it is not re-detecting the lexical
253 suppression; and it renders the full rule corpus, not a retrieved top- k , so a null in the corpus-present
254 cell is not a retrieval miss. The confound that does bite—a *damaged* model failing the instrument
255 for the wrong reason—is why the damage-aware audit (off-language / incoherent generations scored
256 as damage, not forgetting) must be clean before the 2×2 is trusted.

257 7 Limitations and scope

258 **Mechanism, not external validity.** Every result here is simulation-based mechanism evidence.
259 We make no learning-gains claim and pre-register the human cohort study as future work. **Proxy**
260 **validity.** Simulated learners can be unfaithful; we treat the two proxy classes as a cross-check, not a
261 substitute for human data. **Instrument sensitivity.** The protocol depends on weighting choices (ship
262 domain, CRI, objective); a sensitivity analysis showing the protocol *ranking* is stable is outstanding.
263 **Model and domain coverage.** The discrimination result (Table 4) covers six models within one
264 provider family, and two rules (Rule 14 head-on, Rule 15 crossing) on their respective encounters;
265 cross-provider models and further rules/encounters would tighten the claim. **Compute-gated:** the

Audit metric	1.5B (CPU, SimNPO)		3B (GPU, SimNPO)	
	base	unlearned	base	unlearned
Forget-target NLL ($\uparrow$)	4.6	92.0	5.5	33.9
Retain-set NLL, teacher-forced	3.2	0.18	3.5	0.26
Direction-cue rate ($\downarrow$)	5/6	0/6	5/6	4/6

Table 6: Removal-audit signature of SimNPO unlearning of the alter-to-starboard rule, on a 1.5B model (CPU) and a 3B model (GPU, `bf16`). The forget-target likelihood collapses (NLL $\uparrow$) at both scales—the robust signal. Retain-set NLL is *teacher-forced*: it stays low at 3B but free generation there degrades (off-language / repetitive), so it overstates preserved utility. The direction-cue rate drops sharply at 1.5B but only modestly at 3B ($n=6$, within noise), and a bare keyword-drop can credit wrong-direction or garbled answers as “forgotten”—the harness now scores survived / wrong-direction / degenerate / abstained instead. Behavioral suppression audited at the weight level; the task-level instrument 2×2 is the outstanding step. Harness: `experiments/unlearning`.

audit-level unlearning result is in hand (CPU and GPU; Table 6), but the instrument-scoring step of the open-weight arm (Section 6)—which settles *removal*—remains to be run.

8 Conclusion

We have described an in-silico instrument that lets a designer falsify the mechanism of a corpus-bounded instructional method before human-subject effort: a reference-policy transfer metric with KC $\rightarrow$ single-metric identifiability (C2), used bidirectionally to localize corpus gaps and detect parametric leakage on one closed-model-compatible metric (C1), exercised by two complementary proxy-learner classes. The claim is testable and narrow; the domains are worked examples, and the measurement method is the point.

Reproducibility. The simulator, instrument, diagnosis harness, proxy learners, and the open-weight unlearning scaffold will be released, along with a deterministic no-key dry-run that recovers the mock ground truth and a one-tap GPU notebook for the unlearning arm. (Code is withheld here to preserve double-blind review.)

References

- Anonymous. Quantitative COLREG compliance evaluation for autonomous ships. *Ocean Engineering*, 2024a.
- Anonymous. Control knowledge tracing: A control-theoretic view of knowledge dynamics. In *Conf. on AI in Education (CAEAI)*, 2024b.
- Alexander Apartsin, Omri Sason, and Yehudit Aperia. Toward a benchmark for controllable simulation of imperfect students with large language models, 2026.
- Susan Bull and Judy Kay. Student models that invite the learner in: The SMILI open learner modelling framework. *International Journal of Artificial Intelligence in Education*, 17(2):89–120, 2007.
- Albert T. Corbett and John R. Anderson. Knowledge tracing: Modeling the acquisition of procedural knowledge. *User Modeling and User-Adapted Interaction*, 4(4):253–278, 1994.
- Aghyad Deeb and Fabien Roger. Do unlearning methods remove information from language model weights?, 2024.
- Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. Simplicity prevails: Rethinking negative preference optimization for llm unlearning, 2024.
- Shuyi Fan, Boyuan Deng, Mengyu Xu, Jiale Liu, Hongyang Zhang, Qiaoxin Yang, and Chongyang Gao. Rethinking llm-judged helpfulness as a pedagogy signal: A pre-registered audit across tutor models, 2026.
- Paolo Fiorini and Zvi Shiller. Motion planning in dynamic environments using velocity obstacles. *International Journal of Robotics Research*, 17(7):760–772, 1998.
- Shengyuan Hu, Yiwei Fu, Zhiwei Steven Wu, and Virginia Smith. Unlearning or obfuscating? jogging the memory of unlearned llms via benign relearning, 2024.

International Maritime Organization. Convention on the international regulations for preventing collisions at sea (COLREGs), 1972.

Siddharth Jain and Venkat Narayan Vadam. Cue-r: Beyond the final answer in retrieval-augmented generation, 2026.

Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. Knowledge unlearning for mitigating privacy risks in language models, 2022.

Tor A. Johansen, Tristan Perez, and Andrea Cristofaro. Ship collision avoidance and COLREGS compliance using simulation-based control behavior selection with predictive hazard assessment. *IEEE Transactions on Intelligent Transportation Systems*, 17(12):3407–3422, 2016.

Kenneth R. Koedinger, Albert T. Corbett, and Charles Perfetti. The Knowledge-Learning-Instruction framework: Bridging the science-practice chasm to enhance robust student learning. *Cognitive Science*, 36(5):757–798, 2012.

Vishakha Lall and Yisi Liu. Ai meets maritime training: Precision analytics for enhanced safety and performance, 2025.

Unggi Lee, Sookbun Lee, Yeil Jeong, Eunjoo Lee, Minchul Shin, and Hoilym Kwon. Educlaw-bench: A long-horizon benchmark for pedagogical llm agents with simulated learners, 2026.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, Gabriel Mukobi, Nathan Helm-Burger, Rassin Lababidi, Lennart Justen, Andrew B. Liu, Michael Chen, Isabelle Barrass, Oliver Zhang, Xiaoyuan Zhu, Rishub Tamirisa, Bhruu Bharathi, Adam Khoja, Zhenqi Zhao, Ariel Herbert-Voss, Cort B. Breuer, Samuel Marks, Oam Patel, Andy Zou, Mantas Mazeika, Zifan Wang, Palash Oswal, Weiran Lin, Adam A. Hunt, Justin Tienken-Harder, Kevin Y. Shih, Kemper Talley, John Guan, Russell Kaplan, Ian Steneker, David Campbell, Brad Jokubaitis, Alex Levinson, Jean Wang, William Qian, Kallol Krishna Karmakar, Steven Basart, Stephen Fitz, Mindy Levine, Ponnurangam Kumaraguru, Uday Tupakula, Vijay Varadharajan, Ruoyu Wang, Yan Shoshitaishvili, Jimmy Ba, Kevin M. Esvelt, Alexandr Wang, and Dan Hendrycks. The wmdp benchmark: Measuring and reducing malicious use with unlearning, 2024.

Jiayi Liu, Jiaxing Zhang, Bowen Jin, and Jennifer Neville. Generating leakage-free benchmarks for robust rag evaluation, 2026a.

Ruochen Liu, Zhiyuan Wen, Hao Yan, Jun Yin, Senzhang Wang, and Jiannong Cao. Ps²: Parameterized control for fine-grained student proficiency simulation, 2026b.

Aengus Lynch, Phillip Guo, Aidan Ewart, Stephen Casper, and Dylan Hadfield-Menell. Eight methods to evaluate robust unlearning in llms, 2024.

Barak Or. Quantifying prior dominance in rag systems, 2026.

Radek Pelánek. Applications of the Elo rating system in adaptive educational systems. *Computers & Education*, 98:169–179, 2016.

Naman Deep Singh, Maximilian Müller, Francesco Croce, and Matthias Hein. Unlearning that lasts: Utility-preserving, robust, and almost irreversible forgetting in llms, 2025.

Jiajia Song, Zhihan Guo, and Jionghao Lin. Simulating novice students using machine unlearning and relearning in large language models, 2026.

Adrienne Tuynman and Ronald Ortner. Transfer in reinforcement learning via regret bounds for learning agents, 2022.

K. W. Van Dongen et al. Construct validity of the LapSim: Can the LapSim virtual reality simulator distinguish between novices and experts? *Surgical Endoscopy*, 21(8):1413–1417, 2007.

Lev S. Vygotsky. *Mind in Society: The Development of Higher Psychological Processes*. Harvard University Press, 1978.

Qinggang Zhang, Zhishang Xiang, Yilin Xiao, Le Wang, Junhui Li, Xinrun Wang, and Jinsong Su. Faithfulrag: Fact-level conflict modeling for context-faithful retrieval-augmented generation, 2025.

Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. Negative preference optimization: From catastrophic collapse to effective unlearning, 2024.

Zinn et al. Assessing flight competency from deviation to an optimal trajectory. *Cognition, Technology & Work*, 2023.