
A Calibrated In-Silico Screen for Corpus Necessity: Constructing the Parametric Ground Truth, and the Mised-Learner Blind Spot

Anonymous authors

Under review as submission to TMLR

Abstract

Before running a human study on a corpus-bounded tutor, a designer wants to know something cheaper first: does the learner actually *rely* on the curated corpus, or is it coasting on what it already knows? We present an *in-silico measurement instrument* that answers this as a behavioral task outcome. The central quantity is *corpus necessity*: ablate a corpus item and measure the change in a task outcome scored against a reference policy—a with-versus-without contrast, not an influence score. Our headline move is to make necessity *trustworthy by constructing its ground truth*: we teach a fact into a model’s weights and watch necessity fall as a *dose-response*. We calibrate the measure in a *simulator-free* fictional-fact question-answering task scored by an answer checker, where teaching invented facts drives necessity smoothly $1.00 \rightarrow 0.93 \rightarrow 0.29 \rightarrow 0.03$ with the LoRA-scale and checkpoint gradients agreeing. A second, *decision-based* domain (a control-regret simulator with a hidden charted hazard) adds a caution that behavioral-necessity work should heed: a fact taught as prose becomes recallable yet does *not* move the scored decision—a *knowing $\neq$ doing* gap—unless the knowledge is *elicited* by reasoning, and it cannot be reliably *installed* by direct fine-tuning, which yields a shortcut policy rather than the conditional fact. On this calibrated measure we build a *corpus diagnosis* that labels each item *relied*, *redundant* (already known), *unusable* (present but the model fails), or *mised*. The sharp result is the last: a learner that faithfully follows a *wrong* retrieved rule registers as maximally reliant—the decision swings hard when the rule is ablated—yet is actively harmed, and standard necessity and faithfulness metrics, which only ask whether context influenced the output, are blind to it. Reading necessity as *decision-changes $\times$ succeeds-with* separates this case out. We are explicit about scope: every result here is simulation-based mechanism evidence, not human-subject external validity. This is the pre-human-study screen; the human cohort study is the pre-registered endpoint it is built to de-risk, and is not a claim of this paper.

1 Introduction

A growing body of work builds *corpus-bounded* tutors and assistants: systems that abstain outside a curated corpus so that, in safety-critical procedural domains, a semantically plausible but instructionally wrong answer cannot be delivered. A designer who has built such a system faces a prior question, before any question about learning gains: *does the mechanism work?* Does the system actually rely on its corpus, and does the corpus actually carry the domain—or is the model answering from parametric memory and the corpus merely decorative? Answering this by human-subject study is slow, expensive, and confounded: a null there conflates a broken retrieval mechanism, an inadequate corpus, an unmotivated cohort, and a dozen other causes.

We argue that the *mechanism* question can be answered cheaply and in silico, and we build the instrument that does it. The core quantity is *corpus necessity*: remove a corpus item and measure how much a behavioral task outcome, scored against a reference policy, degrades. This is a with-versus-without *contrast*, not a measure of whether the context influenced the output. The difficulty is that a raw necessity reading is confounded—a near-zero value could mean the model already knew the fact, or that the without-context condition triggered some unrelated heuristic. Our contribution is to remove that confound *by construction*: we teach a fact into a model’s weights along a graded schedule and show that necessity for that fact falls as a dose-response, giving the measure a known-groups calibration that influence-based methods structurally lack. On the calibrated measure we build a *corpus diagnosis* that labels each item relied / redundant / unusable / *misled*, and its sharpest output is the misled case: a learner faithfully following a wrong retrieved rule looks maximally reliant yet is harmed, invisible to standard metrics.

Our contribution is a measurement one, scoped as a pre-human-study screen. We make no learning-gains claim; every result is simulation-based mechanism evidence, and the human cohort study is pre-registered as the endpoint this screen de-risks, not something we report here. The paper proceeds as follows: Section 2 positions the measure against faithfulness and context-attribution; Section 3 defines the reference-policy instrument and its construct validity; Section 4 is the headline—necessity read as different-and-usable, calibrated by the construction dose-response; Section 5 turns the calibrated measure into the corpus diagnosis and the misled result; and Sections 6–7 scope and close. Appendices carry the categorical leakage verdict, a weight-level unlearning cross-check, estimator recovery, and a presence-vs-retrieval decomposition.

2 Related work

Faithfulness, context-attribution, and knowledge conflict. A large line asks whether a model uses provided context or parametric memory. Faithfulness metrics score whether an answer is grounded in the supplied context [Es et al., 2023]; context attribution ablates context sources and measures the change in output probability to attribute a generation to them [Cohen-Wang et al., 2024, Or, 2026]; knowledge-conflict work studies which side wins when context contradicts memory [Xu et al., 2024, Zhang et al., 2025]; leakage-free benchmarking filters items answerable with no context [Liu et al., 2026]; and intermediate-step scoring looks beyond the final answer [Jain and Vedom, 2026]. All of these measure whether context *influenced* an output, judged on answer text, with the corpus *present*. Our delta is on two axes. First, we measure *necessity*, a with-versus-without contrast— $\text{acc}(\text{with corpus}) - \text{acc}(\text{without corpus})$ —rather than influence: a faithfulness score is a function of the (*question, context, answer*) triple computed with the corpus present, and RAGAS never runs the without-corpus arm, so it is structurally blind to the quantity—a model that knows a fact and one that does not both score high with the corpus present. Second, and this is what makes the contrast trustworthy, we *calibrate* necessity against a constructed weight-level baseline (Section 4) that these methods have no analogue for.

The closest relative, and the structural gap. ContextCite [Cohen-Wang et al., 2024] is the nearest method: because it ablates context and measures the change in the response’s log-probability against the model’s own baseline, it *partially* tracks necessity. But it requires open weights and per-token log-probabilities (so it cannot run on the closed API models our test does), attributes text-influence rather than a task outcome, carries no weight-level known-groups calibration, and yields no relied/redundant/unusable/misled split. The gap common to this whole strand is that none has a *constructed parametric baseline*: a way to teach a fact into the weights and confirm the measure responds. That construction (Section 4) is what lets us tell a fact the model relied on from one it merely already knew—and, in the misled case, a fact it faithfully followed off a cliff.

Knowing vs. doing. A separate line finds that knowledge a model holds need not govern its behavior: facts learned in one form fail to surface in another [Berglund et al., 2023], edits leave messy or mis-scoped ripples [Cohen et al., 2024], stated reasoning need not reflect the true cause of an answer [Turpin et al., 2023], and tool-use exhibits a measured knowing–doing gap [Anonymous, 2026]. We connect this strand to *necessity measurement*: because our instrument scores a decision, the same gap becomes a validity condition on the measure—a taught fact that is recallable can leave the scored decision unmoved, so necessity read off a single-shot decision under-reports it (Section 4). Unlike Anonymous [2026], which reads internal cognition against tool-call execution, our axis is a

Policy	mean J	median	min	max	cleared
naive (hold course)	1765.44	1988.08	1.08	1995.18	11%
VO reference	0.70	0.58	0.33	1.27	100%
SB-MPC reference	0.01	0.01	0.00	0.03	100%

Table 1: Construct validity and grading across nine varied encounters. The objective J separates the three competence levels cleanly and takes a continuous range of values (20 distinct across all cells, $[0.00, 1995.18]$)—a graded transfer metric, not a near-binary check.

counterfactual ablation of a *corpus item* against a simulator objective, and our construction lets us show the gap closes under elicitation but not under direct fine-tuning.

3 The transfer instrument

The necessity measure is a with-versus-without contrast on a *task outcome*; this section defines that outcome and shows it grades and isolates cleanly, which is what licenses the contrast in Section 4.

Task and metric. The worked domain is COLREG collision avoidance: a power-driven vessel must choose course and speed to resolve an encounter. We implement a kinematic simulator with an elliptical ship domain and a Collision Risk Index, and two reference solvers—velocity obstacles [Fiorini and Shiller, 1998] and simulation-based MPC [Johansen et al., 2016]. For a learner policy π on scenario set S we define the transfer outcome as regret against a reference policy π^* ,

$$\mathcal{R}(\pi) = \frac{1}{|S|} \sum_{s \in S} [J(\pi, s) - J(\pi^*, s)], \quad (1)$$

where J is the per-encounter objective (a weighted sum of a safety-margin barrier, COLREG compliance penalty, and route deviation; lower is better). We deliberately say “reference,” not “optimal”: VO and SB-MPC are strong near-optimal solvers but not proven globally optimal for the full non-convex encounter. The instrument needs only a fixed, reproducible reference that construct validity shows separates naive from expert behavior; we report which solver is used.

Construct validity and grading. The instrument must separate good from bad policies before any necessity claim, and—to be a transfer measure rather than a pass/fail check—the metric must *grade*, not collapse to two values. Across nine varied encounters (head-on, starboard/port crossing, overtaking, restricted-visibility geometries), three policies of increasing competence separate cleanly and continuously on J (Table 1): a naive hold-course policy (mean $J \approx 1765$, clearing 11% of domains), a velocity-obstacle reference ($J \approx 0.70$, all clear), and SB-MPC ($J \approx 0.01$). The objective takes 20 distinct values in $[0.00, 1995.18]$ over the policy $\times$ scenario cells—a graded metric, with the safe regime itself spanning a continuous 0.00–1.27 range. This is the novice/expert-separation logic of Van Dongen et al. [2007], applied to a decision/control task.

KC $\rightarrow$ single-metric identifiability. For the diagnosis to attribute a task failure to a *specific* corpus rule, each knowledge component must govern exactly one metric, so ablating a KC degrades that metric and no other. This is a design requirement to be verified per instrument, not a tautology: designing the metrics does not guarantee that ablating one KC leaves the *others* unchanged—if the objective’s terms are entangled, ablation bleeds across metrics. Identifiability is the empirically-checked absence of that bleed. On a discrete procedural domain (a roadside tire change) the verification is clean (Table 2): each ablation degrades only its governed metric, maximum off-diagonal change 0.0000. Because the property holds on both a continuous-control and a discrete-procedural instrument, it is a general measurement-design property, not a COLREG artifact. Estimator-recovery and calibration on synthetic data appear in Appendix C.

4 Necessity, calibrated by construction

This is the headline. We first fix how necessity should be *read* off the instrument, then make the reading trustworthy by constructing its ground truth.

ablated KC ↓ / metric →	safety	core	sequencing	finishing
safety	−1.00	0.00	0.00	0.00
core steps	0.00	−1.00	0.00	0.00
sequencing	0.00	0.00	−0.22	0.00
finishing	0.00	0.00	0.00	−1.00

Table 2: KC→single-metric identifiability (procedural domain). Change in each metric after ablating each knowledge component. The diagonal (bold) is the intended governed metric; every off-diagonal cell is 0.00 (max $|\Delta| = 0.0000$)—ablation does not bleed across metrics.

	succeeds <i>with</i> the item	fails <i>with</i> the item
decision <i>unchanged</i>	RELIED corpus drove the call <i>and</i> it works (regret-with 0; ablated 1782)	MISLED / can’t execute call changed but still fails: fix the model, or the rule is wrong
decision <i>changes</i>	REDUNDANT same call either way, and it works—already known (prune)	IGNORED (unusable) same call either way, and it fails—present, not used

Figure 1: Necessity read as *different*×*usable*: ablate an item and ask whether the *decision* changes (rows) and whether the learner *succeeds with* it (columns). Only the top-left cell is **relied on**—the corpus changed the call, for the better. The top-right cell is the *misled*/can’t-execute case a subtractive “did removing it hurt” test cannot see. A coarser categorical verdict is deferred to Appendix A.

129 **Necessity as *different and better*.** Ablate a corpus item and compare the run against the with-
130 corpus run on two observables (Figure 1): does the *decision* change (**different**), and does the learner
131 *succeed with* the item present (**usable**)? An item is **relied on** only when the corpus changes the
132 *decision for the better*—removing it flips a succeeding call into a failing one. Reading necessity as
133 “the corpus changed the call, and it helped” is stronger than the subtractive “nothing broke when we
134 removed it,” and, crucially, the two-observable reading is what will separate genuine reliance from
135 the *misled* case in Section 5: a corpus item can change the decision hard (high raw necessity) while
136 the learner still *fails* with it present, which the subtractive test cannot see. This reading is computed
137 off the graded regret instrument itself, not a decoupled side-metric.

138 **Why the reading needs calibration.** The necessity test infers a fact about a model’s *weights* from
139 a change in the *prompt*: ablate an item, and if the governed outcome does not move, the model did
140 not need it. The sharpest objection is that context removal is not weight-level knowledge change, so a
141 small necessity could be a no-context heuristic in disguise, or a large necessity could reflect a fact the
142 model happens not to know for reasons we did not control. We close this *by construction*: if teaching
143 a fact into the weights drives necessity for that fact down as a dose-response, then a near-zero reading
144 is evidence the model already knew the item, and the measure is a non-confounded, known-groups
145 quantity. We build models along a gradient from fact-naïve to fact-knowing by teaching a target
146 fact into the weights (LoRA SFT) and sweeping two independent knowledge gradients—the LoRA
147 scale α (one adapter, evaluated at $\alpha \in [0, 1]$) and training checkpoints—so their agreement rules out
148 a gradient-method artifact. We establish the calibration in a simulator-free QA domain, then use a
149 decision-based domain to surface a limit the calibration alone would hide.

150 **The calibration: simulator-free fictional-fact QA.** We invent facts about fictional entities (re-
151 search outposts and their attributes) that no model can have memorized, and score answers with a
152 programmatic checker—no simulator, no reference policy. Because the facts are fictional, a compe-
153 tent model is necessarily corpus-bound at baseline, and because there are many *independent* facts,
154 partial teaching learns a fraction of them, so the aggregate necessity is *graded*. Teaching the facts
155 into a Qwen2.5-7B-Instruct model drives mean necessity smoothly and monotonically down the




Figure 2: The knowing $\neq$ doing gap and its bridge, on the hazard decision ($\mathcal{R}$ -necessity; lower = clears without the corpus). The taught fact is recallable (top-right, recall 0.00 $\rightarrow$ 0.78) yet leaves the single-shot decision unmoved (top row, flat 667). Only *reason-then-decide on the taught model* clears (bottom-right, 0.3); reasoning on the naive model does not (bottom-left), so the turn is the taught knowledge being elicited, not reasoning alone—the action needs *both* the knowledge and the elicitation. Installing the decision directly by fine-tuning does not reproduce this: it yields a blanket/confabulated policy (`decision-teach-arc.md`), not the conditional fact.

156 LoRA- α gradient: 1.00 $\rightarrow$ 0.93 $\rightarrow$ 0.29 $\rightarrow$ 0.03 (Table 3). A training-checkpoint sweep reproduces
157 the same curve (1.00 $\rightarrow$ 0.25 $\rightarrow$ 0.03)—the two gradients are built differently (scaling one converged
158 adapter vs. genuine partial training), so their agreement rules out a gradient-method artifact. This is
159 the known-groups calibration, in a domain we did not build a simulator for—answering the objection
160 that the measure is an artifact of one hand-built environment. (Necessity here is measured closed-
161 book: the without-corpus condition permits parametric answering, so taught knowledge surfaces
162 rather than being suppressed by a strict “answer only from the provided facts” instruction.)

163 **A decision-domain caution: knowing $\neq$ doing.** The calibration teaches and scores in the *same*
164 channel—a fact, queried as a fact. A behavioral instrument scores a *decision*, and there the two
165 can come apart, so we probe the decision domain directly with a corpus-only charted hazard (a
166 danger scored by the objective barrier but not shown in the prompt, knowable only from the cor-
167 pus) taught into a Qwen2.5-3B model *as prose*. The fact becomes *recallable*—free-text recall of
168 the avoiding action rises from 0.00 to 0.78—yet the scored maneuver *does not move*: $\mathcal{R}$ -necessity
169 is flat ($\approx$ 667 at both the naive and taught ends). The fact is in the weights but does not reach the
170 decision: a *knowing $\neq$ doing* gap, a behavioral cousin of the reversal curse [Berglund et al., 2023]
171 and of the knowing–doing gap reported for tool use [Anonymous, 2026]. Two interventions localize
172 it (Figure 2). *Eliciting* the knowledge by reason-then-decide prompting closes the gap—necessity
173 falls to $\approx$ 0.3, while a naive-model reasoning control still grounds, so it is the taught knowledge
174 being surfaced, not reasoning alone. *Installing* the decision directly by fine-tuning on the scored
175 format does not: across positive-only, contrastive, and surface-debiased teach sets the model learns
176 a blanket or shortcut policy—confabulating the hazard at every location, an instance of unfaithful
177 reasoning [Turpin et al., 2023] and of mis-scoped knowledge editing [Cohen et al., 2024]—never the
178 conditional fact (Appendix B reports the parallel weight-level *says $\neq$ does* dissociation from unlearn-
179 ing). The lesson for the measure: on a decision objective, whether a taught fact “counts” depends
180 on whether it is *elicited*, so necessity read off a single-shot decision can under-report knowledge the
181 model in fact holds—a validity caveat we return to in Section 6.

182 5 The corpus diagnosis

183 The calibrated necessity measure is the input to a per-item *corpus diagnosis*: run the
184 different $\times$ usable reading (Figure 1) on every item and label it. The three non-relied cells demand
185 different fixes. An *unchanged* decision that succeeds is **redundant** (the model already knows it;
186 prune it), calibrated against the dose-response floor (Section 4) so a near-zero reading means already-

	$\alpha=0$	0.25	0.5	0.75	$\alpha=1$
Fictional-fact QA / accuracy (Qwen-7B)	1.00	0.93	0.29	0.03	0.03

Table 3: Necessity dose-response by construction (the calibration). Teaching many independent invented facts into the weights drives the instrument’s necessity for them smoothly down the LoRA- α gradient; a training-checkpoint sweep reproduces the same curve, so the monotone fall is not a gradient-method artifact. The answer-accuracy objective uses no simulator. The decision-based hazard domain does *not* yield such a curve—teaching the fact as prose leaves the scored maneuver unmoved (the *knowing* $\neq$ *doing* gap of Section 4); it is reported there, not as a second calibration.

known rather than never-used. An unchanged decision that fails is **ignored/unusable** (present but the model cannot execute it). The remaining cell is the sharp one.

The misled result. The top-right cell of Figure 1—the decision *changes* but still *fails*—is where a learner faithfully follows a *wrong* retrieved rule. This is the failure the whole measure is built to expose. Consider a corpus item that instructs the wrong give-way maneuver. A faithful learner applies it, and when the item is ablated the learner falls back on a safer parametric reflex and clears—so the item’s raw necessity is *maximal*: the decision swings hard, exactly the signature of strong reliance. Yet the outcome *with* the item is a grounding. A subtractive necessity test (“did removing it hurt?”) and an influence-based faithfulness score both report this item as heavily used and well-grounded—they cannot distinguish a learner relying on a correct rule from one faithfully executing a harmful one, because both change the output and both are “supported” by the context. The two-observable reading separates them: the misled item lands in the top-right cell (changes the call, fails with it), never in **relied** (top-left). The instrument’s diagnostic value is precisely that faithful compliance with a wrong rule is worse than ignoring it, and only the succeeds-with observable can see the difference.

The learners that exercise the override. Necessity is always measured against a *learner*, and the misled/override contrast needs a cast that varies in how deeply it uses the corpus: a **blind** learner cannot perceive the danger and collides; a **naive** learner is sighted but untrained and avoids generically; an **implementer** applies a corpus rule verbatim where the situation matches; and a **reasoner** treats the corpus as premises and combines it with base rules for novel cases. On a matched suite where the textbook rule already fits, implementer and reasoner are indistinguishable ($\Delta\text{regret } 0.00$); on a conflict suite built so the safe side *alternates* port/starboard—so no fixed reflex passes—the reasoner clears 6/6 while the lookup implementer clears only the 3 reaches where the local rule is redundant with Rule 14 and *grounds on the 3 it overrides*. The necessity of the local-rule corpus is thus 3/6, separable *only* on the overriding cases: this is the RAG-as-lookup vs. RAG-as-reasoning-substrate distinction made measurable, and it is exactly the axis on which a *wrong* local rule produces the misled failure above (an implementer follows it off the cliff; the two-observable reading catches the result). A live model run confirms the reading is not an artifact of hand-built policies: Gemini-2.5-flash applies the local rule like a reasoner, relying on it on all three override reaches (5/5 samples, necessity 1782 ± 0)—with the corpus it alters to port and clears, ablated it applies Rule 14 and grounds.

The misled result on a real model. The same live model, run through a *misled* arm—a corpus rule that instructs the wrong (port) give-way toward an *observable* obstacle, so following it grounds while the ablated model clears—makes the blind spot empirical rather than hypothetical. Over four misled scenarios $\times$ six samples (temp-0 point + $K=5$ at 0.7; $n=24$ draws per condition), Gemini’s harmful into-the-obstacle maneuver rate rises from 4% ablated to 33% with the wrong rule, while its correct give-way rate falls from 70% to 33%—the corpus roughly $8\times$ ’s the harmful action and halves the correct one. Read per sample as a binary cell the signal is noisy (misled on 1.6/4 cells on average); read as the *marginal maneuver rate* it is a clean, large shift, and the marginal rate is what we report. The mechanism is not a perception failure—ablated, the model almost never turns toward the obstacle (1/24 draws) and correctly cites it—but a *confabulation*: with the wrong rule present it turns toward the obstacle and reports that doing so “passes clear of the moored barge.” So the model that applies *correct* local rules like a reasoner (above) is, on *wrong* ones, a rule-follower whose harmful compliance a standard necessity or faithfulness score would credit as high, well-

Model	relied	unusable	redundant
Claude Opus 4.5	8	0	0
Claude Haiku 4.5	4	0	4
Claude Sonnet 4.5	3	2 [†]	3
Amazon Nova-micro	2 [†]	2 [†]	4
Llama-4-Maverick-17B	0	4	4

Table 4: Cross-model necessity over the eight-hazard corpus-only suite (five models, AWS Bedrock). Each hazard is isolated in its own corpus, so the three counts partition the suite of 8 and per-model reliance is a fraction. Classification uses $necessity = \mathcal{R}(\text{ablated}) - \mathcal{R}(\text{with-corpus})$ and $regret-with: \text{relied} = necessity > 100 \text{ and } regret-with < 10$; **unusable** = $regret-with \geq 10$ (grounds *with* the item present); **redundant** = otherwise (clears both ways). Values are the temp-0 point estimate; the $K=5$ temp-0.7 ensemble has $sd \approx 0$ except ([†]): Sonnet unusable 1.2 ± 0.7 , Nova-micro relied 0.2 ± 0.4 and unusable 2.2 ± 0.7 . **Counts reflect ablated-arm fallback as well as reading:** reflex-apppliers cap at 4/8 (the four override reaches), and Opus’s 8/8 reflects that it holds course rather than falling back on Rule-14 when the rule is ablated.

231 grounded reliance—exactly the case the succeeds-with observable is built to catch. We report this
232 as a single-model effect size and its mechanism, not a rate we generalize.

233 **Offline recovery of known ground truth.** Before any real-model sweep we confirm the classifi-
234 cation recovers truth we control. Against two reference mock learners the instrument is exact: the
235 corpus-bound mock’s decision *changes* on ablation and it then grounds (regret 0.2 with the rule
236 $\rightarrow 1981$ without $\Rightarrow \text{relied}$); the leaking mock’s decision is *unchanged* and clears both ways ($\Rightarrow$
237 *redundant*). The whole offline backbone regenerates in one deterministic, LLM-free command that
238 checks each headline result against its claimed value.

239 **A supporting cross-model reading (demoted).** As one supporting breadth result we run the ne-
240 cessity test as a suite of eight independent, alternating-bow charted hazards, each isolated in its
241 own corpus, so per-model necessity is the fraction of the suite relied upon (Table 4). This gives a
242 graded reliance spectrum across five production models, but the counts must be read with an im-
243 portant caveat: they reflect ablated-arm fallback as well as reading. The suite is 4 override reaches
244 (the hazard sits where the default Rule-14 starboard turn grounds) plus 4 where starboard already
245 clears, so a model that falls back on the starboard reflex when the rule is ablated is *rescued* on the
246 four non-override reaches and caps at 4/8 *by construction*. Claude Opus’s 8/8 is co-determined by
247 this: it *holds course* when ablated (strict-mode faithfulness—“no rules were provided”) rather than
248 falling back on Rule-14, so it grounds on all eight, whereas reflex-apppliers like Haiku (4) cap at
249 four by construction. Opus’s 8/8 therefore means it does not fall back, not that it out-reads Haiku;
250 the spectrum grades reading and ablated-arm conservatism together, which is why we demote it to
251 support rather than headline.

252 **Per-rule attribution.** To show the diagnosis attributes reliance to a *specific* rule rather than to
253 corpus presence in general, we add a second, independent rule (Rule 15 crossing give-way) exercised
254 on its own crossing scenarios. Ablating each rule produces a large regret signal on its own encounters
255 and localizes there: on `gemini-flash-latest`, ablating Rule 14 gives $\delta_{\mathcal{R}}=1981$ (head-on) and
256 ablating Rule 15 gives 1285 (crossing), each on its own disjoint scenario subset, so the instrument
257 reads reliance per rule, not merely per corpus.

258 **Corpus sufficiency and false sufficiency.** Rolling the per-item classifications to the corpus level
259 yields a sufficiency judgement for a query set: *contributing* (every item relied upon), *partial*, *un-*
260 *usable*, or—the diagnostic ordinary RAG metrics cannot produce—*false sufficiency*: task accuracy
261 is high yet necessity is ≈ 0 everywhere, so the corpus is not carrying the load and success rides on
262 priors, fragile to distribution shift. The claim is explicitly scoped to the probed query set (sufficiency
263 is always “for these queries”); the false-sufficiency signal is precisely the measurable warning that
264 a bounded-query sufficiency claim will not survive a shift. A finer presence-vs-retrieval decomposi-
265 tion is developed in Appendix D.

6 Limitations and scope

Mechanism, not external validity. Every result here is simulation-based mechanism evidence. We make no learning-gains claim; the pre-registered human cohort study is the external-validity test this in-silico screen is built to de-risk, and it is the endpoint, not a claim of this paper. **Single models and seeds.** The calibration dose-response and the knowing $\neq$ doing decision-domain results are single-model, single-seed runs; a queued multi-seed GPU rerun (≥ 3 seeds, and a second model family) is documented in `experiments/provenance/gpu-pending.md` and `decision-teach-arc.md`, and until it lands we treat the curves as single-run and keep the hedging in Section 4. The offline mock recovery already confirms the *instrument* recovers ground truth on these domains; what is pending is the multi-seed *taught-model* band. **Small evidence base.** The cross-model reading (Table 4) covers five models across three provider families on an eight-hazard suite, and reflects ablated-arm fallback as much as reading (Section 5); it is a worked example, not a leaderboard. **Decomposability may not generalize.** KC $\rightarrow$ single-metric identifiability and clean per-rule ablation are properties we *design into* a governed corpus and *verify* per instrument (Table 2); an arbitrary corpus whose rules are entangled may only support coarser, group-level attribution. **Which channel counts is a construct choice.** Necessity is read through a *channel*—a recalled fact or an executed decision—and the knowing $\neq$ doing gap (Section 4) shows the two can diverge: a fact the model demonstrably holds (recall rises 0.00 $\rightarrow$ 0.78) can leave a single-shot decision unmoved. The valid channel is therefore a property of the downstream question, not of the instrument. For a corpus-bounded *tutor*, whose target is what the learner comes to *know*, the recall/knowledge channel (our fictional-fact calibration) is the faithful proxy, and reading necessity off an un-elicited decision would wrongly score an acquired fact as *unnecessary*; for a corpus-bounded *agent* that must act, only the decision counts and a knowing-but-not-doing fact is a genuine failure the recall channel would miss. An instrument should declare its target construct and, where application matters (procedural knowledge, Koedinger et al., 2012), elicit before scoring or measure both channels and treat their gap as diagnostic rather than noise. **Proxy validity.** Simulated learners can be unfaithful; recent work documents systematic LLM-vs-human fidelity gaps [Yuan et al., 2026, Wu et al., 2025, Srivatsa et al., 2025], which is another reason the human study, not the screen, is the endpoint.

7 Conclusion

We described an in-silico instrument that measures whether a learner *needs* a corpus before any human-subject effort, and made the measure trustworthy by *constructing* its ground truth: teaching many invented facts into a model’s weights drives the instrument’s necessity for them down as a graded dose-response (1.00 $\rightarrow$ 0.03, in a simulator-free QA domain, with LoRA-scale and checkpoint gradients agreeing). A decision-based domain adds a validity caution the field should carry: a fact taught as prose is recallable yet does not move a single-shot decision (a *knowing $\neq$ doing* gap) unless reasoning *elicits* it, so the necessity channel must match the downstream construct. On that calibrated measure we built a corpus diagnosis whose sharpest output is the *misled* case—a learner faithfully following a wrong retrieved rule looks maximally reliant yet is harmed, invisible to influence-based faithfulness and to subtractive necessity, and caught only by reading necessity as decision-change *and* succeeds-with. The claim is testable and narrow, the domains are worked examples, and the measurement method—calibrated, and honest about being a pre-human-study screen—is the point.

A The categorical leakage verdict (secondary)

The main text classifies each item on two observables—does the decision change on ablation, and does the learner succeed with the item present (Figure 1). For continuity with prior leakage work we also compute a coarser *categorical* verdict, CORPUS-BOUND/LEAKING/INCONCLUSIVE, by a majority vote over three signals: the ablation-delta (does regret rise when the rule is removed), a *counterfactual* test (replace “alter to starboard” with “alter to port”—does the learner follow the altered rule?), and a *closed-book* contamination baseline (no corpus supplied). The majority vote keeps a single dissenting sub-test from vetoing a clear ablation-and-contamination pattern. We de-emphasize it because it is noisier than the two continuous observables and *undercounts* a model

318 whose decision plainly depends on the fact but which answers closed-book from priors—it put Haiku
319 at 0/8 where the decision-change reading gives 4/8.

320 **Strict-mode reading on standard COLREG.** The verdict is retained mainly for one signal it
321 reads cleanly. On *standard* COLREG, Claude Opus verdicts CORPUS-BOUND, but the audit log
322 shows this is strict-mode faithfulness, not a knowledge gap: when the steering rule is ablated Opus
323 abstains/holds course (“no rules were provided...”) rather than falling back on its obvious para-
324 metric Rule-14, while Haiku falls back to Rule-14 starboard (LEAKING) and Sonnet splits across
325 samples (INCONCLUSIVE). This is the same ablated-arm behavior that co-determines Opus’s 8/8 in
326 Table 4.

327 B Validation by unlearning: a *says* $\neq$ *does* dissociation

328 The complementary weight-level direction removes a rule the model *does* know and asks whether ne-
329 cessity rises. This arm is secondary—it has dynamic range only on a rule with a real corpus-vs-prior
330 gap, which the standard rules lack—but it yields an independently interesting result. We remove the
331 alter-to-starboard knowledge from an open-weight model with a real unlearning method—SimNPO
332 [Fan et al., 2024] as primary (reference-free, length-normalized), with NPO [Zhang et al., 2024],
333 RMU [Li et al., 2024], and gradient ascent [Jang et al., 2022] as baselines—and score the base vs.
334 unlearned model on the reference-policy instrument. A removal audit [Lynch et al., 2024] reports
335 whether the knowledge is *gone* vs. merely *suppressed*; for a stable novice that resists benign relearn-
336 ing we layer in a robust utility-preserving recipe [Singh et al., 2025]. A completed GPU run (gentle,
337 guardrailed SimNPO on Qwen2.5-3B; config in Table 5) delivers a lesson sharper than the predicted
338 2×2 : **standard free-text unlearning metrics overstate removal because they measure what**
339 **the model *says*; the reference-policy instrument measures what the model *does*—its steering**
340 **decision—and shows the decision is untouched.**

341 **Primary result: a *says* $\neq$ *does* dissociation.** Every metric that reads the model’s *words* registers
342 forgetting: on the GPU run the forget-probe “starboard” rate falls $0.43 \rightarrow 0.27$, the forget-set NLL
343 rises $7.4 \rightarrow 32.4$ (retain-set NLL, teacher-forced, even *improves* $4.3 \rightarrow 1.07$), and—most tellingly—
344 the Rule-14 *citation* disappears, the model reattributing its maneuver to Rules 15/16/17. (A CPU run
345 reproduces the likelihood collapse method-agnostically: forget NLL $4.6 \rightarrow 92$, direction-cue $5/6 \rightarrow$
346 $0/6$.) Yet the *decision* the instrument scores does not budge: the unlearned model’s completions *still*
347 *turn +30° to starboard* (model damage flat at 0.10, retain-coherence 0.91). A words-level metric
348 reports a fact removed while the policy that governs behavior is entirely intact.

349 **Suppressed, not removed; and the aggressive inversion.** Twenty benign fine-tuning steps pull
350 the forget-set NLL $32.4 \rightarrow 9.2$, back near its base value—the textbook suppressed-not-removed
351 signature. By contrast an earlier aggressive recipe ($1r \ 1 \times 10^{-4}$, no guardrail) drove model damage
352 $0.10 \rightarrow 0.33$ and turned the ship to *port*—the wrong way—on 6/8 prompts: because the head-
353 on turn is essentially binary, the default objective simply relocated the mass onto “port,” *inverting*
354 the safety rule, a caution that naive weight-level unlearning of a safety rule can yield confident non-
355 compliance. **Why the 2×2 is flat:** Rule 14 already LEAKS at baseline—every frontier model knows
356 head-on $\rightarrow$ starboard parametrically—so ablating it changes nothing (ablation-delta 0), leaving no
357 dynamic range. The LEAKING verdicts are therefore *correct*; this is exactly why the primary weight-
358 level validation is the construction dose-response (Section 4), where a corpus-only fact *does* have
359 range.

360 C Estimator recovery and calibration

361 Feeding the instrument’s outcomes into a generic learner-agent estimator, we recover known ground
362 truth on synthetic data (Table 6). This turns “we have a metric” into “the measurement is valid.”

363 D Presence vs. retrieval: what in the corpus changes the answer

364 The necessity test asks whether the learner relies on the corpus *at all*; a deployed RAG tutor raises
365 a finer question—of the value curation adds, how much comes from the fact being *present* versus

Metric	1.5B (CPU, SimNPO)		3B (GPU, gentle SimNPO)	
	base	unlearned	base	unlearned
Forget-target NLL ($\uparrow$)	4.6	92.0	7.4	32.4
Retain-set NLL, teacher-forced ($\downarrow$)	3.2	0.18	4.3	1.07
Forget-probe “starboard” rate ($\downarrow$)	5/6	0/6	0.43	0.27
Retain-coherence, free-gen ($\uparrow$)	—	—	1.00	0.91
Model damage (wrong+degen., $\downarrow$)	—	—	0.10	0.10
<i>Steering decision (instrument)</i>	—	—	<i>stbd</i>	<i>stbd</i>

Table 5: Gentle, guardrailed SimNPO unlearning of the alter-to-starboard rule, on a 1.5B model (CPU) and Qwen2.5-3B (GPU, `bfloat16`; `lr` 5×10^{-5} , `retain_weight` 3.0, Rule-14 kept in the retain set). Every *words-level* metric registers forgetting while retain utility is preserved and there is no inversion (model damage flat at 0.10). Yet the *decision* the instrument scores is untouched: the unlearned model still turns $+30^\circ$ to starboard, and the 2×2 stays verdict LEAKING, ablation-delta 0.000—a says $\neq$ does dissociation. Benign relearning (20 steps) pulls forget NLL 32.4 $\rightarrow$ 9.2, confirming the fact was *suppressed*, not removed.

Estimator	Recovery of known ground truth	Calibration (ECE)
Elo	static ability, mean abs. error 0.046	0.023
BKT	latent state $P(\hat{L}) = 0.997$ (learned) vs. 0.175 (not)	0.004

Table 6: Estimator-recovery and calibration on synthetic data with a known ground truth. The measurement, not just the metric, is validated.

the retriever actually *surfacing* it. Decomposing over in-corpus $\times$ retrieved gives three scorable conditions: NONE (closed-book, priors only), RETRIEVED (the deployed dense retriever’s top- k), and ORACLE (the answer-bearing chunk, i.e. perfect retrieval). Accuracy across them attributes the gain: $\text{acc}(\text{ORACLE}) - \text{acc}(\text{NONE})$ is the *content ceiling*, $\text{acc}(\text{RETRIEVED}) - \text{acc}(\text{NONE})$ is what the deployed pipeline *delivers*, and their difference is the *retrieval gap*. On seven equipment-SOP fact-recall queries through a small local generator (Qwen2.5-1.5B), closed-book accuracy is 0/7, ORACLE is 7/7, and the deployed MiniLM pipeline lands between at 3/7—so of a 100% content ceiling the pipeline *delivers* 43% and *forfeits* a 57% retrieval gap. A curation failure (fact absent), a retrieval failure (present but unranked), and a priors success are distinct outcomes the binary leakage verdict cannot separate. (Numbers illustrate the method—one small model, seven queries—not a benchmark.)

References

- Anonymous. Model-adaptive tool necessity reveals the knowing-doing gap in LLM tool use, 2026.
- Lukas Berglund, Meg Tong, Max Kaufmann, Mikita Balesni, Asa Cooper Stickland, Tomasz Korbak, and Owain Evans. The reversal curse: LLMs trained on “A is B” fail to learn “B is A”, 2023.
- Roi Cohen, Eden Biran, Ori Yoran, Amir Globerson, and Mor Geva. Evaluating the ripple effects of knowledge editing in language models. *Transactions of the Association for Computational Linguistics (TACL)*, 12: 283–298, 2024.
- Benjamin Cohen-Wang, Andrew Ilyas, Jonathan Wu, and Aleksander Madry. Contextcite: Attributing model generation to context. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- Shahul Es, Jithin James, Luis Espinosa-Anke, and Steven Schockaert. RAGAS: Automated evaluation of retrieval augmented generation, 2023.
- Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. Simplicity prevails: Rethinking negative preference optimization for llm unlearning, 2024.
- Paolo Fiorini and Zvi Shiller. Motion planning in dynamic environments using velocity obstacles. *International Journal of Robotics Research*, 17(7):760–772, 1998.
- Siddharth Jain and Venkat Narayan Vedam. Cue-r: Beyond the final answer in retrieval-augmented generation, 2026.

394 Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon
395 Seo. Knowledge unlearning for mitigating privacy risks in language models, 2022.

396 Tor A. Johansen, Tristan Perez, and Andrea Cristofaro. Ship collision avoidance and COLREGS compliance
397 using simulation-based control behavior selection with predictive hazard assessment. *IEEE Transactions on*
398 *Intelligent Transportation Systems*, 17(12):3407–3422, 2016.

399 Kenneth R. Koedinger, Albert T. Corbett, and Charles Perfetti. The Knowledge-Learning-Instruction frame-
400 work: Bridging the science-practice chasm to enhance robust student learning. *Cognitive Science*, 36(5):
401 757–798, 2012.

402 Nathaniel Li et al. The wmdp benchmark: Measuring and reducing malicious use with unlearning, 2024.

403 Jiayi Liu, Jiaying Zhang, Bowen Jin, and Jennifer Neville. Generating leakage-free benchmarks for robust rag
404 evaluation, 2026.

405 Aengus Lynch, Phillip Guo, Aidan Ewart, Stephen Casper, and Dylan Hadfield-Menell. Eight methods to
406 evaluate robust unlearning in llms, 2024.

407 Barak Or. Quantifying prior dominance in rag systems, 2026.

408 Naman Deep Singh, Maximilian Müller, Francesco Croce, and Matthias Hein. Unlearning that lasts: Utility-
409 preserving, robust, and almost irreversible forgetting in llms, 2025.

410 KV Aditya Srivatsa, Kaushal Kumar Maurya, and Ekaterina Kochmar. Can llms reliably simulate real students’
411 abilities in mathematics and reading comprehension?, 2025.

412 Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language models don’t always say what
413 they think: Unfaithful explanations in chain-of-thought prompting, 2023.

414 K. W. Van Dongen et al. Construct validity of the LapSim: Can the LapSim virtual reality simulator distinguish
415 between novices and experts? *Surgical Endoscopy*, 21(8):1413–1417, 2007.

416 Tao Wu, Jingyuan Chen, Wang Lin, Mengze Li, Yumeng Zhu, Ang Li, Kun Kuang, and Fei Wu. Embracing
417 imperfection: Simulating students with diverse cognitive levels using llm-based agents, 2025.

418 Rongwu Xu, Zehan Qi, Zhijiang Guo, Cunxiang Wang, Hongru Wang, Yue Zhang, and Wei Xu. Knowledge
419 conflicts for LLMs: A survey. In *Proceedings of EMNLP*, 2024.

420 Zhihao Yuan, Yunze Xiao, Ming Li, Weihao Xuan, Richard Tong, Mona Diab, and Tom Mitchell. Towards
421 valid student simulation with large language models, 2026.

422 Qinggang Zhang, Zhishang Xiang, Yilin Xiao, Le Wang, Junhui Li, Xinrun Wang, and Jinsong Su. Faithfulrag:
423 Fact-level conflict modeling for context-faithful retrieval-augmented generation, 2025.

424 Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. Negative preference optimization: From catastrophic collapse
425 to effective unlearning, 2024.