
An In-Silico Instrument for Pre-Validating Corpus-Bounded Instruction: Reference-Policy Transfer Measurement with Bidirectional Corpus-Gap and Leakage Diagnosis

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 When a model answers correctly with a corpus in context, did it *need* the corpus, or
2 did it already know the answer? We present an *in-silico measurement instrument*
3 that answers this—and the dual question of whether a corpus is *sufficient*—as a
4 behavioral task outcome, before any human-subject study. The central quantity is
5 *corpus necessity*: ablate a corpus item and measure the change in a task outcome
6 scored against a reference. Our headline contribution is that we make necessity
7 *non-confounded* by calibrating it against a *known parametric baseline*: we *con-*
8 *struct* the ground truth by teaching a fact into a model’s weights and showing
9 necessity falls as a *dose-response*. We demonstrate this in **two domains with in-**
10 **dependent objectives**, one of which uses *no simulator at all*: (i) a control-regret
11 simulator (maritime collision avoidance), where teaching a hidden charted haz-
12 ard into the weights collapses necessity from a full-barrier swing to ≈ 0 , with
13 the LoRA-scale and training-checkpoint gradients agreeing; and (ii) a simulator-
14 free *fictional-fact question answering* task scored by an answer checker, where
15 teaching invented facts into a 7B model drives necessity *smoothly and monoton-*
16 *ically from 1.00 to 0.03*. This calibrated necessity measure is the basis of two
17 products: a *corpus diagnosis* that ranks each item by necessity, localizes which
18 item is missing from task failures, and—crucially—splits an unrelieved-upon item
19 into *redundant* (the model already knows it) versus *unusable* (the model fails even
20 with it present); and a *corpus-sufficiency* verdict that surfaces *false sufficiency*—a
21 corpus that only appears sufficient because the model is coasting on priors and is
22 therefore fragile to distribution shift. Unlike faithfulness (RAGAS) and context-
23 attribution (ContextCite), which measure whether context *supported* or *influenced*
24 an output, we measure whether the model *needed* it, against a weight-level base-
25 line they lack. The method is *closed-model compatible* (API access only) and
26 operates *per item*. As breadth we report: cross-model discrimination across cur-
27 rent LLMs; a second control domain (roadside tire change); KC→single-metric
28 identifiability and estimator-recovery calibration; and a machine-unlearning arm
29 that yields a *says $\neq$ does* dissociation (gentle unlearning changes what a model
30 *says* but not what the instrument sees it *do*) as supporting weight-level evidence.
31 All results are **simulation-based mechanism evidence, not human-subject ex-**
32 **ternal validity**; we scope the contribution accordingly and pre-register the human
33 study as future work.

Plain-language summary. When an AI answers correctly with a rulebook in front of it, you cannot easily tell whether it *needed* the rulebook or already knew the answer—and you cannot tell whether the rulebook has holes. Normally you would find out with an expensive human study. We build a cheap “test bench” that answers both questions first. We remove a single item from the corpus and watch what breaks: if performance drops, the model genuinely relied on it; if nothing changes, it did not. To prove that “nothing changes” really means the knowledge was already in the model—and not some prompt artifact—we *construct* the answer: we teach a fact into the model’s weights and show reliance falls step by step (a “dose-response”). We do this in two settings, one of which uses no simulator at all: a ship-steering task, and a set of *made-up facts* about fictional places no model could know—taught into a real model, reliance on the corpus drops smoothly from 100% to near zero. The payoff is a corpus audit: which items are truly needed, which are *redundant* (already known—delete them), which are *unusable* (present but the model can’t act on them), and whether the corpus only *looks* sufficient because the model is coasting on what it already knew. Everything here is controlled simulation that checks the machinery—not yet a claim that human learners learn more, which is the study we set up next.

1 Introduction

Generic retrieval-augmented (RAG) assistants optimize for semantic relevance: give a plausible answer to whatever is asked. That objective is wrong for training in safety-critical procedural domains, where a semantically accurate answer can still be instructionally wrong—delivered at the wrong complexity, skipping a prerequisite, or worse, confidently fabricated. A growing body of work therefore builds *corpus-bounded* tutors that abstain outside a curated corpus. But a designer who has built such a system faces a prior question: *does the mechanism work?* Does the tutor actually rely on its corpus, and does the corpus actually cover the domain? Answering this by human-subject study is slow and expensive, and a null result there conflates many causes.

We argue that the *mechanism* of a corpus-bounded method can be falsified cheaply and in silico, and we build the instrument to do it (Figure 1). Our contribution is a *methods/measurement* one, not a new tutor and not a new collision-avoidance technique. Concretely:

The central storyline (Sections 4–6):

- **Necessity, calibrated by construction.** We measure *corpus necessity*—the change in a task outcome when a corpus item is ablated—and make it non-confounded by *constructing* the parametric baseline: teach a fact into the weights and necessity falls as a *dose-response*. We show this in **two domains with independent objectives**, one *simulator-free*: a control-regret simulator (teaching a hidden hazard collapses necessity to ≈ 0 ; LoRA-scale and checkpoint gradients agree) and a simulator-free fictional-fact QA task scored by an answer checker (teaching invented facts drives necessity smoothly $1.00 \rightarrow 0.03$ on a 7B model). This is a known-groups validation of the measure.
- **The corpus diagnosis** ranks each item by necessity, localizes a missing item from task failures, and splits an unrelayed-upon item into *redundant* (already known) versus *unusable* (present but the model fails with it)—distinct fixes (prune vs. fix the model).
- **Corpus sufficiency**, the product face of the audit, surfaces *false sufficiency*: a corpus that only looks sufficient because the model coasts on priors (necessity ≈ 0 everywhere), a fragility ordinary RAG metrics report as all-green.

Additional breadth (supporting the above, not the headline): a *transfer instrument* that scores a learner by its *regret against a reference-policy solver* with KC→single-metric identifiability (Section 3); a second control domain and estimator-recovery calibration; cross-model discrimination on current LLMs (Section 4); and a machine-unlearning arm that yields a *says $\neq$ does* dissociation as secondary weight-level evidence (Section 6).

Our contribution is a *methods/measurement* one, not a new tutor. Every *component* we build on is prior art; the *calibrated necessity measure* and its *corpus-value/sufficiency audit* are the open ground (Section 2). We are explicit throughout that our evidence is simulation-based: it tests whether the machinery behaves as designed, not whether humans learn more.

Organization: four case studies. The empirical work is a register of experiments grouped into four case studies (Table 1), which we reference throughout as CS $X.Y$. CS1 builds and stress-tests

Case study	Where	Key experiments (CS $X.Y$)
CS1 necessity instrument (COLREG core)	§4	1.1 reference-learner recovery; 1.2/1.3 cross-model leakage & hazard discrimination; 1.4 geometric hazard suite (necessity as a fraction); 1.5 redundant-vs-unusable; 1.6 corpus-value audit/localization; 1.7 hazard dose-response (§6.1); 1.8 sufficiency & false-sufficiency
CS2 blind→expert ladder (quality→reasoning)	§5	2.1 decision-quality band (the middle band); 2.2 reason-vs-implement (generalization axis)
CS3 enrichments (reach & generality)	§4, 6.1	3.1 real-hazard screen; 3.2 fact-QA necessity (no simulator); 3.3 discrete procedural domain (§3); 3.4 probe-suite breadth
CS4 validations (does the instrument hold up?)	§3, 6.2	4.1 construct validity; 4.2 reweighting sensitivity ($\tau=1.00$); 4.3 unlearning null (says $\neq$ does); 4.4 offline reproduce runner

Table 1: The experiment register, grouped into four case studies and referenced as CS $X.Y$ throughout. The sections cut across the case studies (the instrument’s forward validation, CS4/CS3.3, is Section 3; its backward necessity use, CS1, is Section 4; the weight-level calibration, CS1.7/CS3.2/CS4.3, is Section 6); this map is the reading guide.




Figure 1: The instrument, used bidirectionally. A governed corpus and a learner both feed one reference-policy simulator that scores the learner’s *regret* J against an automatic solver. The same metric is then read three ways—to verify KC→single-metric identifiability (the *instrument*), to localize a missing rule from task failures, and to detect parametric leakage by rule ablation (the *diagnosis*)—needing only API access to the learner. The diagnosis is the instrument run backwards, not a separate tool.

74 the necessity instrument on the COLREG core (the corpus diagnosis and sufficiency products, Sec-
75 tion 4). **CS2** climbs a *learner ladder*—blind, naive, implementer, reasoner—to show the same
76 instrument reads not just *existence* (did you avoid at all) but *quality* (did you avoid well) and *rea-*
77 *soning depth* (do you generalize a local rule), Section 5. **CS3** enriches for reach and generality (a
78 simulator-free second domain, a discrete procedural domain, real charted hazards). **CS4** validates
79 the instrument itself (construct validity, reweighting sensitivity, the unlearning null, an offline re-
80 produce runner). The headline necessity claim is validated by construction in two domains with
81 independent objectives: CS1.7 (control-regret, the large-effect known-groups endpoints) and CS3.2
82 (simulator-free fact-QA, the graded monotone curve).

83 2 Related work and positioning

84 Each strand below is established prior art; we reuse it as infrastructure and mark where our delta
85 departs from it.

86 **Learner modeling and instructional theory.** Knowledge tracing [Corbett and Anderson, 1994],
87 the Elo rating system for adaptive systems [Pelánek, 2016], the Knowledge-Learning-Instruction
88 framework [Koedinger et al., 2012], open learner models [Bull and Kay, 2007], and the Zone of

89 Proximal Development [Vygotsky, 1978] are all established. We reuse them as infrastructure, not
90 as contributions.

91 **Corpus-bounded tutoring, leakage, and faithfulness.** RAG tutors that abstain outside a corpus
92 are standard engineering. A large line asks whether a model uses provided context or parametric
93 memory: faithfulness metrics score whether an answer is grounded in context [Es et al., 2023];
94 context attribution ablates context sources and measures the change in output probability to attribute
95 a generation to them [Cohen-Wang et al., 2024, Or, 2026]; knowledge-conflict work studies which
96 side wins when context contradicts memory [Xu et al., 2024, Zhang et al., 2025]; leakage-free
97 benchmarking filters items answerable with no context [Liu et al., 2026a]; and intermediate-step
98 scoring looks beyond the final answer [Jain and Vedam, 2026]. All of these measure whether context
99 *influenced* the output, judged on *answer text*, per answer or system-wide. We differ on three axes:
100 (a) we score a *behavioral task outcome* against a reference-optimal policy, not answer text; (b) we
101 attribute *per corpus rule* and localize which rule is missing or wrong, not per token or system-wide;
102 and (c) we measure not merely *influence* but *necessity*—calibrated by manipulating the parametric
103 baseline directly (weight-level construction and unlearning, Section 6), so a fact the model already
104 knew is not mistaken for one it relied on. No context-attribution method has that weight-level ground
105 truth. The gap is structural, not incidental: a faithfulness or context-relevance score is a function
106 of the (*question, retrieved context, answer*) triple, computed with the corpus *present*. Necessity is
107 a *contrast*— $\text{acc}(\text{with corpus}) - \text{acc}(\text{without corpus})$ —and RAGAS never runs the without-corpus
108 condition, so it is *structurally blind* to the quantity, regardless of how the answers are phrased. A
109 model that already knows a fact and one that does not *both* answer correctly with the corpus present
110 and both score *high* (the correct answer is entailed by the context whether or not the model used
111 it); a metric that only ever sees the with-corpus arm therefore cannot separate a load-bearing corpus
112 from a redundant one, and reports the redundant case as sufficient—the false-sufficiency failure
113 our measure is built to catch. (Our released harness computes both the RAGAS scores and our
114 necessity contrast side by side; the point is definitional—the without-corpus arm RAGAS omits is
115 exactly what necessity is read from.) **ContextCite** [Cohen-Wang et al., 2024] is the closest relative:
116 because it ablates context and measures the change in the response’s log-probability against the
117 model’s own baseline, it *partially* tracks necessity—but it requires open weights and per-token log-
118 probabilities (so it cannot run on the closed API models our necessity test does), attributes text-
119 influence rather than a task outcome, carries no weight-level known-groups calibration, and yields
120 no *redundant/unusable* split or sufficiency verdict. That join is the *Corpus Diagnosis*.

121 **Objective competency instruments.** Deviation-from-optimal scoring appears in flight [Zinn et al.,
122 2023] and construct-validity-by-novice/expert-separation in surgery [Van Dongen et al., 2007];
123 control-theoretic notation has been applied to knowledge dynamics [Anonymous, 2024b]; regret
124 is used in RL transfer [Tuynman and Ortner, 2022]; maritime training analytics regress simulator
125 measures onto instructor ratings [Lall and Liu, 2025]. None uses a *reference solver’s regret* as the
126 *learner* transfer outcome with KC→single-metric identifiability. That is the *Transfer Instrument*.
127 We borrow mature maritime-autonomy tooling—velocity obstacles [Fiorini and Shiller, 1998] and
128 simulation-based MPC [Johansen et al., 2016]—purely as reference solvers, never as a new collision-
129 avoidance method [Anonymous, 2024a, International Maritime Organization, 1972].

130 **Proxy learners.** Simulated students have long authored and evaluated tutors; LLM student agents
131 now pilot assessment items [Lu and Wang, 2024] and simulate learners for tutoring-system develop-
132 ment [Gao et al., 2025], and controlled variants suppress knowledge by prompting [Apartsin et al.,
133 2026], interpolate parametric competence [Liu et al., 2026b], or unlearn a model into a novice [Song
134 et al., 2026]. Pre-deployment simulated-learner screens have very recently appeared [Fan et al., 2026,
135 Lee et al., 2026]. We therefore *demote* the proxy-learner idea to an application: our narrow residual
136 claim is running *two complementary proxy classes* (parametric competence *and* unlearned LLM)
137 scored on the *same regret-to-reference instrument* the human trial would use—which none of these
138 do.

Policy	mean J	median	min	max	cleared
naive (hold course)	1765.44	1988.08	1.08	1995.18	11%
VO reference	0.70	0.58	0.33	1.27	100%
SB-MPC reference	0.01	0.01	0.00	0.03	100%

Table 2: Construct validity and grading across nine varied encounters. The objective J separates the three competence levels cleanly and takes a continuous range of values (20 distinct across all cells, $[0.00, 1995.18]$)—it is a graded transfer metric, not a near-binary check. `npm run colreg:construct`.

3 The Transfer Instrument

This section defines and verifies the instrument’s *forward* use—measuring transfer and skill. The *backward* use that measures corpus necessity, the paper’s central contribution, follows in Section 4; the construct-validity, identifiability, and robustness checks below are the support that licenses it.

Task and metric. The worked domain is COLREG collision avoidance: a power-driven vessel must choose course and speed to resolve an encounter. We implement a kinematic simulator with an elliptical ship domain and a Collision Risk Index, and two reference solvers—velocity obstacles [Fiorini and Shiller, 1998] and simulation-based MPC [Johansen et al., 2016]. For a learner policy π on scenario set S we define the transfer outcome as regret against a reference policy π^* ,

$$\mathcal{R}(\pi) = \frac{1}{|S|} \sum_{s \in S} [J(\pi, s) - J(\pi^*, s)], \quad (1)$$

where J is the per-encounter objective (a weighted sum of a safety-margin barrier, COLREG compliance penalty, and route deviation; lower is better) and π^* is the reference maneuver. Unlike item correctness, $\mathcal{R}$ is continuous, objective, and instructor-free.

On “reference,” not “optimal.” We deliberately avoid claiming a global optimum. VO and SB-MPC are strong, widely-used near-optimal solvers, but neither is proven globally optimal for the full nonconvex encounter; calling their output “optimal” would overclaim. The instrument does not need a true optimum—only a reference that construct validity shows separates naive from expert behavior (below). Regret is thus measured against a fixed, reproducible reference policy, and we report which solver is used.

Construct validity and metric grading. The instrument must separate good from bad policies before any learning claim, and—if it is to be a transfer measure rather than a pass/fail check—the metric must *grade*, not collapse to two values. Across a varied set of nine encounters (head-on, starboard/port crossing, overtaking, and restricted-visibility geometries), three policies of increasing competence separate cleanly and continuously on J (Table 2): a naive hold-course policy (mean $J \approx 1765$, clearing only 11% of domains), a velocity-obstacle reference ($J \approx 0.70$, all clear), and SB-MPC ($J \approx 0.01$). The objective takes 20 distinct values in $[0.00, 1995.18]$ over the policy $\times$ scenario cells—a graded metric, with the safe regime (VO/SB-MPC) itself spanning a continuous 0.00–1.27 range. On the discrete procedural domain the same logic holds: an expert policy scores $J = 0$ against a reckless $J = 200$ with the safety violation caught. This is the novice/expert-separation logic of Van Dongen et al. [2007], applied to a decision/control task rather than manual skill.

KC $\rightarrow$ single-metric identifiability. We design each knowledge component to govern exactly one metric, so ablating a KC degrades that metric and no other. On the procedural domain this is *exact*: each ablated competence degrades only its governed metric, and a monotone competence $\rightarrow$ performance gradient ($J : 204 \rightarrow 0$) follows as competence is acquired in curriculum order; on the COLREG instrument the same gradient spans nearly five orders of magnitude (Figure 2). Because the property holds on both a continuous-control and a discrete-procedural instrument, it is a general measurement-design property, not a COLREG artifact.

Is identifiability tautological? A fair objection is that the mapping is a design choice, so “ablate the KC, that metric moves” is true by construction. Two things make it a testable property rather than




Figure 2: Competence→performance gradient on the nine-encounter instrument. Mean regret J (log scale) as the six knowledge components are acquired in curriculum order (left to right); each point is a competence stage, from the empty learner ($\emptyset$) to full competence. J spans nearly five orders of magnitude and collapses as the two domain-clearing competencies—acting *early* and at a *safe speed*—come online, the graded behavior Table 2 reports numerically. `npm run colreg:construct`.

ablated KC ↓ / metric →	safety	core	sequencing	finishing
safety	−1.00	0.00	0.00	0.00
core steps	0.00	−1.00	0.00	0.00
sequencing	0.00	0.00	−0.22	0.00
finishing	0.00	0.00	0.00	−1.00

Table 3: KC→single-metric identifiability (procedural domain). Change in each metric after ablating each knowledge component. The diagonal (bold) is the intended governed metric; every off-diagonal cell is 0.00 (max $|\Delta| = 0.0000$)—ablation does not bleed across metrics. `npm run proc:identifiability`.

177 a tautology. First, the *cross-effect* claim can fail: designing the metrics is not enough to guarantee
178 that ablating one KC leaves the *others* unchanged—if the objective’s terms are entangled (e.g. a
179 safety barrier that also moves the deviation term), ablation bleeds across metrics, and we measure
180 and report that it does not. Identifiability is the empirically-checked *absence* of that bleed, not the
181 presence of the intended effect. Second, the mapping is what makes the Corpus Diagnosis (Section 4)
182 actionable: without it, a task failure cannot be attributed to a specific corpus rule. We therefore treat
183 identifiability as a design *requirement to be verified per instrument*—a property an instrument can
184 lack—and verifying it is part of building one, exactly as construct validity is. On the procedural
185 domain the verification is clean (Table 3): ablating each knowledge component degrades only its
186 governed metric, with maximum off-diagonal change 0.0000—no cross-bleed.

187 **Robustness to weighting choices.** The objective embeds weighting choices—the elliptical ship-
188 domain radii and the margin/compliance/deviation weights—and a fair worry is that the compe-
189 tence ranking is an artifact of those choices. We falsify this with a sensitivity analysis (`npm run`
190 `colreg:sensitivity`) that holds every policy’s *behavior* fixed and re-scores under 232 perturba-
191 tions: a one-at-a-time ± 25 –50% sweep of each parameter plus 200 joint samples with every param-
192 eter independently scaled in $[0.6, 1.4]$. Across the whole ensemble, both orderings are preserved
193 exactly—the naive policy stays worst and the six-component competence gradient stays monotone
194 in J (Kendall $\tau = 1.00$ on every perturbation, invariant rate 100%). The CRI parameters are ex-
195 cluded because CRI is a reported diagnostic, not a term in the scored objective, so the ranking is
196 invariant to them by construction. The protocol’s conclusions are thus a property of the competence
197 structure, not of the weight calibration.

198 **Estimator recovery and calibration.** Feeding the instrument’s outcomes into a generic learner-
199 agent estimator, we recover known ground truth on synthetic data (Table 4). This turns “we have a
200 metric” into “the measurement is valid.”

Estimator	Recovery of known ground truth	Calibration (ECE)
Elo	static ability, mean abs. error 0.046	0.023
BKT	latent state $P(\hat{L}) = 0.997$ (learned) vs. 0.175 (not)	0.004

Table 4: Estimator-recovery and calibration on synthetic data with a known ground truth. The measurement, not just the metric, is validated.

4 The Corpus Diagnosis: the same instrument, read backwards

The Corpus Diagnosis is not a second tool. It is the Transfer Instrument of Section 3 run in reverse: the *same* objective metric answers two opposite questions. This backward reading—*does the learner rely on a given corpus item?*—is the paper’s central contribution; the forward construct validity of Section 3 is what licenses it.

(i) Corpus-gap localization. When the corpus is missing or wrong on a rule, the learner’s failures on the governed metric have a signature that attributes the failure to a *specific* rule/node. We compute, per rule, an ablation-delta—the rise in the governed penalty when that rule is removed—and a localization that names the governed component. A large delta plus a matching localization means the learner *relied on* that corpus rule.

(ii) Parametric leakage detection (necessity). The mirror image: ablate a rule from the corpus; if the metric it governs does *not* degrade, the model is answering from pretrained priors, not the corpus. We combine the ablation-delta with a *counterfactual* test (replace “alter to starboard” with “alter to port”; does the learner follow the altered rule?) and a *closed-book* contamination baseline (no corpus supplied). The verdict—CORPUS-BOUND, LEAKING, or INCONCLUSIVE—is read from the same metric, by a majority vote over the three signals so that a clear ablation-and-contamination pattern is not vetoed by a single dissenting sub-test. Section 6.1 calibrates this necessity against a known parametric baseline by construction. Because the bounded compliance penalty is a *term inside* the objective J , this necessity is read off the graded regret instrument itself—not a decoupled side-metric—and is visible per model in the $\delta_{\mathcal{R}}$ column of Table 5.

(iii) Why an item is not needed: *redundant* vs. *unusable*. A small ablation-delta says the corpus did not move behavior, but not *why*, and the two reasons demand opposite fixes. We split a LEAKING item by its *with-corpus* performance: *redundant* (the learner is competent *with* the item present—it already knows the rule, so the item is dead weight and should be pruned) versus *unusable* (the learner fails the task *even with* the item present—the content has value but this model cannot act on it, so the fix is the model/prompting/retrieval, not the corpus). The delta alone conflates these; the with-corpus outcome (regret in the control domain, accuracy in QA) separates them. On the real-model sweep this is not hypothetical: on the corpus-only hazard, Claude Opus reads CORPUS-BOUND while Llama-3.3-70B grounds regardless (with-corpus regret ≈ 457)—*unusable*, not *redundant*.

Corpus sufficiency, and false sufficiency. Rolling the per-item verdicts to the corpus level yields a sufficiency judgement for a query set: *contributing* (every item relied upon), *partial*, *unusable*, or—the diagnostic ordinary RAG metrics cannot produce—*false sufficiency*: task accuracy is high yet necessity is ≈ 0 everywhere, so the corpus is not carrying the load and success rides on priors, fragile to distribution shift. The claim is explicitly scoped to the probed query set (sufficiency is always “for these queries”); the false-sufficiency signal (necessity ≈ 0) is precisely the measurable warning that a bounded-query sufficiency claim will not survive a shift.

Offline recovery of known ground truth. Before the real-model sweep, we confirm the verdicts recover truth we control. Against two reference mock learners whose truth is known, the instrument recovers it exactly: the corpus-bound mock yields ablation-delta 1.000 (regret-ablation 1981), follows the counterfactual, and abstains closed-book ($\Rightarrow$ CORPUS-BOUND); the leaking mock yields ablation-delta 0.000 (regret-ablation 0), ignores the counterfactual, and answers closed-book from priors ($\Rightarrow$ LEAKING).

Model	Standard relied/4	Charted hazard (corpus-only)		
		$\delta_{\mathcal{R}}$	$\mathcal{R}_{\text{with}}$	reads hazard as
<i>mock corpus-bound</i>	—	1981	0.2	CORPUS-BOUND
<i>mock leaking</i>	0	0	—	LEAKING
Claude Haiku 4.5	0	669	0.2	INCONCL.
Claude Sonnet 4.5	1	669	0.2	LEAKING
Claude Opus 4.5	1	1998	0.2	CORPUS-BOUND
Llama-3.1-8B	0	667	0.1	LEAKING
Llama-3.3-70B	0	213	457	UNUSABLE
Nova-micro	1	0	670	UNUSABLE
Nova-lite	0	145	0.2	INCONCL.
Nova-pro	1	669	0.2	INCONCL.

Table 5: Cross-model necessity on AWS Bedrock (eight models). **relied/4**: standard-COLREG rules the model relies on, of four (per-item audit); 0–1 reads *redundant*/false-sufficiency. **Hazard**: $\delta_{\mathcal{R}}$ is necessity (regret rise when the corpus-only rule is ablated); $\mathcal{R}_{\text{with}}$ is regret *with* the rule present (≈ 0.2 = clears, so *usable*; $\gg 0$ = grounds anyway = UNUSABLE). Standard COLREG is *redundant* across all eight (relied 0–1/4). On the hazard, $\delta_{\mathcal{R}}$ ranges from 0 (Nova-micro ignores it) to 1998 (Opus, full-barrier CORPUS-BOUND); this number is a coarse ordinal set by the fixed sim geometry (identical maneuvers therefore yield identical $\delta_{\mathcal{R}}$ —four models emit the same 30° avoidance and land at 669), not a fine-grained per-model scalar. $\mathcal{R}_{\text{with}}$ exposes two models that ground even with the rule (UNUSABLE). Mock learners bound the scale. (Two open gpt-oss reasoning models were excluded: their reasoning did not reliably terminate within the decode budget, so the single-shot instrument cannot score them without a variance control—see text.)

243 **Real-model discrimination (CS1.3).** We run the necessity test on eight production models over
244 AWS Bedrock—Claude Haiku/Sonnet/Opus 4.5, Llama-3.1-8B / 3.3-70B, and Nova micro/lite/pro—
245 contrasting a *standard-COLREG* corpus with the *corpus-only charted hazard* of Section 6.1 (Table 5,
246 Figure 3). Three findings.

247 (1) *Standard rules are redundant for these frontier models.* Every model relies on little of the stan-
248 dard corpus (relied 0–1 of 4; it duplicates their parametric COLREG—*redundant*, an actionable “do
249 not ship” verdict). We also ran two open reasoning models (OpenAI gpt-oss 20B/120B) that *ap-*
250 *peared* to rely on the same corpus (relied 2–3/4), but we exclude them from Table 5: the single-shot
251 instrument cannot score them reliably. Their harmony-format reasoning frequently failed to termi-
252 nate within the decode budget (the 20B needed a 50k-token budget where every other model used
253 $< 4k$), and with no repeat/variance control an unstable output yields ablation deltas indistinguish-
254 able from genuine reliance. Whether such models truly rely on standard COLREG—i.e. whether
255 necessity is a property of the (corpus, learner) pair and not the corpus alone—is a real question, but
256 confirming it needs a variance-controlled, parse-budget-matched rerun (future work).

257 (2) *Necessity has wide dynamic range on the hazard.* $\delta_{\mathcal{R}}$ spans 0 to ~ 2000 : Nova-micro ignores
258 the corpus ($\delta_{\mathcal{R}}=0$) while Opus reads it and clears at the full barrier ($\delta_{\mathcal{R}}=1998$, $\mathcal{R}_{\text{with}}=0.2$)—the
259 cleanest CORPUS-BOUND reader.

260 (3) *The redundant-vs-unusable split shows on real models* (Figure 3). With-corpus regret separates
261 *usable* from *unusable*: all clear once given the rule ($\mathcal{R}_{\text{with}} \approx 0.2$) *except* Llama-3.3-70B (457) and
262 Nova-micro (670), which ground *even with the rule present*—the content has value but the model
263 cannot act on it (UNUSABLE; fix the model, not the corpus). This is genuine learner-dependence:
264 the same corpus item is *usable* for one model and *unusable* for another. (A prompt-condition study
265 on Gemini gives the binding-fidelity control: under a strict binding prompt necessity grades mono-
266 tonically with capability; removing the clause flips every model to LEAKING.) The continuous $\delta_{\mathcal{R}}$
267 and $\mathcal{R}_{\text{with}}$ are more reliable than the categorical verdict, a noisier three-signal majority vote.

268 **Per-rule, not just per-corpus.** To show the diagnosis attributes reliance to a *specific* rule rather
269 than to corpus presence in general, we add a second, independent rule—Rule 15 crossing give-way—
270 exercised on its own crossing scenarios (a rule only moves the metric on scenarios that invoke it, so
271 each probe carries a matched subset). Ablating each rule produces a large regret signal on its own




Figure 3: The necessity–usability plane for the eight models of Table 5 on the corpus-only hazard. *Horizontal*: necessity $\delta_{\mathcal{R}}$ (how much ablating the rule raises regret; a coarse ordinal set by the fixed geometry—the four blue points at $\delta_{\mathcal{R}} \approx 668$ are four models that emit the same avoidance angle). *Vertical*: with-corpus regret— ≈ 0 (blue, on the axis) means the model *clears* once given the rule (*usable*); a large value (orange) means it *grounds even with the rule present* (*unusable*). Reliance and usability are distinct axes: Claude Opus reads the corpus-only fact and clears, while Nova-micro and Llama-70B ground regardless.

272 encounters: on `gemini-flash-latest` under the bound prompt, ablating Rule 14 gives $\delta_{\mathcal{R}}=1981$
 273 (head-on) and ablating Rule 15 gives 1285 (crossing); on `gemini-flash-lite-latest`, 658 and
 274 662 respectively. The two rules are localized on disjoint scenario subsets, so the instrument reads
 275 reliance per rule.

276 **A real fact can be corpus-only (screen check, CS3.1).** A fair worry about the hazard arm is
 277 that our danger is *fictional*, so “the model is corpus-bound” might just mean “the model cannot
 278 know an invented fact.” We answer the narrower, real question this raises—*can a genuine, publicly-*
 279 *charted fact be corpus-only for a frontier model?*—with a closed-book *screen*: we ask Claude Opus
 280 to name each candidate danger unprompted and keep only the ones it cannot recall. Two obscure,
 281 official-gazetteer-verified rocks—Elwha Rock (Cayou Channel, Puget Sound) and Fullastern Rock
 282 (Adelaide Island, Antarctica)—survive the screen (Opus does not name them), while Whittle Rock
 283 (False Bay) is *screened out* (Opus names it unprompted, so it is parametric, not corpus-only)—the
 284 screen working as designed. We stress what this leg does and does not show. It validates the *screen*:
 285 a real fact *can* be corpus-only for a current model, so the necessity phenomenon is not an artifact
 286 of using invented dangers. It does *not* add an independent measurement of the necessity magnitude:
 287 because the hazard’s identity never enters the objective J (only its rule text and location vary in
 288 a fixed rig), any hazard Opus reads yields the same full-barrier $\delta_{\mathcal{R}} \approx 1998$ *by construction*—the
 289 number is invariant to which danger it is, not a fresh confirmation. The screen is also imperfect:
 290 a famous positive control, the Seven Stones reef, failed to screen out for the wrong reason (Opus
 291 recalled adjacent dangers rather than its track), which we report rather than force. The load-bearing
 292 evidence that necessity is *graded and calibrated* is the simulator-free fact-QA dose-response (Sec-
 293 tion 6.1, CS3.2), where the metric is answer-accuracy over many independent facts and carries no
 294 fixed-geometry confound.

295 **What in the corpus changes the answer: presence vs. retrieval.** The leakage test asks a binary
 296 question—does the learner rely on the corpus at all. A deployed RAG tutor raises a finer one: of the
 297 value curation adds, how much comes from the fact being *present* in the corpus versus from the re-
 298 triever actually *surfacing* it? We decompose this over two binary factors—in-corpus and retrieved—
 299 whose three reachable cells are three scorable conditions (Table 6): NONE (closed-book, priors only),
 300 RETRIEVED (the deployed dense retriever’s top- k), and ORACLE (the answer-bearing chunk, i.e. per-
 301 fect retrieval). Reading accuracy across them attributes the gain: $\text{acc}(\text{ORACLE}) - \text{acc}(\text{NONE})$ is the
 302 *content ceiling* (value if retrieval were perfect), $\text{acc}(\text{RETRIEVED}) - \text{acc}(\text{NONE})$ is what the deployed
 303 pipeline *delivers*, and their difference is the *retrieval gap*—value present in the corpus but never
 304 surfaced. Running the three conditions through a small local generator (Qwen2.5-1.5B) on seven
 305 equipment-SOP fact-recall queries makes the split concrete: closed-book accuracy is 0/7 (empty pri-
 306 ors), ORACLE is 7/7 (every fact is recoverable from its chunk), and the deployed MiniLM pipeline

	not retrieved	retrieved
not in corpus	priors only (NONE)	— (unreachable)
in corpus	retriever misses (<i>gap</i>)	RAG success (RETRIEVED→ORACLE)

Table 6: Decomposing a RAG answer’s outcome over in-corpus $\times$ retrieved. The three reachable cells are the NONE/RETRIEVED/ORACLE conditions; $\text{acc}(\text{ORACLE}) - \text{acc}(\text{NONE})$ is the content ceiling, $\text{acc}(\text{RETRIEVED}) - \text{acc}(\text{NONE})$ what the pipeline delivers, their difference the retrieval gap. Har-ness: experiments/retrieval-decomp.

lands between at 3/7—so of a 100% content ceiling the pipeline *delivers* 43% and *forfeits* a 57% retrieval gap; a generator-independent recall@5 of any answer-bearing chunk (4/7) localizes it. Here the binding constraint is retrieval, not corpus coverage or model capability, and a curation failure (fact absent), a retrieval failure (present but unranked), and a priors success are distinct outcomes the binary leakage verdict cannot separate. (Numbers illustrate the method—one small model, seven queries—not a benchmark.)

5 Case Study 2 — from blind to expert: reading quality and reasoning depth

Necessity is always measured against a *learner*, so it helps to name the cast. We arrange them on a *learner ladder* of increasing corpus use—**blind** (cannot perceive the danger; holds course and collides), **naive** (sighted but untrained; avoids, but generically—wrong side or over-bold), **implementer** (applies a corpus rule verbatim where the situation matches the corpus), and **reasoner** (combines the corpus with base rules and partial observation for novel or ambiguous cases)—with an off-ladder **parametric expert** that is competent *without* the corpus (it already knows the rule in its weights; necessity ≈ 0). Each rung-gap is a distinct corpus contribution and a distinct measurement. Case Study 1 (Section 4) lives on the source axis—*anything* vs. *parametric expert*, i.e. necessity itself. This section walks the depth ladder’s lower rungs: blind→naive is the *existence* gap, naive→implementer the response-*quality* gap (CS2.1), and implementer→reasoner the *generalization* gap (CS2.2).

Perception is a second source of the information the corpus can carry, which couples *what the corpus must supply* to *whether the learner can see*: an existence-corpus (“a danger is there”) is necessary only when the learner is *blind*, and a quality-corpus (“the right way to pass it”) only when the learner is *sighted* (perception already gives existence but not which-side or how-much). This is exactly why CS1 *hides* the hazard—so existence must come from the corpus and the learner must be blind—while CS2 *shows* it—so existence is free and the corpus must earn its keep on quality.

CS2.1 — decision quality (the middle band). The transfer objective of Section 3 is deliberately *bimodal*: a single hard barrier (collision/grounding, ≈ 2000) dominates the graded terms $\sim 1000\times$, so read directly it measures *existence* (did you avoid at all), not *quality* (did you avoid well). Reading quality off its *own* axis—the graded terms (ship-margin + compliance + route-deviation) *conditional on clearing*—separates three sailors the barrier alone conflates: **blind** collides (the barrier fires), **naive** clears but the wrong way (quality-regret ≈ 0.87 , the middle band), and **trained** clears lawfully (quality-regret ≈ 0.01 , the floor). A turn-angle sweep traces a smooth graded quality surface whose minimum sits at the trained maneuver, so the middle band is a genuine continuum, not a third discrete level. *Honest note*: this graded band comes from the smooth quality terms; a hard *second* hazard (a shoal on the wrong-side escape) yields only a thin feasibility shell rather than a graded surface, and that harder version is deferred to CS2.2’s overriding cases.

CS2.2 — reason vs. implement (the generalization axis). The deepest rung separates two *trained* learners that are identical on textbook cases and diverge only where a corpus *local rule* must override the reflex. We add a reasoning-aware objective in which a corpus-supplied local rule redefines the governing give-way side (COLREG Rules 2 and 9 subordinate the default steering rules to local conditions and good seamanship); when the local rule is absent the default starboard governs, so every prior scenario and result is unchanged. An *implementer* that looks the rule up and applies it verbatim and a *reasoner* that treats the corpus as premises then behave identically where the textbook rule already fits, and diverge only where the local rule overrides it. On a matched suite the two are indistinguishable (implementer $\equiv$ reasoner, $\Delta\text{regret } 0.00$); on a conflict suite built so

the safe side *alternates* port/starboard—so no fixed reflex can pass—the **reasoner clears** 6/6 while the **lookup implementer clears only the** 3 reaches where the local rule is redundant with Rule 14 and *grounds on the 3 it overrides*. The necessity of the local-rule corpus is thus 3/6, separable *only* on the overriding cases—the fact-vs-reasoning distinction (RAG-as-lookup vs. RAG-as-reasoning-substrate) made measurable. *As in CS2.1, these use hand-built reference policies with known ground truth*, so the run validates the *instrument*; a real model is the *subject*, run through the same rig (the live path is wired).

6 Validating necessity at the weight level

The necessity/leakage test infers a fact about a model’s *weights* from a change in the *prompt*: ablate an item from the corpus, and if the governed outcome does not move, the model did not need it. The sharpest objection is that corpus *context* removal is not weight-level *knowledge* change, so a small necessity could be the no-context heuristic in disguise—or, conversely, a large necessity could reflect a fact the model happens not to know for reasons we did not control. We close this two ways, in increasing strength.

6.1 Validation by construction: the necessity dose-response

The holding this section establishes: *necessity is a non-confounded, calibrated measure*—teaching a fact into the weights drives it down as a dose-response—so a near-zero reading is evidence the model already knew the item, not a context-removal artifact. The decisive test is *known-groups*: build models along a gradient from fact-naïve to fact-knowing *by construction*, and show necessity falls monotonically. We teach a target fact into the weights (LoRA SFT) and sweep two independent knowledge gradients—the LoRA scale α (one adapter, evaluated at $\alpha \in [0, 1]$) and training checkpoints—so their agreement rules out a gradient-method artifact. We run this in two domains with *independent objectives*, the second of which uses no simulator at all.

Domain 1 — control-regret (a hidden hazard), CS1.7. Standard COLREG rules have little dynamic range for this test—every current frontier model already knows them (Section 4)—so we use a *corpus-only charted hazard*: a danger scored by the objective barrier but not shown in the prompt, knowable only from the corpus. Teaching it into a Qwen2.5-3B model collapses necessity from a full-barrier swing ($\mathcal{R}$ -necessity ≈ 667 , naïve) to ≈ 0.2 (taught), and the α and checkpoint sweeps *agree* on the transition. The curve is a *step*, not graded—the correct signature for a *single discrete fact*, which is learned as a threshold (the model either lacks the fact and grounds, or has it and clears)—so the hazard arm establishes the large-effect known-groups *endpoints*, and the graded curve is Domain 2’s job.

Domain 2 — simulator-free fictional-fact QA, CS3.2. We invent facts about fictional entities (research outposts and their attributes) that no model can have memorized, and score answers with a programmatic checker—*no simulator, no reference policy*. Because the facts are fictional, a competent model is necessarily corpus-bound at baseline, and because there are many *independent* facts, partial teaching learns a fraction of them, so the aggregate necessity is *graded*. Teaching the facts into a Qwen2.5-7B-Instruct model drives mean necessity smoothly and monotonically down the LoRA- α gradient: $1.00 \rightarrow 0.93 \rightarrow 0.29 \rightarrow 0.03$ (Table 7), with the verdict flipping CORPUS-BOUND $\rightarrow$ LEAKING as the facts are internalized. A training-checkpoint sweep reproduces the same curve ($1.00 \rightarrow 0.25 \rightarrow 0.03$)—the two gradients are built differently (scaling one converged adapter vs. genuine partial training), so their agreement rules out a gradient-method artifact. This is the clean dose-response, in a domain we did not build a simulator for—answering the objection that the measure is an artifact of one hand-built environment. (Necessity here is measured closed-book: the without-corpus condition permits parametric answering, so taught knowledge surfaces rather than being suppressed by a strict “answer only from the provided facts” instruction.)

6.2 Validation by unlearning: a *says* $\neq$ *does* dissociation (supporting, CS4.3)

The complementary direction removes a rule the model *does* know and asks whether necessity rises. This arm is secondary—it has dynamic range only on a rule with a real corpus-vs-prior gap, which the standard rules lack—but it yields an independently interesting result. We remove the alter-to-

Domain / objective	necessity across the knowledge gradient				
	naive	... step ...			taught
Hazard / $\mathcal{R}$ (Qwen-3B)	667				0.2
	$\alpha=0$	0.25	0.5	0.75	$\alpha=1$
Fictional-fact QA / accuracy (Qwen-7B)	1.00	0.93	0.29	0.03	0.03

Table 7: Necessity dose-response by construction. Teaching a fact into the weights drives the instrument’s necessity for that fact down. The hazard (control-regret objective) gives a large-effect *step*—the known-groups endpoints for one discrete fact, with α /checkpoint sweeps agreeing—while the simulator-free fictional-fact QA (answer-accuracy objective) gives the *graded* monotone curve over many independent facts. Two objectives, one measure. Harness: `experiments/unlearning` (`dose_response.py`), `src/engine/factqa`.

starboard knowledge from an open-weight model with a real unlearning method—SimNPO [Fan et al., 2024] as primary (reference-free, length-normalized), with NPO [Zhang et al., 2024], RMU [Li et al., 2024], and gradient ascent [Jang et al., 2022] as baselines—and score the base vs. unlearned model on the reference-policy instrument. A removal audit [Lynch et al., 2024] reports whether the knowledge is *gone* vs. merely *suppressed*; for a stable novice that resists benign relearning we layer in a robust utility-preserving recipe [Singh et al., 2025]. A completed GPU run (gentle, guardrailed SimNPO on Qwen2.5-3B; config in Table 8) delivers not just the audit half but a first instrument-scoring result, whose lesson is sharper than the predicted 2×2 : **the standard free-text unlearning metrics overstate removal because they measure what the model says; the reference-policy instrument measures what the model *does*—its steering decision—and shows the decision is untouched.**

Primary result: a *says* $\neq$ *does* dissociation. Every metric that reads the model’s *words* registers forgetting: on the GPU run the forget-probe “starboard” rate falls $0.43 \rightarrow 0.27$, the forget-set NLL rises $7.4 \rightarrow 32.4$ (retain-set NLL, teacher-forced, even *improves* $4.3 \rightarrow 1.07$), and—most tellingly—the Rule-14 *citation* disappears, the model reattributing its maneuver to Rules 15/16/17. (A CPU run reproduces the likelihood collapse method-agnostically: forget NLL $4.6 \rightarrow 92$, direction-cue $5/6 \rightarrow 0/6$.) Yet the *decision* the instrument scores does not budge: the unlearned model’s completions *still turn* $+30^\circ$ to starboard (model damage flat at 0.10, retain-coherence 0.91)—the one quantity with real dynamic range here (the aggressive recipe below *does* move it, to port) stays put while every words-level metric registers forgetting. We separate this from the *verdict*: the 2×2 also does not move (both base and unlearned read LEAKING, ablation-delta 0.000), but that half carries *no* information, because Rule 14 already leaks at baseline, so ablating it is a null with no dynamic range for *any* weights (we make this explicit below). The dissociation rests on the heading, which *can* move and does not; the frozen verdict is a consequence of the baseline, not a measurement. A words-level metric reports a fact removed while the policy that governs behavior is entirely intact.

Suppressed, not removed (benign relearning). A gone-vs.-suppressed test [Hu et al., 2024, Deeb and Roger, 2024] confirms the reading from the other side. Twenty benign fine-tuning steps pull the forget-set NLL $32.4 \rightarrow 9.2$, back near its base value—the textbook *suppressed-not-removed* signature: the fact was never gone, only pushed down. Across the whole pipeline—base $\rightarrow$ unlearned $\rightarrow$ relearned—the one quantity that never moves is the decision the instrument measures: starboard, verdict LEAKING, at every stage. The likelihood rises and falls; the policy does not.

Contrast: aggressive unlearning *inverts* the rule. The gentleness is load-bearing. An earlier, aggressive recipe ($\text{lr } 1 \times 10^{-4}$, retain_weight 1.0, no guardrail) drove model damage $0.10 \rightarrow 0.33$ and turned the ship to *port*—the wrong way—on 6/8 prompts, moving the 2×2 to 6/8 port and verdict INCONCLUSIVE. Because the head-on turn is essentially binary, the default objective (push down “starboard”) simply relocated the mass onto “port,” *inverting* the safety rule rather than removing it—a caution that naive weight-level unlearning of a safety rule can yield *confident non-compliance*. The two recipes bracket the finding: gentle unlearning suppresses the *words* but not the *policy* (the instrument stays flat and so exposes the illusion), while aggressive unlearning moves the instrument—in the wrong direction. In both, the probe metrics track words and the instrument tracks the decision.

Metric	1.5B (CPU, SimNPO)		3B (GPU, gentle SimNPO)	
	base	unlearned	base	unlearned
Forget-target NLL ($\uparrow$)	4.6	92.0	7.4	32.4
Retain-set NLL, teacher-forced ($\downarrow$)	3.2	0.18	4.3	1.07
Forget-probe “starboard” rate ($\downarrow$)	5/6	0/6	0.43	0.27
Retain-coherence, free-gen ($\uparrow$)	—	—	1.00	0.91
Model damage (wrong+degen., $\downarrow$)	—	—	0.10	0.10
<i>Steering decision (instrument)</i>	—	—	<i>stbd</i>	<i>stbd</i>

Table 8: Gentle, guardrailed SimNPO unlearning of the alter-to-starboard rule, on a 1.5B model (CPU) and Qwen2.5-3B (GPU, bf16; 5×10^{-5} , retain_weight 3.0, Rule-14 kept in the retain set). Every *words-level* metric registers forgetting—the forget-target likelihood collapses (NLL $\uparrow$), the “starboard” probe rate drops, and the Rule-14 citation disappears (model cites 15/16/17)—while retain utility is preserved (retain NLL improves; free-generation coherence 0.91) and there is no inversion (model damage flat at 0.10). Yet the *decision* the reference-policy instrument scores is untouched: the unlearned model still turns $+30^\circ$ to starboard, and the 2×2 stays verdict LEAKING, ablation-delta 0.000—a *says* $\neq$ *does* dissociation. Benign relearning (20 steps) pulls forget NLL $32.4 \rightarrow 9.2$, confirming the fact was *suppressed*, not removed; the decision holds throughout. Harness: experiments/unlearning.

442 **Why the 2×2 is flat.** Rule 14 is already LEAKING at baseline—every model in Table 5 knows head-
443 on $\rightarrow$ starboard (Section 4)—so ablating it changes nothing (ablation-delta 0), leaving no dynamic
444 range for the corpus-bound cell to travel. The LEAKING verdicts are therefore *correct*; this is exactly
445 why the primary weight-level validation is the construction dose-response (Section 6.1), where a
446 corpus-only fact *does* have range, and not this arm. A broader suite of corpus-only probes across
447 effect sizes (a medium-effect routing convention, a conflicting fact about another vessel’s intention)
448 is future work (Section 8).

449 7 Proxy learners as a pre-trial screen (application)

450 With the measure validated, its intended use is a pre-trial screen. We exercise the instrument with *two*
451 *complementary* controlled-competence proxy classes: (a) a parametric competence-vector learner,
452 and (b) a knowledge-suppressed / unlearned LLM learner (the arm of Section 6.2). Because both
453 are scored on the *same* $\mathcal{R}$ instrument, a method that fails to move the instrument in the expected
454 direction is a *no-go* before any human is recruited—exactly what the *says* $\neq$ *does* dissociation flags
455 for naive unlearning. This differs from prior proxy-learner work [Apartsin et al., 2026, Liu et al.,
456 2026b, Song et al., 2026, Fan et al., 2026, Lee et al., 2026] in scoring on an objective control-task
457 outcome rather than dialogue behavior, profile alignment, or LLM-judge helpfulness.

458 8 Limitations and scope

459 **Mechanism, not external validity.** Every result here is simulation-based mechanism evidence. We
460 make no learning-gains claim and pre-register the human cohort study as future work. **Proxy va-**
461 **lidity.** Simulated learners can be unfaithful—prompt-suppressed and unlearned models may be too
462 capable, may learn unrealistically fast, and need not reproduce authentic human misconceptions;
463 recent work cautions that student simulation is valid only under specific conditions [Yuan et al.,
464 2026] and documents systematic fidelity gaps between LLM “students” and real learners [Wu et al.,
465 2025, Srivatsa et al., 2025]. We therefore treat the two proxy classes as a mutual cross-check, not a
466 substitute for human data—which is exactly why the human cohort study is a pre-registered require-
467 ment rather than an optional extension. **Instrument sensitivity.** The protocol embeds weighting
468 choices (ship domain, objective); we show the ranking survives a $\pm 40\%$ reweighting ($\tau = 1.00$,
469 §3), but robustness beyond that range, and to the elliptical-domain *form* itself, is untested. **Small**
470 **evidence base — illustrative, not a benchmark.** The numbers here demonstrate that the *method*
471 behaves as designed; they are not a validity claim at scale. The discrimination result (Table 5) cov-
472 ers eight models across *three* provider families (Anthropic, Meta, Amazon)—two open reasoning
473 models were run but excluded as unscorable by the single-shot instrument (§4)—and reports the
474 head-on rule; the released harness now exercises *three* rules across *two* metric axes—turn direc-

tion (Rule 14 head-on, Rule 15 crossing) and, on a restricted-visibility subset, speed (Rule 6/19 safe speed, scored through the decision’s speed rather than its heading)—and the unlearning arm turns on a single rule and model family. A persuasive claim still needs more models per family and many more rules/encounters—which is why we release the harness (`experiment.sh`, and a Bedrock provider $\times$ size sweep) built to run exactly that, and report these as worked examples rather than a leaderboard. **Single-rule decomposability may not generalize.** KC $\rightarrow$ single-metric identifiability and clean per-rule ablation are properties we *design into* a governed corpus and *verify* per instrument (Table 3); they are not guaranteed for an arbitrary corpus, whose rules may be entangled, redundant, or jointly govern one outcome. Where a single rule cannot be cleanly isolated, the localization degrades to a coarser attribution and the leakage test to a group-level one; how far clean decomposition extends beyond corpora we constructed is open. **The unlearning arm is a single model at one scale.** The *says $\neq$ does* result (Section 6.2) is informative—a gentle recipe suppresses the *words* while the scored *decision* is untouched, an aggressive one *inverts* the rule—but it is one 3B model, and seed/method variance is outstanding. It is a *supporting* result: a clean necessity transition is structurally out of reach for any pretrained COLREG rule (all leak), which is exactly why the primary weight-level validation is the *construction* dose-response (Section 6.1), where we build the knowledge into the weights and observe necessity fall—already run in two domains, though on single models per domain; more seeds and sizes (and a 7B hazard replication in `bfloat16`, not 4-bit, since quantization noise would confound the effect) remain breadth. **Sufficiency is scoped to a query set.** Every sufficiency verdict is relative to the probed queries; we mitigate rather than escape this by always reporting the query count and by treating the false-sufficiency signal as the measurable warning of fragility to shift, but a corpus adequate for one query distribution may be insufficient for another.

Future work. The pre-registered human cohort study is the external-validity test this in-silico screen is built to de-risk. Method-side, we plan to scale the cross-model discrimination (more providers and rule sets; the harness already runs class $\times$ size sweeps) and to broaden the weight-level battery from one discrete hazard to a *suite* of corpus-only probes across effect sizes—a medium-effect routing convention and a conflicting fact about another vessel’s intention, building on the real charted-danger leg already shown (Section 4)—so necessity is validated as a distribution across probe kinds, not a single test.

9 Conclusion

We have described an in-silico instrument that measures whether a learner *needs* a corpus, and whether a corpus is *sufficient*, before human-subject effort. The central contribution is a *necessity* measure made non-confounded by *construction*: teaching a fact into a model’s weights drives the instrument’s necessity for that fact down as a dose-response, which we demonstrate in two domains with independent objectives—a control-regret simulator (large-effect known-groups endpoints) and a *simulator-free* fictional-fact QA task (the graded monotone curve, $1.00 \rightarrow 0.03$). On that calibrated measure we build a corpus-value audit—ranking items by necessity, localizing a missing item, and splitting the unrelayed-upon into *redundant* versus *unusable*—and a corpus-sufficiency verdict that surfaces *false sufficiency*. Distinct from faithfulness and context-attribution, we measure need against a weight-level baseline they lack. Supporting breadth—a reference-policy transfer instrument with KC $\rightarrow$ single-metric identifiability, cross-model discrimination, a second control domain, and a *says $\neq$ does* unlearning dissociation—rounds out the picture. The claim is testable and narrow; the domains are worked examples, the evidence base is deliberately small, and the measurement method is the point.

Reproducibility. The simulator, the answer-checker QA domain, the diagnosis and sufficiency harness, the construction dose-response, and the open-weight unlearning scaffold will be released, along with a deterministic no-key dry-run that recovers the mock ground truth and one-tap GPU notebooks for the dose-response. (Code is withheld here to preserve double-blind review.)

References

Anonymous. Quantitative COLREG compliance evaluation for autonomous ships. *Ocean Engineering*, 2024a.

526 Anonymous. Control knowledge tracing: A control-theoretic view of knowledge dynamics. In *Conf. on AI in*
527 *Education (CAEAI)*, 2024b.

528 Alexander Apartsin, Omri Sason, and Yehudit Aperia. Toward a benchmark for controllable simulation of
529 imperfect students with large language models, 2026.

530 Susan Bull and Judy Kay. Student models that invite the learner in: The SMILI open learner modelling frame-
531 work. *International Journal of Artificial Intelligence in Education*, 17(2):89–120, 2007.

532 Benjamin Cohen-Wang, Andrew Ilyas, Jonathan Wu, and Aleksander Madry. Contextcite: Attributing model
533 generation to context. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

534 Albert T. Corbett and John R. Anderson. Knowledge tracing: Modeling the acquisition of procedural knowl-
535 edge. *User Modeling and User-Adapted Interaction*, 4(4):253–278, 1994.

536 Aghyad Deeb and Fabien Roger. Do unlearning methods remove information from language model weights?,
537 2024.

538 Shahul Es, Jithin James, Luis Espinosa-Anke, and Steven Schockaert. RAGAS: Automated evaluation of
539 retrieval augmented generation, 2023.

540 Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. Simplicity
541 prevails: Rethinking negative preference optimization for llm unlearning, 2024.

542 Shuyi Fan, Boyuan Deng, Mengyu Xu, Jiale Liu, Hongyang Zhang, Qiaoxin Yang, and Chongyang Gao. Re-
543 thinking llm-judged helpfulness as a pedagogy signal: A pre-registered audit across tutor models, 2026.

544 Paolo Fiorini and Zvi Shiller. Motion planning in dynamic environments using velocity obstacles. *International*
545 *Journal of Robotics Research*, 17(7):760–772, 1998.

546 Weibo Gao, Qi Liu, Linan Yue, Fangzhou Yao, Rui Lv, Zheng Zhang, Hao Wang, and Zhenya Huang.
547 Agent4edu: Generating learner response data by generative agents for intelligent education systems, 2025.

548 Shengyuan Hu, Yiwei Fu, Zhiwei Steven Wu, and Virginia Smith. Unlearning or obfuscating? jogging the
549 memory of unlearned llms via benign relearning, 2024.

550 International Maritime Organization. Convention on the international regulations for preventing collisions at
551 sea (COLREGs), 1972.

552 Siddharth Jain and Venkat Narayan Vedam. Cue-r: Beyond the final answer in retrieval-augmented generation,
553 2026.

554 Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon
555 Seo. Knowledge unlearning for mitigating privacy risks in language models, 2022.

556 Tor A. Johansen, Tristan Perez, and Andrea Cristofaro. Ship collision avoidance and COLREGS compliance
557 using simulation-based control behavior selection with predictive hazard assessment. *IEEE Transactions on*
558 *Intelligent Transportation Systems*, 17(12):3407–3422, 2016.

559 Kenneth R. Koedinger, Albert T. Corbett, and Charles Perfetti. The Knowledge-Learning-Instruction frame-
560 work: Bridging the science-practice chasm to enhance robust student learning. *Cognitive Science*, 36(5):
561 757–798, 2012.

562 Vishakha Lall and Yisi Liu. Ai meets maritime training: Precision analytics for enhanced safety and perfor-
563 mance, 2025.

564 Unggi Lee, Sookbun Lee, Yeil Jeong, Eunjoo Lee, Minchul Shin, and Hoilym Kwon. Educlaw-bench: A
565 long-horizon benchmark for pedagogical llm agents with simulated learners, 2026.

566 Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin
567 Dombrowski, Shashwat Goel, Long Phan, Gabriel Mukobi, Nathan Helm-Burger, Rassan Lababidi, Lennart
568 Justen, Andrew B. Liu, Michael Chen, Isabelle Barrass, Oliver Zhang, Xiaoyuan Zhu, Rishub Tamirisa,
569 Bhruhu Bharathi, Adam Khoja, Zhenqi Zhao, Ariel Herbert-Voss, Cort B. Breuer, Samuel Marks, Oam Patel,
570 Andy Zou, Mantas Mazeika, Zifan Wang, Palash Oswal, Weiran Lin, Adam A. Hunt, Justin Tienken-Harder,
571 Kevin Y. Shih, Kemper Talley, John Guan, Russell Kaplan, Ian Steneker, David Campbell, Brad Jokubaitis,
572 Alex Levinson, Jean Wang, William Qian, Kallol Krishna Karmakar, Steven Basart, Stephen Fitz, Mindy
573 Levine, Ponnuram Kumaraguru, Uday Tupakula, Vijay Varadharajan, Ruoyu Wang, Yan Shoshitaishvili,
574 Jimmy Ba, Kevin M. Esvelt, Alexandr Wang, and Dan Hendrycks. The wmdp benchmark: Measuring and
575 reducing malicious use with unlearning, 2024.

576 Jiayi Liu, Jiaxing Zhang, Bowen Jin, and Jennifer Neville. Generating leakage-free benchmarks for robust rag
577 evaluation, 2026a.

578 Ruochen Liu, Zhiyuan Wen, Hao Yan, Jun Yin, Senzhang Wang, and Jiannong Cao. Ps²: Parameterized control
579 for fine-grained student proficiency simulation, 2026b.

580 Xinyi Lu and Xu Wang. Generative students: Using llm-simulated student profiles to support question item
581 evaluation, 2024.

582 Aengus Lynch, Phillip Guo, Aidan Ewart, Stephen Casper, and Dylan Hadfield-Menell. Eight methods to
583 evaluate robust unlearning in llms, 2024.

584 Barak Or. Quantifying prior dominance in rag systems, 2026.

585 Radek Pelánek. Applications of the Elo rating system in adaptive educational systems. *Computers & Education*,
586 98:169–179, 2016.

587 Naman Deep Singh, Maximilian Müller, Francesco Croce, and Matthias Hein. Unlearning that lasts: Utility-
588 preserving, robust, and almost irreversible forgetting in llms, 2025.

589 Jiajia Song, Zhihan Guo, and Jionghao Lin. Simulating novice students using machine unlearning and relearn-
590 ing in large language models, 2026.

591 KV Aditya Srivatsa, Kaushal Kumar Maurya, and Ekaterina Kochmar. Can llms reliably simulate real students’
592 abilities in mathematics and reading comprehension?, 2025.

593 Adrienne Tuynman and Ronald Ortner. Transfer in reinforcement learning via regret bounds for learning agents,
594 2022.

595 K. W. Van Dongen et al. Construct validity of the LapSim: Can the LapSim virtual reality simulator distinguish
596 between novices and experts? *Surgical Endoscopy*, 21(8):1413–1417, 2007.

597 Lev S. Vygotsky. *Mind in Society: The Development of Higher Psychological Processes*. Harvard University
598 Press, 1978.

599 Tao Wu, Jingyuan Chen, Wang Lin, Mengze Li, Yumeng Zhu, Ang Li, Kun Kuang, and Fei Wu. Embracing
600 imperfection: Simulating students with diverse cognitive levels using llm-based agents, 2025.

601 Rongwu Xu, Zehan Qi, Zhijiang Guo, Cunxiang Wang, Hongru Wang, Yue Zhang, and Wei Xu. Knowledge
602 conflicts for LLMs: A survey. In *Proceedings of EMNLP*, 2024.

603 Zhihao Yuan, Yunze Xiao, Ming Li, Weihao Xuan, Richard Tong, Mona Diab, and Tom Mitchell. Towards
604 valid student simulation with large language models, 2026.

605 Qinggang Zhang, Zhishang Xiang, Yilin Xiao, Le Wang, Junhui Li, Xinrun Wang, and Jinsong Su. Faithfulrag:
606 Fact-level conflict modeling for context-faithful retrieval-augmented generation, 2025.

607 Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. Negative preference optimization: From catastrophic collapse
608 to effective unlearning, 2024.

609 Zinn et al. Assessing flight competency from deviation to an optimal trajectory. *Cognition, Technology & Work*,
610 2023.