

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Deep Learning and its Applications

3RSM Research Project

Tom Wright

University of Birmingham

June 5, 2023

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR


Optimisation
Learning XOR

Applications

References

What is deep learning?

- ▶ Deep learning is a type of **machine learning**.
Statistical technique for extracting knowledge from data (e.g. driving a car, translating text).
- ▶ Centres around the neural network (NN).
- ▶ Inspired by the human brain.
Composition of many simple functions → complex behaviour.

What is deep
learning?Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

History of deep learning

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Deep learning has developed in three distinct waves.

- ▶ **Cybernetics** (1940s - 1960s)

Simple linear networks, inspired by advances in psychology and neuroscience

- ▶ **Connectionism** (1980s - 1990s)

Non-linearity, backpropagation, multi-layer networks

- ▶ **Deep Learning** (2000s - present)

More powerful computers, larger datasets → larger networks, increased complexity and accuracy

Deep learning in recent times

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Deep learning is now used widely throughout the modern world.

- ▶ Facial detection
- ▶ Medical diagnosis
- ▶ Speech recognition (e.g. Siri)
- ▶ Natural language processing (e.g. ChatGPT)
- ▶ Many other cases

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Supervised Learning

Supervised Learning

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

$$\begin{pmatrix} X_1 \\ X_2 \\ X_3 \\ \vdots \\ X_d \end{pmatrix} \in \mathbb{R}^d = X \xrightarrow{\text{"True" Relationship}} Y = f^*(X) + \epsilon \in \mathcal{Y}$$

$$s = \left\{ \left(x^{(i)}, y^{(i)} \right) \right\}_{i=1}^n$$

Dataset

Goal of Supervised Learning

Given:

- ▶ Input $X \in \mathbb{R}^d$ and output $Y = f^*(X) + \epsilon$,
- ▶ Dataset $s = \{(x^{(i)}, y^{(i)})\}_{i=1}^n$,

determine a function

$$f_s : \mathbb{R}^d \rightarrow \mathcal{Y}$$

that makes an accurate **prediction**

$$\hat{y} = f_s(x)$$

of y on unseen observations.

Supervised Learning Task

A supervised learning task involves identifying the following.

1. A **loss function** $\mathcal{L}(f, (x, y))$ that measures the performance of $f : \mathbb{R}^d \rightarrow \mathcal{Y}$ on a single data point.
2. A **hypothesis set** $\mathcal{F}_\theta \subset \mathcal{M}(\mathbb{R}^d, \mathcal{Y})$ that defines a **model** for f_s with parameters θ (we will use neural network!).
3. A **training algorithm** \mathcal{A} that outputs an optimised model $f_s = \mathcal{A}(s)$.

The algorithm \mathcal{A} typically chooses θ by minimising **cost**, the average loss over the dataset:

$$C(f, s) = \frac{1}{n} \sum_{i=1}^n \mathcal{L}(f, s^{(i)}).$$

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Regression vs Classification

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Definition

In a **regression** task, the output Y is a vector of continuous real values with $Y \in \mathcal{Y} = \mathbb{R}^m$.

In a **classification** task, the output Y is one of K discrete classes, with $Y \in \mathcal{Y} = \{0, 1, 2, K - 1\}$.

Simple Regression

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



- ▶ $X, Y \in \mathbb{R}$
- ▶ Each point is an observation $(x^{(i)}, y^{(i)}) \in s$.

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



- ▶ Linear model $\mathcal{F}_{\{a,b\}} = \{f(x) = ax + b \mid a, b \in \mathbb{R}\}$,
- ▶ Train using squared residual loss:

$$\mathcal{L}(f, (x, y)) = (f(x) - y)^2.$$

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



- ▶ Linear model (orange) underfits.
- ▶ Polynomial (red) overfits.
- ▶ Neither is close to the true function f^* .

Overfitting neural networks

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

- ▶ Neural networks **generalise** remarkably well! [1]
*They tend to not overfit: if they fit the training data,
they tend to be close to the true distribution*
- ▶ We will focus on neural networks' ability to fit training data.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Neural Networks

[What is deep learning?](#)[Supervised Learning](#)[Neural Networks](#)[Representing XOR](#)[Optimisation](#)[Learning XOR](#)[Applications](#)[References](#)

Perceptron

- ▶ Simple linear network for binary classification i.e.

$$\mathcal{Y} = \{0, 1\}.$$

- ▶ Invented in 1943 by McCulloch and Pitts.
- ▶ Implemented as enormous electronic machine by Frank Rosenblatt in 1958.



Source: Wikimedia Commons

Figure: Frank Rosenblatt with his Perceptron machine

Perceptron - model

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

- ▶ Input: $x = (x_1, x_2, \dots, x_d)^T$
- ▶ Computes weighted sum

$$z(x) = w^T x + b = w_1 x_1 + \dots + w_d x_d + b$$

for **weights** $w \in \mathbb{R}^d$ and **bias** $b \in \mathbb{R}$.

- ▶ Applies threshold $g(z) = \mathbb{1}(z > 0)$ to obtain prediction.
- ▶ Overall model is

$$\hat{y} = (g \circ z)(x) = \begin{cases} 1 & \text{if } w^T x + b > 0 \\ 0 & \text{otherwise.} \end{cases}$$

Perceptron - example classifier

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



Perceptron - computational graph

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References




$$\hat{y} = (g \circ z)(x) = \begin{cases} 1 & \text{if } w^T x + b > 0 \\ 0 & \text{otherwise.} \end{cases}$$

Extending perceptron

Deep Learning and
its Applications

Tom Wright



- ▶ Replace $\hat{y} \in \mathcal{Y}$ with $a \in \mathbb{R}$ (better for optimisation).
- ▶ Use a to predict \hat{y} (depending on use case).
- ▶ Map $g : \mathbb{R} \rightarrow \mathbb{R}$ is any suitable output map.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References




- ▶ Introduce vector $z^{(1)} \in \mathbb{R}^{N_1}$; each entry is a distinct weighted sum of the inputs.
- ▶ Vector $a^{(1)} = \sigma(z^{(1)})$; σ is non-linear **activation function** applied element-wise.

Extending perceptron

Deep Learning and
its Applications

Tom Wright



- ▶ Entries $z_j^{(1)}$ are called **pre-activations**.
- ▶ Entries $a_j^{(1)}$ are called **activations**.

- Vector $z^{(1)}$ can be written

$$z^{(1)} = \begin{pmatrix} w^1{}^T x + b_1 \\ w^2{}^T x + b_2 \\ \vdots \\ w^{N_1}{}^T x + b_{N_1} \end{pmatrix} = W^{(1)}x + b^{(1)},$$

with

$$W^{(1)} = \begin{pmatrix} w_1^1 & w_2^1 & \cdots & w_d^1 \\ w_1^2 & w_2^2 & \cdots & w_d^2 \\ \vdots & \vdots & \ddots & \vdots \\ w_1^{N_1} & w_2^{N_1} & \cdots & w_d^{N_1} \end{pmatrix}, \quad b^{(1)} = \begin{pmatrix} b_1 \\ b_2 \\ \vdots \\ b_{N_1} \end{pmatrix}.$$

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR


Optimisation

Learning XOR

Applications


References

Activation Functions



Sigmoid

$$g(z) = \frac{e^z}{1 + e^z}$$




Rectified Linear Unit (ReLU)

$$g(z) = \max\{0, z\}$$


*(More efficient for large networks
on digital computers.)*

Extending perceptron



- We have $a = g(z) = g(w^T \sigma(W^{(1)}x + b^{(1)}) + b)$

Extending perceptron



- ▶ Replace z and a with vectors $z^{(2)} = W^{(2)}z^{(1)} + b^{(2)}$ and $a^{(2)} = g(z^{(2)})$

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR


Optimisation

Learning XOR

Applications

References

Output layer



- ▶ Different types of output layer are possible.
- ▶ For multi-class classification, may output probability for each class using a **softmax** output layer:

$$g_i(z) = \frac{e^{z_i}}{\sum_{k=1}^K e^{z_k}}.$$

General Neural Network

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

A neural network with $L \in \mathbb{N}$ layers is defined by architecture $\alpha = (N, \sigma, g)$, where

- ▶ $N = (N_0, N_1, \dots, N_L) \in \mathbb{N}^{L+1}$ gives number of units in each layer,
- ▶ $\sigma : \mathbb{R} \rightarrow \mathbb{R}$ is activation function,
- ▶ $g : \mathbb{R} \rightarrow \mathbb{R}$ is mapping defining output layer.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Activations

In layer $l = 1, 2, \dots, L$ we have **activations** $a^{(l)} \in \mathbb{R}^{N_l}$ and **preactivations** $z^{(l)} \in \mathbb{R}^{N_l}$, related by the following.

$$z^{(1)}(x) = W^{(1)}x + b^{(1)},$$

$$z^{(l)}(x) = W^{(l)}a^{(l-1)} + b^{(l)} \quad \forall l = 2, 3, \dots, L,$$

$$a^{(l)}(x) = \sigma(z^{(l)}) \quad \forall l = 1, 2, \dots, L-1,$$

and $a^{(L)}(x) = g(z^{(L)})$.

Example: a deep network

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



Architecture $\alpha = ((4, 5, 4, 2), \sigma, g)$.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR


Optimisation

Learning XOR

Applications

References

Example: a deep network



- ▶ Architecture $\alpha = ((4, 5, 4, 2), \sigma, g)$, **preativations omitted**.
- ▶ These networks are also known as multi-level perceptrons (MLP).
- ▶ They are called **feed-forward** and **fully-connected**.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Representing XOR



Representations

Deep Learning and
its Applications

Tom Wright

- ▶ A **feature** is a measurable factor of variation.
- ▶ Traditional ML requires engineer to design good **representation**:

A set of features that describe variation in the data well.



What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Representation learning in NNs

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR


Applications

References

- ▶ Each layer of a neural network encodes an increasingly complex representation of the data.
e.g. edges → regions → facial features → identity
- ▶ More layers, more units → more complex representations.
- ▶ By optimising network parameters to fit training data, a good representation is **automatically** selected.

AND Problem

... is linearly separable, so perceptron works!



(x_1, x_2)	$\text{AND}(x_1, x_2)$
(0, 0)	0
(1, 0)	0
(0, 1)	0
(1, 1)	1

Predict $\hat{y} = 1$ if

$$x_1 + x_2 > 1.5$$

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation


Learning XOR

Applications

References

OR Problem

... is linearly separable, so perceptron works!



(x_1, x_2)	$\text{OR}(x_1, x_2)$
$(0, 0)$	0
$(1, 0)$	1
$(0, 1)$	1
$(1, 1)$	1

Predict $\hat{y} = 1$ if


$$x_1 + x_2 > 0.5$$

XOR Problem

Deep Learning and
its Applications

Tom Wright

... is **NOT** linearly separable, so perceptron fails!



(x_1, x_2)	$\text{XOR}(x_1, x_2)$
$(0, 0)$	0
$(1, 0)$	1
$(0, 1)$	1
$(1, 1)$	0

No linear decision
boundary! (Minsky and
Papert, 1969).

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR


Applications

References

Shallow network for XOR

Deep Learning and
its Applications

Tom Wright



- ▶ ReLU activation $\sigma(z) = \max\{0, z\}$.
- ▶ Binary output $g(z) = \mathbb{1}(z^{(2)} > 0)$.
- ▶ Weights:

$$W^{(1)} = \begin{pmatrix} 1 & 1 \\ 1 & 1 \end{pmatrix}, \quad b^{(1)} = \begin{pmatrix} 0 \\ -1 \end{pmatrix}, \quad w = \begin{pmatrix} 1 \\ -2 \end{pmatrix}, \quad b = 0.$$

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Shallow network for XOR

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation


Learning XOR

Applications

References



- With these weights, the **hidden layer** $a^{(1)}$ encodes a new representation of the data...



...in which the data is linearly separable! The weights $w = (1, -2)^T$ and $b = 0$ define a hyperplane: predict $\hat{y} = 1$ if

$$z^{(2)} = w^T a^{(1)} + b = a_1^{(1)} - 2a_2^{(1)} > 0.$$

What is deep
learning?Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Transformation of XOR problem

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Universal Approximation

Theorem (Universal Approximation Theorem)

- ▶ $\Phi_{(N,\sigma,g)}$ a neural network with $L \geq 2$ layers,
- ▶ Output $g(z) = z$ (identity),
- ▶ Finite feature space \mathbb{R}^d and response space \mathcal{Y} ,
- ▶ Weak conditions on activation σ

Then, with enough hidden units, the network $\Phi_{(N,\sigma,g)}$ can approximate any Borel-measurable function $f : \mathbb{R}^d \rightarrow \mathcal{Y}$ with arbitrary precision [1].

Remark

Every continuous function $f : S \subset \mathbb{R}^d \rightarrow \mathbb{R}$ defined on compact set S is Borel-measurable.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Optimisation

Gradient Descent

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References


- ▶ Training data $s = \{(x^{(i)}, y^{(i)})\}_{i=1}^n$.
- ▶ Parameters $\theta = ((W^{(l)}, b^{(l)}))_{l=1}^L$.
- ▶ Minimise cost $C(\theta; s)$ over parameters θ ,

$$C(f, s) = \frac{1}{n} \sum_{i=1}^n \mathcal{L}(f, s^{(i)}).$$

Gradient descent

- ▶ Gradient descent - take small steps in direction of gradient, with learning rate $\eta > 0$:

$$\theta \leftarrow \theta - \eta \nabla_{\theta} C(\theta; s).$$



What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Backpropagation

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

- ▶ To calculate $\nabla_{\theta} C(\theta; s)$ we require


$$\frac{\partial C}{\partial w_{jk}^{(l)}} \quad \text{and} \quad \frac{\partial C}{\partial b_j^{(l)}}.$$

- ▶ To do this we define error vector $\delta^{(l)}$ for each layer with entries

$$\delta_j^{(l)} = \frac{\partial \mathcal{L}}{\partial z_j^{(l)}}.$$

Errors

By a clever application of the chain rule, these errors can be propagated backwards.



What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Backpropagation: equations

This is done using the four equations of backpropagation.

$$\delta_j^{(L)} = \nabla_{a^{(L)}} \mathcal{L}(\theta) \odot g'(z^{(L)}), \quad (\text{BP1})$$

$$\delta^{(I)} = W^{(I+1)T} \delta^{(I+1)} \odot \sigma' \left(z^{(I)} \right), \quad (\text{BP2})$$

$$\frac{\partial \mathcal{L}}{\partial b_j^{(I)}} = \left[\delta^{(I)} \right]_j, \quad (\text{BP3})$$

and $\frac{\partial \mathcal{L}}{\partial w_{jk}^{(I)}} = \left[\delta^{(I)} a^{(I-1)T} \right]_{jk}. \quad (\text{BP4})$

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Learning XOR

XOR without random noise

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



XOR with random noise

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation


Learning XOR

Applications

References



Network model



- ▶ Sigmoid activation σ and output g ,
- ▶ Binary cross-entropy loss (from maximum-likelihood)

$$\mathcal{L}(\theta) = \zeta \left((1 - 2y)z^{(2)} \right),$$

- ▶ Stochastic gradient descent, $\eta = 0.1$, with backprop,
- ▶ Initial random weights and biases
 $W^{(1)} \in \mathbb{R}^{2 \times 2}$, $b^{(1)} \in \mathbb{R}^2$, $w \in \mathbb{R}^2$, $b \in \mathbb{R}$.

Bad Training

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



Good Training

What is deep
learning?

Supervised
Learning

Neural Networks


Representing XOR

Optimisation

Learning XOR

Applications

References



What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

$$W^{(1)} = \begin{pmatrix} -5.63 & -5.48 \\ -7.27 & -7.26 \end{pmatrix}, \quad b^{(1)} = \begin{pmatrix} 8.22 \\ 3.04 \end{pmatrix},$$
$$w = \begin{pmatrix} 12.07 \\ -12.43 \end{pmatrix}, \quad \text{and } b = -5.71.$$

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR


Optimisation

Learning XOR

Applications

References

Evolution of cost with gradient descent iterations



What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Applications

Specialised Networks

Deep Learning and
its Applications

Tom Wright

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

We've studied the most general kind of neural network. In practice, specialised networks are used. These include:

- ▶ Convolutional Neural Networks (CNNs)

Designed for data in grid form, e.g. medical diagnosis, facial recognition.

- ▶ Recurrent Neural Networks (RNNs)

Designed for series data, e.g. weather prediction, natural language processing.

The rise of powerful AI will be either the best or the worst thing ever to happen to humanity. We do not yet know which. —Stephen Hawking

BBC News headlines from May 2023:

- ▶ “*‘AI godfather’ likens his emotions to atom bomb inventors*” (May 31st)
- ▶ “*New super-bug killing antibiotic discovered using AI*” (May 25th)
- ▶ “*BT to cut 55,000 jobs with up to a fifth replaced by AI*” (May 18th)
- ▶ “*Artificial intelligence could lead to extinction, experts warn*” (May 30th)

What is deep learning?

Supervised Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

- ▶ **Mathematical Aspects of Deep Learning** (Grohs and Kutyniok, 2022) [1]
Detailed introduction to mathematical analysis of neural networks.
- ▶ **Deep Learning** (Goodfellow et al., 2016) [2]
Comprehensive textbook on deep learning.
- ▶ **Neural networks and deep learning** (Nielsen, 2015) [3]
Excellent introduction to backpropagation.
- ▶ **An introduction to statistical learning** (Hastie et al., 2022) [4]
Overview of all aspects of machine learning.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Bibliography

Deep Learning and
its Applications

Tom Wright

- [1] Philipp Grohs and Gitta Kutyniok, eds. *Mathematical Aspects of Deep Learning*. Cambridge University Press, 2022. DOI: 10.1017/9781009025096.
- [2] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. <http://www.deeplearningbook.org>. MIT Press, 2016.
- [3] Michael A Nielsen. *Neural networks and deep learning*. Vol. 25. Determination press San Francisco, CA, USA, 2015.
- [4] Gareth James et al. *An introduction to statistical learning: With applications in R*. Springer, 2022.

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

What is deep
learning?

Supervised
Learning

Neural Networks

Representing XOR

Optimisation

Learning XOR

Applications

References

Thank you for listening!