

Writing Regexprs 2021-22 / Regex Parser

Generated by Doxygen 1.9.3

1 Namespace Index	1
1.1 Namespace List	1
2 Hierarchical Index	3
2.1 Class Hierarchy	3
3 Class Index	5
3.1 Class List	5
4 File Index	7
4.1 File List	7
5 Namespace Documentation	9
5.1 wr22 Namespace Reference	9
5.2 wr22::regex_parser Namespace Reference	9
5.3 wr22::regex_parser::parser Namespace Reference	9
5.3.1 Function Documentation	10
5.3.1.1 parse_regex()	10
5.3.1.2 Parser()	10
5.4 wr22::regex_parser::parser::errors Namespace Reference	10
5.5 wr22::regex_parser::regex Namespace Reference	11
5.5.1 Enumeration Type Documentation	11
5.5.1.1 NamedCaptureFlavor	12
5.5.2 Function Documentation	13
5.5.2.1 operator<<() [1/5]	13
5.5.2.2 operator<<() [2/5]	13
5.5.2.3 operator<<() [3/5]	13
5.5.2.4 operator<<() [4/5]	13
5.5.2.5 operator<<() [5/5]	14
5.5.2.6 to_json() [1/6]	14
5.5.2.7 to_json() [2/6]	14
5.5.2.8 to_json() [3/6]	14
5.5.2.9 to_json() [4/6]	14
5.5.2.10 to_json() [5/6]	14
5.5.2.11 to_json() [6/6]	15
5.6 wr22::regex_parser::regex::capture Namespace Reference	15
5.6.1 Typedef Documentation	15
5.6.1.1 Adt	15
5.6.2 Function Documentation	15
5.6.2.1 to_json() [1/3]	15
5.6.2.2 to_json() [2/3]	16
5.6.2.3 to_json() [3/3]	16
5.7 wr22::regex_parser::regex::part Namespace Reference	16
5.7.1 Detailed Description	17

5.7.2 Typedef Documentation	17
5.7.2.1 Adt	17
5.7.3 Function Documentation	17
5.7.3.1 to_json() [1/10]	17
5.7.3.2 to_json() [2/10]	17
5.7.3.3 to_json() [3/10]	18
5.7.3.4 to_json() [4/10]	18
5.7.3.5 to_json() [5/10]	18
5.7.3.6 to_json() [6/10]	18
5.7.3.7 to_json() [7/10]	18
5.7.3.8 to_json() [8/10]	18
5.7.3.9 to_json() [9/10]	19
5.7.3.10 to_json() [10/10]	19
5.8 wr22::regex_parser::span Namespace Reference	19
5.8.1 Function Documentation	19
5.8.1.1 operator<<()	19
5.8.1.2 to_json()	19
6 Class Documentation	21
6.1 wr22::regex_parser::regex::part::Alternatives Struct Reference	21
6.1.1 Detailed Description	21
6.1.2 Constructor & Destructor Documentation	22
6.1.2.1 Alternatives()	22
6.1.3 Member Function Documentation	22
6.1.3.1 operator==()	22
6.1.4 Member Data Documentation	22
6.1.4.1 alternatives	22
6.1.4.2 code_name	22
6.2 wr22::regex_parser::regex::Capture Class Reference	23
6.2.1 Detailed Description	23
6.3 wr22::regex_parser::regex::part::CharacterClass Struct Reference	23
6.3.1 Detailed Description	24
6.3.2 Constructor & Destructor Documentation	24
6.3.2.1 CharacterClass()	24
6.3.3 Member Function Documentation	24
6.3.3.1 operator==()	24
6.3.4 Member Data Documentation	24
6.3.4.1 code_name	24
6.3.4.2 data	24
6.4 wr22::regex_parser::regex::CharacterClassData Struct Reference	25
6.4.1 Detailed Description	25
6.4.2 Member Function Documentation	25

6.4.2.1 operator==()	25
6.4.3 Member Data Documentation	25
6.4.3.1 inverted	25
6.4.3.2 ranges	26
6.5 wr22::regex_parser::regex::CharacterRange Class Reference	26
6.5.1 Detailed Description	26
6.5.2 Member Function Documentation	26
6.5.2.1 contains()	27
6.5.2.2 first()	27
6.5.2.3 from_endpoints()	27
6.5.2.4 from_single_character()	27
6.5.2.5 is_single_character()	27
6.5.2.6 last()	28
6.5.2.7 operator==()	28
6.6 wr22::regex_parser::regex::part::Empty Struct Reference	28
6.6.1 Detailed Description	28
6.6.2 Constructor & Destructor Documentation	28
6.6.2.1 Empty()	29
6.6.3 Member Function Documentation	29
6.6.3.1 operator==()	29
6.6.4 Member Data Documentation	29
6.6.4.1 code_name	29
6.7 wr22::regex_parser::parser::errors::ExpectedEnd Class Reference	29
6.7.1 Detailed Description	30
6.7.2 Constructor & Destructor Documentation	30
6.7.2.1 ExpectedEnd()	30
6.7.3 Member Function Documentation	30
6.7.3.1 char_got()	30
6.7.3.2 position()	31
6.8 wr22::regex_parser::regex::part::Group Struct Reference	31
6.8.1 Detailed Description	31
6.8.2 Constructor & Destructor Documentation	32
6.8.2.1 Group()	32
6.8.3 Member Function Documentation	32
6.8.3.1 operator==()	32
6.8.4 Member Data Documentation	32
6.8.4.1 capture	32
6.8.4.2 code_name	32
6.8.4.3 inner	33
6.9 wr22::regex_parser::regex::capture::Index Struct Reference	33
6.9.1 Detailed Description	33
6.9.2 Constructor & Destructor Documentation	33

6.9.2.1 Index()	33
6.9.3 Member Function Documentation	33
6.9.3.1 operator==()	34
6.9.4 Member Data Documentation	34
6.9.4.1 code_name	34
6.10 wr22::regex_parser::regex::InvalidCharacterRange Struct Reference	34
6.10.1 Constructor & Destructor Documentation	34
6.10.1.1 InvalidCharacterRange()	35
6.10.2 Member Data Documentation	35
6.10.2.1 first	35
6.10.2.2 last	35
6.11 wr22::regex_parser::parser::errors::InvalidRange Class Reference	35
6.11.1 Detailed Description	36
6.11.2 Constructor & Destructor Documentation	36
6.11.2.1 InvalidRange()	36
6.11.3 Member Function Documentation	36
6.11.3.1 first()	36
6.11.3.2 last()	37
6.11.3.3 span()	37
6.12 wr22::regex_parser::span::InvalidSpan Struct Reference	37
6.12.1 Detailed Description	37
6.12.2 Constructor & Destructor Documentation	38
6.12.2.1 InvalidSpan()	38
6.12.3 Member Data Documentation	38
6.12.3.1 begin	38
6.12.3.2 end	38
6.13 wr22::regex_parser::regex::part::Literal Struct Reference	38
6.13.1 Detailed Description	39
6.13.2 Constructor & Destructor Documentation	39
6.13.2.1 Literal()	39
6.13.3 Member Function Documentation	39
6.13.3.1 operator==()	39
6.13.4 Member Data Documentation	39
6.13.4.1 character	39
6.13.4.2 code_name	40
6.14 wr22::regex_parser::regex::capture::Name Struct Reference	40
6.14.1 Detailed Description	40
6.14.2 Constructor & Destructor Documentation	40
6.14.2.1 Name()	40
6.14.3 Member Function Documentation	41
6.14.3.1 operator==()	41
6.14.4 Member Data Documentation	41

6.14.4.1 <code>code_name</code>	41
6.14.4.2 <code>flavor</code>	41
6.14.4.3 <code>name</code>	41
6.15 <code>wr22::regex_parser::regex::capture::None</code> Struct Reference	41
6.15.1 Detailed Description	42
6.15.2 Constructor & Destructor Documentation	42
6.15.2.1 <code>None()</code>	42
6.15.3 Member Function Documentation	42
6.15.3.1 <code>operator==()</code>	42
6.15.4 Member Data Documentation	42
6.15.4.1 <code>code_name</code>	42
6.16 <code>wr22::regex_parser::regex::part::Optional</code> Struct Reference	42
6.16.1 Detailed Description	43
6.16.2 Constructor & Destructor Documentation	43
6.16.2.1 <code>Optional()</code>	43
6.16.3 Member Function Documentation	43
6.16.3.1 <code>operator==()</code>	43
6.16.4 Member Data Documentation	43
6.16.4.1 <code>code_name</code>	44
6.16.4.2 <code>inner</code>	44
6.17 <code>wr22::regex_parser::parser::errors::ParseError</code> Struct Reference	44
6.17.1 Detailed Description	44
6.18 <code>wr22::regex_parser::parser::Parser< Iter, Sentinel ></code> Class Template Reference	44
6.18.1 Detailed Description	45
6.18.2 Constructor & Destructor Documentation	45
6.18.2.1 <code>Parser()</code>	45
6.18.3 Member Function Documentation	46
6.18.3.1 <code>expect_end()</code>	46
6.18.3.2 <code>parse_alternatives()</code>	46
6.18.3.3 <code>parse_atom()</code>	46
6.18.3.4 <code>parse_char_class()</code>	47
6.18.3.5 <code>parse_char_literal()</code>	47
6.18.3.6 <code>parse_group()</code>	47
6.18.3.7 <code>parse_group_name()</code>	48
6.18.3.8 <code>parse_regex()</code>	48
6.18.3.9 <code>parse_sequence()</code>	48
6.18.3.10 <code>parse_sequence_or_empty()</code>	49
6.18.3.11 <code>parse_wildcard()</code>	49
6.19 <code>wr22::regex_parser::regex::Part</code> Class Reference	50
6.19.1 Detailed Description	50
6.20 <code>wr22::regex_parser::regex::part::Plus</code> Struct Reference	51
6.20.1 Detailed Description	51

6.20.2 Constructor & Destructor Documentation	51
6.20.2.1 Plus()	51
6.20.3 Member Function Documentation	51
6.20.3.1 operator==()	51
6.20.4 Member Data Documentation	52
6.20.4.1 code_name	52
6.20.4.2 inner	52
6.21 wr22::regex_parser::regex::part::Sequence Struct Reference	52
6.21.1 Detailed Description	53
6.21.2 Constructor & Destructor Documentation	53
6.21.2.1 Sequence()	53
6.21.3 Member Function Documentation	53
6.21.3.1 operator==()	53
6.21.4 Member Data Documentation	53
6.21.4.1 code_name	53
6.21.4.2 items	53
6.22 wr22::regex_parser::span::Span Class Reference	54
6.22.1 Detailed Description	54
6.22.2 Member Function Documentation	54
6.22.2.1 begin()	55
6.22.2.2 end()	55
6.22.2.3 extend_right()	55
6.22.2.4 length()	55
6.22.2.5 make_empty()	55
6.22.2.6 make_from_positions()	56
6.22.2.7 make_single_position()	56
6.22.2.8 make_with_length()	56
6.22.2.9 operator!=()	57
6.22.2.10 operator==()	57
6.23 wr22::regex_parser::regex::SpannedCharacterRange Struct Reference	57
6.23.1 Detailed Description	57
6.23.2 Member Function Documentation	57
6.23.2.1 operator==()	57
6.23.3 Member Data Documentation	58
6.23.3.1 range	58
6.23.3.2 span	58
6.24 wr22::regex_parser::regex::SpannedPart Class Reference	58
6.24.1 Detailed Description	58
6.24.2 Constructor & Destructor Documentation	58
6.24.2.1 SpannedPart()	59
6.24.3 Member Function Documentation	59
6.24.3.1 operator!=()	59

6.24.3.2 operator==()	59
6.24.3.3 part() [1/2]	59
6.24.3.4 part() [2/2]	59
6.24.3.5 span()	59
6.25 wr22::regex_parser::regex::part::Star Struct Reference	60
6.25.1 Detailed Description	60
6.25.2 Constructor & Destructor Documentation	60
6.25.2.1 Star()	60
6.25.3 Member Function Documentation	60
6.25.3.1 operator==()	60
6.25.4 Member Data Documentation	61
6.25.4.1 code_name	61
6.25.4.2 inner	61
6.26 wr22::regex_parser::parser::errors::UnexpectedChar Class Reference	61
6.26.1 Detailed Description	62
6.26.2 Constructor & Destructor Documentation	62
6.26.2.1 UnexpectedChar()	62
6.26.3 Member Function Documentation	62
6.26.3.1 char_got()	62
6.26.3.2 expected()	62
6.26.3.3 position()	63
6.27 wr22::regex_parser::parser::errors::UnexpectedEnd Class Reference	63
6.27.1 Detailed Description	63
6.27.2 Constructor & Destructor Documentation	63
6.27.2.1 UnexpectedEnd()	63
6.27.3 Member Function Documentation	64
6.27.3.1 expected()	64
6.27.3.2 needs_closing()	64
6.27.3.3 position()	64
6.28 wr22::regex_parser::regex::part::Wildcard Struct Reference	64
6.28.1 Detailed Description	65
6.28.2 Constructor & Destructor Documentation	65
6.28.2.1 Wildcard()	65
6.28.3 Member Function Documentation	65
6.28.3.1 operator==()	65
6.28.4 Member Data Documentation	65
6.28.4.1 code_name	65
7 File Documentation	67
7.1 include/wr22/regex_parser/parser/errors.hpp File Reference	67
7.2 errors.hpp	68
7.3 include/wr22/regex_parser/parser/regex.hpp File Reference	68

7.4 regex.hpp	69
7.5 include/wr22/regex_parser/regex/capture.hpp File Reference	69
7.6 capture.hpp	70
7.7 include/wr22/regex_parser/regex/character_class_data.hpp File Reference	71
7.8 character_class_data.hpp	71
7.9 include/wr22/regex_parser/regex/character_range.hpp File Reference	71
7.10 character_range.hpp	72
7.11 include/wr22/regex_parser/regex/named_capture_flavor.hpp File Reference	72
7.12 named_capture_flavor.hpp	73
7.13 include/wr22/regex_parser/regex/part.hpp File Reference	73
7.14 part.hpp	75
7.15 include/wr22/regex_parser/regex/spanned_character_range.hpp File Reference	77
7.16 spanned_character_range.hpp	77
7.17 include/wr22/regex_parser/span/span.hpp File Reference	78
7.18 span.hpp	78
7.19 src/parser/capture.cpp File Reference	79
7.20 src/parser/errors.cpp File Reference	79
7.21 src/parser/regex.cpp File Reference	80
7.22 src/regex/character_range.cpp File Reference	80
7.23 src/regex/named_capture_flavor.cpp File Reference	81
7.24 src/regex/part.cpp File Reference	81
7.25 src/regex/spanned_character_range.cpp File Reference	82
7.26 src/span/span.cpp File Reference	82
Index	83

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all namespaces with brief descriptions:

wr22	9
wr22::regex_parser	9
wr22::regex_parser::parser	9
wr22::regex_parser::parser::errors	10
wr22::regex_parser::regex	11
wr22::regex_parser::regex::capture	15
wr22::regex_parser::regex::part The namespace with the variants of Part	16
wr22::regex_parser::span	19

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

capture::Adt	
wr22::regex_parser::regex::Capture	23
part::Adt	
wr22::regex_parser::regex::Part	50
wr22::regex_parser::regex::part::Alternatives	21
wr22::regex_parser::regex::part::CharacterClass	23
wr22::regex_parser::regex::CharacterClassData	25
wr22::regex_parser::regex::CharacterRange	26
wr22::regex_parser::regex::part::Empty	28
wr22::regex_parser::regex::part::Group	31
wr22::regex_parser::regex::capture::Index	33
wr22::regex_parser::regex::part::Literal	38
wr22::regex_parser::regex::capture::Name	40
wr22::regex_parser::regex::capture::None	41
wr22::regex_parser::regex::part::Optional	42
wr22::regex_parser::parser::Parser< Iter, Sentinel >	44
wr22::regex_parser::regex::part::Plus	51
std::runtime_error	
wr22::regex_parser::parser::errors::ParseError	44
wr22::regex_parser::parser::errors::ExpectedEnd	29
wr22::regex_parser::parser::errors::InvalidRange	35
wr22::regex_parser::parser::errors::UnexpectedChar	61
wr22::regex_parser::parser::errors::UnexpectedEnd	63
wr22::regex_parser::regex::InvalidCharacterRange	34
wr22::regex_parser::span::InvalidSpan	37
wr22::regex_parser::regex::part::Sequence	52
wr22::regex_parser::span::Span	54
wr22::regex_parser::regex::SpannedCharacterRange	57
wr22::regex_parser::regex::SpannedPart	58
wr22::regex_parser::regex::part::Star	60
wr22::regex_parser::regex::part::Wildcard	64

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

wr22::regex_parser::regex::part::Alternatives	21
A regex part with the list of alternatives to be matched	
wr22::regex_parser::regex::Capture	23
Group capture behavior	
wr22::regex_parser::regex::part::CharacterClass	23
A regex part specifying a character class (e.g. [a-z_])	
wr22::regex_parser::regex::CharacterClassData	25
A character class representation: a list of character ranges plus some additional properties . .	
wr22::regex_parser::regex::CharacterRange	26
A non-empty character range, possibly containing only one character	
wr22::regex_parser::regex::part::Empty	28
An empty regex part	
wr22::regex_parser::parser::errors::ExpectedEnd	29
The error when the parser expected the input to end, but it did not	
wr22::regex_parser::regex::part::Group	31
A regex part that represents a group in parentheses	
wr22::regex_parser::regex::capture::Index	33
Denotes a group captured by index	
wr22::regex_parser::regex::InvalidCharacterRange	34
wr22::regex_parser::parser::errors::InvalidRange	35
The error indicating that a character range in a character class is invalid	
wr22::regex_parser::span::InvalidSpan	37
The exception thrown on an attempt to construct an invalid span	
wr22::regex_parser::regex::part::Literal	38
An regex part that matches a single character literally	
wr22::regex_parser::regex::capture::Name	40
Denotes a group captured by name	
wr22::regex_parser::regex::capture::None	41
Denotes an non-capturing group	
wr22::regex_parser::regex::part::Optional	42
A regex part specifying an optional quantifier ((expression)?)	
wr22::regex_parser::parser::errors::ParseError	44
The base class for parse errors	
wr22::regex_parser::parser::Parser< Iter, Sentinel >	44
A regex parser	

wr22::regex_parser::regex::Part	
A part of a regular expression and its AST node type	50
wr22::regex_parser::regex::part::Plus	
A regex part specifying an "at least one" quantifier ((expression)+)	51
wr22::regex_parser::regex::part::Sequence	
A regex part with the list of items to be matched one after another	52
wr22::regex_parser::span::Span	
Character position range in the input string	54
wr22::regex_parser::regex::SpannedCharacterRange	
A CharacterRange with its span	57
wr22::regex_parser::regex::SpannedPart	
A version of Part including the span information (position in the input) of the root AST node (child nodes always contain it because they are represented as SpannedPart s themselves)	58
wr22::regex_parser::regex::part::Star	
A regex part specifying an "at least zero" quantifier ((expression)*)	60
wr22::regex_parser::parser::errors::UnexpectedChar	
The error when the parser got a character it didn't expect at the current position	61
wr22::regex_parser::parser::errors::UnexpectedEnd	
The error when the parser hit the end of the input earlier than it expected	63
wr22::regex_parser::regex::part::Wildcard	
A regex part specifying any single character (.)	64

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

include/wr22/regex_parser/parser/ errors.hpp	67
include/wr22/regex_parser/parser/ regex.hpp	68
include/wr22/regex_parser/regex/ capture.hpp	69
include/wr22/regex_parser/regex/ character_class_data.hpp	71
include/wr22/regex_parser/regex/ character_range.hpp	71
include/wr22/regex_parser/regex/ named_capture_flavor.hpp	72
include/wr22/regex_parser/regex/ part.hpp	73
include/wr22/regex_parser/regex/ spanned_character_range.hpp	77
include/wr22/regex_parser/span/ span.hpp	78
src/parser/ capture.cpp	79
src/parser/ errors.cpp	79
src/parser/ regex.cpp	80
src/regex/ character_range.cpp	80
src/regex/ named_capture_flavor.cpp	81
src/regex/ part.cpp	81
src/regex/ spanned_character_range.cpp	82
src/span/ span.cpp	82

Chapter 5

Namespace Documentation

5.1 wr22 Namespace Reference

Namespaces

- namespace [regex_parser](#)

5.2 wr22::regex_parser Namespace Reference

Namespaces

- namespace [parser](#)
- namespace [regex](#)
- namespace [span](#)

5.3 wr22::regex_parser::parser Namespace Reference

Namespaces

- namespace [errors](#)

Classes

- class [Parser](#)
A regex parser.

Functions

- template<typename Iter , typename Sentinel >
[Parser](#) (Iter begin, Sentinel end) -> [Parser](#)< Iter, Sentinel >
The type deduction guideline for [Parser](#).
- [regex::SpannedPart parse_regex](#) (const std::u32string_view ®ex)
Parse a regular expression into its AST.

5.3.1 Function Documentation

5.3.1.1 `parse_regex()`

```
regex::SpannedPart wr22::regex_parser::parser::parse_regex (
    const std::u32string_view & regex )
```

Parse a regular expression into its AST.

The regular expression is a string view in the UTF-32 encoding. It is parsed and its object representation (see the docs for `regex::SpannedPart`) is built. The returned representation is an owned object and its lifetime does not depend on the lifetime of the `regex` argument.

If the parsing fails, an exception is thrown. `errors::ParseError` is the base class for all exceptions thrown from this function, but more specific exceptions may be caught and handled separately. See the docs for the `errors.hpp` file for details.

Returns

the parsed regex AST if the parsing succeeds.

Exceptions

<code>errors::ParseError</code>	if the parsing fails.
---------------------------------	-----------------------

5.3.1.2 `Parser()`

```
template<typename Iter , typename Sentinel >
wr22::regex_parser::parser::Parser (
    Iter begin,
    Sentinel end ) -> Parser< Iter, Sentinel >
```

The type deduction guideline for `Parser`.

5.4 `wr22::regex_parser::parser::errors` Namespace Reference

Classes

- class `ExpectedEnd`
The error when the parser expected the input to end, but it did not.
- class `InvalidRange`
The error indicating that a character range in a character class is invalid.
- struct `ParseError`
The base class for parse errors.
- class `UnexpectedChar`
The error when the parser got a character it didn't expect at the current position.
- class `UnexpectedEnd`
The error when the parser hit the end of the input earlier than it expected.

5.5 wr22::regex_parser::regex Namespace Reference

Namespaces

- namespace [capture](#)
- namespace [part](#)

The namespace with the variants of [Part](#).

Classes

- class [Capture](#)
Group capture behavior.
- struct [CharacterClassData](#)
A character class representation: a list of character ranges plus some additional properties.
- class [CharacterRange](#)
A non-empty character range, possibly containing only one character.
- struct [InvalidCharacterRange](#)
- class [Part](#)
A part of a regular expression and its AST node type.
- struct [SpannedCharacterRange](#)
A [CharacterRange](#) with its span.
- class [SpannedPart](#)
A version of [Part](#) including the span information (position in the input) of the root AST node (child nodes always contain it because they are represented as [SpannedParts](#) themselves).

Enumerations

- enum class [NamedCaptureFlavor](#) { [Apostrophes](#) , [Angles](#) , [AnglesWithP](#) }
- The flavor (dialect) of a named group capture.*

Functions

- `std::ostream & operator<< (std::ostream &out, const Capture &capture)`
- `void to_json (nlohmann::json &j, const Capture &capture)`
- `std::ostream & operator<< (std::ostream &out, const CharacterRange &range)`
- `void to_json (nlohmann::json &j, const CharacterRange &range)`
- `std::ostream & operator<< (std::ostream &out, NamedCaptureFlavor flavor)`
- `void to_json (nlohmann::json &j, NamedCaptureFlavor flavor)`
- `std::ostream & operator<< (std::ostream &out, const SpannedPart &part)`
Convert a [SpannedPart](#) to a textual representation and write it to an `std::ostream`.
- `void to_json (nlohmann::json &j, const Part &part)`
- `void to_json (nlohmann::json &j, const SpannedPart &part)`
- `std::ostream & operator<< (std::ostream &out, const SpannedCharacterRange &range)`
- `void to_json (nlohmann::json &j, const SpannedCharacterRange &range)`

5.5.1 Enumeration Type Documentation

5.5.1.1 NamedCaptureFlavor

```
enum class wr22::regex_parser::regex::NamedCaptureFlavor [strong]
```

The flavor (dialect) of a named group capture.

The most common variants are included. This list is subject to extension if deemed necessary. The source used as a reference is <https://www.regular-expressions.info/named.html>.

Enumerator

Apostrophes	The flavor (? 'name' contents) . Mostly used in C# and other .NET-oriented languages, although can also be found in certain versions Perl, Boost and elsewhere.
Angles	The flavor (<name>contents) . Mostly used in C# and other .NET-oriented languages, although can also be found in certain versions Perl, Boost and elsewhere.
AnglesWithP	The flavor (?P<name>contents) . Found in Python, PCRE and elsewhere.

5.5.2 Function Documentation

5.5.2.1 operator<<() [1/5]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    const Capture & capture )
```

5.5.2.2 operator<<() [2/5]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    const CharacterRange & range )
```

5.5.2.3 operator<<() [3/5]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    const SpannedCharacterRange & range )
```

5.5.2.4 operator<<() [4/5]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    const SpannedPart & spanned_part )
```

Convert a [SpannedPart](#) to a textual representation and write it to an `std::ostream`.

5.5.2.5 operator<<() [5/5]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    NamedCaptureFlavor flavor )
```

5.5.2.6 to_json() [1/6]

```
void wr22::regex_parser::regex::to_json (
    nlohmann::json & j,
    const Capture & capture )
```

5.5.2.7 to_json() [2/6]

```
void wr22::regex_parser::regex::to_json (
    nlohmann::json & j,
    const CharacterRange & range )
```

5.5.2.8 to_json() [3/6]

```
void wr22::regex_parser::regex::to_json (
    nlohmann::json & j,
    const Part & part )
```

5.5.2.9 to_json() [4/6]

```
void wr22::regex_parser::regex::to_json (
    nlohmann::json & j,
    const SpannedCharacterRange & range )
```

5.5.2.10 to_json() [5/6]

```
void wr22::regex_parser::regex::to_json (
    nlohmann::json & j,
    const SpannedPart & part )
```


5.5.2.11 to_json() [6/6]

```
void wr22::regex_parser::regex::to_json (
    nlohmann::json & j,
    NamedCaptureFlavor flavor )
```

5.6 wr22::regex_parser::regex::capture Namespace Reference

Classes

- struct [Index](#)
Denotes a group captured by index.
- struct [Name](#)
Denotes a group captured by name.
- struct [None](#)
Denotes an non-capturing group.

Typedefs

- using [Adt](#) = utils::Adt< [None](#), [Index](#), [Name](#) >

Functions

- void [to_json](#) (nlohmann::json &j, const [None](#) &capture)
- void [to_json](#) (nlohmann::json &j, const [Index](#) &capture)
- void [to_json](#) (nlohmann::json &j, const [Name](#) &capture)

5.6.1 Typedef Documentation

5.6.1.1 Adt

```
using wr22::regex_parser::regex::capture::Adt = typedef utils::Adt<None, Index, Name>
```

5.6.2 Function Documentation

5.6.2.1 to_json() [1/3]

```
void wr22::regex_parser::regex::capture::to_json (
    nlohmann::json & j,
    const Index & capture )
```

5.6.2.2 to_json() [2/3]

```
void wr22::regex_parser::regex::capture::to_json (
    nlohmann::json & j,
    const Name & capture )
```

5.6.2.3 to_json() [3/3]

```
void wr22::regex_parser::regex::capture::to_json (
    nlohmann::json & j,
    const None & capture )
```

5.7 wr22::regex_parser::regex::part Namespace Reference

The namespace with the variants of [Part](#).

Classes

- struct [Alternatives](#)
A regex part with the list of alternatives to be matched.
- struct [CharacterClass](#)
A regex part specifying a character class (e.g. `[a-z_]`).
- struct [Empty](#)
An empty regex part.
- struct [Group](#)
A regex part that represents a group in parentheses.
- struct [Literal](#)
A regex part that matches a single character literally.
- struct [Optional](#)
A regex part specifying an optional quantifier `((expression)?)`.
- struct [Plus](#)
A regex part specifying an "at least one" quantifier `((expression)+)`.
- struct [Sequence](#)
A regex part with the list of items to be matched one after another.
- struct [Star](#)
A regex part specifying an "at least zero" quantifier `((expression)*)`.
- struct [Wildcard](#)
A regex part specifying any single character `(.)`.

Typedefs

- using [Adt](#) = `utils::Adt< Empty, Literal, Alternatives, Sequence, Group, Optional, Plus, Star, Wildcard, CharacterClass >`

Functions

- void [to_json](#) (nlohmann::json &j, const [part::Empty](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Literal](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Alternatives](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Sequence](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Group](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Optional](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Plus](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Star](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::Wildcard](#) &part)
- void [to_json](#) (nlohmann::json &j, const [part::CharacterClass](#) &part)

5.7.1 Detailed Description

The namespace with the variants of [Part](#).

See the docs for the [Part](#) type for additional information.

5.7.2 Typedef Documentation

5.7.2.1 Adt

```
using wr22::regex_parser::regex::part::Adt = typedef utils:: Adt<Empty, Literal, Alternatives,  
Sequence, Group, Optional, Plus, Star, Wildcard, CharacterClass>
```

5.7.3 Function Documentation

5.7.3.1 to_json() [1/10]

```
void wr22::regex_parser::regex::part::to_json (  
    nlohmann::json & j,  
    const part::Alternatives & part )
```

5.7.3.2 to_json() [2/10]

```
void wr22::regex_parser::regex::part::to_json (  
    nlohmann::json & j,  
    const part::CharacterClass & part )
```

5.7.3.3 to_json() [3/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Empty & part )
```

5.7.3.4 to_json() [4/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Group & part )
```

5.7.3.5 to_json() [5/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Literal & part )
```

5.7.3.6 to_json() [6/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Optional & part )
```

5.7.3.7 to_json() [7/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Plus & part )
```

5.7.3.8 to_json() [8/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Sequence & part )
```

5.7.3.9 to_json() [9/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Star & part )
```

5.7.3.10 to_json() [10/10]

```
void wr22::regex_parser::regex::part::to_json (
    nlohmann::json & j,
    const part::Wildcard & part )
```

5.8 wr22::regex_parser::span Namespace Reference

Classes

- struct [InvalidSpan](#)
The exception thrown on an attempt to construct an invalid span.
- class [Span](#)
Character position range in the input string.

Functions

- std::ostream & [operator<<](#) (std::ostream &out, [Span](#) span)
- void [to_json](#) (nlohmann::json &j, [Span](#) span)

5.8.1 Function Documentation

5.8.1.1 operator<<()

```
std::ostream & wr22::regex_parser::span::operator<< (
    std::ostream & out,
    Span span )
```

5.8.1.2 to_json()

```
void wr22::regex_parser::span::to_json (
    nlohmann::json & j,
    Span span )
```


Chapter 6

Class Documentation

6.1 `wr22::regex_parser::regex::part::Alternatives` Struct Reference

A regex part with the list of alternatives to be matched.

```
#include <part.hpp>
```

Public Member Functions

- `Alternatives` (`std::vector< SpannedPart > alternatives`)
- `bool operator==` (`const Alternatives &rhs`) `const` =default

Public Attributes

- `std::vector< SpannedPart > alternatives`
The list of the alternatives.

Static Public Attributes

- `static constexpr const char * code_name = "alternatives"`

6.1.1 Detailed Description

A regex part with the list of alternatives to be matched.

`Alternatives` in regular expressions are subexpressions by `|`. For the whole expression part's match to succeed, at least one of the subexpressions must match the input successfully.

As an example, `a| (b) |cde` would be represented as an `Alternatives` part with 3 alternatives. The alternatives themselves are represented recursively as `SpannedParts`.

6.1.2 Constructor & Destructor Documentation

6.1.2.1 Alternatives()

```
wr22::regex_parser::regex::part::Alternatives::Alternatives (
    std::vector< SpannedPart > alternatives ) [explicit]
```

6.1.3 Member Function Documentation

6.1.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Alternatives::operator== (
    const Alternatives & rhs ) const [default]
```

6.1.4 Member Data Documentation

6.1.4.1 alternatives

```
std::vector<SpannedPart> wr22::regex_parser::regex::part::Alternatives::alternatives
```

The list of the alternatives.

6.1.4.2 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Alternatives::code_name = "alternatives"
[static], [constexpr]
```

The documentation for this struct was generated from the following files:


- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.2 wr22::regex_parser::regex::Capture Class Reference

Group capture behavior.

```
#include <capture.hpp>
```

Inheritance diagram for wr22::regex_parser::regex::Capture:



6.2.1 Detailed Description

Group capture behavior.

A group can be captured by index (when one writes `(contents)`), by name (e.g. `(?<name>contents)` in some dialects) or not captured at all (`(?:contents)`). Objects of this type determine how exactly a certain group is going to be captured. This is a variant type (see [Part](#) and `utils::Adt` for a more detailed explanation of the concept). The variants for this class (explicitly or implicitly convertible to this type) are located in the `capture` namespace.

The documentation for this class was generated from the following file:

- `include/wr22/regex_parser/regex/capture.hpp`

6.3 wr22::regex_parser::regex::part::CharacterClass Struct Reference

A regex part specifying a character class (e.g. `[a-z_]`).

```
#include <part.hpp>
```

Public Member Functions

- [CharacterClass](#) ([CharacterClassData](#) data)
- `bool operator== (const CharacterClass &rhs) const` =default

Public Attributes

- [CharacterClassData](#) data
The list of character ranges.

Static Public Attributes

- `static constexpr const char * code_name = "character_class"`

6.3.1 Detailed Description

A regex part specifying a character class (e.g. `[a-z_]`).

6.3.2 Constructor & Destructor Documentation

6.3.2.1 CharacterClass()

```
wr22::regex_parser::regex::part::CharacterClass::CharacterClass (
    CharacterClassData data ) [explicit]
```

6.3.3 Member Function Documentation

6.3.3.1 operator==()

```
bool wr22::regex_parser::regex::part::CharacterClass::operator== (
    const CharacterClass & rhs ) const [default]
```

6.3.4 Member Data Documentation

6.3.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::part::CharacterClass::code_name = "character↵
_class" [static], [constexpr]
```

6.3.4.2 data

```
CharacterClassData wr22::regex_parser::regex::part::CharacterClass::data
```

The list of character ranges.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.4 wr22::regex_parser::regex::CharacterClassData Struct Reference

A character class representation: a list of character ranges plus some additional properties.

```
#include <character_class_data.hpp>
```

Public Member Functions

- bool `operator==` (const [CharacterClassData](#) &rhs) const =default

Public Attributes

- std::vector< [SpannedCharacterRange](#) > `ranges`
List of character ranges and their spans.
- bool `inverted`
True if the match is inverted (i.e. `[^something]`), false otherwise.

6.4.1 Detailed Description

A character class representation: a list of character ranges plus some additional properties.

6.4.2 Member Function Documentation

6.4.2.1 `operator==()`

```
bool wr22::regex_parser::regex::CharacterClassData::operator== (
    const CharacterClassData & rhs ) const [default]
```

6.4.3 Member Data Documentation

6.4.3.1 `inverted`

```
bool wr22::regex_parser::regex::CharacterClassData::inverted
```

True if the match is inverted (i.e. `[^something]`), false otherwise.

6.4.3.2 ranges

```
std::vector<SpannedCharacterRange> wr22::regex_parser::regex::CharacterClassData::ranges
```

List of character ranges and their spans.

Example: for `[a-z123]` it is `['a'..'z' [1..4], '1'..'1' [4..4], '2'..'2' [5..5], '3'..'3' [6..6]]` (both ends in character ranges are included; `[A..B]` are spans with the left end included and the right one excluded).

The documentation for this struct was generated from the following file:

- `include/wr22/regex_parser/regex/character_class_data.hpp`

6.5 wr22::regex_parser::regex::CharacterRange Class Reference

A non-empty character range, possibly containing only one character.

```
#include <character_range.hpp>
```

Public Member Functions

- `char32_t first ()` const noexcept
Get the left range bound (inclusive).
- `char32_t last ()` const noexcept
Get the right range bound (inclusive).
- `bool contains (char32_t character)` const noexcept
Check if this range contains a given character.
- `bool is_single_character ()` const noexcept
Check if this range contains exactly one character.
- `bool operator== (const CharacterRange &rhs)` const noexcept=default

Static Public Member Functions

- static `CharacterRange from_endpoints (char32_t first, char32_t last)`
Construct a character range given its two inclusive endpoints.
- static `CharacterRange from_single_character (char32_t character)` noexcept
Construct a character range containing one given character.

6.5.1 Detailed Description

A non-empty character range, possibly containing only one character.

6.5.2 Member Function Documentation

6.5.2.1 contains()

```
bool wr22::regex_parser::regex::CharacterRange::contains (
    char32_t character ) const [noexcept]
```

Check if this range contains a given character.

6.5.2.2 first()

```
char32_t wr22::regex_parser::regex::CharacterRange::first ( ) const [noexcept]
```

Get the left range bound (inclusive).

6.5.2.3 from_endpoints()

```
CharacterRange wr22::regex_parser::regex::CharacterRange::from_endpoints (
    char32_t first,
    char32_t last ) [static]
```

Construct a character range given its two inclusive endpoints.

Exceptions

<code>`InvalidCharacterRange`</code>	if <code>last < first</code> .
--------------------------------------	-----------------------------------

6.5.2.4 from_single_character()

```
CharacterRange wr22::regex_parser::regex::CharacterRange::from_single_character (
    char32_t character ) [static], [noexcept]
```

Construct a character range containing one given character.

6.5.2.5 is_single_character()

```
bool wr22::regex_parser::regex::CharacterRange::is_single_character ( ) const [noexcept]
```

Check if this range contains exactly one character.

6.5.2.6 last()

```
char32_t wr22::regex_parser::regex::CharacterRange::last ( ) const [noexcept]
```

Get the right range bound (inclusive).

6.5.2.7 operator==(

```
bool wr22::regex_parser::regex::CharacterRange::operator== (
    const CharacterRange & rhs ) const [default], [noexcept]
```

The documentation for this class was generated from the following files:

- include/wr22/regex_parser/regex/character_range.hpp
- src/regex/character_range.cpp

6.6 wr22::regex_parser::regex::part::Empty Struct Reference

An empty regex part.

```
#include <part.hpp>
```

Public Member Functions

- [Empty](#) ()=default
- bool [operator==](#) (const [Empty](#) &rhs) const =default

Static Public Attributes

- static constexpr const char * [code_name](#) = "empty"

6.6.1 Detailed Description

An empty regex part.

Corresponds to an empty regular expression ("") or the contents of an empty parenthesized group (" () ").

6.6.2 Constructor & Destructor Documentation

6.6.2.1 Empty()

```
wr22::regex_parser::regex::part::Empty::Empty ( ) [explicit], [default]
```

6.6.3 Member Function Documentation

6.6.3.1 operator==(

```
bool wr22::regex_parser::regex::part::Empty::operator== (
    const Empty & rhs ) const [default]
```

6.6.4 Member Data Documentation

6.6.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Empty::code_name = "empty" [static],
[constexpr]
```

The documentation for this struct was generated from the following file:


- include/wr22/regex_parser/regex/part.hpp

6.7 wr22::regex_parser::parser::errors::ExpectedEnd Class Reference

The error when the parser expected the input to end, but it did not.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::ExpectedEnd:



Public Member Functions

- [ExpectedEnd](#) (size_t [position](#), char32_t [char_got](#))
Constructor.
- size_t [position](#) () const
Get the input position. See the constructor docs for a more detailed description.
- char32_t [char_got](#) () const
Get the character the parser has received.

6.7.1 Detailed Description

The error when the parser expected the input to end, but it did not.

6.7.2 Constructor & Destructor Documentation

6.7.2.1 ExpectedEnd()

```
wr22::regex_parser::parser::errors::ExpectedEnd::ExpectedEnd (
    size_t position,
    char32_t char_got )
```

Constructor.

Parameters

<i>position</i>	the 0-based position in the input when the parser has encountered the end of input.
<i>char_got</i>	the character that the parser has received instead of the end of input.

6.7.3 Member Function Documentation

6.7.3.1 char_got()

```
char32_t wr22::regex_parser::parser::errors::ExpectedEnd::char_got ( ) const
```

Get the character the parser has received.

See the constructor docs for a more detailed description.

6.7.3.2 position()

```
size_t wr22::regex_parser::parser::errors::ExpectedEnd::position ( ) const
```

Get the input position. See the constructor docs for a more detailed description.

The documentation for this class was generated from the following files:

- include/wr22/regex_parser/parser/errors.hpp
- src/parser/errors.cpp

6.8 wr22::regex_parser::regex::part::Group Struct Reference

A regex part that represents a group in parentheses.

```
#include <part.hpp>
```

Public Member Functions

- [Group](#) ([Capture capture](#), [SpannedPart inner](#))
Convenience constructor.
- bool [operator==](#) (const [Group](#) &rhs) const =default

Public Attributes

- [Capture capture](#)
[Capture](#) behavior.
- [utils::Box](#)< [SpannedPart](#) > [inner](#)
The smart pointer to the group contents.

Static Public Attributes

- static constexpr const char * [code_name](#) = "group"

6.8.1 Detailed Description

A regex part that represents a group in parentheses.

A group in regular expressions is virtually everything that is enclosed with parentheses: (some group), (?↵:blablabla) and (?P<group_name>group contents) are all groups.

A group has two main attributes: (1) how it is captured during matching and (2) the contents of the group. The contents is simply another [SpannedPart](#). The capture behavior is expressed by a separate type [Capture](#). See its docs for additional info, and take a look at <https://www.regular-expressions.info/brackets.↵html> for an introduction to or a recap of regex groups and capturing.

6.8.2 Constructor & Destructor Documentation

6.8.2.1 Group()

```
wr22::regex_parser::regex::part::Group::Group (
    Capture capture,
    SpannedPart inner ) [explicit]
```

Convenience constructor.

6.8.3 Member Function Documentation

6.8.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Group::operator== (
    const Group & rhs ) const [default]
```

6.8.4 Member Data Documentation

6.8.4.1 capture

Capture wr22::regex_parser::regex::part::Group::capture

Capture behavior.

6.8.4.2 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Group::code_name = "group" [static],
[constexpr]
```

6.8.4.3 inner

```
utils::Box<SpannedPart> wr22::regex_parser::regex::part::Group::inner
```

The smart pointer to the group contents.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.9 wr22::regex_parser::regex::capture::Index Struct Reference

Denotes a group captured by index.

```
#include <capture.hpp>
```

Public Member Functions

- [Index](#) ()=default
- bool [operator==](#) (const [Index](#) &rhs) const =default

Static Public Attributes

- static constexpr const char * [code_name](#) = "index"

6.9.1 Detailed Description

Denotes a group captured by index.

6.9.2 Constructor & Destructor Documentation

6.9.2.1 Index()

```
wr22::regex_parser::regex::capture::Index::Index ( ) [explicit], [default]
```

6.9.3 Member Function Documentation

6.9.3.1 operator==()

```
bool wr22::regex_parser::regex::capture::Index::operator==(
    const Index & rhs ) const [default]
```

6.9.4 Member Data Documentation

6.9.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::capture::Index::code_name = "index" [static],
[constexpr]
```


The documentation for this struct was generated from the following file:

- include/wr22/regex_parser/regex/capture.hpp

6.10 wr22::regex_parser::regex::InvalidCharacterRange Struct Reference

```
#include <character_range.hpp>
```

Inheritance diagram for wr22::regex_parser::regex::InvalidCharacterRange:



Public Member Functions

- [InvalidCharacterRange](#) (char32_t first, char32_t last)

Public Attributes

- char32_t first
- char32_t last

6.10.1 Constructor & Destructor Documentation

6.10.1.1 InvalidCharacterRange()

```
wr22::regex_parser::regex::InvalidCharacterRange::InvalidCharacterRange (
    char32_t first,
    char32_t last ) [explicit]
```

6.10.2 Member Data Documentation

6.10.2.1 first

```
char32_t wr22::regex_parser::regex::InvalidCharacterRange::first
```

6.10.2.2 last

```
char32_t wr22::regex_parser::regex::InvalidCharacterRange::last
```

The documentation for this struct was generated from the following files:


- include/wr22/regex_parser/regex/[character_range.hpp](#)
- src/regex/[character_range.cpp](#)

6.11 wr22::regex_parser::parser::errors::InvalidRange Class Reference

The error indicating that a character range in a character class is invalid.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::InvalidRange:



Public Member Functions

- `InvalidRange` (`span::Span span`, `char32_t first`, `char32_t last`)
Constructor.
- `span::Span span` () const
Get the span of the character range. See the constructor docs for a more detailed explanation.
- `char32_t first` () const
Get the first character in the character range.
- `char32_t last` () const
Get the last character in the character range.

6.11.1 Detailed Description

The error indicating that a character range in a character class is invalid.

6.11.2 Constructor & Destructor Documentation

6.11.2.1 InvalidRange()

```
wr22::regex_parser::parser::errors::InvalidRange::InvalidRange (
    span::Span span,
    char32_t first,
    char32_t last )
```

Constructor.

Parameters

<i>span</i>	the span of the character range considered.
<i>first</i>	the first character in (left bound of) the range, as in the regex.
<i>last</i>	the last character in (right bound of) the range, as in the regex.

6.11.3 Member Function Documentation

6.11.3.1 first()

```
char32_t wr22::regex_parser::parser::errors::InvalidRange::first ( ) const
```

Get the first character in the character range.

See the constructor docs for a more detailed explanation.

6.11.3.2 last()

```
char32_t wr22::regex_parser::parser::errors::InvalidRange::last ( ) const
```

Get the last character in the character range.

See the constructor docs for a more detailed explanation.

6.11.3.3 span()

```
span::Span wr22::regex_parser::parser::errors::InvalidRange::span ( ) const
```

Get the span of the character range. See the constructor docs for a more detailed explanation.

The documentation for this class was generated from the following files:


- include/wr22/regex_parser/parser/errors.hpp
- src/parser/errors.cpp

6.12 wr22::regex_parser::span::InvalidSpan Struct Reference

The exception thrown on an attempt to construct an invalid span.

```
#include <span.hpp>
```

Inheritance diagram for wr22::regex_parser::span::InvalidSpan:



Public Member Functions

- [InvalidSpan](#) (size_t [begin](#), size_t [end](#))

Public Attributes

- size_t [begin](#)
- size_t [end](#)

6.12.1 Detailed Description

The exception thrown on an attempt to construct an invalid span.

See the documentation for [Span](#) for additional information.

6.12.2 Constructor & Destructor Documentation

6.12.2.1 InvalidSpan()

```
wr22::regex_parser::span::InvalidSpan::InvalidSpan (
    size_t begin,
    size_t end )
```

6.12.3 Member Data Documentation

6.12.3.1 begin

```
size_t wr22::regex_parser::span::InvalidSpan::begin
```

6.12.3.2 end

```
size_t wr22::regex_parser::span::InvalidSpan::end
```

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/span/[span.hpp](#)
- src/span/[span.cpp](#)

6.13 wr22::regex_parser::regex::part::Literal Struct Reference

An regex part that matches a single character literally.

```
#include <part.hpp>
```

Public Member Functions

- [Literal](#) (char32_t [character](#))
- bool [operator==](#) (const [Literal](#) &rhs) const =default

Public Attributes

- char32_t [character](#)

Static Public Attributes

- static constexpr const char * `code_name` = "literal"

6.13.1 Detailed Description

An regex part that matches a single character literally.

Corresponds to a plain character in a regular expression. E.g. the regex "foo" contains three character literals: f, o and o.

6.13.2 Constructor & Destructor Documentation

6.13.2.1 Literal()

```
wr22::regex_parser::regex::part::Literal::Literal (  
    char32_t character ) [explicit]
```

6.13.3 Member Function Documentation

6.13.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Literal::operator== (  
    const Literal & rhs ) const [default]
```

6.13.4 Member Data Documentation

6.13.4.1 character

```
char32_t wr22::regex_parser::regex::part::Literal::character
```

6.13.4.2 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Literal::code_name = "literal" [static],
[constexpr]
```

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.14 wr22::regex_parser::regex::capture::Name Struct Reference

Denotes a group captured by name.

```
#include <capture.hpp>
```

Public Member Functions

- [Name](#) (std::string [name](#), [NamedCaptureFlavor](#) [flavor](#))
- bool [operator==](#) (const [Name](#) &rhs) const =default

Public Attributes

- std::string [name](#)
- [NamedCaptureFlavor](#) [flavor](#)

Static Public Attributes

- static constexpr const char * [code_name](#) = "name"

6.14.1 Detailed Description

Denotes a group captured by name.

A specific name and the syntax variant for this name's specification (see [NamedCaptureFlavor](#)) are stored.

6.14.2 Constructor & Destructor Documentation

6.14.2.1 Name()

```
wr22::regex_parser::regex::capture::Name::Name (
    std::string name,
    NamedCaptureFlavor flavor ) [explicit]
```

6.14.3 Member Function Documentation

6.14.3.1 operator==(

```
bool wr22::regex_parser::regex::capture::Name::operator== (
    const Name & rhs ) const [default]
```

6.14.4 Member Data Documentation

6.14.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::capture::Name::code_name = "name" [static],
[constexpr]
```

6.14.4.2 flavor

```
NamedCaptureFlavor wr22::regex_parser::regex::capture::Name::flavor
```

6.14.4.3 name

```
std::string wr22::regex_parser::regex::capture::Name::name
```

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/[capture.hpp](#)
- src/parser/[capture.cpp](#)

6.15 wr22::regex_parser::regex::capture::None Struct Reference

Denotes an non-capturing group.

```
#include <capture.hpp>
```

Public Member Functions

- [None](#) ()=default
- bool [operator==](#) (const [None](#) &rhs) const =default

Static Public Attributes

- static constexpr const char * `code_name` = "none"

6.15.1 Detailed Description

Denotes an non-capturing group.

6.15.2 Constructor & Destructor Documentation

6.15.2.1 None()

```
wr22::regex_parser::regex::capture::None::None ( ) [explicit], [default]
```

6.15.3 Member Function Documentation

6.15.3.1 operator==()

```
bool wr22::regex_parser::regex::capture::None::operator== (
    const None & rhs ) const [default]
```

6.15.4 Member Data Documentation

6.15.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::capture::None::code_name = "none" [static],
[constexpr]
```

The documentation for this struct was generated from the following file:

- include/wr22/regex_parser/regex/capture.hpp

6.16 wr22::regex_parser::regex::part::Optional Struct Reference

A regex part specifying an optional quantifier (`(expression) ?`).

```
#include <part.hpp>
```

Public Member Functions

- [Optional](#) ([SpannedPart](#) *inner*)
Convenience constructor.
- bool [operator==](#) (const [Optional](#) &*rhs*) const =default

Public Attributes

- `utils::Box< SpannedPart > inner`
The smart pointer to the subexpression under the quantifier.

Static Public Attributes

- static constexpr const char * [code_name](#) = "optional"

6.16.1 Detailed Description

A regex part specifying an optional quantifier ([expression](#) ?).

6.16.2 Constructor & Destructor Documentation

6.16.2.1 Optional()

```
wr22::regex_parser::regex::part::Optional::Optional (
    SpannedPart inner ) [explicit]
```

Convenience constructor.

6.16.3 Member Function Documentation

6.16.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Optional::operator== (
    const Optional & rhs ) const [default]
```

6.16.4 Member Data Documentation

6.16.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Optional::code_name = "optional" [static],
[constexpr]
```

6.16.4.2 inner

```
utils::Box<SpannedPart> wr22::regex_parser::regex::part::Optional::inner
```

The smart pointer to the subexpression under the quantifier.

The documentation for this struct was generated from the following files:


- [include/wr22/regex_parser/regex/part.hpp](#)
- [src/regex/part.cpp](#)

6.17 wr22::regex_parser::parser::errors::ParseError Struct Reference

The base class for parse errors.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::ParseError:



6.17.1 Detailed Description

The base class for parse errors.

This exception type should be caught if it is desired to catch all parse errors. However, there are more specific exceptions deriving from this one that can be handled separately for greater flexibility.

The documentation for this struct was generated from the following file:

- [include/wr22/regex_parser/parser/errors.hpp](#)

6.18 wr22::regex_parser::parser::Parser< Iter, Sentinel > Class Template Reference

A regex parser.

Public Member Functions

- [Parser](#) (Iter begin, Sentinel end)
Constructor.
- void [expect_end](#) ()
Ensure that the parser has consumed all of the input.
- [regex::SpannedPart](#) [parse_regex](#) ()
Parse a regex consuming part of the remaining input.
- [regex::SpannedPart](#) [parse_alternatives](#) ()
Intermediate rule: parse a pipe-separated list of alternatives (e.g.
- [regex::SpannedPart](#) [parse_sequence](#) ()
Intermediate rule: parse a sequence of atoms (e.g.
- [regex::SpannedPart](#) [parse_sequence_or_empty](#) ()
Intermediate rule: parse a possibly empty sequence of atoms.
- [regex::SpannedPart](#) [parse_atom](#) ()
Intermediate rule: parse an atom.
- [regex::SpannedPart](#) [parse_wildcard](#) ()
Intermediate rule: parse a wildcard (.
- [regex::SpannedPart](#) [parse_char_literal](#) ()
Intermediate rule: parse a character literal.
- [regex::SpannedPart](#) [parse_group](#) ()
Intermediate rule: parse a parenthesized group (any capture variant).
- std::pair< std::string, [Span](#) > [parse_group_name](#) ()
Intermediate rule: parse a group name.
- [regex::SpannedPart](#) [parse_char_class](#) ()
Intermediate rule: parse a character class (e.g.

6.18.1 Detailed Description

```
template<typename Iter, typename Sentinel>
requires requires (Iter iter, Sentinel end) { ++iter; { *iter } -> std::convertible_to<char32_t>; { iter == end } -> std::convertible_to<bool>; { iter != end } -> std::convertible_to<bool>; }
class wr22::regex_parser::parser::Parser< Iter, Sentinel >
```

A regex parser.

For additional information see the methods' docs, particularly the constructor and the `parse_regex` method.

6.18.2 Constructor & Destructor Documentation

6.18.2.1 Parser()

```
template<typename Iter , typename Sentinel >
wr22::regex_parser::parser::Parser< Iter, Sentinel >::Parser (
    Iter begin,
    Sentinel end ) [inline]
```

Constructor.

This constructor stores a pair of forward iterators that should generate a sequence of Unicode code points (`char32_t`). The `begin` iterator and the `end` sentinel may have different types provided that the iterator can be equality comparable with the sentinel.

SAFETY: The iterators must not be invalidated as long as this [Parser](#) object is still alive.

6.18.3 Member Function Documentation

6.18.3.1 expect_end()

```
template<typename Iter , typename Sentinel >
void wr22::regex_parser::parser::Parser< Iter, Sentinel >::expect_end ( ) [inline]
```

Ensure that the parser has consumed all of the input.

Does nothing if all input has been consumed.

Exceptions

<code>errors::ExpectedEnd</code>	if this is not the case.
----------------------------------	--------------------------

6.18.3.2 parse_alternatives()

```
template<typename Iter , typename Sentinel >
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_alternatives (
) [inline]
```

Intermediate rule: parse a pipe-separated list of alternatives (e.g.

`a|bb|ccc`).

Returns

the list of parsed alternatives packed into `regex::part::Alternatives` or, if and only if the list of alternatives contains exactly 1 element, the only alternative unchanged.

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.18.3.3 parse_atom()

```
template<typename Iter , typename Sentinel >
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_atom ( ) [inline]
```

Intermediate rule: parse an atom.

Currently, this grammar only recognizes two kinds of atoms: character literals (individual plain characters in a regex) and parenthesized groups. As the project development goes on, new kinds of atoms will be added.

Returns

the parsed atom (some variant of `regex::SpannedPart` depending on the atom kind).

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.18.3.4 parse_char_class()

```
template<typename Iter , typename Sentinel >
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_char_class ( )
[inline]
```

Intermediate rule: parse a character class (e.g.

`[^a-z0-9_-]`).

Returns

the character class AST node.

– is found right after the character range started or right after another range. In either case, it is considered as a plain character.

6.18.3.5 parse_char_literal()

```
template<typename Iter , typename Sentinel >
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_char_literal (
) [inline]
```

Intermediate rule: parse a character literal.

Returns

the parsed character literal (`regex::part::Literal`).

Exceptions

<code>errors::UnexpectedEnd</code>	if all characters from the input have already been consumed.
------------------------------------	--

6.18.3.6 parse_group()

```
template<typename Iter , typename Sentinel >
```

```
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_group ( )
[inline]
```

Intermediate rule: parse a parenthesized group (any capture variant).

Returns

the parsed group ([regex::part::Group](#)).

6.18.3.7 parse_group_name()

```
template<typename Iter , typename Sentinel >
std::pair< std::string, Span > wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_group_name ( ) [inline]
```

Intermediate rule: parse a group name.

Returns

the UTF-8 encoded group name as an `std::string`.

6.18.3.8 parse_regex()

```
template<typename Iter , typename Sentinel >
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_regex ( )
[inline]
```

Parse a regex consuming part of the remaining input.

This is **the** method that should be called to parse a regular expression because it represents the root rule of the regex grammar. Please note that this method may not consume all of the parser's input. Hence, if a whole regex is to be parsed, the `expect_end` method should be called afterwards.

Returns

the parsed regex AST (some variant of [regex::SpannedPart](#) depending on the input).

Exceptions

errors::ParseError	if the input cannot be parsed.
------------------------------------	--------------------------------

6.18.3.9 parse_sequence()

```
template<typename Iter , typename Sentinel >
```

```
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_sequence ( )
[inline]
```

Intermediate rule: parse a sequence of atoms (e.g.

a(?:b)[c-e]).

Returns

the list of parsed atoms packed into `regex::part::Sequence` or, if and only if this list of contains exactly 1 element, the only atom unchanged.

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.18.3.10 parse_sequence_or_empty()

```
template<typename Iter , typename Sentinel >
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_sequence_or_↵
empty ( ) [inline]
```

Intermediate rule: parse a possibly empty sequence of atoms.

Returns

`regex::part::Empty` if the sequence is empty, or calls `parse_sequence` otherwise.

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.18.3.11 parse_wildcard()

```
template<typename Iter , typename Sentinel >
regex::SpannedPart wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_wildcard ( )
[inline]
```

Intermediate rule: parse a wildcard (.

).

Returns

the wildcard AST node.

Exceptions

<code>errors::UnexpectedEnd</code>	if all characters from the input have already been consumed.
<code>errors::UnexpectedChar</code>	if the next input character is not . .

The documentation for this class was generated from the following file:


- [src/parser/regex.cpp](#)

6.19 wr22::regex_parser::regex::Part Class Reference

A part of a regular expression and its AST node type.

```
#include <part.hpp>
```

Inheritance diagram for wr22::regex_parser::regex::Part:



6.19.1 Detailed Description

A part of a regular expression and its AST node type.

The parsed regular expressions are represented as abstract syntax trees (ASTs). These are tree-like data structures where each node represents a regular expression part (or the whole regex), and, depending on their type, these nodes may have subexpressions. Subexpressions are [Parts](#) themselves, which also have child expressions and so on. For example, [`part::Sequence`](#) has a number of subexpressions, and each of them is of the type [Part](#) and is an AST node.

Each regex part has its own simple function. For example, [`part::Alternatives`](#) tries to match several alternative subexpressions against the input and succeeds if at least one of them does; and [`part::Sequence`](#) matches several subexpressions one after another, requiring them all to match respective parts of the input. By combining these simple nodes, it becomes possible to represent complex regular expressions. For example, the regex `aaa|bb` can be represented as a [`part::Alternatives`](#), where each of the alternatives is a [`part::Sequence`](#) of [`part::Literals`](#).

The [Part](#) itself is represented by `std::variant` via the helper class `utils::Adt`. In a nutshell, it allows a regex part to "have" one of the several predefined types (the so-called variants, which are defined in the `part` namespace), but still be represented as a [Part](#). For the list of operations that can be performed on this type, e.g. to check if an instance of [Parts](#) has a specific variant and, if yes, access the value of this variant, see the documentation for the `utils::Adt` class, which [Part](#) inherits from.

Note that this type contains no span information for the root AST node. For a spanned version, see [SpannedPart](#).

The documentation for this class was generated from the following file:

- [include/wr22/regex_parser/regex/part.hpp](#)

6.20 wr22::regex_parser::regex::part::Plus Struct Reference

A regex part specifying an "at least one" quantifier ((expression) +).

```
#include <part.hpp>
```

Public Member Functions

- [Plus](#) ([SpannedPart](#) inner)
Convenience constructor.
- bool [operator==](#) (const [Plus](#) &rhs) const =default

Public Attributes

- [utils::Box](#)< [SpannedPart](#) > inner
The smart pointer to the subexpression under the quantifier.

Static Public Attributes

- static constexpr const char * [code_name](#) = "plus"

6.20.1 Detailed Description

A regex part specifying an "at least one" quantifier ((expression) +).

6.20.2 Constructor & Destructor Documentation

6.20.2.1 Plus()

```
wr22::regex_parser::regex::part::Plus::Plus (
    SpannedPart inner ) [explicit]
```

Convenience constructor.

6.20.3 Member Function Documentation

6.20.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Plus::operator== (
    const Plus & rhs ) const [default]
```

6.20.4 Member Data Documentation

6.20.4.1 `code_name`

```
constexpr const char* wr22::regex_parser::regex::part::Plus::code_name = "plus" [static],
[constexpr]
```

6.20.4.2 `inner`

```
utils::Box<SpannedPart> wr22::regex_parser::regex::part::Plus::inner
```

The smart pointer to the subexpression under the quantifier.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/[part.hpp](#)
- src/regex/[part.cpp](#)

6.21 `wr22::regex_parser::regex::part::Sequence` Struct Reference

A regex part with the list of items to be matched one after another.

```
#include <part.hpp>
```

Public Member Functions

- [Sequence](#) (std::vector< [SpannedPart](#) > [items](#))
- bool [operator==](#) (const [Sequence](#) &rhs) const =default

Public Attributes

- std::vector< [SpannedPart](#) > [items](#)
The list of the subexpressions.

Static Public Attributes

- static constexpr const char * [code_name](#) = "sequence"

6.21.1 Detailed Description

A regex part with the list of items to be matched one after another.

Sequences in regular expressions are just subexpressions going directly one after another. As an example, `a[b-e]` is a sequence of 3 subexpressions: `a`, `[b-e]` and `.`. As an another example, `ab` is a sequence of 2 subexpressions: `a` and `b`.

6.21.2 Constructor & Destructor Documentation

6.21.2.1 Sequence()

```
wr22::regex_parser::regex::part::Sequence::Sequence (
    std::vector< SpannedPart > items ) [explicit]
```

6.21.3 Member Function Documentation

6.21.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Sequence::operator== (
    const Sequence & rhs ) const [default]
```

6.21.4 Member Data Documentation

6.21.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Sequence::code_name = "sequence" [static],
[constexpr]
```

6.21.4.2 items

```
std::vector<SpannedPart> wr22::regex_parser::regex::part::Sequence::items
```

The list of the subexpressions.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.22 wr22::regex_parser::span::Span Class Reference

Character position range in the input string.

```
#include <span.hpp>
```

Public Member Functions

- [Span extend_right](#) (size_t num_positions) const
Construct a new span that equals the current span extended to the right by a specified number of positions.
- size_t [length](#) () const
Get the length of the span (the number of characters covered).
- size_t [begin](#) () const
*Get the *begin* position of the span.*
- size_t [end](#) () const
*Get the *end* position of the span.*
- bool [operator==](#) (const [Span](#) &other) const =default
- bool [operator!=](#) (const [Span](#) &other) const =default

Static Public Member Functions

- static [Span make_empty](#) (size_t position)
Construct an empty span that "starts" at a given position.
- static [Span make_single_position](#) (size_t position)
Construct a span that captures only one position.
- static [Span make_from_positions](#) (size_t [begin](#), size_t [end](#))
*Construct a span with given values of *begin* and *end* without any transformations.*
- static [Span make_with_length](#) (size_t [begin](#), size_t [length](#))
*Construct a span with a given value of *begin* and a given length.*

6.22.1 Detailed Description

Character position range in the input string.

The range is encoded by two numbers: `begin`, the position (0-based index) of the first character in the range, and `end`, the past-the-end position, or the 0-based index of the last character in the range **plus 1**. This is to be consistent with the behavior of C++ iterators and `begin()/end()` functions on STL containers. Please note, however, that the `begin()/end()` methods here are just accessors that are not used for iteration, they return plain indices which have no iterator semantics.

Invalid spans (`begin > end`) are not allowed and their construction will result in an error. See the documentation for the relevant methods for details.

6.22.2 Member Function Documentation

6.22.2.1 begin()

```
size_t wr22::regex_parser::span::Span::begin ( ) const
```

Get the `begin` position of the span.

6.22.2.2 end()

```
size_t wr22::regex_parser::span::Span::end ( ) const
```

Get the `end` position of the span.

6.22.2.3 extend_right()

```
Span wr22::regex_parser::span::Span::extend_right (
    size_t num_positions ) const
```

Construct a new span that equals the current span extended to the right by a specified number of positions.

Please note that this method creates a new span and does not modify the existing one.

Formally, `[begin..end].extend_right(n) = [begin..(end+n)]`.

Exceptions

<code>InvalidSpan</code>	if <code>end + length</code> overflows <code>size_t</code> . Note that the error message might not be precise enough.
--------------------------	---

6.22.2.4 length()

```
size_t wr22::regex_parser::span::Span::length ( ) const
```

Get the length of the span (the number of characters covered).

6.22.2.5 make_empty()

```
Span wr22::regex_parser::span::Span::make_empty (
    size_t position ) [static]
```

Construct an empty span that "starts" at a given position.

The resulting span will have `begin = position` and `end = position`.

6.22.2.6 `make_from_positions()`

```
Span wr22::regex_parser::span::Span::make_from_positions (
    size_t begin,
    size_t end ) [static]
```

Construct a span with given values of `begin` and `end` without any transformations.

Exceptions

<i>InvalidSpan</i>	if <code>end < begin</code> .
--------------------	----------------------------------

6.22.2.7 `make_single_position()`

```
Span wr22::regex_parser::span::Span::make_single_position (
    size_t position ) [static]
```

Construct a span that captures only one position.

The resulting span will have `begin = position` and `end = position + 1`.

Exceptions

<i>InvalidSpan</i>	if <code>position + 1</code> overflows <code>size_t</code> . Note that the error message might not be precise enough.
--------------------	---

6.22.2.8 `make_with_length()`

```
Span wr22::regex_parser::span::Span::make_with_length (
    size_t begin,
    size_t length ) [static]
```

Construct a span with a given value of `begin` and a given `length`.

The length is determined by the number of characters covered by this span, and, since `begin` and `end` form a half-interval, it equals `end - begin`.

Exceptions

<i>InvalidSpan</i>	if <code>begin + length</code> overflows <code>size_t</code> . Note that the error message might not be precise enough.
--------------------	---

6.22.2.9 operator!=(())

```
bool wr22::regex_parser::span::Span::operator!= (
    const Span & other ) const [default]
```

6.22.2.10 operator==(())

```
bool wr22::regex_parser::span::Span::operator== (
    const Span & other ) const [default]
```

The documentation for this class was generated from the following files:

- include/wr22/regex_parser/span/[span.hpp](#)
- src/span/[span.cpp](#)

6.23 wr22::regex_parser::regex::SpannedCharacterRange Struct Reference

A [CharacterRange](#) with its span.

```
#include <spanned_character_range.hpp>
```

Public Member Functions

- bool [operator==](#) (const [SpannedCharacterRange](#) &rhs) const =default

Public Attributes

- [CharacterRange](#) range
- [span::Span](#) span

6.23.1 Detailed Description

A [CharacterRange](#) with its span.

6.23.2 Member Function Documentation

6.23.2.1 operator==(())

```
bool wr22::regex_parser::regex::SpannedCharacterRange::operator== (
    const SpannedCharacterRange & rhs ) const [default]
```

6.23.3 Member Data Documentation

6.23.3.1 range

`CharacterRange` `wr22::regex_parser::regex::SpannedCharacterRange::range`

6.23.3.2 span

`span::Span` `wr22::regex_parser::regex::SpannedCharacterRange::span`

The documentation for this struct was generated from the following file:

- `include/wr22/regex_parser/regex/spanned_character_range.hpp`

6.24 wr22::regex_parser::regex::SpannedPart Class Reference

A version of `Part` including the span information (position in the input) of the root AST node (child nodes always contain it because they are represented as `SpannedParts` themselves).

```
#include <part.hpp>
```

Public Member Functions

- `SpannedPart` (`Part` part, `span::Span` span)
- `bool operator==` (const `SpannedPart` &other) const =default
- `bool operator!=` (const `SpannedPart` &other) const =default
- `const Part & part` () const
Access the wrapped `Part` (const version).
- `Part & part` ()
Access the wrapped `Part` (non-const version).
- `span::Span` span () const
Get the associated span.

6.24.1 Detailed Description

A version of `Part` including the span information (position in the input) of the root AST node (child nodes always contain it because they are represented as `SpannedParts` themselves).

6.24.2 Constructor & Destructor Documentation

6.24.2.1 SpannedPart()

```
wr22::regex_parser::regex::SpannedPart::SpannedPart (
    Part part,
    span::Span span ) [explicit]
```

6.24.3 Member Function Documentation

6.24.3.1 operator!=(())

```
bool wr22::regex_parser::regex::SpannedPart::operator!= (
    const SpannedPart & other ) const [default]
```

6.24.3.2 operator==(())

```
bool wr22::regex_parser::regex::SpannedPart::operator== (
    const SpannedPart & other ) const [default]
```

6.24.3.3 part() [1/2]

```
Part & wr22::regex_parser::regex::SpannedPart::part ( )
```

Access the wrapped [Part](#) (non-const version).

6.24.3.4 part() [2/2]

```
const Part & wr22::regex_parser::regex::SpannedPart::part ( ) const
```

Access the wrapped [Part](#) (const version).

6.24.3.5 span()

```
span::Span wr22::regex_parser::regex::SpannedPart::span ( ) const
```

Get the associated span.

The documentation for this class was generated from the following files:

- include/wr22/regex_parser/regex/[part.hpp](#)
- src/regex/[part.cpp](#)

6.25 wr22::regex_parser::regex::part::Star Struct Reference

A regex part specifying an "at least zero" quantifier ((expression) *).

```
#include <part.hpp>
```

Public Member Functions

- [Star](#) ([SpannedPart](#) inner)
Convenience constructor.
- bool [operator==](#) (const [Star](#) &rhs) const =default

Public Attributes

- [utils::Box](#)< [SpannedPart](#) > inner
The smart pointer to the subexpression under the quantifier.

Static Public Attributes

- static constexpr const char * [code_name](#) = "star"

6.25.1 Detailed Description

A regex part specifying an "at least zero" quantifier ((expression) *).

6.25.2 Constructor & Destructor Documentation

6.25.2.1 Star()

```
wr22::regex_parser::regex::part::Star::Star (
    SpannedPart inner ) [explicit]
```

Convenience constructor.

6.25.3 Member Function Documentation

6.25.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Star::operator== (
    const Star & rhs ) const [default]
```

6.25.4 Member Data Documentation

6.25.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Star::code_name = "star" [static],
[constexpr]
```

6.25.4.2 inner

```
utils::Box<SpannedPart> wr22::regex_parser::regex::part::Star::inner
```

The smart pointer to the subexpression under the quantifier.

The documentation for this struct was generated from the following files:


- include/wr22/regex_parser/regex/[part.hpp](#)
- src/regex/[part.cpp](#)

6.26 wr22::regex_parser::parser::errors::UnexpectedChar Class Reference

The error when the parser got a character it didn't expect at the current position.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::UnexpectedChar:



Public Member Functions

- [UnexpectedChar](#) (size_t [position](#), char32_t [char_got](#), std::string [expected](#))
Constructor.
- size_t [position](#) () const
Get the input position. See the constructor docs for a more detailed description.
- char32_t [char_got](#) () const
Get the character the parser has received.
- const std::string & [expected](#) () const
Get the description of expected characters.

6.26.1 Detailed Description

The error when the parser got a character it didn't expect at the current position.

6.26.2 Constructor & Destructor Documentation

6.26.2.1 UnexpectedChar()

```
wr22::regex_parser::parser::errors::UnexpectedChar::UnexpectedChar (
    size_t position,
    char32_t char_got,
    std::string expected )
```

Constructor.

Parameters

<i>position</i>	the 0-based position in the input when the parser has encountered the unexpected character.
<i>char_got</i>	the character that the parser has received.
<i>expected</i>	a textual description of a class of characters expected instead.

6.26.3 Member Function Documentation

6.26.3.1 char_got()

```
char32_t wr22::regex_parser::parser::errors::UnexpectedChar::char_got ( ) const
```

Get the character the parser has received.

See the constructor docs for a more detailed description.

6.26.3.2 expected()

```
const std::string & wr22::regex_parser::parser::errors::UnexpectedChar::expected ( ) const
```

Get the description of expected characters.

See the constructor docs for a more detailed description.

6.26.3.3 position()

```
size_t wr22::regex_parser::parser::errors::UnexpectedChar::position ( ) const
```

Get the input position. See the constructor docs for a more detailed description.

The documentation for this class was generated from the following files:


- include/wr22/regex_parser/parser/errors.hpp
- src/parser/errors.cpp

6.27 wr22::regex_parser::parser::errors::UnexpectedEnd Class Reference

The error when the parser hit the end of the input earlier than it expected.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::UnexpectedEnd:



Public Member Functions

- **UnexpectedEnd** (size_t [position](#), std::string [expected](#), std::optional< char32_t > [needs_closing](#))
Constructor.
- size_t [position](#) () const
Get the input position. See the constructor docs for a more detailed description.
- const std::string & [expected](#) () const
Get the description of expected characters.
- std::optional< char32_t > [needs_closing](#) () const
Get the bracket that needs to be closed.

6.27.1 Detailed Description

The error when the parser hit the end of the input earlier than it expected.

6.27.2 Constructor & Destructor Documentation

6.27.2.1 UnexpectedEnd()

```
wr22::regex_parser::parser::errors::UnexpectedEnd::UnexpectedEnd (
    size_t position,
    std::string expected,
    std::optional< char32_t > needs_closing )
```

Constructor.

Parameters

<i>position</i>	the 0-based position in the input when the parser has encountered the end of input.
<i>expected</i>	a textual description of a class of characters expected instead.
<i>needs_closing</i>	a character describing the type of bracket that needs to be closed, if any.

6.27.3 Member Function Documentation

6.27.3.1 `expected()`

```
const std::string & wr22::regex_parser::parser::errors::UnexpectedEnd::expected ( ) const
```

Get the description of expected characters.

See the constructor docs for a more detailed description.

6.27.3.2 `needs_closing()`

```
std::optional< char32_t > wr22::regex_parser::parser::errors::UnexpectedEnd::needs_closing ( )  
const
```

Get the bracket that needs to be closed.

6.27.3.3 `position()`

```
size_t wr22::regex_parser::parser::errors::UnexpectedEnd::position ( ) const
```

Get the input position. See the constructor docs for a more detailed description.

The documentation for this class was generated from the following files:

- `include/wr22/regex_parser/parser/errors.hpp`
- `src/parser/errors.cpp`

6.28 `wr22::regex_parser::regex::part::Wildcard` Struct Reference

A regex part specifying any single character (`.`).

```
#include <part.hpp>
```

Public Member Functions

- [Wildcard](#) ()=default
- bool [operator==](#) (const [Wildcard](#) &rhs) const =default

Static Public Attributes

- static constexpr const char * [code_name](#) = "wildcard"

6.28.1 Detailed Description

A regex part specifying any single character (.).

6.28.2 Constructor & Destructor Documentation

6.28.2.1 Wildcard()

```
wr22::regex_parser::regex::part::Wildcard::Wildcard ( ) [explicit], [default]
```

6.28.3 Member Function Documentation

6.28.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Wildcard::operator== (
    const Wildcard & rhs ) const [default]
```

6.28.4 Member Data Documentation

6.28.4.1 code_name

```
constexpr const char* wr22::regex_parser::regex::part::Wildcard::code_name = "wildcard" [static],
[constexpr]
```

The documentation for this struct was generated from the following file:

- include/wr22/regex_parser/regex/[part.hpp](#)

Chapter 7

File Documentation

7.1 include/wr22/regex_parser/parser/errors.hpp File Reference

```
#include <wr22/regex_parser/span/span.hpp>
#include <exception>
#include <optional>
#include <stdexcept>
#include <string>
```

Classes

- struct [wr22::regex_parser::parser::errors::ParseError](#)
The base class for parse errors.
- class [wr22::regex_parser::parser::errors::UnexpectedEnd](#)
The error when the parser hit the end of the input earlier than it expected.
- class [wr22::regex_parser::parser::errors::ExpectedEnd](#)
The error when the parser expected the input to end, but it did not.
- class [wr22::regex_parser::parser::errors::UnexpectedChar](#)
The error when the parser got a character it didn't expect at the current position.
- class [wr22::regex_parser::parser::errors::InvalidRange](#)
The error indicating that a character range in a character class is invalid.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::parser](#)
- namespace [wr22::regex_parser::parser::errors](#)

7.2 errors.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // wr22
4 #include <wr22/regex_parser/span/span.hpp>
5
6 // STL
7 #include <exception>
8 #include <optional>
9 #include <stdexcept>
10 #include <string>
11
12 namespace wr22::regex_parser::parser::errors {
13
14     struct ParseError : public std::runtime_error {
15         using std::runtime_error::runtime_error;
16     };
17
18     class UnexpectedEnd : public ParseError {
19     public:
20         UnexpectedEnd(size_t position, std::string expected, std::optional<char32_t> needs_closing);
21
22         size_t position() const;
23         const std::string& expected() const;
24         std::optional<char32_t> needs_closing() const;
25
26     private:
27         size_t m_position;
28         std::string m_expected;
29         std::optional<char32_t> m_needs_closing;
30     };
31
32     class ExpectedEnd : public ParseError {
33     public:
34         ExpectedEnd(size_t position, char32_t char_got);
35
36         size_t position() const;
37         char32_t char_got() const;
38
39     private:
40         size_t m_position;
41         char32_t m_char_got;
42     };
43
44     class UnexpectedChar : public ParseError {
45     public:
46         UnexpectedChar(size_t position, char32_t char_got, std::string expected);
47
48         size_t position() const;
49         char32_t char_got() const;
50         const std::string& expected() const;
51
52     private:
53         size_t m_position;
54         char32_t m_char_got;
55         std::string m_expected;
56     };
57
58     class InvalidRange : public ParseError {
59     public:
60         InvalidRange(span::Span span, char32_t first, char32_t last);
61
62         span::Span span() const;
63         char32_t first() const;
64         char32_t last() const;
65
66     private:
67         span::Span m_span;
68         char32_t m_first;
69         char32_t m_last;
70     };
71 } // namespace wr22::regex_parser::parser::errors

```

7.3 include/wr22/regex_parser/parser/regex.hpp File Reference

```

#include <wr22/regex_parser/regex/part.hpp>
#include <string_view>

```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::parser](#)

Functions

- `regex::SpannedPart wr22::regex_parser::parser::parse_regex` (const std::u32string_view ®ex)
Parse a regular expression into its AST.

7.4 regex.hpp

[Go to the documentation of this file.](#)

```
1 #pragma once
2
3 // wr22
4 #include <wr22/regex_parser/regex/part.hpp>
5
6 // stl
7 #include <string_view>
8
9 namespace wr22::regex_parser::parser {
10
11     regex::SpannedPart parse\_regex(const std::u32string_view& regex);
12
13 } // namespace wr22::regex_parser::parser
```

7.5 include/wr22/regex_parser/regex/capture.hpp File Reference

```
#include <wr22/regex_parser/regex/named_capture_flavor.hpp>
#include <wr22/regex_parser/regex/capture.hpp>
#include <iosfwd>
#include <string>
#include <nlohmann/json.hpp>
```

Classes

- struct [wr22::regex_parser::regex::capture::None](#)
Denotes an non-capturing group.
- struct [wr22::regex_parser::regex::capture::Index](#)
Denotes a group captured by index.
- struct [wr22::regex_parser::regex::capture::Name](#)
Denotes a group captured by name.
- class [wr22::regex_parser::regex::Capture](#)
Group capture behavior.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)
- namespace [wr22::regex_parser::regex::capture](#)

Typedefs

- using `wr22::regex_parser::regex::capture::Adt` = `utils::Adt<None, Index, Name>`

Functions

- void `wr22::regex_parser::regex::capture::to_json` (`nlohmann::json& j`, `const None& capture`)
- void `wr22::regex_parser::regex::capture::to_json` (`nlohmann::json& j`, `const Index& capture`)
- void `wr22::regex_parser::regex::capture::to_json` (`nlohmann::json& j`, `const Name& capture`)
- `std::ostream&` `wr22::regex_parser::regex::operator<<` (`std::ostream& out`, `const Capture& capture`)
- void `wr22::regex_parser::regex::to_json` (`nlohmann::json& j`, `const Capture& capture`)

7.6 capture.hpp

[Go to the documentation of this file.](#)

```

1  #pragma once
2
3  // wr22
4  #include <wr22/regex_parser/regex/named_capture_flavor.hpp>
5  #include <wr22/utils/adt.hpp>
6
7  // stl
8  #include <iosfwd>
9  #include <string>
10
11 // nlohmann
12 #include <nlohmann/json.hpp>
13
14 namespace wr22::regex_parser::regex {
15
16 class Capture;
17
18 namespace capture {
19     struct None {
20         explicit None() = default;
21         bool operator==(const None& rhs) const = default;
22         static constexpr const char* code_name = "none";
23     };
24     void to_json(nlohmann::json& j, const None& capture);
25
26     struct Index {
27         explicit Index() = default;
28         bool operator==(const Index& rhs) const = default;
29         static constexpr const char* code_name = "index";
30     };
31     void to_json(nlohmann::json& j, const Index& capture);
32
33     struct Name {
34         explicit Name(std::string name, NamedCaptureFlavor flavor);
35         std::string name;
36         NamedCaptureFlavor flavor;
37         bool operator==(const Name& rhs) const = default;
38         static constexpr const char* code_name = "name";
39     };
40     void to_json(nlohmann::json& j, const Name& capture);
41
42     using Adt = utils::Adt<None, Index, Name>;
43 } // namespace capture
44
45 //
46 class Capture : public capture::Adt {
47 public:
48     using capture::Adt::Adt;
49 };
50
51 std::ostream& operator<<(std::ostream& out, const Capture& capture);
52 void to_json(nlohmann::json& j, const Capture& capture);
53
54 } // namespace wr22::regex_parser::regex

```


7.7 include/wr22/regex_parser/regex/character_class_data.hpp File Reference

```
#include <wr22/regex_parser/regex/spanned_character_range.hpp>
#include <vector>
```

Classes

- struct [wr22::regex_parser::regex::CharacterClassData](#)
A character class representation: a list of character ranges plus some additional properties.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

7.8 character_class_data.hpp

[Go to the documentation of this file.](#)

```
1 #pragma once
2
3 // wr22
4 #include <wr22/regex_parser/regex/spanned_character_range.hpp>
5
6 // stl
7 #include <vector>
8
9 namespace wr22::regex_parser::regex {
10
12 struct CharacterClassData {
13     std::vector<SpannedCharacterRange> ranges;
14
15     bool inverted;
16
17     bool operator==(const CharacterClassData& rhs) const = default;
18 };
19
20 }
```

7.9 include/wr22/regex_parser/regex/character_range.hpp File Reference

```
#include <stdexcept>
#include <iosfwd>
#include <fmt/core.h>
#include <nlohmann/json.hpp>
```

Classes

- struct [wr22::regex_parser::regex::InvalidCharacterRange](#)
- class [wr22::regex_parser::regex::CharacterRange](#)
A non-empty character range, possibly containing only one character.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

Functions

- `std::ostream & wr22::regex_parser::regex::operator<<` (`std::ostream &out`, `const CharacterRange &range`)
- `void wr22::regex_parser::regex::to_json` (`nlohmann::json &j`, `const CharacterRange &range`)

7.10 character_range.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // stl
4 #include <stdexcept>
5 #include <iosfwd>
6
7 // fmt
8 #include <fmt/core.h>
9
10 // nlohmann
11 #include <nlohmann/json.hpp>
12
13 namespace wr22::regex_parser::regex {
14
15 struct InvalidCharacterRange : public std::runtime_error {
16     explicit InvalidCharacterRange(char32_t first, char32_t last);
17
18     char32_t first;
19     char32_t last;
20 };
21
22 class CharacterRange {
23 public:
24     static CharacterRange from_endpoints(char32_t first, char32_t last);
25
26     static CharacterRange from_single_character(char32_t character) noexcept;
27
28     char32_t first() const noexcept;
29
30     char32_t last() const noexcept;
31
32     bool contains(char32_t character) const noexcept;
33
34     bool is_single_character() const noexcept;
35
36     bool operator==(const CharacterRange& rhs) const noexcept = default;
37
38 private:
39     explicit CharacterRange(char32_t first, char32_t last);
40
41     char32_t m_first;
42     char32_t m_last;
43 };
44
45 std::ostream& operator<<(std::ostream& out, const CharacterRange& range);
46 void to_json(nlohmann::json& j, const CharacterRange& range);
47
48 } // namespace wr22::regex_parser::regex

```

7.11 include/wr22/regex_parser/regex/named_capture_flavor.hpp File Reference

```

#include <iosfwd>
#include <nlohmann/json.hpp>

```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

Enumerations

- enum class [wr22::regex_parser::regex::NamedCaptureFlavor](#) { [wr22::regex_parser::regex::Apostrophes](#) , [wr22::regex_parser::regex::Angles](#) , [wr22::regex_parser::regex::AnglesWithP](#) }

The flavor (dialect) of a named group capture.

Functions

- `std::ostream & wr22::regex_parser::regex::operator<< (std::ostream &out, NamedCaptureFlavor flavor)`
- `void wr22::regex_parser::regex::to_json (nlohmann::json &j, NamedCaptureFlavor flavor)`

7.12 named_capture_flavor.hpp

[Go to the documentation of this file.](#)

```
1 #pragma once
2
3 // stl
4 #include <iosfwd>
5
6 // nlohmann
7 #include <nlohmann/json.hpp>
8
9 namespace wr22::regex_parser::regex {
10
11     enum class NamedCaptureFlavor
12     {
13         Apostrophes,
14         Angles,
15         AnglesWithP,
16     };
17
18     std::ostream& operator<<(std::ostream& out, NamedCaptureFlavor flavor);
19     void to_json(nlohmann::json& j, NamedCaptureFlavor flavor);
20
21 } // namespace wr22::regex_parser::regex
```

7.13 include/wr22/regex_parser/regex/part.hpp File Reference

```
#include <nlohmann/json_fwd.hpp>
#include <wr22/regex_parser/regex/capture.hpp>
#include <wr22/regex_parser/regex/character_class_data.hpp>
#include <wr22/regex_parser/regex/span/span.hpp>
#include <wr22/regex_parser/regex/adt.hpp>
#include <wr22/regex_parser/regex/box.hpp>
#include <iosfwd>
#include <memory>
#include <vector>
#include <nlohmann/json.hpp>
```

Classes

- struct [wr22::regex_parser::regex::part::Empty](#)
An empty regex part.
- struct [wr22::regex_parser::regex::part::Literal](#)
A regex part that matches a single character literally.
- struct [wr22::regex_parser::regex::part::Alternatives](#)
A regex part with the list of alternatives to be matched.
- struct [wr22::regex_parser::regex::part::Sequence](#)
A regex part with the list of items to be matched one after another.
- struct [wr22::regex_parser::regex::part::Group](#)
A regex part that represents a group in parentheses.
- struct [wr22::regex_parser::regex::part::Optional](#)
A regex part specifying an optional quantifier $((expression)?)$.
- struct [wr22::regex_parser::regex::part::Plus](#)
A regex part specifying an "at least one" quantifier $((expression)+)$.
- struct [wr22::regex_parser::regex::part::Star](#)
A regex part specifying an "at least zero" quantifier $((expression)*)$.
- struct [wr22::regex_parser::regex::part::Wildcard](#)
A regex part specifying any single character $(.)$.
- struct [wr22::regex_parser::regex::part::CharacterClass](#)
A regex part specifying a character class (e.g. $[a-z_]$).
- class [wr22::regex_parser::regex::Part](#)
A part of a regular expression and its AST node type.
- class [wr22::regex_parser::regex::SpannedPart](#)
A version of [Part](#) including the span information (position in the input) of the root AST node (child nodes always contain it because they are represented as [SpannedParts](#) themselves).

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)
- namespace [wr22::regex_parser::regex::part](#)
The namespace with the variants of [Part](#).

Typedefs

- using [wr22::regex_parser::regex::part::Adt](#) = `utils::Adt< Empty, Literal, Alternatives, Sequence, Group, Optional, Plus, Star, Wildcard, CharacterClass >`

Functions

- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Empty &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Literal &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Alternatives &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Sequence &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Group &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Optional &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Plus &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Star &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::Wildcard &part)
- void `wr22::regex_parser::regex::part::to_json` (nlohmann::json &j, const part::CharacterClass &part)
- void `wr22::regex_parser::regex::to_json` (nlohmann::json &j, const Part &part)
- void `wr22::regex_parser::regex::to_json` (nlohmann::json &j, const SpannedPart &part)
- std::ostream & `wr22::regex_parser::regex::operator<<` (std::ostream &out, const SpannedPart &part)

Convert a *SpannedPart* to a textual representation and write it to an *std::ostream*.

7.14 part.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // wr22
4 #include <nlohmann/json_fwd.hpp>
5 #include <wr22/regex_parser/regex/capture.hpp>
6 #include <wr22/regex_parser/regex/character_class_data.hpp>
7 #include <wr22/regex_parser/span/span.hpp>
8 #include <wr22/utils/adt.hpp>
9 #include <wr22/utils/box.hpp>
10
11 // stl
12 #include <iosfwd>
13 #include <memory>
14 #include <vector>
15
16 // nlohmann
17 #include <nlohmann/json.hpp>
18
19 namespace wr22::regex_parser::regex {
20
21 // Forward declarations.
22 class Part;
23 class SpannedPart;
24
25 namespace part {
26     struct Empty {
27         explicit Empty() = default;
28         bool operator==(const Empty& rhs) const = default;
29         static constexpr const char* code_name = "empty";
30     };
31     void to_json(nlohmann::json& j, const Empty& part);
32
33     struct Literal {
34         explicit Literal(char32_t character);
35         bool operator==(const Literal& rhs) const = default;
36         static constexpr const char* code_name = "literal";
37         char32_t character;
38     };
39     void to_json(nlohmann::json& j, const Literal& part);
40
41     struct Alternatives {
42         explicit Alternatives(std::vector<SpannedPart> alternatives);
43         bool operator==(const Alternatives& rhs) const = default;
44         static constexpr const char* code_name = "alternatives";
45         std::vector<SpannedPart> alternatives;
46     };
47     void to_json(nlohmann::json& j, const Alternatives& part);
48
49     struct Sequence {
50         explicit Sequence(std::vector<SpannedPart> items);

```

```

78     bool operator==(const Sequence& rhs) const = default;
79     static constexpr const char* code_name = "sequence";
80
81     std::vector<SpannedPart> items;
82 };
83 void to_json(nlohmann::json& j, const Sequence& part);
84
85 struct Group {
86     explicit Group(Capture capture, SpannedPart inner);
87     bool operator==(const Group& rhs) const = default;
88     static constexpr const char* code_name = "group";
89
90     Capture capture;
91     utils::Box<SpannedPart> inner;
92 };
93 void to_json(nlohmann::json& j, const Group& part);
94
95 struct Optional {
96     explicit Optional(SpannedPart inner);
97     bool operator==(const Optional& rhs) const = default;
98     static constexpr const char* code_name = "optional";
99
100    utils::Box<SpannedPart> inner;
101 };
102 void to_json(nlohmann::json& j, const Optional& part);
103
104 struct Plus {
105     explicit Plus(SpannedPart inner);
106     bool operator==(const Plus& rhs) const = default;
107     static constexpr const char* code_name = "plus";
108
109    utils::Box<SpannedPart> inner;
110 };
111 void to_json(nlohmann::json& j, const Plus& part);
112
113 struct Star {
114     explicit Star(SpannedPart inner);
115     bool operator==(const Star& rhs) const = default;
116     static constexpr const char* code_name = "star";
117
118    utils::Box<SpannedPart> inner;
119 };
120 void to_json(nlohmann::json& j, const Star& part);
121
122 struct Wildcard {
123     explicit Wildcard() = default;
124     bool operator==(const Wildcard& rhs) const = default;
125     static constexpr const char* code_name = "wildcard";
126 };
127 void to_json(nlohmann::json& j, const Wildcard& part);
128
129 struct CharacterClass {
130     explicit CharacterClass(CharacterClassData data);
131     bool operator==(const CharacterClass& rhs) const = default;
132     static constexpr const char* code_name = "character_class";
133
134    CharacterClassData data;
135 };
136 void to_json(nlohmann::json& j, const CharacterClass& part);
137
138 using Adt = utils::
139     Adt<Empty, Literal, Alternatives, Sequence, Group, Optional, Plus, Star, Wildcard,
140     CharacterClass>;
141 } // namespace part
142
143 class Part : public part::Adt {
144 public:
145     using part::Adt::Adt;
146 };
147 void to_json(nlohmann::json& j, const Part& part);
148
149 class SpannedPart {
150 public:
151     explicit SpannedPart(Part part, span::Span span);
152
153     bool operator==(const SpannedPart& other) const = default;
154     bool operator!=(const SpannedPart& other) const = default;
155
156     const Part& part() const;
157     Part& part();
158
159     span::Span span() const;
160
161 private:
162     Part m_part;
163     span::Span m_span;
164 };

```

```

221 void to_json(nlohmann::json& j, const SpannedPart& part);
222
224 std::ostream& operator<<(std::ostream& out, const SpannedPart& part);
225
226 } // namespace wr22::regex_parser::regex

```

7.15 include/wr22/regex_parser/regex/spanned_character_range.hpp File Reference

```

#include <wr22/regex_parser/regex/character_range.hpp>
#include <wr22/regex_parser/span/span.hpp>
#include <iosfwd>
#include <nlohmann/json.hpp>

```

Classes

- struct `wr22::regex_parser::regex::SpannedCharacterRange`
A *CharacterRange* with its *span*.

Namespaces

- namespace `wr22`
- namespace `wr22::regex_parser`
- namespace `wr22::regex_parser::regex`

Functions

- `std::ostream & wr22::regex_parser::regex::operator<<` (`std::ostream &out`, `const SpannedCharacterRange &range`)
- `void wr22::regex_parser::regex::to_json` (`nlohmann::json& j`, `const SpannedCharacterRange &range`)

7.16 spanned_character_range.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // wr22
4 #include <wr22/regex_parser/regex/character_range.hpp>
5 #include <wr22/regex_parser/span/span.hpp>
6
7 // stl
8 #include <iosfwd>
9
10 // nlohmann
11 #include <nlohmann/json.hpp>
12
13 namespace wr22::regex_parser::regex {
14
15     struct SpannedCharacterRange {
16         CharacterRange range;
17         span::Span span;
18
19         bool operator==(const SpannedCharacterRange& rhs) const = default;
20     };
21
22     std::ostream& operator<<(std::ostream& out, const SpannedCharacterRange& range);
23 void to_json(nlohmann::json& j, const SpannedCharacterRange& range);
24
25 } // namespace wr22::regex_parser::regex

```

7.17 include/wr22/regex_parser/span/span.hpp File Reference

```
#include <cstdint>
#include <stdexcept>
#include <ostream>
#include <nlohmann/json.hpp>
```

Classes

- struct [wr22::regex_parser::span::InvalidSpan](#)
The exception thrown on an attempt to construct an invalid span.
- class [wr22::regex_parser::span::Span](#)
Character position range in the input string.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::span](#)

Functions

- [std::ostream & wr22::regex_parser::span::operator<<](#) (std::ostream &out, Span span)
- void [wr22::regex_parser::span::to_json](#) (nlohmann::json &j, Span span)

7.18 span.hpp

[Go to the documentation of this file.](#)

```
1 #pragma once
2
3 // stl
4 #include <cstdint>
5 #include <stdexcept>
6 #include <ostream>
7
8 // nlohmann
9 #include <nlohmann/json.hpp>
10
11 namespace wr22::regex_parser::span {
12
13     struct InvalidSpan : public std::runtime_error {
14         InvalidSpan(size_t begin, size_t end);
15
16         size_t begin;
17         size_t end;
18     };
19
20     class Span {
21     public:
22         static Span make_empty(size_t position);
23
24         static Span make_single_position(size_t position);
25
26         static Span make_from_positions(size_t begin, size_t end);
27
28         static Span make_with_length(size_t begin, size_t length);
29
30         Span extend_right(size_t num_positions) const;
31
32         size_t length() const;
```



```

73
74     size_t begin() const;
75
76     size_t end() const;
77
78     bool operator==(const Span& other) const = default;
79     bool operator!=(const Span& other) const = default;
80
81 private:
82     explicit Span(size_t begin, size_t end);
83
84     size_t m_begin;
85     size_t m_end;
86 };
87
88 std::ostream& operator<<(std::ostream& out, Span span);
89 void to_json(nlohmann::json& j, Span span);
90
91 } // namespace wr22::regex_parser::span

```

7.19 src/parser/capture.cpp File Reference

```

#include <wr22/regex_parser/regex/capture.hpp>
#include <wr22/regex_parser/regex/named_capture_flavor.hpp>
#include <iterator>
#include <ostream>
#include <fmt/core.h>
#include <fmt/ostream.h>

```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)
- namespace [wr22::regex_parser::regex::capture](#)

Functions

- [std::ostream & wr22::regex_parser::regex::operator<<](#) (std::ostream &out, const Capture &capture)
- [void wr22::regex_parser::regex::to_json](#) (nlohmann::json &j, const Capture &capture)
- [void wr22::regex_parser::regex::capture::to_json](#) (nlohmann::json &j, const None &capture)
- [void wr22::regex_parser::regex::capture::to_json](#) (nlohmann::json &j, const Index &capture)
- [void wr22::regex_parser::regex::capture::to_json](#) (nlohmann::json &j, const Name &capture)

7.20 src/parser/errors.cpp File Reference

```

#include <wr22/regex_parser/parser/errors.hpp>
#include <wr22/unicode/conversion.hpp>
#include <fmt/core.h>
#include <fmt/ostream.h>

```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::parser](#)
- namespace [wr22::regex_parser::parser::errors](#)

7.21 src/parser/regex.cpp File Reference

```
#include "wr22/regex_parser/span/span.hpp"
#include <wr22/regex_parser/parser/errors.hpp>
#include <wr22/regex_parser/parser/regex.hpp>
#include <wr22/regex_parser/regex/part.hpp>
#include <wr22/unicode/conversion.hpp>
#include <optional>
#include <stdexcept>
#include <string>
#include <vector>
```

Classes

- class [wr22::regex_parser::parser::Parser< Iter, Sentinel >](#)
A regex parser.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::parser](#)

Functions

- template<typename Iter , typename Sentinel >
[wr22::regex_parser::parser::Parser](#) (Iter begin, Sentinel end) -> Parser< Iter, Sentinel >
The type deduction guideline for [Parser](#).
- regex::SpannedPart [wr22::regex_parser::parser::parse_regex](#) (const std::u32string_view ®ex)
Parse a regular expression into its AST.

7.22 src/regex/character_range.cpp File Reference

```
#include <wr22/regex_parser/regex/character_range.hpp>
#include <wr22/unicode/conversion.hpp>
#include <ostream>
#include <fmt/core.h>
#include <fmt/ostream.h>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

Functions

- `std::ostream & wr22::regex_parser::regex::operator<<` (`std::ostream &out`, `const CharacterRange &range`)
- `void wr22::regex_parser::regex::to_json` (`nlohmann::json &j`, `const CharacterRange &range`)

7.23 src/regex/named_capture_flavor.cpp File Reference

```
#include <wr22/regex_parser/regex/named_capture_flavor.hpp>
#include <ostream>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

Functions

- `std::ostream & wr22::regex_parser::regex::operator<<` (`std::ostream &out`, `NamedCaptureFlavor flavor`)
- `void wr22::regex_parser::regex::to_json` (`nlohmann::json &j`, `NamedCaptureFlavor flavor`)

7.24 src/regex/part.cpp File Reference

```
#include <wr22/regex_parser/regex/part.hpp>
#include <wr22/regex_parser/span/span.hpp>
#include <wr22/unicode/conversion.hpp>
#include <iterator>
#include <ostream>
#include <fmt/core.h>
#include <fmt/ostream.h>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)
- namespace [wr22::regex_parser::regex::part](#)

The namespace with the variants of [Part](#).

Functions

- `std::ostream & wr22::regex_parser::regex::operator<<` (`std::ostream &out`, `const SpannedPart &part`)
Convert a `SpannedPart` to a textual representation and write it to an `std::ostream`.
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Empty &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Literal &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Alternatives &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Sequence &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Group &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Optional &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Plus &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Star &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::Wildcard &part`)
- `void wr22::regex_parser::regex::part::to_json` (`nlohmann::json &j`, `const part::CharacterClass &part`)
- `void wr22::regex_parser::regex::to_json` (`nlohmann::json &j`, `const Part &part`)
- `void wr22::regex_parser::regex::to_json` (`nlohmann::json &j`, `const SpannedPart &part`)

7.25 src/regex/spanned_character_range.cpp File Reference

```
#include <wr22/regex_parser/regex/spanned_character_range.hpp>
#include <ostream>
#include <fmt/core.h>
#include <fmt/ostream.h>
```

Namespaces

- namespace `wr22`
- namespace `wr22::regex_parser`
- namespace `wr22::regex_parser::regex`

Functions

- `std::ostream & wr22::regex_parser::regex::operator<<` (`std::ostream &out`, `const SpannedCharacterRange &range`)
- `void wr22::regex_parser::regex::to_json` (`nlohmann::json &j`, `const SpannedCharacterRange &range`)

7.26 src/span/span.cpp File Reference

```
#include <stdexcept>
#include <wr22/regex_parser/span/span.hpp>
#include <fmt/core.h>
#include <fmt/ostream.h>
```

Namespaces

- namespace `wr22`
- namespace `wr22::regex_parser`
- namespace `wr22::regex_parser::span`

Functions

- `std::ostream & wr22::regex_parser::span::operator<<` (`std::ostream &out`, `Span span`)
- `void wr22::regex_parser::span::to_json` (`nlohmann::json &j`, `Span span`)

Index

Adt

- [wr22::regex_parser::regex::capture](#), [15](#)
- [wr22::regex_parser::regex::part](#), [17](#)

Alternatives

- [wr22::regex_parser::regex::part::Alternatives](#), [22](#)

alternatives

- [wr22::regex_parser::regex::part::Alternatives](#), [22](#)

Angles

- [wr22::regex_parser::regex](#), [13](#)

AnglesWithP

- [wr22::regex_parser::regex](#), [13](#)

Apostrophes

- [wr22::regex_parser::regex](#), [13](#)

begin

- [wr22::regex_parser::span::InvalidSpan](#), [38](#)
- [wr22::regex_parser::span::Span](#), [54](#)

capture

- [wr22::regex_parser::regex::part::Group](#), [32](#)

char_got

- [wr22::regex_parser::parser::errors::ExpectedEnd](#), [30](#)
- [wr22::regex_parser::parser::errors::UnexpectedChar](#), [62](#)

character

- [wr22::regex_parser::regex::part::Literal](#), [39](#)

CharacterClass

- [wr22::regex_parser::regex::part::CharacterClass](#), [24](#)

code_name

- [wr22::regex_parser::regex::capture::Index](#), [34](#)
- [wr22::regex_parser::regex::capture::Name](#), [41](#)
- [wr22::regex_parser::regex::capture::None](#), [42](#)
- [wr22::regex_parser::regex::part::Alternatives](#), [22](#)
- [wr22::regex_parser::regex::part::CharacterClass](#), [24](#)
- [wr22::regex_parser::regex::part::Empty](#), [29](#)
- [wr22::regex_parser::regex::part::Group](#), [32](#)
- [wr22::regex_parser::regex::part::Literal](#), [39](#)
- [wr22::regex_parser::regex::part::Optional](#), [43](#)
- [wr22::regex_parser::regex::part::Plus](#), [52](#)
- [wr22::regex_parser::regex::part::Sequence](#), [53](#)
- [wr22::regex_parser::regex::part::Star](#), [61](#)
- [wr22::regex_parser::regex::part::Wildcard](#), [65](#)

contains

- [wr22::regex_parser::regex::CharacterRange](#), [26](#)

data

- [wr22::regex_parser::regex::part::CharacterClass](#), [24](#)

Empty

- [wr22::regex_parser::regex::part::Empty](#), [28](#)

end

- [wr22::regex_parser::span::InvalidSpan](#), [38](#)
- [wr22::regex_parser::span::Span](#), [55](#)

expect_end

- [wr22::regex_parser::parser::Parser< Iter, Sentinel >](#), [46](#)

expected

- [wr22::regex_parser::parser::errors::UnexpectedChar](#), [62](#)
- [wr22::regex_parser::parser::errors::UnexpectedEnd](#), [64](#)

ExpectedEnd

- [wr22::regex_parser::parser::errors::ExpectedEnd](#), [30](#)

extend_right

- [wr22::regex_parser::span::Span](#), [55](#)

first

- [wr22::regex_parser::parser::errors::InvalidRange](#), [36](#)
- [wr22::regex_parser::regex::CharacterRange](#), [27](#)
- [wr22::regex_parser::regex::InvalidCharacterRange](#), [35](#)

flavor

- [wr22::regex_parser::regex::capture::Name](#), [41](#)

from_endpoints

- [wr22::regex_parser::regex::CharacterRange](#), [27](#)

from_single_character

- [wr22::regex_parser::regex::CharacterRange](#), [27](#)

Group

- [wr22::regex_parser::regex::part::Group](#), [32](#)

- [include/wr22/regex_parser/parser/errors.hpp](#), [67](#), [68](#)

- [include/wr22/regex_parser/parser/regex.hpp](#), [68](#), [69](#)

- [include/wr22/regex_parser/regex/capture.hpp](#), [69](#), [70](#)

- [include/wr22/regex_parser/regex/character_class_data.hpp](#), [71](#)

- [include/wr22/regex_parser/regex/character_range.hpp](#), [71](#), [72](#)

- [include/wr22/regex_parser/regex/named_capture_flavor.hpp](#), [72](#), [73](#)

- [include/wr22/regex_parser/regex/part.hpp](#), [73](#), [75](#)

- [include/wr22/regex_parser/regex/spanned_character_range.hpp](#), [77](#)

- include/wr22/regex_parser/span/span.hpp, 78
- Index
 - wr22::regex_parser::regex::capture::Index, 33
- inner
 - wr22::regex_parser::regex::part::Group, 32
 - wr22::regex_parser::regex::part::Optional, 44
 - wr22::regex_parser::regex::part::Plus, 52
 - wr22::regex_parser::regex::part::Star, 61
- InvalidCharacterRange
 - wr22::regex_parser::regex::InvalidCharacterRange, 34
- InvalidRange
 - wr22::regex_parser::parser::errors::InvalidRange, 36
- InvalidSpan
 - wr22::regex_parser::span::InvalidSpan, 38
- inverted
 - wr22::regex_parser::regex::CharacterClassData, 25
- is_single_character
 - wr22::regex_parser::regex::CharacterRange, 27
- items
 - wr22::regex_parser::regex::part::Sequence, 53
- last
 - wr22::regex_parser::parser::errors::InvalidRange, 36
 - wr22::regex_parser::regex::CharacterRange, 27
 - wr22::regex_parser::regex::InvalidCharacterRange, 35
- length
 - wr22::regex_parser::span::Span, 55
- Literal
 - wr22::regex_parser::regex::part::Literal, 39
- make_empty
 - wr22::regex_parser::span::Span, 55
- make_from_positions
 - wr22::regex_parser::span::Span, 55
- make_single_position
 - wr22::regex_parser::span::Span, 56
- make_with_length
 - wr22::regex_parser::span::Span, 56
- Name
 - wr22::regex_parser::regex::capture::Name, 40
- name
 - wr22::regex_parser::regex::capture::Name, 41
- NamedCaptureFlavor
 - wr22::regex_parser::regex, 11
- needs_closing
 - wr22::regex_parser::parser::errors::UnexpectedEnd, 64
- None
 - wr22::regex_parser::regex::capture::None, 42
- operator!=
 - wr22::regex_parser::regex::SpannedPart, 59
 - wr22::regex_parser::span::Span, 56
- operator<<
 - wr22::regex_parser::regex, 13
 - wr22::regex_parser::span, 19
- operator==
 - wr22::regex_parser::regex::capture::Index, 33
 - wr22::regex_parser::regex::capture::Name, 41
 - wr22::regex_parser::regex::capture::None, 42
 - wr22::regex_parser::regex::CharacterClassData, 25
 - wr22::regex_parser::regex::CharacterRange, 28
 - wr22::regex_parser::regex::part::Alternatives, 22
 - wr22::regex_parser::regex::part::CharacterClass, 24
 - wr22::regex_parser::regex::part::Empty, 29
 - wr22::regex_parser::regex::part::Group, 32
 - wr22::regex_parser::regex::part::Literal, 39
 - wr22::regex_parser::regex::part::Optional, 43
 - wr22::regex_parser::regex::part::Plus, 51
 - wr22::regex_parser::regex::part::Sequence, 53
 - wr22::regex_parser::regex::part::Star, 60
 - wr22::regex_parser::regex::part::Wildcard, 65
 - wr22::regex_parser::regex::SpannedCharacterRange, 57
 - wr22::regex_parser::regex::SpannedPart, 59
 - wr22::regex_parser::span::Span, 57
- Optional
 - wr22::regex_parser::regex::part::Optional, 43
- parse_alternatives
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 46
- parse_atom
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 46
- parse_char_class
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 47
- parse_char_literal
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 47
- parse_group
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 47
- parse_group_name
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 48
- parse_regex
 - wr22::regex_parser::parser, 10
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 48
- parse_sequence
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 48
- parse_sequence_or_empty
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 49
- parse_wildcard
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 49

- Parser
 - wr22::regex_parser::parser, 10
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 45
- part
 - wr22::regex_parser::regex::SpannedPart, 59
- Plus
 - wr22::regex_parser::regex::part::Plus, 51
- position
 - wr22::regex_parser::parser::errors::ExpectedEnd, 30
 - wr22::regex_parser::parser::errors::UnexpectedChar, 62
 - wr22::regex_parser::parser::errors::UnexpectedEnd, 64
- range
 - wr22::regex_parser::regex::SpannedCharacterRange, 58
- ranges
 - wr22::regex_parser::regex::CharacterClassData, 25
- Sequence
 - wr22::regex_parser::regex::part::Sequence, 53
- span
 - wr22::regex_parser::parser::errors::InvalidRange, 37
 - wr22::regex_parser::regex::SpannedCharacterRange, 58
 - wr22::regex_parser::regex::SpannedPart, 59
- SpannedPart
 - wr22::regex_parser::regex::SpannedPart, 58
- src/parser/capture.cpp, 79
- src/parser/errors.cpp, 79
- src/parser/regex.cpp, 80
- src/regex/character_range.cpp, 80
- src/regex/named_capture_flavor.cpp, 81
- src/regex/part.cpp, 81
- src/regex/spanned_character_range.cpp, 82
- src/span/span.cpp, 82
- Star
 - wr22::regex_parser::regex::part::Star, 60
- to_json
 - wr22::regex_parser::regex, 14
 - wr22::regex_parser::regex::capture, 15, 16
 - wr22::regex_parser::regex::part, 17–19
 - wr22::regex_parser::span, 19
- UnexpectedChar
 - wr22::regex_parser::parser::errors::UnexpectedChar, 62
- UnexpectedEnd
 - wr22::regex_parser::parser::errors::UnexpectedEnd, 63
- Wildcard
 - wr22::regex_parser::regex::part::Wildcard, 65
- wr22, 9
- wr22::regex_parser, 9
- wr22::regex_parser::parser, 9
 - parse_regex, 10
 - Parser, 10
- wr22::regex_parser::parser::errors, 10
- wr22::regex_parser::parser::errors::ExpectedEnd, 29
 - char_got, 30
 - ExpectedEnd, 30
 - position, 30
- wr22::regex_parser::parser::errors::InvalidRange, 35
 - first, 36
 - InvalidRange, 36
 - last, 36
 - span, 37
- wr22::regex_parser::parser::errors::ParseError, 44
- wr22::regex_parser::parser::errors::UnexpectedChar, 61
 - char_got, 62
 - expected, 62
 - position, 62
 - UnexpectedChar, 62
- wr22::regex_parser::parser::errors::UnexpectedEnd, 63
 - expected, 64
 - needs_closing, 64
 - position, 64
 - UnexpectedEnd, 63
- wr22::regex_parser::parser::Parser< Iter, Sentinel >, 44
 - expect_end, 46
 - parse_alternatives, 46
 - parse_atom, 46
 - parse_char_class, 47
 - parse_char_literal, 47
 - parse_group, 47
 - parse_group_name, 48
 - parse_regex, 48
 - parse_sequence, 48
 - parse_sequence_or_empty, 49
 - parse_wildcard, 49
 - Parser, 45
- wr22::regex_parser::regex, 11
 - Angles, 13
 - AnglesWithP, 13
 - Apostrophes, 13
 - NamedCaptureFlavor, 11
 - operator<<, 13
 - to_json, 14
- wr22::regex_parser::regex::Capture, 23
- wr22::regex_parser::regex::capture, 15
 - Adt, 15
 - to_json, 15, 16
- wr22::regex_parser::regex::capture::Index, 33
 - code_name, 34
 - Index, 33
 - operator==, 33
- wr22::regex_parser::regex::capture::Name, 40
 - code_name, 41

- flavor, 41
- Name, 40
- name, 41
- operator==, 41
- wr22::regex_parser::regex::capture::None, 41
 - code_name, 42
 - None, 42
 - operator==, 42
- wr22::regex_parser::regex::CharacterClassData, 25
 - inverted, 25
 - operator==, 25
 - ranges, 25
- wr22::regex_parser::regex::CharacterRange, 26
 - contains, 26
 - first, 27
 - from_endpoints, 27
 - from_single_character, 27
 - is_single_character, 27
 - last, 27
 - operator==, 28
- wr22::regex_parser::regex::InvalidCharacterRange, 34
 - first, 35
 - InvalidCharacterRange, 34
 - last, 35
- wr22::regex_parser::regex::Part, 50
- wr22::regex_parser::regex::part, 16
 - Adt, 17
 - to_json, 17–19
- wr22::regex_parser::regex::part::Alternatives, 21
 - Alternatives, 22
 - alternatives, 22
 - code_name, 22
 - operator==, 22
- wr22::regex_parser::regex::part::CharacterClass, 23
 - CharacterClass, 24
 - code_name, 24
 - data, 24
 - operator==, 24
- wr22::regex_parser::regex::part::Empty, 28
 - code_name, 29
 - Empty, 28
 - operator==, 29
- wr22::regex_parser::regex::part::Group, 31
 - capture, 32
 - code_name, 32
 - Group, 32
 - inner, 32
 - operator==, 32
- wr22::regex_parser::regex::part::Literal, 38
 - character, 39
 - code_name, 39
 - Literal, 39
 - operator==, 39
- wr22::regex_parser::regex::part::Optional, 42
 - code_name, 43
 - inner, 44
 - operator==, 43
 - Optional, 43
- wr22::regex_parser::regex::part::Plus, 51
 - code_name, 52
 - inner, 52
 - operator==, 51
 - Plus, 51
- wr22::regex_parser::regex::part::Sequence, 52
 - code_name, 53
 - items, 53
 - operator==, 53
 - Sequence, 53
- wr22::regex_parser::regex::part::Star, 60
 - code_name, 61
 - inner, 61
 - operator==, 60
 - Star, 60
- wr22::regex_parser::regex::part::Wildcard, 64
 - code_name, 65
 - operator==, 65
 - Wildcard, 65
- wr22::regex_parser::regex::SpannedCharacterRange, 57
 - operator==, 57
 - range, 58
 - span, 58
- wr22::regex_parser::regex::SpannedPart, 58
 - operator!=, 59
 - operator==, 59
 - part, 59
 - span, 59
 - SpannedPart, 58
- wr22::regex_parser::span, 19
 - operator<<, 19
 - to_json, 19
- wr22::regex_parser::span::InvalidSpan, 37
 - begin, 38
 - end, 38
 - InvalidSpan, 38
- wr22::regex_parser::span::Span, 54
 - begin, 54
 - end, 55
 - extend_right, 55
 - length, 55
 - make_empty, 55
 - make_from_positions, 55
 - make_single_position, 56
 - make_with_length, 56
 - operator!=, 56
 - operator==, 57