

Writing Regexprs 2021-22 / Regex Parser

Generated by Doxygen 1.9.3

1 Namespace Index	1
1.1 Namespace List	1
2 Hierarchical Index	3
2.1 Class Hierarchy	3
3 Class Index	5
3.1 Class List	5
4 File Index	7
4.1 File List	7
5 Namespace Documentation	9
5.1 wr22 Namespace Reference	9
5.2 wr22::regex_parser Namespace Reference	9
5.3 wr22::regex_parser::parser Namespace Reference	9
5.3.1 Function Documentation	10
5.3.1.1 parse_regex()	10
5.3.1.2 Parser()	10
5.4 wr22::regex_parser::parser::errors Namespace Reference	10
5.5 wr22::regex_parser::regex Namespace Reference	11
5.5.1 Enumeration Type Documentation	11
5.5.1.1 NamedCaptureFlavor	11
5.5.2 Function Documentation	12
5.5.2.1 operator<<() [1/3]	12
5.5.2.2 operator<<() [2/3]	12
5.5.2.3 operator<<() [3/3]	12
5.6 wr22::regex_parser::regex::capture Namespace Reference	12
5.6.1 Typedef Documentation	12
5.6.1.1 Adt	13
5.7 wr22::regex_parser::regex::part Namespace Reference	13
5.7.1 Detailed Description	13
5.7.2 Typedef Documentation	13
5.7.2.1 Adt	13
5.8 wr22::regex_parser::utils Namespace Reference	14
5.8.1 Typedef Documentation	14
5.8.1.1 utf_traits	14
5.8.2 Function Documentation	15
5.8.2.1 Box() [1/2]	15
5.8.2.2 Box() [2/2]	15
5.8.2.3 operator!=(()) [1/2]	15
5.8.2.4 operator!=(()) [2/2]	15
5.8.2.5 operator==(()) [1/2]	15
5.8.2.6 operator==(()) [2/2]	16

5.9 wr22::regex_parser::utils::detail Namespace Reference	16
5.10 wr22::regex_parser::utils::detail::adt Namespace Reference	16
6 Class Documentation	17
6.1 wr22::regex_parser::utils::Adt< Variants > Class Template Reference	17
6.1.1 Detailed Description	18
6.1.2 Member Typedef Documentation	18
6.1.2.1 VariantType	18
6.1.3 Constructor & Destructor Documentation	18
6.1.3.1 Adt()	18
6.1.4 Member Function Documentation	19
6.1.4.1 as_variant() [1/2]	19
6.1.4.2 as_variant() [2/2]	19
6.1.4.3 visit() [1/2]	19
6.1.4.4 visit() [2/2]	19
6.1.5 Member Data Documentation	20
6.1.5.1 m_variant	20
6.2 wr22::regex_parser::regex::part::Alternatives Struct Reference	20
6.2.1 Detailed Description	20
6.2.2 Constructor & Destructor Documentation	20
6.2.2.1 Alternatives()	21
6.2.3 Member Function Documentation	21
6.2.3.1 operator==()	21
6.2.4 Member Data Documentation	21
6.2.4.1 alternatives	21
6.3 wr22::regex_parser::utils::Box< T > Class Template Reference	21
6.3.1 Detailed Description	22
6.3.2 Constructor & Destructor Documentation	22
6.3.2.1 Box() [1/3]	22
6.3.2.2 Box() [2/3]	22
6.3.2.3 Box() [3/3]	23
6.3.3 Member Function Documentation	24
6.3.3.1 construct_in_place()	24
6.3.3.2 operator*() [1/2]	24
6.3.3.3 operator*() [2/2]	24
6.4 wr22::regex_parser::utils::BoxIsEmpty Struct Reference	25
6.4.1 Member Function Documentation	25
6.4.1.1 what()	25
6.5 wr22::regex_parser::regex::Capture Class Reference	25
6.5.1 Detailed Description	26
6.6 wr22::regex_parser::regex::part::Empty Struct Reference	26
6.6.1 Detailed Description	26

6.6.2 Constructor & Destructor Documentation	26
6.6.2.1 Empty()	26
6.6.3 Member Function Documentation	26
6.6.3.1 operator==()	27
6.7 wr22::regex_parser::parser::errors::ExpectedEnd Class Reference	27
6.7.1 Detailed Description	27
6.7.2 Constructor & Destructor Documentation	27
6.7.2.1 ExpectedEnd()	27
6.7.3 Member Function Documentation	28
6.7.3.1 char_got()	28
6.7.3.2 position()	28
6.8 wr22::regex_parser::regex::part::Group Struct Reference	28
6.8.1 Detailed Description	29
6.8.2 Constructor & Destructor Documentation	29
6.8.2.1 Group()	29
6.8.3 Member Function Documentation	29
6.8.3.1 operator==()	29
6.8.4 Member Data Documentation	29
6.8.4.1 capture	29
6.8.4.2 inner	30
6.9 wr22::regex_parser::regex::capture::Index Struct Reference	30
6.9.1 Detailed Description	30
6.9.2 Constructor & Destructor Documentation	30
6.9.2.1 Index()	30
6.9.3 Member Function Documentation	30
6.9.3.1 operator==()	30
6.10 wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8 Struct Reference	31
6.10.1 Detailed Description	31
6.10.2 Member Function Documentation	31
6.10.2.1 what()	31
6.11 wr22::regex_parser::regex::part::Literal Struct Reference	31
6.11.1 Detailed Description	32
6.11.2 Constructor & Destructor Documentation	32
6.11.2.1 Literal()	32
6.11.3 Member Function Documentation	32
6.11.3.1 operator==()	32
6.11.4 Member Data Documentation	32
6.11.4.1 character	32
6.12 wr22::regex_parser::utils::detail::adt::MultiCallable< Fs > Struct Template Reference	33
6.12.1 Constructor & Destructor Documentation	33
6.12.1.1 MultiCallable()	33
6.13 wr22::regex_parser::regex::capture::Name Struct Reference	33

6.13.1 Detailed Description	34
6.13.2 Constructor & Destructor Documentation	34
6.13.2.1 Name()	34
6.13.3 Member Function Documentation	34
6.13.3.1 operator==()	34
6.13.4 Member Data Documentation	34
6.13.4.1 flavor	34
6.13.4.2 name	34
6.14 wr22::regex_parser::regex::capture::None Struct Reference	35
6.14.1 Detailed Description	35
6.14.2 Constructor & Destructor Documentation	35
6.14.2.1 None()	35
6.14.3 Member Function Documentation	35
6.14.3.1 operator==()	35
6.15 wr22::regex_parser::regex::part::Optional Struct Reference	35
6.15.1 Detailed Description	36
6.15.2 Constructor & Destructor Documentation	36
6.15.2.1 Optional()	36
6.15.3 Member Function Documentation	36
6.15.3.1 operator==()	36
6.15.4 Member Data Documentation	36
6.15.4.1 inner	37
6.16 wr22::regex_parser::parser::errors::ParseError Struct Reference	37
6.16.1 Detailed Description	37
6.17 wr22::regex_parser::parser::Parser< Iter, Sentinel > Class Template Reference	37
6.17.1 Detailed Description	38
6.17.2 Constructor & Destructor Documentation	38
6.17.2.1 Parser()	38
6.17.3 Member Function Documentation	39
6.17.3.1 expect_end()	39
6.17.3.2 parse_alternatives()	39
6.17.3.3 parse_atom()	39
6.17.3.4 parse_char_literal()	40
6.17.3.5 parse_group()	40
6.17.3.6 parse_group_name()	40
6.17.3.7 parse_regex()	41
6.17.3.8 parse_sequence()	41
6.17.3.9 parse_sequence_or_empty()	41
6.18 wr22::regex_parser::regex::Part Class Reference	42
6.18.1 Detailed Description	42
6.19 wr22::regex_parser::regex::part::Plus Struct Reference	43
6.19.1 Detailed Description	43

6.19.2 Constructor & Destructor Documentation	43
6.19.2.1 Plus()	43
6.19.3 Member Function Documentation	43
6.19.3.1 operator==()	43
6.19.4 Member Data Documentation	43
6.19.4.1 inner	44
6.20 wr22::regex_parser::regex::part::Sequence Struct Reference	44
6.20.1 Detailed Description	44
6.20.2 Constructor & Destructor Documentation	44
6.20.2.1 Sequence()	44
6.20.3 Member Function Documentation	45
6.20.3.1 operator==()	45
6.20.4 Member Data Documentation	45
6.20.4.1 items	45
6.21 wr22::regex_parser::regex::part::Star Struct Reference	45
6.21.1 Detailed Description	45
6.21.2 Constructor & Destructor Documentation	46
6.21.2.1 Star()	46
6.21.3 Member Function Documentation	46
6.21.3.1 operator==()	46
6.21.4 Member Data Documentation	46
6.21.4.1 inner	46
6.22 wr22::regex_parser::parser::errors::UnexpectedChar Class Reference	46
6.22.1 Detailed Description	47
6.22.2 Constructor & Destructor Documentation	47
6.22.2.1 UnexpectedChar()	47
6.22.3 Member Function Documentation	47
6.22.3.1 char_got()	47
6.22.3.2 expected()	48
6.22.3.3 position()	48
6.23 wr22::regex_parser::parser::errors::UnexpectedEnd Class Reference	48
6.23.1 Detailed Description	48
6.23.2 Constructor & Destructor Documentation	49
6.23.2.1 UnexpectedEnd()	49
6.23.3 Member Function Documentation	49
6.23.3.1 expected()	49
6.23.3.2 position()	49
6.24 wr22::regex_parser::utils::UnicodeStringView Class Reference	49
6.24.1 Detailed Description	50
6.24.2 Constructor & Destructor Documentation	50
6.24.2.1 UnicodeStringView()	50
6.24.3 Member Function Documentation	51

6.24.3.1 begin()	51
6.24.3.2 end()	51
6.24.3.3 raw()	51
6.24.4 Friends And Related Function Documentation	51
6.24.4.1 UnicodeStringViewIterator	51
6.25 wr22::regex_parser::utils::UnicodeStringViewIterator Class Reference	51
6.25.1 Detailed Description	52
6.25.2 Member Typedef Documentation	52
6.25.2.1 category_type	52
6.25.2.2 value_type	52
6.25.3 Constructor & Destructor Documentation	53
6.25.3.1 UnicodeStringViewIterator()	53
6.25.4 Member Function Documentation	53
6.25.4.1 operator!==(())	53
6.25.4.2 operator*()	53
6.25.4.3 operator++()	53
6.25.4.4 operator==(())	54
6.25.5 Friends And Related Function Documentation	54
6.25.5.1 UnicodeStringView	54
7 File Documentation	55
7.1 include/wr22/regex_parser/parser/errors.hpp File Reference	55
7.2 errors.hpp	56
7.3 include/wr22/regex_parser/parser/regex.hpp File Reference	56
7.4 regex.hpp	57
7.5 include/wr22/regex_parser/regex/capture.hpp File Reference	57
7.6 capture.hpp	58
7.7 include/wr22/regex_parser/regex/named_capture_flavor.hpp File Reference	58
7.8 named_capture_flavor.hpp	59
7.9 include/wr22/regex_parser/regex/part.hpp File Reference	59
7.10 part.hpp	60
7.11 include/wr22/regex_parser/utils/adt.hpp File Reference	61
7.12 adt.hpp	62
7.13 include/wr22/regex_parser/utils/box.hpp File Reference	63
7.14 box.hpp	63
7.15 include/wr22/regex_parser/utils/utf8_string_view.hpp File Reference	64
7.16 utf8_string_view.hpp	65
7.17 src/parser/capture.cpp File Reference	65
7.18 src/parser/errors.cpp File Reference	66
7.19 src/parser/regex.cpp File Reference	66
7.20 src/regex/named_capture_flavor.cpp File Reference	67
7.21 src/regex/part.cpp File Reference	67

7.22 src/utls/box.cpp File Reference	68
7.23 src/utls/utf8_string_view.cpp File Reference	68
Index	69

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all namespaces with brief descriptions:

wr22	9
wr22::regex_parser	9
wr22::regex_parser::parser	9
wr22::regex_parser::parser::errors	10
wr22::regex_parser::regex	11
wr22::regex_parser::regex::capture	12
wr22::regex_parser::regex::part The namespace with the variants of Part	13
wr22::regex_parser::utils	14
wr22::regex_parser::utils::detail	16
wr22::regex_parser::utils::detail::adt	16

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

wr22::regex_parser::utils::Adt< Variants >	17
wr22::regex_parser::regex::Capture	25
wr22::regex_parser::regex::Part	42
wr22::regex_parser::regex::part::Alternatives	20
wr22::regex_parser::utils::Box< T >	21
wr22::regex_parser::utils::Box< wr22::regex_parser::regex::Part >	21
wr22::regex_parser::regex::part::Empty	26
std::exception	
wr22::regex_parser::utils::BoxIsEmpty	25
wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8	31
wr22::regex_parser::regex::part::Group	28
wr22::regex_parser::regex::capture::Index	30
wr22::regex_parser::regex::part::Literal	31
wr22::regex_parser::regex::capture::Name	33
wr22::regex_parser::regex::capture::None	35
wr22::regex_parser::regex::part::Optional	35
wr22::regex_parser::parser::Parser< Iter, Sentinel >	37
wr22::regex_parser::regex::part::Plus	43
std::runtime_error	
wr22::regex_parser::parser::errors::ParseError	37
wr22::regex_parser::parser::errors::ExpectedEnd	27
wr22::regex_parser::parser::errors::UnexpectedChar	46
wr22::regex_parser::parser::errors::UnexpectedEnd	48
wr22::regex_parser::regex::part::Sequence	44
wr22::regex_parser::regex::part::Star	45
wr22::regex_parser::utils::UnicodeStringView	49
wr22::regex_parser::utils::UnicodeStringViewIterator	51
wr22::regex_parser::utils::detail::adt::Fs	
wr22::regex_parser::utils::detail::adt::MultiCallable< Fs >	33

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

wr22::regex_parser::utils::Adt< Variants >	17
A helper class that simplifies creation of algebraic data types	
wr22::regex_parser::regex::part::Alternatives	20
A regex part with the list of alternatives to be matched	
wr22::regex_parser::utils::Box< T >	21
A copyable and equality-comparable wrapper around <code>std::unique_ptr</code>	
wr22::regex_parser::utils::BoxIsEmpty	25
wr22::regex_parser::regex::Capture	25
Group capture behavior	
wr22::regex_parser::regex::part::Empty	26
An empty regex part	
wr22::regex_parser::parser::errors::ExpectedEnd	27
The error when the parser expected the input to end, but it did not	
wr22::regex_parser::regex::part::Group	28
A regex part that represents a group in parentheses	
wr22::regex_parser::regex::capture::Index	30
Denotes a group captured by index	
wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8	31
An error thrown when the string's encoding is not valid UTF-8	
wr22::regex_parser::regex::part::Literal	31
An regex part that matches a single character literally	
wr22::regex_parser::utils::detail::adt::MultiCallable< Fs >	33
wr22::regex_parser::regex::capture::Name	33
Denotes a group captured by name	
wr22::regex_parser::regex::capture::None	35
Denotes an non-capturing group	
wr22::regex_parser::regex::part::Optional	35
A regex part specifying an optional quantifier <code>((expression)?)</code>	
wr22::regex_parser::parser::errors::ParseError	37
The base class for parse errors	
wr22::regex_parser::parser::Parser< Iter, Sentinel >	37
A regex parser	
wr22::regex_parser::regex::Part	42
A part of a regular expression and its AST node type	
wr22::regex_parser::regex::part::Plus	43
A regex part specifying an "at least one" quantifier <code>((expression)+)</code>	

wr22::regex_parser::regex::part::Sequence	
A regex part with the list of items to be matched one after another	44
wr22::regex_parser::regex::part::Star	
A regex part specifying an "at least zero" quantifier ((expression)*)	45
wr22::regex_parser::parser::errors::UnexpectedChar	
The error when the parser got a character it didn't expect at the current position	46
wr22::regex_parser::parser::errors::UnexpectedEnd	
The error when the parser hit the end of the input earlier than it expected	48
wr22::regex_parser::utils::UnicodeStringView	
A wrapper around <code>std::string_view</code> that enables UTF-8 codepoint iteration	49
wr22::regex_parser::utils::UnicodeStringViewIterator	
Iterator over code points for UnicodeStringView	51

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

include/wr22/regex_parser/parser/ errors.hpp	55
include/wr22/regex_parser/parser/ regex.hpp	56
include/wr22/regex_parser/regex/ capture.hpp	57
include/wr22/regex_parser/regex/ named_capture_flavor.hpp	58
include/wr22/regex_parser/regex/ part.hpp	59
include/wr22/regex_parser/utils/ adt.hpp	61
include/wr22/regex_parser/utils/ box.hpp	63
include/wr22/regex_parser/utils/ utf8_string_view.hpp	64
src/parser/ capture.cpp	65
src/parser/ errors.cpp	66
src/parser/ regex.cpp	66
src/regex/ named_capture_flavor.cpp	67
src/regex/ part.cpp	67
src/utils/ box.cpp	68
src/utils/ utf8_string_view.cpp	68

Chapter 5

Namespace Documentation

5.1 wr22 Namespace Reference

Namespaces

- namespace [regex_parser](#)

5.2 wr22::regex_parser Namespace Reference

Namespaces

- namespace [parser](#)
- namespace [regex](#)
- namespace [utils](#)

5.3 wr22::regex_parser::parser Namespace Reference

Namespaces

- namespace [errors](#)

Classes

- class [Parser](#)
A regex parser.

Functions

- template<typename Iter , typename Sentinel >
[Parser](#) (Iter begin, Sentinel end) -> [Parser](#)< Iter, Sentinel >
The type deduction guideline for [Parser](#).
- [regex::Part](#) [parse_regex](#) (const [utils::UnicodeStringView](#) ®ex)
Parse a regular expression into its AST.

5.3.1 Function Documentation

5.3.1.1 `parse_regex()`

```
regex::Part wr22::regex_parser::parser::parse_regex (
    const utils::UnicodeStringView & regex )
```

Parse a regular expression into its AST.

The regular expression is a string view in the UTF-8 encoding (the `utils::UnicodeStringView` wrapper is used for convenience and type safety; see its docs for additional information). It is parsed and its object representation (see the docs for `regex::Part`) is built. The returned representation is an owned object and its lifetime does not depend on the lifetime of the `regex` argument.

If the parsing fails, an exception is thrown. `errors::ParseError` is the base class for all exceptions thrown from this function, but more specific exceptions may be caught and handled separately. See the docs for the `errors.hpp` file for details.

Returns

the parsed regex AST if the parsing succeeds.

Exceptions

<code>errors::ParseError</code>	if the parsing fails.
---------------------------------	-----------------------

5.3.1.2 `Parser()`

```
template<typename Iter , typename Sentinel >
wr22::regex_parser::parser::Parser (
    Iter begin,
    Sentinel end ) -> Parser< Iter, Sentinel >
```

The type deduction guideline for `Parser`.

5.4 `wr22::regex_parser::parser::errors` Namespace Reference

Classes

- class `ExpectedEnd`
The error when the parser expected the input to end, but it did not.
- struct `ParseError`
The base class for parse errors.
- class `UnexpectedChar`
The error when the parser got a character it didn't expect at the current position.
- class `UnexpectedEnd`
The error when the parser hit the end of the input earlier than it expected.

5.5 wr22::regex_parser::regex Namespace Reference

Namespaces

- namespace [capture](#)
- namespace [part](#)

The namespace with the variants of [Part](#).

Classes

- class [Capture](#)

Group capture behavior.

- class [Part](#)

A part of a regular expression and its AST node type.

Enumerations

- enum class [NamedCaptureFlavor](#) { [Apostrophes](#) , [Angles](#) , [AnglesWithP](#) }

The flavor (dialect) of a named group capture.

Functions

- std::ostream & [operator<<](#) (std::ostream &out, const [Capture](#) &capture)
- std::ostream & [operator<<](#) (std::ostream &out, [NamedCaptureFlavor](#) flavor)
- std::ostream & [operator<<](#) (std::ostream &out, const [Part](#) &part)

Convert a [Part](#) to a textual representation and write it to an `std::ostream`.

5.5.1 Enumeration Type Documentation

5.5.1.1 NamedCaptureFlavor

```
enum class wr22::regex_parser::regex::NamedCaptureFlavor [strong]
```

The flavor (dialect) of a named group capture.

The most common variants are included. This list is subject to extension if deemed necessary. The source used as a reference is <https://www.regular-expressions.info/named.html>.

Enumerator

Apostrophes	The flavor (<code>? 'name' contents</code>). Mostly used in C# and other .NET-oriented languages, although can also be found in certain versions Perl, Boost and elsewhere.
Angles	The flavor (<code>?<name>contents</code>). Mostly used in C# and other .NET-oriented languages, although can also be found in certain versions Perl, Boost and elsewhere.
AnglesWithP	The flavor (<code>?P<name>contents</code>). Found in Python, PCRE and elsewhere.

5.5.2 Function Documentation

5.5.2.1 `operator<<()` [1/3]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    const Capture & capture )
```

5.5.2.2 `operator<<()` [2/3]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    const Part & part )
```

Convert a `Part` to a textual representation and write it to an `std::ostream`.

5.5.2.3 `operator<<()` [3/3]

```
std::ostream & wr22::regex_parser::regex::operator<< (
    std::ostream & out,
    NamedCaptureFlavor flavor )
```

5.6 `wr22::regex_parser::regex::capture` Namespace Reference

Classes

- struct `Index`
Denotes a group captured by index.
- struct `Name`
Denotes a group captured by name.
- struct `None`
Denotes an non-capturing group.

Typedefs

- using `Adt` = `utils::Adt< None, Index, Name >`

5.6.1 Typedef Documentation

5.6.1.1 Adt

```
using wr22::regex_parser::regex::capture::Adt = typedef utils::Adt<None, Index, Name>
```

5.7 wr22::regex_parser::regex::part Namespace Reference

The namespace with the variants of [Part](#).

Classes

- struct [Alternatives](#)
A regex part with the list of alternatives to be matched.
- struct [Empty](#)
An empty regex part.
- struct [Group](#)
A regex part that represents a group in parentheses.
- struct [Literal](#)
A regex part that matches a single character literally.
- struct [Optional](#)
A regex part specifying an optional quantifier $((expression)?)$.
- struct [Plus](#)
A regex part specifying an "at least one" quantifier $((expression)+)$.
- struct [Sequence](#)
A regex part with the list of items to be matched one after another.
- struct [Star](#)
A regex part specifying an "at least zero" quantifier $((expression)*)$.

Typedefs

- using [Adt](#) = [utils::Adt](#)< [Empty](#), [Literal](#), [Alternatives](#), [Sequence](#), [Group](#), [Optional](#), [Plus](#), [Star](#) >

5.7.1 Detailed Description

The namespace with the variants of [Part](#).

See the docs for the [Part](#) type for additional information.

5.7.2 Typedef Documentation

5.7.2.1 Adt

```
using wr22::regex_parser::regex::part::Adt = typedef utils::Adt<Empty, Literal, Alternatives, Sequence, Group, Optional, Plus, Star>
```

5.8 wr22::regex_parser::utils Namespace Reference

Namespaces

- namespace [detail](#)

Classes

- class [Adt](#)
A helper class that simplifies creation of algebraic data types.
- class [Box](#)
A copyable and equality-comparable wrapper around `std::unique_ptr`.
- struct [BoxIsEmpty](#)
- class [UnicodeStringView](#)
A wrapper around `std::string_view` that enables UTF-8 codepoint iteration.
- class [UnicodeStringViewIterator](#)
Iterator over code points for [UnicodeStringView](#).

Typedefs

- using [utf_traits](#) = boost::locale::utf::utf_traits< char >

Functions

- template<typename... Variants>
bool [operator==](#) (const [Adt](#)< Variants... > &lhs, const [Adt](#)< Variants... > &rhs)
Compare two compatible ADTs for equality.
- template<typename... Variants>
bool [operator!=](#) (const [Adt](#)< Variants... > &lhs, const [Adt](#)< Variants... > &rhs)
Compare two compatible ADTs for non-equality.
- template<typename T >
[Box](#) (T &&value) -> [Box](#)< T >
Type deduction guideline for [Box](#) (value initialization).
- template<typename T >
[Box](#) (std::unique_ptr< T > ptr) -> [Box](#)< T >
Type deduction guideline for [Box](#) (std::unique_ptr adoption).
- template<typename T, typename U >
bool [operator==](#) (const [Box](#)< T > &lhs, const [Box](#)< U > &rhs)
- template<typename T, typename U >
bool [operator!=](#) (const [Box](#)< T > &lhs, const [Box](#)< U > &rhs)

5.8.1 Typedef Documentation

5.8.1.1 utf_traits

```
using wr22::regex_parser::utils::utf_traits = typedef boost::locale::utf::utf_traits<char>
```


5.8.2 Function Documentation

5.8.2.1 Box() [1/2]

```
template<typename T >
wr22::regex_parser::utils::Box (
    std::unique_ptr< T > ptr ) -> Box< T >
```

Type deduction guideline for `Box` (`std::unique_ptr` adoption).

5.8.2.2 Box() [2/2]

```
template<typename T >
wr22::regex_parser::utils::Box (
    T && value ) -> Box< T >
```

Type deduction guideline for `Box` (value initialization).

5.8.2.3 operator!=() [1/2]

```
template<typename... Variants>
bool wr22::regex_parser::utils::operator!= (
    const Adt< Variants... > & lhs,
    const Adt< Variants... > & rhs )
```

Compare two compatible ADTs for non-equality.

5.8.2.4 operator!=() [2/2]

```
template<typename T , typename U >
bool wr22::regex_parser::utils::operator!= (
    const Box< T > & lhs,
    const Box< U > & rhs )
```

5.8.2.5 operator==() [1/2]

```
template<typename... Variants>
bool wr22::regex_parser::utils::operator== (
    const Adt< Variants... > & lhs,
    const Adt< Variants... > & rhs )
```

Compare two compatible ADTs for equality.

5.8.2.6 `operator==()` [2/2]

```
template<typename T , typename U >
bool wr22::regex_parser::utils::operator== (
    const Box< T > & lhs,
    const Box< U > & rhs )
```

5.9 `wr22::regex_parser::utils::detail` Namespace Reference

Namespaces

- namespace [adt](#)

5.10 `wr22::regex_parser::utils::detail::adt` Namespace Reference

Classes

- struct [MultiCallable](#)

Chapter 6


Class Documentation

6.1 wr22::regex_parser::utils::Adt< Variants > Class Template Reference

A helper class that simplifies creation of algebraic data types.

```
#include <adt.hpp>
```

Inheritance diagram for wr22::regex_parser::utils::Adt< Variants >:



Public Types

- using `VariantType` = `std::variant< Variants... >`
A convenience type alias for the concrete `std::variant` type used.

Public Member Functions

- template<typename V >
`Adt` (V variant)
Constructor for each of the variants.
- template<typename... Fs>
`decltype(auto)` `visit` (Fs &&... visitors) `const`
Visit the ADT, applying the suitable function from the list of visitors on the variant held.
- template<typename... Fs>
`decltype(auto)` `visit` (Fs &&... visitors)
Visit the ADT, applying the suitable function from the list of visitors on the variant held.
- `const` `VariantType` & `as_variant` () `const`
Access the underlying `std::variant` type (constant version).
- `VariantType` & `as_variant` ()
Access the underlying `std::variant` type (non-constant version).

Protected Attributes

- [VariantType m_variant](#)

6.1.1 Detailed Description

```
template<typename... Variants>
class wr22::regex_parser::utils::Adt< Variants >
```

A helper class that simplifies creation of algebraic data types.

Algebraic data types are data types that can have one type of a predefined set of variants, but be stored and represented as values of one common type. In C++, `std::variant` serves exactly this purpose. It is, however, not very convenient to work with or build upon, so this class is designed to simplify building new algebraic data types. It still uses `std::variant` under the hood.

The template type parameters are the types that the variants may hold (must be distinct types).

6.1.2 Member Typedef Documentation

6.1.2.1 VariantType

```
template<typename... Variants>
using wr22::regex_parser::utils::Adt< Variants >::VariantType = std::variant<Variants...>
```

A convenience type alias for the concrete `std::variant` type used.

6.1.3 Constructor & Destructor Documentation

6.1.3.1 Adt()

```
template<typename... Variants>
template<typename V >
wr22::regex_parser::utils::Adt< Variants >::Adt (
    V variant ) [inline]
```

Constructor for each of the variants.

Construct an instance holding a specified variant. The type `V` of the variant provided must be one of the types from `Variants`. Note that this constructor is purposefully implicit, so that the variants as separate types are transparently converted to this common type when necessary.

The variant is taken by value and moved thereafter, so that, when constructing the common type, the variant may be either copied or moved, depending on the user's intentions.

6.1.4 Member Function Documentation

6.1.4.1 as_variant() [1/2]

```
template<typename... Variants>
VariantType & wr22::regex_parser::utils::Adt< Variants >::as_variant ( ) [inline]
```

Access the underlying `std::variant` type (non-constant version).

6.1.4.2 as_variant() [2/2]

```
template<typename... Variants>
const VariantType & wr22::regex_parser::utils::Adt< Variants >::as_variant ( ) const [inline]
```

Access the underlying `std::variant` type (constant version).

6.1.4.3 visit() [1/2]

```
template<typename... Variants>
template<typename... Fs>
decltype(auto) wr22::regex_parser::utils::Adt< Variants >::visit (
    Fs &&... visitors ) [inline]
```

Visit the ADT, applying the suitable function from the list of visitors on the variant held.

This is the non-constant version of the method. See the docs for the constant version for a detailed description and code examples. The only thing different in this version of the method is that the visitors get called with a non-const lvalue reference to the variants instead of a const reference.

6.1.4.4 visit() [2/2]

```
template<typename... Variants>
template<typename... Fs>
decltype(auto) wr22::regex_parser::utils::Adt< Variants >::visit (
    Fs &&... visitors ) const [inline]
```

Visit the ADT, applying the suitable function from the list of visitors on the variant held.

Using this method is essentially the same as using `std::visit` on the variant, except that, for convenience, multiple visitors are joined into one big visitor. That is, a typical `Adt` usage might look like this:

```
struct MyAdt : public Adt<int, double> {
    // Make the constructor available in the derived class.
    using Adt<int, double>::Adt;
};
// <...>
void func() {
    // Variant type: double.
    MyAdt my_adt = 3.14;
    // Prints "Double: 3.14".
    my_adt.visit(
        [](int x) { std::cout << "Int: " << x << std::endl; },
        [](double x) { std::cout << "Double: " << x << std::endl; }
    );
}
```

This is the constant version of the method. Visitors must be callable with the const reference to variant types.

6.1.5 Member Data Documentation

6.1.5.1 m_variant

```
template<typename... Variants>
VariantType wr22::regex_parser::utils::Adt< Variants >::m_variant [protected]
```

The documentation for this class was generated from the following file:

- include/wr22/regex_parser/utils/[adt.hpp](#)

6.2 wr22::regex_parser::regex::part::Alternatives Struct Reference

A regex part with the list of alternatives to be matched.

```
#include <part.hpp>
```

Public Member Functions

- [Alternatives](#) (std::vector< [Part](#) > [alternatives](#))
- bool [operator==](#) (const [Alternatives](#) &rhs) const =default

Public Attributes

- std::vector< [Part](#) > [alternatives](#)
The list of the alternatives.

6.2.1 Detailed Description

A regex part with the list of alternatives to be matched.

[Alternatives](#) in regular expressions are subexpressions by `|`. For the whole expression part's match to succeed, at least one of the subexpressions must match the input successfully.

As an example, `a| (b) |cde` would be represented as an [Alternatives](#) part with 3 alternatives. The alternatives themselves are represented recursively as [Parts](#).

6.2.2 Constructor & Destructor Documentation

6.2.2.1 Alternatives()

```
wr22::regex_parser::regex::part::Alternatives::Alternatives (
    std::vector< Part > alternatives ) [explicit]
```

6.2.3 Member Function Documentation

6.2.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Alternatives::operator== (
    const Alternatives & rhs ) const [default]
```

6.2.4 Member Data Documentation

6.2.4.1 alternatives

```
std::vector<Part> wr22::regex_parser::regex::part::Alternatives::alternatives
```

The list of the alternatives.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.3 wr22::regex_parser::utils::Box< T > Class Template Reference

A copyable and equality-comparable wrapper around `std::unique_ptr`.

```
#include <box.hpp>
```

Public Member Functions

- `Box (T &&value)`
Constructor that places a value inside the wrapped `std::unique_ptr`.
- `Box (std::unique_ptr< T > ptr)`
Constructor that adopts an existing `std::unique_ptr`.
- `template<typename Dummy = T>`
`Box (const Box &other)`
Copy constructor.
- `const T & operator* () const`
Dereferencing operator: obtain a const reference to the stored value.
- `T & operator* ()`
Dereferencing operator: obtain a reference to the stored value.

Static Public Member Functions

- `template<typename... Args>`
`static Box< T > construct_in_place (Args &&... args)`
Construct a value on the heap in place.

6.3.1 Detailed Description

```
template<typename T>
class wr22::regex_parser::utils::Box< T >
```

A copyable and equality-comparable wrapper around `std::unique_ptr`.

The behavior of this wrapper regarding copying and equality comparison are akin to that of Rust's `std::boxed::Box`, and hence the class's name. Namely, when testing for (in)equality, the wrapped values are compared instead of raw pointers, and, when wrapped values are copyable, copying a `Box` creates another `std::unique_ptr` with a copy of the wrapped value.

A `Box` usually contains a value. However, it may become empty when it is moved from. To ensure safety, most operations on an empty box will throw a `BoxIsEmpty` exception instead of causing undefined behavior.

6.3.2 Constructor & Destructor Documentation

6.3.2.1 `Box()` [1/3]

```
template<typename T >
wr22::regex_parser::utils::Box< T >::Box (
    T && value ) [inline], [explicit]
```

Constructor that places a value inside the wrapped `std::unique_ptr`.

Takes the value by a universal reference and, due to perfect forwarding, both copy and move initialization is possible.

6.3.2.2 `Box()` [2/3]

```
template<typename T >
wr22::regex_parser::utils::Box< T >::Box (
    std::unique_ptr< T > ptr ) [inline], [explicit]
```

Constructor that adopts an existing `std::unique_ptr`.

Takes the `std::unique_ptr` by value, so the latter must be either passed directly as an rvalue or `std::move()` d into the argument. However, please note that if your code snippet looks like this:
`Box(std::make_unique<T>(args...))`

Then you should take a look at the `construct_in_place` method:
`Box<T>::construct_in_place(args...)`

6.3.2.3 Box() [3/3]

```
template<typename T >
template<typename Dummy = T>
wr22::regex_parser::utils::Box< T >::Box (
    const Box< T > & other ) [inline]
```

Copy constructor.

Creates another `std::unique_ptr` with a copy of the currently wrapped value.

Parameters

<code>`other`</code>	the Box from which to copy.
----------------------	---

Exceptions

BoxIsEmpty	if <code>other</code> is empty.
----------------------------	---------------------------------

6.3.3 Member Function Documentation

6.3.3.1 `construct_in_place()`

```
template<typename T >
template<typename... Args>
static Box< T > wr22::regex\_parser::utils::Box< T >::construct_in_place (
    Args &&... args ) [inline], [static]
```

Construct a value on the heap in place.

Forwards the arguments to `std::make_unique` and wraps the resulting `std::unique_ptr`.

6.3.3.2 `operator*()` [1/2]

```
template<typename T >
T & wr22::regex\_parser::utils::Box< T >::operator* ( ) [inline]
```

Dereferencing operator: obtain a reference to the stored value.

Exceptions

BoxIsEmpty	if this Box does not contain a value at the moment.
----------------------------	---

6.3.3.3 `operator*()` [2/2]

```
template<typename T >
const T & wr22::regex\_parser::utils::Box< T >::operator* ( ) const [inline]
```

Dereferencing operator: obtain a const reference to the stored value.

Exceptions

BoxIsEmpty	if this Box does not contain a value at the moment.
----------------------------	---


The documentation for this class was generated from the following file:

- include/wr22/regex_parser/utils/[box.hpp](#)

6.4 wr22::regex_parser::utils::BoxIsEmpty Struct Reference

```
#include <box.hpp>
```

Inheritance diagram for wr22::regex_parser::utils::BoxIsEmpty:



Public Member Functions

- const char * [what](#) () const noexcept override

6.4.1 Member Function Documentation

6.4.1.1 what()

```
const char * wr22::regex_parser::utils::BoxIsEmpty::what ( ) const [override], [noexcept]
```

The documentation for this struct was generated from the following files:


- include/wr22/regex_parser/utils/[box.hpp](#)
- src/utils/[box.cpp](#)

6.5 wr22::regex_parser::regex::Capture Class Reference

Group capture behavior.

```
#include <capture.hpp>
```

Inheritance diagram for wr22::regex_parser::regex::Capture:



Additional Inherited Members

6.5.1 Detailed Description

Group capture behavior.

A group can be captured by index (when one writes `(contents)`), by name (e.g. `(?<name>contents)` in some dialects) or not captured at all (`(?:contents)`). Objects of this type determine how exactly a certain group is going to be captured. This is a variant type (see [Part](#) and [utils::Adt](#) for a more detailed explanation of the concept). The variants for this class (explicitly or implicitly convertible to this type) are located in the `capture` namespace.

The documentation for this class was generated from the following file:

- `include/wr22/regex_parser/regex/capture.hpp`

6.6 wr22::regex_parser::regex::part::Empty Struct Reference

An empty regex part.

```
#include <part.hpp>
```

Public Member Functions

- [Empty](#) ()=default
- bool [operator==](#) (const [Empty](#) &rhs) const =default

6.6.1 Detailed Description

An empty regex part.

Corresponds to an empty regular expression `(" ")` or the contents of an empty parenthesized group `(" () ")`.

6.6.2 Constructor & Destructor Documentation

6.6.2.1 Empty()

```
wr22::regex_parser::regex::part::Empty::Empty ( ) [explicit], [default]
```

6.6.3 Member Function Documentation

6.6.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Empty::operator== (
    const Empty & rhs ) const [default]
```

The documentation for this struct was generated from the following file:


- include/wr22/regex_parser/regex/part.hpp

6.7 wr22::regex_parser::parser::errors::ExpectedEnd Class Reference

The error when the parser expected the input to end, but it did not.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::ExpectedEnd:



Public Member Functions

- [ExpectedEnd](#) (size_t position, char32_t char_got)
Constructor.
- size_t position () const
Get the input position. See the constructor docs for a more detailed description.
- char32_t char_got () const
Get the character the parser has received.

6.7.1 Detailed Description

The error when the parser expected the input to end, but it did not.

6.7.2 Constructor & Destructor Documentation

6.7.2.1 ExpectedEnd()

```
wr22::regex_parser::parser::errors::ExpectedEnd::ExpectedEnd (
    size_t position,
    char32_t char_got )
```

Constructor.

Parameters

<i>position</i>	the 0-based position in the input when the parser has encountered the end of input.
<i>char_got</i>	the character that the parser has received instead of the end of input.

6.7.3 Member Function Documentation

6.7.3.1 char_got()

```
char32_t wr22::regex_parser::parser::errors::ExpectedEnd::char_got ( ) const
```

Get the character the parser has received.

See the constructor docs for a more detailed description.

6.7.3.2 position()

```
size_t wr22::regex_parser::parser::errors::ExpectedEnd::position ( ) const
```

Get the input position. See the constructor docs for a more detailed description.

The documentation for this class was generated from the following files:

- [include/wr22/regex_parser/parser/errors.hpp](#)
- [src/parser/errors.cpp](#)

6.8 wr22::regex_parser::regex::part::Group Struct Reference

A regex part that represents a group in parentheses.

```
#include <part.hpp>
```

Public Member Functions

- [Group](#) ([Capture capture](#), [Part inner](#))
Convenience constructor.
- bool [operator==](#) (const [Group](#) &rhs) const =default

Public Attributes

- [Capture capture](#)
[Capture](#) behavior.
- [utils::Box](#)< [Part](#) > [inner](#)
The smart pointer to the group contents.

6.8.1 Detailed Description

A regex part that represents a group in parentheses.

A group in regular expressions is virtually everything that is enclosed with parentheses: (some group), (?↵:blablabla) and (?P<group_name>group contents) are all groups.

A group has two main attributes: (1) how it is captured during matching and (2) the contents of the group. The contents is simply another [Part](#). The capture behavior is expressed by a separate type [Capture](#). See its docs for additional info, and take a look at <https://www.regular-expressions.info/brackets.html> for an introduction to or a recap of regex groups and capturing.

6.8.2 Constructor & Destructor Documentation

6.8.2.1 Group()

```
wr22::regex_parser::regex::part::Group::Group (  
    Capture capture,  
    Part inner ) [explicit]
```

Convenience constructor.

6.8.3 Member Function Documentation

6.8.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Group::operator== (  
    const Group & rhs ) const [default]
```

6.8.4 Member Data Documentation

6.8.4.1 capture

[Capture](#) wr22::regex_parser::regex::part::Group::capture

[Capture](#) behavior.

6.8.4.2 inner

```
utils::Box<Part> wr22::regex_parser::regex::part::Group::inner
```

The smart pointer to the group contents.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/[part.hpp](#)
- src/regex/[part.cpp](#)

6.9 wr22::regex_parser::regex::capture::Index Struct Reference

Denotes a group captured by index.

```
#include <capture.hpp>
```

Public Member Functions

- [Index](#) ()=default
- bool [operator==](#) (const [Index](#) &rhs) const =default

6.9.1 Detailed Description

Denotes a group captured by index.

6.9.2 Constructor & Destructor Documentation

6.9.2.1 Index()

```
wr22::regex_parser::regex::capture::Index::Index ( ) [explicit], [default]
```

6.9.3 Member Function Documentation

6.9.3.1 operator==()

```
bool wr22::regex_parser::regex::capture::Index::operator== (
    const Index & rhs ) const [default]
```

The documentation for this struct was generated from the following file:


- include/wr22/regex_parser/regex/[capture.hpp](#)

6.10 wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8 Struct Reference

An error thrown when the string's encoding is not valid UTF-8.

```
#include <utf8_string_view.hpp>
```

Inheritance diagram for wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8:



Public Member Functions

- const char * [what](#) () const noexcept override

6.10.1 Detailed Description

An error thrown when the string's encoding is not valid UTF-8.

6.10.2 Member Function Documentation

6.10.2.1 what()

```
const char * wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8::what ( ) const [override],
[noexcept]
```

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/utils/[utf8_string_view.hpp](#)
- src/utils/[utf8_string_view.cpp](#)

6.11 wr22::regex_parser::regex::part::Literal Struct Reference

An regex part that matches a single character literally.

```
#include <part.hpp>
```

Public Member Functions

- [Literal](#) (char32_t [character](#))
- bool [operator==](#) (const [Literal](#) &rhs) const =default

Public Attributes

- char32_t [character](#)

6.11.1 Detailed Description

An regex part that matches a single character literally.

Corresponds to a plain character in a regular expression. E.g. the regex "foo" contains three character literals: f, o and o.

6.11.2 Constructor & Destructor Documentation

6.11.2.1 Literal()

```
wr22::regex_parser::regex::part::Literal::Literal (
    char32_t character ) [explicit]
```

6.11.3 Member Function Documentation

6.11.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Literal::operator== (
    const Literal & rhs ) const [default]
```

6.11.4 Member Data Documentation

6.11.4.1 character

```
char32_t wr22::regex_parser::regex::part::Literal::character
```


The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/[part.hpp](#)
- src/regex/[part.cpp](#)

6.12 wr22::regex_parser::utils::detail::adt::MultiCallable< Fs > Struct Template Reference

```
#include <adt.hpp>
```

Inheritance diagram for wr22::regex_parser::utils::detail::adt::MultiCallable< Fs >:



Public Member Functions

- [MultiCallable](#) (Fs &&... fs)

6.12.1 Constructor & Destructor Documentation

6.12.1.1 MultiCallable()

```
template<typename... Fs>
wr22::regex_parser::utils::detail::adt::MultiCallable< Fs >::MultiCallable (
    Fs &&... fs ) [inline]
```

The documentation for this struct was generated from the following file:

- include/wr22/regex_parser/utils/[adt.hpp](#)

6.13 wr22::regex_parser::regex::capture::Name Struct Reference

Denotes a group captured by name.

```
#include <capture.hpp>
```

Public Member Functions

- [Name](#) (std::string name, [NamedCaptureFlavor](#) flavor)
- bool [operator==](#) (const [Name](#) &rhs) const =default

Public Attributes

- std::string name
- [NamedCaptureFlavor](#) flavor

6.13.1 Detailed Description

Denotes a group captured by name.

A specific name and the syntax variant for this name's specification (see `NamedCaptureFlavor`) are stored.

6.13.2 Constructor & Destructor Documentation

6.13.2.1 Name()

```
wr22::regex_parser::regex::capture::Name::Name (
    std::string name,
    NamedCaptureFlavor flavor ) [explicit]
```

6.13.3 Member Function Documentation

6.13.3.1 operator==()

```
bool wr22::regex_parser::regex::capture::Name::operator== (
    const Name & rhs ) const [default]
```

6.13.4 Member Data Documentation

6.13.4.1 flavor

```
NamedCaptureFlavor wr22::regex_parser::regex::capture::Name::flavor
```

6.13.4.2 name

```
std::string wr22::regex_parser::regex::capture::Name::name
```

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/capture.hpp
- src/parser/capture.cpp

6.14 wr22::regex_parser::regex::capture::None Struct Reference

Denotes an non-capturing group.

```
#include <capture.hpp>
```

Public Member Functions

- [None](#) ()=default
- bool [operator==](#) (const [None](#) &rhs) const =default

6.14.1 Detailed Description

Denotes an non-capturing group.

6.14.2 Constructor & Destructor Documentation

6.14.2.1 None()

```
wr22::regex_parser::regex::capture::None::None ( ) [explicit], [default]
```

6.14.3 Member Function Documentation

6.14.3.1 operator==()

```
bool wr22::regex_parser::regex::capture::None::operator== (
    const None & rhs ) const [default]
```

The documentation for this struct was generated from the following file:

- include/wr22/regex_parser/regex/[capture.hpp](#)

6.15 wr22::regex_parser::regex::part::Optional Struct Reference

A regex part specifying an optional quantifier (`(expression)?`).

```
#include <part.hpp>
```

Public Member Functions

- [Optional](#) ([Part](#) *inner*)
Convenience constructor.
- bool [operator==](#) (const [Optional](#) &*rhs*) const =default

Public Attributes

- [utils::Box](#)< [Part](#) > *inner*
The smart pointer to the subexpression under the quantifier.

6.15.1 Detailed Description

A regex part specifying an optional quantifier ((*expression*) ?).

6.15.2 Constructor & Destructor Documentation

6.15.2.1 Optional()

```
wr22::regex_parser::regex::part::Optional::Optional (
    Part inner ) [explicit]
```

Convenience constructor.

6.15.3 Member Function Documentation

6.15.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Optional::operator== (
    const Optional & rhs ) const [default]
```

6.15.4 Member Data Documentation

6.15.4.1 inner

```
utils::Box<Part> wr22::regex_parser::regex::part::Optional::inner
```

The smart pointer to the subexpression under the quantifier.

The documentation for this struct was generated from the following files:


- include/wr22/regex_parser/regex/[part.hpp](#)
- src/regex/[part.cpp](#)

6.16 wr22::regex_parser::parser::errors::ParseError Struct Reference

The base class for parse errors.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::ParseError:



6.16.1 Detailed Description

The base class for parse errors.

This exception type should be caught if it is desired to catch all parse errors. However, there are more specific exceptions deriving from this one that can be handled separately for greater flexibility.

The documentation for this struct was generated from the following file:

- include/wr22/regex_parser/parser/[errors.hpp](#)

6.17 wr22::regex_parser::parser::Parser<Iter, Sentinel> Class Template Reference

A regex parser.

Public Member Functions

- [Parser](#) (Iter begin, Sentinel end)
Constructor.
- void [expect_end](#) ()
Ensure that the parser has consumed all of the input.
- [regex::Part](#) [parse_regex](#) ()
Parse a regex consuming part of the remaining input.
- [regex::Part](#) [parse_alternatives](#) ()
Intermediate rule: parse a pipe-separated list of alternatives (e.g.
- [regex::Part](#) [parse_sequence](#) ()
Intermediate rule: parse a sequence of atoms (e.g.
- [regex::Part](#) [parse_sequence_or_empty](#) ()
Intermediate rule: parse a possibly empty sequence of atoms.
- [regex::Part](#) [parse_atom](#) ()
Intermediate rule: parse an atom.
- [regex::Part](#) [parse_char_literal](#) ()
Intermediate rule: parse a character literal.
- [regex::Part](#) [parse_group](#) ()
Intermediate rule: parse a parenthesized group (any capture variant).
- std::string [parse_group_name](#) ()
Intermediate rule: parse a group name.

6.17.1 Detailed Description

```
template<typename Iter, typename Sentinel>
requires requires(Iter iter, Sentinel end) { ++iter; { *iter } -> std::convertible_to<char32_t>; { iter == end } -> std::convertible_to<bool>; { iter != end } -> std::convertible_to<bool>; }
class wr22::regex_parser::parser::Parser< Iter, Sentinel >
```

A regex parser.

For additional information see the methods' docs, particularly the constructor and the `parse_regex` method.

6.17.2 Constructor & Destructor Documentation

6.17.2.1 Parser()

```
template<typename Iter , typename Sentinel >
wr22::regex_parser::parser::Parser< Iter, Sentinel >::Parser (
    Iter begin,
    Sentinel end ) [inline]
```

Constructor.

This constructor stores a pair of forward iterators that should generate a sequence of Unicode code points (`char32_t`). The `begin` iterator and the `end` sentinel may have different types provided that the iterator can be equality comparable with the sentinel.

SAFETY: The iterators must not be invalidated as long as this [Parser](#) object is still alive.

6.17.3 Member Function Documentation

6.17.3.1 expect_end()

```
template<typename Iter , typename Sentinel >
void wr22::regex_parser::parser::Parser< Iter, Sentinel >::expect_end ( ) [inline]
```

Ensure that the parser has consumed all of the input.

Does nothing if all input has been consumed.

Exceptions

<code>errors::ExpectedEnd</code>	if this is not the case.
----------------------------------	--------------------------

6.17.3.2 parse_alternatives()

```
template<typename Iter , typename Sentinel >
regex::Part wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_alternatives ( )
[inline]
```

Intermediate rule: parse a pipe-separated list of alternatives (e.g.

`a|bb|ccc`).

Returns

the list of parsed alternatives packed into `regex::part::Alternatives` or, if and only if the list of alternatives contains exactly 1 element, the only alternative unchanged.

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.17.3.3 parse_atom()

```
template<typename Iter , typename Sentinel >
regex::Part wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_atom ( ) [inline]
```

Intermediate rule: parse an atom.

Currently, this grammar only recognizes two kinds of atoms: character literals (individual plain characters in a regex) and parenthesized groups. As the project development goes on, new kinds of atoms will be added.

Returns

the parsed atom (some variant of `regex::Part` depending on the atom kind).

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.17.3.4 parse_char_literal()

```
template<typename Iter , typename Sentinel >
regex::Part wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_char_literal ( )
[inline]
```

Intermediate rule: parse a character literal.

Returns

the parsed character literal (`regex::part::Literal`).

Exceptions

<code>errors::UnexpectedEnd</code>	if all characters from the input have already been consumed.
------------------------------------	--

6.17.3.5 parse_group()

```
template<typename Iter , typename Sentinel >
regex::Part wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_group ( ) [inline]
```

Intermediate rule: parse a parenthesized group (any capture variant).

Returns

the parsed group (`regex::part::Group`).

6.17.3.6 parse_group_name()

```
template<typename Iter , typename Sentinel >
std::string wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_group_name ( ) [inline]
```

Intermediate rule: parse a group name.

Returns

the UTF-8 encoded group name as an `std::string`.

6.17.3.7 parse_regex()

```
template<typename Iter , typename Sentinel >
regex::Part wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_regex ( ) [inline]
```

Parse a regex consuming part of the remaining input.

This is **the** method that should be called to parse a regular expression because it represents the root rule of the regex grammar. Please note that this method may not consume all of the parser's input. Hence, if a whole regex is to be parsed, the `expect_end` method should be called afterwards.

Returns

the parsed regex AST (some variant of `regex::Part` depending on the input).

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.17.3.8 parse_sequence()

```
template<typename Iter , typename Sentinel >
regex::Part wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_sequence ( ) [inline]
```

Intermediate rule: parse a sequence of atoms (e.g.

`a(?:b) [c-e]`).

Returns

the list of parsed atoms packed into `regex::part::Sequence` or, if and only if this list of contains exactly 1 element, the only atom unchanged.

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

6.17.3.9 parse_sequence_or_empty()

```
template<typename Iter , typename Sentinel >
regex::Part wr22::regex_parser::parser::Parser< Iter, Sentinel >::parse_sequence_or_empty ( )
[inline]
```

Intermediate rule: parse a possibly empty sequence of atoms.

Returns

`regex::part::Empty` if the sequence is empty, or calls `parse_sequence` otherwise.

Exceptions

<code>errors::ParseError</code>	if the input cannot be parsed.
---------------------------------	--------------------------------

The documentation for this class was generated from the following file:


- `src/parser/regex.cpp`

6.18 wr22::regex_parser::regex::Part Class Reference

A part of a regular expression and its AST node type.

```
#include <part.hpp>
```

Inheritance diagram for `wr22::regex_parser::regex::Part`:



Additional Inherited Members

6.18.1 Detailed Description

A part of a regular expression and its AST node type.

The parsed regular expressions are represented as abstract syntax trees (ASTs). These are tree-like data structures where each node represents a regular expression part (or the whole regex), and, depending on their type, these nodes may have subexpressions. Subexpressions are `Parts` themselves, which also have child expressions and so on. For example, `part::Sequence` has a number of subexpressions, and each of them is of the type `Part` and is an AST node.

Each regex part has its own simple function. For example, `part::Alternatives` tries to match several alternative subexpressions against the input and succeeds if at least one of them does; and `part::Sequence` matches several subexpressions one after another, requiring them all to match respective parts of the input. By combining these simple nodes, it becomes possible to represent complex regular expressions. For example, the regex `aaa|bb` can be represented as a `part::Alternatives`, where each of the alternatives is a `parts::Sequence` of `part::Literals`.

The `Part` itself is represented by `std::variant` via the helper class `utils::Adt`. In a nutshell, it allows a regex part to "have" one of the several predefined types (the so-called variants, which are defined in the `part` namespace), but still be represented as a `Part`. For the list of operations that can be performed on this type, e.g. to check if an instance of `Parts` has a specific variant and, if yes, access the value of this variant, see the documentation for the `utils::Adt` class, which `Part` inherits from.

The documentation for this class was generated from the following file:

- `include/wr22/regex_parser/regex/part.hpp`

6.19 wr22::regex_parser::regex::part::Plus Struct Reference

A regex part specifying an "at least one" quantifier ((expression) +).

```
#include <part.hpp>
```

Public Member Functions

- [Plus](#) ([Part](#) inner)
Convenience constructor.
- bool [operator==](#) (const [Plus](#) &rhs) const =default

Public Attributes

- [utils::Box](#)< [Part](#) > inner
The smart pointer to the subexpression under the quantifier.

6.19.1 Detailed Description

A regex part specifying an "at least one" quantifier ((expression) +).

6.19.2 Constructor & Destructor Documentation

6.19.2.1 Plus()

```
wr22::regex_parser::regex::part::Plus::Plus (  
    Part inner ) [explicit]
```

Convenience constructor.

6.19.3 Member Function Documentation

6.19.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Plus::operator== (  
    const Plus & rhs ) const [default]
```

6.19.4 Member Data Documentation

6.19.4.1 inner

```
utils::Box<Part> wr22::regex_parser::regex::part::Plus::inner
```

The smart pointer to the subexpression under the quantifier.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.20 wr22::regex_parser::regex::part::Sequence Struct Reference

A regex part with the list of items to be matched one after another.

```
#include <part.hpp>
```

Public Member Functions

- [Sequence](#) (std::vector< [Part](#) > items)
- bool [operator==](#) (const [Sequence](#) &rhs) const =default

Public Attributes

- std::vector< [Part](#) > [items](#)
The list of the subexpressions.

6.20.1 Detailed Description

A regex part with the list of items to be matched one after another.

Sequences in regular expressions are just subexpressions going directly one after another. As an example, `a[b-e]` is a sequence of 3 subexpressions: `a`, `[b-e]` and `.`. As an another example, `ab` is a sequence of 2 subexpressions: `a` and `b`.

6.20.2 Constructor & Destructor Documentation

6.20.2.1 Sequence()

```
wr22::regex_parser::regex::part::Sequence::Sequence (
    std::vector< Part > items ) [explicit]
```

6.20.3 Member Function Documentation

6.20.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Sequence::operator== (
    const Sequence & rhs ) const [default]
```

6.20.4 Member Data Documentation

6.20.4.1 items

```
std::vector<Part> wr22::regex_parser::regex::part::Sequence::items
```

The list of the subexpressions.

The documentation for this struct was generated from the following files:

- include/wr22/regex_parser/regex/[part.hpp](#)
- src/regex/[part.cpp](#)

6.21 wr22::regex_parser::regex::part::Star Struct Reference

A regex part specifying an "at least zero" quantifier ((expression) *).

```
#include <part.hpp>
```

Public Member Functions

- [Star](#) ([Part](#) inner)
Convenience constructor.
- bool [operator==](#) (const [Star](#) &rhs) const =default

Public Attributes

- [utils::Box](#)< [Part](#) > inner
The smart pointer to the subexpression under the quantifier.

6.21.1 Detailed Description

A regex part specifying an "at least zero" quantifier ((expression) *).

6.21.2 Constructor & Destructor Documentation

6.21.2.1 Star()

```
wr22::regex_parser::regex::part::Star::Star (
    Part inner ) [explicit]
```

Convenience constructor.

6.21.3 Member Function Documentation

6.21.3.1 operator==()

```
bool wr22::regex_parser::regex::part::Star::operator== (
    const Star & rhs ) const [default]
```

6.21.4 Member Data Documentation

6.21.4.1 inner

```
utils::Box<Part> wr22::regex_parser::regex::part::Star::inner
```

The smart pointer to the subexpression under the quantifier.

The documentation for this struct was generated from the following files:


- include/wr22/regex_parser/regex/part.hpp
- src/regex/part.cpp

6.22 wr22::regex_parser::parser::errors::UnexpectedChar Class Reference

The error when the parser got a character it didn't expect at the current position.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::UnexpectedChar:



Public Member Functions

- [UnexpectedChar](#) (size_t [position](#), char32_t [char_got](#), std::string [expected](#))
Constructor.
- size_t [position](#) () const
Get the input position. See the constructor docs for a more detailed description.
- char32_t [char_got](#) () const
Get the character the parser has received.
- const std::string & [expected](#) () const
Get the description of expected characters.

6.22.1 Detailed Description

The error when the parser got a character it didn't expect at the current position.

6.22.2 Constructor & Destructor Documentation

6.22.2.1 UnexpectedChar()

```
wr22::regex_parser::parser::errors::UnexpectedChar::UnexpectedChar (
    size_t position,
    char32_t char_got,
    std::string expected )
```

Constructor.

Parameters

<i>position</i>	the 0-based position in the input when the parser has encountered the unexpected character.
<i>char_got</i>	the character that the parser has received.
<i>expected</i>	a textual description of a class of characters expected instead.

6.22.3 Member Function Documentation

6.22.3.1 char_got()

```
char32_t wr22::regex_parser::parser::errors::UnexpectedChar::char_got ( ) const
```

Get the character the parser has received.

See the constructor docs for a more detailed description.

6.22.3.2 expected()

```
const std::string & wr22::regex_parser::parser::errors::UnexpectedChar::expected ( ) const
```

Get the description of expected characters.

See the constructor docs for a more detailed description.

6.22.3.3 position()

```
size_t wr22::regex_parser::parser::errors::UnexpectedChar::position ( ) const
```

Get the input position. See the constructor docs for a more detailed description.

The documentation for this class was generated from the following files:


- include/wr22/regex_parser/parser/errors.hpp
- src/parser/errors.cpp

6.23 wr22::regex_parser::parser::errors::UnexpectedEnd Class Reference

The error when the parser hit the end of the input earlier than it expected.

```
#include <errors.hpp>
```

Inheritance diagram for wr22::regex_parser::parser::errors::UnexpectedEnd:



Public Member Functions

- [UnexpectedEnd](#) (size_t [position](#), std::string [expected](#))
Constructor.
- size_t [position](#) () const
Get the input position. See the constructor docs for a more detailed description.
- const std::string & [expected](#) () const
Get the description of expected characters.

6.23.1 Detailed Description

The error when the parser hit the end of the input earlier than it expected.

6.23.2 Constructor & Destructor Documentation

6.23.2.1 UnexpectedEnd()

```
wr22::regex_parser::parser::errors::UnexpectedEnd::UnexpectedEnd (
    size_t position,
    std::string expected )
```

Constructor.

Parameters

<i>position</i>	the 0-based position in the input when the parser has encountered the end of input.
<i>expected</i>	a textual description of a class of characters expected instead.

6.23.3 Member Function Documentation

6.23.3.1 expected()

```
const std::string & wr22::regex_parser::parser::errors::UnexpectedEnd::expected ( ) const
```

Get the description of expected characters.

See the constructor docs for a more detailed description.

6.23.3.2 position()

```
size_t wr22::regex_parser::parser::errors::UnexpectedEnd::position ( ) const
```

Get the input position. See the constructor docs for a more detailed description.

The documentation for this class was generated from the following files:

- include/wr22/regex_parser/parser/[errors.hpp](#)
- src/parser/[errors.cpp](#)

6.24 wr22::regex_parser::utils::UnicodeStringView Class Reference

A wrapper around `std::string_view` that enables UTF-8 codepoint iteration.

```
#include <utf8_string_view.hpp>
```

Classes

- struct [InvalidUtf8](#)
An error thrown when the string's encoding is not valid UTF-8.

Public Member Functions

- [UnicodeStringView](#) (const std::string_view &raw)
Constructor.
- const std::string_view & [raw](#) () const
Access the wrapped std::string_view.
- [UnicodeStringViewIterator](#) [begin](#) () const
Create an iterator to the beginning of the string.
- [UnicodeStringViewIterator](#) [end](#) () const
Create an iterator past the end of the string.

Friends

- class [UnicodeStringViewIterator](#)

6.24.1 Detailed Description

A wrapper around `std::string_view` that enables UTF-8 codepoint iteration.

An [UnicodeStringView](#) holds a "raw" `std::string_view` and assumes it is UTF-8 encoded. It provides the [begin\(\)](#) & [end\(\)](#) methods, which return iterators that work with Unicode codepoints instead of raw bytes. This makes this type useful in contexts where one needs to iterate over Unicode code points (like characters, but technically a different thing) in an `std::string` or an `std::string_view`.

6.24.2 Constructor & Destructor Documentation

6.24.2.1 UnicodeStringView()

```
wr22::regex_parser::utils::UnicodeStringView::UnicodeStringView (
    const std::string_view & raw ) [explicit]
```

Constructor.

Wrap an existing `std::string_view`.

The ownership of the data pointed to by `raw` is not taken, and the string contents are not copied. Hence, just like with an ordinary `std::string_view`, if the pointed data is invalidated, the [UnicodeStringView](#) referring to it is invalidated as well.

This constructor does not check that `raw` is a correct UTF-8 encoded string.

SAFETY: If the string contents change during the [UnicodeStringView](#)'s lifetime or the string is destroyed, the behavior is undefined.

6.24.3 Member Function Documentation

6.24.3.1 begin()

```
UnicodeStringViewIterator wr22::regex_parser::utils::UnicodeStringView::begin ( ) const
```

Create an iterator to the beginning of the string.

SAFETY: The returned iterator must not outlive this object.

6.24.3.2 end()

```
UnicodeStringViewIterator wr22::regex_parser::utils::UnicodeStringView::end ( ) const
```

Create an iterator past the end of the string.

SAFETY: The returned iterator must not outlive this object.

6.24.3.3 raw()

```
const std::string_view & wr22::regex_parser::utils::UnicodeStringView::raw ( ) const
```

Access the wrapped `std::string_view`.

6.24.4 Friends And Related Function Documentation

6.24.4.1 UnicodeStringViewIterator

```
friend class UnicodeStringViewIterator [friend]
```

The documentation for this class was generated from the following files:

- include/wr22/regex_parser/utils/utf8_string_view.hpp
- src/utils/utf8_string_view.cpp

6.25 wr22::regex_parser::utils::UnicodeStringViewIterator Class Reference

Iterator over code points for [UnicodeStringView](#).

```
#include <utf8_string_view.hpp>
```

Public Types

- using `value_type` = `char32_t`
The type of value this iterator yields. Part of the STL iterator interface.
- using `category_type` = `std::forward_iterator_tag`
This iterator's category. Part of the STL iterator interface.

Public Member Functions

- `UnicodeStringViewIterator` ()=delete
The default constructor is meaningless and is thus deleted.
- `UnicodeStringViewIterator` & `operator++` ()
Iterator interface: pre-increment.
- `char32_t` `operator*` ()
Iterator interface: dereferencing.
- bool `operator==` (const `UnicodeStringViewIterator` &rhs) const
- bool `operator!=` (const `UnicodeStringViewIterator` &rhs) const

Friends

- class `UnicodeStringView`

6.25.1 Detailed Description

Iterator over code points for `UnicodeStringView`.

SAFETY: No object of this class must outlive the `UnicodeStringView` that has created it. If this is violated, the behavior is undefined.

6.25.2 Member Typedef Documentation

6.25.2.1 `category_type`

```
using wr22::regex_parser::utils::UnicodeStringViewIterator::category_type = std::forward_iterator_tag
```

This iterator's category. Part of the STL iterator interface.

6.25.2.2 `value_type`

```
using wr22::regex_parser::utils::UnicodeStringViewIterator::value_type = char32_t
```

The type of value this iterator yields. Part of the STL iterator interface.

6.25.3 Constructor & Destructor Documentation

6.25.3.1 UnicodeStringViewIterator()

```
wr22::regex_parser::utils::UnicodeStringViewIterator::UnicodeStringViewIterator ( ) [delete]
```

The default constructor is meaningless and is thus deleted.

6.25.4 Member Function Documentation

6.25.4.1 operator"!==(())

```
bool wr22::regex_parser::utils::UnicodeStringViewIterator::operator!=(
    const UnicodeStringViewIterator & rhs ) const
```

6.25.4.2 operator*()

```
char32_t wr22::regex_parser::utils::UnicodeStringViewIterator::operator* ( )
```

Iterator interface: dereferencing.

Exceptions

<i>UnicodeStringView::InvalidUtf8</i>	if the codepoint decodes into an invalid or incomplete value.
---	---

6.25.4.3 operator++()

```
UnicodeStringViewIterator & wr22::regex_parser::utils::UnicodeStringViewIterator::operator++ (
)
```

Iterator interface: pre-increment.

Exceptions

<i>UnicodeStringView::InvalidUtf8</i>	if the codepoint decodes into an invalid or incomplete value.
---	---

6.25.4.4 operator==()

```
bool wr22::regex_parser::utils::UnicodeStringViewIterator::operator== (
    const UnicodeStringViewIterator & rhs ) const
```

6.25.5 Friends And Related Function Documentation

6.25.5.1 UnicodeStringView

```
friend class UnicodeStringView [friend]
```

The documentation for this class was generated from the following files:

- [include/wr22/regex_parser/utils/utf8_string_view.hpp](#)
- [src/utils/utf8_string_view.cpp](#)

Chapter 7

File Documentation

7.1 `include/wr22/regex_parser/parser/errors.hpp` File Reference

```
#include <exception>
#include <stdexcept>
#include <string>
```

Classes

- struct `wr22::regex_parser::parser::errors::ParseError`
The base class for parse errors.
- class `wr22::regex_parser::parser::errors::UnexpectedEnd`
The error when the parser hit the end of the input earlier than it expected.
- class `wr22::regex_parser::parser::errors::ExpectedEnd`
The error when the parser expected the input to end, but it did not.
- class `wr22::regex_parser::parser::errors::UnexpectedChar`
The error when the parser got a character it didn't expect at the current position.

Namespaces

- namespace `wr22`
- namespace `wr22::regex_parser`
- namespace `wr22::regex_parser::parser`
- namespace `wr22::regex_parser::parser::errors`

7.2 errors.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // STL
4 #include <exception>
5 #include <stdexcept>
6 #include <string>
7
8 namespace wr22::regex_parser::parser::errors {
9
10 struct ParseError : public std::runtime_error {
11     using std::runtime_error::runtime_error;
12 };
13
14 class UnexpectedEnd : public ParseError {
15 public:
16     UnexpectedEnd(size_t position, std::string expected);
17
18     size_t position() const;
19     const std::string& expected() const;
20 private:
21     size_t m_position;
22     std::string m_expected;
23 };
24
25 class ExpectedEnd : public ParseError {
26 public:
27     ExpectedEnd(size_t position, char32_t char_got);
28
29     size_t position() const;
30     char32_t char_got() const;
31 private:
32     size_t m_position;
33     char32_t m_char_got;
34 };
35
36 class UnexpectedChar : public ParseError {
37 public:
38     UnexpectedChar(size_t position, char32_t char_got, std::string expected);
39
40     size_t position() const;
41     char32_t char_got() const;
42     const std::string& expected() const;
43 private:
44     size_t m_position;
45     char32_t m_char_got;
46     std::string m_expected;
47 };
48 } // namespace wr22::regex_parser::parser::errors

```

7.3 include/wr22/regex_parser/parser/regex.hpp File Reference

```

#include <wr22/regex_parser/regex/part.hpp>
#include <wr22/regex_parser/utils/utf8_string_view.hpp>
#include <string_view>

```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::parser](#)

Functions

- `regex::Part wr22::regex_parser::parser::parse_regex` (`const utils::UnicodeStringView ®ex`)
Parse a regular expression into its AST.

7.4 regex.hpp

[Go to the documentation of this file.](#)

```
1 #pragma once
2
3 // wr22
4 #include <wr22/regex_parser/regex/part.hpp>
5 #include <wr22/regex_parser/utils/utf8_string_view.hpp>
6
7 // stl
8 #include <string_view>
9
10 namespace wr22::regex_parser::parser {
11
12     regex::Part parse_regex(const utils::UnicodeStringView& regex);
13
14 } // namespace wr22::regex_parser::parser
```

7.5 include/wr22/regex_parser/regex/capture.hpp File Reference

```
#include <wr22/regex_parser/regex/named_capture_flavor.hpp>
#include <wr22/regex_parser/utils/adt.hpp>
#include <iosfwd>
#include <string>
```

Classes

- struct `wr22::regex_parser::regex::capture::None`
Denotes an non-capturing group.
- struct `wr22::regex_parser::regex::capture::Index`
Denotes a group captured by index.
- struct `wr22::regex_parser::regex::capture::Name`
Denotes a group captured by name.
- class `wr22::regex_parser::regex::Capture`
Group capture behavior.

Namespaces

- namespace `wr22`
- namespace `wr22::regex_parser`
- namespace `wr22::regex_parser::regex`
- namespace `wr22::regex_parser::regex::capture`

Typedefs

- using `wr22::regex_parser::regex::capture::Adt` = `utils::Adt< None, Index, Name >`

Functions

- `std::ostream & wr22::regex_parser::regex::operator<<` (`std::ostream &out`, `const Capture &capture`)

7.6 capture.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // wr22
4 #include <wr22/regex_parser/regex/named_capture_flavor.hpp>
5 #include <wr22/regex_parser/utils/adt.hpp>
6
7 // stl
8 #include <iosfwd>
9 #include <string>
10
11 namespace wr22::regex_parser::regex {
12
13 class Capture;
14
15 namespace capture {
16     struct None {
17         explicit None() = default;
18         bool operator==(const None& rhs) const = default;
19     };
20
21     struct Index {
22         explicit Index() = default;
23         bool operator==(const Index& rhs) const = default;
24     };
25
26     struct Name {
27         explicit Name(std::string name, NamedCaptureFlavor flavor);
28
29         std::string name;
30         NamedCaptureFlavor flavor;
31         bool operator==(const Name& rhs) const = default;
32     };
33
34     using Adt = utils::Adt<None, Index, Name>;
35 } // namespace capture
36
37 //
38 class Capture : public capture::Adt {
39 public:
40     using capture::Adt::Adt;
41 };
42
43 std::ostream& operator<<(std::ostream& out, const Capture& capture);
44
45 } // namespace wr22::regex_parser::regex

```

7.7 include/wr22/regex_parser/regex/named_capture_flavor.hpp File Reference

```
#include <iosfwd>
```

Namespaces

- namespace `wr22`
- namespace `wr22::regex_parser`
- namespace `wr22::regex_parser::regex`

Enumerations

- enum class [wr22::regex_parser::regex::NamedCaptureFlavor](#) { [wr22::regex_parser::regex::Apostrophes](#) , [wr22::regex_parser::regex::Angles](#) , [wr22::regex_parser::regex::AnglesWithP](#) }

The flavor (dialect) of a named group capture.

Functions

- std::ostream & [wr22::regex_parser::regex::operator<<](#) (std::ostream &out, NamedCaptureFlavor flavor)

7.8 named_capture_flavor.hpp

[Go to the documentation of this file.](#)

```
1 #pragma once
2
3 // stl
4 #include <iosfwd>
5
6 namespace wr22::regex_parser::regex {
7
12 enum class NamedCaptureFlavor
13 {
16     Apostrophes,
19     Angles,
21     AnglesWithP,
22 };
23
24 std::ostream& operator<<(std::ostream& out, NamedCaptureFlavor flavor);
25
26 } // namespace wr22::regex_parser::regex
```

7.9 include/wr22/regex_parser/regex/part.hpp File Reference

```
#include <wr22/regex_parser/regex/capture.hpp>
#include <wr22/regex_parser/utils/adt.hpp>
#include <wr22/regex_parser/utils/box.hpp>
#include <iosfwd>
#include <memory>
#include <vector>
```

Classes

- struct [wr22::regex_parser::regex::part::Empty](#)
An empty regex part.
- struct [wr22::regex_parser::regex::part::Literal](#)
An regex part that matches a single character literally.
- struct [wr22::regex_parser::regex::part::Alternatives](#)
A regex part with the list of alternatives to be matched.
- struct [wr22::regex_parser::regex::part::Sequence](#)
A regex part with the list of items to be matched one after another.
- struct [wr22::regex_parser::regex::part::Group](#)
A regex part that represents a group in parentheses.
- struct [wr22::regex_parser::regex::part::Optional](#)

- *A regex part specifying an optional quantifier ((expression) ?).*
- struct `wr22::regex_parser::regex::part::Plus`
A regex part specifying an "at least one" quantifier ((expression) +).
- struct `wr22::regex_parser::regex::part::Star`
*A regex part specifying an "at least zero" quantifier ((expression) *).*
- class `wr22::regex_parser::regex::Part`
A part of a regular expression and its AST node type.

Namespaces

- namespace `wr22`
- namespace `wr22::regex_parser`
- namespace `wr22::regex_parser::regex`
- namespace `wr22::regex_parser::regex::part`
The namespace with the variants of `Part`.

Typedefs

- using `wr22::regex_parser::regex::part::Adt` = `utils::Adt< Empty, Literal, Alternatives, Sequence, Group, Optional, Plus, Star >`

Functions

- `std::ostream & wr22::regex_parser::regex::operator<< (std::ostream &out, const Part &part)`
Convert a `Part` to a textual representation and write it to an `std::ostream`.

7.10 part.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // wr22
4 #include <wr22/regex_parser/regex/capture.hpp>
5 #include <wr22/regex_parser/utils/adt.hpp>
6 #include <wr22/regex_parser/utils/box.hpp>
7
8 // stl
9 #include <iosfwd>
10 #include <memory>
11 #include <vector>
12
13 namespace wr22::regex_parser::regex {
14
15 // Forward declaration of 'Part'.
16 class Part;
17
18 namespace part {
19     struct Empty {
20         explicit Empty() = default;
21         bool operator==(const Empty& rhs) const = default;
22     };
23
24     struct Literal {
25         explicit Literal(char32_t character);
26         bool operator==(const Literal& rhs) const = default;
27         char32_t character;
28     };
29
30     struct Alternatives {
31         explicit Alternatives(std::vector<Part> alternatives);

```

```

52         bool operator==(const Alternatives& rhs) const = default;
53
54     std::vector<Part> alternatives;
55 };
56
57 struct Sequence {
58     explicit Sequence(std::vector<Part> items);
59     bool operator==(const Sequence& rhs) const = default;
60
61     std::vector<Part> items;
62 };
63
64 struct Group {
65     explicit Group(Capture capture, Part inner);
66     bool operator==(const Group& rhs) const = default;
67
68     Capture capture;
69     utils::Box<Part> inner;
70 };
71
72 struct Optional {
73     explicit Optional(Part inner);
74     bool operator==(const Optional& rhs) const = default;
75
76     utils::Box<Part> inner;
77 };
78
79 struct Plus {
80     explicit Plus(Part inner);
81     bool operator==(const Plus& rhs) const = default;
82
83     utils::Box<Part> inner;
84 };
85
86 struct Star {
87     explicit Star(Part inner);
88     bool operator==(const Star& rhs) const = default;
89
90     utils::Box<Part> inner;
91 };
92
93 using Adt = utils::Adt<Empty, Literal, Alternatives, Sequence, Group, Optional, Plus, Star>;
94 } // namespace part
95
96 class Part : public part::Adt {
97 public:
98     using part::Adt::Adt;
99 };
100
101 std::ostream& operator<<(std::ostream& out, const Part& part);
102
103 } // namespace wr22::regex_parser::regex

```

7.11 include/wr22/regex_parser/utils/adt.hpp File Reference

```

#include <utility>
#include <variant>

```

Classes

- struct [wr22::regex_parser::utils::detail::adt::MultiCallable< Fs >](#)
- class [wr22::regex_parser::utils::Adt< Variants >](#)
A helper class that simplifies creation of algebraic data types.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::utils](#)
- namespace [wr22::regex_parser::utils::detail](#)
- namespace [wr22::regex_parser::utils::detail::adt](#)

Functions

- `template<typename... Variants>`
`bool wr22::regex_parser::utils::operator== (const Adt< Variants... > &lhs, const Adt< Variants... > &rhs)`
Compare two compatible ADTs for equality.
- `template<typename... Variants>`
`bool wr22::regex_parser::utils::operator!= (const Adt< Variants... > &lhs, const Adt< Variants... > &rhs)`
Compare two compatible ADTs for non-equality.

7.12 adt.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // stl
4 #include <utility>
5 #include <variant>
6
7 namespace wr22::regex_parser::utils {
8
9 namespace detail::adt {
10     // https://en.cppreference.com/w/cpp/utility/variant/visit#Example provides a very similar
11     // example of C++ template black magic.
12     template <typename... Fs>
13     struct MultiCallable : public Fs... {
14         MultiCallable(Fs&&... fs) : Fs(fs)... {}
15         using Fs::operator()...;
16     };
17 } // namespace detail::adt
18
19 template <typename... Variants>
20 class Adt {
21 public:
22     using VariantType = std::variant<Variants...>;
23
24     template <typename V>
25     Adt(V variant) : m_variant(std::move(variant)) {}
26
27     template <typename... Fs>
28     decltype(auto) visit(Fs&&... visitors) const {
29         return std::visit(
30             detail::adt::MultiCallable<Fs...>(std::forward<Fs>(visitors)...),
31             m_variant);
32     }
33
34     template <typename... Fs>
35     decltype(auto) visit(Fs&&... visitors) {
36         return std::visit(
37             detail::adt::MultiCallable<Fs...>(std::forward<Fs>(visitors)...),
38             m_variant);
39     }
40
41     const VariantType& as_variant() const {
42         return m_variant;
43     }
44
45     VariantType& as_variant() {
46         return m_variant;
47     }
48
49 protected:
50     VariantType m_variant;
51 };
52
53 template <typename... Variants>
54 bool operator==(const Adt<Variants...>& lhs, const Adt<Variants...>& rhs) {
55     return lhs.as_variant() == rhs.as_variant();
56 }
57
58 template <typename... Variants>
59 bool operator!=(const Adt<Variants...>& lhs, const Adt<Variants...>& rhs) {
60     return !(lhs == rhs);
61 }
62
63 } // namespace wr22::regex_parser::utils

```


7.13 include/wr22/regex_parser/utils/box.hpp File Reference

```
#include <exception>
#include <memory>
#include <utility>
```

Classes

- struct [wr22::regex_parser::utils::BoxIsEmpty](#)
- class [wr22::regex_parser::utils::Box< T >](#)
A copyable and equality-comparable wrapper around `std::unique_ptr`.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::utils](#)

Functions

- template<typename T >
[wr22::regex_parser::utils::Box](#) (T &&value) -> Box< T >
Type deduction guideline for [Box](#) (value initialization).
- template<typename T >
[wr22::regex_parser::utils::Box](#) (std::unique_ptr< T > ptr) -> Box< T >
Type deduction guideline for [Box](#) (std::unique_ptr adoption).
- template<typename T, typename U >
bool [wr22::regex_parser::utils::operator==](#) (const Box< T > &lhs, const Box< U > &rhs)
- template<typename T, typename U >
bool [wr22::regex_parser::utils::operator!=](#) (const Box< T > &lhs, const Box< U > &rhs)

7.14 box.hpp

[Go to the documentation of this file.](#)

```
1 #pragma once
2
3 // stl
4 #include <exception>
5 #include <memory>
6 #include <utility>
7
8 namespace wr22::regex_parser::utils {
9
10 struct BoxIsEmpty : public std::exception {
11     const char* what() const noexcept override;
12 };
13
14 template <typename T>
15 class Box {
16 public:
17     explicit Box(T&& value) : m_ptr(std::make_unique<T>(std::forward<T>(value))) {}
18
19     explicit Box(std::unique_ptr<T> ptr) : m_ptr(std::move(ptr)) {}
20
21     template <typename Dummy = T>
22     Box(const Box& other) : m_ptr(std::make_unique<T>(*other)) {}
```

```

59
63     template <typename... Args>
64     static Box<T> construct_in_place(Args&&... args) {
65         return Box(std::make_unique<T>(std::forward<Args>(args)...));
66     }
67
71     const T& operator*() const {
72         if (m_ptr == nullptr) {
73             throw BoxIsEmpty{};
74         }
75         return *m_ptr;
76     }
77
81     T& operator*() {
82         if (m_ptr == nullptr) {
83             throw BoxIsEmpty{};
84         }
85         return *m_ptr;
86     }
87
88 private:
89     std::unique_ptr<T> m_ptr;
90 };
91
93 template <typename T>
94 Box(T&& value) -> Box<T>;
95
97 template <typename T>
98 Box(std::unique_ptr<T> ptr) -> Box<T>;
99
100 template <typename T, typename U>
101 bool operator==(const Box<T>& lhs, const Box<U>& rhs) {
102     return *lhs == *rhs;
103 }
104
105 template <typename T, typename U>
106 bool operator!=(const Box<T>& lhs, const Box<U>& rhs) {
107     return !(lhs == rhs);
108 }
109
110 } // namespace wr22::regex_parser::utils

```

7.15 include/wr22/regex_parser/utils/utf8_string_view.hpp File Reference

```

#include <compare>
#include <cstdint>
#include <exception>
#include <iterator>
#include <optional>
#include <string_view>

```

Classes

- class [wr22::regex_parser::utils::UnicodeStringView](#)
A wrapper around `std::string_view` that enables UTF-8 codepoint iteration.
- struct [wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8](#)
An error thrown when the string's encoding is not valid UTF-8.
- class [wr22::regex_parser::utils::UnicodeStringViewIterator](#)
Iterator over code points for [UnicodeStringView](#).

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::utils](#)

7.16 utf8_string_view.hpp

[Go to the documentation of this file.](#)

```

1 #pragma once
2
3 // STL
4 #include <compare>
5 #include <cstddef>
6 #include <exception>
7 #include <iterator>
8 #include <optional>
9 #include <string_view>
10
11 namespace wr22::regex_parser::utils {
12
13 class UnicodeStringViewIterator;
14
15 class UnicodeStringView {
16     friend class UnicodeStringViewIterator;
17
18 public:
19     struct InvalidUtf8 : std::exception {
20         const char* what() const noexcept override;
21     };
22
23     explicit UnicodeStringView(const std::string_view& raw);
24
25     const std::string_view& raw() const;
26
27     UnicodeStringViewIterator begin() const;
28     UnicodeStringViewIterator end() const;
29
30 private:
31     std::string_view m_raw;
32 };
33
34 class UnicodeStringViewIterator {
35     friend class UnicodeStringView;
36
37 public:
38     using value_type = char32_t;
39
40     using category_type = std::forward_iterator_tag;
41
42     UnicodeStringViewIterator() = delete;
43
44     UnicodeStringViewIterator& operator++();
45
46     char32_t operator*();
47
48     bool operator==(const UnicodeStringViewIterator& rhs) const;
49     bool operator!=(const UnicodeStringViewIterator& rhs) const;
50
51 private:
52     using UnderlyingIterator = std::string_view::const_iterator;
53
54     explicit UnicodeStringViewIterator(
55         const UnderlyingIterator& iter,
56         const UnderlyingIterator& end);
57     std::optional<char32_t> decode_current_codepoint();
58     void update_current_codepoint_size();
59
60     UnderlyingIterator m_iter;
61     UnderlyingIterator m_end;
62
63     // A memoization of the result of decoding of the last code point.
64     // This is done purely for optimization to avoid having to decode a code point
65     // twice: for dereferencing the iterator and for incrementing it. The value
66     // of 0 indicates an absence of a memoized value (0 is not a valid byte size of
67     // a codepoint).
68     size_t m_last_codepoint_size = 0;
69 };
70
71 } // namespace wr22::regex_parser::utils

```

7.17 src/parser/capture.cpp File Reference

```

#include <wr22/regex_parser/regex/capture.hpp>
#include <wr22/regex_parser/regex/named_capture_flavor.hpp>

```

```
#include <iterator>
#include <ostream>
#include <boost/locale/utf.hpp>
#include <fmt/core.h>
#include <fmt/ostream.h>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

Functions

- `std::ostream & wr22::regex_parser::regex::operator<< (std::ostream &out, const Capture &capture)`

7.18 src/parser/errors.cpp File Reference

```
#include <wr22/regex_parser/parser/errors.hpp>
#include <fmt/core.h>
#include <boost/locale/encoding_utf.hpp>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::parser](#)
- namespace [wr22::regex_parser::parser::errors](#)

7.19 src/parser/regex.cpp File Reference

```
#include <boost/locale/utf.hpp>
#include <wr22/regex_parser/parser/errors.hpp>
#include <wr22/regex_parser/parser/regex.hpp>
#include <wr22/regex_parser/regex/part.hpp>
#include <optional>
#include <stdexcept>
#include <string>
#include <vector>
#include <boost/locale/encoding_utf.hpp>
```

Classes

- class [wr22::regex_parser::parser::Parser< Iter, Sentinel >](#)
A regex parser.

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::parser](#)

Functions

- template<typename Iter , typename Sentinel >
[wr22::regex_parser::parser::Parser](#) (Iter begin, Sentinel end) -> Parser< Iter, Sentinel >
The type deduction guideline for [Parser](#).
- regex::Part [wr22::regex_parser::parser::parse_regex](#) (const utils::UnicodeStringView ®ex)
Parse a regular expression into its AST.

7.20 src/regex/named_capture_flavor.cpp File Reference

```
#include <wr22/regex_parser/regex/named_capture_flavor.hpp>
#include <ostream>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

Functions

- std::ostream & [wr22::regex_parser::regex::operator<<](#) (std::ostream &out, NamedCaptureFlavor flavor)

7.21 src/regex/part.cpp File Reference

```
#include <wr22/regex_parser/regex/part.hpp>
#include <iterator>
#include <ostream>
#include <boost/locale/utf.hpp>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::regex](#)

Functions

- `std::ostream & wr22::regex_parser::regex::operator<< (std::ostream &out, const Part &part)`
Convert a [Part](#) to a textual representation and write it to an `std::ostream`.

7.22 src/utils/box.cpp File Reference

```
#include <wr22/regex_parser/utils/box.hpp>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::utils](#)

7.23 src/utils/utf8_string_view.cpp File Reference

```
#include <wr22/regex_parser/utils/utf8_string_view.hpp>  
#include <boost/locale/utf.hpp>  
#include <cassert>
```

Namespaces

- namespace [wr22](#)
- namespace [wr22::regex_parser](#)
- namespace [wr22::regex_parser::utils](#)

Typedefs

- using [wr22::regex_parser::utils::utf_traits](#) = `boost::locale::utf::utf_traits< char >`

Index

- Adt
 - wr22::regex_parser::regex::capture, [12](#)
 - wr22::regex_parser::regex::part, [13](#)
 - wr22::regex_parser::utils::Adt< Variants >, [18](#)
- Alternatives
 - wr22::regex_parser::regex::part::Alternatives, [20](#)
- alternatives
 - wr22::regex_parser::regex::part::Alternatives, [21](#)
- Angles
 - wr22::regex_parser::regex, [11](#)
- AnglesWithP
 - wr22::regex_parser::regex, [11](#)
- Apostrophes
 - wr22::regex_parser::regex, [11](#)
- as_variant
 - wr22::regex_parser::utils::Adt< Variants >, [19](#)
- begin
 - wr22::regex_parser::utils::UnicodeStringView, [51](#)
- Box
 - wr22::regex_parser::utils, [15](#)
 - wr22::regex_parser::utils::Box< T >, [22](#)
- capture
 - wr22::regex_parser::regex::part::Group, [29](#)
- category_type
 - wr22::regex_parser::utils::UnicodeStringViewIterator, [52](#)
- char_got
 - wr22::regex_parser::parser::errors::ExpectedEnd, [28](#)
 - wr22::regex_parser::parser::errors::UnexpectedChar, [47](#)
- character
 - wr22::regex_parser::regex::part::Literal, [32](#)
- construct_in_place
 - wr22::regex_parser::utils::Box< T >, [24](#)
- Empty
 - wr22::regex_parser::regex::part::Empty, [26](#)
- end
 - wr22::regex_parser::utils::UnicodeStringView, [51](#)
- expect_end
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, [39](#)
- expected
 - wr22::regex_parser::parser::errors::UnexpectedChar, [47](#)
 - wr22::regex_parser::parser::errors::UnexpectedEnd, [49](#)
- ExpectedEnd
 - wr22::regex_parser::parser::errors::ExpectedEnd, [27](#)
- flavor
 - wr22::regex_parser::regex::capture::Name, [34](#)
- Group
 - wr22::regex_parser::regex::part::Group, [29](#)
- include/wr22/regex_parser/parser/errors.hpp, [55](#), [56](#)
- include/wr22/regex_parser/parser/regex.hpp, [56](#), [57](#)
- include/wr22/regex_parser/regex/capture.hpp, [57](#), [58](#)
- include/wr22/regex_parser/regex/named_capture_flavor.hpp, [58](#), [59](#)
- include/wr22/regex_parser/regex/part.hpp, [59](#), [60](#)
- include/wr22/regex_parser/utils/adt.hpp, [61](#), [62](#)
- include/wr22/regex_parser/utils/box.hpp, [63](#)
- include/wr22/regex_parser/utils/utf8_string_view.hpp, [64](#), [65](#)
- Index
 - wr22::regex_parser::regex::capture::Index, [30](#)
- inner
 - wr22::regex_parser::regex::part::Group, [29](#)
 - wr22::regex_parser::regex::part::Optional, [36](#)
 - wr22::regex_parser::regex::part::Plus, [43](#)
 - wr22::regex_parser::regex::part::Star, [46](#)
- items
 - wr22::regex_parser::regex::part::Sequence, [45](#)
- Literal
 - wr22::regex_parser::regex::part::Literal, [32](#)
- m_variant
 - wr22::regex_parser::utils::Adt< Variants >, [20](#)
- MultiCallable
 - wr22::regex_parser::utils::detail::adt::MultiCallable< Fs >, [33](#)
- Name
 - wr22::regex_parser::regex::capture::Name, [34](#)
- name
 - wr22::regex_parser::regex::capture::Name, [34](#)
- NamedCaptureFlavor
 - wr22::regex_parser::regex, [11](#)
- None
 - wr22::regex_parser::regex::capture::None, [35](#)
- operator!=
 - wr22::regex_parser::utils, [15](#)

- wr22::regex_parser::utils::UnicodeStringViewIterator, 53
- operator<<
 - wr22::regex_parser::regex, 12
- operator*
 - wr22::regex_parser::utils::Box< T >, 24
 - wr22::regex_parser::utils::UnicodeStringViewIterator, 53
- operator++
 - wr22::regex_parser::utils::UnicodeStringViewIterator, raw 53
- operator==
 - wr22::regex_parser::regex::capture::Index, 30
 - wr22::regex_parser::regex::capture::Name, 34
 - wr22::regex_parser::regex::capture::None, 35
 - wr22::regex_parser::regex::part::Alternatives, 21
 - wr22::regex_parser::regex::part::Empty, 26
 - wr22::regex_parser::regex::part::Group, 29
 - wr22::regex_parser::regex::part::Literal, 32
 - wr22::regex_parser::regex::part::Optional, 36
 - wr22::regex_parser::regex::part::Plus, 43
 - wr22::regex_parser::regex::part::Sequence, 45
 - wr22::regex_parser::regex::part::Star, 46
 - wr22::regex_parser::utils, 15
 - wr22::regex_parser::utils::UnicodeStringViewIterator, 53
- Optional
 - wr22::regex_parser::regex::part::Optional, 36
- parse_alternatives
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 39
- parse_atom
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 39
- parse_char_literal
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 40
- parse_group
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 40
- parse_group_name
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 40
- parse_regex
 - wr22::regex_parser::parser, 10
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 40
- parse_sequence
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 41
- parse_sequence_or_empty
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 41
- Parser
 - wr22::regex_parser::parser, 10
 - wr22::regex_parser::parser::Parser< Iter, Sentinel >, 38
- Plus
 - wr22::regex_parser::regex::part::Plus, 43
- position
 - wr22::regex_parser::parser::errors::ExpectedEnd, 28
 - wr22::regex_parser::parser::errors::UnexpectedChar, 48
 - wr22::regex_parser::parser::errors::UnexpectedEnd, 49
- Sequence
 - wr22::regex_parser::regex::part::Sequence, 44
 - src/parser/capture.cpp, 65
 - src/parser/errors.cpp, 66
 - src/parser/regex.cpp, 66
 - src/regex/named_capture_flavor.cpp, 67
 - src/regex/part.cpp, 67
 - src/utils/box.cpp, 68
 - src/utils/utf8_string_view.cpp, 68
- Star
 - wr22::regex_parser::regex::part::Star, 46
- UnexpectedChar
 - wr22::regex_parser::parser::errors::UnexpectedChar, 47
- UnexpectedEnd
 - wr22::regex_parser::parser::errors::UnexpectedEnd, 49
- UnicodeStringView
 - wr22::regex_parser::utils::UnicodeStringView, 50
 - wr22::regex_parser::utils::UnicodeStringViewIterator, 54
- UnicodeStringViewIterator
 - wr22::regex_parser::utils::UnicodeStringView, 51
 - wr22::regex_parser::utils::UnicodeStringViewIterator, 53
- utf_traits
 - wr22::regex_parser::utils, 14
- value_type
 - wr22::regex_parser::utils::UnicodeStringViewIterator, 52
- VariantType
 - wr22::regex_parser::utils::Adt< Variants >, 18
- visit
 - wr22::regex_parser::utils::Adt< Variants >, 19
- what
 - wr22::regex_parser::utils::BoxIsEmpty, 25
 - wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8, 31
- wr22, 9
- wr22::regex_parser, 9
- wr22::regex_parser::parser, 9
 - parse_regex, 10
 - Parser, 10
- wr22::regex_parser::parser::errors, 10

- wr22::regex_parser::parser::errors::ExpectedEnd, 27
 - char_got, 28
 - ExpectedEnd, 27
 - position, 28
- wr22::regex_parser::parser::errors::ParseError, 37
- wr22::regex_parser::parser::errors::UnexpectedChar, 46
 - char_got, 47
 - expected, 47
 - position, 48
 - UnexpectedChar, 47
- wr22::regex_parser::parser::errors::UnexpectedEnd, 48
 - expected, 49
 - position, 49
 - UnexpectedEnd, 49
- wr22::regex_parser::parser::Parser< Iter, Sentinel >, 37
 - expect_end, 39
 - parse_alternatives, 39
 - parse_atom, 39
 - parse_char_literal, 40
 - parse_group, 40
 - parse_group_name, 40
 - parse_regex, 40
 - parse_sequence, 41
 - parse_sequence_or_empty, 41
 - Parser, 38
- wr22::regex_parser::regex, 11
 - Angles, 11
 - AnglesWithP, 11
 - Apostrophes, 11
 - NamedCaptureFlavor, 11
 - operator<<, 12
- wr22::regex_parser::regex::Capture, 25
- wr22::regex_parser::regex::capture, 12
 - Adt, 12
- wr22::regex_parser::regex::capture::Index, 30
 - Index, 30
 - operator==, 30
- wr22::regex_parser::regex::capture::Name, 33
 - flavor, 34
 - Name, 34
 - name, 34
 - operator==, 34
- wr22::regex_parser::regex::capture::None, 35
 - None, 35
 - operator==, 35
- wr22::regex_parser::regex::Part, 42
- wr22::regex_parser::regex::part, 13
 - Adt, 13
- wr22::regex_parser::regex::part::Alternatives, 20
 - Alternatives, 20
 - alternatives, 21
 - operator==, 21
- wr22::regex_parser::regex::part::Empty, 26
 - Empty, 26
 - operator==, 26
- wr22::regex_parser::regex::part::Group, 28
 - capture, 29
 - Group, 29
 - inner, 29
 - operator==, 29
- wr22::regex_parser::regex::part::Literal, 31
 - character, 32
 - Literal, 32
 - operator==, 32
- wr22::regex_parser::regex::part::Optional, 35
 - inner, 36
 - operator==, 36
 - Optional, 36
- wr22::regex_parser::regex::part::Plus, 43
 - inner, 43
 - operator==, 43
 - Plus, 43
- wr22::regex_parser::regex::part::Sequence, 44
 - items, 45
 - operator==, 45
 - Sequence, 44
- wr22::regex_parser::regex::part::Star, 45
 - inner, 46
 - operator==, 46
 - Star, 46
- wr22::regex_parser::utils, 14
 - Box, 15
 - operator!=, 15
 - operator==, 15
 - utf_traits, 14
- wr22::regex_parser::utils::Adt< Variants >, 17
 - Adt, 18
 - as_variant, 19
 - m_variant, 20
 - VariantType, 18
 - visit, 19
- wr22::regex_parser::utils::Box< T >, 21
 - Box, 22
 - construct_in_place, 24
 - operator*, 24
- wr22::regex_parser::utils::BoxIsEmpty, 25
 - what, 25
- wr22::regex_parser::utils::detail, 16
- wr22::regex_parser::utils::detail::adt, 16
- wr22::regex_parser::utils::detail::adt::MultiCallable< Fs >, 33
 - MultiCallable, 33
- wr22::regex_parser::utils::UnicodeStringView, 49
 - begin, 51
 - end, 51
 - raw, 51
 - UnicodeStringView, 50
 - UnicodeStringViewIterator, 51
- wr22::regex_parser::utils::UnicodeStringView::InvalidUtf8, 31
 - what, 31
- wr22::regex_parser::utils::UnicodeStringViewIterator, 51
 - category_type, 52
 - operator!=, 53

`operator*`, [53](#)
`operator++`, [53](#)
`operator==`, [53](#)
`UnicodeStringView`, [54](#)
`UnicodeStringViewIterator`, [53](#)
`value_type`, [52](#)