Bill's Helix Cheat Sheet / Command Reference

1 Introduction

Document version: 1.0.0-beta, April-2026.
Distributed at GitHub
https://github.com/wrwetzel/helix
https://helix.wrwetzel.com
Based on Helix version: 25.07.1.
https://helix-editor.com/
© 2026 Bill Wetzel - Licensed under CC BY 4.0.
https://creativecommons.org/licenses/by/4.0/

1.1 Definitions

- **file** - the actual data on storage device
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor, not just the selection
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping

1.2 Typographic Conventions

- **`word`** - alphanumeric, punctuation-delimited
- **`WORD`** - whitespace-delimited
- **`Ctrl-c`** - Ctrl and c key pressed simultaneous.
- **`Alt-c`** - Alt and c key pressed simultaneous.
- Metavars **`<regex>`**, **`<file>`** and **`<ch>`** represent user input. The angle-brackets are not part of the command.
- **`␣c`** is space followed by the character c.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- **`␣`**, **`<minus>`**, and **`<under>`** used for clarity. **`<enter>`**, **`<del>`**, **`<bksp>`**, etc. used for non-printing control characters.

1.3 Launching

- **`helix`**
- **`helix`** `<file>`
- **`helix`** `<file1> <file2> … <filen>`
- **`helix`** `–help`
- **`hx`** `in some distributions or by alias`

1.4 Basics

Editing paradigm: select first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
```

1.4.1 Example

```
v3wd
          v – enter select mode
          3 – select 3
          w – words
          d – delete
```

1.4.2 Samples

```
         wd – delete word
         xc – change line
         %y – yank entire file
```

1.5 Modes

As used in Helix documentation.

```
          : – command
          i – insert
          v – select or extend
          z – view - change view preserving selection
          g – goto
          m – match
     Ctrl-w – window
          ␣ – space
       [, ] – unimpaired
```

2 Primary Commands

2.1 Essentials

```
      u / U – undo / redo change in linear history
   Alt-u / – move backward / forward in tree history
     Alt-U
:ear / :lat – move backward / forward in history by
              step count or time span (1s, 2m, 3h, 4d)
  <nn><cmd> – repeat <cmd> <nn> times
        Esc – return to normal mode
```

2.1.1 Quit

Add **!** suffix to force operation.

```
        :wq – write current buffer and quit
  :wq <file> – write current buffer to <file> and quit
       :wqa – write all buffer(s) and quit
         :q – quit current buffer, exits if last
```

2.1.2 Files

```
   :o <file> – open <file> in new buffer
   :w <file> – write current buffer to <file>

  :hs <file> – open/create <file> in new horizontal split
  :vs <file> – open/create <file> in new vertical split
         ␣wf – open/create file(s) under selection(s) in
               horizontal split
         ␣wF – open/create file(s) under selection(s) in
               vertical split
          gf – open/create file(s) under selection, open
               url under selection.

          ␣f – open file picker at LSP workspace root
          ␣F – open file picker at current working
               directory
          ␣g – open changed file picker
```

2.1.2.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

```
   <enter> – open selected in current view
    Ctrl-s – open selected in new horizontal split
    Ctrl-v – open selected in new vertical split
```

2.1.3 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

```
        :n – create new scratch buffer
       :bc – close current buffer
      :bca – close all buffers
      :bco – close all but current buffer
       :bn – next buffer
        ␣b – open buffer picker

        ga – go to last accessed/alternate buffer
        gm – go to last modified/alternate buffer
        gn – go to next buffer
        gp – go to previous buffer
```

2.1.4 Views

Ctrl-w and ␣w are synonymous.

```
  ␣ws / ␣wv  – split horizontal / vertical, current buffer
      ␣wns / – split horizontal / vertical, new buffer
        ␣wnv
         ␣wq – close current split
         ␣wo – close all but current split
         ␣ww – next split

  ␣wh/j/k/l – move to buffer left / up / down / right
  ␣wH/J/K/L – swap split with buffer on left / up /
              down / right
         ␣wt – transpose split
```

2.1.4.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

```
          Z – enter sticky mode, exit with Esc

     zz, zc – align to center
         zt – align to top
         zb – align to bottom
         zm – align to middle horizontally
         zj – scroll down
         zk – scroll up
```

2.1.5 Help

```
     :tutor – open tutorial
         ␣? – open command palette
```

2.2 Movement

2.2.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

```
      h/j/k/l – left / up / down / right
     gh, g|   – beginning of line
     <nn>g|   – column <nn>
         gl   – end of line
         gg   – top of file
<nn>G, g<nn>g – line <nn>
         ge   – bottom of file
         gw   – two-char labels on words, label to go
                to word

          g.  – to last modification in current file
         gj   – down textual line
         gk   – up textual line

         gs   – first non-white-space char
         gt   – top of screen
         gc   – middle of screen
         gb   – bottom of screen
```

2.2.2 By Language Server Protocol - Semantics

Requires LSP support.

```
gd  – go to definition
gy  – go to type definition
gr  – go to references
gi  – go to implementation

]d  – next diagnostic
[d  – prior diagnostic
]D  – last diagnostic
[D  – first diagnostic
```

2.2.3 By Treesitter - Syntax

Requires Treesitter support.

```
]f, [f  – to next, prior function
]t, [t  – to next, prior type definition
]T, [T  – to next, prior test
]a, [a  – to next, prior arg
]c, [c  – to next, prior comment
]g, [g  – to next, prior change
]G, [G  – to last, first change

Alt-e  – move to end of parent node in syntax
         tree
Alt-b  – move to start of parent node in syntax
         tree
```

2.2.4 By Page

```
Ctrl-b  – page up
Ctrl-f  – page down
Ctrl-u  – half page up
Ctrl-d  – half page down
```

2.3 Selection

Selection: a range of characters between anchor and cursor
Normal Mode: move and select
Select Mode: move and extend selection

2.3.1 Operations

```
%       – select whole file
Alt-;   – swap anchor and cursor
Alt-:   – selection to normal direction (cursor at
          end)
Alt-o   – expand selection syntax-aware
Alt-i   – shrink selection
;       – collapse selection(s) to cursor(s)
```

2.3.2 By TextObjects

```
ma<ch> / mi<ch>  – match around / inside the object
                   indicated by <ch> below:

w / W  – word / WORD
p      – paragraph
(, [, ', etc.– specified surround pairs
m      –  closest surround pair
f      – function
t      – type or class
a      – argument/parameter
c      – comment
T      – test
g      – change git hunk
```

2.3.3 By Syntactic Objects

```
w / W  – to start of next word / WORD
e / E  – to end of current word / WORD
b / B  – to start of current word / WORD
x      – current line, extend by line
X      – extend to line
Alt-x  – shrink to line bounds
]p     – to next paragraph
[p     – to prior paragraph
```

2.3.4 By Treesitter - Syntax

Requires Treesitter support.

```
Alt-o  – expand selection to parent syntax node
Alt-i  – shrink syntax tree object selection
Alt-p  – select previous sibling node in syntax
         tree
Alt-n  – select next sibling node in syntax tree
Alt-a  – select all sibling nodes in syntax tree
Alt-I  – select all children nodes in syntax tree
```

2.3.5 By Character Value

Lower case: forward
Upper case: backward

```
f<ch>, F<ch>  – to <ch> inclusive (find)
t<ch>, T<ch>  – to <ch> exclusive (till)
Alt-.         – repeat last find / till
```

2.4 Select Mode

Movement: extends selection
Search: adds to selection

```
v    – toggle select mode
Esc  – return to normal
)    – cycle primary selection forward
(    – cycle primary selection backward
Alt-,  – remove primary selection
```

2.5 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.5.1 Creating

Create multiple selections from selection.

```
s<regex>  – matches become selections
S         – split on match
Alt-s     – split on newlines
C, Alt-C  – add selection below, above
```

2.5.2 Operations

```
&            – align on primary cursor
Alt-<minus>  – merge selections
Alt-<under>  – merge consecutive selections
,            – remove all except primary selection
Alt-,        – remove primary selection
( / )        – rotate primary backwards / forwards
Alt-( / Alt-) – rotate content backward / forward
K            – keep selections matching the regex
Alt-K        – remove selections matching the regex
```

2.6 Alter Buffer Content

2.6.1 Insert

```
i – before selection
a – after selection
I – at start of line
A – at end of line
o – add line and insert below cursor
O – add line and insert above cursor
Esc – end insert (return to normal)
. – repeat last insert
```

2.6.2 Add

```
]␣ – newline below
[␣ – newline above
ms<ch> – add delim <ch> around selection
```

2.6.3 Delete

```
d – selection -> yank buf, delete selection
Alt-d – delete, no save
md<ch> – delete delim <ch> around selection
```

2.6.4 Change

```
c – selection -> yank buf, change selection
Alt-c – change, no save
= – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.6.5 Indent Lines

```
> – Indent line(s) containing selection
< – Undent line(s) containing selection
```

2.6.6 Change Case

Change case of all letters in selection

```
~ – change case
` – set lowercase
Alt-` – set uppercase
```

2.6.7 Comments

All apply to selection.

```
␣c, Ctrl-c – Toggle comment
␣C – Toggle block comment
␣Alt-C – Toggle line comment
```

2.6.8 Increment / Decrement

```
Ctrl-a – increment the selected number
Ctrl-x – decrement the selected number
```

2.6.9 Miscellaneous

```
J – join lines in a selection
Alt-J – join lines inside selection and select the
        inserted space
<under> – trim whitespace from selection
```

2.7 Copy / Paste / Replace

```
y – selection -> yank buf
p – paste yank buf after the cursor
P – paste yank buf before the cursor
␣y – yank selection(s) -> system clipboard
␣Y – yank main selection -> system clipboard
␣p / ␣P – paste clipboard after / before
          selections(s)
␣R – replace selection(s) with clipboard
r<ch> – replace selection with <ch>
R – replace selection with yank buf
" – select register to yank to or paste from
```

2.8 Search

```
/<regex> – search forward for regex
?<regex> – search backward for regex
n, N – next, previous match
* – search for current selection, respect
    word boundaries
Alt-* – search for current selection
```

2.9 Registers

Identified by single char <ch>

```
"<ch> – change to reg <ch>
"<ch>y – yank into reg <ch>
"<ch>p – paste from reg <ch>
"<ch>R – replace with reg <ch>
```

2.10 Macros

```
"<ch>Q – toggle capture to reg <ch>, default @
"<ch>q – play macro in reg <ch>, default @
```

2.11 Jumplists

```
Ctrl-s – save current position to jumplist
Ctrl-i – move forward in jumplist
Ctrl-o – move backwards in jumplist
␣j – open jumplist picker
```

2.12 Match Mode

With regard to balanced delimiters.

```
mm – go to matching delim
mi<ch> – match inside delim <ch>
ma<ch> – match around delim <ch>
ms<ch> – add delim <ch> around selection
md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.13 Shell

All commands pipe each selection to shell command.

```
| – replace selection(s) with output
Alt-| – ignore output
! – insert output before each selection(s)
Alt-! – append output after each selection(s)
$ – keep selection(s) where command
    returned 0
```

2.14 Approaching an IDE

`␣G`	– debug - experimental
`␣k`	– show documentation for item under cursor
`␣s`	– open document symbol picker
`␣S`	– open workspace symbol picker
`␣d`	– open document diagnostics picker
`␣D`	– open workspace diagnostics picker
`␣r`	– rename symbol
`␣a`	– apply code action
`␣h`	– select symbol references for symbol under cursor

2.15 Editor Configuration

`:config-open`	– open the config file
`:config-open-workspace`	– open the workspace config file
`:config-reload`	– reload the config file

2.16 Miscellaneous

`␣'`	– open last picker
`␣/`	– open global search in workspace folder picker

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

```
                Ctrl-s – commit undo checkpoint
                Ctrl-x – autocomplete
                Ctrl-r – insert a register content
   Ctrl-w, Alt-<bksp> – delete previous word
     Alt-d, Alt-<del> – delete next word
                Ctrl-u – delete to start of line
                Ctrl-k – delete to end of line
       Ctrl-h, <bksp>,– delete previous char
          Shift-<bksp>
        Ctrl-d, <del> – delete next char
      Ctrl-j, <enter> – insert new line
  <Up> <Down> <Left> – usual meaning but
    <Right> <PageUp>   discouraged
   <PageDown> <Home>
               <End>
```

3.2 Command Line Editing

```
            Esc, Ctrl-c – close prompt
                <enter> – open selected
                  <tab> – select next completion item
             <backtab> – select previous completion
                          item
                 Alt-b – backward a word
                Ctrl-b – backward a char
                 Alt-f – forward a word
                Ctrl-f – forward a char
                Ctrl-e – to prompt end
                Ctrl-a – to prompt start
   Ctrl-w, Ctrl-<bksp> – delete previous word
     Alt-d, Ctrl-<del> – delete next word
                Ctrl-u – delete to start of line
                Ctrl-k – delete to end of line
        <bksp>, Ctrl-h – delete previous char
         <del>, Ctrl-d – delete next char
                Ctrl-s – insert a word under doc
                          cursor (may be changed to
                          Ctrl-r Ctrl-w later)
                Ctrl-p – select previous history
                Ctrl-n – select next history
                Ctrl-r – insert the content of the
                          register selected by
                          following input char
```

3.3 Pickers

Navigation keys shown.

```
   Shift-<tab>, Ctrl-p,– previous entry
                  <Up>
         <tab>, Ctrl-n,– next entry
                <Down>
                <Home> – to first entry
                 <End> – to last entry
      Ctrl-u, <PageUp> – page up
    Ctrl-d, <PageDown> – page down
               <enter> – open selected
           Alt-<enter> – open selected in the
                          background without closing
                          the picker
                Ctrl-s – open horizontally
                Ctrl-v – open vertically
                Ctrl-t – toggle preview
            Esc, Ctrl-c – close picker
```

3.4 Popups

Displays documentation for item under cursor.

```
      Ctrl-u – scroll up
      Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
   Shift-Tab, Ctrl-p – previous entry
         Tab, Ctrl-n – next entry
             <enter> – close menu and accept
                       completion
              Ctrl-c – close menu and reject
                       completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
      Alt-p – previous signature
      Alt-n – next signature
```

4 Command Index

␣' – open last picker (2.16)
␣/ – open global search in workspace folder picker (2.16)
␣? – open command palette (2.1.5)
␣Alt-C – Toggle line comment (2.6.7)
␣C – Toggle block comment (2.6.7)
␣D – open workspace diagnostics picker (2.14)
␣F – open file picker at current working directory (2.1.2)
␣G – debug - experimental (2.14)
␣R – replace selection(s) with clipboard (2.7)
␣S – open workspace symbol picker (2.14)
␣Y – yank main selection -> system clipboard (2.7)
␣a – apply code action (2.14)
␣b – open buffer picker (2.1.3)
␣c – Toggle comment (2.6.7)
␣d – open document diagnostics picker (2.14)
␣f – open file picker at LSP workspace root (2.1.2)
␣g – open changed file picker (2.1.2)
␣h – select symbol references for symbol under cursor (2.14)
␣j – open jumplist picker (2.11)
␣k – show documentation for item under cursor (2.14)
␣p / ␣P – paste clipboard after / before selections(s) (2.7)
␣r – rename symbol (2.14)
␣s – open document symbol picker (2.14)
␣wF – open/create file(s) under selection(s) in vertical split (2.1.2)
␣wH/J/K/L – swap split with buffer on left / up / down / right (2.1.4)
␣wf – open/create file(s) under selection(s) in horizontal split (2.1.2)
␣wh/j/k/l – move to buffer left / up / down / right (2.1.4)
␣wns / ␣wnv – split horizontal / vertical, new buffer (2.1.4)
␣wo – close all but current split (2.1.4)
␣wq – close current split (2.1.4)
␣ws / ␣wv – split horizontal / vertical, current buffer (2.1.4)
␣wt – transpose split (2.1.4)
␣ww – next split (2.1.4)
␣y – yank selection(s) -> system clipboard (2.7)
! – insert output before each selection(s) (2.13)
" – select register to yank to or paste from (2.7)
"<ch> – change to reg <ch> (2.9)
"<ch>Q – toggle capture to reg <ch>, default @ (2.10)
"<ch>R – replace with reg <ch> (2.9)
"<ch>p – paste from reg <ch> (2.9)
"<ch>q – play macro in reg <ch>, default @ (2.10)
"<ch>y – yank into reg <ch> (2.9)
$ – keep selection(s) where command returned 0 (2.13)
% – select whole file (2.3.1)
& – align on primary cursor (2.5.2)
' – specified surround pairs (2.3.2)
(– cycle primary selection backward (2.4)
(– specified surround pairs (2.3.2)
(/) – rotate primary backwards / forwards (2.5.2)
) – cycle primary selection forward (2.4)
* – search for current selection, respect word boundaries (2.8)
, – remove all except primary selection (2.5.2)
. – repeat last insert (2.6.1)
/<regex> – search forward for regex (2.8)
:bc – close current buffer (2.1.3)
:bca – close all buffers (2.1.3)
:bco – close all but current buffer (2.1.3)
:bn – next buffer (2.1.3)
:config-open – open the config file (2.15)
:config-open-workspace – open the workspace config file (2.15)
:config-reload – reload the config file (2.15)
:ear / :lat – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) (2.1)
:hs <file> – open/create <file> in new horizontal split (2.1.2)
:n – create new scratch buffer (2.1.3)
:o <file> – open <file> in new buffer (2.1.2)
:q – quit current buffer, exits if last (2.1.1)
:tutor – open tutorial (2.1.5)
:vs <file> – open/create <file> in new vertical split (2.1.2)
:w <file> – write current buffer to <file> (2.1.2)
:wq – write current buffer and quit (2.1.1)
:wq <file> – write current buffer to <file> and quit (2.1.1)
:wqa – write all buffer(s) and quit (2.1.1)
; – collapse selection(s) to cursor(s) (2.3.1)
< – Undent line(s) containing selection (2.6.5)
<Down> – next entry (3.3)
<End> – to last entry (3.3)
<Home> – to first entry (3.3)
<PageDown> – page down (3.3)
<PageUp> – page up (3.3)
<Up> – previous entry (3.3)
<Up> <Down> <Left> <Right> <PageUp> <PageDown> <Home> <End> – usual meaning but discouraged (3.1)
<backtab> – select previous completion item (3.2)
<bksp> – delete previous char (3.1)
<bksp> – delete previous char (3.2)
<del> – delete next char (3.1)
<del> – delete next char (3.2)
<enter> – close menu and accept completion (3.5)
<enter> – insert new line (3.1)
<enter> – open selected (3.2)
<enter> – open selected (3.3)
<enter> – open selected in current view (2.1.2.1)
<nn><cmd> – repeat <cmd> <nn> times (2.1)
<nn>G – line <nn> (2.2.1)
<nn>g| – column <nn> (2.2.1)
<tab> – next entry (3.3)
<tab> – select next completion item (3.2)
<under> – trim whitespace from selection (2.6.9)
= – format by LSP (2.6.4)
> – Indent line(s) containing selection (2.6.5)
?<regex> – search backward for regex (2.8)
A – at end of line (2.6.1)
Alt-! – append output after each selection(s) (2.13)
Alt-(/ Alt-) – rotate content backward / forward (2.5.2)
Alt-* – search for current selection (2.8)
Alt-, – remove primary selection (2.4)
Alt-, – remove primary selection (2.5.2)
Alt-. – repeat last find / till (2.3.5)
Alt-: – selection to normal direction (cursor at end) (2.3.1)
Alt-; – swap anchor and cursor (2.3.1)

- **Alt-<bksp>** – delete previous word (3.1)
- **Alt-<del>** – delete next word (3.1)
- **Alt-<enter>** – open selected in the background without closing the picker (3.3)
- **Alt-<minus>** – merge selections (2.5.2)
- **Alt-<under>** – merge consecutive selections (2.5.2)
- **Alt-C** – add selection below, above (2.5.1)
- **Alt-I** – select all children nodes in syntax tree (2.3.4)
- **Alt-J** – join lines inside selection and select the inserted space (2.6.9)
- **Alt-K** – remove selections matching the regex (2.5.2)
- **Alt-`** – set uppercase (2.6.6)
- **Alt-a** – select all sibling nodes in syntax tree (2.3.4)
- **Alt-b** – backward a word (3.2)
- **Alt-b** – move to start of parent node in syntax tree (2.2.3)
- **Alt-c** – change, no save (2.6.4)
- **Alt-d** – delete next word (3.1)
- **Alt-d** – delete next word (3.2)
- **Alt-d** – delete, no save (2.6.3)
- **Alt-e** – move to end of parent node in syntax tree (2.2.3)
- **Alt-f** – forward a word (3.2)
- **Alt-i** – shrink selection (2.3.1)
- **Alt-i** – shrink syntax tree object selection (2.3.4)
- **Alt-n** – next signature (3.6)
- **Alt-n** – select next sibling node in syntax tree (2.3.4)
- **Alt-o** – expand selection syntax-aware (2.3.1)
- **Alt-o** – expand selection to parent syntax node (2.3.4)
- **Alt-p** – previous signature (3.6)
- **Alt-p** – select previous sibling node in syntax tree (2.3.4)
- **Alt-s** – split on newlines (2.5.1)
- **Alt-u / Alt-U** – move backward / forward in tree history (2.1)
- **Alt-x** – shrink to line bounds (2.3.3)
- **Alt-\|** – ignore output (2.13)
- **C** – add selection below, above (2.5.1)
- **Ctrl-<bksp>** – delete previous word (3.2)
- **Ctrl-<del>** – delete next word (3.2)
- **Ctrl-a** – increment the selected number (2.6.8)
- **Ctrl-a** – to prompt start (3.2)
- **Ctrl-b** – backward a char (3.2)
- **Ctrl-b** – page up (2.2.4)
- **Ctrl-c** – Toggle comment (2.6.7)
- **Ctrl-c** – close menu and reject completion (3.5)
- **Ctrl-c** – close picker (3.3)
- **Ctrl-c** – close prompt (3.2)
- **Ctrl-d** – delete next char (3.1)
- **Ctrl-d** – delete next char (3.2)
- **Ctrl-d** – half page down (2.2.4)
- **Ctrl-d** – page down (3.3)
- **Ctrl-d** – scroll down (3.4)
- **Ctrl-e** – to prompt end (3.2)
- **Ctrl-f** – forward a char (3.2)
- **Ctrl-f** – page down (2.2.4)
- **Ctrl-h** – delete previous char (3.1)
- **Ctrl-h** – delete previous char (3.2)
- **Ctrl-i** – move forward in jumplist (2.11)
- **Ctrl-j** – insert new line (3.1)
- **Ctrl-k** – delete to end of line (3.1)
- **Ctrl-k** – delete to end of line (3.2)
- **Ctrl-n** – next entry (3.3)
- **Ctrl-n** – next entry (3.5)
- **Ctrl-n** – select next history (3.2)
- **Ctrl-o** – move backwards in jumplist (2.11)
- **Ctrl-p** – previous entry (3.3)
- **Ctrl-p** – previous entry (3.5)
- **Ctrl-p** – select previous history (3.2)
- **Ctrl-r** – insert a register content (3.1)
- **Ctrl-r** – insert the content of the register selected by following input char (3.2)
- **Ctrl-s** – commit undo checkpoint (3.1)
- **Ctrl-s** – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) (3.2)
- **Ctrl-s** – open horizontally (3.3)
- **Ctrl-s** – open selected in new horizontal split (2.1.2.1)
- **Ctrl-s** – save current position to jumplist (2.11)
- **Ctrl-t** – toggle preview (3.3)
- **Ctrl-u** – delete to start of line (3.1)
- **Ctrl-u** – delete to start of line (3.2)
- **Ctrl-u** – half page up (2.2.4)
- **Ctrl-u** – page up (3.3)
- **Ctrl-u** – scroll up (3.4)
- **Ctrl-v** – open selected in new vertical split (2.1.2.1)
- **Ctrl-v** – open vertically (3.3)
- **Ctrl-w** – delete previous word (3.1)
- **Ctrl-w** – delete previous word (3.2)
- **Ctrl-x** – autocomplete (3.1)
- **Ctrl-x** – decrement the selected number (2.6.8)
- **Esc** – close picker (3.3)
- **Esc** – close prompt (3.2)
- **Esc** – end insert (return to normal) (2.6.1)
- **Esc** – return to normal (2.4)
- **Esc** – return to normal mode (2.1)
- **F<ch>** – to <ch> inclusive (find) (2.3.5)
- **I** – at start of line (2.6.1)
- **J** – join lines in a selection (2.6.9)
- **K** – keep selections matching the regex (2.5.2)
- **N** – next, previous match (2.8)
- **O** – add line and insert above cursor (2.6.1)
- **P** – paste yank buf before the cursor (2.7)
- **R** – replace selection with yank buf (2.7)
- **S** – split on match (2.5.1)
- **Shift-<bksp>** – delete previous char (3.1)
- **Shift-<tab>** – previous entry (3.3)
- **Shift-Tab** – previous entry (3.5)
- **T** – test (2.3.2)
- **T<ch>** – to <ch> exclusive (till) (2.3.5)
- **Tab** – next entry (3.5)
- **X** – extend to line (2.3.3)
- **Z** – enter sticky mode, exit with Esc (2.1.4.1)
- **[␣** – newline above (2.6.2)
- **[** – specified surround pairs (2.3.2)
- **[D** – first diagnostic (2.2.2)
- **[G** – to last, first change (2.2.3)
- **[T** – to next, prior test (2.2.3)
- **[a** – to next, prior arg (2.2.3)
- **[c** – to next, prior comment (2.2.3)
- **[d** – prior diagnostic (2.2.2)
- **[f** – to next, prior function (2.2.3)
- **[g** – to next, prior change (2.2.3)
- **[p** – to prior paragraph (2.3.3)
- **[t** – to next, prior type definition (2.2.3)
- **]␣** – newline below (2.6.2)
- **]D** – last diagnostic (2.2.2)
- **]G** – to last, first change (2.2.3)
- **]T** – to next, prior test (2.2.3)
- **]a** – to next, prior arg (2.2.3)
- **]c** – to next, prior comment (2.2.3)
- **]d** – next diagnostic (2.2.2)
- **]f** – to next, prior function (2.2.3)
- **]g** – to next, prior change (2.2.3)
- **]p** – to next paragraph (2.3.3)
- **]t** – to next, prior type definition (2.2.3)
- **`** – set lowercase (2.6.6)
- **a** – after selection (2.6.1)
- **a** – argument/parameter (2.3.2)
- **b / B** – to start of current word / WORD (2.3.3)
- **c** – comment (2.3.2)
- **c** – selection -> yank buf, change selection (2.6.4)

```
            d – selection -> yank buf, delete selection
                (2.6.3)
        e / E – to end of current word / WORD (2.3.3)
         etc.– specified surround pairs (2.3.2)
            f – function (2.3.2)
       f<ch> – to <ch> inclusive (find) (2.3.5)
            g – change git hunk (2.3.2)
           g.– to last modification in current file (2.2.1)
      g<nn>g – line <nn> (2.2.1)
           ga – go to last accessed/alternate buffer (2.1.3)
           gb – bottom of screen (2.2.1)
           gc – middle of screen (2.2.1)
           gd – go to definition (2.2.2)
           ge – bottom of file (2.2.1)
           gf – open/create file(s) under selection, open
                url under selection. (2.1.2)
           gg – top of file (2.2.1)
           gh – beginning of line (2.2.1)
           gi – go to implementation (2.2.2)
           gj – down textual line (2.2.1)
           gk – up textual line (2.2.1)
           gl – end of line (2.2.1)
           gm – go to last modified/alternate buffer (2.1.3)
           gn – go to next buffer (2.1.3)
           gp – go to previous buffer (2.1.3)
           gr – go to references (2.2.2)
           gs – first non-white-space char (2.2.1)
           gt – top of screen (2.2.1)
           gw – two-char labels on words, label to go to
                word (2.2.1)
           gy – go to type definition (2.2.2)
           g| – beginning of line (2.2.1)
     h/j/k/l – left / up / down / right (2.2.1)
            i – before selection (2.6.1)
            m –  closest surround pair (2.3.2)
       ma<ch> – match around delim <ch> (2.12)
    ma<ch> / – match around / inside the object
      mi<ch>   indicated by <ch> below: (2.3.2)
       md<ch> – delete delim <ch> around selection (2.12)
       md<ch> – delete delim <ch> around selection (2.6.3)
       mi<ch> – match inside delim <ch> (2.12)
           mm – go to matching delim (2.12)
mr<ch1><ch2> – replace delim <ch1> with <ch2> (2.12)
mr<ch1><ch2> – replace delim <ch1> with <ch2> (2.6.4)
       ms<ch> – add delim <ch> around selection (2.12)
       ms<ch> – add delim <ch> around selection (2.6.2)
            n – next, previous match (2.8)
            o – add line and insert below cursor (2.6.1)
            p – paragraph (2.3.2)
            p – paste yank buf after the cursor (2.7)
       r<ch> – replace selection with <ch> (2.7)
    s<regex> – matches become selections (2.5.1)
            t – type or class (2.3.2)
       t<ch> – to <ch> exclusive (till) (2.3.5)
        u / U – undo / redo change in linear history (2.1)
            v – toggle select mode (2.4)
        w / W – to start of next word / WORD (2.3.3)
        w / W – word / WORD (2.3.2)
            x – current line, extend by line (2.3.3)
            y – selection -> yank buf (2.7)
           zb – align to bottom (2.1.4.1)
           zc – align to center (2.1.4.1)
           zj – scroll down (2.1.4.1)
           zk – scroll up (2.1.4.1)
           zm – align to middle horizontally (2.1.4.1)
           zt – align to top (2.1.4.1)
           zz – align to center (2.1.4.1)
            | – replace selection(s) with output (2.13)
            ~ – change case (2.6.6)
```