# Bill's Helix Cheat Sheet / Command Reference

## 1 Introduction

Document version: 1.0.0-beta, April-2026.
Distributed at GitHub
https://github.com/wrwetzel/helix
https://helix.wrwetzel.com
Based on Helix version: 25.07.1.
https://helix-editor.com/
© 2026 Bill Wetzel - Licensed under CC BY 4.0.
https://creativecommons.org/licenses/by/4.0/

### 1.1 Definitions

- **file** - the actual data on storage device
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor, not just the selection
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping

### 1.2 Typographic Conventions

- `word` - alphanumeric, punctuation-delimited
- `WORD` - whitespace-delimited
- `Ctrl-c` - Ctrl and c key pressed simultaneous.
- `Alt-c` - Alt and c key pressed simultaneous.
- Metavars `<regex>`, `<file>` and `<ch>` represent user input. The angle-brackets are not part of the command.
- `␣c` is space followed by the character c.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- `␣`, `<minus>`, and `<under>` used for clarity. `<enter>`, `<del>`, `<bksp>`, etc. used for non-printing control characters.

### 1.3 Launching

```
helix
helix <file>
helix <file1> <file2> … <file>
helix -help
hx in some distributions or by alias
```

### 1.4 Basics

Editing paradigm: select first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
```

#### 1.4.1 Example

```
v3wd
        v – enter select mode
        3 – select 3
        w – words
        d – delete
```

#### 1.4.2 Samples

```
       wd – delete word
       xc – change line
       %y – yank entire file
```

### 1.5 Modes

As used in Helix documentation.

```
        : – command
        i – insert
        v – select or extend
        z – view - change view preserving selection
        g – goto
        m – match
   Ctrl-w – window
        ␣ – space
      [, ] – unimpaired
```

## 2 Primary Commands

### 2.1 Essentials

```
        u / U – undo / redo change in linear history
  Alt-u / Alt-U – move backward / forward in tree history
     :ear / :lat – move backward / forward in history by step count or time
                   span (1s, 2m, 3h, 4d)
     <nn><cmd> – repeat <cmd> <nn> times
           Esc – return to normal mode
```

#### 2.1.1 Quit

Add ! suffix to force operation.

```
        :wq – write current buffer and quit
  :wq <file> – write current buffer to <file> and quit
        :wqa – write all buffer(s) and quit
         :q – quit current buffer, exits if last
```

#### 2.1.2 Files

```
      :o <file> – open <file> in new buffer
      :w <file> – write current buffer to <file>
     :hs <file> – open/create <file> in new horizontal split
     :vs <file> – open/create <file> in new vertical split
             ␣wf – open/create file(s) under selection(s) in horizontal split
             ␣wF – open/create file(s) under selection(s) in vertical split
              gf – open/create file(s) under selection, open url under selection.
              ␣f – open file picker at LSP workspace root
              ␣F – open file picker at current working directory
              ␣g – open changed file picker
```

##### 2.1.2.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

```
     <enter> – open selected in current view
      Ctrl-s – open selected in new horizontal split
      Ctrl-v – open selected in new vertical split
```

#### 2.1.3 Buffers

Add ! suffix to force operation. Buffers named by file they contain.

```
         :n – create new scratch buffer
        :bc – close current buffer
       :bca – close all buffers
      :bco – close all but current buffer
       :bn – next buffer
        ␣b – open buffer picker
        ga – go to last accessed/alternate buffer
        gm – go to last modified/alternate buffer
        gn – go to next buffer
        gp – go to previous buffer
```

#### 2.1.4 Views

Ctrl-w and `␣w` are synonymous.

```
  ␣ws / ␣wv – split horizontal / vertical, current buffer
  ␣wns / ␣wnv – split horizontal / vertical, new buffer
        ␣wq – close current split
        ␣wo – close all but current split
        ␣ww – next split
  ␣wh/j/k/l – move to buffer left / up / down / right
  ␣wH/J/K/L – swap split with buffer on left / up / down / right
        ␣wt – transpose split
```

##### 2.1.4.1 View Movement

Commands shown with `z` prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

```
         Z – enter sticky mode, exit with Esc
     zz, zc – align to center
         zt – align to top
         zb – align to bottom
         zm – align to middle horizontally
         zj – scroll down
         zk – scroll up
```

#### 2.1.5 Help

```
     :tutor – open tutorial
        ␣? – open command palette
```

### 2.2 Movement

#### 2.2.1 Cursor Movement

*Normal Mode*: motion replaces selection
*Select Mode*: motion extends selection

```
     h/j/k/l – left / up / down / right
        gh, g| – beginning of line
      <nn>g| – column <nn>
          gl – end of line
          gg – top of file
  <nn>G, g<nn>g – line <nn>
          ge – bottom of file
          gw – two-char labels on words, label to go to word
          g.– to last modification in current file
          gj – down textual line
          gk – up textual line
          gs – first non-white-space char
          gt – top of screen
          gc – middle of screen
          gb – bottom of screen
```

#### 2.2.2 By Language Server Protocol - Semantics

Requires LSP support.

```
          gd – go to definition
          gy – go to type definition
          gr – go to references
          gi – go to implementation
          ]d – next diagnostic
          [d – prior diagnostic
          ]D – last diagnostic
          [D – first diagnostic
```

#### 2.2.3 By Treesitter - Syntax

Requires Treesitter support.

```
     ]f, [f – to next, prior function
     ]t, [t – to next, prior type definition
     ]T, [T – to next, prior test
     ]a, [a – to next, prior arg
     ]c, [c – to next, prior comment
     ]g, [g – to next, prior change
     ]G, [G – to last, first change
      Alt-e – move to end of parent node in syntax tree
      Alt-b – move to start of parent node in syntax tree
```

#### 2.2.4 By Page

```
     Ctrl-b – page up
     Ctrl-f – page down
     Ctrl-u – half page up
     Ctrl-d – half page down
```

### 2.3 Selection

Selection: a range of characters between anchor and cursor
*Normal Mode*: move and select
*Select Mode*: move and extend selection

#### 2.3.1 Operations

```
         % – select whole file
     Alt-; – swap anchor and cursor
     Alt-: – selection to normal direction (cursor at end)
     Alt-o – expand selection syntax-aware
     Alt-i – shrink selection
         ; – collapse selection(s) to cursor(s)
```

#### 2.3.2 By TextObjects

```
  ma<ch> / mi<ch> – match around / inside the object indicated by <ch>
                    below:
            w / W – word / WORD
                p – paragraph
     (, [, ', etc.– specified surround pairs
                m –  closest surround pair
                f – function
                t – type or class
                a – argument/parameter
                c – comment
                T – test
                g – change git hunk
```

#### 2.3.3 By Syntactic Objects

```
        w / W – to start of next word / WORD
        e / E – to end of current word / WORD
        b / B – to start of current word / WORD
            x – current line, extend by line
            X – extend to line
      Alt-x – shrink to line bounds
        ]p – to next paragraph
        [p – to prior paragraph
```

#### 2.3.4 By Treesitter - Syntax

Requires Treesitter support.

```
      Alt-o – expand selection to parent syntax node
      Alt-i – shrink syntax tree object selection
      Alt-p – select previous sibling node in syntax tree
      Alt-n – select next sibling node in syntax tree
      Alt-a – select all sibling nodes in syntax tree
      Alt-I – select all children nodes in syntax tree
```

#### 2.3.5 By Character Value

*Lower case*: forward
*Upper case*: backward

```
  f<ch>, F<ch> – to <ch> inclusive (find)
  t<ch>, T<ch> – to <ch> exclusive (till)
        Alt-.  – repeat last find / till
```

### 2.4 Select Mode

*Movement*: extends selection
*Search*: adds to selection

```
         v – toggle select mode
       Esc – return to normal
         ) – cycle primary selection forward
         ( – cycle primary selection backward
     Alt-,  – remove primary selection
```

### 2.5 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

#### 2.5.1 Creating

Create multiple selections from selection.

```
  s<regex> – matches become selections
         S – split on match
     Alt-s – split on newlines
  C, Alt-C – add selection below, above
```

#### 2.5.2 Operations

```
         & – align on primary cursor
  Alt-<minus> – merge selections
  Alt-<under> – merge consecutive selections
         ,  – remove all except primary selection
     Alt-,  – remove primary selection
     ( / )  – rotate primary backwards / forwards
Alt-( / Alt-) – rotate content backward / forward
         K – keep selections matching the regex
     Alt-K – remove selections matching the regex
```

### 2.6 Alter Buffer Content

#### 2.6.1 Insert

```
         i – before selection
         a – after selection
         I – at start of line
         A – at end of line
         o – add line and insert below cursor
         O – add line and insert above cursor
       Esc – end insert (return to normal)
         . – repeat last insert
```

#### 2.6.2 Add

```
        ]␣ – newline below
        [␣ – newline above
    ms<ch> – add delim <ch> around selection
```

#### 2.6.3 Delete

```
         d – selection -> yank buf, delete selection
     Alt-d – delete, no save
   md<ch> – delete delim <ch> around selection
```

#### 2.6.4 Change

```
         c – selection -> yank buf, change selection
     Alt-c – change, no save
         = – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

#### 2.6.5 Indent Lines

```
         > – Indent line(s) containing selection
         < – Undent line(s) containing selection
```

#### 2.6.6 Change Case

Change case of all letters in selection

```
         ~ – change case
         ` – set lowercase
     Alt-` – set uppercase
```

#### 2.6.7 Comments

All apply to selection.

```
  ␣c, Ctrl-c – Toggle comment
         ␣C – Toggle block comment
     ␣Alt-C – Toggle line comment
```

#### 2.6.8 Increment / Decrement

```
     Ctrl-a – increment the selected number
     Ctrl-x – decrement the selected number
```

#### 2.6.9 Miscellaneous

```
         J – join lines in a selection
     Alt-J – join lines inside selection and select the inserted space
    <under> – trim whitespace from selection
```

### 2.7 Copy / Paste / Replace

```
         y – selection -> yank buf
         p – paste yank buf after the cursor
         P – paste yank buf before the cursor
        ␣y – yank selection(s) -> system clipboard
        ␣Y – yank main selection -> system clipboard
  ␣p / ␣P – paste clipboard after / before selections(s)
        ␣R – replace selection(s) with clipboard
     r<ch> – replace selection with <ch>
         R – replace selection with yank buf
         " – select register to yank to or paste from
```

### 2.8 Search

```
   /<regex> – search forward for regex
   ?<regex> – search backward for regex
       n, N – next, previous match
          * – search for current selection, respect word boundaries
     Alt-* – search for current selection
```

### 2.9 Registers

Identified by single char <ch>

```
     "<ch> – change to reg <ch>
"<ch>y – yank into reg <ch>
"<ch>p – paste from reg <ch>
"<ch>R – replace with reg <ch>
```

### 2.10 Macros

```
     "<ch>Q – toggle capture to reg <ch>, default @
     "<ch>q – play macro in reg <ch>, default @
```

### 2.11 Jumplists

```
      Ctrl-s – save current position to jumplist
      Ctrl-i – move forward in jumplist
      Ctrl-o – move backwards in jumplist
        ␣j – open jumplist picker
```

### 2.12 Match Mode

With regard to balanced delimiters.

```
         mm – go to matching delim
     mi<ch> – match inside delim <ch>
     ma<ch> – match around delim <ch>
     ms<ch> – add delim <ch> around selection
     md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

### 2.13 Shell

All commands pipe each selection to shell command.

```
          | – replace selection(s) with output
      Alt-| – ignore output
          ! – insert output before each selection(s)
      Alt-! – append output after each selection(s)
          $ – keep selection(s) where command returned 0
```

### 2.14 Approaching an IDE

```
        ␣G – debug - experimental
        ␣k – show documentation for item under cursor
        ␣s – open document symbol picker
        ␣S – open workspace symbol picker
        ␣d – open document diagnostics picker
        ␣D – open workspace diagnostics picker
        ␣r – rename symbol
        ␣a – apply code action
        ␣h – select symbol references for symbol under cursor
```

### 2.15 Editor Configuration

```
   :config-open – open the config file
:config-open-workspace – open the workspace config file
  :config-reload – reload the config file
```

### 2.16 Miscellaneous

```
        ␣' – open last picker
        ␣/ – open global search in workspace folder picker
```

## 3 Commands in Specific Contexts

### 3.1 Insert Mode Editing

Navigation keys shown.

```
          Ctrl-s – commit undo checkpoint
          Ctrl-x – autocomplete
          Ctrl-r – insert a register content
   Ctrl-w, Alt-<bksp> – delete previous word
     Alt-d, Alt-<del> – delete next word
          Ctrl-u – delete to start of line
          Ctrl-k – delete to end of line
Ctrl-h, <bksp>, Shift-<bksp> – delete previous char
       Ctrl-d, <del> – delete next char
       Ctrl-j, <enter> – insert new line
<Up> <Down> <Left> <Right> – usual meaning but discouraged
<PageUp> <PageDown> <Home>
                  <End>
```

### 3.2 Command Line Editing

```
       Esc, Ctrl-c – close prompt
           <enter> – open selected
             <tab> – select next completion item
         <backtab> – select previous completion item
            Alt-b – backward a word
            Ctrl-b – backward a char
            Alt-f – forward a word
            Ctrl-f – forward a char
            Ctrl-e – to prompt end
            Ctrl-a – to prompt start
   Ctrl-w, Ctrl-<bksp> – delete previous word
     Alt-d, Ctrl-<del> – delete next word
            Ctrl-u – delete to start of line
            Ctrl-k – delete to end of line
       <bksp>, Ctrl-h – delete previous char
            <del>, Ctrl-d – delete next char
            Ctrl-s – insert a word under doc cursor (may be
                     changed to Ctrl-r Ctrl-w later)
            Ctrl-p – select previous history
            Ctrl-n – select next history
            Ctrl-r – insert the content of the register selected
                     by following input char
```

### 3.3 Pickers

Navigation keys shown.

```
Shift-<tab>, Ctrl-p, <Up> – previous entry
<tab>, Ctrl-n, <Down> – next entry
                <Home> – to first entry
                 <End> – to last entry
     Ctrl-u, <PageUp> – page up
   Ctrl-d, <PageDown> – page down
             <enter> – open selected
       Alt-<enter> – open selected in the background without
                     closing the picker
            Ctrl-s – open horizontally
            Ctrl-v – open vertically
            Ctrl-t – toggle preview
       Esc, Ctrl-c – close picker
```

### 3.4 Popups

Displays documentation for item under cursor.

```
     Ctrl-u – scroll up
     Ctrl-d – scroll down
```

### 3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
Shift-Tab, Ctrl-p – previous entry
      Tab, Ctrl-n – next entry
           <enter> – close menu and accept completion
            Ctrl-c – close menu and reject completion
```

### 3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
     Alt-p – previous signature
     Alt-n – next signature
```