Bill's Helix Cheat Sheet / Command Reference

1 Introduction

1.1 Metadata

- Document version: 1.1.0-beta, 27-Apr-2026
- Based on Helix version: 25.07.1
- Built with Typst version: 0.14.2
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.2 Definitions

- **file** - data on storage device, e.g., hard disk or ssd
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.3 Typographic Conventions

- `word` - alphanumeric, punctuation-delimited
- `WORD` - whitespace-delimited
- `Ctrl-c` - Ctrl and c key pressed simultaneous.
- `Alt-c` - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- `␣c` is space followed by the character c.
- Metavars `<regex>`, `<file>` and `<ch>` represent user input. The angle-brackets are not part of the input.
- `␣`, `<minus>`, and `<under>` used for clarity. `<enter>`, `<del>`, `<bksp>`, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.4 Launching

```
helix
helix <file>
helix <file1> <file2> ... <filen>
helix <directory>
helix --help
hx in some distributions or by alias
```

2 Primary Commands

2.1 Editing Paradigm

Selection first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
      v3wd – enter select mode, select 3 words, delete
```

2.2 Regular Expressions

Helix uses Rust's regex. Escape following metachars with <backslash> when searching for literal value.

```
        . – any character
        * – zero or more
        + – one or more
        ? – zero or one / lazy match
        ^ – start of line / negation in class
        $ – end of line
      ( ) – capture group
      [ ] – character class
      { } – repetition count
        | – alternation
        \ – escape character itself
```

2.3 Essentials

2.3.1 Undo / Repeat / Normal Mode

```
        u / U – undo / redo change in linear history
Alt-u / Alt-U – move backward / forward in tree history
  :ear / :lat – move backward / forward in history by step
                count or time span (1s, 2m, 3h, 4d)
   <nn><cmd> – repeat <cmd> <nn> times
          Esc – return to normal mode
```

2.3.2 Quit

Add **!** suffix to force operation.

```
       :wq – write current buffer and quit
:wq <file> – write current buffer to <file> and quit
      :wqa – write all buffer(s) and quit
        :q – quit current buffer, exits if last
```

2.3.3 Files

```
 :o <file> – open <file> in new buffer
 :w <file> – write current buffer to <file>

:hs <file> – open/create <file> in new horizontal split
:vs <file> – open/create <file> in new vertical split
       ␣wf – open/create file(s) under selection(s) in
             horizontal split
       ␣wF – open/create file(s) under selection(s) in vertical
             split
        gf – open/create file(s) under selection, open url
             under selection.

        ␣f – open file picker at LSP workspace root
        ␣F – open file picker at current working directory
        ␣g – open changed file picker
```

2.3.3.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

```
<enter> – open selected in current view
 Ctrl-s – open selected in new horizontal split
 Ctrl-v – open selected in new vertical split
```

2.3.4 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

```
   :n – create new scratch buffer
  :bc – close current buffer
 :bca – close all buffers
 :bco – close all but current buffer
  :bn – next buffer
   ␣b – open buffer picker

   ga – go to last accessed/alternate buffer
   gm – go to last modified/alternate buffer
   gn – go to next buffer
   gp – go to previous buffer
```

2.3.5 Views

Ctrl-w and ␣w are synonymous.

```
 ␣ws / ␣wv  – split horizontal / vertical, current buffer
␣wns / ␣wnv – split horizontal / vertical, new buffer
       ␣wq – close current split
       ␣wo – close all but current split
       ␣ww – next split

 ␣wh/j/k/l – move to buffer left / up / down / right
 ␣wH/J/K/L – swap split with buffer on left / up / down /
             right
       ␣wt – transpose split
```

2.3.5.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

```
     Z – enter sticky mode, exit with Esc

zz, zc – align to center
    zt – align to top
    zb – align to bottom
    zm – align to middle horizontally
    zj – scroll down
    zk – scroll up
```

2.3.6 Help

```
 :tutor – open tutorial
     ␣? – open command palette
```

2.4 Movement

2.4.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

```
      h/j/k/l – left / up / down / right
     gh, g| – beginning of line
     <nn>g| – column <nn>
         gl – end of line
         gg – top of file
<nn>G, g<nn>g – line <nn>
         ge – bottom of file
         gw – two-char labels on words, label to go to
              word

         g.– to last modification in current file
         gj – down textual line
         gk – up textual line

         gs – first non-white-space char
         gt – top of screen
         gc – middle of screen
         gb – bottom of screen
```

2.4.2 By Language Server Protocol

Requires LSP support.

```
 gd – go to definition
 gy – go to type definition
 gr – go to references
 gi – go to implementation

 ]d – next diagnostic
 [d – prior diagnostic
 ]D – last diagnostic
 [D – first diagnostic
```

2.4.3 By Treesitter - Syntax

Requires Treesitter support.

```
 ]f, [f – to next, prior function
 ]t, [t – to next, prior type definition
 ]T, [T – to next, prior test
 ]a, [a – to next, prior arg
 ]c, [c – to next, prior comment
 ]g, [g – to next, prior change
 ]G, [G – to last, first change

Alt-e – move to end of parent node in syntax tree
Alt-b – move to start of parent node in syntax tree
```

2.4.4 By Page

```
Ctrl-b – page up
Ctrl-f – page down
Ctrl-u – half page up
Ctrl-d – half page down
```

2.5 Selection

Selection: a range of characters between anchor and cursor
Normal Mode: move and select
Select Mode: move and extend selection

2.5.1 Operations

```
     % – select whole file
Alt-; – swap anchor and cursor
Alt-: – selection to normal direction (cursor at end)
Alt-o – expand selection syntax-aware
Alt-i – shrink selection
     ; – collapse selection(s) to cursor(s)
```

2.5.2 By TextObjects

```
ma<ch> / mi<ch> – match around / inside the object
                  indicated by <ch> below:
        w / W – word / WORD
            p – paragraph
  (, [, ', etc.– specified surround pairs
            m –  closest surround pair
            f – function
            t – type or class
            a – argument/parameter
            c – comment
            T – test
            g – change git hunk
```

2.5.3 By Syntactic Objects

```
    w / W – to start of next word / WORD
    e / E – to end of current word / WORD
    b / B – to start of current word / WORD
        x – current line, extend by line
        X – extend to line
    Alt-x – shrink to line bounds
       ]p – to next paragraph
       [p – to prior paragraph
```

2.5.4 By Treesitter - Syntax

Requires Treesitter support.

```
    Alt-o – expand selection to parent syntax node
    Alt-i – shrink syntax tree object selection
    Alt-p – select previous sibling node in syntax tree
    Alt-n – select next sibling node in syntax tree
    Alt-a – select all sibling nodes in syntax tree
    Alt-I – select all children nodes in syntax tree
```

2.5.5 By Character Value

Lower case: forward
Upper case: backward

```
f<ch>, F<ch> – to <ch> inclusive (find)
t<ch>, T<ch> – to <ch> exclusive (till)
      Alt-.  – repeat last find / till
```

2.6 Select Mode

Movement: extends selection
Search: adds to selection

```
     v – toggle select mode
   Esc – return to normal
     ) – cycle primary selection forward
     ( – cycle primary selection backward
  Alt-,  – remove primary selection
```

2.7 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.7.1 Creating

Create multiple selections from selection.

```
  s<regex> – matches become selections
         S – split on match
     Alt-s – split on newlines
 C / Alt-C – add selection below / above
```

2.7.2 Operations

```
             & – align on primary cursor
  Alt-<minus> – merge selections
  Alt-<under> – merge consecutive selections
            ,  – remove all except primary selection
       Alt-,  – remove primary selection
         ( / ) – rotate primary backwards / forwards
Alt-( / Alt-) – rotate content backward / forward
             K – keep selections matching the regex
         Alt-K – remove selections matching the regex
```

2.8 Alter Buffer Content

2.8.1 Insert

```
     i – before selection
     a – after selection
     I – at start of line
     A – at end of line
     o – add line and insert below cursor
     O – add line and insert above cursor
   Esc – end insert (return to normal)
     . – repeat last insert
```

2.8.2 Add

```
    ]␣ – newline below
    [␣ – newline above
ms<ch> – add delim <ch> around selection
```

2.8.3 Delete

```
     d – selection -> yank buf, delete selection
  Alt-d – delete, no save
md<ch> – delete delim <ch> around selection
```

2.8.4 Change

```
c – selection -> yank buf, change selection
Alt-c – change, no save
= – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.8.5 Indent Lines

```
> – Indent line(s) containing selection
< – Undent line(s) containing selection
```

2.8.6 Change Case

Change case of all letters in selection

```
~ – change case
` – set lowercase
Alt-` – set uppercase
```

2.8.7 Comments

All apply to selection.

```
␣c, Ctrl-c – Toggle comment
␣C – Toggle block comment
␣Alt-C – Toggle line comment
```

2.8.8 Increment / Decrement

```
Ctrl-a – increment the selected number
Ctrl-x – decrement the selected number
```

2.8.9 Miscellaneous

```
J – join lines in a selection
Alt-J – join lines inside selection and select the
        inserted space
<under> – trim whitespace from selection
:reflow <width> – wrap selection to <width>, default 80
:sort – sort ranges in selection
:format – format file using external formatter /
          language server
```

2.9 Copy / Paste / Replace

```
y – selection -> yank buf
p – paste yank buf after the cursor
P – paste yank buf before the cursor
␣y – yank selection(s) -> system clipboard
␣Y – yank main selection -> system clipboard
␣p / ␣P – paste clipboard after / before selections(s)
␣R – replace selection(s) with clipboard
r<ch> – replace selection with <ch>
R – replace selection with yank buf
" – select register to yank to or paste from
```

2.10 Search

```
/<regex> – search forward for regex
?<regex> – search backward for regex
n, N – next, previous match
* – search for current selection, respect word
    boundaries
Alt-* – search for current selection
```

2.11 Registers

Identified by single char <ch>

```
"<ch> – change to reg <ch>
"<ch>y – yank into reg <ch>
"<ch>p – paste from reg <ch>
"<ch>R – replace with reg <ch>
```

2.12 Macros

```
"<ch>Q – toggle capture to reg <ch>, default @
"<ch>q – play macro in reg <ch>, default @
```

2.13 Jumplists

```
Ctrl-s – save current position to jumplist
Ctrl-i – move forward in jumplist
Ctrl-o – move backwards in jumplist
␣j – open jumplist picker
```

2.14 Match Mode

With regard to balanced delimiters.

```
mm – go to matching delim
mi<ch> – match inside delim <ch>
ma<ch> – match around delim <ch>
ms<ch> – add delim <ch> around selection
md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.15 Shell

All commands pipe each selection to shell command.

```
| – replace selection(s) with output
Alt-| – ignore output
! – insert output before each selection(s)
Alt-! – append output after each selection(s)
$ – keep selection(s) where command returned 0
```

2.16 Approaching an IDE

```
␣G – debug - experimental
␣k – show documentation for item under cursor
␣s – open document symbol picker
␣S – open workspace symbol picker
␣d – open document diagnostics picker
␣D – open workspace diagnostics picker
␣r – rename symbol
␣a – apply code action
␣h – select symbol references for symbol under
     cursor
```

2.17 Editor Configuration

```
:config-open – open the config file
:config-open-workspace – open the workspace config file
:config-reload – reload the config file
```

2.18 Miscellaneous

```
␣' – open last picker
␣/ – open global search in workspace folder picker
```

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

```
                    Ctrl-s – commit undo checkpoint
                    Ctrl-x – autocomplete
                    Ctrl-r – insert a register content
        Ctrl-w, Alt-<bksp> – delete previous word
          Alt-d, Alt-<del> – delete next word
                    Ctrl-u – delete to start of line
                    Ctrl-k – delete to end of line
    Ctrl-h, <bksp>, Shift-– delete previous char
                    <bksp>
            Ctrl-d, <del> – delete next char
          Ctrl-j, <enter> – insert new line

     <Up>, <Down>, <Left>,– usual meaning but
        <Right>, <PageUp>,  discouraged
<PageDown>, <Home>, <End>
```

3.2 Command Line Editing

```
        Esc, Ctrl-c – close prompt
            <enter> – open selected
              <tab> – select next completion item
          <backtab> – select previous completion item
              Alt-b – backward a word
             Ctrl-b – backward a char
              Alt-f – forward a word
             Ctrl-f – forward a char
             Ctrl-e – to prompt end
             Ctrl-a – to prompt start
Ctrl-w, Ctrl-<bksp> – delete previous word
  Alt-d, Ctrl-<del> – delete next word
             Ctrl-u – delete to start of line
             Ctrl-k – delete to end of line
     <bksp>, Ctrl-h – delete previous char
      <del>, Ctrl-d – delete next char
             Ctrl-s – insert a word under doc cursor
                      (may be changed to Ctrl-r Ctrl-w
                      later)
             Ctrl-p – select previous history
             Ctrl-n – select next history
             Ctrl-r – insert the content of the register
                      selected by following input char
```

3.3 Pickers

Navigation keys shown.

```
Shift-<tab>, Ctrl-p, <Up> – previous entry
    <tab>, Ctrl-n, <Down> – next entry
                  <Home> – to first entry
                   <End> – to last entry
        Ctrl-u, <PageUp> – page up
      Ctrl-d, <PageDown> – page down
                 <enter> – open selected
            Alt-<enter> – open selected in the
                          background without closing
                          the picker
                  Ctrl-s – open horizontally
                  Ctrl-v – open vertically
                  Ctrl-t – toggle preview
            Esc, Ctrl-c – close picker
```

3.4 Popups

Displays documentation for item under cursor.

```
Ctrl-u – scroll up
Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
Shift-Tab, Ctrl-p – previous entry
      Tab, Ctrl-n – next entry
          <enter> – close menu and accept completion
           Ctrl-c – close menu and reject completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
Alt-p – previous signature
Alt-n – next signature
```

4 Command Index

␣' – open last picker **(2.18)**
␣/ – open global search in workspace folder picker **(2.18)**
␣? – open command palette **(2.3.6)**
␣Alt-C – Toggle line comment **(2.8.7)**
␣C – Toggle block comment **(2.8.7)**
␣D – open workspace diagnostics picker **(2.16)**
␣F – open file picker at current working directory **(2.3.3)**
␣G – debug - experimental **(2.16)**
␣R – replace selection(s) with clipboard **(2.9)**
␣S – open workspace symbol picker **(2.16)**
␣Y – yank main selection -> system clipboard **(2.9)**
␣a – apply code action **(2.16)**
␣b – open buffer picker **(2.3.4)**
␣c – Toggle comment **(2.8.7)**
␣d – open document diagnostics picker **(2.16)**
␣f – open file picker at LSP workspace root **(2.3.3)**
␣g – open changed file picker **(2.3.3)**
␣h – select symbol references for symbol under cursor **(2.16)**
␣j – open jumplist picker **(2.13)**
␣k – show documentation for item under cursor **(2.16)**
␣p / ␣P – paste clipboard after / before selections(s) **(2.9)**
␣r – rename symbol **(2.16)**
␣s – open document symbol picker **(2.16)**
␣wF – open/create file(s) under selection(s) in vertical split **(2.3.3)**
␣wH/J/K/L – swap split with buffer on left / up / down / right **(2.3.5)**
␣wf – open/create file(s) under selection(s) in horizontal split **(2.3.3)**
␣wh/j/k/l – move to buffer left / up / down / right **(2.3.5)**
␣wns / ␣wnv – split horizontal / vertical, new buffer **(2.3.5)**
␣wo – close all but current split **(2.3.5)**
␣wq – close current split **(2.3.5)**
␣ws / ␣wv – split horizontal / vertical, current buffer **(2.3.5)**
␣wt – transpose split **(2.3.5)**
␣ww – next split **(2.3.5)**
␣y – yank selection(s) -> system clipboard **(2.9)**
! – insert output before each selection(s) **(2.15)**
" – select register to yank to or paste from **(2.9)**
"<ch> – change to reg <ch> **(2.11)**
"<ch>Q – toggle capture to reg <ch>, default @ **(2.12)**
"<ch>R – replace with reg <ch> **(2.11)**
"<ch>p – paste from reg <ch> **(2.11)**
"<ch>q – play macro in reg <ch>, default @ **(2.12)**
"<ch>y – yank into reg <ch> **(2.11)**
$ – keep selection(s) where command returned 0 **(2.15)**
% – select whole file **(2.5.1)**
& – align on primary cursor **(2.7.2)**
' – specified surround pairs **(2.5.2)**
(– cycle primary selection backward **(2.6)**
(– specified surround pairs **(2.5.2)**
(/) – rotate primary backwards / forwards **(2.7.2)**
) – cycle primary selection forward **(2.6)**
* – search for current selection, respect word boundaries **(2.10)**
, – remove all except primary selection **(2.7.2)**
. – repeat last insert **(2.8.1)**
/<regex> – search forward for regex **(2.10)**
:bc – close current buffer **(2.3.4)**
:bca – close all buffers **(2.3.4)**
:bco – close all but current buffer **(2.3.4)**
:bn – next buffer **(2.3.4)**
:config-open – open the config file **(2.17)**
:config-open-workspace – open the workspace config file **(2.17)**
:config-reload – reload the config file **(2.17)**
:ear / :lat – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.3.1)**
:format – format file using external formatter / language server **(2.8.9)**
:hs <file> – open/create <file> in new horizontal split **(2.3.3)**
:n – create new scratch buffer **(2.3.4)**
:o <file> – open <file> in new buffer **(2.3.3)**
:q – quit current buffer, exits if last **(2.3.2)**
:reflow <width> – wrap selection to <width>, default 80 **(2.8.9)**
:sort – sort ranges in selection **(2.8.9)**
:tutor – open tutorial **(2.3.6)**
:vs <file> – open/create <file> in new vertical split **(2.3.3)**
:w <file> – write current buffer to <file> **(2.3.3)**
:wq – write current buffer and quit **(2.3.2)**
:wq <file> – write current buffer to <file> and quit **(2.3.2)**
:wqa – write all buffer(s) and quit **(2.3.2)**
; – collapse selection(s) to cursor(s) **(2.5.1)**
< – Undent line(s) containing selection **(2.8.5)**
<Down> – next entry **(3.3)**
<Down> – usual meaning but discouraged **(3.1)**
<End> – to last entry **(3.3)**
<End> – usual meaning but discouraged **(3.1)**
<Home> – to first entry **(3.3)**
<Home> – usual meaning but discouraged **(3.1)**
<Left> – usual meaning but discouraged **(3.1)**
<PageDown> – page down **(3.3)**
<PageDown> – usual meaning but discouraged **(3.1)**
<PageUp> – page up **(3.3)**
<PageUp> – usual meaning but discouraged **(3.1)**
<Right> – usual meaning but discouraged **(3.1)**
<Up> – previous entry **(3.3)**
<Up> – usual meaning but discouraged **(3.1)**
<backtab> – select previous completion item **(3.2)**
<bksp> – delete previous char **(3.1)**
<bksp> – delete previous char **(3.2)**
<del> – delete next char **(3.1)**
<del> – delete next char **(3.2)**
<enter> – close menu and accept completion **(3.5)**
<enter> – insert new line **(3.1)**
<enter> – open selected **(3.2)**
<enter> – open selected **(3.3)**
<enter> – open selected in current view **(2.3.3.1)**
<nn><cmd> – repeat <cmd> <nn> times **(2.3.1)**
<nn>G – line <nn> **(2.4.1)**
<nn>g| – column <nn> **(2.4.1)**

- `<tab>` – next entry **(3.3)**
- `<tab>` – select next completion item **(3.2)**
- `<under>` – trim whitespace from selection **(2.8.9)**
- `=` – format by LSP **(2.8.4)**
- `>` – Indent line(s) containing selection **(2.8.5)**
- `?<regex>` – search backward for regex **(2.10)**
- `A` – at end of line **(2.8.1)**
- `Alt-!` – append output after each selection(s) **(2.15)**
- `Alt-( / Alt-)` – rotate content backward / forward **(2.7.2)**
- `Alt-*` – search for current selection **(2.10)**
- `Alt-,` – remove primary selection **(2.6)**
- `Alt-,` – remove primary selection **(2.7.2)**
- `Alt-.` – repeat last find / till **(2.5.5)**
- `Alt-:` – selection to normal direction (cursor at end) **(2.5.1)**
- `Alt-;` – swap anchor and cursor **(2.5.1)**
- `Alt-<bksp>` – delete previous word **(3.1)**
- `Alt-<del>` – delete next word **(3.1)**
- `Alt-<enter>` – open selected in the background without closing the picker **(3.3)**
- `Alt-<minus>` – merge selections **(2.7.2)**
- `Alt-<under>` – merge consecutive selections **(2.7.2)**
- `Alt-I` – select all children nodes in syntax tree **(2.5.4)**
- `Alt-J` – join lines inside selection and select the inserted space **(2.8.9)**
- `Alt-K` – remove selections matching the regex **(2.7.2)**
- `Alt-` ` – set uppercase **(2.8.6)**
- `Alt-a` – select all sibling nodes in syntax tree **(2.5.4)**
- `Alt-b` – backward a word **(3.2)**
- `Alt-b` – move to start of parent node in syntax tree **(2.4.3)**
- `Alt-c` – change, no save **(2.8.4)**
- `Alt-d` – delete next word **(3.1)**
- `Alt-d` – delete next word **(3.2)**
- `Alt-d` – delete, no save **(2.8.3)**
- `Alt-e` – move to end of parent node in syntax tree **(2.4.3)**
- `Alt-f` – forward a word **(3.2)**
- `Alt-i` – shrink selection **(2.5.1)**
- `Alt-i` – shrink syntax tree object selection **(2.5.4)**
- `Alt-n` – next signature **(3.6)**
- `Alt-n` – select next sibling node in syntax tree **(2.5.4)**
- `Alt-o` – expand selection syntax-aware **(2.5.1)**
- `Alt-o` – expand selection to parent syntax node **(2.5.4)**
- `Alt-p` – previous signature **(3.6)**
- `Alt-p` – select previous sibling node in syntax tree **(2.5.4)**
- `Alt-s` – split on newlines **(2.7.1)**
- `Alt-u / Alt-U` – move backward / forward in tree history **(2.3.1)**
- `Alt-x` – shrink to line bounds **(2.5.3)**
- `Alt-|` – ignore output **(2.15)**
- `C / Alt-C` – add selection below / above **(2.7.1)**
- `Ctrl-<bksp>` – delete previous word **(3.2)**
- `Ctrl-<del>` – delete next word **(3.2)**
- `Ctrl-a` – increment the selected number **(2.8.8)**
- `Ctrl-a` – to prompt start **(3.2)**
- `Ctrl-b` – backward a char **(3.2)**
- `Ctrl-b` – page up **(2.4.4)**
- `Ctrl-c` – Toggle comment **(2.8.7)**
- `Ctrl-c` – close menu and reject completion **(3.5)**
- `Ctrl-c` – close picker **(3.3)**
- `Ctrl-c` – close prompt **(3.2)**
- `Ctrl-d` – delete next char **(3.1)**
- `Ctrl-d` – delete next char **(3.2)**
- `Ctrl-d` – half page down **(2.4.4)**
- `Ctrl-d` – page down **(3.3)**
- `Ctrl-d` – scroll down **(3.4)**
- `Ctrl-e` – to prompt end **(3.2)**
- `Ctrl-f` – forward a char **(3.2)**
- `Ctrl-f` – page down **(2.4.4)**
- `Ctrl-h` – delete previous char **(3.1)**
- `Ctrl-h` – delete previous char **(3.2)**
- `Ctrl-i` – move forward in jumplist **(2.13)**
- `Ctrl-j` – insert new line **(3.1)**
- `Ctrl-k` – delete to end of line **(3.1)**
- `Ctrl-k` – delete to end of line **(3.2)**
- `Ctrl-n` – next entry **(3.3)**
- `Ctrl-n` – next entry **(3.5)**
- `Ctrl-n` – select next history **(3.2)**
- `Ctrl-o` – move backwards in jumplist **(2.13)**
- `Ctrl-p` – previous entry **(3.3)**
- `Ctrl-p` – previous entry **(3.5)**
- `Ctrl-p` – select previous history **(3.2)**
- `Ctrl-r` – insert a register content **(3.1)**
- `Ctrl-r` – insert the content of the register selected by following input char **(3.2)**
- `Ctrl-s` – commit undo checkpoint **(3.1)**
- `Ctrl-s` – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
- `Ctrl-s` – open horizontally **(3.3)**
- `Ctrl-s` – open selected in new horizontal split **(2.3.3.1)**
- `Ctrl-s` – save current position to jumplist **(2.13)**
- `Ctrl-t` – toggle preview **(3.3)**
- `Ctrl-u` – delete to start of line **(3.1)**
- `Ctrl-u` – delete to start of line **(3.2)**
- `Ctrl-u` – half page up **(2.4.4)**
- `Ctrl-u` – page up **(3.3)**
- `Ctrl-u` – scroll up **(3.4)**
- `Ctrl-v` – open selected in new vertical split **(2.3.3.1)**
- `Ctrl-v` – open vertically **(3.3)**
- `Ctrl-w` – delete previous word **(3.1)**
- `Ctrl-w` – delete previous word **(3.2)**
- `Ctrl-x` – autocomplete **(3.1)**
- `Ctrl-x` – decrement the selected number **(2.8.8)**
- `Esc` – close picker **(3.3)**
- `Esc` – close prompt **(3.2)**
- `Esc` – end insert (return to normal) **(2.8.1)**
- `Esc` – return to normal **(2.6)**
- `Esc` – return to normal mode **(2.3.1)**
- `F<ch>` – to <ch> inclusive (find) **(2.5.5)**
- `I` – at start of line **(2.8.1)**
- `J` – join lines in a selection **(2.8.9)**
- `K` – keep selections matching the regex **(2.7.2)**
- `N` – next, previous match **(2.10)**
- `O` – add line and insert above cursor **(2.8.1)**
- `P` – paste yank buf before the cursor **(2.9)**
- `R` – replace selection with yank buf **(2.9)**
- `S` – split on match **(2.7.1)**
- `Shift-<bksp>` – delete previous char **(3.1)**
- `Shift-<tab>` – previous entry **(3.3)**
- `Shift-Tab` – previous entry **(3.5)**
- `T` – test **(2.5.2)**
- `T<ch>` – to <ch> exclusive (till) **(2.5.5)**
- `Tab` – next entry **(3.5)**
- `X` – extend to line **(2.5.3)**

- `Z` – enter sticky mode, exit with Esc **(2.3.5.1)**
- `[␣` – newline above **(2.8.2)**
- `[` – specified surround pairs **(2.5.2)**
- `[D` – first diagnostic **(2.4.2)**
- `[G` – to last, first change **(2.4.3)**
- `[T` – to next, prior test **(2.4.3)**
- `[a` – to next, prior arg **(2.4.3)**
- `[c` – to next, prior comment **(2.4.3)**
- `[d` – prior diagnostic **(2.4.2)**
- `[f` – to next, prior function **(2.4.3)**
- `[g` – to next, prior change **(2.4.3)**
- `[p` – to prior paragraph **(2.5.3)**
- `[t` – to next, prior type definition **(2.4.3)**
- `]␣` – newline below **(2.8.2)**
- `]D` – last diagnostic **(2.4.2)**
- `]G` – to last, first change **(2.4.3)**
- `]T` – to next, prior test **(2.4.3)**
- `]a` – to next, prior arg **(2.4.3)**
- `]c` – to next, prior comment **(2.4.3)**
- `]d` – next diagnostic **(2.4.2)**
- `]f` – to next, prior function **(2.4.3)**
- `]g` – to next, prior change **(2.4.3)**
- `]p` – to next paragraph **(2.5.3)**
- `]t` – to next, prior type definition **(2.4.3)**
- `` ` `` – set lowercase **(2.8.6)**
- `a` – after selection **(2.8.1)**
- `a` – argument/parameter **(2.5.2)**
- `b / B` – to start of current word / WORD **(2.5.3)**
- `c` – comment **(2.5.2)**
- `c` – selection -> yank buf, change selection **(2.8.4)**
- `d` – selection -> yank buf, delete selection **(2.8.3)**
- `e / E` – to end of current word / WORD **(2.5.3)**
- `etc.` – specified surround pairs **(2.5.2)**
- `f` – function **(2.5.2)**
- `f<ch>` – to <ch> inclusive (find) **(2.5.5)**
- `g` – change git hunk **(2.5.2)**
- `g.` – to last modification in current file **(2.4.1)**
- `g<nn>g` – line <nn> **(2.4.1)**
- `ga` – go to last accessed/alternate buffer **(2.3.4)**
- `gb` – bottom of screen **(2.4.1)**
- `gc` – middle of screen **(2.4.1)**
- `gd` – go to definition **(2.4.2)**
- `ge` – bottom of file **(2.4.1)**
- `gf` – open/create file(s) under selection, open url under selection. **(2.3.3)**
- `gg` – top of file **(2.4.1)**
- `gh` – beginning of line **(2.4.1)**
- `gi` – go to implementation **(2.4.2)**
- `gj` – down textual line **(2.4.1)**
- `gk` – up textual line **(2.4.1)**
- `gl` – end of line **(2.4.1)**
- `gm` – go to last modified/alternate buffer **(2.3.4)**
- `gn` – go to next buffer **(2.3.4)**
- `gp` – go to previous buffer **(2.3.4)**
- `gr` – go to references **(2.4.2)**
- `gs` – first non-white-space char **(2.4.1)**
- `gt` – top of screen **(2.4.1)**
- `gw` – two-char labels on words, label to go to word **(2.4.1)**
- `gy` – go to type definition **(2.4.2)**
- `g|` – beginning of line **(2.4.1)**
- `h/j/k/l` – left / up / down / right **(2.4.1)**
- `i` – before selection **(2.8.1)**

- `m` – closest surround pair **(2.5.2)**
- `ma<ch>` – match around delim <ch> **(2.14)**
- `ma<ch> / mi<ch>` – match around / inside the object indicated by <ch> below: **(2.5.2)**
- `md<ch>` – delete delim <ch> around selection **(2.14)**
- `md<ch>` – delete delim <ch> around selection **(2.8.3)**
- `mi<ch>` – match inside delim <ch> **(2.14)**
- `mm` – go to matching delim **(2.14)**
- `mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.14)**
- `mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.8.4)**
- `ms<ch>` – add delim <ch> around selection **(2.14)**
- `ms<ch>` – add delim <ch> around selection **(2.8.2)**
- `n` – next, previous match **(2.10)**
- `o` – add line and insert below cursor **(2.8.1)**
- `p` – paragraph **(2.5.2)**
- `p` – paste yank buf after the cursor **(2.9)**
- `r<ch>` – replace selection with <ch> **(2.9)**
- `s<regex>` – matches become selections **(2.7.1)**
- `t` – type or class **(2.5.2)**
- `t<ch>` – to <ch> exclusive (till) **(2.5.5)**
- `u / U` – undo / redo change in linear history **(2.3.1)**
- `v` – toggle select mode **(2.6)**
- `w / W` – to start of next word / WORD **(2.5.3)**
- `w / W` – word / WORD **(2.5.2)**
- `x` – current line, extend by line **(2.5.3)**
- `y` – selection -> yank buf **(2.9)**
- `zb` – align to bottom **(2.3.5.1)**
- `zc` – align to center **(2.3.5.1)**
- `zj` – scroll down **(2.3.5.1)**
- `zk` – scroll up **(2.3.5.1)**
- `zm` – align to middle horizontally **(2.3.5.1)**
- `zt` – align to top **(2.3.5.1)**
- `zz` – align to center **(2.3.5.1)**
- `|` – replace selection(s) with output **(2.15)**
- `~` – change case **(2.8.6)**