Bill's Helix Cheat Sheet / Command Reference

1 Introduction

1.1 Metadata

- Document version: 1.1.0-beta, 27-Apr-2026
- Based on Helix version: 25.07.1
- Built with Typst version: 0.14.2
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.2 Definitions

- **file** - data on storage device, e.g., hard disk or ssd
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.3 Typographic Conventions

- `word` - alphanumeric, punctuation-delimited
- `WORD` - whitespace-delimited
- `Ctrl-c` - Ctrl and c key pressed simultaneous.
- `Alt-c` - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- `␣c` is space followed by the character c.
- Metavars `<regex>`, `<file>` and `<ch>` represent user input. The angle-brackets are not part of the input.
- `␣`, `<minus>`, and `<under>` used for clarity. `<enter>`, `<del>`, `<bksp>`, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.4 Launching

```
helix
helix <file>
helix <file1> <file2> ... <filen>
helix <directory>
helix --help
hx in some distributions or by alias
```

2 Primary Commands

2.1 Editing Paradigm

Selection first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
      v3wd – enter select mode, select 3 words, delete
```

2.2 Regular Expressions

Helix uses Rust's regex. Escape following metachars with <backslash> when searching for literal value.

```
          . – any character
          * – zero or more
          + – one or more
          ? – zero or one / lazy match
          ^ – start of line / negation in class
          $ – end of line
        ( ) – capture group
        [ ] – character class
        { } – repetition count
          | – alternation
          \ – escape character itself
```

2.3 Essentials

2.3.1 Undo / Repeat / Normal Mode

```
         u / U – undo / redo change in linear history
Alt-u / Alt-U – move backward / forward in tree history
  :ear / :lat – move backward / forward in history by step
                count or time span (1s, 2m, 3h, 4d)
    <nn><cmd> – repeat <cmd> <nn> times
           Esc – return to normal mode
```

2.3.2 Quit

Add **!** suffix to force operation.

```
        :wq – write current buffer and quit
:wq <file> – write current buffer to <file> and quit
       :wqa – write all buffer(s) and quit
         :q – quit current buffer, exits if last
```

2.3.3 Files

```
 :o <file> – open <file> in new buffer
 :w <file> – write current buffer to <file>

:hs <file> – open/create <file> in new horizontal split
:vs <file> – open/create <file> in new vertical split
       ␣wf – open/create file(s) under selection(s) in
             horizontal split
       ␣wF – open/create file(s) under selection(s) in vertical
             split
        gf – open/create file(s) under selection, open url
             under selection.

        ␣f – open file picker at LSP workspace root
        ␣F – open file picker at current working directory
        ␣g – open changed file picker
```

2.3.3.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

```
<enter> – open selected in current view
 Ctrl-s – open selected in new horizontal split
 Ctrl-v – open selected in new vertical split
```

2.3.4 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

```
   :n – create new scratch buffer
  :bc – close current buffer
 :bca – close all buffers
 :bco – close all but current buffer
  :bn – next buffer
   ␣b – open buffer picker

   ga – go to last accessed/alternate buffer
   gm – go to last modified/alternate buffer
   gn – go to next buffer
   gp – go to previous buffer
```

2.3.5 Views

Ctrl-w and ␣w are synonymous.

```
 ␣ws / ␣wv  – split horizontal / vertical, current buffer
␣wns / ␣wnv – split horizontal / vertical, new buffer
        ␣wq – close current split
        ␣wo – close all but current split
        ␣ww – next split

  ␣wh/j/k/l – move to buffer left / up / down / right
  ␣wH/J/K/L – swap split with buffer on left / up / down /
              right
        ␣wt – transpose split
```

2.3.5.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

```
     Z – enter sticky mode, exit with Esc

zz, zc – align to center
    zt – align to top
    zb – align to bottom
    zm – align to middle horizontally
    zj – scroll down
    zk – scroll up
```

2.3.6 Help

```
 :tutor – open tutorial
     ␣? – open command palette
```

2.4 Movement

2.4.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

```
      h/j/k/l – left / up / down / right
       gh, g| – beginning of line
       <nn>g| – column <nn>
           gl – end of line
           gg – top of file
<nn>G, g<nn>g – line <nn>
           ge – bottom of file
           gw – two-char labels on words, label to go to
                word

           g.– to last modification in current file
           gj – down textual line
           gk – up textual line

           gs – first non-white-space char
           gt – top of screen
           gc – middle of screen
           gb – bottom of screen
```

2.4.2 By Language Server Protocol

Requires LSP support.

```
   gd – go to definition
   gy – go to type definition
   gr – go to references
   gi – go to implementation

   ]d – next diagnostic
   [d – prior diagnostic
   ]D – last diagnostic
   [D – first diagnostic
```

2.4.3 By Treesitter - Syntax

Requires Treesitter support.

```
  ]f, [f – to next, prior function
  ]t, [t – to next, prior type definition
  ]T, [T – to next, prior test
  ]a, [a – to next, prior arg
  ]c, [c – to next, prior comment
  ]g, [g – to next, prior change
  ]G, [G – to last, first change

 Alt-e – move to end of parent node in syntax tree
 Alt-b – move to start of parent node in syntax tree
```

2.4.4 By Page

```
 Ctrl-b – page up
 Ctrl-f – page down
 Ctrl-u – half page up
 Ctrl-d – half page down
```

2.5 Selection

Selection: a range of characters between anchor and cursor
Normal Mode: move and select
Select Mode: move and extend selection

2.5.1 Operations

```
      % – select whole file
   Alt-; – swap anchor and cursor
   Alt-: – selection to normal direction (cursor at end)
  Alt-o – expand selection syntax-aware
  Alt-i – shrink selection
      ; – collapse selection(s) to cursor(s)
```

2.5.2 By TextObjects

```
ma<ch> / mi<ch> – match around / inside the object
                  indicated by <ch> below:
        w / W – word / WORD
            p – paragraph
  (, [, ', etc.– specified surround pairs
            m –  closest surround pair
            f – function
            t – type or class
            a – argument/parameter
            c – comment
            T – test
            g – change git hunk
```

2.5.3 By Syntactic Objects

```
    w / W – to start of next word / WORD
    e / E – to end of current word / WORD
    b / B – to start of current word / WORD
        x – current line, extend by line
        X – extend to line
   Alt-x – shrink to line bounds
       ]p – to next paragraph
       [p – to prior paragraph
```

2.5.4 By Treesitter - Syntax

Requires Treesitter support.

```
   Alt-o – expand selection to parent syntax node
   Alt-i – shrink syntax tree object selection
   Alt-p – select previous sibling node in syntax tree
   Alt-n – select next sibling node in syntax tree
   Alt-a – select all sibling nodes in syntax tree
   Alt-I – select all children nodes in syntax tree
```

2.5.5 By Character Value

Lower case: forward
Upper case: backward

```
f<ch>, F<ch> – to <ch> inclusive (find)
t<ch>, T<ch> – to <ch> exclusive (till)
     Alt-.  – repeat last find / till
```

2.6 Select Mode

Movement: extends selection
Search: adds to selection

```
      v – toggle select mode
    Esc – return to normal
      ) – cycle primary selection forward
      ( – cycle primary selection backward
  Alt-,  – remove primary selection
```

2.7 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.7.1 Creating

Create multiple selections from selection.

```
  s<regex> – matches become selections
         S – split on match
    Alt-s – split on newlines
C / Alt-C – add selection below / above
```

2.7.2 Operations

```
             & – align on primary cursor
  Alt-<minus> – merge selections
  Alt-<under> – merge consecutive selections
            , – remove all except primary selection
       Alt-,  – remove primary selection
        ( / ) – rotate primary backwards / forwards
Alt-( / Alt-) – rotate content backward / forward
            K – keep selections matching the regex
        Alt-K – remove selections matching the regex
```

2.8 Alter Buffer Content

2.8.1 Insert

```
      i – before selection
      a – after selection
      I – at start of line
      A – at end of line
      o – add line and insert below cursor
      O – add line and insert above cursor
    Esc – end insert (return to normal)
      . – repeat last insert
```

2.8.2 Add

```
     ]␣ – newline below
     [␣ – newline above
ms<ch> – add delim <ch> around selection
```

2.8.3 Delete

```
      d – selection -> yank buf, delete selection
  Alt-d – delete, no save
md<ch> – delete delim <ch> around selection
```

2.8.4 Change

```
            c – selection -> yank buf, change selection
       Alt-c – change, no save
           = – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.8.5 Indent Lines

```
          > – Indent line(s) containing selection
          < – Undent line(s) containing selection
```

2.8.6 Change Case

Change case of all letters in selection

```
          ~ – change case
          ` – set lowercase
     Alt-` – set uppercase
```

2.8.7 Comments

All apply to selection.

```
␣c, Ctrl-c – Toggle comment
        ␣C – Toggle block comment
    ␣Alt-C – Toggle line comment
```

2.8.8 Increment / Decrement

```
    Ctrl-a – increment the selected number
    Ctrl-x – decrement the selected number
```

2.8.9 Miscellaneous

```
                J – join lines in a selection
            Alt-J – join lines inside selection and select the
                    inserted space
         <under> – trim whitespace from selection
:reflow <width> – wrap selection to <width>, default 80
           :sort – sort ranges in selection
         :format – format file using external formatter /
                   language server
```

2.9 Copy / Paste / Replace

```
           y – selection -> yank buf
           p – paste yank buf after the cursor
           P – paste yank buf before the cursor
          ␣y – yank selection(s) -> system clipboard
          ␣Y – yank main selection -> system clipboard
   ␣p / ␣P – paste clipboard after / before selections(s)
          ␣R – replace selection(s) with clipboard
       r<ch> – replace selection with <ch>
           R – replace selection with yank buf
           " – select register to yank to or paste from
```

2.10 Search

```
   /<regex> – search forward for regex
   ?<regex> – search backward for regex
       n, N – next, previous match
          * – search for current selection, respect word
              boundaries
      Alt-* – search for current selection
```

2.11 Registers

Identified by single char <ch>

```
     "<ch> – change to reg <ch>
    "<ch>y – yank into reg <ch>
    "<ch>p – paste from reg <ch>
    "<ch>R – replace with reg <ch>
```

2.12 Macros

```
    "<ch>Q – toggle capture to reg <ch>, default @
    "<ch>q – play macro in reg <ch>, default @
```

2.13 Jumplists

```
    Ctrl-s – save current position to jumplist
    Ctrl-i – move forward in jumplist
    Ctrl-o – move backwards in jumplist
        ␣j – open jumplist picker
```

2.14 Match Mode

With regard to balanced delimiters.

```
          mm – go to matching delim
     mi<ch> – match inside delim <ch>
     ma<ch> – match around delim <ch>
     ms<ch> – add delim <ch> around selection
     md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.15 Shell

All commands pipe each selection to shell command.

```
          | – replace selection(s) with output
      Alt-| – ignore output
          ! – insert output before each selection(s)
      Alt-! – append output after each selection(s)
          $ – keep selection(s) where command returned 0
```

2.16 Approaching an IDE

```
␣G – debug - experimental
␣k – show documentation for item under cursor
␣s – open document symbol picker
␣S – open workspace symbol picker
␣d – open document diagnostics picker
␣D – open workspace diagnostics picker
␣r – rename symbol
␣a – apply code action
␣h – select symbol references for symbol under
     cursor
```

2.17 Editor Configuration

```
:config-open – open the config file
:config-open-workspace – open the workspace config file
:config-reload – reload the config file
```

2.18 Miscellaneous

```
␣' – open last picker
␣/ – open global search in workspace folder picker
```

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

```
                    Ctrl-s – commit undo checkpoint
                    Ctrl-x – autocomplete
                    Ctrl-r – insert a register content
       Ctrl-w, Alt-<bksp> – delete previous word
         Alt-d, Alt-<del> – delete next word
                    Ctrl-u – delete to start of line
                    Ctrl-k – delete to end of line
   Ctrl-h, <bksp>, Shift-– delete previous char
                    <bksp>
           Ctrl-d, <del> – delete next char
         Ctrl-j, <enter> – insert new line
     <Up>, <Down>, <Left>,– usual meaning but
        <Right>, <PageUp>,  discouraged
<PageDown>, <Home>, <End>
```

3.2 Command Line Editing

```
        Esc, Ctrl-c – close prompt
            <enter> – open selected
              <tab> – select next completion item
          <backtab> – select previous completion item
              Alt-b – backward a word
             Ctrl-b – backward a char
              Alt-f – forward a word
             Ctrl-f – forward a char
             Ctrl-e – to prompt end
             Ctrl-a – to prompt start
Ctrl-w, Ctrl-<bksp> – delete previous word
  Alt-d, Ctrl-<del> – delete next word
             Ctrl-u – delete to start of line
             Ctrl-k – delete to end of line
     <bksp>, Ctrl-h – delete previous char
      <del>, Ctrl-d – delete next char
             Ctrl-s – insert a word under doc cursor
                      (may be changed to Ctrl-r Ctrl-w
                      later)
             Ctrl-p – select previous history
             Ctrl-n – select next history
             Ctrl-r – insert the content of the register
                      selected by following input char
```

3.3 Pickers

Navigation keys shown.

```
Shift-<tab>, Ctrl-p, <Up> – previous entry
    <tab>, Ctrl-n, <Down> – next entry
                  <Home> – to first entry
                   <End> – to last entry
         Ctrl-u, <PageUp> – page up
       Ctrl-d, <PageDown> – page down
                 <enter> – open selected
            Alt-<enter> – open selected in the
                          background without closing
                          the picker
                  Ctrl-s – open horizontally
                  Ctrl-v – open vertically
                  Ctrl-t – toggle preview
            Esc, Ctrl-c – close picker
```

3.4 Popups

Displays documentation for item under cursor.

```
    Ctrl-u – scroll up
    Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
Shift-Tab, Ctrl-p – previous entry
      Tab, Ctrl-n – next entry
          <enter> – close menu and accept completion
           Ctrl-c – close menu and reject completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
Alt-p – previous signature
Alt-n – next signature
```

4 Command Index

␣' – open last picker **(2.18)**
␣/ – open global search in workspace folder picker **(2.18)**
␣? – open command palette **(2.3.6)**
␣Alt-C – Toggle line comment **(2.8.7)**
␣C – Toggle block comment **(2.8.7)**
␣D – open workspace diagnostics picker **(2.16)**
␣F – open file picker at current working directory **(2.3.3)**
␣G – debug - experimental **(2.16)**
␣R – replace selection(s) with clipboard **(2.9)**
␣S – open workspace symbol picker **(2.16)**
␣Y – yank main selection -> system clipboard **(2.9)**
␣a – apply code action **(2.16)**
␣b – open buffer picker **(2.3.4)**
␣c – Toggle comment **(2.8.7)**
␣d – open document diagnostics picker **(2.16)**
␣f – open file picker at LSP workspace root **(2.3.3)**
␣g – open changed file picker **(2.3.3)**
␣h – select symbol references for symbol under cursor **(2.16)**
␣j – open jumplist picker **(2.13)**
␣k – show documentation for item under cursor **(2.16)**
␣p / ␣P – paste clipboard after / before selections(s) **(2.9)**
␣r – rename symbol **(2.16)**
␣s – open document symbol picker **(2.16)**
␣wF – open/create file(s) under selection(s) in vertical split **(2.3.3)**
␣wH/J/K/L – swap split with buffer on left / up / down / right **(2.3.5)**
␣wf – open/create file(s) under selection(s) in horizontal split **(2.3.3)**
␣wh/j/k/l – move to buffer left / up / down / right **(2.3.5)**
␣wns / ␣wnv – split horizontal / vertical, new buffer **(2.3.5)**
␣wo – close all but current split **(2.3.5)**
␣wq – close current split **(2.3.5)**
␣ws / ␣wv – split horizontal / vertical, current buffer **(2.3.5)**
␣wt – transpose split **(2.3.5)**
␣ww – next split **(2.3.5)**
␣y – yank selection(s) -> system clipboard **(2.9)**
! – insert output before each selection(s) **(2.15)**
" – select register to yank to or paste from **(2.9)**
"<ch> – change to reg <ch> **(2.11)**
"<ch>Q – toggle capture to reg <ch>, default @ **(2.12)**
"<ch>R – replace with reg <ch> **(2.11)**
"<ch>p – paste from reg <ch> **(2.11)**
"<ch>q – play macro in reg <ch>, default @ **(2.12)**
"<ch>y – yank into reg <ch> **(2.11)**
$ – keep selection(s) where command returned 0 **(2.15)**
% – select whole file **(2.5.1)**
& – align on primary cursor **(2.7.2)**
' – specified surround pairs **(2.5.2)**
(– cycle primary selection backward **(2.6)**
(– specified surround pairs **(2.5.2)**
(/) – rotate primary backwards / forwards **(2.7.2)**
) – cycle primary selection forward **(2.6)**
* – search for current selection, respect word boundaries **(2.10)**
, – remove all except primary selection **(2.7.2)**
. – repeat last insert **(2.8.1)**
/<regex> – search forward for regex **(2.10)**
:bc – close current buffer **(2.3.4)**
:bca – close all buffers **(2.3.4)**
:bco – close all but current buffer **(2.3.4)**
:bn – next buffer **(2.3.4)**
:config-open – open the config file **(2.17)**
:config-open-workspace – open the workspace config file **(2.17)**
:config-reload – reload the config file **(2.17)**
:ear / :lat – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.3.1)**
:format – format file using external formatter / language server **(2.8.9)**
:hs <file> – open/create <file> in new horizontal split **(2.3.3)**
:n – create new scratch buffer **(2.3.4)**
:o <file> – open <file> in new buffer **(2.3.3)**
:q – quit current buffer, exits if last **(2.3.2)**
:reflow <width> – wrap selection to <width>, default 80 **(2.8.9)**
:sort – sort ranges in selection **(2.8.9)**
:tutor – open tutorial **(2.3.6)**
:vs <file> – open/create <file> in new vertical split **(2.3.3)**
:w <file> – write current buffer to <file> **(2.3.3)**
:wq – write current buffer and quit **(2.3.2)**
:wq <file> – write current buffer to <file> and quit **(2.3.2)**
:wqa – write all buffer(s) and quit **(2.3.2)**
; – collapse selection(s) to cursor(s) **(2.5.1)**
< – Undent line(s) containing selection **(2.8.5)**
<Down> – next entry **(3.3)**
<Down> – usual meaning but discouraged **(3.1)**
<End> – to last entry **(3.3)**
<End> – usual meaning but discouraged **(3.1)**
<Home> – to first entry **(3.3)**
<Home> – usual meaning but discouraged **(3.1)**
<Left> – usual meaning but discouraged **(3.1)**
<PageDown> – page down **(3.3)**
<PageDown> – usual meaning but discouraged **(3.1)**
<PageUp> – page up **(3.3)**
<PageUp> – usual meaning but discouraged **(3.1)**
<Right> – usual meaning but discouraged **(3.1)**
<Up> – previous entry **(3.3)**
<Up> – usual meaning but discouraged **(3.1)**
<backtab> – select previous completion item **(3.2)**
<bksp> – delete previous char **(3.1)**
<bksp> – delete previous char **(3.2)**
<del> – delete next char **(3.1)**
<del> – delete next char **(3.2)**
<enter> – close menu and accept completion **(3.5)**
<enter> – insert new line **(3.1)**
<enter> – open selected **(3.2)**
<enter> – open selected **(3.3)**
<enter> – open selected in current view **(2.3.3.1)**
<nn><cmd> – repeat <cmd> <nn> times **(2.3.1)**
<nn>G – line <nn> **(2.4.1)**
<nn>g| – column <nn> **(2.4.1)**

- **<tab>** – next entry **(3.3)**
- **<tab>** – select next completion item **(3.2)**
- **<under>** – trim whitespace from selection **(2.8.9)**
- **=** – format by LSP **(2.8.4)**
- **>** – Indent line(s) containing selection **(2.8.5)**
- **?<regex>** – search backward for regex **(2.10)**
- **A** – at end of line **(2.8.1)**
- **Alt-!** – append output after each selection(s) **(2.15)**
- **Alt-(/ Alt-)** – rotate content backward / forward **(2.7.2)**
- **Alt-*** – search for current selection **(2.10)**
- **Alt-,** – remove primary selection **(2.6)**
- **Alt-,** – remove primary selection **(2.7.2)**
- **Alt-.** – repeat last find / till **(2.5.5)**
- **Alt-:** – selection to normal direction (cursor at end) **(2.5.1)**
- **Alt-;** – swap anchor and cursor **(2.5.1)**
- **Alt-<bksp>** – delete previous word **(3.1)**
- **Alt-<del>** – delete next word **(3.1)**
- **Alt-<enter>** – open selected in the background without closing the picker **(3.3)**
- **Alt-<minus>** – merge selections **(2.7.2)**
- **Alt-<under>** – merge consecutive selections **(2.7.2)**
- **Alt-I** – select all children nodes in syntax tree **(2.5.4)**
- **Alt-J** – join lines inside selection and select the inserted space **(2.8.9)**
- **Alt-K** – remove selections matching the regex **(2.7.2)**
- **Alt-`** – set uppercase **(2.8.6)**
- **Alt-a** – select all sibling nodes in syntax tree **(2.5.4)**
- **Alt-b** – backward a word **(3.2)**
- **Alt-b** – move to start of parent node in syntax tree **(2.4.3)**
- **Alt-c** – change, no save **(2.8.4)**
- **Alt-d** – delete next word **(3.1)**
- **Alt-d** – delete next word **(3.2)**
- **Alt-d** – delete, no save **(2.8.3)**
- **Alt-e** – move to end of parent node in syntax tree **(2.4.3)**
- **Alt-f** – forward a word **(3.2)**
- **Alt-i** – shrink selection **(2.5.1)**
- **Alt-i** – shrink syntax tree object selection **(2.5.4)**
- **Alt-n** – next signature **(3.6)**
- **Alt-n** – select next sibling node in syntax tree **(2.5.4)**
- **Alt-o** – expand selection syntax-aware **(2.5.1)**
- **Alt-o** – expand selection to parent syntax node **(2.5.4)**
- **Alt-p** – previous signature **(3.6)**
- **Alt-p** – select previous sibling node in syntax tree **(2.5.4)**
- **Alt-s** – split on newlines **(2.7.1)**
- **Alt-u / Alt-U** – move backward / forward in tree history **(2.3.1)**
- **Alt-x** – shrink to line bounds **(2.5.3)**
- **Alt-|** – ignore output **(2.15)**
- **C / Alt-C** – add selection below / above **(2.7.1)**
- **Ctrl-<bksp>** – delete previous word **(3.2)**
- **Ctrl-<del>** – delete next word **(3.2)**
- **Ctrl-a** – increment the selected number **(2.8.8)**
- **Ctrl-a** – to prompt start **(3.2)**
- **Ctrl-b** – backward a char **(3.2)**
- **Ctrl-b** – page up **(2.4.4)**
- **Ctrl-c** – Toggle comment **(2.8.7)**
- **Ctrl-c** – close menu and reject completion **(3.5)**
- **Ctrl-c** – close picker **(3.3)**
- **Ctrl-c** – close prompt **(3.2)**
- **Ctrl-d** – delete next char **(3.1)**
- **Ctrl-d** – delete next char **(3.2)**
- **Ctrl-d** – half page down **(2.4.4)**
- **Ctrl-d** – page down **(3.3)**
- **Ctrl-d** – scroll down **(3.4)**
- **Ctrl-e** – to prompt end **(3.2)**
- **Ctrl-f** – forward a char **(3.2)**
- **Ctrl-f** – page down **(2.4.4)**
- **Ctrl-h** – delete previous char **(3.1)**
- **Ctrl-h** – delete previous char **(3.2)**
- **Ctrl-i** – move forward in jumplist **(2.13)**
- **Ctrl-j** – insert new line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.2)**
- **Ctrl-n** – next entry **(3.3)**
- **Ctrl-n** – next entry **(3.5)**
- **Ctrl-n** – select next history **(3.2)**
- **Ctrl-o** – move backwards in jumplist **(2.13)**
- **Ctrl-p** – previous entry **(3.3)**
- **Ctrl-p** – previous entry **(3.5)**
- **Ctrl-p** – select previous history **(3.2)**
- **Ctrl-r** – insert a register content **(3.1)**
- **Ctrl-r** – insert the content of the register selected by following input char **(3.2)**
- **Ctrl-s** – commit undo checkpoint **(3.1)**
- **Ctrl-s** – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
- **Ctrl-s** – open horizontally **(3.3)**
- **Ctrl-s** – open selected in new horizontal split **(2.3.3.1)**
- **Ctrl-s** – save current position to jumplist **(2.13)**
- **Ctrl-t** – toggle preview **(3.3)**
- **Ctrl-u** – delete to start of line **(3.1)**
- **Ctrl-u** – delete to start of line **(3.2)**
- **Ctrl-u** – half page up **(2.4.4)**
- **Ctrl-u** – page up **(3.3)**
- **Ctrl-u** – scroll up **(3.4)**
- **Ctrl-v** – open selected in new vertical split **(2.3.3.1)**
- **Ctrl-v** – open vertically **(3.3)**
- **Ctrl-w** – delete previous word **(3.1)**
- **Ctrl-w** – delete previous word **(3.2)**
- **Ctrl-x** – autocomplete **(3.1)**
- **Ctrl-x** – decrement the selected number **(2.8.8)**
- **Esc** – close picker **(3.3)**
- **Esc** – close prompt **(3.2)**
- **Esc** – end insert (return to normal) **(2.8.1)**
- **Esc** – return to normal **(2.6)**
- **Esc** – return to normal mode **(2.3.1)**
- **F<ch>** – to <ch> inclusive (find) **(2.5.5)**
- **I** – at start of line **(2.8.1)**
- **J** – join lines in a selection **(2.8.9)**
- **K** – keep selections matching the regex **(2.7.2)**
- **N** – next, previous match **(2.10)**
- **O** – add line and insert above cursor **(2.8.1)**
- **P** – paste yank buf before the cursor **(2.9)**
- **R** – replace selection with yank buf **(2.9)**
- **S** – split on match **(2.7.1)**
- **Shift-<bksp>** – delete previous char **(3.1)**
- **Shift-<tab>** – previous entry **(3.3)**
- **Shift-Tab** – previous entry **(3.5)**
- **T** – test **(2.5.2)**
- **T<ch>** – to <ch> exclusive (till) **(2.5.5)**
- **Tab** – next entry **(3.5)**
- **X** – extend to line **(2.5.3)**

- **Z** – enter sticky mode, exit with Esc **(2.3.5.1)**
- **[␣** – newline above **(2.8.2)**
- **[** – specified surround pairs **(2.5.2)**
- **[D** – first diagnostic **(2.4.2)**
- **[G** – to last, first change **(2.4.3)**
- **[T** – to next, prior test **(2.4.3)**
- **[a** – to next, prior arg **(2.4.3)**
- **[c** – to next, prior comment **(2.4.3)**
- **[d** – prior diagnostic **(2.4.2)**
- **[f** – to next, prior function **(2.4.3)**
- **[g** – to next, prior change **(2.4.3)**
- **[p** – to prior paragraph **(2.5.3)**
- **[t** – to next, prior type definition **(2.4.3)**
- **]␣** – newline below **(2.8.2)**
- **]D** – last diagnostic **(2.4.2)**
- **]G** – to last, first change **(2.4.3)**
- **]T** – to next, prior test **(2.4.3)**
- **]a** – to next, prior arg **(2.4.3)**
- **]c** – to next, prior comment **(2.4.3)**
- **]d** – next diagnostic **(2.4.2)**
- **]f** – to next, prior function **(2.4.3)**
- **]g** – to next, prior change **(2.4.3)**
- **]p** – to next paragraph **(2.5.3)**
- **]t** – to next, prior type definition **(2.4.3)**
- **`** – set lowercase **(2.8.6)**
- **a** – after selection **(2.8.1)**
- **a** – argument/parameter **(2.5.2)**
- **b / B** – to start of current word / WORD **(2.5.3)**
- **c** – comment **(2.5.2)**
- **c** – selection -> yank buf, change selection **(2.8.4)**
- **d** – selection -> yank buf, delete selection **(2.8.3)**
- **e / E** – to end of current word / WORD **(2.5.3)**
- **etc.** – specified surround pairs **(2.5.2)**
- **f** – function **(2.5.2)**
- **f<ch>** – to <ch> inclusive (find) **(2.5.5)**
- **g** – change git hunk **(2.5.2)**
- **g.** – to last modification in current file **(2.4.1)**
- **g<nn>g** – line <nn> **(2.4.1)**
- **ga** – go to last accessed/alternate buffer **(2.3.4)**
- **gb** – bottom of screen **(2.4.1)**
- **gc** – middle of screen **(2.4.1)**
- **gd** – go to definition **(2.4.2)**
- **ge** – bottom of file **(2.4.1)**
- **gf** – open/create file(s) under selection, open url under selection. **(2.3.3)**
- **gg** – top of file **(2.4.1)**
- **gh** – beginning of line **(2.4.1)**
- **gi** – go to implementation **(2.4.2)**
- **gj** – down textual line **(2.4.1)**
- **gk** – up textual line **(2.4.1)**
- **gl** – end of line **(2.4.1)**
- **gm** – go to last modified/alternate buffer **(2.3.4)**
- **gn** – go to next buffer **(2.3.4)**
- **gp** – go to previous buffer **(2.3.4)**
- **gr** – go to references **(2.4.2)**
- **gs** – first non-white-space char **(2.4.1)**
- **gt** – top of screen **(2.4.1)**
- **gw** – two-char labels on words, label to go to word **(2.4.1)**
- **gy** – go to type definition **(2.4.2)**
- **g|** – beginning of line **(2.4.1)**
- **h/j/k/l** – left / up / down / right **(2.4.1)**
- **i** – before selection **(2.8.1)**

- **m** – closest surround pair **(2.5.2)**
- **ma<ch>** – match around delim <ch> **(2.14)**
- **ma<ch> / mi<ch>** – match around / inside the object indicated by <ch> below: **(2.5.2)**
- **md<ch>** – delete delim <ch> around selection **(2.14)**
- **md<ch>** – delete delim <ch> around selection **(2.8.3)**
- **mi<ch>** – match inside delim <ch> **(2.14)**
- **mm** – go to matching delim **(2.14)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.14)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.8.4)**
- **ms<ch>** – add delim <ch> around selection **(2.14)**
- **ms<ch>** – add delim <ch> around selection **(2.8.2)**
- **n** – next, previous match **(2.10)**
- **o** – add line and insert below cursor **(2.8.1)**
- **p** – paragraph **(2.5.2)**
- **p** – paste yank buf after the cursor **(2.9)**
- **r<ch>** – replace selection with <ch> **(2.9)**
- **s<regex>** – matches become selections **(2.7.1)**
- **t** – type or class **(2.5.2)**
- **t<ch>** – to <ch> exclusive (till) **(2.5.5)**
- **u / U** – undo / redo change in linear history **(2.3.1)**
- **v** – toggle select mode **(2.6)**
- **w / W** – to start of next word / WORD **(2.5.3)**
- **w / W** – word / WORD **(2.5.2)**
- **x** – current line, extend by line **(2.5.3)**
- **y** – selection -> yank buf **(2.9)**
- **zb** – align to bottom **(2.3.5.1)**
- **zc** – align to center **(2.3.5.1)**
- **zj** – scroll down **(2.3.5.1)**
- **zk** – scroll up **(2.3.5.1)**
- **zm** – align to middle horizontally **(2.3.5.1)**
- **zt** – align to top **(2.3.5.1)**
- **zz** – align to center **(2.3.5.1)**
- **|** – replace selection(s) with output **(2.15)**
- **~** – change case **(2.8.6)**