# Bill's Helix Cheat Sheet / Command Reference

## 1 Introduction

- Document version: 1.0.0-beta, April-2026
- Based on Helix version: 25.07.1.
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

### 1.1 Definitions

- **file** - the actual data on storage device
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor, not just the selection
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping

### 1.2 Typographic Conventions

- **`word`** - alphanumeric, punctuation-delimited
- **`WORD`** - whitespace-delimited
- **`Ctrl-c`** - Ctrl and c key pressed simultaneous.
- **`Alt-c`** - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- **`␣c`** is space followed by the character c.
- Metavars **`<regex>`**, **`<file>`** and **`<ch>`** represent user input. The angle-brackets are not part of the input.
- **`␣`**, **`<minus>`**, and **`<under>`** used for clarity. **`<enter>`**, **`<del>`**, **`<bksp>`**, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

### 1.3 Launching

- **`helix`**
- **`helix`** `<file>`
- **`helix`** `<file1> <file2> … <filen>`
- **`helix`** `–help`
- **`hx`** `in some distributions or by alias`

### 1.4 Basics

Editing paradigm: select first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
```

#### 1.4.1 Example

```
v3wd
        v – enter select mode
        3 – select 3
        w – words
        d – delete
```

#### 1.4.2 Samples

```
       wd – delete word
       xc – change line
       %y – yank entire file
```

### 1.5 Modes

As used in Helix documentation.

```
        : – command
        i – insert
        v – select or extend
        z – view - change view preserving
            selection
        g – goto
        m – match
   Ctrl-w – window
        ␣ – space
     [, ] – unimpaired
```

# 2 Primary Commands

## 2.1 Essentials

| | |
|---|---|
| `u / U` | undo / redo change in linear history |
| `Alt-u / Alt-U` | move backward / forward in tree history |
| `:ear / :lat` | move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) |
| `<nn><cmd>` | repeat <cmd> <nn> times |
| `Esc` | return to normal mode |

### 2.1.1 Quit

Add **!** suffix to force operation.

| | |
|---|---|
| `:wq` | write current buffer and quit |
| `:wq <file>` | write current buffer to <file> and quit |
| `:wqa` | write all buffer(s) and quit |
| `:q` | quit current buffer, exits if last |

### 2.1.2 Files

| | |
|---|---|
| `:o <file>` | open <file> in new buffer |
| `:w <file>` | write current buffer to <file> |
| `:hs <file>` | open/create <file> in new horizontal split |
| `:vs <file>` | open/create <file> in new vertical split |
| `␣wf` | open/create file(s) under selection(s) in horizontal split |
| `␣wF` | open/create file(s) under selection(s) in vertical split |
| `gf` | open/create file(s) under selection, open url under selection. |
| `␣f` | open file picker at LSP workspace root |
| `␣F` | open file picker at current working directory |
| `␣g` | open changed file picker |

#### 2.1.2.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

| | |
|---|---|
| `<enter>` | open selected in current view |
| `Ctrl-s` | open selected in new horizontal split |
| `Ctrl-v` | open selected in new vertical split |

### 2.1.3 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

| | |
|---|---|
| `:n` | create new scratch buffer |
| `:bc` | close current buffer |
| `:bca` | close all buffers |
| `:bco` | close all but current buffer |
| `:bn` | next buffer |
| `␣b` | open buffer picker |
| `ga` | go to last accessed/alternate buffer |
| `gm` | go to last modified/alternate buffer |
| `gn` | go to next buffer |
| `gp` | go to previous buffer |

### 2.1.4 Views

Ctrl-w and `␣w` are synonymous.

| | |
|---|---|
| `␣ws / ␣wv` | split horizontal / vertical, current buffer |
| `␣wns / ␣wnv` | split horizontal / vertical, new buffer |
| `␣wq` | close current split |
| `␣wo` | close all but current split |
| `␣ww` | next split |
| `␣wh/j/k/l` | move to buffer left / up / down / right |
| `␣wH/J/K/L` | swap split with buffer on left / up / down / right |
| `␣wt` | transpose split |

#### 2.1.4.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

| | |
|---|---|
| `Z` | enter sticky mode, exit with Esc |
| `zz, zc` | align to center |
| `zt` | align to top |
| `zb` | align to bottom |
| `zm` | align to middle horizontally |
| `zj` | scroll down |
| `zk` | scroll up |

### 2.1.5 Help

| | |
|---|---|
| `:tutor` | open tutorial |
| `␣?` | open command palette |

## 2.2 Movement

### 2.2.1 Cursor Movement

*Normal Mode*: motion replaces selection
*Select Mode*: motion extends selection

```
h/j/k/l – left / up / down / right
 gh, g| – beginning of line
 <nn>g| – column <nn>
     gl – end of line
     gg – top of file
  <nn>G,– line <nn>
 g<nn>g
     ge – bottom of file
     gw – two-char labels on words, label to
          go to word
      g.– to last modification in current file
     gj – down textual line
     gk – up textual line
     gs – first non-white-space char
     gt – top of screen
     gc – middle of screen
     gb – bottom of screen
```

### 2.2.2 By Language Server Protocol - Semantics

Requires LSP support.

```
 gd – go to definition
 gy – go to type definition
 gr – go to references
 gi – go to implementation
 ]d – next diagnostic
 [d – prior diagnostic
 ]D – last diagnostic
 [D – first diagnostic
```

### 2.2.3 By Treesitter - Syntax

Requires Treesitter support.

```
 ]f, [f – to next, prior function
 ]t, [t – to next, prior type definition
 ]T, [T – to next, prior test
 ]a, [a – to next, prior arg
 ]c, [c – to next, prior comment
 ]g, [g – to next, prior change
 ]G, [G – to last, first change
 Alt-e – move to end of parent node in
         syntax tree
 Alt-b – move to start of parent node in
         syntax tree
```

### 2.2.4 By Page

```
 Ctrl-b – page up
 Ctrl-f – page down
 Ctrl-u – half page up
 Ctrl-d – half page down
```

## 2.3 Selection

Selection: a range of characters between anchor and cursor
*Normal Mode*: move and select
*Select Mode*: move and extend selection

### 2.3.1 Operations

```
     % – select whole file
Alt-; – swap anchor and cursor
Alt-: – selection to normal direction (cursor
        at end)
Alt-o – expand selection syntax-aware
Alt-i – shrink selection
     ; – collapse selection(s) to cursor(s)
```

### 2.3.2 By TextObjects

```
 ma<ch> / – match around / inside the
 mi<ch>   object indicated by <ch> below:
     w / W – word / WORD
         p – paragraph
(, [, ', etc.– specified surround pairs
         m –  closest surround pair
         f – function
         t – type or class
         a – argument/parameter
         c – comment
         T – test
         g – change git hunk
```

### 2.3.3 By Syntactic Objects

```
 w / W – to start of next word / WORD
 e / E – to end of current word / WORD
 b / B – to start of current word / WORD
     x – current line, extend by line
     X – extend to line
Alt-x – shrink to line bounds
    ]p – to next paragraph
    [p – to prior paragraph
```

### 2.3.4 By Treesitter - Syntax

Requires Treesitter support.

```
Alt-o – expand selection to parent syntax
        node
Alt-i – shrink syntax tree object selection
Alt-p – select previous sibling node in
        syntax tree
Alt-n – select next sibling node in syntax
        tree
Alt-a – select all sibling nodes in syntax tree
Alt-I – select all children nodes in syntax
        tree
```

### 2.3.5 By Character Value

*Lower case:* forward
*Upper case:* backward

| | |
|---|---|
| `f<ch>, F<ch>` | – to <ch> inclusive (find) |
| `t<ch>, T<ch>` | – to <ch> exclusive (till) |
| `Alt-.` | – repeat last find / till |

## 2.4 Select Mode

*Movement*: extends selection
*Search*: adds to selection

| | |
|---|---|
| `v` | – toggle select mode |
| `Esc` | – return to normal |
| `)` | – cycle primary selection forward |
| `(` | – cycle primary selection backward |
| `Alt-,` | – remove primary selection |

## 2.5 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

### 2.5.1 Creating

Create multiple selections from selection.

| | |
|---|---|
| `s<regex>` | – matches become selections |
| `S` | – split on match |
| `Alt-s` | – split on newlines |
| `C, Alt-C` | – add selection below, above |

### 2.5.2 Operations

| | |
|---|---|
| `&` | – align on primary cursor |
| `Alt-<minus>` | – merge selections |
| `Alt-<under>` | – merge consecutive selections |
| `,` | – remove all except primary selection |
| `Alt-,` | – remove primary selection |
| `( / )` | – rotate primary backwards / forwards |
| `Alt-( / Alt-)` | – rotate content backward / forward |
| `K` | – keep selections matching the regex |
| `Alt-K` | – remove selections matching the regex |

## 2.6 Alter Buffer Content

### 2.6.1 Insert

| | |
|---|---|
| `i` | – before selection |
| `a` | – after selection |
| `I` | – at start of line |
| `A` | – at end of line |
| `o` | – add line and insert below cursor |
| `O` | – add line and insert above cursor |
| `Esc` | – end insert (return to normal) |
| `.` | – repeat last insert |

### 2.6.2 Add

| | |
|---|---|
| `]␣` | – newline below |
| `[␣` | – newline above |
| `ms<ch>` | – add delim <ch> around selection |

### 2.6.3 Delete

| | |
|---|---|
| `d` | – selection -> yank buf, delete selection |
| `Alt-d` | – delete, no save |
| `md<ch>` | – delete delim <ch> around selection |

### 2.6.4 Change

| | |
|---|---|
| `c` | – selection -> yank buf, change selection |
| `Alt-c` | – change, no save |
| `=` | – format by LSP |
| `mr<ch1><ch2>` | – replace delim <ch1> with <ch2> |

### 2.6.5 Indent Lines

| | |
|---|---|
| `>` | – Indent line(s) containing selection |
| `<` | – Undent line(s) containing selection |

### 2.6.6 Change Case

Change case of all letters in selection

| | |
|---|---|
| `~` | – change case |
| `` ` `` | – set lowercase |
| `Alt-` ` | – set uppercase |

### 2.6.7 Comments

All apply to selection.

| | |
|---|---|
| `␣c, Ctrl-c` | – Toggle comment |
| `␣C` | – Toggle block comment |
| `␣Alt-C` | – Toggle line comment |

### 2.6.8 Increment / Decrement

| | |
|---|---|
| `Ctrl-a` | – increment the selected number |
| `Ctrl-x` | – decrement the selected number |

### 2.6.9 Miscellaneous

| | |
|---|---|
| `J` | – join lines in a selection |
| `Alt-J` | – join lines inside selection and select the inserted space |
| `<under>` | – trim whitespace from selection |

## 2.7 Copy / Paste / Replace

- `y` – selection -> yank buf
- `p` – paste yank buf after the cursor
- `P` – paste yank buf before the cursor
- `␣y` – yank selection(s) -> system clipboard
- `␣Y` – yank main selection -> system clipboard
- `␣p / ␣P` – paste clipboard after / before selections(s)
- `␣R` – replace selection(s) with clipboard
- `r<ch>` – replace selection with <ch>
- `R` – replace selection with yank buf
- `"` – select register to yank to or paste from

## 2.8 Search

- `/<regex>` – search forward for regex
- `?<regex>` – search backward for regex
- `n, N` – next, previous match
- `*` – search for current selection, respect word boundaries
- `Alt-*` – search for current selection

## 2.9 Registers

Identified by single char <ch>

- `"<ch>` – change to reg <ch>
- `"<ch>y` – yank into reg <ch>
- `"<ch>p` – paste from reg <ch>
- `"<ch>R` – replace with reg <ch>

## 2.10 Macros

- `"<ch>Q` – toggle capture to reg <ch>, default @
- `"<ch>q` – play macro in reg <ch>, default @

## 2.11 Jumplists

- `Ctrl-s` – save current position to jumplist
- `Ctrl-i` – move forward in jumplist
- `Ctrl-o` – move backwards in jumplist
- `␣j` – open jumplist picker

## 2.12 Match Mode

With regard to balanced delimiters.

- `mm` – go to matching delim
- `mi<ch>` – match inside delim <ch>
- `ma<ch>` – match around delim <ch>
- `ms<ch>` – add delim <ch> around selection
- `md<ch>` – delete delim <ch> around selection
- `mr<ch1><ch2>` – replace delim <ch1> with <ch2>

## 2.13 Shell

All commands pipe each selection to shell command.

- `|` – replace selection(s) with output
- `Alt-|` – ignore output
- `!` – insert output before each selection(s)
- `Alt-!` – append output after each selection(s)
- `$` – keep selection(s) where command returned 0

## 2.14 Approaching an IDE

- `␣G` – debug - experimental
- `␣k` – show documentation for item under cursor
- `␣s` – open document symbol picker
- `␣S` – open workspace symbol picker
- `␣d` – open document diagnostics picker
- `␣D` – open workspace diagnostics picker
- `␣r` – rename symbol
- `␣a` – apply code action
- `␣h` – select symbol references for symbol under cursor

## 2.15 Editor Configuration

- `:config-open` – open the config file
- `:config-open-workspace` – open the workspace config file
- `:config-reload` – reload the config file

## 2.16 Miscellaneous

- `␣'` – open last picker
- `␣/` – open global search in workspace folder picker

# 3 Commands in Specific Contexts

## 3.1 Insert Mode Editing

Navigation keys shown.

| | |
|---|---|
| Ctrl-s | commit undo checkpoint |
| Ctrl-x | autocomplete |
| Ctrl-r | insert a register content |
| Ctrl-w, Alt-<bksp> | delete previous word |
| Alt-d, Alt-<del> | delete next word |
| Ctrl-u | delete to start of line |
| Ctrl-k | delete to end of line |
| Ctrl-h, <bksp>, Shift-<bksp> | delete previous char |
| Ctrl-d, <del> | delete next char |
| Ctrl-j, <enter> | insert new line |
| <Up> <Down> <Left> <Right> <PageUp> <PageDown> <Home> <End> | usual meaning but discouraged |

## 3.2 Command Line Editing

| | |
|---|---|
| Esc, Ctrl-c | close prompt |
| <enter> | open selected |
| <tab> | select next completion item |
| <backtab> | select previous completion item |
| Alt-b | backward a word |
| Ctrl-b | backward a char |
| Alt-f | forward a word |
| Ctrl-f | forward a char |
| Ctrl-e | to prompt end |
| Ctrl-a | to prompt start |
| Ctrl-w, Ctrl-<bksp> | delete previous word |
| Alt-d, Ctrl-<del> | delete next word |
| Ctrl-u | delete to start of line |
| Ctrl-k | delete to end of line |
| <bksp>, Ctrl-h | delete previous char |
| <del>, Ctrl-d | delete next char |
| Ctrl-s | insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) |
| Ctrl-p | select previous history |
| Ctrl-n | select next history |
| Ctrl-r | insert the content of the register selected by following input char |

## 3.3 Pickers

Navigation keys shown.

| | |
|---|---|
| Shift-<tab>, Ctrl-p, <Up> | previous entry |
| <tab>, Ctrl-n, <Down> | next entry |
| <Home> | to first entry |
| <End> | to last entry |
| Ctrl-u, <PageUp> | page up |
| Ctrl-d, <PageDown> | page down |
| <enter> | open selected |
| Alt-<enter> | open selected in the background without closing the picker |
| Ctrl-s | open horizontally |
| Ctrl-v | open vertically |
| Ctrl-t | toggle preview |
| Esc, Ctrl-c | close picker |

## 3.4 Popups

Displays documentation for item under cursor.

| | |
|---|---|
| Ctrl-u | scroll up |
| Ctrl-d | scroll down |

## 3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

| | |
|---|---|
| Shift-Tab, Ctrl-p | previous entry |
| Tab, Ctrl-n | next entry |
| <enter> | close menu and accept completion |
| Ctrl-c | close menu and reject completion |

## 3.6 Signature-help Popup

Displays the signature of the selected completion item.

| | |
|---|---|
| Alt-p | previous signature |
| Alt-n | next signature |

# 4 Command Index

- ␣' – open last picker **(2.16)**
- ␣/ – open global search in workspace folder picker **(2.16)**
- ␣? – open command palette **(2.1.5)**
- ␣Alt-C – Toggle line comment **(2.6.7)**
- ␣C – Toggle block comment **(2.6.7)**
- ␣D – open workspace diagnostics picker **(2.14)**
- ␣F – open file picker at current working directory **(2.1.2)**
- ␣G – debug - experimental **(2.14)**
- ␣R – replace selection(s) with clipboard **(2.7)**
- ␣S – open workspace symbol picker **(2.14)**
- ␣Y – yank main selection -> system clipboard **(2.7)**
- ␣a – apply code action **(2.14)**
- ␣b – open buffer picker **(2.1.3)**
- ␣c – Toggle comment **(2.6.7)**
- ␣d – open document diagnostics picker **(2.14)**
- ␣f – open file picker at LSP workspace root **(2.1.2)**
- ␣g – open changed file picker **(2.1.2)**
- ␣h – select symbol references for symbol under cursor **(2.14)**
- ␣j – open jumplist picker **(2.11)**
- ␣k – show documentation for item under cursor **(2.14)**
- ␣p / ␣P – paste clipboard after / before selections(s) **(2.7)**
- ␣r – rename symbol **(2.14)**
- ␣s – open document symbol picker **(2.14)**
- ␣wF – open/create file(s) under selection(s) in vertical split **(2.1.2)**
- ␣wH/J/K/L – swap split with buffer on left / up / down / right **(2.1.4)**
- ␣wf – open/create file(s) under selection(s) in horizontal split **(2.1.2)**
- ␣wh/j/k/l – move to buffer left / up / down / right **(2.1.4)**
- ␣wns / ␣wnv – split horizontal / vertical, new buffer **(2.1.4)**
- ␣wo – close all but current split **(2.1.4)**
- ␣wq – close current split **(2.1.4)**
- ␣ws / ␣wv – split horizontal / vertical, current buffer **(2.1.4)**
- ␣wt – transpose split **(2.1.4)**
- ␣ww – next split **(2.1.4)**

- ␣y – yank selection(s) -> system clipboard **(2.7)**
- ! – insert output before each selection(s) **(2.13)**
- " – select register to yank to or paste from **(2.7)**
- "<ch> – change to reg <ch> **(2.9)**
- "<ch>Q – toggle capture to reg <ch>, default @ **(2.10)**
- "<ch>R – replace with reg <ch> **(2.9)**
- "<ch>p – paste from reg <ch> **(2.9)**
- "<ch>q – play macro in reg <ch>, default @ **(2.10)**
- "<ch>y – yank into reg <ch> **(2.9)**
- $ – keep selection(s) where command returned 0 **(2.13)**
- % – select whole file **(2.3.1)**
- & – align on primary cursor **(2.5.2)**
- ' – specified surround pairs **(2.3.2)**
- ( – cycle primary selection backward **(2.4)**
- ( – specified surround pairs **(2.3.2)**
- ( / ) – rotate primary backwards / forwards **(2.5.2)**
- ) – cycle primary selection forward **(2.4)**
- * – search for current selection, respect word boundaries **(2.8)**
- , – remove all except primary selection **(2.5.2)**
- . – repeat last insert **(2.6.1)**
- /<regex> – search forward for regex **(2.8)**
- :bc – close current buffer **(2.1.3)**
- :bca – close all buffers **(2.1.3)**
- :bco – close all but current buffer **(2.1.3)**
- :bn – next buffer **(2.1.3)**
- :config-open – open the config file **(2.15)**
- :config-open-workspace – open the workspace config file **(2.15)**
- :config-reload – reload the config file **(2.15)**
- :ear / :lat – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.1)**
- :hs <file> – open/create <file> in new horizontal split **(2.1.2)**
- :n – create new scratch buffer **(2.1.3)**
- :o <file> – open <file> in new buffer **(2.1.2)**
- :q – quit current buffer, exits if last **(2.1.1)**
- :tutor – open tutorial **(2.1.5)**

- :vs <file> – open/create <file> in new vertical split **(2.1.2)**
- :w <file> – write current buffer to <file> **(2.1.2)**
- :wq – write current buffer and quit **(2.1.1)**
- :wq <file> – write current buffer to <file> and quit **(2.1.1)**
- :wqa – write all buffer(s) and quit **(2.1.1)**
- ; – collapse selection(s) to cursor(s) **(2.3.1)**
- < – Undent line(s) containing selection **(2.6.5)**
- <Down> – next entry **(3.3)**
- <End> – to last entry **(3.3)**
- <Home> – to first entry **(3.3)**
- <PageDown> – page down **(3.3)**
- <PageUp> – page up **(3.3)**
- <Up> – previous entry **(3.3)**
- <Up> – usual meaning but discouraged **(3.1)**
- <Down>
- <Left>
- <Right>
- <PageUp>
- <PageDown>
- <Home>
- <End>
- <backtab> – select previous completion item **(3.2)**
- <bksp> – delete previous char **(3.1)**
- <bksp> – delete previous char **(3.2)**
- <del> – delete next char **(3.1)**
- <del> – delete next char **(3.2)**
- <enter> – close menu and accept completion **(3.5)**
- <enter> – insert new line **(3.1)**
- <enter> – open selected **(3.2)**
- <enter> – open selected **(3.3)**
- <enter> – open selected in current view **(2.1.2.1)**
- <nn><cmd> – repeat <cmd> <nn> times **(2.1)**
- <nn>G – line <nn> **(2.2.1)**
- <nn>g| – column <nn> **(2.2.1)**
- <tab> – next entry **(3.3)**
- <tab> – select next completion item **(3.2)**
- <under> – trim whitespace from selection **(2.6.9)**
- = – format by LSP **(2.6.4)**
- > – Indent line(s) containing selection **(2.6.5)**
- ?<regex> – search backward for regex **(2.8)**
- A – at end of line **(2.6.1)**
- Alt-! – append output after each selection(s) **(2.13)**

- **Alt-( / Alt-)** – rotate content backward / forward **(2.5.2)**
- **Alt-*** – search for current selection **(2.8)**
- **Alt-,** – remove primary selection **(2.4)**
- **Alt-,** – remove primary selection **(2.5.2)**
- **Alt-.** – repeat last find / till **(2.3.5)**
- **Alt-:** – selection to normal direction (cursor at end) **(2.3.1)**
- **Alt-;** – swap anchor and cursor **(2.3.1)**
- **Alt-<bksp>** – delete previous word **(3.1)**
- **Alt-<del>** – delete next word **(3.1)**
- **Alt-<enter>** – open selected in the background without closing the picker **(3.3)**
- **Alt-<minus>** – merge selections **(2.5.2)**
- **Alt-<under>** – merge consecutive selections **(2.5.2)**
- **Alt-C** – add selection below, above **(2.5.1)**
- **Alt-I** – select all children nodes in syntax tree **(2.3.4)**
- **Alt-J** – join lines inside selection and select the inserted space **(2.6.9)**
- **Alt-K** – remove selections matching the regex **(2.5.2)**
- **Alt-`** – set uppercase **(2.6.6)**
- **Alt-a** – select all sibling nodes in syntax tree **(2.3.4)**
- **Alt-b** – backward a word **(3.2)**
- **Alt-b** – move to start of parent node in syntax tree **(2.2.3)**
- **Alt-c** – change, no save **(2.6.4)**
- **Alt-d** – delete next word **(3.1)**
- **Alt-d** – delete next word **(3.2)**
- **Alt-d** – delete, no save **(2.6.3)**
- **Alt-e** – move to end of parent node in syntax tree **(2.2.3)**
- **Alt-f** – forward a word **(3.2)**
- **Alt-i** – shrink selection **(2.3.1)**
- **Alt-i** – shrink syntax tree object selection **(2.3.4)**
- **Alt-n** – next signature **(3.6)**
- **Alt-n** – select next sibling node in syntax tree **(2.3.4)**
- **Alt-o** – expand selection syntax-aware **(2.3.1)**
- **Alt-o** – expand selection to parent syntax node **(2.3.4)**
- **Alt-p** – previous signature **(3.6)**
- **Alt-p** – select previous sibling node in syntax tree **(2.3.4)**
- **Alt-s** – split on newlines **(2.5.1)**
- **Alt-u / Alt-U** – move backward / forward in tree history **(2.1)**
- **Alt-x** – shrink to line bounds **(2.3.3)**
- **Alt-|** – ignore output **(2.13)**
- **C** – add selection below, above **(2.5.1)**
- **Ctrl-<bksp>** – delete previous word **(3.2)**
- **Ctrl-<del>** – delete next word **(3.2)**
- **Ctrl-a** – increment the selected number **(2.6.8)**
- **Ctrl-a** – to prompt start **(3.2)**
- **Ctrl-b** – backward a char **(3.2)**
- **Ctrl-b** – page up **(2.2.4)**
- **Ctrl-c** – Toggle comment **(2.6.7)**
- **Ctrl-c** – close menu and reject completion **(3.5)**
- **Ctrl-c** – close picker **(3.3)**
- **Ctrl-c** – close prompt **(3.2)**
- **Ctrl-d** – delete next char **(3.1)**
- **Ctrl-d** – delete next char **(3.2)**
- **Ctrl-d** – half page down **(2.2.4)**
- **Ctrl-d** – page down **(3.3)**
- **Ctrl-d** – scroll down **(3.4)**
- **Ctrl-e** – to prompt end **(3.2)**
- **Ctrl-f** – forward a char **(3.2)**
- **Ctrl-f** – page down **(2.2.4)**
- **Ctrl-h** – delete previous char **(3.1)**
- **Ctrl-h** – delete previous char **(3.2)**
- **Ctrl-i** – move forward in jumplist **(2.11)**
- **Ctrl-j** – insert new line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.2)**
- **Ctrl-n** – next entry **(3.3)**
- **Ctrl-n** – next entry **(3.5)**
- **Ctrl-n** – select next history **(3.2)**
- **Ctrl-o** – move backwards in jumplist **(2.11)**
- **Ctrl-p** – previous entry **(3.3)**
- **Ctrl-p** – previous entry **(3.5)**
- **Ctrl-p** – select previous history **(3.2)**
- **Ctrl-r** – insert a register content **(3.1)**
- **Ctrl-r** – insert the content of the register selected by following input char **(3.2)**
- **Ctrl-s** – commit undo checkpoint **(3.1)**
- **Ctrl-s** – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
- **Ctrl-s** – open horizontally **(3.3)**
- **Ctrl-s** – open selected in new horizontal split **(2.1.2.1)**
- **Ctrl-s** – save current position to jumplist **(2.11)**
- **Ctrl-t** – toggle preview **(3.3)**
- **Ctrl-u** – delete to start of line **(3.1)**
- **Ctrl-u** – delete to start of line **(3.2)**
- **Ctrl-u** – half page up **(2.2.4)**
- **Ctrl-u** – page up **(3.3)**
- **Ctrl-u** – scroll up **(3.4)**
- **Ctrl-v** – open selected in new vertical split **(2.1.2.1)**
- **Ctrl-v** – open vertically **(3.3)**
- **Ctrl-w** – delete previous word **(3.1)**
- **Ctrl-w** – delete previous word **(3.2)**
- **Ctrl-x** – autocomplete **(3.1)**
- **Ctrl-x** – decrement the selected number **(2.6.8)**
- **Esc** – close picker **(3.3)**
- **Esc** – close prompt **(3.2)**
- **Esc** – end insert (return to normal) **(2.6.1)**
- **Esc** – return to normal **(2.4)**
- **Esc** – return to normal mode **(2.1)**
- **F<ch>** – to <ch> inclusive (find) **(2.3.5)**
- **I** – at start of line **(2.6.1)**
- **J** – join lines in a selection **(2.6.9)**
- **K** – keep selections matching the regex **(2.5.2)**
- **N** – next, previous match **(2.8)**
- **O** – add line and insert above cursor **(2.6.1)**
- **P** – paste yank buf before the cursor **(2.7)**
- **R** – replace selection with yank buf **(2.7)**
- **S** – split on match **(2.5.1)**
- **Shift-<bksp>** – delete previous char **(3.1)**
- **Shift-<tab>** – previous entry **(3.3)**
- **Shift-Tab** – previous entry **(3.5)**
- **T** – test **(2.3.2)**
- **T<ch>** – to <ch> exclusive (till) **(2.3.5)**
- **Tab** – next entry **(3.5)**
- **X** – extend to line **(2.3.3)**
- **Z** – enter sticky mode, exit with Esc **(2.1.4.1)**
- **[␣** – newline above **(2.6.2)**
- **[** – specified surround pairs **(2.3.2)**
- **[D** – first diagnostic **(2.2.2)**
- **[G** – to last, first change **(2.2.3)**
- **[T** – to next, prior test **(2.2.3)**
- **[a** – to next, prior arg **(2.2.3)**
- **[c** – to next, prior comment **(2.2.3)**
- **[d** – prior diagnostic **(2.2.2)**

`[f` – to next, prior function **(2.2.3)**
`[g` – to next, prior change **(2.2.3)**
`[p` – to prior paragraph **(2.3.3)**
`[t` – to next, prior type definition **(2.2.3)**
`]␣` – newline below **(2.6.2)**
`]D` – last diagnostic **(2.2.2)**
`]G` – to last, first change **(2.2.3)**
`]T` – to next, prior test **(2.2.3)**
`]a` – to next, prior arg **(2.2.3)**
`]c` – to next, prior comment **(2.2.3)**
`]d` – next diagnostic **(2.2.2)**
`]f` – to next, prior function **(2.2.3)**
`]g` – to next, prior change **(2.2.3)**
`]p` – to next paragraph **(2.3.3)**
`]t` – to next, prior type definition **(2.2.3)**
`` ` `` – set lowercase **(2.6.6)**
`a` – after selection **(2.6.1)**
`a` – argument/parameter **(2.3.2)**
`b / B` – to start of current word / WORD **(2.3.3)**
`c` – comment **(2.3.2)**
`c` – selection -> yank buf, change selection **(2.6.4)**
`d` – selection -> yank buf, delete selection **(2.6.3)**
`e / E` – to end of current word / WORD **(2.3.3)**
`etc.` – specified surround pairs **(2.3.2)**
`f` – function **(2.3.2)**
`f<ch>` – to <ch> inclusive (find) **(2.3.5)**
`g` – change git hunk **(2.3.2)**
`g.` – to last modification in current file **(2.2.1)**
`g<nn>g` – line <nn> **(2.2.1)**
`ga` – go to last accessed/alternate buffer **(2.1.3)**
`gb` – bottom of screen **(2.2.1)**
`gc` – middle of screen **(2.2.1)**
`gd` – go to definition **(2.2.2)**
`ge` – bottom of file **(2.2.1)**
`gf` – open/create file(s) under selection, open url under selection. **(2.1.2)**
`gg` – top of file **(2.2.1)**
`gh` – beginning of line **(2.2.1)**
`gi` – go to implementation **(2.2.2)**
`gj` – down textual line **(2.2.1)**
`gk` – up textual line **(2.2.1)**
`gl` – end of line **(2.2.1)**
`gm` – go to last modified/alternate buffer **(2.1.3)**
`gn` – go to next buffer **(2.1.3)**
`gp` – go to previous buffer **(2.1.3)**

`gr` – go to references **(2.2.2)**
`gs` – first non-white-space char **(2.2.1)**
`gt` – top of screen **(2.2.1)**
`gw` – two-char labels on words, label to go to word **(2.2.1)**
`gy` – go to type definition **(2.2.2)**
`g|` – beginning of line **(2.2.1)**
`h/j/k/l` – left / up / down / right **(2.2.1)**
`i` – before selection **(2.6.1)**
`m` – closest surround pair **(2.3.2)**
`ma<ch>` – match around delim <ch> **(2.12)**
`ma<ch> /` – match around / inside the object
`mi<ch>` indicated by <ch> below: **(2.3.2)**
`md<ch>` – delete delim <ch> around selection **(2.12)**
`md<ch>` – delete delim <ch> around selection **(2.6.3)**
`mi<ch>` – match inside delim <ch> **(2.12)**
`mm` – go to matching delim **(2.12)**
`mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.12)**
`mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.6.4)**
`ms<ch>` – add delim <ch> around selection **(2.12)**
`ms<ch>` – add delim <ch> around selection **(2.6.2)**
`n` – next, previous match **(2.8)**
`o` – add line and insert below cursor **(2.6.1)**
`p` – paragraph **(2.3.2)**
`p` – paste yank buf after the cursor **(2.7)**
`r<ch>` – replace selection with <ch> **(2.7)**
`s<regex>` – matches become selections **(2.5.1)**
`t` – type or class **(2.3.2)**
`t<ch>` – to <ch> exclusive (till) **(2.3.5)**
`u / U` – undo / redo change in linear history **(2.1)**
`v` – toggle select mode **(2.4)**
`w / W` – to start of next word / WORD **(2.3.3)**
`w / W` – word / WORD **(2.3.2)**
`x` – current line, extend by line **(2.3.3)**
`y` – selection -> yank buf **(2.7)**
`zb` – align to bottom **(2.1.4.1)**
`zc` – align to center **(2.1.4.1)**
`zj` – scroll down **(2.1.4.1)**
`zk` – scroll up **(2.1.4.1)**
`zm` – align to middle horizontally **(2.1.4.1)**
`zt` – align to top **(2.1.4.1)**
`zz` – align to center **(2.1.4.1)**
`|` – replace selection(s) with output **(2.13)**
`~` – change case **(2.6.6)**