Bill's Helix Cheat Sheet / Command Reference

1 Introduction

1.1 Metadata

- Document version: 1.1.0-beta, 27-Apr-2026
- Based on Helix version: 25.07.1
- Built with Typst version: 0.14.2
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.2 Definitions

- **file** - data on storage device, e.g., hard disk or ssd
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.3 Typographic Conventions

- `word` - alphanumeric, punctuation-delimited
- `WORD` - whitespace-delimited
- `Ctrl-c` - Ctrl and c key pressed simultaneous.
- `Alt-c` - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- `␣c` is space followed by the character c.
- Metavars `<regex>`, `<file>` and `<ch>` represent user input. The angle-brackets are not part of the input.
- `␣`, `<minus>`, and `<under>` used for clarity. `<enter>`, `<del>`, `<bksp>`, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.4 Launching

```
helix
helix <file>
helix <file1> <file2> ... <filen>
helix <directory>
helix --help
hx in some distributions or by alias
```

2 Primary Commands

2.1 Editing Paradigm

Selection first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
      v3wd – enter select mode, select 3 words, delete
```

2.2 Regular Expressions

Helix uses Rust's regex. Escape following metachars with <backslash> when searching for literal value.

```
        . – any character
        * – zero or more
        + – one or more
        ? – zero or one / lazy match
        ^ – start of line / negation in class
        $ – end of line
      ( ) – capture group
      [ ] – character class
      { } – repetition count
        | – alternation
        \ – escape character itself
```

2.3 Essentials

2.3.1 Undo / Repeat / Normal Mode

```
        u / U – undo / redo change in linear history
Alt-u / Alt-U – move backward / forward in tree history
  :ear / :lat – move backward / forward in history by
                step count or time span (1s, 2m, 3h, 4d)
    <nn><cmd> – repeat <cmd> <nn> times
          Esc – return to normal mode
```

2.3.2 Quit

Add **!** suffix to force operation.

```
       :wq – write current buffer and quit
:wq <file> – write current buffer to <file> and quit
      :wqa – write all buffer(s) and quit
        :q – quit current buffer, exits if last
```

2.3.3 Files

```
 :o <file> – open <file> in new buffer
 :w <file> – write current buffer to <file>

:hs <file> – open/create <file> in new horizontal split
:vs <file> – open/create <file> in new vertical split
       ␣wf – open/create file(s) under selection(s) in
             horizontal split
       ␣wF – open/create file(s) under selection(s) in
             vertical split
        gf – open/create file(s) under selection, open url
             under selection.

        ␣f – open file picker at LSP workspace root
        ␣F – open file picker at current working directory
        ␣g – open changed file picker
```

2.3.3.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

```
<enter> – open selected in current view
 Ctrl-s – open selected in new horizontal split
 Ctrl-v – open selected in new vertical split
```

2.3.4 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

```
   :n – create new scratch buffer
  :bc – close current buffer
 :bca – close all buffers
 :bco – close all but current buffer
  :bn – next buffer
   ␣b – open buffer picker

   ga – go to last accessed/alternate buffer
   gm – go to last modified/alternate buffer
   gn – go to next buffer
   gp – go to previous buffer
```

2.3.5 Views

Ctrl-w and ␣w are synonymous.

```
 ␣ws / ␣wv  – split horizontal / vertical, current buffer
␣wns / ␣wnv – split horizontal / vertical, new buffer
       ␣wq – close current split
       ␣wo – close all but current split
       ␣ww – next split

  ␣wh/j/k/l – move to buffer left / up / down / right
  ␣wH/J/K/L – swap split with buffer on left / up / down /
              right
       ␣wt – transpose split
```

2.3.5.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

```
     Z – enter sticky mode, exit with Esc

zz, zc – align to center
    zt – align to top
    zb – align to bottom
    zm – align to middle horizontally
    zj – scroll down
    zk – scroll up
```

2.3.6 Help

```
 :tutor – open tutorial
     ␣? – open command palette
```

2.4 Movement

2.4.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

```
     h/j/k/l – left / up / down / right
      gh, g| – beginning of line
      <nn>g| – column <nn>
          gl – end of line
          gg – top of file
<nn>G, g<nn>g – line <nn>
          ge – bottom of file
          gw – two-char labels on words, label to go to
               word

          g.– to last modification in current file
          gj – down textual line
          gk – up textual line

          gs – first non-white-space char
          gt – top of screen
          gc – middle of screen
          gb – bottom of screen
```

2.4.2 By Language Server Protocol

Requires LSP support.

```
  gd – go to definition
  gy – go to type definition
  gr – go to references
  gi – go to implementation

  ]d – next diagnostic
  [d – prior diagnostic
  ]D – last diagnostic
  [D – first diagnostic
```

2.4.3 By Treesitter - Syntax

Requires Treesitter support.

```
  ]f, [f – to next, prior function
  ]t, [t – to next, prior type definition
  ]T, [T – to next, prior test
  ]a, [a – to next, prior arg
  ]c, [c – to next, prior comment
  ]g, [g – to next, prior change
  ]G, [G – to last, first change

Alt-e – move to end of parent node in syntax tree
Alt-b – move to start of parent node in syntax tree
```

2.4.4 By Page

```
Ctrl-b – page up
Ctrl-f – page down
Ctrl-u – half page up
Ctrl-d – half page down
```

2.5 Selection

Selection: a range of characters between anchor and cursor
Normal Mode: move and select
Select Mode: move and extend selection

2.5.1 Operations

```
     % – select whole file
Alt-; – swap anchor and cursor
Alt-: – selection to normal direction (cursor at end)
Alt-o – expand selection syntax-aware
Alt-i – shrink selection
     ; – collapse selection(s) to cursor(s)
```

2.5.2 By TextObjects

```
ma<ch> / mi<ch> – match around / inside the object
                  indicated by <ch> below:
          w / W – word / WORD
              p – paragraph
  (, [, ', etc.– specified surround pairs
              m –  closest surround pair
              f – function
              t – type or class
              a – argument/parameter
              c – comment
              T – test
              g – change git hunk
```

2.5.3 By Syntactic Objects

```
    w / W – to start of next word / WORD
    e / E – to end of current word / WORD
    b / B – to start of current word / WORD
        x – current line, extend by line
        X – extend to line
    Alt-x – shrink to line bounds
       ]p – to next paragraph
       [p – to prior paragraph
```

2.5.4 By Treesitter - Syntax

Requires Treesitter support.

```
    Alt-o – expand selection to parent syntax node
    Alt-i – shrink syntax tree object selection
    Alt-p – select previous sibling node in syntax tree
    Alt-n – select next sibling node in syntax tree
    Alt-a – select all sibling nodes in syntax tree
    Alt-I – select all children nodes in syntax tree
```

2.5.5 By Character Value

Lower case: forward
Upper case: backward

```
f<ch>, F<ch> – to <ch> inclusive (find)
t<ch>, T<ch> – to <ch> exclusive (till)
      Alt-.  – repeat last find / till
```

2.6 Select Mode

Movement: extends selection
Search: adds to selection

```
       v – toggle select mode
     Esc – return to normal
       ) – cycle primary selection forward
       ( – cycle primary selection backward
  Alt-,  – remove primary selection
```

2.7 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.7.1 Creating

Create multiple selections from selection.

```
  s<regex> – matches become selections
         S – split on match
     Alt-s – split on newlines
 C / Alt-C – add selection below / above
```

2.7.2 Operations

```
             & – align on primary cursor
  Alt-<minus> – merge selections
  Alt-<under> – merge consecutive selections
            , – remove all except primary selection
       Alt-,  – remove primary selection
         ( / ) – rotate primary backwards / forwards
Alt-( / Alt-) – rotate content backward / forward
             K – keep selections matching the regex
       Alt-K – remove selections matching the regex
```

2.8 Alter Buffer Content

2.8.1 Insert

```
       i – before selection
       a – after selection
       I – at start of line
       A – at end of line
       o – add line and insert below cursor
       O – add line and insert above cursor
     Esc – end insert (return to normal)
       . – repeat last insert
```

2.8.2 Add

```
     ]␣ – newline below
     [␣ – newline above
  ms<ch> – add delim <ch> around selection
```

2.8.3 Delete

```
       d – selection -> yank buf, delete selection
   Alt-d – delete, no save
  md<ch> – delete delim <ch> around selection
```

2.8.4 Change

```
       c – selection -> yank buf, change selection
   Alt-c – change, no save
       = – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.8.5 Indent Lines

```
> – Indent line(s) containing selection
< – Undent line(s) containing selection
```

2.8.6 Change Case

Change case of all letters in selection

```
~ – change case
` – set lowercase
Alt-` – set uppercase
```

2.8.7 Comments

All apply to selection.

```
␣c, Ctrl-c – Toggle comment
       ␣C – Toggle block comment
  ␣Alt-C – Toggle line comment
```

2.8.8 Increment / Decrement

```
Ctrl-a – increment the selected number
Ctrl-x – decrement the selected number
```

2.8.9 Miscellaneous

```
           J – join lines in a selection
       Alt-J – join lines inside selection and select
               the inserted space
     <under> – trim whitespace from selection
:reflow <width> – wrap selection to <width>, default 80
       :sort – sort ranges in selection
     :format – format file using external formatter /
               language server
```

2.9 Copy / Paste / Replace

```
          y – selection -> yank buf
          p – paste yank buf after the cursor
          P – paste yank buf before the cursor
         ␣y – yank selection(s) -> system clipboard
         ␣Y – yank main selection -> system clipboard
  ␣p / ␣P – paste clipboard after / before selections(s)
         ␣R – replace selection(s) with clipboard
      r<ch> – replace selection with <ch>
          R – replace selection with yank buf
          " – select register to yank to or paste from
```

2.10 Search

```
  /<regex> – search forward for regex
  ?<regex> – search backward for regex
      n, N – next, previous match
         * – search for current selection, respect word
             boundaries
     Alt-* – search for current selection
```

2.11 Registers

Identified by single char <ch>

```
  "<ch> – change to reg <ch>
 "<ch>y – yank into reg <ch>
 "<ch>p – paste from reg <ch>
 "<ch>R – replace with reg <ch>
```

2.12 Macros

```
 "<ch>Q – toggle capture to reg <ch>, default @
 "<ch>q – play macro in reg <ch>, default @
```

2.13 Jumplists

```
Ctrl-s – save current position to jumplist
Ctrl-i – move forward in jumplist
Ctrl-o – move backwards in jumplist
    ␣j – open jumplist picker
```

2.14 Match Mode

With regard to balanced delimiters.

```
        mm – go to matching delim
   mi<ch> – match inside delim <ch>
   ma<ch> – match around delim <ch>
   ms<ch> – add delim <ch> around selection
   md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.15 Shell

All commands pipe each selection to shell command.

```
     | – replace selection(s) with output
  Alt-| – ignore output
     ! – insert output before each selection(s)
  Alt-! – append output after each selection(s)
     $ – keep selection(s) where command returned 0
```

2.16 Approaching an IDE

```
    ␣G – debug - experimental
    ␣k – show documentation for item under cursor
    ␣s – open document symbol picker
    ␣S – open workspace symbol picker
    ␣d – open document diagnostics picker
    ␣D – open workspace diagnostics picker
    ␣r – rename symbol
    ␣a – apply code action
    ␣h – select symbol references for symbol under
         cursor
```

2.17 Editor Configuration

```
       :config-open – open the config file
:config-open-workspace – open the workspace config file
     :config-reload – reload the config file
```

2.18 Miscellaneous

```
    ␣' – open last picker
    ␣/ – open global search in workspace folder picker
```

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

```
                    Ctrl-s – commit undo checkpoint
                    Ctrl-x – autocomplete
                    Ctrl-r – insert a register content
        Ctrl-w, Alt-<bksp> – delete previous word
          Alt-d, Alt-<del> – delete next word
                    Ctrl-u – delete to start of line
                    Ctrl-k – delete to end of line
    Ctrl-h, <bksp>, Shift-– delete previous char
                    <bksp>
            Ctrl-d, <del> – delete next char
           Ctrl-j, <enter> – insert new line
      <Up>, <Down>, <Left>,– usual meaning but
         <Right>, <PageUp>, discouraged
 <PageDown>, <Home>, <End>
```

3.2 Command Line Editing

```
         Esc, Ctrl-c – close prompt
             <enter> – open selected
               <tab> – select next completion item
           <backtab> – select previous completion item
               Alt-b – backward a word
              Ctrl-b – backward a char
               Alt-f – forward a word
              Ctrl-f – forward a char
              Ctrl-e – to prompt end
              Ctrl-a – to prompt start
Ctrl-w, Ctrl-<bksp> – delete previous word
  Alt-d, Ctrl-<del> – delete next word
              Ctrl-u – delete to start of line
              Ctrl-k – delete to end of line
     <bksp>, Ctrl-h – delete previous char
      <del>, Ctrl-d – delete next char
              Ctrl-s – insert a word under doc cursor
                       (may be changed to Ctrl-r Ctrl-w
                       later)
              Ctrl-p – select previous history
              Ctrl-n – select next history
              Ctrl-r – insert the content of the register
                       selected by following input char
```

3.3 Pickers

Navigation keys shown.

```
Shift-<tab>, Ctrl-p, <Up> – previous entry
    <tab>, Ctrl-n, <Down> – next entry
                   <Home> – to first entry
                    <End> – to last entry
         Ctrl-u, <PageUp> – page up
       Ctrl-d, <PageDown> – page down
                  <enter> – open selected
             Alt-<enter> – open selected in the
                           background without
                           closing the picker
                   Ctrl-s – open horizontally
                   Ctrl-v – open vertically
                   Ctrl-t – toggle preview
             Esc, Ctrl-c – close picker
```

3.4 Popups

Displays documentation for item under cursor.

```
     Ctrl-u – scroll up
     Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
Shift-Tab, Ctrl-p – previous entry
      Tab, Ctrl-n – next entry
          <enter> – close menu and accept completion
           Ctrl-c – close menu and reject completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
     Alt-p – previous signature
     Alt-n – next signature
```

4 Command Index

- `␣'` – open last picker **(2.18)**
- `␣/` – open global search in workspace folder picker **(2.18)**
- `␣?` – open command palette **(2.3.6)**
- `␣Alt-C` – Toggle line comment **(2.8.7)**
- `␣C` – Toggle block comment **(2.8.7)**
- `␣D` – open workspace diagnostics picker **(2.16)**
- `␣F` – open file picker at current working directory **(2.3.3)**
- `␣G` – debug - experimental **(2.16)**
- `␣R` – replace selection(s) with clipboard **(2.9)**
- `␣S` – open workspace symbol picker **(2.16)**
- `␣Y` – yank main selection -> system clipboard **(2.9)**
- `␣a` – apply code action **(2.16)**
- `␣b` – open buffer picker **(2.3.4)**
- `␣c` – Toggle comment **(2.8.7)**
- `␣d` – open document diagnostics picker **(2.16)**
- `␣f` – open file picker at LSP workspace root **(2.3.3)**
- `␣g` – open changed file picker **(2.3.3)**
- `␣h` – select symbol references for symbol under cursor **(2.16)**
- `␣j` – open jumplist picker **(2.13)**
- `␣k` – show documentation for item under cursor **(2.16)**
- `␣p / ␣P` – paste clipboard after / before selections(s) **(2.9)**
- `␣r` – rename symbol **(2.16)**
- `␣s` – open document symbol picker **(2.16)**
- `␣wF` – open/create file(s) under selection(s) in vertical split **(2.3.3)**
- `␣wH/J/K/L` – swap split with buffer on left / up / down / right **(2.3.5)**
- `␣wf` – open/create file(s) under selection(s) in horizontal split **(2.3.3)**
- `␣wh/j/k/l` – move to buffer left / up / down / right **(2.3.5)**
- `␣wns / ␣wnv` – split horizontal / vertical, new buffer **(2.3.5)**
- `␣wo` – close all but current split **(2.3.5)**
- `␣wq` – close current split **(2.3.5)**
- `␣ws / ␣wv` – split horizontal / vertical, current buffer **(2.3.5)**
- `␣wt` – transpose split **(2.3.5)**
- `␣ww` – next split **(2.3.5)**
- `␣y` – yank selection(s) -> system clipboard **(2.9)**
- `!` – insert output before each selection(s) **(2.15)**
- `"` – select register to yank to or paste from **(2.9)**
- `"<ch>` – change to reg <ch> **(2.11)**
- `"<ch>Q` – toggle capture to reg <ch>, default @ **(2.12)**
- `"<ch>R` – replace with reg <ch> **(2.11)**
- `"<ch>p` – paste from reg <ch> **(2.11)**
- `"<ch>q` – play macro in reg <ch>, default @ **(2.12)**
- `"<ch>y` – yank into reg <ch> **(2.11)**
- `$` – keep selection(s) where command returned 0 **(2.15)**
- `%` – select whole file **(2.5.1)**
- `&` – align on primary cursor **(2.7.2)**
- `'` – specified surround pairs **(2.5.2)**
- `(` – cycle primary selection backward **(2.6)**
- `(` – specified surround pairs **(2.5.2)**
- `( / )` – rotate primary backwards / forwards **(2.7.2)**
- `)` – cycle primary selection forward **(2.6)**
- `*` – search for current selection, respect word boundaries **(2.10)**
- `,` – remove all except primary selection **(2.7.2)**
- `.` – repeat last insert **(2.8.1)**
- `/<regex>` – search forward for regex **(2.10)**
- `:bc` – close current buffer **(2.3.4)**
- `:bca` – close all buffers **(2.3.4)**
- `:bco` – close all but current buffer **(2.3.4)**
- `:bn` – next buffer **(2.3.4)**
- `:config-open` – open the config file **(2.17)**
- `:config-open-workspace` – open the workspace config file **(2.17)**
- `:config-reload` – reload the config file **(2.17)**
- `:ear / :lat` – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.3.1)**
- `:format` – format file using external formatter / language server **(2.8.9)**
- `:hs <file>` – open/create <file> in new horizontal split **(2.3.3)**
- `:n` – create new scratch buffer **(2.3.4)**
- `:o <file>` – open <file> in new buffer **(2.3.3)**
- `:q` – quit current buffer, exits if last **(2.3.2)**
- `:reflow <width>` – wrap selection to <width>, default 80 **(2.8.9)**
- `:sort` – sort ranges in selection **(2.8.9)**
- `:tutor` – open tutorial **(2.3.6)**
- `:vs <file>` – open/create <file> in new vertical split **(2.3.3)**
- `:w <file>` – write current buffer to <file> **(2.3.3)**
- `:wq` – write current buffer and quit **(2.3.2)**
- `:wq <file>` – write current buffer to <file> and quit **(2.3.2)**
- `:wqa` – write all buffer(s) and quit **(2.3.2)**
- `;` – collapse selection(s) to cursor(s) **(2.5.1)**
- `<` – Undent line(s) containing selection **(2.8.5)**
- `<Down>` – next entry **(3.3)**
- `<Down>` – usual meaning but discouraged **(3.1)**
- `<End>` – to last entry **(3.3)**
- `<End>` – usual meaning but discouraged **(3.1)**
- `<Home>` – to first entry **(3.3)**
- `<Home>` – usual meaning but discouraged **(3.1)**
- `<Left>` – usual meaning but discouraged **(3.1)**
- `<PageDown>` – page down **(3.3)**
- `<PageDown>` – usual meaning but discouraged **(3.1)**
- `<PageUp>` – page up **(3.3)**
- `<PageUp>` – usual meaning but discouraged **(3.1)**
- `<Right>` – usual meaning but discouraged **(3.1)**
- `<Up>` – previous entry **(3.3)**
- `<Up>` – usual meaning but discouraged **(3.1)**
- `<backtab>` – select previous completion item **(3.2)**
- `<bksp>` – delete previous char **(3.1)**
- `<bksp>` – delete previous char **(3.2)**
- `<del>` – delete next char **(3.1)**
- `<del>` – delete next char **(3.2)**
- `<enter>` – close menu and accept completion **(3.5)**
- `<enter>` – insert new line **(3.1)**
- `<enter>` – open selected **(3.2)**
- `<enter>` – open selected **(3.3)**
- `<enter>` – open selected in current view **(2.3.3.1)**
- `<nn><cmd>` – repeat <cmd> <nn> times **(2.3.1)**
- `<nn>G` – line <nn> **(2.4.1)**
- `<nn>g|` – column <nn> **(2.4.1)**
- `<tab>` – next entry **(3.3)**
- `<tab>` – select next completion item **(3.2)**
- `<under>` – trim whitespace from selection **(2.8.9)**
- `=` – format by LSP **(2.8.4)**

`>` – Indent line(s) containing selection **(2.8.5)**
`?<regex>` – search backward for regex **(2.10)**
`A` – at end of line **(2.8.1)**
`Alt-!` – append output after each selection(s) **(2.15)**
`Alt-( / Alt-)` – rotate content backward / forward **(2.7.2)**
`Alt-*` – search for current selection **(2.10)**
`Alt-,` – remove primary selection **(2.6)**
`Alt-,` – remove primary selection **(2.7.2)**
`Alt-.` – repeat last find / till **(2.5.5)**
`Alt-:` – selection to normal direction (cursor at end) **(2.5.1)**
`Alt-;` – swap anchor and cursor **(2.5.1)**
`Alt-<bksp>` – delete previous word **(3.1)**
`Alt-<del>` – delete next word **(3.1)**
`Alt-<enter>` – open selected in the background without closing the picker **(3.3)**
`Alt-<minus>` – merge selections **(2.7.2)**
`Alt-<under>` – merge consecutive selections **(2.7.2)**
`Alt-I` – select all children nodes in syntax tree **(2.5.4)**
`Alt-J` – join lines inside selection and select the inserted space **(2.8.9)**
`Alt-K` – remove selections matching the regex **(2.7.2)**
`Alt-` ` – set uppercase **(2.8.6)**
`Alt-a` – select all sibling nodes in syntax tree **(2.5.4)**
`Alt-b` – backward a word **(3.2)**
`Alt-b` – move to start of parent node in syntax tree **(2.4.3)**
`Alt-c` – change, no save **(2.8.4)**
`Alt-d` – delete next word **(3.1)**
`Alt-d` – delete next word **(3.2)**
`Alt-d` – delete, no save **(2.8.3)**
`Alt-e` – move to end of parent node in syntax tree **(2.4.3)**
`Alt-f` – forward a word **(3.2)**
`Alt-i` – shrink selection **(2.5.1)**
`Alt-i` – shrink syntax tree object selection **(2.5.4)**
`Alt-n` – next signature **(3.6)**
`Alt-n` – select next sibling node in syntax tree **(2.5.4)**
`Alt-o` – expand selection syntax-aware **(2.5.1)**
`Alt-o` – expand selection to parent syntax node **(2.5.4)**
`Alt-p` – previous signature **(3.6)**
`Alt-p` – select previous sibling node in syntax tree **(2.5.4)**
`Alt-s` – split on newlines **(2.7.1)**
`Alt-u / Alt-U` – move backward / forward in tree history **(2.3.1)**
`Alt-x` – shrink to line bounds **(2.5.3)**
`Alt-|` – ignore output **(2.15)**
`C / Alt-C` – add selection below / above **(2.7.1)**
`Ctrl-<bksp>` – delete previous word **(3.2)**
`Ctrl-<del>` – delete next word **(3.2)**
`Ctrl-a` – increment the selected number **(2.8.8)**
`Ctrl-a` – to prompt start **(3.2)**
`Ctrl-b` – backward a char **(3.2)**
`Ctrl-b` – page up **(2.4.4)**
`Ctrl-c` – Toggle comment **(2.8.7)**
`Ctrl-c` – close menu and reject completion **(3.5)**
`Ctrl-c` – close picker **(3.3)**
`Ctrl-c` – close prompt **(3.2)**
`Ctrl-d` – delete next char **(3.1)**
`Ctrl-d` – delete next char **(3.2)**
`Ctrl-d` – half page down **(2.4.4)**
`Ctrl-d` – page down **(3.3)**
`Ctrl-d` – scroll down **(3.4)**
`Ctrl-e` – to prompt end **(3.2)**
`Ctrl-f` – forward a char **(3.2)**
`Ctrl-f` – page down **(2.4.4)**
`Ctrl-h` – delete previous char **(3.1)**
`Ctrl-h` – delete previous char **(3.2)**
`Ctrl-i` – move forward in jumplist **(2.13)**
`Ctrl-j` – insert new line **(3.1)**
`Ctrl-k` – delete to end of line **(3.1)**
`Ctrl-k` – delete to end of line **(3.2)**
`Ctrl-n` – next entry **(3.3)**
`Ctrl-n` – next entry **(3.5)**
`Ctrl-n` – select next history **(3.2)**
`Ctrl-o` – move backwards in jumplist **(2.13)**
`Ctrl-p` – previous entry **(3.3)**
`Ctrl-p` – previous entry **(3.5)**
`Ctrl-p` – select previous history **(3.2)**
`Ctrl-r` – insert a register content **(3.1)**
`Ctrl-r` – insert the content of the register selected by following input char **(3.2)**
`Ctrl-s` – commit undo checkpoint **(3.1)**
`Ctrl-s` – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
`Ctrl-s` – open horizontally **(3.3)**
`Ctrl-s` – open selected in new horizontal split **(2.3.3.1)**
`Ctrl-s` – save current position to jumplist **(2.13)**
`Ctrl-t` – toggle preview **(3.3)**
`Ctrl-u` – delete to start of line **(3.1)**
`Ctrl-u` – delete to start of line **(3.2)**
`Ctrl-u` – half page up **(2.4.4)**
`Ctrl-u` – page up **(3.3)**
`Ctrl-u` – scroll up **(3.4)**
`Ctrl-v` – open selected in new vertical split **(2.3.3.1)**
`Ctrl-v` – open vertically **(3.3)**
`Ctrl-w` – delete previous word **(3.1)**
`Ctrl-w` – delete previous word **(3.2)**
`Ctrl-x` – autocomplete **(3.1)**
`Ctrl-x` – decrement the selected number **(2.8.8)**
`Esc` – close picker **(3.3)**
`Esc` – close prompt **(3.2)**
`Esc` – end insert (return to normal) **(2.8.1)**
`Esc` – return to normal **(2.6)**
`Esc` – return to normal mode **(2.3.1)**
`F<ch>` – to <ch> inclusive (find) **(2.5.5)**
`I` – at start of line **(2.8.1)**
`J` – join lines in a selection **(2.8.9)**
`K` – keep selections matching the regex **(2.7.2)**
`N` – next, previous match **(2.10)**
`O` – add line and insert above cursor **(2.8.1)**
`P` – paste yank buf before the cursor **(2.9)**
`R` – replace selection with yank buf **(2.9)**
`S` – split on match **(2.7.1)**
`Shift-<bksp>` – delete previous char **(3.1)**
`Shift-<tab>` – previous entry **(3.3)**
`Shift-Tab` – previous entry **(3.5)**
`T` – test **(2.5.2)**
`T<ch>` – to <ch> exclusive (till) **(2.5.5)**
`Tab` – next entry **(3.5)**
`X` – extend to line **(2.5.3)**
`Z` – enter sticky mode, exit with Esc **(2.3.5.1)**
`[␣` – newline above **(2.8.2)**
`[` – specified surround pairs **(2.5.2)**
`[D` – first diagnostic **(2.4.2)**
`[G` – to last, first change **(2.4.3)**
`[T` – to next, prior test **(2.4.3)**
`[a` – to next, prior arg **(2.4.3)**

`[c` – to next, prior comment **(2.4.3)**
`[d` – prior diagnostic **(2.4.2)**
`[f` – to next, prior function **(2.4.3)**
`[g` – to next, prior change **(2.4.3)**
`[p` – to prior paragraph **(2.5.3)**
`[t` – to next, prior type definition **(2.4.3)**
`]␣` – newline below **(2.8.2)**
`]D` – last diagnostic **(2.4.2)**
`]G` – to last, first change **(2.4.3)**
`]T` – to next, prior test **(2.4.3)**
`]a` – to next, prior arg **(2.4.3)**
`]c` – to next, prior comment **(2.4.3)**
`]d` – next diagnostic **(2.4.2)**
`]f` – to next, prior function **(2.4.3)**
`]g` – to next, prior change **(2.4.3)**
`]p` – to next paragraph **(2.5.3)**
`]t` – to next, prior type definition **(2.4.3)**
`` ` `` – set lowercase **(2.8.6)**
`a` – after selection **(2.8.1)**
`a` – argument/parameter **(2.5.2)**
`b / B` – to start of current word / WORD **(2.5.3)**
`c` – comment **(2.5.2)**
`c` – selection -> yank buf, change selection **(2.8.4)**
`d` – selection -> yank buf, delete selection **(2.8.3)**
`e / E` – to end of current word / WORD **(2.5.3)**
`etc.` – specified surround pairs **(2.5.2)**
`f` – function **(2.5.2)**
`f<ch>` – to <ch> inclusive (find) **(2.5.5)**
`g` – change git hunk **(2.5.2)**
`g.` – to last modification in current file **(2.4.1)**
`g<nn>g` – line <nn> **(2.4.1)**
`ga` – go to last accessed/alternate buffer **(2.3.4)**
`gb` – bottom of screen **(2.4.1)**
`gc` – middle of screen **(2.4.1)**
`gd` – go to definition **(2.4.2)**
`ge` – bottom of file **(2.4.1)**
`gf` – open/create file(s) under selection, open url under selection. **(2.3.3)**
`gg` – top of file **(2.4.1)**
`gh` – beginning of line **(2.4.1)**
`gi` – go to implementation **(2.4.2)**
`gj` – down textual line **(2.4.1)**
`gk` – up textual line **(2.4.1)**
`gl` – end of line **(2.4.1)**
`gm` – go to last modified/alternate buffer **(2.3.4)**
`gn` – go to next buffer **(2.3.4)**
`gp` – go to previous buffer **(2.3.4)**
`gr` – go to references **(2.4.2)**
`gs` – first non-white-space char **(2.4.1)**
`gt` – top of screen **(2.4.1)**
`gw` – two-char labels on words, label to go to word **(2.4.1)**
`gy` – go to type definition **(2.4.2)**
`g|` – beginning of line **(2.4.1)**
`h/j/k/l` – left / up / down / right **(2.4.1)**
`i` – before selection **(2.8.1)**
`m` – closest surround pair **(2.5.2)**
`ma<ch>` – match around delim <ch> **(2.14)**
`ma<ch> / mi<ch>` – match around / inside the object indicated by <ch> below: **(2.5.2)**
`md<ch>` – delete delim <ch> around selection **(2.14)**
`md<ch>` – delete delim <ch> around selection **(2.8.3)**
`mi<ch>` – match inside delim <ch> **(2.14)**
`mm` – go to matching delim **(2.14)**
`mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.14)**
`mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.8.4)**

`ms<ch>` – add delim <ch> around selection **(2.14)**
`ms<ch>` – add delim <ch> around selection **(2.8.2)**
`n` – next, previous match **(2.10)**
`o` – add line and insert below cursor **(2.8.1)**
`p` – paragraph **(2.5.2)**
`p` – paste yank buf after the cursor **(2.9)**
`r<ch>` – replace selection with <ch> **(2.9)**
`s<regex>` – matches become selections **(2.7.1)**
`t` – type or class **(2.5.2)**
`t<ch>` – to <ch> exclusive (till) **(2.5.5)**
`u / U` – undo / redo change in linear history **(2.3.1)**
`v` – toggle select mode **(2.6)**
`w / W` – to start of next word / WORD **(2.5.3)**
`w / W` – word / WORD **(2.5.2)**
`x` – current line, extend by line **(2.5.3)**
`y` – selection -> yank buf **(2.9)**
`zb` – align to bottom **(2.3.5.1)**
`zc` – align to center **(2.3.5.1)**
`zj` – scroll down **(2.3.5.1)**
`zk` – scroll up **(2.3.5.1)**
`zm` – align to middle horizontally **(2.3.5.1)**
`zt` – align to top **(2.3.5.1)**
`zz` – align to center **(2.3.5.1)**
`|` – replace selection(s) with output **(2.15)**
`~` – change case **(2.8.6)**