Bill's Helix Cheat Sheet / Command Reference

1 Introduction

1.1 Metadata

- Document version: 1.1.0-beta, 27-Apr-2026
- Based on Helix version: 25.07.1
- Built with Typst version: 0.14.2
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.2 Definitions

- **file** - data on storage device, e.g., hard disk or ssd
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.3 Typographic Conventions

- `word` - alphanumeric, punctuation-delimited
- `WORD` - whitespace-delimited
- `Ctrl-c` - Ctrl and c key pressed simultaneous.
- `Alt-c` - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- `␣c` is space followed by the character c.
- Metavars `<regex>`, `<file>` and `<ch>` represent user input. The angle-brackets are not part of the input.
- `␣`, `<minus>`, and `<under>` used for clarity. `<enter>`, `<del>`, `<bksp>`, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.4 Launching

```
helix
helix <file>
helix <file1> <file2> ... <filen>
helix <directory>
helix --help
hx in some distributions or by alias
```

2 Primary Commands

2.1 Editing Paradigm

Selection first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
      v3wd – enter select mode, select 3 words, delete
```

2.2 Regular Expressions

Helix uses Rust's regex. Escape following metachars with <backslash> when searching for literal value.

```
  . – any character
  * – zero or more
  + – one or more
  ? – zero or one / lazy match
  ^ – start of line / negation in class
  $ – end of line
( ) – capture group
[ ] – character class
{ } – repetition count
  | – alternation
  \ – escape character itself
```

2.3 Essentials

2.3.1 Undo / Repeat / Normal Mode

```
          u / U – undo / redo change in linear
                  history
  Alt-u / Alt-U – move backward / forward in tree
                  history
   :ear / :lat – move backward / forward in
                  history by step count or time span
                  (1s, 2m, 3h, 4d)
     <nn><cmd> – repeat <cmd> <nn> times
           Esc – return to normal mode
```

2.3.2 Quit

Add **!** suffix to force operation.

```
        :wq – write current buffer and quit
  :wq <file> – write current buffer to <file> and quit
       :wqa – write all buffer(s) and quit
         :q – quit current buffer, exits if last
```

2.3.3 Files

`:o <file>`	open <file> in new buffer
`:w <file>`	write current buffer to <file>
`:hs <file>`	open/create <file> in new horizontal split
`:vs <file>`	open/create <file> in new vertical split
`␣wf`	open/create file(s) under selection(s) in horizontal split
`␣wF`	open/create file(s) under selection(s) in vertical split
`gf`	open/create file(s) under selection, open url under selection.
`␣f`	open file picker at LSP workspace root
`␣F`	open file picker at current working directory
`␣g`	open changed file picker

2.3.3.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

`<enter>`	open selected in current view
`Ctrl-s`	open selected in new horizontal split
`Ctrl-v`	open selected in new vertical split

2.3.4 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

`:n`	create new scratch buffer
`:bc`	close current buffer
`:bca`	close all buffers
`:bco`	close all but current buffer
`:bn`	next buffer
`␣b`	open buffer picker
`ga`	go to last accessed/alternate buffer
`gm`	go to last modified/alternate buffer
`gn`	go to next buffer
`gp`	go to previous buffer

2.3.5 Views

Ctrl-w and `␣w` are synonymous.

`␣ws / ␣wv`	split horizontal / vertical, current buffer
`␣wns / ␣wnv`	split horizontal / vertical, new buffer
`␣wq`	close current split
`␣wo`	close all but current split
`␣ww`	next split
`␣wh/j/k/l`	move to buffer left / up / down / right
`␣wH/J/K/L`	swap split with buffer on left / up / down / right
`␣wt`	transpose split

2.3.5.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

`Z`	enter sticky mode, exit with Esc
`zz, zc`	align to center
`zt`	align to top
`zb`	align to bottom
`zm`	align to middle horizontally
`zj`	scroll down
`zk`	scroll up

2.3.6 Help

`:tutor`	open tutorial
`␣?`	open command palette

2.4 Movement

2.4.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

`h/j/k/l`	left / up / down / right
`gh, g|`	beginning of line
`<nn>g|`	column <nn>
`gl`	end of line
`gg`	top of file
`<nn>G, g<nn>g`	line <nn>
`ge`	bottom of file
`gw`	two-char labels on words, label to go to word
`g.`	to last modification in current file
`gj`	down textual line
`gk`	up textual line
`gs`	first non-white-space char
`gt`	top of screen
`gc`	middle of screen
`gb`	bottom of screen

2.4.2 By Language Server Protocol

Requires LSP support.

`gd`	go to definition
`gy`	go to type definition
`gr`	go to references
`gi`	go to implementation
`]d`	next diagnostic
`[d`	prior diagnostic
`]D`	last diagnostic
`[D`	first diagnostic

2.4.3 By Treesitter - Syntax

Requires Treesitter support.

```
]f, [f – to next, prior function
]t, [t – to next, prior type definition
]T, [T – to next, prior test
]a, [a – to next, prior arg
]c, [c – to next, prior comment
]g, [g – to next, prior change
]G, [G – to last, first change

Alt-e – move to end of parent node in syntax tree
Alt-b – move to start of parent node in syntax tree
```

2.4.4 By Page

```
Ctrl-b – page up
Ctrl-f – page down
Ctrl-u – half page up
Ctrl-d – half page down
```

2.5 Selection

Selection: a range of characters between anchor and cursor

Normal Mode: move and select

Select Mode: move and extend selection

2.5.1 Operations

```
%      – select whole file
Alt-;  – swap anchor and cursor
Alt-:  – selection to normal direction (cursor at end)
Alt-o  – expand selection syntax-aware
Alt-i  – shrink selection
;      – collapse selection(s) to cursor(s)
```

2.5.2 By TextObjects

```
ma<ch> / mi<ch> – match around / inside the object indicated by <ch> below:

w / W – word / WORD
p     – paragraph
(, [, ', etc.– specified surround pairs
m     – closest surround pair
f     – function
t     – type or class
a     – argument/parameter
c     – comment
T     – test
g     – change git hunk
```

2.5.3 By Syntactic Objects

```
w / W – to start of next word / WORD
e / E – to end of current word / WORD
b / B – to start of current word / WORD
x     – current line, extend by line
X     – extend to line
Alt-x – shrink to line bounds
]p    – to next paragraph
[p    – to prior paragraph
```

2.5.4 By Treesitter - Syntax

Requires Treesitter support.

```
Alt-o – expand selection to parent syntax node
Alt-i – shrink syntax tree object selection
Alt-p – select previous sibling node in syntax tree
Alt-n – select next sibling node in syntax tree
Alt-a – select all sibling nodes in syntax tree
Alt-I – select all children nodes in syntax tree
```

2.5.5 By Character Value

Lower case: forward

Upper case: backward

```
f<ch>, F<ch> – to <ch> inclusive (find)
t<ch>, T<ch> – to <ch> exclusive (till)
Alt-.        – repeat last find / till
```

2.6 Select Mode

Movement: extends selection

Search: adds to selection

```
v   – toggle select mode
Esc – return to normal
)   – cycle primary selection forward
(   – cycle primary selection backward
Alt-,  – remove primary selection
```

2.7 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.7.1 Creating

Create multiple selections from selection.

```
s<regex> – matches become selections
S        – split on match
Alt-s    – split on newlines
C / Alt-C – add selection below / above
```

2.7.2 Operations

```
&            – align on primary cursor
Alt-<minus>  – merge selections
Alt-<under>  – merge consecutive selections
,            – remove all except primary selection
Alt-,        – remove primary selection
( / )        – rotate primary backwards / forwards
Alt-( / Alt-) – rotate content backward / forward
K            – keep selections matching the regex
Alt-K        – remove selections matching the regex
```

2.8 Alter Buffer Content

2.8.1 Insert

```
     i – before selection
     a – after selection
     I – at start of line
     A – at end of line
     o – add line and insert below cursor
     O – add line and insert above cursor
   Esc – end insert (return to normal)
     . – repeat last insert
```

2.8.2 Add

```
    ]␣ – newline below
    [␣ – newline above
ms<ch> – add delim <ch> around selection
```

2.8.3 Delete

```
     d – selection -> yank buf, delete selection
  Alt-d – delete, no save
md<ch> – delete delim <ch> around selection
```

2.8.4 Change

```
       c – selection -> yank buf, change
           selection
  Alt-c – change, no save
       = – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.8.5 Indent Lines

```
> – Indent line(s) containing selection
< – Undent line(s) containing selection
```

2.8.6 Change Case

Change case of all letters in selection

```
     ~ – change case
     ` – set lowercase
  Alt-` – set uppercase
```

2.8.7 Comments

All apply to selection.

```
␣c, Ctrl-c – Toggle comment
        ␣C – Toggle block comment
   ␣Alt-C – Toggle line comment
```

2.8.8 Increment / Decrement

```
  Ctrl-a – increment the selected number
  Ctrl-x – decrement the selected number
```

2.8.9 Miscellaneous

```
           J – join lines in a selection
       Alt-J – join lines inside selection and
               select the inserted space
     <under> – trim whitespace from selection
:reflow <width> – wrap selection to <width>,
               default 80
       :sort – sort ranges in selection
     :format – format file using external
               formatter / language server
```

2.9 Copy / Paste / Replace

```
       y – selection -> yank buf
       p – paste yank buf after the cursor
       P – paste yank buf before the cursor
      ␣y – yank selection(s) -> system clipboard
      ␣Y – yank main selection -> system clipboard
  ␣p / ␣P – paste clipboard after / before
            selections(s)
      ␣R – replace selection(s) with clipboard
    r<ch> – replace selection with <ch>
       R – replace selection with yank buf
       " – select register to yank to or paste from
```

2.10 Search

```
  /<regex> – search forward for regex
  ?<regex> – search backward for regex
     n, N – next, previous match
        * – search for current selection, respect
            word boundaries
    Alt-* – search for current selection
```

2.11 Registers

Identified by single char <ch>

```
   "<ch> – change to reg <ch>
  "<ch>y – yank into reg <ch>
  "<ch>p – paste from reg <ch>
  "<ch>R – replace with reg <ch>
```

2.12 Macros

```
  "<ch>Q – toggle capture to reg <ch>, default @
  "<ch>q – play macro in reg <ch>, default @
```

2.13 Jumplists

```
  Ctrl-s – save current position to jumplist
  Ctrl-i – move forward in jumplist
  Ctrl-o – move backwards in jumplist
      ␣j – open jumplist picker
```

2.14 Match Mode

With regard to balanced delimiters.

```
       mm – go to matching delim
   mi<ch> – match inside delim <ch>
   ma<ch> – match around delim <ch>
   ms<ch> – add delim <ch> around selection
   md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.15 Shell

All commands pipe each selection to shell command.

`|`	– replace selection(s) with output
`Alt-|`	– ignore output
`!`	– insert output before each selection(s)
`Alt-!`	– append output after each selection(s)
`$`	– keep selection(s) where command returned 0

2.16 Approaching an IDE

`␣G`	– debug - experimental
`␣k`	– show documentation for item under cursor
`␣s`	– open document symbol picker
`␣S`	– open workspace symbol picker
`␣d`	– open document diagnostics picker
`␣D`	– open workspace diagnostics picker
`␣r`	– rename symbol
`␣a`	– apply code action
`␣h`	– select symbol references for symbol under cursor

2.17 Editor Configuration

`:config-open`	– open the config file
`:config-open-workspace`	– open the workspace config file
`:config-reload`	– reload the config file

2.18 Miscellaneous

`␣'`	– open last picker
`␣/`	– open global search in workspace folder picker

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

`Ctrl-s`	– commit undo checkpoint
`Ctrl-x`	– autocomplete
`Ctrl-r`	– insert a register content
`Ctrl-w, Alt-<bksp>`	– delete previous word
`Alt-d, Alt-<del>`	– delete next word
`Ctrl-u`	– delete to start of line
`Ctrl-k`	– delete to end of line
`Ctrl-h, <bksp>, Shift-<bksp>`	– delete previous char
`Ctrl-d, <del>`	– delete next char
`Ctrl-j, <enter>`	– insert new line
`<Up>, <Down>, <Left>, <Right>, <PageUp>, <PageDown>, <Home>, <End>`	– usual meaning but discouraged

3.2 Command Line Editing

`Esc, Ctrl-c`	– close prompt
`<enter>`	– open selected
`<tab>`	– select next completion item
`<backtab>`	– select previous completion item
`Alt-b`	– backward a word
`Ctrl-b`	– backward a char
`Alt-f`	– forward a word
`Ctrl-f`	– forward a char
`Ctrl-e`	– to prompt end
`Ctrl-a`	– to prompt start
`Ctrl-w, Ctrl-<bksp>`	– delete previous word
`Alt-d, Ctrl-<del>`	– delete next word
`Ctrl-u`	– delete to start of line
`Ctrl-k`	– delete to end of line
`<bksp>, Ctrl-h`	– delete previous char
`<del>, Ctrl-d`	– delete next char
`Ctrl-s`	– insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later)
`Ctrl-p`	– select previous history
`Ctrl-n`	– select next history
`Ctrl-r`	– insert the content of the register selected by following input char

3.3 Pickers

Navigation keys shown.

`Shift-<tab>, Ctrl-p, <Up>`	– previous entry
`<tab>, Ctrl-n, <Down>`	– next entry
`<Home>`	– to first entry
`<End>`	– to last entry
`Ctrl-u, <PageUp>`	– page up
`Ctrl-d, <PageDown>`	– page down
`<enter>`	– open selected
`Alt-<enter>`	– open selected in the background without closing the picker
`Ctrl-s`	– open horizontally
`Ctrl-v`	– open vertically
`Ctrl-t`	– toggle preview
`Esc, Ctrl-c`	– close picker

3.4 Popups

Displays documentation for item under cursor.

```
Ctrl-u – scroll up
Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
Shift-Tab, Ctrl-p – previous entry
      Tab, Ctrl-n – next entry
          <enter> – close menu and accept
                    completion
           Ctrl-c – close menu and reject
                    completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
Alt-p – previous signature
Alt-n – next signature
```

4 Command Index

␣' – open last picker **(2.18)**
␣/ – open global search in workspace folder picker **(2.18)**
␣? – open command palette **(2.3.6)**
␣Alt-C – Toggle line comment **(2.8.7)**
␣C – Toggle block comment **(2.8.7)**
␣D – open workspace diagnostics picker **(2.16)**
␣F – open file picker at current working directory **(2.3.3)**
␣G – debug - experimental **(2.16)**
␣R – replace selection(s) with clipboard **(2.9)**
␣S – open workspace symbol picker **(2.16)**
␣Y – yank main selection -> system clipboard **(2.9)**
␣a – apply code action **(2.16)**
␣b – open buffer picker **(2.3.4)**
␣c – Toggle comment **(2.8.7)**
␣d – open document diagnostics picker **(2.16)**
␣f – open file picker at LSP workspace root **(2.3.3)**
␣g – open changed file picker **(2.3.3)**
␣h – select symbol references for symbol under cursor **(2.16)**
␣j – open jumplist picker **(2.13)**
␣k – show documentation for item under cursor **(2.16)**
␣p / ␣P – paste clipboard after / before selections(s) **(2.9)**
␣r – rename symbol **(2.16)**
␣s – open document symbol picker **(2.16)**
␣wF – open/create file(s) under selection(s) in vertical split **(2.3.3)**
␣wH/J/K/L – swap split with buffer on left / up / down / right **(2.3.5)**
␣wf – open/create file(s) under selection(s) in horizontal split **(2.3.3)**
␣wh/j/k/l – move to buffer left / up / down / right **(2.3.5)**
␣wns / ␣wnv – split horizontal / vertical, new buffer **(2.3.5)**
␣wo – close all but current split **(2.3.5)**
␣wq – close current split **(2.3.5)**
␣ws / ␣wv – split horizontal / vertical, current buffer **(2.3.5)**
␣wt – transpose split **(2.3.5)**
␣ww – next split **(2.3.5)**
␣y – yank selection(s) -> system clipboard **(2.9)**
! – insert output before each selection(s) **(2.15)**
" – select register to yank to or paste from **(2.9)**
"<ch> – change to reg <ch> **(2.11)**
"<ch>Q – toggle capture to reg <ch>, default @ **(2.12)**
"<ch>R – replace with reg <ch> **(2.11)**
"<ch>p – paste from reg <ch> **(2.11)**
"<ch>q – play macro in reg <ch>, default @ **(2.12)**
"<ch>y – yank into reg <ch> **(2.11)**
$ – keep selection(s) where command returned 0 **(2.15)**
% – select whole file **(2.5.1)**
& – align on primary cursor **(2.7.2)**
' – specified surround pairs **(2.5.2)**
(– cycle primary selection backward **(2.6)**
(– specified surround pairs **(2.5.2)**
(/) – rotate primary backwards / forwards **(2.7.2)**
) – cycle primary selection forward **(2.6)**
* – search for current selection, respect word boundaries **(2.10)**
, – remove all except primary selection **(2.7.2)**
. – repeat last insert **(2.8.1)**
/<regex> – search forward for regex **(2.10)**
:bc – close current buffer **(2.3.4)**
:bca – close all buffers **(2.3.4)**
:bco – close all but current buffer **(2.3.4)**
:bn – next buffer **(2.3.4)**
:config-open – open the config file **(2.17)**
:config-open-workspace – open the workspace config file **(2.17)**
:config-reload – reload the config file **(2.17)**
:ear / :lat – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.3.1)**
:format – format file using external formatter / language server **(2.8.9)**
:hs <file> – open/create <file> in new horizontal split **(2.3.3)**
:n – create new scratch buffer **(2.3.4)**
:o <file> – open <file> in new buffer **(2.3.3)**
:q – quit current buffer, exits if last **(2.3.2)**
:reflow <width> – wrap selection to <width>, default 80 **(2.8.9)**
:sort – sort ranges in selection **(2.8.9)**
:tutor – open tutorial **(2.3.6)**
:vs <file> – open/create <file> in new vertical split **(2.3.3)**
:w <file> – write current buffer to <file> **(2.3.3)**
:wq – write current buffer and quit **(2.3.2)**
:wq <file> – write current buffer to <file> and quit **(2.3.2)**
:wqa – write all buffer(s) and quit **(2.3.2)**
; – collapse selection(s) to cursor(s) **(2.5.1)**
< – Undent line(s) containing selection **(2.8.5)**
<Down> – next entry **(3.3)**
<Down> – usual meaning but discouraged **(3.1)**
<End> – to last entry **(3.3)**
<End> – usual meaning but discouraged **(3.1)**
<Home> – to first entry **(3.3)**
<Home> – usual meaning but discouraged **(3.1)**
<Left> – usual meaning but discouraged **(3.1)**
<PageDown> – page down **(3.3)**
<PageDown> – usual meaning but discouraged **(3.1)**
<PageUp> – page up **(3.3)**
<PageUp> – usual meaning but discouraged **(3.1)**
<Right> – usual meaning but discouraged **(3.1)**
<Up> – previous entry **(3.3)**
<Up> – usual meaning but discouraged **(3.1)**
<backtab> – select previous completion item **(3.2)**
<bksp> – delete previous char **(3.1)**
<bksp> – delete previous char **(3.2)**
<del> – delete next char **(3.1)**
<del> – delete next char **(3.2)**

- `<enter>` – close menu and accept completion **(3.5)**
- `<enter>` – insert new line **(3.1)**
- `<enter>` – open selected **(3.2)**
- `<enter>` – open selected **(3.3)**
- `<enter>` – open selected in current view **(2.3.3.1)**
- `<nn><cmd>` – repeat <cmd> <nn> times **(2.3.1)**
- `<nn>G` – line <nn> **(2.4.1)**
- `<nn>g|` – column <nn> **(2.4.1)**
- `<tab>` – next entry **(3.3)**
- `<tab>` – select next completion item **(3.2)**
- `<under>` – trim whitespace from selection **(2.8.9)**
- `=` – format by LSP **(2.8.4)**
- `>` – Indent line(s) containing selection **(2.8.5)**
- `?<regex>` – search backward for regex **(2.10)**
- `A` – at end of line **(2.8.1)**
- `Alt-!` – append output after each selection(s) **(2.15)**
- `Alt-( / Alt-)` – rotate content backward / forward **(2.7.2)**
- `Alt-*` – search for current selection **(2.10)**
- `Alt-,` – remove primary selection **(2.6)**
- `Alt-,` – remove primary selection **(2.7.2)**
- `Alt-.` – repeat last find / till **(2.5.5)**
- `Alt-:` – selection to normal direction (cursor at end) **(2.5.1)**
- `Alt-;` – swap anchor and cursor **(2.5.1)**
- `Alt-<bksp>` – delete previous word **(3.1)**
- `Alt-<del>` – delete next word **(3.1)**
- `Alt-<enter>` – open selected in the background without closing the picker **(3.3)**
- `Alt-<minus>` – merge selections **(2.7.2)**
- `Alt-<under>` – merge consecutive selections **(2.7.2)**
- `Alt-I` – select all children nodes in syntax tree **(2.5.4)**
- `Alt-J` – join lines inside selection and select the inserted space **(2.8.9)**
- `Alt-K` – remove selections matching the regex **(2.7.2)**
- `Alt-` ` – set uppercase **(2.8.6)**
- `Alt-a` – select all sibling nodes in syntax tree **(2.5.4)**
- `Alt-b` – backward a word **(3.2)**
- `Alt-b` – move to start of parent node in syntax tree **(2.4.3)**
- `Alt-c` – change, no save **(2.8.4)**
- `Alt-d` – delete next word **(3.1)**
- `Alt-d` – delete next word **(3.2)**
- `Alt-d` – delete, no save **(2.8.3)**
- `Alt-e` – move to end of parent node in syntax tree **(2.4.3)**
- `Alt-f` – forward a word **(3.2)**
- `Alt-i` – shrink selection **(2.5.1)**
- `Alt-i` – shrink syntax tree object selection **(2.5.4)**
- `Alt-n` – next signature **(3.6)**
- `Alt-n` – select next sibling node in syntax tree **(2.5.4)**
- `Alt-o` – expand selection syntax-aware **(2.5.1)**
- `Alt-o` – expand selection to parent syntax node **(2.5.4)**
- `Alt-p` – previous signature **(3.6)**
- `Alt-p` – select previous sibling node in syntax tree **(2.5.4)**
- `Alt-s` – split on newlines **(2.7.1)**
- `Alt-u / Alt-U` – move backward / forward in tree history **(2.3.1)**
- `Alt-x` – shrink to line bounds **(2.5.3)**
- `Alt-|` – ignore output **(2.15)**
- `C / Alt-C` – add selection below / above **(2.7.1)**
- `Ctrl-<bksp>` – delete previous word **(3.2)**
- `Ctrl-<del>` – delete next word **(3.2)**
- `Ctrl-a` – increment the selected number **(2.8.8)**
- `Ctrl-a` – to prompt start **(3.2)**
- `Ctrl-b` – backward a char **(3.2)**
- `Ctrl-b` – page up **(2.4.4)**
- `Ctrl-c` – Toggle comment **(2.8.7)**
- `Ctrl-c` – close menu and reject completion **(3.5)**
- `Ctrl-c` – close picker **(3.3)**
- `Ctrl-c` – close prompt **(3.2)**
- `Ctrl-d` – delete next char **(3.1)**
- `Ctrl-d` – delete next char **(3.2)**
- `Ctrl-d` – half page down **(2.4.4)**
- `Ctrl-d` – page down **(3.3)**
- `Ctrl-d` – scroll down **(3.4)**
- `Ctrl-e` – to prompt end **(3.2)**
- `Ctrl-f` – forward a char **(3.2)**
- `Ctrl-f` – page down **(2.4.4)**
- `Ctrl-h` – delete previous char **(3.1)**
- `Ctrl-h` – delete previous char **(3.2)**
- `Ctrl-i` – move forward in jumplist **(2.13)**
- `Ctrl-j` – insert new line **(3.1)**
- `Ctrl-k` – delete to end of line **(3.1)**
- `Ctrl-k` – delete to end of line **(3.2)**
- `Ctrl-n` – next entry **(3.3)**
- `Ctrl-n` – next entry **(3.5)**
- `Ctrl-n` – select next history **(3.2)**
- `Ctrl-o` – move backwards in jumplist **(2.13)**
- `Ctrl-p` – previous entry **(3.3)**
- `Ctrl-p` – previous entry **(3.5)**
- `Ctrl-p` – select previous history **(3.2)**
- `Ctrl-r` – insert a register content **(3.1)**
- `Ctrl-r` – insert the content of the register selected by following input char **(3.2)**
- `Ctrl-s` – commit undo checkpoint **(3.1)**
- `Ctrl-s` – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
- `Ctrl-s` – open horizontally **(3.3)**
- `Ctrl-s` – open selected in new horizontal split **(2.3.3.1)**
- `Ctrl-s` – save current position to jumplist **(2.13)**
- `Ctrl-t` – toggle preview **(3.3)**
- `Ctrl-u` – delete to start of line **(3.1)**
- `Ctrl-u` – delete to start of line **(3.2)**
- `Ctrl-u` – half page up **(2.4.4)**
- `Ctrl-u` – page up **(3.3)**
- `Ctrl-u` – scroll up **(3.4)**
- `Ctrl-v` – open selected in new vertical split **(2.3.3.1)**
- `Ctrl-v` – open vertically **(3.3)**
- `Ctrl-w` – delete previous word **(3.1)**
- `Ctrl-w` – delete previous word **(3.2)**
- `Ctrl-x` – autocomplete **(3.1)**
- `Ctrl-x` – decrement the selected number **(2.8.8)**
- `Esc` – close picker **(3.3)**
- `Esc` – close prompt **(3.2)**
- `Esc` – end insert (return to normal) **(2.8.1)**
- `Esc` – return to normal **(2.6)**
- `Esc` – return to normal mode **(2.3.1)**
- `F<ch>` – to <ch> inclusive (find) **(2.5.5)**
- `I` – at start of line **(2.8.1)**
- `J` – join lines in a selection **(2.8.9)**
- `K` – keep selections matching the regex **(2.7.2)**
- `N` – next, previous match **(2.10)**
- `O` – add line and insert above cursor **(2.8.1)**
- `P` – paste yank buf before the cursor **(2.9)**

- **R** – replace selection with yank buf **(2.9)**
- **S** – split on match **(2.7.1)**
- **Shift-<bksp>** – delete previous char **(3.1)**
- **Shift-<tab>** – previous entry **(3.3)**
- **Shift-Tab** – previous entry **(3.5)**
- **T** – test **(2.5.2)**
- **T<ch>** – to <ch> exclusive (till) **(2.5.5)**
- **Tab** – next entry **(3.5)**
- **X** – extend to line **(2.5.3)**
- **Z** – enter sticky mode, exit with Esc **(2.3.5.1)**
- **[␣** – newline above **(2.8.2)**
- **[** – specified surround pairs **(2.5.2)**
- **[D** – first diagnostic **(2.4.2)**
- **[G** – to last, first change **(2.4.3)**
- **[T** – to next, prior test **(2.4.3)**
- **[a** – to next, prior arg **(2.4.3)**
- **[c** – to next, prior comment **(2.4.3)**
- **[d** – prior diagnostic **(2.4.2)**
- **[f** – to next, prior function **(2.4.3)**
- **[g** – to next, prior change **(2.4.3)**
- **[p** – to prior paragraph **(2.5.3)**
- **[t** – to next, prior type definition **(2.4.3)**
- **]␣** – newline below **(2.8.2)**
- **]D** – last diagnostic **(2.4.2)**
- **]G** – to last, first change **(2.4.3)**
- **]T** – to next, prior test **(2.4.3)**
- **]a** – to next, prior arg **(2.4.3)**
- **]c** – to next, prior comment **(2.4.3)**
- **]d** – next diagnostic **(2.4.2)**
- **]f** – to next, prior function **(2.4.3)**
- **]g** – to next, prior change **(2.4.3)**
- **]p** – to next paragraph **(2.5.3)**
- **]t** – to next, prior type definition **(2.4.3)**
- **`** – set lowercase **(2.8.6)**
- **a** – after selection **(2.8.1)**
- **a** – argument/parameter **(2.5.2)**
- **b / B** – to start of current word / WORD **(2.5.3)**
- **c** – comment **(2.5.2)**
- **c** – selection -> yank buf, change selection **(2.8.4)**
- **d** – selection -> yank buf, delete selection **(2.8.3)**
- **e / E** – to end of current word / WORD **(2.5.3)**
- **etc.** – specified surround pairs **(2.5.2)**
- **f** – function **(2.5.2)**
- **f<ch>** – to <ch> inclusive (find) **(2.5.5)**

- **g** – change git hunk **(2.5.2)**
- **g.** – to last modification in current file **(2.4.1)**
- **g<nn>g** – line <nn> **(2.4.1)**
- **ga** – go to last accessed/alternate buffer **(2.3.4)**
- **gb** – bottom of screen **(2.4.1)**
- **gc** – middle of screen **(2.4.1)**
- **gd** – go to definition **(2.4.2)**
- **ge** – bottom of file **(2.4.1)**
- **gf** – open/create file(s) under selection, open url under selection. **(2.3.3)**
- **gg** – top of file **(2.4.1)**
- **gh** – beginning of line **(2.4.1)**
- **gi** – go to implementation **(2.4.2)**
- **gj** – down textual line **(2.4.1)**
- **gk** – up textual line **(2.4.1)**
- **gl** – end of line **(2.4.1)**
- **gm** – go to last modified/alternate buffer **(2.3.4)**
- **gn** – go to next buffer **(2.3.4)**
- **gp** – go to previous buffer **(2.3.4)**
- **gr** – go to references **(2.4.2)**
- **gs** – first non-white-space char **(2.4.1)**
- **gt** – top of screen **(2.4.1)**
- **gw** – two-char labels on words, label to go to word **(2.4.1)**
- **gy** – go to type definition **(2.4.2)**
- **g|** – beginning of line **(2.4.1)**
- **h/j/k/l** – left / up / down / right **(2.4.1)**
- **i** – before selection **(2.8.1)**
- **m** – closest surround pair **(2.5.2)**
- **ma<ch>** – match around delim <ch> **(2.14)**
- **ma<ch> / mi<ch>** – match around / inside the object indicated by <ch> below: **(2.5.2)**
- **md<ch>** – delete delim <ch> around selection **(2.14)**
- **md<ch>** – delete delim <ch> around selection **(2.8.3)**
- **mi<ch>** – match inside delim <ch> **(2.14)**
- **mm** – go to matching delim **(2.14)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.14)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.8.4)**
- **ms<ch>** – add delim <ch> around selection **(2.14)**
- **ms<ch>** – add delim <ch> around selection **(2.8.2)**
- **n** – next, previous match **(2.10)**

- **o** – add line and insert below cursor **(2.8.1)**
- **p** – paragraph **(2.5.2)**
- **p** – paste yank buf after the cursor **(2.9)**
- **r<ch>** – replace selection with <ch> **(2.9)**
- **s<regex>** – matches become selections **(2.7.1)**
- **t** – type or class **(2.5.2)**
- **t<ch>** – to <ch> exclusive (till) **(2.5.5)**
- **u / U** – undo / redo change in linear history **(2.3.1)**
- **v** – toggle select mode **(2.6)**
- **w / W** – to start of next word / WORD **(2.5.3)**
- **w / W** – word / WORD **(2.5.2)**
- **x** – current line, extend by line **(2.5.3)**
- **y** – selection -> yank buf **(2.9)**
- **zb** – align to bottom **(2.3.5.1)**
- **zc** – align to center **(2.3.5.1)**
- **zj** – scroll down **(2.3.5.1)**
- **zk** – scroll up **(2.3.5.1)**
- **zm** – align to middle horizontally **(2.3.5.1)**
- **zt** – align to top **(2.3.5.1)**
- **zz** – align to center **(2.3.5.1)**
- **|** – replace selection(s) with output **(2.15)**
- **~** – change case **(2.8.6)**